1. RF Exposure Test Report

1.1 General Information

Client Information

Applicant: EasyTech Shenzhen Co., Ltd.

Address of applicant: A516, JianSheng Plaza, No.1 PingJi Road, NanWan Town, Longgang

District

Manufacturer: Cyzon PCB Solutions

Address of manufacturer: Xinhu Road, Xinan Street, BaoAn District, Shenzhen, China

Description of EUT

Product Name: wireless charger

Trade Name: /

Model No.: WX-KT02-XYX. WX-XP01-XYX, WX-CD03-XYX, WX-CG03-XYX,

WX-KT01-XYX

FCC ID: 2ADL2WX5XYX
Rated Voltage: Input: DC 5V 2A
Frequency Range: 112-205kHz

Modulation Type: ASK

Antenna Type: Coil Antenna

Rated Voltage: DC 5V (Wireless output)
Rated Current: < 1A (Wireless output)
Rated Power: < 5W (Wireless output)

1.2 Standard Applicable

According to § 1.1310 system operating under the provisions of this section shall be operating in a manner that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure.

TABLE 1-LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

| Frequency range (MHz) | Electric field strength (V/m) | Magnetic field strength (A/m) | Power density (mW/cm ²) | Averaging time (minutes) | | | | |
|---|-------------------------------|-------------------------------|--|-----------------------------|--|--|--|--|
| (A) Limits for Occupational/Controlled Exposure | | | | | | | | |
| 0.3-3.0 | 614 | 1.63 | *100 | 6 | | | | |
| 3.0-30 | 1842/1 | 4.89/1 | *900/f ² | 6 | | | | |
| 30-300 | 61.4 | 0.163 | 1.0 | 6 | | | | |
| 300-1,500 | | | f/300 | 6 | | | | |
| 1,500-100,000 | | | 5 | 6 | | | | |
| | (B) Limits for Gene | ral Population/Uncontrolled | Exposure | | | | | |
| 0.3-1.34 | 614 | 1.63 | *100 | 30 | | | | |
| 1.34-30 | 824/1 | 2.19/1 | *180/f ² | 30 | | | | |
| 30-300 | 27.5 | 0.073 | 0.2 | 30 | | | | |
| 300-1,500 | | | f/1500 | 30 | | | | |
| 1,500-100,000 | | | 1.0 | 30 | | | | |

f = frequency in MHz * = Plane-wave equivalent power density

1.3 Test Conditions

| Test Mode | Description | Remark | |
|-----------------------|--------------------|-----------------------|--|
| TM1 | Full Charge | With receiving module | |
| | | | |
| Measurement Distance: | 10 cm | | |
| Test Standard: | KDB 680106 D01 V02 | | |

1.4 Test Result

The following test data shall to demonstrate RF exposure compliance.

Test Mode: TM1 (with receiving module)

| Electric Field Emissions | | | | | | |
|--------------------------|---------------------|------------|-----------------|--|--|--|
| Test Position | Measure Value (V/m) | Limit(V/m) | 30% Limit (V/m) | | | |
| Тор | 2.68 | 614 | 184.2 | | | |
| Bottom | 2.09 | 614 | 184.2 | | | |
| Side 1 | 1.86 | 614 | 184.2 | | | |
| Side 2 | 1.84 | 614 | 184.2 | | | |
| Side 3 | 1.69 | 614 | 184.2 | | | |
| Side 4 | 1.67 | 614 | 184.2 | | | |
| | Ma | | | | | |
| Magnetic Field Emissions | | | | | | |
| Test Position | Measure Value (A/m) | Limit(A/m) | 30% Limit (A/m) | | | |
| Top | 0.0081 | 1.63 | 0.489 | | | |
| Bottom | 0.0072 | 1.63 | 0.489 | | | |
| Side 1 | 0.0062 | 1.63 | 0.489 | | | |
| Side 2 | 0.0065 | 1.63 | 0.489 | | | |
| Side 3 | 0.0057 | 1.63 | 0.489 | | | |
| Side 4 | 0.0050 | 1.63 | 0.489 | | | |

1.5 Test Photos

