



RADIO TEST REPORT

Test Report No. 14568536S-A-R1

Customer	TDK Corporation
Description of EUT	Sensor Module
Model Number of EUT	i3 Micro Module
FCC ID	2ADLX-MM0110113M
Test Regulation	FCC Part 15 Subpart C
Test Result	Complied (Refer to SECTION 3)
Issue Date	September 21, 2023
Remarks	-

Representative Test Engineer

Y. Tanikawara

Yusuke Tanikawara
Engineer

Approved By

K. Takeyama

Kazutaka Takeyama
Leader



CERTIFICATE 1266.03

- The testing in which "Non-accreditation" is displayed is outside the accreditation scopes in UL Japan, Inc.
 There is no testing item of "Non-accreditation".

Report Cover Page - Form-ULID-003532 (DCS:13-EM-F0429) Issue# 21.0

ANNOUNCEMENT

- This test report shall not be reproduced in full or partial, without the written approval of UL Japan, Inc.
- The results in this report apply only to the sample tested. (Laboratory was not involved in sampling.)
- This sample tested is in compliance with the limits of the above regulation.
- The test results in this test report are traceable to the national or international standards.
- This test report must not be used by the customer to claim product certification, approval, or endorsement by the A2LA accreditation body.
- This test report covers Radio technical requirements.
It does not cover administrative issues such as Manual or non-Radio test related Requirements. (if applicable)
- The all test items in this test report are conducted by UL Japan, Inc. Shonan EMC Lab.
- The opinions and the interpretations to the result of the description in this report are outside scopes where UL Japan, Inc. has been accredited.
- The information provided from the customer for this report is identified in Section 1.
- For test report(s) referred in this report, the latest version (including any revisions) is always referred.

REVISION HISTORY

Original Test Report No.: 14568536S-A

This report is a revised version of 14568536S-A. 14568536S-A is replaced with this report.

Revision	Test Report No.	Date	Page Revised Contents
- (Original)	14568536S-A	February 28, 2023	-
1	14568536S-A-R1	September 21, 2023	Page 3 Corrected Rating in Clause 2.2 from “DC 2.20 V to 5.25 V” to “DC 2.2 V to 3.2 V (Battery), DC 4.75 V to 5.25 V (USB Bus Power)”.
			Page 5 • Added “and August 30, 2023” to Receipt Date. • Corrected testing end date from “February 14, 2023” to “September 1, 2023”.
			Page 10 Corrected note about supply voltage during Conducted Emission test from “AC 120 V of the worst voltage” to “AC 240 V of the worst voltage”.
			Page 29 Corrected DCCF waveform.

Reference: Abbreviations (Including words undescribed in this report)

A2LA	The American Association for Laboratory Accreditation	ICES	Interference-Causing Equipment Standard
AC	Alternating Current	IEC	International Electrotechnical Commission
AFH	Adaptive Frequency Hopping	IEEE	Institute of Electrical and Electronics Engineers
AM	Amplitude Modulation	IF	Intermediate Frequency
Amp, AMP	Amplifier	ILAC	International Laboratory Accreditation Conference
ANSI	American National Standards Institute	ISED	Innovation, Science and Economic Development Canada
Ant, ANT	Antenna	ISO	International Organization for Standardization
AP	Access Point	JAB	Japan Accreditation Board
ASK	Amplitude Shift Keying	LAN	Local Area Network
Atten., ATT	Attenuator	LIMS	Laboratory Information Management System
AV	Average	MCS	Modulation and Coding Scheme
BPSK	Binary Phase-Shift Keying	MRA	Mutual Recognition Arrangement
BR	Bluetooth Basic Rate	N/A	Not Applicable
BT	Bluetooth	NIST	National Institute of Standards and Technology
BT LE	Bluetooth Low Energy	NS	No signal detect.
BW	BandWidth	NSA	Normalized Site Attenuation
Cal Int	Calibration Interval	NVLAP	National Voluntary Laboratory Accreditation Program
CCK	Complementary Code Keying	OBW	Occupied Band Width
Ch., CH	Channel	OFDM	Orthogonal Frequency Division Multiplexing
CISPR	Comite International Special des Perturbations Radioelectriques	P/M	Power meter
CW	Continuous Wave	PCB	Printed Circuit Board
DBPSK	Differential BPSK	PER	Packet Error Rate
DC	Direct Current	PHY	Physical Layer
D-factor	Distance factor	PK	Peak
DFS	Dynamic Frequency Selection	PN	Pseudo random Noise
DQPSK	Differential QPSK	PRBS	Pseudo-Random Bit Sequence
DSSS	Direct Sequence Spread Spectrum	PSD	Power Spectral Density
EDR	Enhanced Data Rate	QAM	Quadrature Amplitude Modulation
EIRP, e.i.r.p.	Equivalent Isotropically Radiated Power	QP	Quasi-Peak
EMC	ElectroMagnetic Compatibility	QPSK	Quadri-Phase Shift Keying
EMI	ElectroMagnetic Interference	RBW	Resolution Band Width
EN	European Norm	RDS	Radio Data System
ERP, e.r.p.	Effective Radiated Power	RE	Radio Equipment
EU	European Union	RF	Radio Frequency
EUT	Equipment Under Test	RMS	Root Mean Square
Fac.	Factor	RSS	Radio Standards Specifications
FCC	Federal Communications Commission	Rx	Receiving
FHSS	Frequency Hopping Spread Spectrum	SA, S/A	Spectrum Analyzer
FM	Frequency Modulation	SG	Signal Generator
Freq.	Frequency	SVSWR	Site-Voltage Standing Wave Ratio
FSK	Frequency Shift Keying	TR	Test Receiver
GFSK	Gaussian Frequency-Shift Keying	Tx	Transmitting
GNSS	Global Navigation Satellite System	VBW	Video BandWidth
GPS	Global Positioning System	Vert.	Vertical
Hori.	Horizontal	WLAN	Wireless LAN

CONTENTS	PAGE
SECTION 1: Customer Information	5
SECTION 2: Equipment Under Test (EUT).....	5
SECTION 3: Test Specification, Procedures & Results	6
SECTION 4: Operation of EUT during testing.....	9
SECTION 5: Conducted Emission	12
SECTION 6: Radiated Spurious Emission	13
SECTION 7: Antenna Terminal Conducted Tests.....	16
APPENDIX 1: Test Data	17
Conducted Emission	17
99 % Occupied Bandwidth and 6 dB Bandwidth	21
Maximum Peak Output Power.....	24
Average Output Power.....	26
Radiated Spurious Emission	30
Conducted Spurious Emission	42
Power Density.....	48
APPENDIX 2: Test Instruments.....	50
APPENDIX 3: Photographs of Test Setup.....	52
Conducted Emission	52
Radiated Spurious Emission	53
Pre check of Worst Case Position.....	55
Antenna Terminal Conducted Tests.....	56

SECTION 1: Customer Information

Company Name	TDK Corporation
Address	2-15-7 Higashiohwa Ichikawa-shi Chiba, Japan
Telephone Number	+81-70-2260-5879
Contact Person	Michihiro Muramoto

The information provided from the customer is as follows;

- Customer, Description of EUT, Model Number of EUT, FCC ID on the cover and other relevant pages
- Operating/Test Mode(s) (Mode(s)) on all the relevant pages
- SECTION 1: Customer Information
- SECTION 2: Equipment Under Test (EUT) other than the Receipt Date and Test Date
- SECTION 4: Operation of EUT during testing

* The laboratory is exempted from liability of any test results affected from the above information in SECTION 2 and 4.

SECTION 2: Equipment Under Test (EUT)

2.1 Identification of EUT

Description	Sensor Module
Model Number	i3 Micro Module
Serial Number	Refer to SECTION 4.2
Condition	Engineering prototype (Not for Sale: This sample is equivalent to mass-produced items.)
Modification	No Modification by the test lab
Receipt Date	December 19, 2022 and August 30, 2023
Test Date	December 19, 2022 to September 1, 2023

2.2 Product Description

General Specification

Rating	DC 2.2 V to 3.2 V (Battery), DC 4.75 V to 5.25 V (USB Bus Power)
Operating temperature	-10 deg. C to +60 deg. C

Radio Specification

IEEE 802.15.4

Equipment Type	Transceiver
Frequency of Operation	2405 MHz to 2480 MHz
Type of Modulation	O-QPSK
Antenna Gain	-4.1 dBi

Bluetooth (Low Energy)

Equipment Type	Transceiver
Frequency of Operation	2402 MHz to 2480 MHz
Type of Modulation	GFSK
Antenna Gain	-4.1 dBi

* IEEE 802.15.4 and Bluetooth do not transmit simultaneously.

SECTION 3: Test Specification, Procedures & Results

3.1 Test Specification

Test Specification	FCC Part 15 Subpart C The latest version on the first day of the testing period
Title	FCC 47 CFR Part 15 Radio Frequency Device Subpart C Intentional Radiators Section 15.207 Conducted limits Section 15.247 Operation within the bands 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz

* Also the EUT complies with FCC Part 15 Subpart B.

3.2 Procedures and Results

Item	Test Procedure	Specification	Worst Margin	Results	Remarks
Conducted Emission	FCC: ANSI C63.10-2013 6. Standard test methods ISED: RSS-Gen 8.8	FCC: Section 15.207 ----- ISED: RSS-Gen 8.8	12.1 dB, 0.50013 MHz, L1 Mode : Tx BT LE, 2M-PHY 2402 MHz	Complied a)	-
6dB Bandwidth	FCC: KDB 558074 D01 15.247 Meas Guidance v05r02 ISED: -	FCC: Section 15.247(a)(2) ----- ISED: RSS-247 5.2(a)	See data.	Complied b)	Conducted
Maximum Peak Output Power	FCC: KDB 558074 D01 15.247 Meas Guidance v05r02 ISED: RSS-Gen 6.12	FCC: Section 15.247(b)(3) ----- ISED: RSS-247 5.4(d)		Complied c)	Conducted
Power Density	FCC: KDB 558074 D01 15.247 Meas Guidance v05r02 ISED: -	FCC: Section 15.247(e) ----- ISED: RSS-247 5.2(b)		Complied d)	Conducted
Spurious Emission Restricted Band Edges	FCC: KDB 558074 D01 15.247 Meas Guidance v05r02 ISED: RSS-Gen 6.13	FCC: Section 15.247(d) ----- ISED: RSS-247 5.5 RSS-Gen 8.9 RSS-Gen 8.10	3.7 dB 4804.000 MHz, AV, Hori. Mode : Tx BT LE, 2M-PHY 2402 MHz	Complied e), f)	Conducted (below 30 MHz)/ Radiated (above 30 MHz) *1)

Note: UL Japan, Inc.'s EMI Work Procedures: Work Instructions-ULID-003591 and Work Instructions-ULID-003593.

* In case any questions arise about test procedure, ANSI C63.10: 2013 is also referred.

*1) Radiated test was selected over 30 MHz based on section 15.247(d) and KDB 558074 D01 15.247 Meas Guidance v05r02 8.5 and 8.6.

- a) Refer to APPENDIX 1 (data of Conducted Emission)
- b) Refer to APPENDIX 1 (data of 6 dB Bandwidth and 99 % Occupied Bandwidth)
- c) Refer to APPENDIX 1 (data of Maximum Peak Output Power)
- d) Refer to APPENDIX 1 (data of Power Density)
- e) Refer to APPENDIX 1 (data of Conducted Spurious Emission)
- f) Refer to APPENDIX 1 (data of Radiated Spurious Emission)

FCC Part 15.31 (e)

This EUT provides the stable voltage constantly to RF Part regardless of input voltage.
Therefore, this EUT complies with the requirement.

FCC Part 15.203 Antenna requirement

It is impossible for end users to replace the antenna, because the antenna is mounted inside of the EUT.
Therefore, the equipment complies with the antenna requirement of Section 15.203.

3.3 Addition to Standard

Item	Test Procedure	Specification	Worst Margin	Results	Remarks
99% Occupied Bandwidth	ISED: RSS-Gen 6.7	ISED: -	N/A	- a)	Conducted
a) Refer to APPENDIX 1 (data of 6 dB Bandwidth and 99 % Occupied Bandwidth)					

Other than above, no addition, exclusion nor deviation has been made from the standard.

3.4 Uncertainty

Measurement uncertainty is not taken into account when stating conformity with a specified requirement.

Note: When margins obtained from test results are less than the measurement uncertainty, the test results may exceed the limit.

The following uncertainties have been calculated to provide a confidence level of 95 % using a coverage factor $k = 2$.

Item	Frequency range	Uncertainty (+/-)
Conducted emission (AC Mains) LISN	150 kHz-30 MHz	3.1 dB
Radiated emission (Measurement distance: 3 m)	9 kHz-30 MHz	3.3 dB
	30 MHz-200 MHz	4.8 dB
	200 MHz-1 GHz	6.1 dB
	1 GHz-6 GHz	4.7 dB
	6 GHz-18 GHz	5.3 dB
	18 GHz-40 GHz	5.5 dB
Radiated emission (Measurement distance: 1 m)	1 GHz-18 GHz	5.6 dB
	18 GHz-40 GHz	5.8 dB

Antenna terminal test	Uncertainty (+/-)
Power Measurement above 1 GHz (Average Detector)_SPM-06	1.3 dB
Power Measurement above 1 GHz (Peak Detector)_SPM-06	2.1 dB
Power Measurement above 1 GHz (Average Detector)_SPM-07	1.1 dB
Power Measurement above 1 GHz (Peak Detector)_SPM-07	1.2 dB
Power Measurement above 1 GHz (Average Detector)_SPM-13	1.1 dB
Power Measurement above 1 GHz (Peak Detector)_SPM-13	1.4 dB
Spurious emission (Conducted) below 1 GHz	0.84 dB
Conducted emissions Power Density Measurement 1 GHz-3 GHz	0.86 dB
Conducted emissions Power Density Measurement 3 GHz-18 GHz	2.4 dB
Spurious emission (Conducted) 18 GHz-26.5 GHz	2.4 dB
Spurious emission (Conducted) 26.5 GHz-40 GHz	2.2 dB
Bandwidth Measurement	0.012 %
Duty cycle and Time Measurement	0.27 %
Temperature_SCH-01	0.87 deg.C.
Humidity_SCH-01	3.5 %
Temperature_SCH-02	2.0 deg.C.
Humidity_SCH-02	6.7 %
Voltage	0.92 %

3.5 Test Location

UL Japan, Inc. Shonan EMC Lab.
1-22-3, Megumigaoka, Hiratsuka-shi, Kanagawa-ken 259-1220 Japan
Telephone: +81-463-50-6400
A2LA Certificate Number: 1266.03
(FCC test firm registration number: 626366, ISED lab company number: 2973D / CAB identifier: JP0001)

Test site	IC Registration Number	Width x Depth x Height (m)	Size of reference ground plane (m) / horizontal conducting plane	Maximum measurement distance
No.1 Semi-anechoic chamber	2973D-1	20.6 x 11.3 x 7.65	20.6 x 11.3	10 m
No.2 Semi-anechoic chamber	2973D-2	20.6 x 11.3 x 7.65	20.6 x 11.3	10 m
No.3 Semi-anechoic chamber	2973D-3	12.7 x 7.7 x 5.35	12.7 x 7.7	5 m
No.4 Semi-anechoic chamber	-	8.1 x 5.1 x 3.55	8.1 x 5.1	-
No.1 Shielded room	-	6.8 x 4.1 x 2.7	6.8 x 4.1	-
No.2 Shielded room	-	6.8 x 4.1 x 2.7	6.8 x 4.1	-
No.3 Shielded room	-	6.3 x 4.7 x 2.7	6.3 x 4.7	-
No.4 Shielded room	-	4.4 x 4.7 x 2.7	4.4 x 4.7	-
No.5 Shielded room	-	7.8 x 6.4 x 2.7	7.8 x 6.4	-
No.6 Shielded room	-	7.8 x 6.4 x 2.7	7.8 x 6.4	-
No.8 Shielded room	-	3.45 x 5.5 x 2.4	3.45 x 5.5	-
No.1 Measurement room	-	2.55 x 4.1 x 2.5	-	-

3.6 Test Data, Test Instruments, and Test Set Up

Refer to APPENDIX.

SECTION 4: Operation of EUT during testing

4.1 Operating Mode(s)

Mode	Remarks*
IEEE 802.15.4	Maximum Packet Size, PRBS9
Bluetooth Low Energy (BLE) 2M-PHY Uncoded PHY (2M-PHY)	Maximum Packet Size, PRBS9
<p>*Power of the EUT was set by the software as follows; Power Setting: 5 dBm Software: SmartRF Studio 7 Version: 2.27.0 (Date: 2022.10 07, Storage location: Driven by connected PC)</p> <p>*This setting of software is the worst case. Any conditions under the normal use do not exceed the condition of setting. In addition, end users cannot change the settings of the output power of the product.</p>	


*The Details of Operating Mode(s)

Test Item	Operating Mode	Tested frequency
Conducted Emission, Radiated Spurious Emission (Below 1 GHz)	Tx IEEE 802.15.4 *1)	2405 MHz
	Tx BLE, 2M-PHY *1)	2402 MHz
Radiated Spurious Emission (Above 1 GHz), Maximum Peak Output Power, Power Density, 6dB Bandwidth, 99% Occupied Bandwidth, Conducted Spurious Emission	Tx IEEE 802.15.4	2405 MHz 2440 MHz 2480 MHz
	Tx BLE, 2M-PHY	2402 MHz 2440 MHz 2480 MHz


*1) The mode was tested as a representative, because it had the highest power at antenna terminal test.

4.2 Configuration and Peripherals

Other than Conducted Emission test



Conducted Emission test



* Cabling and setup(s) were taken into consideration and test data was taken under worse case conditions.

*As a result of comparing AC 120 V and AC 240 V at pre-check, conducted emission test was performed with AC 240 V of the worst voltage as representative.

Description of EUT and Support Equipment

No.	Item	Model number	Serial Number	Manufacturer	Remarks
A	Sensor Module	i3 Micro Module	i3 MM 001*1) i3 MM 003*2) i3 MM 004*3)	TDK Corporation	EUT
B	Laptop PC	DX-C3	723450-25086	THIRDWAVE	-
C	AC Adapter	A18-045N2A	CNYAAG19023C 169014T00829	Chiconya POWER TECHNOLOGY	-
D	Laptop PC	E1Q57PA#ABJ	5CB3310KHW	HP	-
E	AC Adapter	PPP009L-E	3453442403	HP	-

*1) Used for Conducted Emission test and Radiated Emission test.

*2) Used for Antenna Terminal conducted test.

*3) Used for Duty cycle correction factor test.

List of Cables Used

No.	Name	Length (m)	Shield		Remarks
			Cable	Connector	
1	USB	1.0 + 2.0 1.0 *4)	Shielded	Shielded	-
2	Signal	0.15	Unshielded	Unshielded	-
3	DC	1.5	Unshielded	Unshielded	-
4	AC	0.9	Unshielded	Unshielded	-
5	DC	1.7	Unshielded	Unshielded	-
6	AC	1.0	Unshielded	Unshielded	-

*4) Used for Conducted Emission test.

SECTION 5: Conducted Emission

Test Procedure and Conditions

EUT was placed on a urethane platform of nominal size, 1.0 m by 1.5 m, raised 0.8 m above the conducting ground plane.

The rear of tabletop was located 40 cm to the vertical conducting plane. The rear of EUT, including peripherals, was aligned and flushed with rear of tabletop. All other surfaces of tabletop were at least 80cm from any other grounded conducting surface. EUT was located 80 cm from a Line Impedance Stabilization Network (LISN) / Artificial mains Network (AMN).

For the tests on EUT with other peripherals (as a whole system)

I/O cables that were connected to the peripherals were bundled in center. They were folded back and forth forming a bundle 30 cm to 40 cm long and were hanged at a 40 cm height to the ground plane. All unused 50ohm connectors of the LISN (AMN) were resistivity terminated in 50 ohm when not connected to the measuring equipment.

The AC Mains Terminal Continuous disturbance Voltage has been measured with the EUT in a Shielded Room.


The EUT was connected to a LISN (AMN).

An overview sweep with peak detection has been performed.

The test results and limit are rounded off to one decimal place, so some differences might be observed.

Detector	: QP and CISPR AV
Measurement Range	: 0.15 MHz to 30 MHz
Test Data	: APPENDIX
Test Result	: Pass

Figure 1: Test Setup



SECTION 6: Radiated Spurious Emission

Test Procedure

It was measured based on "8.5 and 8.6 of KDB 558074 D01 15.247 Meas Guidance v05r02".

[For below 1 GHz]

EUT was placed on a urethane platform of nominal size, 1.0 m by 1.5 m, raised 0.8 m above the conducting ground plane. The Radiated Electric Field Strength has been measured in a Semi Anechoic Chamber with a ground plane.

[For above 1 GHz]

EUT was placed on a urethane platform of nominal size, 0.5 m by 0.5 m, raised 1.5 m above the conducting ground plane. The Radiated Electric Field Strength has been measured in a Semi Anechoic Chamber with absorbent materials lined on a ground plane. Test antenna was aimed at the EUT for receiving the maximum signal and always kept within the illumination area of the 3 dB beamwidth of the antenna.

The height of the measuring antenna varied between 1 m and 4 m and EUT was rotated a full revolution in order to obtain the maximum value of the electric field strength.

The measurements were performed for both vertical and horizontal antenna polarization with the Test Receiver, or the Spectrum Analyzer.

The measurements were made with the following detector function of the test receiver and the Spectrum analyzer (in linear mode).

The test was made with the detector (RBW/VBW) in the following table.

When using Spectrum analyzer, the test was made with adjusting span to zero by using peak hold.

Test Antennas are used as below;

Frequency	30 MHz to 200 MHz	200 MHz to 1 GHz	Above 1 GHz
Antenna Type	Biconical	Logperiodic	Horn

In any 100 kHz bandwidth outside the restricted band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator confirmed 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on a radiated measurement.


20 dBc was applied to the frequency over the limit of FCC 15.209 / Table 4 of RSS-Gen 8.9(ISED) and outside the restricted band of FCC15.205 / Table 6 of RSS-Gen 8.10 (ISED).

Frequency	Below 1 GHz	Above 1 GHz		20 dBc
Instrument Used	Test Receiver	Spectrum Analyzer		Spectrum Analyzer
Detector	QP	PK	AV	PK
IF Bandwidth	BW 120 kHz	RBW: 1 MHz VBW: 3 MHz	For IEEE 802.15.4 *1) For BT LE <u>11.12.2.5.1</u> RBW: 1 MHz VBW: 3 MHz Detector: Power Averaging (RMS) Trace: 100 traces <u>11.12.2.5.2</u> The duty cycle was less than 98% for detected noise, a duty factor was added to the 11.12.2.5.1 results.	RBW: 100 kHz VBW: 300 kHz

*1) Measurement with Average detector was not performed. The limit for Average detector is applied to the measurement value with Peak detector used Duty cycle correction factor (DCCF).


Figure 2: Test Setup

Below 1 GHz



Test Distance: 3 m


1 GHz to 10 GHz



Distance Factor: $20 \times \log(3.97 \text{ m} / 3.0 \text{ m}) = 2.44 \text{ dB}$
* Test Distance: $(3 + \text{SVSWR Volume} / 2) - r = 3.97 \text{ m}$

SVSWR Volume : 2.0 m
(SVSWR Volume has been calibrated based on CISPR 16-1-4.)
 $r = 0.03 \text{ m}$

10 GHz to 26.5 GHz



Distance Factor: $20 \times \log(1.0 \text{ m} / 3.0 \text{ m}) = -9.54 \text{ dB}$
* Test Distance: 1 m

- The carrier level and noise levels were confirmed at each position of X, Y and Z axes of EUT to see the position of maximum noise, and the test was made at the position that has the maximum noise.

IEEE 802.15.4

	Horizontal	Vertical
Below 1 GHz	Axis X	Axis X
1 GHz - 2.8 GHz	Axis X	Axis Y
2.8 GHz - 10 GHz	Axis X	Axis Z
Above 10 GHz	Axis X	Axis X

BT LE

	Horizontal	Vertical
Below 1 GHz	Axis X	Axis X
1 GHz - 2.8 GHz	Axis X	Axis Y
2.8 GHz - 10 GHz	Axis X	Axis Z
Above 10 GHz	Axis X	Axis X

The test results and limit are rounded off to one decimal place, so some differences might be observed.

Measurement Range : 30 MHz to 26.5 GHz
Test Data : APPENDIX
Test Result : Pass

SECTION 7: Antenna Terminal Conducted Tests

Test Procedure

The tests were made with below setting connected to the antenna port.

Test	Span	RBW	VBW	Sweep time	Detector	Trace	Instrument Used
6dB Bandwidth	5 MHz	100 kHz	300 kHz	Auto	Peak	Max Hold	Spectrum Analyzer
99% Occupied Bandwidth *1)	Enough width to display emission skirts	1 to 5 % of OBW	Three times of RBW	Auto	Peak	Max Hold	Spectrum Analyzer
Maximum Peak Output Power	-	-	-	Auto	Peak/ Average *2)	-	Power Meter (Sensor: 160 MHz BW)
Peak Power Density	1.5 times the 6dB Bandwidth	3 kHz	9.1 kHz	Auto	Peak	Max Hold	Spectrum Analyzer *3)
Conducted Spurious Emission *4) *5)	9 kHz to 150 kHz	200 Hz	620 Hz	Auto	Peak	Max Hold	Spectrum Analyzer
	150 kHz to 30 MHz	10 kHz	30 kHz				
<p>*1) Peak hold was applied as Worst-case measurement. *2) Reference data *3) Section 11.10.2 Method PKPSD (peak PSD) of "ANSI C63.10-2013". *4) In the frequency range below 30MHz, RBW was narrowed to separate the noise contents. Then, wide-band noise near the limit was checked separately, however the noise was not detected as shown in the chart. *5) The limits in CFR 47, Part 15, Subpart C, paragraph 15.209(a), are identical to those in RSS-Gen section 8.9, Table 6, since the measurements are performed in terms of magnetic field strength and converted to electric field strength levels (as reported in the table) using the free space impedance of 377 Ohms. For example, the measurement at frequency 9 kHz resulted in a level of 45.5 dBuV/m, which is equivalent to $45.5 - 51.5 = -6.0$ dBuA/m, which has the same margin, 3 dB, to the corresponding RSS-Gen Table 6 limit as it has to 15.209(a) limit.</p>							

The test results and limit are rounded off to two decimals place, so some differences might be observed.
 The equipment and cables were not used for factor 0 dB of the data sheets.

Test Data : **APPENDIX**
Test Result : **Pass**

APPENDIX 1: Test Data

Conducted Emission

DATA OF CONDUCTED EMISSION TEST

UL Japan, Inc. Shonan EMC Lab. No.2 Shielded Room
Date : 2023/02/14


Mode : Tx IEEE 802.15.4, 2405 MHz

Power : AC 240 V / 60 Hz (AC Adapter)
Temp./Humi. : 23 deg.C / 25 %RH

Remarks : -

Limit : FCC_Part 15 Subpart C(15.207)

Engineer : Yusuke Tanikawara




No.	Freq. [MHz]	Reading		C.Fac	Results		Limit		Margin		Phase	Comment
		(QP) [dBuV]	(CAV) [dBuV]		(QP) [dBuV]	(CAV) [dBuV]	(QP) [dBuV]	(AV) [dBuV]	(QP) [dB]	(AV) [dB]		
1	0.15000	35.30	22.00	12.35	47.65	34.35	66.00	56.00	18.3	21.6	N	
2	0.16263	34.00	22.10	12.36	46.36	34.46	65.33	55.33	18.9	20.8	N	
3	0.17331	33.60	22.40	12.36	45.96	34.76	64.80	54.80	18.8	20.0	N	
4	0.19465	35.50	25.20	12.35	47.85	37.55	63.84	53.84	15.9	16.2	N	
5	0.21442	35.70	26.70	12.35	48.05	39.05	63.03	53.03	14.9	13.9	N	
6	0.22260	35.50	26.40	12.35	47.85	38.75	62.72	52.72	14.8	13.9	N	
7	0.23695	33.80	25.50	12.36	46.16	37.86	62.20	52.20	16.0	14.3	N	
8	0.25443	31.40	23.30	12.36	43.76	35.66	61.61	51.61	17.8	15.9	N	
9	0.27281	29.40	20.30	12.36	41.76	32.66	61.03	51.03	19.2	18.3	N	
10	0.29795	26.30	18.00	12.35	38.65	30.35	60.30	50.30	21.6	19.9	N	
11	0.49321	24.30	19.60	12.37	36.67	31.97	56.11	46.11	19.4	14.1	N	
12	2.88687	11.10	5.90	12.44	23.54	18.34	56.00	46.00	32.4	27.6	N	
13	0.15000	36.10	21.50	12.35	48.45	33.85	66.00	56.00	17.5	22.1	L1	
14	0.16263	35.20	21.40	12.36	47.56	33.76	65.33	55.33	17.7	21.5	L1	
15	0.17331	33.60	22.00	12.36	45.96	34.36	64.80	54.80	18.8	20.4	L1	
16	0.19465	34.50	24.60	12.35	46.85	36.95	63.84	53.84	16.9	16.8	L1	
17	0.21341	35.50	27.00	12.35	47.85	39.35	63.07	53.07	15.2	13.7	L1	
18	0.22110	35.40	26.90	12.35	47.75	39.25	62.78	52.78	15.0	13.5	L1	
19	0.23695	33.80	25.80	12.36	46.16	38.16	62.20	52.20	16.0	14.0	L1	
20	0.25443	31.50	23.30	12.36	43.86	35.66	61.61	51.61	17.7	15.9	L1	
21	0.27281	29.30	20.50	12.36	41.66	32.86	61.03	51.03	19.3	18.1	L1	
22	0.29795	26.50	18.60	12.35	38.85	30.95	60.30	50.30	21.4	19.3	L1	
23	0.49321	26.00	21.10	12.37	38.37	33.47	56.11	46.11	17.7	12.6	L1	
24	2.88900	16.30	11.50	12.43	28.73	23.93	56.00	46.00	27.2	22.0	L1	

Calculation: Result[dBuV]=Reading[dBuV]+C.Fac(LISN(AMN)+Cable+ATT)[dB]
LISN(AMN)=SLS-03

Conducted Emission

Test place	Shonan EMC Lab. No.2 Shielded Room
Date	February 14, 2023
Temperature / Humidity	23 deg. C / 25 % RH
Engineer	Yusuke Tanikawara
Mode	Tx IEEE 802.15.4



Conducted Emission

DATA OF CONDUCTED EMISSION TEST


UL Japan, Inc. Shonan EMC Lab. No.2 Shielded Room
Date : 2023/02/14

Mode : Tx BT LE 2M-PHY, 2402 MHz
Power : AC 240 V / 60 Hz (AC Adapter)
Temp./Humi. : 23 deg.C / 25 %RH

Remarks : -

Limit : FCC_Part 15 Subpart C(15.207)

Engineer : Yusuke Tanikawara




No.	Freq. [MHz]	Reading		C.Fac	Results		Limit		Margin		Phase	Comment
		<QP> [dBuV]	<CAV> [dBuV]		<QP> [dBuV]	<CAV> [dBuV]	<QP> [dBuV]	<AV> [dBuV]	<QP> [dB]	<AV> [dB]		
1	0.15000	35.10	22.00	12.35	47.45	34.35	66.00	56.00	18.5	21.6	N	
2	0.16327	34.00	21.90	12.36	46.36	34.26	65.30	55.30	18.9	21.0	N	
3	0.17203	33.50	22.10	12.36	45.86	34.46	64.86	54.86	19.0	20.4	N	
4	0.18920	34.20	25.30	12.35	46.55	37.65	64.07	54.07	17.5	16.4	N	
5	0.21377	36.00	26.50	12.35	48.35	38.85	63.06	53.06	14.7	14.2	N	
6	0.22616	34.70	26.10	12.36	47.06	38.46	62.59	52.59	15.5	14.1	N	
7	0.23759	33.10	25.20	12.36	45.46	37.56	62.18	52.18	16.7	14.6	N	
8	0.24751	32.20	24.20	12.36	44.56	36.56	61.84	51.84	17.2	15.2	N	
9	0.26324	30.30	21.60	12.36	42.66	33.96	61.33	51.33	18.6	17.3	N	
10	0.28066	28.50	19.30	12.35	40.85	31.65	60.80	50.80	19.9	19.1	N	
11	0.49879	24.40	19.70	12.37	36.77	32.07	56.02	46.02	19.2	13.9	N	
12	2.88139	11.10	5.90	12.44	23.54	18.34	56.00	46.00	32.4	27.6	N	
13	0.15000	35.60	21.30	12.35	47.95	33.65	66.00	56.00	18.0	22.3	L1	
14	0.16327	34.20	21.50	12.36	46.56	33.86	65.30	55.30	18.7	21.4	L1	
15	0.17203	33.40	21.60	12.36	45.76	33.96	64.86	54.86	19.1	20.9	L1	
16	0.18920	34.20	24.10	12.35	46.55	36.45	64.07	54.07	17.5	17.6	L1	
17	0.21314	35.40	26.30	12.35	47.75	38.65	63.08	53.08	15.3	14.4	L1	
18	0.22616	34.50	26.30	12.36	46.86	38.66	62.59	52.59	15.7	13.9	L1	
19	0.23759	33.40	25.60	12.36	45.76	37.96	62.18	52.18	16.4	14.2	L1	
20	0.24751	32.10	24.20	12.36	44.46	36.56	61.84	51.84	17.3	15.2	L1	
21	0.26324	31.00	21.80	12.36	43.36	34.16	61.33	51.33	17.9	17.1	L1	
22	0.28066	28.20	19.40	12.35	40.55	31.75	60.80	50.80	20.2	19.0	L1	
23	0.50013	26.30	21.50	12.37	38.67	33.87	56.00	46.00	17.3	12.1	L1	
24	2.84803	16.30	11.50	12.43	28.73	23.93	56.00	46.00	27.2	22.0	L1	

Calculation: Result[dBuV]=Reading[dBuV]+C.Fac(LISN(AMN))+Cable+ATT[dB]
LISN(AMN)=SLS-03

Conducted Emission

Test place	Shonan EMC Lab. No.2 Shielded Room
Date	February 14, 2023
Temperature / Humidity	23 deg. C / 25 % RH
Engineer	Yusuke Tanikawara
Mode	Tx BT LE



99 % Occupied Bandwidth and 6 dB Bandwidth

Test place Shonan EMC Lab. No.1 Shielded Room
Date December 19, 2022
Temperature / Humidity 25 deg. C / 46 % RH
Engineer Yosuke Murakami
Mode Tx

IEEE 802.15.4


Frequency [MHz]	99 % Occupied Bandwidth [kHz]	6 dB Bandwidth [MHz]	Limit for 6 dB Bandwidth [MHz]
2405	2578.0	1.618	> 0.5000
2440	2563.7	1.602	> 0.5000
2480	2574.5	1.628	> 0.5000

BT LE 2 M-PHY

Frequency [MHz]	99 % Occupied Bandwidth [kHz]	6 dB Bandwidth [MHz]	Limit for 6 dB Bandwidth [MHz]
2402	2062.5	1.299	> 0.5000
2440	2060.0	1.271	> 0.5000
2480	2072.5	1.329	> 0.5000


99 % Occupied Bandwidth and 6 dB Bandwidth

IEEE 802.15.4



99 % Occupied Bandwidth and 6 dB Bandwidth

BT LE 2 M-PHY



Maximum Peak Output Power

Test place	Shonan EMC Lab. No.1 Shielded Room
Date	December 19, 2022
Temperature / Humidity	25 deg. C / 46 % RH
Engineer	Yosuke Murakami
Mode	Tx IEEE 802.15.4

Maximum peak output power

Freq.	Reading	Cable Loss	Atten. Loss	Conducted Power					e.i.r.p. for RSS-247					
				Result		Limit		Margin	Antenna Gain	Result		Limit		Margin
				[dBm]	[mW]	[dBm]	[mW]			[dB]	[dBi]	[dBm]	[mW]	
2405	-6.48	1.67	9.64	4.83	3.04	30.00	1000	25.17	-4.10	0.73	1.18	36.02	4000	35.29
2440	-6.71	1.68	9.64	4.61	2.89	30.00	1000	25.39	-4.10	0.51	1.12	36.02	4000	35.51
2480	-7.09	1.69	9.64	4.24	2.65	30.00	1000	25.76	-4.10	0.14	1.03	36.02	4000	35.88

Sample Calculation:

Result = Reading + Cable Loss (including the cable(s) customer supplied) + Attenuator Loss

e.i.r.p. Result = Conducted Power Result + Antenna Gain

Maximum Peak Output Power

Test place	Shonan EMC Lab. No.1 Shielded Room
Date	December 19, 2022
Temperature / Humidity	25 deg. C / 46 % RH
Engineer	Yosuke Murakami
Mode	Tx BT LE 2 M - PHY

Maximum peak output power

Freq. [MHz]	Reading [dBm]	Cable Loss [dB]	Atten. Loss [dB]	Conducted Power					e.i.r.p. for RSS-247					
				Result		Limit		Margin [dB]	Antenna Gain [dBi]	Result		Limit		Margin [dB]
				[dBm]	[mW]	[dBm]	[mW]			[dBm]	[mW]	[dBm]	[mW]	
2402	-6.47	1.67	9.64	4.84	3.05	30.00	1000	25.16	-4.10	0.74	1.19	36.02	4000	35.28
2440	-6.73	1.68	9.64	4.59	2.88	30.00	1000	25.41	-4.10	0.49	1.12	36.02	4000	35.53
2480	-7.11	1.69	9.64	4.22	2.64	30.00	1000	25.78	-4.10	0.12	1.03	36.02	4000	35.90

Sample Calculation:

Result = Reading + Cable Loss (including the cable(s) customer supplied) + Attenuator Loss

e.i.r.p. Result = Conducted Power Result + Antenna Gain

Average Output Power
(Reference data for RF Exposure)

Test place	Shonan EMC Lab. No.1 Shielded Room
Date	December 19, 2022
Temperature / Humidity	25 deg. C / 46 % RH
Engineer	Yosuke Murakami
Mode	Tx IEEE 802.15.4

Average power

Freq. [MHz]	Reading [dBm]	Cable Loss [dB]	Atten. Loss [dB]	Result (Time average)		Duty factor [dB]	Result (Burst power average)	
				[dBm]	[mW]		[dBm]	[mW]
2405	-6.69	1.67	9.64	4.62	2.90	0.00	4.62	2.90
2440	-6.93	1.68	9.64	4.39	2.75	0.00	4.39	2.75
2480	-7.32	1.69	9.64	4.01	2.52	0.00	4.01	2.52

Sample Calculation:

Result (Time average) = Reading + Cable Loss (including the cable(s) customer supplied) + Attenuator Loss

Result (Burst power average) = Result (Time average) + Duty factor

Average Output Power
(Reference data for RF Exposure)

Test place Shonan EMC Lab. No.1 Shielded Room
Date December 19, 2022
Temperature / Humidity 25 deg. C / 46 % RH
Engineer Yosuke Murakami
Mode Tx BT LE 2 M - PHY

Average power

Freq. [MHz]	Reading [dBm]	Cable Loss [dB]	Atten. Loss [dB]	Result (Time average)		Duty factor [dB]	Result (Burst power average)	
				[dBm]	[mW]		[dBm]	[mW]
2402	-6.66	1.67	9.64	4.65	2.92	0.00	4.65	2.92
2440	-6.93	1.68	9.64	4.39	2.75	0.00	4.39	2.75
2480	-7.32	1.69	9.64	4.01	2.52	0.00	4.01	2.52


Sample Calculation:

Result (Time average) = Reading + Cable Loss (including the cable(s) customer supplied) + Attenuator Loss

Result (Burst power average) = Result (Time average) + Duty factor

Burst rate confirmation

Test place Shonan EMC Lab. No.1 Shielded Room
Date December 19, 2022
Temperature / Humidity 25 deg. C / 46 % RH
Engineer Yosuke Murakami
Mode Tx




* Since the burst rate is not different between the channels, the data has been obtained on the representative channel.

Duty cycle correction factor
(for Spurious emissions)

Test place Shonan EMC Lab. No.5 Shielded Room
Date September 1, 2023
Temperature / Humidity 26 deg. C / 44 % RH
Engineer Kouki Yamada
Mode Tx

Worst 100 ms (reference chart)
IEEE 802.15.4



* Since the burst rate is not different between the channels, the data has been obtained on the representative channel.

Radiated Spurious Emission

Test place	Shonan EMC Lab.		
Semi Anechoic Chamber	No.3	No.2	No.3
Date	February 9, 2023	December 27, 2022	February 8, 2023
Temperature / Humidity	21 deg. C / 26 % RH	21 deg. C / 26 % RH	24 deg. C / 25 % RH
Engineer	Kouki Yamada	Akihiro Oda	Shiro Kobayashi
	(Below 1 GHz)	(1 GHz - 10 GHz)	(Above 10 GHz)
Mode	Tx IEEE 802.15.4 2405 MHz		

(* PK: Peak, AV: Average, QP: Quasi-Peak)

Polarity	Frequency [MHz]	Detector	Reading [dBuV]	Ant.Fac. [dB/m]	Loss [dB]	Gain [dB]	Distance Factor [dB]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Height [cm]	Angle [deg]	Remark
Hori.	30.733	QP	22.50	18.45	6.48	32.17	0.00	15.26	40.0	24.7	100	284	-
Hori.	35.630	QP	22.00	16.54	6.57	32.16	0.00	12.95	40.0	27.0	100	172	-
Hori.	919.123	QP	20.30	22.02	11.02	30.85	0.00	22.49	46.0	23.5	100	211	-
Hori.	2390.000	PK	44.98	28.57	14.20	38.81	2.44	51.38	73.9	22.5	154	198	-
Hori.	4810.000	PK	53.41	31.91	6.62	38.64	2.44	55.74	73.9	18.1	100	84	-
Hori.	7215.000	PK	47.65	37.58	8.14	39.24	2.44	56.57	73.9	17.3	100	55	-
Vert.	30.255	QP	22.60	18.64	6.46	32.17	0.00	15.53	40.0	24.4	100	127	-
Vert.	37.067	QP	22.40	15.98	6.59	32.16	0.00	12.81	40.0	27.1	100	231	-
Vert.	44.319	QP	22.30	13.31	6.73	32.16	0.00	10.18	40.0	29.8	100	153	-
Vert.	55.413	QP	23.10	9.44	6.73	32.15	0.00	7.12	40.0	32.8	100	273	-
Vert.	65.976	QP	29.00	7.12	6.55	32.14	0.00	10.53	40.0	29.4	100	210	-
Vert.	86.819	QP	25.80	7.61	7.59	32.13	0.00	8.87	40.0	31.1	100	210	-
Vert.	910.675	QP	20.30	22.04	10.99	30.90	0.00	22.43	46.0	23.5	100	107	-
Vert.	2390.000	PK	45.37	28.57	14.20	38.81	2.44	51.77	73.9	22.1	117	234	-
Vert.	4810.000	PK	52.93	31.91	6.62	38.64	2.44	55.26	73.9	18.6	100	167	-
Vert.	7215.000	PK	47.28	37.58	8.14	39.24	2.44	56.20	73.9	17.7	103	68	-

Result = Reading + Ant.Fac. + Loss (Cable+(Attenuator or Filter)(below 18 GHz)) - Gain(Amplifier) + Distance factor

Distance factor : 1 GHz - 10 GHz : 20log(3.97 m / 3.0 m) = 2.44 dB

10 GHz - 40 GHz : 20log(1.0 m / 3.0 m) = -9.54 dB

Peak measurement value with Duty cycle correction factor (DCCF)

Polarity	Frequency [MHz]	Detector	Reading [dBuV]	Ant.Fac. [dB/m]	Loss [dB]	Gain [dB]	DCCF [dB]	Distance Factor [dB]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Remark
Hori.	2390.000	PK	44.98	28.57	14.20	38.81	-28.40	2.44	22.98	53.9	30.9	*1)
Hori.	4810.000	PK	53.41	31.91	6.62	38.64	-28.40	2.44	27.34	53.9	26.5	-
Hori.	7215.000	PK	47.65	37.58	8.14	39.24	-28.40	2.44	28.17	53.9	25.7	-
Vert.	2390.000	PK	45.37	28.57	14.20	38.81	-28.40	2.44	23.37	53.9	30.5	*1)
Vert.	4810.000	PK	52.93	31.91	6.62	38.64	-28.40	2.44	26.86	53.9	27.0	-
Vert.	7215.000	PK	47.28	37.58	8.14	39.24	-28.40	2.44	27.80	53.9	26.1	-

Result = Reading + Ant.Fac. + Loss (Cable+(Attenuator or Filter)(below 18 GHz)) - Gain(Amplifier) + DCCF + Distance factor

Distance factor : 1 GHz - 10 GHz : 20log(3.97 m / 3.0 m) = 2.44 dB

10 GHz - 40 GHz : 20log(1.0 m / 3.0 m) = -9.54 dB

Duty cycle correction factor (DCCF) refer to "Duty cycle correction factor" sheet.

*1) Not out of band emission (Leakage Power)

20 dBc Data Sheet (RBW 100 kHz, VBW 300 kHz)

Polarity	Frequency [MHz]	Detector	Reading [dBuV]	Ant.Fac. [dB/m]	Loss [dB]	Gain [dB]	Distance Factor [dB]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Remark
Hori.	2405.000	PK	85.27	28.54	14.22	38.80	2.44	91.67	-	-	Carrier
Hori.	2398.850	PK	37.89	28.55	14.21	38.81	2.44	44.28	71.6	27.3	-
Hori.	2400.000	PK	38.96	28.55	14.21	38.81	2.44	45.35	71.6	26.2	-
Vert.	2405.000	PK	83.83	28.54	14.22	38.80	2.44	90.23	-	-	Carrier
Vert.	2399.900	PK	39.12	28.55	14.21	38.81	2.44	45.51	70.2	24.6	-
Vert.	2400.000	PK	37.89	28.55	14.21	38.81	2.44	44.28	70.2	25.9	-



Result = Reading + Ant.Fac. + Loss (Cable+(Attenuator or Filter)(below 18 GHz)) - Gain(Amplifier) + Distance factor

Distance factor : 1 GHz - 10 GHz : 20log(3.97 m / 3.0 m) = 2.44 dB

10 GHz - 40 GHz : 20log(1.0 m / 3.0 m) = -9.54 dB

Radiated Spurious Emission
(Reference Plot for band-edge)

Test place	Shonan EMC Lab.
Semi Anechoic Chamber	No.2
Date	December 27, 2022
Temperature / Humidity	21 deg. C / 26 % RH
Engineer	Akihiro Oda
	(1 GHz - 10 GHz)
Mode	Tx IEEE 802.15.4 2405 MHz



* The measurement was conducted for a sufficiently long enough time to detect any possible spurious emissions. Final result of restricted band edge was shown in tabular data.

Radiated Spurious Emission

Test place	Shonan EMC Lab.	
Semi Anechoic Chamber	No.2	No.3
Date	December 27, 2022	February 8, 2023
Temperature / Humidity	21 deg. C / 26 % RH	24 deg. C / 25 % RH
Engineer	Akihiro Oda	Shiro Kobayashi
	(1 GHz - 10 GHz)	(Above 10 GHz)
Mode	Tx IEEE 802.15.4 2440 MHz	

(* PK: Peak, AV: Average, QP: Quasi-Peak)

Polarity	Frequency [MHz]	Detector	Reading [dBuV]	Ant. Fac. [dB/m]	Loss [dB]	Gain [dB]	Distance Factor [dB]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Height [cm]	Angle [deg]	Remark
Hori.	4880.000	PK	49.30	31.92	6.67	38.68	2.44	51.65	73.9	22.2	100	88	-
Hori.	7320.000	PK	47.91	37.66	8.20	39.28	2.44	56.93	73.9	16.9	107	57	-
Vert.	4880.000	PK	50.06	31.92	6.67	38.68	2.44	52.41	73.9	21.4	108	15	-
Vert.	7320.000	PK	46.22	37.66	8.20	39.28	2.44	55.24	73.9	18.6	100	13	-

Result = Reading + Ant.Fac. + Loss (Cable+(Attenuator or Filter)(below 18 GHz)) - Gain(Amplifier) + Distance factor

Distance factor : 1 GHz - 10 GHz : $20\log(3.97\text{ m} / 3.0\text{ m}) = 2.44\text{ dB}$

10 GHz - 40 GHz : $20\log(1.0\text{ m} / 3.0\text{ m}) = -9.54\text{ dB}$

Peak measurement value with Duty cycle correction factor (DCCF)

Polarity	Frequency [MHz]	Detector	Reading [dBuV]	Ant. Fac. [dB/m]	Loss [dB]	Gain [dB]	DCCF [dB]	Distance Factor [dB]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Remark
Hori.	4880.000	PK	49.30	31.92	6.67	38.68	-28.40	2.44	23.25	53.9	30.6	-
Hori.	7320.000	PK	47.91	37.66	8.20	39.28	-28.40	2.44	28.53	53.9	25.3	-
Vert.	4880.000	PK	50.06	31.92	6.67	38.68	-28.40	2.44	24.01	53.9	29.8	-
Vert.	7320.000	PK	46.22	37.66	8.20	39.28	-28.40	2.44	26.84	53.9	27.0	-

Result = Reading + Ant.Fac. + Loss (Cable+(Attenuator or Filter)(below 18 GHz)) - Gain(Amplifier) + DCCF + Distance factor

Distance factor : 1 GHz - 10 GHz : $20\log(3.97\text{ m} / 3.0\text{ m}) = 2.44\text{ dB}$

10 GHz - 40 GHz : $20\log(1.0\text{ m} / 3.0\text{ m}) = -9.54\text{ dB}$

Duty cycle correction factor (DCCF) refer to "Duty cycle correction factor" sheet.

Radiated Spurious Emission

Test place	Shonan EMC Lab.	
Semi Anechoic Chamber	No.2	No.3
Date	December 27, 2022	February 8, 2023
Temperature / Humidity	21 deg. C / 26 % RH	24 deg. C / 25 % RH
Engineer	Akihiro Oda	Shiro Kobayashi
	(1 GHz - 10 GHz)	(Above 10 GHz)
Mode	Tx IEEE 802.15.4 2480 MHz	

(* PK: Peak, AV: Average, QP: Quasi-Peak)

Polarity	Frequency [MHz]	Detector	Reading [dBuV]	Ant. Fac. [dB/m]	Loss [dB]	Gain [dB]	Distance Factor [dB]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Height [cm]	Angle [deg]	Remark
Hori.	2483.500	PK	50.77	28.44	14.30	38.76	2.44	57.19	73.9	16.7	142	216	-
Hori.	2484.283	PK	48.98	28.44	14.30	38.76	2.44	55.40	73.9	18.5	142	216	-
Hori.	4960.000	PK	47.86	32.10	6.72	38.72	2.44	50.40	73.9	23.5	104	86	-
Hori.	7440.000	PK	47.92	37.82	8.26	39.33	2.44	57.11	73.9	16.7	120	59	-
Vert.	2483.500	PK	50.57	28.44	14.30	38.76	2.44	56.99	73.9	16.9	151	231	-
Vert.	2484.317	PK	49.19	28.44	14.30	38.76	2.44	55.61	73.9	18.2	151	231	-
Vert.	4960.000	PK	47.50	32.10	6.72	38.72	2.44	50.04	73.9	23.8	129	184	-
Vert.	7440.000	PK	46.59	37.82	8.26	39.33	2.44	55.78	73.9	18.1	134	76	-

Result = Reading + Ant. Fac. + Loss (Cable+(Attenuator or Filter)(below 18 GHz)) - Gain(Amplifier) + Distance factor

Distance factor : 1 GHz - 10 GHz : $20\log(3.97\text{ m} / 3.0\text{ m}) = 2.44\text{ dB}$

10 GHz - 40 GHz : $20\log(1.0\text{ m} / 3.0\text{ m}) = -9.54\text{ dB}$

Peak measurement value with Duty cycle correction factor (DCCF)

Polarity	Frequency [MHz]	Detector	Reading [dBuV]	Ant. Fac. [dB/m]	Loss [dB]	Gain [dB]	DCCF [dB]	Distance Factor [dB]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Remark
Hori.	2483.500	PK	50.77	28.44	14.30	38.76	-28.40	2.44	28.79	53.9	25.1	*1)
Hori.	2484.283	PK	48.98	28.44	14.30	38.76	-28.40	2.44	27.00	53.9	26.9	-
Hori.	4960.000	PK	47.86	32.10	6.72	38.72	-28.40	2.44	22.00	53.9	31.9	-
Hori.	7440.000	PK	47.92	37.82	8.26	39.33	-28.40	2.44	28.71	53.9	25.1	-
Vert.	2483.500	PK	50.57	28.44	14.30	38.76	-28.40	2.44	28.59	53.9	25.3	*1)
Vert.	2484.317	PK	49.19	28.44	14.30	38.76	-28.40	2.44	27.21	53.9	26.6	-
Vert.	4960.000	PK	47.50	32.10	6.72	38.72	-28.40	2.44	21.64	53.9	32.2	-
Vert.	7440.000	PK	46.59	37.82	8.26	39.33	-28.40	2.44	27.38	53.9	26.5	-

Result = Reading + Ant. Fac. + Loss (Cable+(Attenuator or Filter)(below 18 GHz)) - Gain(Amplifier) + DCCF + Distance factor

Distance factor : 1 GHz - 10 GHz : $20\log(3.97\text{ m} / 3.0\text{ m}) = 2.44\text{ dB}$



10 GHz - 40 GHz : $20\log(1.0\text{ m} / 3.0\text{ m}) = -9.54\text{ dB}$

Duty cycle correction factor (DCCF) refer to "Duty cycle correction factor" sheet.

*1) Not out of band emission (Leakage Power)

Radiated Spurious Emission
(Reference Plot for band-edge)


Test place	Shonan EMC Lab.
Semi Anechoic Chamber	No.2
Date	December 27, 2022
Temperature / Humidity	21 deg. C / 26 % RH
Engineer	Akihiro Oda
	(1 GHz - 10 GHz)
Mode	Tx IEEE 802.15.4 2480 MHz



* The measurement was conducted for a sufficiently long enough time to detect any possible spurious emissions. Final result of restricted band edge was shown in tabular data.

Radiated Spurious Emission
(Plot data, Worst case mode for Maximum Peak Output Power)

Test place	Shonan EMC Lab.		
Semi Anechoic Chamber	No.3	No.2	No.3
Date	February 9, 2023	December 27, 2022	February 8, 2023
Temperature / Humidity	21 deg. C / 26 % RH	21 deg. C / 26 % RH	24 deg. C / 25 % RH
Engineer	Kouki Yamada (Below 1 GHz)	Akihiro Oda (1 GHz - 10 GHz)	Shiro Kobayashi (Above 10 GHz)
Mode	Tx IEEE 802.15.4 2405 MHz		



*These plots data contains sufficient number to show the trend of characteristic features for EUT.

Radiated Spurious Emission

Test place	Shonan EMC Lab.		
Semi Anechoic Chamber	No.3	No.2	No.3
Date	February 9, 2023	December 27, 2022	February 8, 2023
Temperature / Humidity	21 deg. C / 26 % RH	21 deg. C / 26 % RH	24 deg. C / 25 % RH
Engineer	Kouki Yamada (Below 1 GHz)	Akihiro Oda (1 GHz - 10 GHz)	Shiro Kobayashi (Above 10 GHz)
Mode	Tx BT LE 2M-PHY 2402 MHz		

(* PK: Peak, AV: Average, QP: Quasi-Peak)

Polarity	Frequency [MHz]	Detector	Reading [dBuV]	Ant. Fac. [dB/m]	Loss [dB]	Gain [dB]	Distance Factor [dB]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Height [cm]	Angle [deg]	Remark
Hori.	31.513	QP	22.20	18.14	6.49	32.17	0.00	14.66	40.0	25.3	100	31	-
Hori.	44.754	QP	22.30	13.15	6.75	32.16	0.00	10.04	40.0	29.9	100	112	-
Hori.	884.571	QP	20.40	22.03	10.91	31.06	0.00	22.28	46.0	23.7	100	89	-
Hori.	2390.000	PK	44.16	28.57	14.20	38.81	2.44	50.56	73.9	23.3	157	188	-
Hori.	4804.000	PK	54.04	31.90	6.62	38.64	2.44	56.36	73.9	17.5	100	85	-
Hori.	7206.000	PK	46.41	37.57	8.12	39.24	2.44	55.30	73.9	18.6	110	65	-
Hori.	2390.000	AV	35.54	28.57	14.20	38.81	2.44	41.94	53.9	11.9	157	188	-
Hori.	4804.000	AV	47.83	31.90	6.62	38.64	2.44	50.15	53.9	3.7	100	85	-
Hori.	7206.000	AV	38.02	37.57	8.12	39.24	2.44	46.91	53.9	6.9	110	65	-
Vert.	31.173	QP	22.20	18.27	6.48	32.17	0.00	14.78	40.0	25.2	100	342	-
Vert.	55.602	QP	25.50	9.39	6.72	32.15	0.00	9.46	40.0	30.5	100	185	-
Vert.	64.319	QP	31.40	7.42	6.49	32.14	0.00	13.17	40.0	26.8	100	93	-
Vert.	70.221	QP	28.40	6.62	6.80	32.14	0.00	9.68	40.0	30.3	100	353	-
Vert.	162.837	QP	21.80	15.28	7.87	32.06	0.00	12.89	43.5	30.6	100	85	-
Vert.	180.856	QP	21.70	16.00	7.83	32.04	0.00	13.49	43.5	30.0	100	332	-
Vert.	871.481	QP	20.60	22.03	10.87	31.15	0.00	22.35	46.0	23.6	100	95	-
Vert.	2390.000	PK	44.85	28.57	14.20	38.81	2.44	51.25	73.9	22.6	160	240	-
Vert.	4804.000	PK	53.62	31.90	6.62	38.64	2.44	55.94	73.9	17.9	100	13	-
Vert.	7206.000	PK	46.93	37.57	8.12	39.24	2.44	55.82	73.9	18.0	102	112	-
Vert.	2390.000	AV	35.68	28.57	14.20	38.81	2.44	42.08	53.9	11.8	160	240	-
Vert.	4804.000	AV	47.51	31.90	6.62	38.64	2.44	49.83	53.9	4.0	100	13	-
Vert.	7206.000	AV	37.73	37.57	8.12	39.24	2.44	46.62	53.9	7.2	102	112	-

Result = Reading + Ant.Fac. + Loss (Cable+(Attenuator or Filter)(below 18 GHz)) - Gain(Amplifier) + Distance factor

Distance factor : 1 GHz - 10 GHz : $20\log(3.97\text{ m} / 3.0\text{ m}) = 2.44\text{ dB}$

10 GHz - 40 GHz : $20\log(1.0\text{ m} / 3.0\text{ m}) = -9.54\text{ dB}$

20 dBc Data Sheet (RBW 100 kHz, VBW 300 kHz)

Polarity	Frequency [MHz]	Detector	Reading [dBuV]	Ant. Fac. [dB/m]	Loss [dB]	Gain [dB]	Distance Factor [dB]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Remark
Hori.	2402.000	PK	86.33	28.55	14.22	38.80	2.44	92.74	-	-	Carrier
Hori.	2399.117	PK	40.11	28.55	14.21	38.81	2.44	46.50	72.7	26.2	-
Hori.	2400.000	PK	54.80	28.55	14.21	38.81	2.44	61.19	72.7	11.5	-
Vert.	2402.000	PK	86.17	28.55	14.22	38.80	2.44	92.58	-	-	Carrier
Vert.	2399.100	PK	39.82	28.55	14.21	38.81	2.44	46.21	72.5	26.2	-
Vert.	2400.000	PK	54.46	28.55	14.21	38.81	2.44	60.85	72.5	11.6	-



Result = Reading + Ant.Fac. + Loss (Cable+(Attenuator or Filter)(below 18 GHz)) - Gain(Amplifier) + Distance factor

Distance factor : 1 GHz - 10 GHz : $20\log(3.97\text{ m} / 3.0\text{ m}) = 2.44\text{ dB}$

10 GHz - 40 GHz : $20\log(1.0\text{ m} / 3.0\text{ m}) = -9.54\text{ dB}$

Radiated Spurious Emission
(Reference Plot for band-edge)

Test place	Shonan EMC Lab.
Semi Anechoic Chamber	No.2
Date	December 27, 2022
Temperature / Humidity	21 deg. C / 26 % RH
Engineer	Akihiro Oda
	(1 GHz - 10 GHz)
Mode	Tx BT LE 2M-PHY 2402 MHz



* The measurement was conducted for a sufficiently long enough time to detect any possible spurious emissions. Final result of restricted band edge was shown in tabular data.

Radiated Spurious Emission

Test place	Shonan EMC Lab.	
Semi Anechoic Chamber	No.2	No.3
Date	December 27, 2022	February 8, 2023
Temperature / Humidity	21 deg. C / 26 % RH	24 deg. C / 25 % RH
Engineer	Akihiro Oda	Shiro Kobayashi
	(1 GHz - 10 GHz)	(Above 10 GHz)
Mode	Tx BT LE 2M-PHY 2440 MHz	

(* PK: Peak, AV: Average, QP: Quasi-Peak)

Polarity	Frequency [MHz]	Detector	Reading [dBuV]	Ant. Fac. [dB/m]	Loss [dB]	Gain [dB]	Distance Factor [dB]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Height [cm]	Angle [deg]	Remark
Hori.	4880.000	PK	50.08	31.92	6.67	38.68	2.44	52.43	73.9	21.4	112	78	-
Hori.	7320.000	PK	47.26	37.66	8.20	39.28	2.44	56.28	73.9	17.6	102	44	-
Hori.	4880.000	AV	41.47	31.92	6.67	38.68	2.44	43.82	53.9	10.0	112	78	-
Hori.	7320.000	AV	38.54	37.66	8.20	39.28	2.44	47.56	53.9	6.3	102	44	-
Vert.	4880.000	PK	49.75	31.92	6.67	38.68	2.44	52.10	73.9	21.8	152	302	-
Vert.	7320.000	PK	46.65	37.66	8.20	39.28	2.44	55.67	73.9	18.2	100	14	-
Vert.	4880.000	AV	41.98	31.92	6.67	38.68	2.44	44.33	53.9	9.5	152	302	-
Vert.	7320.000	AV	38.11	37.66	8.20	39.28	2.44	47.13	53.9	6.7	100	14	-

Result = Reading + Ant. Fac. + Loss (Cable+(Attenuator or Filter)(below 18 GHz)) - Gain(Amplifier) + Distance factor

Distance factor : 1 GHz - 10 GHz : $20\log(3.97\text{ m} / 3.0\text{ m}) = 2.44\text{ dB}$

10 GHz - 40 GHz : $20\log(1.0\text{ m} / 3.0\text{ m}) = -9.54\text{ dB}$

Radiated Spurious Emission

Test place	Shonan EMC Lab.	
Semi Anechoic Chamber	No.2	No.3
Date	December 27, 2022	February 8, 2023
Temperature / Humidity	21 deg. C / 26 % RH	24 deg. C / 25 % RH
Engineer	Akihiro Oda	Shiro Kobayashi
	(1 GHz - 10 GHz)	(Above 10 GHz)
Mode	Tx BT LE 2M-PHY 2480 MHz	

(* PK: Peak, AV: Average, QP: Quasi-Peak)

Polarity	Frequency [MHz]	Detector	Reading [dBuV]	Ant. Fac. [dB/m]	Loss [dB]	Gain [dB]	Distance Factor [dB]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Height [cm]	Angle [deg]	Remark
Hori.	2483.500	PK	49.28	28.44	14.30	38.76	2.44	55.70	73.9	18.2	146	189	-
Hori.	4960.000	PK	49.07	32.10	6.72	38.72	2.44	51.61	73.9	22.2	108	85	-
Hori.	7440.000	PK	46.81	37.82	8.26	39.33	2.44	56.00	73.9	17.9	101	49	-
Hori.	2483.500	AV	38.92	28.44	14.30	38.76	2.44	45.34	53.9	8.5	146	189	-
Hori.	4960.000	AV	39.56	32.10	6.72	38.72	2.44	42.10	53.9	11.8	108	85	-
Hori.	7440.000	AV	38.23	37.82	8.26	39.33	2.44	47.42	53.9	6.4	101	49	-
Vert.	2483.500	PK	47.28	28.44	14.30	38.76	2.44	53.70	73.9	20.2	154	249	-
Vert.	4960.000	PK	48.62	32.10	6.72	38.72	2.44	51.16	73.9	22.7	103	34	-
Vert.	7440.000	PK	47.17	37.82	8.26	39.33	2.44	56.36	73.9	17.5	100	0	-
Vert.	2483.500	AV	37.89	28.44	14.30	38.76	2.44	44.31	53.9	9.5	154	249	-
Vert.	4960.000	AV	40.78	32.10	6.72	38.72	2.44	43.32	53.9	10.5	103	34	-
Vert.	7440.000	AV	38.15	37.82	8.26	39.33	2.44	47.34	53.9	6.5	100	0	-



Result = Reading + Ant. Fac. + Loss (Cable+(Attenuator or Filter)(below 18 GHz)) - Gain(Amplifier) + Distance factor

Distance factor : 1 GHz - 10 GHz : $20\log(3.97\text{ m} / 3.0\text{ m}) = 2.44\text{ dB}$

10 GHz - 40 GHz : $20\log(1.0\text{ m} / 3.0\text{ m}) = -9.54\text{ dB}$

Radiated Spurious Emission
(Reference Plot for band-edge)


Test place	Shonan EMC Lab.
Semi Anechoic Chamber	No.2
Date	December 27, 2022
Temperature / Humidity	21 deg. C / 26 % RH
Engineer	Akihiro Oda
	(1 GHz - 10 GHz)
Mode	Tx BT LE 2M-PHY 2480 MHz



* The measurement was conducted for a sufficiently long enough time to detect any possible spurious emissions. Final result of restricted band edge was shown in tabular data.

Radiated Spurious Emission
(Plot data, Worst case mode for Maximum Peak Output Power)

Test place	Shonan EMC Lab.		
Semi Anechoic Chamber	No.3	No.2	No.3
Date	February 9, 2023	December 27, 2022	February 8, 2023
Temperature / Humidity	21 deg. C / 26 % RH	21 deg. C / 26 % RH	24 deg. C / 25 % RH
Engineer	Kouki Yamada (Below 1 GHz)	Akihiro Oda (1 GHz - 10 GHz)	Shiro Kobayashi (Above 10 GHz)
Mode	Tx BT LE 2M-PHY 2402 MHz		




*These plots data contains sufficient number to show the trend of characteristic features for EUT.

Conducted Spurious Emission

Test place	Shonan EMC Lab. No.1 Shielded Room
Date	December 19, 2022
Temperature / Humidity	25 deg. C / 46 % RH
Engineer	Yosuke Murakami
Mode	Tx IEEE 802.15.4 2405 MHz

Tx, 2405 MHz



Frequency [kHz]	Reading [dBm]	Cable Loss [dB]	Attenuator Loss [dB]	Antenna Gain* [dBi]	N (Number of Output)	EIRP [dBm]	Distance [m]	Ground bounce [dB]	E (field strength) [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Remark
13.82	-101.8	0.34	9.5	2.0	1	-90.0	300	6.0	-28.7	44.7	73.4	-
1170.00	-91.4	0.35	9.5	2.0	1	-79.5	30	6.0	1.8	26.2	24.4	-

$E \text{ [dBuV/m]} = \text{EIRP [dBm]} - 20 \log(\text{Distance [m]}) + \text{Ground bounce [dB]} + 104.8 \text{ [dBuV/m]}$

$\text{EIRP [dBm]} = \text{Reading [dBm]} + \text{Cable loss [dB]} + \text{Attenuator Loss [dB]} + \text{Antenna gain [dBi]} + 10 * \log(N)$


N: Number of output

*2.0 dBi was applied to the test result based on ANSI C63.10 since antenna gain was less than 2.0 dBi.

Conducted Spurious Emission

Test place	Shonan EMC Lab. No.1 Shielded Room
Date	December 19, 2022
Temperature / Humidity	25 deg. C / 46 % RH
Engineer	Yosuke Murakami
Mode	Tx IEEE 802.15.4 2440 MHz

Tx, 2440 MHz



Frequency [kHz]	Reading [dBm]	Cable Loss [dB]	Attenuator Loss [dB]	Antenna Gain* [dBi]	N (Number of Output)	EIRP [dBm]	Distance [m]	Ground bounce [dB]	E (field strength) [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Remark
9.12	-101.4	0.34	9.5	2.0	1	-89.5	300	6.0	-28.3	48.4	76.7	-
349.00	-91.5	0.34	9.5	2.0	1	-79.6	300	6.0	-18.3	16.7	35.0	-

$E \text{ [dBuV/m]} = \text{EIRP [dBm]} - 20 \log(\text{Distance [m]}) + \text{Ground bounce [dB]} + 104.8 \text{ [dBuV/m]}$

$\text{EIRP [dBm]} = \text{Reading [dBm]} + \text{Cable loss [dB]} + \text{Attenuator Loss [dB]} + \text{Antenna gain [dBi]} + 10 * \log(N)$


N: Number of output

*2.0 dBi was applied to the test result based on ANSI C63.10 since antenna gain was less than 2.0 dBi.

Conducted Spurious Emission

Test place	Shonan EMC Lab. No.1 Shielded Room
Date	December 19, 2022
Temperature / Humidity	25 deg. C / 46 % RH
Engineer	Yosuke Murakami
Mode	Tx IEEE 802.15.4 2480 MHz

Tx, 2480 MHz



Frequency [kHz]	Reading [dBm]	Cable Loss [dB]	Attenuator Loss [dB]	Antenna Gain* [dBi]	N (Number of Output)	EIRP [dBm]	Distance [m]	Ground bounce [dB]	E (field strength) [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Remark
13.82	-100.3	0.34	9.5	2.0	1	-88.4	300	6.0	-27.2	44.7	71.9	-
274.00	-90.8	0.34	9.5	2.0	1	-78.9	300	6.0	-17.6	18.8	36.4	-

$E \text{ [dBuV/m]} = \text{EIRP [dBm]} - 20 \log(\text{Distance [m]}) + \text{Ground bounce [dB]} + 104.8 \text{ [dBuV/m]}$

$\text{EIRP [dBm]} = \text{Reading [dBm]} + \text{Cable loss [dB]} + \text{Attenuator Loss [dB]} + \text{Antenna gain [dBi]} + 10 * \log(N)$


N: Number of output

*2.0 dBi was applied to the test result based on ANSI C63.10 since antenna gain was less than 2.0 dBi.

Conducted Spurious Emission

Test place	Shonan EMC Lab. No.1 Shielded Room
Date	December 19, 2022
Temperature / Humidity	25 deg. C / 46 % RH
Engineer	Yosuke Murakami
Mode	Tx BT LE 2 M - PHY 2402 MHz

Tx, 2402 MHz



Frequency [kHz]	Reading [dBm]	Cable Loss [dB]	Attenuator Loss [dB]	Antenna Gain* [dBi]	N (Number of Output)	EIRP [dBm]	Distance [m]	Ground bounce [dB]	E (field strength) [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Remark
14.05	-102.1	0.34	9.5	2.0	1	-90.2	300	6.0	-29.0	44.6	73.6	-
150.00	-89.6	0.34	9.5	2.0	1	-77.7	300	6.0	-16.5	24.0	40.5	-

$E \text{ [dBuV/m]} = \text{EIRP [dBm]} - 20 \log(\text{Distance [m]}) + \text{Ground bounce [dB]} + 104.8 \text{ [dBuV/m]}$

$\text{EIRP[dBm]} = \text{Reading [dBm]} + \text{Cable loss [dB]} + \text{Attenuator Loss [dB]} + \text{Antenna gain [dBi]} + 10 * \log(N)$


N: Number of output

*2.0 dBi was applied to the test result based on ANSI C63.10 since antenna gain was less than 2.0 dBi.

Conducted Spurious Emission

Test place	Shonan EMC Lab. No.1 Shielded Room
Date	December 19, 2022
Temperature / Humidity	25 deg. C / 46 % RH
Engineer	Yosuke Murakami
Mode	Tx BT LE 2 M - PHY 2440 MHz

Tx, 2440 MHz



Frequency [kHz]	Reading [dBm]	Cable Loss [dB]	Attenuator Loss [dB]	Antenna Gain* [dBi]	N (Number of Output)	EIRP [dBm]	Distance [m]	Ground bounce [dB]	E (field strength) [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Remark
11.35	-101.8	0.34	9.5	2.0	1	-89.9	300	6.0	-28.6	46.5	75.1	-
175.00	-90.6	0.34	9.5	2.0	1	-78.7	300	6.0	-17.5	22.7	40.2	-

$E \text{ [dBuV/m]} = \text{EIRP [dBm]} - 20 \log(\text{Distance [m]}) + \text{Ground bounce [dB]} + 104.8 \text{ [dBuV/m]}$

$\text{EIRP[dBm]} = \text{Reading [dBm]} + \text{Cable loss [dB]} + \text{Attenuator Loss [dB]} + \text{Antenna gain [dBi]} + 10 * \log(N)$


N: Number of output

*2.0 dBi was applied to the test result based on ANSI C63.10 since antenna gain was less than 2.0 dBi.

Conducted Spurious Emission

Test place	Shonan EMC Lab. No.1 Shielded Room
Date	December 19, 2022
Temperature / Humidity	25 deg. C / 46 % RH
Engineer	Yosuke Murakami
Mode	Tx BT LE 2 M - PHY 2402 MHz

Tx, 2480 MHz



Frequency [kHz]	Reading [dBm]	Cable Loss [dB]	Attenuator Loss [dB]	Antenna Gain* [dBi]	N (Number of Output)	EIRP [dBm]	Distance [m]	Ground bounce [dB]	E (field strength) [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Remark
10.88	-100.0	0.34	9.5	2.0	1	-88.2	300	6.0	-26.9	46.8	73.7	
1120.00	-90.5	0.35	9.5	2.0	1	-78.6	30	6.0	2.7	26.6	23.9	

$E \text{ [dBuV/m]} = \text{EIRP [dBm]} - 20 \log(\text{Distance [m]}) + \text{Ground bounce [dB]} + 104.8 \text{ [dBuV/m]}$

$\text{EIRP [dBm]} = \text{Reading [dBm]} + \text{Cable loss [dB]} + \text{Attenuator Loss [dB]} + \text{Antenna gain [dBi]} + 10 * \log(N)$

N: Number of output

*2.0 dBi was applied to the test result based on ANSI C63.10 since antenna gain was less than 2.0 dBi.

Power Density

Test place	Shonan EMC Lab. No.1 Shielded Room
Date	December 19, 2022
Temperature / Humidity	25 deg. C / 46 % RH
Engineer	Yosuke Murakami
Mode	Tx

IEEE 802.15.4

Frequency [MHz]	Measured Frequency [MHz]	Reading [dBm/3 kHz]	Cable Loss [dB]	Atten. Loss [dB]	Result [dBm/3 kHz]	Limit [dBm/3 kHz]	Margin [dB]
2405	2404.615	-20.35	1.67	9.64	-9.04	8.00	17.04
2440	2439.983	-21.37	1.68	9.64	-10.05	8.00	18.05
2480	2479.994	-20.82	1.69	9.64	-9.49	8.00	17.49

BT LE 2 M-PHY

Frequency [MHz]	Measured Frequency [MHz]	Reading [dBm/3 kHz]	Cable Loss [dB]	Atten. Loss [dB]	Result [dBm/3 kHz]	Limit [dBm/3 kHz]	Margin [dB]
2402	2402.055	-18.66	1.67	9.64	-7.35	8.00	15.35
2440	2440.057	-18.94	1.68	9.64	-7.62	8.00	15.62
2480	2480.055	-19.50	1.69	9.64	-8.17	8.00	16.17


Sample Calculation:

Result = Reading + Cable Loss (including the cable(s) customer supplied) + Attenuator Loss

Power Density

IEEE 802.15.4

BT LE 2 M-PHY



APPENDIX 2: Test Instruments**Test Equipment(1/2)**

Test Item	Local ID	LIMS ID	Description	Manufacturer	Model	Serial	Last Calibration Date	Cal Int
AT	KTS-07	145111	Digital Tester	SANWA	PC500	7019232	2022/09/20	12
AT	SAT10-09	145132	Attenuator	Weinschel Corp.	54A-10	W5692	2022/10/20	12
AT	SAT10-14	154591	Attenuator	Weinschel Corp.	54A-10	81595	2022/04/01	12
AT	SAT10-24	204928	Attenuator	Weinschel Corp.	54A-10	109973	2022/02/21	12
AT	SCC-G13	145166	Coaxial Cable	Suhner	SUCOFLEX 102	31599/2	2022/12/01	12
AT	SCC-G53	179107	Coaxial Cable	Junkosha	MWX241-01000KMSKMS/B	1901Q062-R	2022/04/01	12
AT	SCC-G67	196949	Coaxial Cable	Huber+Suhner	SUCOFLEX 102	803480/2	2022/03/02	12
AT	SOS-16	167990	Thermo-Hygrometer	CUSTOM. Inc	CTH-202	708Q08R	2022/10/18	12
AT	SOS-27	191845	Thermo-Hygrometer	CUSTOM. Inc	CTH-201	-	2022/08/08	12
AT	SPM-13	169910	Power Meter	Keysight Technologies Inc	8990B	MY51000448	2022/11/08	12
AT	SPSS-06	169911	Power sensor	Keysight Technologies Inc	N1923A	MY57270004	2022/11/08	12
AT	STS-01	145792	Digital Hitester	HIOKI E.E. CORPORATION	3805-50	80997812	2022/09/20	12
AT,RE	KSA-08	145089	Spectrum Analyzer	Keysight Technologies Inc	E4446A	MY46180525	2022/11/01	12
CE	KAT3-12	144896	Attenuator	JFW IND. INC.	50HF-003N	-	2022/07/14	12
CE	SCC-C9	145035	Coaxial Cable	Suhner	RG223U	-	2022/04/20	12
CE	SLS-03	145540	LISN	Rohde & Schwarz	ENV216	100513	2022/02/23	12
CE	SOS-22	191839	Thermo-Hygrometer	CUSTOM. Inc	CTH-201	-	2022/10/18	12
CE	STR-07	146209	Test Receiver	Rohde & Schwarz	ESU26	100484	2022/09/14	12
CE,RE	COTS-SEMI-5	170932	EMI Software	TSJ (Techno Science Japan)	TEPTO-DV3(RE,CE,ME,PE)	-	-	-
CE,RE	SJM-20	207277	Measuring	ASKUL	-	-	-	-
CE,RE	STS-02	145793	Digital Hitester	HIOKI E.E. CORPORATION	3805-50	80997819	2022/04/07	12
RE	KJM-02	146432	Measure	TAJIMA	GL19-55	-	-	-
RE	SAEC-02(SVSWR)	145598	Semi-Anechoic Chamber	TDK	SAEC-02(SVSWR)	2	2022/05/16	12
RE	SAEC-03(NSA)	145565	Semi-Anechoic Chamber	TDK	SAEC-03(NSA)	3	2022/04/15	12
RE	SAEC-03(SVSWR)	145566	Semi-Anechoic Chamber	TDK	SAEC-03(SVSWR)	3	2022/05/18	12
RE	SAF-03	145126	Pre Amplifier	SONOMA	310N	290213	2022/02/24	12
RE	SAF-05	145128	Pre Amplifier	Toyo Corporation	TPA0118-36	1440490	2022/05/12	12
RE	SAF-06	145005	Pre Amplifier	Toyo Corporation	TPA0118-36	1440491	2022/02/04	12
RE	SAF-09	145008	Pre Amplifier	Toyo Corporation	HAP18-26W	18	2022/09/01	12
RE	SAT10-06	145137	Attenuator	Keysight Technologies Inc	8493C-010	74865	2022/10/20	12
RE	SAT6-13	167094	Attenuator	JFW	50HF-006N	-	2022/02/21	12
RE	SBA-03	145023	Biconical Antenna	Schwarzbeck Mess-Elektronik OHG	BBA9106	91032666	2022/05/14	12
RE	SCC-C1/C2/C3/C4/C5/C10/SRSE-03	145171	Coaxial Cable&RF Selector	Fujikura/Fujikura/Suhner/Suhner/Suhner/Suhner/TOYO	8D2W/12DSFA/141PE/141PE/141PE/NS4906	-/0901-271(RF Selector)	2022/04/20	12
RE	SCC-G15	145176	Coaxial Cable	Suhner	SUCOFLEX 102	32703/2	2022/03/03	12
RE	SCC-G41	151617	Coaxial Cable	Junkosha	MWX221-01000NFSNMS/B	1612S006	2023/01/12	12
RE	SCC-G43	156380	Coaxial Cable	Huber+Suhner	SUCOFLEX_104_E	SN MY 13406/4E	2022/05/20	12

Test Equipment(2/2)

Test Item	Local ID	LIMS ID	Description	Manufacturer	Model	Serial	Last Calibration Date	Cal Int
RE	SCC-G50	178573	Coaxial Cable	Huber+Suhner	SUCOFLEX_104_E	MY13407/4E	2022/03/03	12
RE	SCC-G51	178572	Coaxial Cable	Huber+Suhner	SUCOFLEX 104	800288 /4A	2022/03/03	12
RE	SCC-G57	179540	Coaxial Cable	Huber+Suhner	SUCOFLEX 102	802815/2	2022/05/12	12
RE	SCC-G58	183047	Coaxial Cable	Huber+Suhner	SUCOFLEX 104	800287/4A	-	-
RE	SCC-G70	200010	Coaxial Cable	Huber+Suhner	SUCOFLEX 104	575618/4	2022/07/22	12
RE	SFL-18	145305	Highpass Filter	MICRO-TRONICS	HPM50111	119	2022/03/02	12
RE	SHA-02	145384	Horn Antenna	Schwarzbeck Mess-Elektronik OHG	BBHA9120D	9120D-726	2022/03/10	12
RE	SHA-05	145513	Horn Antenna	ETS-Lindgren	3160-09	00094867	2022/06/06	12
RE	SHA-10	194685	Horn Antenna	Schwarzbeck Mess-Elektronik OHG	BBHA 9120 C	711	2022/03/16	12
RE	SLA-07	145529	Logperiodic Antenna	Schwarzbeck Mess-Elektronik OHG	VUSLP9111B	196	2022/05/14	12
RE	SOS-21	191838	Thermo-Hygrometer	CUSTOM. Inc	CTH-201	-	2022/08/08	12
RE	SOS-23	191840	Thermo-Hygrometer	CUSTOM. Inc	CTH-201	-	2022/08/08	12
RE	SSA-03	145801	Spectrum Analyzer	Keysight Technologies Inc	E4448A	MY48250152	2022/08/04	12
RE	STR-08	150463	Test Receiver	Rohde & Schwarz	ESW44	101581	2022/03/02	12
RE	STS-03	146210	Digital Hitester	HIOKI E.E. CORPORATION	3805-50	80997823	2022/09/20	12

*Hyphens for Last Calibration Date and Cal Int (month) are instruments that Calibration is not required (e.g. software), or instruments checked in advance before use.

The expiration date of the calibration is the end of the expired month.

As for some calibrations performed after the tested dates, those test equipment have been controlled by means of an unbroken chains of calibrations.

All equipment is calibrated with valid calibrations. Each measurement data is traceable to the national or international standards.

Test item: CE: Conducted Emission
 RE: Radiated Emission
 AT: Antenna Terminal Conducted