

# TEST REPORT

**Product Name :** FUNKO TWS STITCH, FUNKO TWS STITCH CROWN, FUNKO TWS STITCH ELVIS, FUNKO TWS GRUMPY, FUNKO TWS VENOM, FUNKO TWS SNOOPY SCOUT  
**Model Number :** EP-0700-Stitch; EP-0700-S-CROWN; EP-0700-S-ELVIS; EP-0700-GRUMPY; EP-0700-VENOM; EP-0700-SY-SCOU  
**FCC ID :** 2ADM5-EP-0700

**Prepared for Address :** Zeeva Int Ltd  
1007B-8, 1012 & 15, 10th Fl, Exchange Tower, 33 Wang Chiu Road, Kowloon Bay, Hong Kong

**Prepared by Address :** EMTEK (DONGGUAN) CO., LTD.  
-1&2/F., Building 2, Zone A, Zhongda Marine Biotechnology Research and Development Base, No.9, Xincheng Avenue, Songshanhu High-technology Industrial Development Zone, Dongguan, Guangdong, China

TEL: +86-0769-22807078  
FAX: +86-0769-22807079

**Report Number :** EDG2502130181E00102R  
**Date of sample receipt :** Feb 13, 2025  
**Date(s) of Tests :** Feb 13, 2025 to Feb 28, 2025  
**Date of issue :** Mar 03, 2025

## Table of Contents

|                                    |   |
|------------------------------------|---|
| 1. TEST RESULT CERTIFICATION ..... | 3 |
| 2. EUT SPECIFICATION .....         | 5 |
| 3. TEST REQUIREMENT .....          | 6 |
| 4. MEASUREMENT RESULT .....        | 7 |



## 1. TEST RESULT CERTIFICATION

Applicant : Zeeva Int Ltd  
Address : 1007B-8, 1012 & 15, 10th Fl, Exchange Tower, 33 Wang Chiu Road, Kowloon Bay, Hong Kong  
Manufacturer : Zeeva Int Ltd  
Address : 1007B-8, 1012 & 15, 10th Fl, Exchange Tower, 33 Wang Chiu Road, Kowloon Bay, Hong Kong  
EUT : FUNKO TWS STITCH, FUNKO TWS STITCH CROWN, FUNKO TWS STITCH ELVIS, FUNKO TWS GRUMPY, FUNKO TWS VENOM, FUNKO TWS SNOOPY SCOUT  
Model Name : EP-0700-Stitch; EP-0700-S-CROWN; EP-0700-S-ELVIS; EP-0700-GRUMPY; EP-0700-VENOM; EP-0700-SY-SCOU  
Trademark : N/A

Measurement Procedure Used:

| APPLICABLE STANDARDS  |             |
|-----------------------|-------------|
| STANDARD              | TEST RESULT |
| § 15.247(i), § 2.1093 | PASS        |


The above equipment was tested by EMTEK(DONGGUAN) CO., LTD. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.10 (2013) and the energy emitted by the sample EUT tested as described in this report is in compliance with the requirements of FCC Rules FCC § 15.247(i), § 2.1093.

The test results of this report relate only to the tested sample identified in this report

Date of Test : Feb 13, 2025 to Feb 28, 2025

Prepared by :   
Galen Xiao /Editor

Reviewer :   
Warren Deng /Supervisor

Approve & Authorized Signer :    
Sam Lv /Manager

## Modified History

| Version | Report No.           | Revision Date | Summary         |
|---------|----------------------|---------------|-----------------|
|         | EDG2502130181E00102R | /             | Original Report |
|         |                      |               |                 |
|         |                      |               |                 |



## 2. EUT Specification

| Characteristics                       | Description                                                                                                                                                                                                         |
|---------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Product:</b>                       | FUNKO TWS STITCH, FUNKO TWS STITCH CROWN, FUNKO TWS STITCH ELVIS, FUNKO TWS GRUMPY, FUNKO TWS VENOM, FUNKO TWS SNOOPY SCOUT                                                                                         |
| <b>Model Number:</b>                  | EP-0700-Stitch; EP-0700-S-CROWN; EP-0700-S-ELVIS; EP-0700-GRUMPY; EP-0700-VENOM; EP-0700-SY-SCOU<br>All products are identical except the model number and color. Here we selected EP-0700-Stitch for all the test. |
| <b>SKU:</b>                           | 9110429, 9187425, 9187426, 9193521, 9194650, 9194648                                                                                                                                                                |
| <b>UPC:</b>                           | 1922342330487, 1922346349362, 1922346349379, 1922344853069, 1922344855827, 1922344855810                                                                                                                            |
| <b>COLOR:</b>                         | BLUE, BLUE, BLUE MULTI, RED, BLACK, WHITE                                                                                                                                                                           |
| <b>Sample:</b>                        | 1#                                                                                                                                                                                                                  |
| <b>Data Rate:</b>                     | 1Mbps for GFSK modulation<br>2Mbps for $\pi/4$ -DQPSK modulation<br>3Mbps for 8DPSK modulation                                                                                                                      |
| <b>Modulation:</b>                    | GFSK, $\pi/4$ -DQPSK, 8DPSK                                                                                                                                                                                         |
| <b>Operating Frequency Range(s) :</b> | 2402-2480MHz                                                                                                                                                                                                        |
| <b>Number of Channels:</b>            | 79 channels                                                                                                                                                                                                         |
| <b>Transmit Power Max:</b>            | -8.79 dBm(0.000132W)                                                                                                                                                                                                |
| <b>Antenna Gain:</b>                  | -0.05 dBi                                                                                                                                                                                                           |
| <b>Power supply:</b>                  | DC 5V from USB<br>DC3.7V from battery                                                                                                                                                                               |
| <b>Evaluation applied:</b>            | <input type="checkbox"/> MPE Evaluation<br><input checked="" type="checkbox"/> SAR Evaluation                                                                                                                       |

### 3. Test Requirement

#### SAR Evaluation

According to 447498 D01 V06, systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at *test separation distances*  $\leq 50$  mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot$

$[\sqrt{f_{(\text{GHz})}}] \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR,<sup>24</sup> where

- $f_{(\text{GHz})}$  is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation<sup>25</sup>
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

The test exclusions are applicable only when the minimum *test separation distance* is  $\leq 50$  mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum *test separation distance* is  $< 5$  mm, a distance of 5 mm according to 5) in section 4.1 is applied to determine SAR test exclusion.

Routine SAR evaluation refers to that specifically required by § 2.1093, using measurements or computer simulation. When routine SAR evaluation is not required, portable transmitters with output power greater than the applicable low threshold require SAR evaluation to qualify for TCB approval. One antenna is available for the EUT. The minimum separation distance is 5mm.

## 4. Measurement Result

Antenna gain: -0.05 dBi

| Transmit Frequency (MHz) | Mode      | Measured Power (dBm) | Tune up Power (dBm) | Max tune up power (dBm) | Calculation Result | Calculation threshold(1-g SAR) |
|--------------------------|-----------|----------------------|---------------------|-------------------------|--------------------|--------------------------------|
| 2402                     | GFSK      | -9.21                | -9±1                | -8                      | 0.0491             | 3                              |
| 2441                     | GFSK      | -12.32               | -12±1               | -11                     | 0.0248             | 3                              |
| 2480                     | GFSK      | -11.79               | -11±1               | -10                     | 0.0315             | 3                              |
| 2402                     | Π/4-DQPSK | -8.79                | -8±1                | -7                      | 0.0618             | 3                              |
| 2441                     | Π/4-DQPSK | -11.60               | -11±1               | -10                     | 0.0312             | 3                              |
| 2480                     | Π/4-DQPSK | -11.64               | -11±1               | -10                     | 0.0315             | 3                              |
| 2402                     | 8DPSK     | -8.94                | -8±1                | -7                      | 0.0618             | 3                              |
| 2441                     | 8DPSK     | -12.09               | -12±1               | -11                     | 0.0248             | 3                              |
| 2480                     | 8DPSK     | -11.83               | -11±1               | -10                     | 0.0315             | 3                              |

According to KDB 447498 D01 V06, no stand-alone required for BT antenna, and no simultaneous SAR measurement is required.

\*\*\* End of Report \*\*\*