

Test report

275499-4TRFWL

Date of issue: April 24, 2015

Applicant:

Helium Systems, Inc.

Product:

RF module

Model:

ATOM-AM

FCC ID: IC Registration number:

2ADMK-1 12590A-1

Specifications:

• FCC 47 CFR Part 15 Subpart C, §15.247

Operation in the 902-928 MHz, 2400-2483.5 MHz, 5725-5850 MHz

RSS-210, Issue 8, December 2010, Annex 8

Frequency Hopping and Digital Modulation Systems Operating in the 902–928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz Bands





Test location

Company name:	Nemko Canada Inc.
Address:	303 River Road
City:	Ottawa
Province:	Ontario
Postal code:	K1V 1H2
Country:	Canada
Telephone:	+1 613 737 9680
Facsimile:	+1 613 737 9691
Toll free:	+1 800 563 6336
Website:	www.nemko.com
Site number:	FCC: 176392; IC: 2040A-4 (3 m semi anechoic chamber)

Tested by:	Kevin Rose, Wireless/EMC Specialist	
Reviewed by:	Andrey Adelberg, Senior Wireless/EMC Specialist	
Date:	April 24, 2015	
Signature:		

Limits of responsibility

Note that the results contained in this report relate only to the items tested and were obtained in the period between the date of initial receipt of samples and the date of issue of the report.

This test report has been completed in accordance with the requirements of ISO/IEC 17025. All results contain in this report are within Nemko Canada's ISO/IEC 17025 accreditation.

Copyright notification

Nemko Canada Inc. authorizes the applicant to reproduce this report provided it is reproduced in its entirety and for use by the company's employees only. Any use which a third party makes of this report, or any reliance on or decisions to be made based on it, are the responsibility of such third parties.

Nemko Canada Inc. accepts no responsibility for damages, if any, suffered by any third party as a result of decisions made or actions based on this report.

© Nemko Canada Inc.



Table of contents

Table of	contents	3
Section 1	1. Report summary	4
1.1	Applicant and manufacturer	4
1.2	Test specifications	4
1.3	Test methods	4
1.4	Statement of compliance	4
1.5	Exclusions	4
1.6	Test report revision history	4
Section 2	2. Summary of test results	5
2.1	FCC Part 15 Subpart C, general requirements test results	5
2.2	FCC Part 15 Subpart C, intentional radiators test results	5
2.3	IC RSS-GEN, Issue 4, test results	5
2.4	IC RSS-210, Issue 8, test results	6
Section 3	3. Equipment under test (EUT) details	7
3.1	Sample information	7
3.2	EUT information	7
3.3	Technical information	7
3.4	Product description and theory of operation	7
3.5	EUT exercise details	7
Section 2	4. Engineering considerations	9
4.1	Modifications incorporated in the EUT	9
4.2	Technical judgment	9
4.3	Deviations from laboratory tests procedures	9
Section 5	5. Test conditions	10
5.1	Atmospheric conditions	10
5.2	Power supply range	10
Section 6	6. Measurement uncertainty	11
6.1	Uncertainty of measurement	11
Section 7	7. Test equipment	12
7.1	Test equipment list	
Section 8	8. Testing data	13
8.1	FCC 15.207(a) and RSS-Gen 8.8 AC power line conducted emissions limits	13
8.2	FCC 15.247(a)(2) and RSS-210 A8.2(a) Minimum 6 dB bandwidth for systems using digital modulation techniques	16
8.3	RSS-Gen 6.6 Occupied bandwidth	18
8.4	FCC 15.247(b) and RSS-210 A8.4 (4) Transmitter output power and e.i.r.p. requirements	20
8.5	FCC 15.247(d) and RSS-210 A8.5 Spurious (out-of-band) emissions	22
8.6	FCC 15.247(e) and RSS-210 A8.2(b) Power spectral density for digitally modulated devices	29
Section 9	9. Block diagrams of test set-ups	31
9.1	Radiated emissions set-up	31
9.2	Conducted emissions set-up	31



Section 1. Report summary

1.1 Applicant and manufacturer

Company name:	Helium Systems, Inc.
Address:	717 Market St. #100
City:	San Francisco
Province/State:	CA
Postal/Zip code:	94013
Country:	USA

1.2 Test specifications

FCC 47 CFR Part 15, Subpart C, Clause 15.247	Operation in the 902–928 MHz, 2400–2483.5 MHz, 5725–5850 MHz
RSS-210. Issue 8 Annex 8	Frequency Hopping and Digital Modulation Systems Operating in the 902–928 MHz, 2400–2483.5 MHz,
133-210, 133ue 8 Affilex 8	and 5725–5850 MHz Bands

1.3 Test methods

558074 D01 Meas Guidance v03r02 (June 5, 2014)	Guidance for compliance measurements on DTS operating under 15.247
ANSI C63.10:2013	American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices

1.4 Statement of compliance

In the configuration tested, the EUT was found compliant.

Testing was completed against all relevant requirements of the test standard. Results obtained indicate that the product under test complies in full with the requirements tested. The test results relate only to the items tested.

See "Summary of test results" for full details.

1.5 Exclusions

None

1.6 Test report revision history

Revision #	Details of changes made to test report
TRF	Original report issued



Section 2. Summary of test results

2.1 FCC Part 15 Subpart C, general requirements test results

Part	Test description	Verdict
§15.207(a)	Conducted limits	Pass
§15.31(e)	Variation of power source	Pass ¹
§15.203	Antenna requirement	Pass ²

Notes: ¹ Measurements of the variation of the input power or the radiated signal level of the fundamental frequency component of the emission, as appropriate, was performed with the supply voltage varied between 85 % and 115 % of the nominal rated supply voltage. ² The Antennas are located within the enclosure of EUT and not user accessible.

2.2 FCC Part 15 Subpart C, intentional radiators test results

Part	Test description	Verdict
§15.247(a)(1)(i)	Frequency hopping systems operating in the 902–928 MHz band	Not applicable
§15.247(a)(1)(ii)	Frequency hopping systems operating in the 5725–5850 MHz band Not applic	
§15.247(a)(1)(iii)	Frequency hopping systems operating in the 2400–2483.5 MHz band	Not applicable
§15.247(a)(2)	Minimum 6 dB bandwidth for systems using digital modulation techniques	Pass
§15.247(b)(1)	Maximum peak output power of frequency hopping systems operating in the 2400–2483.5 MHz band and 5725–5850 MHz band	Not applicable
§15.247(b)(2)	Maximum peak output power of Frequency hopping systems operating in the 902–928 MHz band	Not applicable
§15.247(b)(3)	Maximum peak output power of systems using digital modulation in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands	Pass
§15.247(b)(4)	Maximum peak output power	Pass
§15.247(c)(1)	Fixed point-to-point operation with directional antenna gains greater than 6 dBi	Not applicable
§15.247(c)(2)	Transmitters operating in the 2400–2483.5 MHz band that emit multiple directional beams	Not applicable
§15.247(d)	Spurious emissions	Pass
§15.247(e)	Power spectral density for digitally modulated devices	Pass
§15.247(f)	Time of occupancy for hybrid systems	Not applicable

2.3 IC RSS-GEN, Issue 4, test results

Part	Test description	Verdict
6.6	Occupied bandwidth	Pass
6.11	Transmitter frequency stability	Not applicable
7.1.2	Receiver spurious emissions limits (radiated)	Not applicable
7.1.3	Receiver spurious emissions limits (antenna conducted)	Not applicable
8.8	AC power lines conducted emission limits	Pass

Notes: ¹ According to Notice 2012-DRS0126 (from January 2012) section 2.2 of RSS-Gen, Issue 3 has been revised. The EUT does not have a stand-alone receiver neither scanner receiver, therefore exempt from receiver requirements.



2.4 IC RSS-210, Issue 8, test results

Part	Test description	Verdict
A8.1	Frequency hopping systems	
A8.1 (a)	Bandwidth of a frequency hopping channel	Not applicable
A8.1 (b)	Minimum channel spacing for frequency hopping systems	Not applicable
A8.1 (c)	Frequency hopping systems operating in the 902–928 MHz band	Not applicable
A8.1 (d)	Frequency hopping systems operating in the 2400–2483.5 MHz band	Not applicable
A8.1 (e)	Frequency hopping systems operating in the 5725–5850 MHz band	Not applicable
A8.2	Digital modulation systems	
A8.2 (a)	Minimum 6 dB bandwidth	Pass
A8.2 (b)	Maximum power spectral density	Pass
A8.3	Hybrid systems	
A8.3 (1)	Digital modulation turned off	Not applicable
A8.3 (2)	Frequency hopping turned off	Not applicable
A8.4	Transmitter output power and e.i.r.p. requirements	
A8.4 (1)	Frequency hopping systems operating in the 902–928 MHz band	Not applicable
A8.4 (2)	Frequency hopping systems operating in the 2400–2483.5 MHz band	Not applicable
A8.4 (3)	Frequency hopping systems operating in the 5725–5850 MHz	Not applicable
A8.4 (4)	Systems employing digital modulation techniques	Pass
A8.4 (5)	Point-to-point systems in 2400–2483.5 MHz and 5725–5850 MHz band	Not applicable
A8.4 (6)	Transmitters which operate in the 2400–2483.5 MHz band with multiple directional beams	Not applicable
A8.5	Out-of-band emissions	Pass

Notes: None



Section 3. Equipment under test (EUT) details

3.1 Sample information

Receipt date	December 10, 2014
Nemko sample ID number	2

3.2 EUT information

Product name	RF module
Model	ATOM-AM
Serial number	Proto1

3.3 Technical information

Company number:	12590A
Model number:	ATOM-AM
Manufacturer:	Helium Systems, Inc.
Tested to Radio Standards Specification:	RSS210
Open Area Test Site Industry Canada #:	2040A
Frequency Min (MHz)	2.405 GHz
Frequency Max (MHz)	2.480 GHz
RF power in Watts: max	0.0255
Field strength (at what distance):	N/A
Occupied bandwidth (99 % BW):	2.405 MHz
Type of modulation:	O-QPSK-250
Emission designator (TRC-43):	W7D
Transmitter spurious (worst case):	4810 MHz 53.78 dBμV/m @ 3 meters
Power requirements	3.3 VDC via USB cable to a host computer
	Johanson Technology Inc 2450AT18B100 0.5 dBi chip antenna and
Antenna information	Mobile Mark PSKN3-2400S 2.3 dBi external whip.
	The EUT uses a unique antenna coupling/ non-detachable antenna to the intentional radiator.

3.4 Product description and theory of operation

Dual Band RF Module

3.5 EUT exercise details

Operational Firmware allows the EUT to put into several different test modes to include options for Tx power, channels and antenna choice. The firmware will give feedback to the operator via a standard serial interface displayed within a terminal program (ie. Hyper terminal, simple term, TeraTerm, etc.). The module under test is a board that is mounted onto the carrier board that provides the virtual Comm port connection via the USB cable connection.



Table 3.5-1: EUT sub assemblies

Description	Brand name	Model/Part number	Serial number	Rev.
EUT (mounted on carrier board)	Atom	ATOM-AM	Proto1	1

Table 3.5-2: EUT interface ports

_ Description	Qty.
USB Connector (on interface board)	1

Table 3.5-3: Support equipment

Description	Brand name	Model/Part number	Serial number	Rev.
SMA to U.FL Adaptor Cable	TE	2032440-1	NA	NA
2.4GHz External Antenna	Mobile Mark	PSKN3-2400S	NA	NA
subGhz External Antenna	Mobile Mark	PSKN3-700/2100S	NA	NA
USB Interface Board	CMD	USB2UART	NA	1

Table 3.5-4: Inter-connection cables

Cable description	From	То	Length (m)
USB Cable	Type A	mini	2
F/F Jumper Wire	Female Plug	Female Plug	.125




Figure 3.5-1: Setup diagram



Section 4. Engineering considerations

4.1 Modifications incorporated in the EUT

There were no modifications performed to the EUT during this assessment.

4.2 Technical judgment

None

4.3 Deviations from laboratory tests procedures

No deviations were made from laboratory procedures.



Section 5. Test conditions

5.1 Atmospheric conditions

Temperature	15–30 °C
Relative humidity	20–75 %
Air pressure	860–1060 mbar

When it is impracticable to carry out tests under these conditions, a note to this effect stating the ambient temperature and relative humidity during the tests shall be recorded and stated.

5.2 Power supply range

The normal test voltage for equipment to be connected to the mains shall be the nominal mains voltage. For the purpose of the present document, the nominal voltage shall be the declared voltage, or any of the declared voltages ±5 %, for which the equipment was designed.



Section 6. Measurement uncertainty

6.1 Uncertainty of measurement

Measurement uncertainty budgets for the tests are detailed below. Measurement uncertainty calculations assume a coverage factor of K = 2 with 95% certainty.

Test name	Measurement uncertainty, dB
All antenna port measurements	0.55
Conducted spurious emissions	1.13
Radiated spurious emissions	3.78
AC power line conducted emissions	3.55



Section 7. Test equipment

7.1 Test equipment list

Table 7.1-1: Equipment list

Equipment	Manufacturer	Model no.	Asset no.	Cal cycle	Next cal.
3 m EMI test chamber	TDK	SAC-3	FA002047	1 year	Mar. 18/15
Flush mount turntable	Sunol	FM2022	FA002082	_	NCR
Controller	Sunol	SC104V	FA002060	_	NCR
Antenna mast	Sunol	TLT2	FA002061	_	NCR
Receiver/spectrum analyzer	Rohde & Schwarz	ESU 26	FA002043	1 year	Jan. 07/16
Spectrum analyzer	Rohde & Schwarz	FSU	FA001877	1 year	Jan. 27/15
Bilog antenna (20–3000 MHz)	Sunol	JB3	FA002108	1 year	Mar. 12/15
Horn antenna (1–18 GHz)	EMCO	3115	FA000825	1 year	Mar. 10/15
Pre-amplifier (1–18 GHz)	JCA	JCA118-503	FA002091	1 year	June 23/15
50 Ω coax cable	C.C.A.	None	FA002555	1 year	June 23/15
50 Ω coax cable	Huber + Suhner	None	FA002074	1 year	June 23/15
Horn antenna 18–26.5 GHz	Electro-metrics	SH-50/60-1	FA000479	_	VOU
18–26 GHz pre-amplifier	Narda	BBS-1826N612	FA001550	_	VOU
LISN	Rohde & Schwarz	ENV216	FA002023	1 year	Dec. 28/14

Note: NCR - no calibration required, VOU - verify on use



Section 8. Testing data

8.1 FCC 15.207(a) and RSS-Gen 8.8 AC power line conducted emissions limits

8.1.1 Definitions and limits

FCC:

Except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a $50 \,\mu\text{H}/50 \,\Omega$ line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequency ranges.

IC:

The purpose of this test is to measure unwanted radio frequency currents induced in any AC conductor external to the equipment which could conduct interference to other equipment via the AC electrical network.

Except when the requirements applicable to a given device state otherwise, for any licence-exempt radiocommunication device equipped to operate from the public utility AC power supply, either directly or indirectly, the radio frequency voltage that is conducted back onto the AC power lines in the frequency range of 0.15 MHz to 30 MHz shall not exceed the limits shown in Table 2. The tighter limit applies at the frequency range boundaries.

The conducted emissions shall be measured with a 50 $\Omega/50~\mu H$ line impedance stabilization network (LISN).

Table 8.1-1: Conducted emissions limit

Frequency of emission,	Condu	ucted limit, dBμV
MHz	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5–5	56	46
5–30	60	50

Note: * - Decreases with the logarithm of the frequency.

8.1.2 Test summary

Test date:	December 17, 2014	Temperature:	23 °C
Test engineer:	Kevin Rose	Air pressure:	1002 mbar
Verdict:	Pass	Relative humidity:	34 %

Section 8 Testing data

Test name FCC 15.207(a) and RSS-Gen 8.8 AC power line conducted emissions limits **Specification** FCC Part 15 Subpart C and RSS-Gen, Issue 4



8.1.3 Observations, settings and special notes

The EUT was set up as tabletop configuration.

The spectral scan has been corrected with transducer factors (i.e. cable loss, LISN factors, and attenuators) for determination of compliance.

A preview measurement was generated with the receiver in continuous scan mode. Emissions detected within 6 dB or above limit were re-measured with the appropriate detector against the correlating limit and recorded as the final measurement.

Receiver settings for preview measurements:


Resolution bandwidth:	9 kHz
Video bandwidth:	30 kHz
Detector mode:	Peak and Average
Trace mode:	Max Hold
Measurement time:	1000 ms

Receiver settings for final measurements:


Resolution bandwidth:	9 kHz
Video bandwidth:	30 kHz
Detector mode:	Quasi-Peak and Average
Trace mode:	Max Hold
Measurement time:	1000 ms



8.1.4 Test data



Plot 8.1-1: Conducted emissions on phase line



Plot 8.1-2: Conducted emissions on neutral line

Section 8 Testing data

Test name FCC 15.247(a)(2) and RSS-210 A8.2(a) Minimum 6 dB bandwidth for systems using digital

modulation techniques

Specification FCC 15 Subpart C and RSS-210, Issue 8



8.2 FCC 15.247(a)(2) and RSS-210 A8.2(a) Minimum 6 dB bandwidth for systems using digital modulation techniques

8.2.1 Definitions and limits

FCC and IC:

- (a) Operation under the provisions of this Section is limited to frequency hopping and digitally modulated intentional radiators that comply with the following provisions:
 - (2) Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

8.2.2 Test summary

Test date:	December 17, 2014	Temperature:	25 °C
Test engineer:	Kevin Rose	Air pressure:	1010 mbar
Verdict:	Pass	Relative humidity:	28 %

8.2.3 Observations, settings and special notes

Spectrum analyser settings:

Resolution bandwidth:	100 kHz
Video bandwidth:	≥3 × RBW
Detector mode:	Peak
Trace mode:	Max Hold

8.2.4 Test data

Table 8.2-1: 6 dB bandwidth results

Frequency, MHz	6 dB bandwidth, MHz	Limit, MHz	Margin, MHz
2405	1.32	0.50	0.82
2445	1.44	0.50	0.94
2480	1.64	0.50	1.14

Section 8 Testing data


Test name FCC 15.247(a)(2) and RSS-210 A8.2(a) Minimum 6 dB bandwidth for systems using digital

modulation techniques

Specification FCC 15 Subpart C and RSS-210, Issue 8



8.2.4 Test data, continued



Date: 28.JAN.2015 15:19:17

Figure 8.2-1: 6 dB bandwidth sample



8.3 RSS-Gen 6.6 Occupied bandwidth

8.3.1 Definitions and limits

When an occupied bandwidth value is not specified in the applicable RSS, the transmitted signal bandwidth to be reported is to be its 99 percent emission bandwidth, as calculated or measured.

The transmitter shall be operated at its maximum carrier power measured under normal test conditions.

The span of the analyzer shall be set to capture all products of the modulation process, including the emission skirts. The resolution bandwidth shall be set to as close to 1 percent of the selected span as is possible without being below 1 percent. The video bandwidth shall be set to 3 times the resolution bandwidth. Video averaging is not permitted. Where practical, a sampling detector shall be used since a peak or, peak hold, may produce a wider bandwidth than actual.

The trace data points are recovered and are directly summed in linear terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5 percent of the total is reached and that frequency recorded. The process is repeated for the highest frequency data points. This frequency is recorded.

The span between the two recorded frequencies is the occupied bandwidth.

8.3.2 Test summary

Test date:	December 17, 2014	Temperature:	22 °C
Test engineer:	Kevin Rose	Air pressure:	1003 mbar
Verdict:	Pass	Relative humidity:	34 %

8.3.3 Observations, settings and special notes

Spectrum analyser settings:


Resolution bandwidth:	≥1 % of span
Video bandwidth:	≥3 × RBW
Detector mode:	Peak
Trace mode:	Max Hold

8.3.4 Test data

Table 8.3-1: 99 % bandwidth results

Modulation	99 % bandwidth, MHz
2405	2.405
2445	2.346
2480	2.262

8.3.4 Test data, continued



Date: 11.FEB.2015 18:08:05

Figure 8.3-1: 99% bandwidth sample

FCC 15.247(b) and RSS-210 A8.4 (4) Transmitter output power and e.i.r.p. requirements

FCC Part 15 Subpart C and RSS-210, Issue 8



8.4 FCC 15.247(b) and RSS-210 A8.4 (4) Transmitter output power and e.i.r.p. requirements

8.4.1 Definitions and limits

FCC:

- (b) The maximum peak conducted output power of the intentional radiator shall not exceed the following:
 - (3) For systems using digital modulation in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands: 1 W (30 dBm). As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.
 - (4) The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.
 - (i) Systems operating in the 2400–2483.5 MHz band that are used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6 dBi provided the maximum peak output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.

Fixed, point-to-point operation, as used in paragraphs (b)(3)(i) and (b)(3)(ii) of this section, excludes the use of point-to-multipoint systems, omnidirectional applications, and multiple co-located intentional radiators transmitting the same information. The operator of the spread spectrum intentional radiator or, if the equipment is professionally installed, the installer is responsible for ensuring that the system is used exclusively for fixed, point-to-point operations. The instruction manual furnished with the intentional radiator shall contain language in the installation instructions informing the operator and the installer of this responsibility.

- (c) Operation with directional antenna gains greater than 6 dBi.
 - (2) In addition to the provisions in paragraphs (b)(1), (b)(3), (b)(4) and (c)(1)(i) of this section, transmitters operating in the 2400–2483.5 MHz band that emit multiple directional beams, simultaneously or sequentially, for the purpose of directing signals to individual receivers or to groups of receivers provided the emissions comply with the following:
 - (i) Different information must be transmitted to each receiver.
 - (ii) If the transmitter employs an antenna system that emits multiple directional beams but does not do emit multiple directional beams simultaneously, the total output power conducted to the array or arrays that comprise the device, i.e., the sum of the power supplied to all antennas, antenna elements, staves, etc. and summed across all carriers or frequency channels, shall not exceed the limit specified in paragraph (b)(1) or (b)(3) of this section, as applicable. However, the total conducted output power shall be reduced by 1 dB below the specified limits for each 3 dB that the directional gain of the antenna/antenna array exceeds 6 dBi. The directional antenna gain shall be computed as follows:
 - (A) The directional gain shall be calculated as the sum of 10 log (number of array elements or staves) plus the directional gain of the element or stave having the highest gain.

IC:

A8.4 (4) Transmitter Output Power and e.i.r.p. Requirements for systems employing digital modulation techniques operating in the bands 902–928 MHz, 2400–2483.5 MHz and 5725–5850 MHz bands

For systems employing digital modulation techniques operating in the bands 902–928 MHz, 2400–2483.5 MHz and 5725–5850 MHz, the maximum peak conducted output power shall not exceed 1 W. Except as provided in Section A8.4(5), the e.i.r.p. shall not exceed 4 W.

As an alternative to a peak power measurement, compliance can be based on a measurement of the maximum conducted output power (see RSS-Gen).

8.4.2 Test summary

Test date:	December 17, 2014	Temperature:	22 °C
Test engineer:	Kevin Rose	Air pressure:	1003 mbar
Verdict:	Pass	Relative humidity:	34 %

Section 8

Test name

Testing data

FCC 15.247(b) and RSS-210 A8.4 (4) Transmitter output power and e.i.r.p. requirements

Specification FCC Part 15 Subpart C and RSS-210, Issue 8



8.4.3 Observations, settings and special notes

The test was performed according to DTS guidelines section 9.2.3.1: maximum conducted (average) output power

8.4.4 Test data

Table 8.4-1: Output power measurements results Antenna 1

Frequency,	Conducted output power, dBm		Manain dD	Antenna gain,	EIRP,	EIRP limit,	FIDD manning dD
MHz	Measured	Limit	Margin, dB	dBi	dBm	dBm	EIRP margin, dB
2405	13.82	30	16.18	0.5	14.32	36	21.68
2445	14.07	30	15.93	0.5	14.57	36	21.43
2480	1.52	30	28.48	0.5	2.02	36	33.98

Table 8.4-2: Output power measurements results Antenna 2

Frequency,	Conducted output power, dBm		Maurin dD	Antenna gain,	EIRP,	EIRP limit,	FIDD manning dD
MHz	Measured	Limit	Margin, dB	dBi	dBm	dBm	EIRP margin, dB
2405	13.82	30	16.18	2.3	16.12	36	19.88
2445	14.07	30	15.93	2.3	16.37	36	19.63
2480	1.52	30	28.48	2.3	3.82	36	32.18



8.5 FCC 15.247(d) and RSS-210 A8.5 Spurious (out-of-band) emissions

8.5.1 Definitions and limits

FCC:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

IC:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the radio frequency power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under Section A8.4(4), the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Tables 2 and 3 is not required.

Table 8.5-1: FCC §15.209 and RSS-Gen - Radiated emission limits

Frequency,	Field stren	gth of emissions	Measurement distance, m
MHz	μV/m	dBμV/m	
0.009-0.490	2400/F	$67.6 - 20 \times \log_{10}(F)$	300
0.490-1.705	24000/F	$87.6 - 20 \times \log_{10}(F)$	30
1.705-30.0	30	29.5	30
30–88	100	40.0	3
88–216	150	43.5	3
216–960	200	46.0	3
above 960	500	54.0	3

Notes: In the emission table above, the tighter limit applies at the band edges.

For frequencies above 1 GHz the limit on peak RF emissions is 20 dB above the maximum permitted average emission limit applicable to the equipment under test

Table 8.5-2: IC restricted frequency bands

MHz	MHz	MHz	GHz
0.090-0.110	12.51975-12.52025	399.9–410	5.35-5.46
2.1735-2.1905	12.57675-12.57725	608-614	7.25–7.75
3.020-3.026	13.36-13.41	960–1427	8.025–8.5
4.125-4.128	16.42-16.423	1435-1626.5	9.0-9.2
4.17725-4.17775	16.69475-16.69525	1645.5-1646.5	9.3–9.5
4.20725-4.20775	16.80425-16.80475	1660-1710	10.6-12.7
5.677-5.683	25.5–25.67	1718.8-1722.2	13.25-13.4
6.215-6.218	37.5–38.25	2200–2300	14.47-14.5
6.26775-6.26825	73–74.6	2310–2390	15.35–16.2
6.31175-6.31225	74.8–75.2	2655–2900	17.7-21.4
8.291-8.294	108-138	3260–3267	22.01-23.12
8.362-8.366	156.52475-156.52525	3332–3339	23.6-24.0
8.37625-8.38675	156.7–156.9	3345.8–3358	31.2-31.8
8.41425-8.41475	240–285	3500-4400	36.43-36.5
12.29-12.293	322-335.4	4500-5150	Above 38.6

Note: Certain frequency bands listed in Table 8.5-2 and above 38.6 GHz are designated for low-power licence-exempt applications. These frequency bands and the requirements that apply to the devices are set out in this Standard

Section 8 Testing data

Test name FCC 15.247(d) and RSS-210 A8.5 Spurious (out-of-band) emissions

Specification FCC Part 15 Subpart C and RSS-210, Issue 8



8.5.1 Definitions and limits, continued

Table 8.5-3: FCC restricted frequency bands

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9–410	4.5–5.15
0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25–7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5–38.25	1435–1626.5	9.0–9.2
4.20725-4.20775	73–74.6	1645.5-1646.5	9.3–9.5
6.215-6.218	74.8–75.2	1660–1710	10.6–12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175–6.31225	123–138	2200–2300	14.47–14.5
8.291-8.294	149.9-150.05	2310-2390	15.35–16.2
8.362-8.366	156.52475-156.52525	2483.5–2500	17.7–21.4
8.37625-8.38675	156.7-156.9	2690–2900	22.01–23.12
8.41425-8.41475	162.0125-167.17	3260–3267	23.6-24.0
12.29-12.293	167.72-173.2	3332–3339	31.2-31.8
12.51975-12.52025	240–285	3345.8–3358	36.43–36.5
12.57675-12.57725	322-335.4	3600-4400	Above 38.6
13.36–13.41			

8.5.2 Test summary

Test date:	December 17, 2014	Temperature:	22 °C
Test engineer:	Kevin Rose	Air pressure:	1003 mbar
Verdict:	Pass	Relative humidity:	34 %

Section 8 Testing data

Test name FCC 15.247(d) and RSS-210 A8.5 Spurious (out-of-band) emissions

Specification FCC Part 15 Subpart C and RSS-210, Issue 8



8.5.3 Observations, settings and special notes

The spectrum was searched from 30 MHz to the 10th harmonic.

EUT was set to transmit with 100 % duty cycle.

Since fundamental power was tested using average method, the spurious emissions limit is $-30~\mathrm{dBc/100~kHz}$

Spectrum analyser settings for radiated measurements within restricted bands below 1 GHz:

Resolution bandwidth:	100 kHz
Video bandwidth:	300 kHz
Detector mode:	Peak
Trace mode:	Max Hold

Spectrum analyser settings for peak radiated measurements within restricted bands above 1 GHz:

Resolution bandwidth:	1 MHz
Video bandwidth:	3 MHz
Detector mode:	Peak
Trace mode:	Max Hold

Spectrum analyser settings for average radiated measurements within restricted bands above 1 GHz:

Resolution bandwidth:	1 MHz
Video bandwidth:	10 Hz
Detector mode:	Peak
Trace mode:	Max Hold

Spectrum analyser settings for conducted spurious emissions measurements:

Resolution bandwidth:	100 kHz
Video bandwidth:	300 kHz
Detector mode:	Peak
Trace mode:	Max Hold



8.5.4 Test data

Table 8.5-4: Radiated field strength measurement Peak results for Antenna 1

Channel	Frequency,	Peak Field strength, dBμV/m		Margin,
Chamie	MHz	Measured	Limit	dB
Low	2390	59.75	74	14.25
Low	4810	63.13	74	10.87
Mid	4889	60.53	74	13.47
Mid	7333	63.74	74	10.26
Low	7213	60.34	74	13.66
High	2483.5	67.50	74	1.58

Notes: Field strength includes correction factor of antenna, cable loss, amplifier, and attenuators where applicable.

Table 8.5-5: Radiated field strength measurement Peak results for Antenna 2

Channel	Frequency,	ency, Peak Field strength, dBμV/m		Margin,
Chamiei	MHz	Measured	Limit	dB
Low	2390	49.32	74	24.68
Low	4810	63.42	74	10.58
Mid	4889	61.39	74	12.61
Mid	7333	62.35	74	10.26
Low	7213	61.82	74	13.66
High	2483.5	59.97	74	14.03

Notes: Field strength includes correction factor of antenna, cable loss, amplifier, and attenuators where applicable.

Table 8.5-6: Radiated field strength measurement Average results for Antenna 1

Channel	Frequency,	Calculated Average Field strength, dBμV/m		Margin,
Chamie	MHz	Measured	Limit	dB
Low	2390	49.99	54	4.01
Low	4810	53.37	54	0.63
Mid	4889	50.77	54	3.23
Mid	7333	53.98	54	0.02
Low	7213	50.58	54	3.42
High	2483.5	53.12	54	0.88

Notes: Field strength includes correction factor of antenna, cable loss, amplifier, and attenuators where applicable.

Calculated Average Field strength is the Peak field Strength –duty cycle correction factor. 9.76 dB for all channels and 14.38 dB for High channel

Table 8.5-7: Radiated field strength measurement Average results for Antenna 2

Channel	Frequency,	Calculated Average Field strength, dBμV/m		Margin,
Chamer	MHz	Measured	Limit	dB
Low	2390	39.56	54	14.44
Low	4810	53.66	54	0.34
Mid	4889	51.63	54	2.37
Mid	7333	52.59	54	1.41
Low	7213	52.06	54	1.94
High	2483.5	45.59	54	8.41

Notes: Field strength includes correction factor of antenna, cable loss, amplifier, and attenuators where applicable.

Calculated Average Field strength is the Peak field Strength –duty cycle correction factor. 9.76 dB for all channels and 14.38 dB for High channel

only

only

Section 8 Testing data

Test name FCC 15.247(d) and RSS-210 A8.5 Spurious (out-of-band) emissions

Specification FCC Part 15 Subpart C and RSS-210, Issue 8



Table 8.5-8: Duty Cycle Correction factor for all channels, except for the upper

Pulse width, ms	Number of pulses	On time within 100 ms, ms	Duty Cycle correction, dB
32.50	1	32.50	9.76

Note: Duty Cycle Correction = 20 Log₁₀ (on time / 100 ms)

Table 8.5-9: Duty Cycle Correction factor only for upper channel (2.480 GHz)

Pulse width, ms	Number of pulses	On time within 100 ms, ms	Duty Cycle correction, dB
19.10	1	19.10	14.38

Note: Duty Cycle Correction = 20 Log₁₀ (on time / 100 ms)




Figure 8.5-1: Duty Cycle Correction 32.5ms pulse

Figure 8.5-2: Duty Cycle Correction 19.1ms pulse





8.5.4 Test data, continued





Figure 8.5-3: Conducted spurious emissions for, low channel

Figure 8.5-4: Conducted spurious emissions for Mid channel





Date: 11.FEB.2015 18:04:11

Figure 8.5-5: Conducted spurious emissions for High channel

Specification FCC Part 15 Subpart C and RSS-210, Issue 8







Date: 28.JAN.2015 15:00:32

Date: 11.FEB.2015 18:01:29

Figure 8.5-6: Conducted spurious emissions for, low edge channel

Figure 8.5-7: Conducted spurious emissions for high edge channel

FCC Clause 15.247(e) and RSS-210 A8.2(b) Power spectral density for digitally modulated devices

FCC Part 15 Subpart C and RSS-210, Issue 8



8.6 FCC 15.247(e) and RSS-210 A8.2(b) Power spectral density for digitally modulated devices

8.6.1 Definitions and limits

FCC:

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

IC:

The transmitter power spectral density conducted from the transmitter to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission or over 1.0 second if the transmission exceeds 1.0-second duration. This power spectral density shall be determined in accordance with the provisions of Section A8.4(4); (i.e. the power spectral density shall be determined using the same method for determining the conducted output power).

8.6.2 Test summary

Test date:	December 17, 2014	Temperature:	22 °C
Test engineer:	Kevin Rose	Air pressure:	1003 mbar
Verdict:	Pass	Relative humidity:	34 %

8.6.3 Observations, settings and special notes

The test was performed using method described in section 10.3 Option 2 of the 558074 D01 DTS Meas Guidance v03r02. Spectrum analyser settings:

Resolution bandwidth:	3 kHz
Video bandwidth:	VBW ≥ 3 x RBW.
Frequency span:	1.5 times the OBW.
Detector mode:	RMS
Trace mode:	Power average
Averaging sweeps number:	100




8.6.4 Test data

Table 8.6-1: PSD measurements

Frequency, MHz	PSD, dBm/3 kHz	PSD limit, dBm/3 kHz	Margin, dB
2405	-10.54	8.00	18.54
2445	-9.37	8.00	17.37
2480	-18.02	8.00	26.02

8.6.4 Test data, continued




Date: 17.DEC.2014 16:59:22

Figure 8.6-1: PSD sample plot



Section 9. Block diagrams of test set-ups

9.1 Radiated emissions set-up



9.2 Conducted emissions set-up

