

Shenzhen CTL Testing Technology Co., Ltd. Tel: +86-755-89486194 Fax: +86-755-26636041

Lowy Chi

FCC PART 15 SUBPART C & RSS-210 TEST REPORT

Report Reference No...... CTL1410272589-WF02

Compiled by

(position+printed name+signature)... File administrators Jacky Chen

Name of the organization performing

the tests

Test Engineer Tracy Qi

(position+printed name+signature)..:

Approved by

(position+printed name+signature)... Manager Tracy Qi

Date of issue..... Nov. 26, 2014

Shenzhen CTL Testing Technology Co., Ltd. Test Firm....:

Floor 1-A, Baisha Technology Park, No. 3011, Shahexi Road, Address.....

Nanshan, Shenzhen 518055 China.

Applicant's name..... Shenzhen Valuelink Technology Co.,LTD

No.2 Road #2, Yangtze Riverside, Henggang Street, Longgang Address....:

District, Shenzhen City, Guangdong Province, China

Test specification:

FCC Part 15.249: Operation within the bands 920-928 MHz, 2400-Standard

2483.5 MHz, 5725-5850 MHz and 24.0 - 24.25 GHz.

RSS-210 Issue 8 (2010): Licence-exempt Radio Apparatus (All

Frequency Bands): Category I Equipment

TRF Originator..... Shenzhen CTL Testing Technology Co., Ltd.

Master TRF...... Dated 2011-01

Shenzhen CTL Testing Technology Co., Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen CTL Testing Technology Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen CTL Testing Technology Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Test item description: Bluetooth 4.0 Headset

Trade Mark: OXA Models/Type reference....: OXA

Modulation GFSK

Work Frequency...... 2402 MHz~2480 MHz

Antenna Type..... internal

FCC ID 2ADMT-OXA

IC: 12523A-OXA

Result..... Positive

V1.0

Page 2 of 51

TEST REPORT

Test Report No. :	CTL1410272589-WF02	Nov. 26, 2014
rest Keport No	C1L1410212303-W1 02	Date of issue

Equipment under Test : Bluetooth 4.0 Headset

Model /Type : OXA

Applicant : Shenzhen Valuelink Technology Co.,LTD

Address : No.2 Road #2, Yangtze Riverside, Henggang Street,

Longgang District, Shenzhen City, Guangdong Province,

Report No.: CTL1410272589-WF02

China

Manufacturer Shenzhen Valuelink Technology Co.,LTD

Address No.2 Road #2, Yangtze Riverside, Henggang Street,

Longgang District, Shenzhen City, Guangdong Province,

China

Test Result according to the standards on page 4:	Positive
---	----------

The test report merely corresponds to the test sample. It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

Testing Techno

Report No.: CTL1410272589-WF02

Contents

_Toc404795735

CUMMARY	
SUMMARY	
General Remarks	5
Equipment Under Test	5
Short description of the Equipment under Test (EUT)	5
EUT operation mode	6
EUT configuration	6
Related Submittal(s) / Grant (s)	6
Modifications	6
TEST ENVIRONMENT	7
in to	
Address of the test laboratory	7
Test Facility	7
Environmental conditions	7
Configuration of Tested System	7
Statement of the measurement uncertainty	8
Equipments Used during the Test	9
TEST CONDITIONS AND RESULTS	
Conducted Emissions Test	10
Fundamental Emissions	14
Transmitter Radiated Unwanted Emissions	15
Band Edge Measurement	33
Occupied Bandwidth Measurement	42
	3
	0)
ANTENNA REQUIREMENT	42
0,	
I'll	
TEST SETUP PHOTOS OF THE EUT	4.5
TEST SETUP PROTOS OF THE EUT	
EXTERNAL AND INTERNAL PHOTOS OF THE EU	T 47
EXTERNAL AND INTERNAL PROTOS OF THE EU	<u> </u>

1. TEST STANDARDS

The tests were performed according to following standards:

FCC Rules Part 15.249: Operation within the bands 902 - 928 MHz, 2400 - 2483.5 MHz, 5725 - 5875 MHz, and 24.0 - 24.25 GHz.

ANSI C63.4-2009

RSS-210 Issue 8 (2010): Licence-exempt Radio Apparatus (All Frequency Bands): Category I Equipment



2. SUMMARY

2.1. General Remarks

Date of receipt of test sample : Oct. 28, 2014

Testing commenced on : Oct. 28, 2014

Testing concluded on : Nov. 27, 2014

2.2. Equipment Under Test

Power supply system utilised

Power supply voltage : o 120V / 60 Hz o 115V / 60Hz

o 12 V DC o 24 V DC

Report No.: CTL1410272589-WF02

Other (specified in blank below)

DC 3.7V from battery

2.3. Short description of the Equipment under Test (EUT)

The EUT is a Bluetooth 4.0 Headset work at 2402~2480 MHz support Bluetooth 4.0. Channel List:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
00	2402	20	2442
01	2404	21	2444
02	2406	22	2446
03	2408	23	2448
04	2410	24	2450
05	2412	25	2452
06	2414	26	2454
07	2416	27	2456
08	2418	28	2458
09	2420	29	2460
10	2422	30	2462
11	2424	31	2464
12	2426	32	2466
13	2428	33	2468
14	2430	34	2470
15	2432	35	2472
16	2434	36	2474
17	2436	37	2476
18	2438	38	2478
19	2440	39	2480

Modulation: GFSK

For more details, refer to the user's manual of the EUT.

Serial number: Prototype

V1.0 Page 6 of 51 Report No.: CTL1410272589-WF02

2.4. EUT operation mode

Test Mode(TM)	Description	Remark
TM1	Bottom Channel Transmitting	1
TM2	Middle Channel Transmitting	1
TM3	Top Channel Transmitting	1
TM4	Charging and keeping TX	USB power by PC

The field strength of radiation emission was measured in the following position: EUT stand-up position (Y axis), lie-down position (X, Z axis).

The following data show only with the worst case setup.

The worst case of Y axis was reported.

Based on client request, all normal using modes of the normal function were tested but only the worst test data of the worst mode is reported by this report.

2.5. EUT configuration

The following peripheral devices and interface cables were connected during the measurement:

o - supplied by the manufacturer

supplied by the lab

Notebook PC (FCC DOC approved)

Manufacturer: DELL

Model No.: PP18L

Technolo

2.6. Related Submittal(s) / Grant (s)

This submittal(s) (test report) is intended for FCC ID: 2ADMT-OXA and IC ID: 12523A-OXA filing to comply with Section 15.249 of the FCC Part 15, Subpart C Rules and RSS-210 Rules.

C/Z Testing

2.7. Modifications

No modifications were implemented to meet testing criteria.

3. TEST ENVIRONMENT

3.1. Address of the test laboratory

Shenzhen CTL Testing Technology Co., Ltd. Floor 1-A, Baisha Technology Park, No. 3011, Shahexi Road, Nanshan, Shenzhen 518055 China

There is one 3m semi-anechoic chamber and two line conducted labs for final test. The Test Sites meet the requirements in documents ANSI C63.4 and CISPR 22/EN 55022 requirements.

Report No.: CTL1410272589-WF02

3.2. Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

IC Registration No.: 9618B

The 3m alternate test site of Shenzhen CTL Testing Technology Co., Ltd. EMC Laboratory has been registered by Certification and Engineer Bureau of Industry Canada for the performance of with Registration No.: 9618B on November 13, 2013.

FCC-Registration No.: 970318

Shenzhen CTL Testing Technology Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 970318, December 19, 2013.

3.3. Environmental conditions

During the measurement the er	nvironmental conditions were within the listed ranges:
Temperature:	15-35 ° C
Humidity:	30-60 %
Atmospheric pressure:	950-1050mbar

3.4. Configuration of Tested System

Fig. 2-1 Configuration of Tested System

10	41
EUT	

3.5. Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to CISPR 16 - 4 "Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements" and is documented in the Shenzhen CTL Testing Technology Co., Ltd. quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for CTL laboratory is reported:

Test	Range	Measurement Uncertainty	Notes
Radiated Emission	30~1000MHz	4.10dB	(1)
Radiated Emission	1~26.5GHz	4.32dB	(1)
Conducted Disturbance	0.15~30MHz	3.20dB	(1)

(1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.



3.6. Equipments Used during the Test


Test Equipment	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Due Date
Bilog Antenna	Sunol Sciences Corp.	JB1	A061713	2014/07/12	2015/07/11
EMI Test Receiver	R&S	ESCI	103710	2014/07/10	2015/07/09
Spectrum Analyzer	Agilent	E4407B	MY45108355	2014/07/06	2015/07/05
Controller	EM Electronics	Controller EM 1000	N/A	2014/07/06	2015/07/05
Horn Antenna	Sunol Sciences Corp.	DRH-118	A062013	2014/07/12	2015/07/11
Horn Antenna	SCHWARZBECK	BBHA9170	1562	2014/07/12	2015/07/11
Active Loop Antenna	SCHWARZBECK	FMZB1519	1519-037	2014/07/12	2015/07/11
LISN	R&S	ENV216	101316	2014/07/10	2015/07/09
LISN	SCHWARZBECK	NSLK8127	8127687	2014/07/10	2015/07/09
Microwave Preamplifier	HP to	8349B	3155A00882	2014/07/10	2015/07/09
Amplifier	HP	8447D	3113A07663	2014/07/10	2015/07/09
Transient Limiter	Com-Power	LIT-153	532226	2014/07/10	2015/07/09
Radio Communication Tester	R&S	CMU200	3655A03522	2014/07/06	2015/07/05
Temperature/Humidity Meter	zhicheng	ZC1-2	22522	2014/07/10	2015/07/09
SIGNAL GENERATOR	HP	8647A	3200A00852	2014/07/10	2015/07/09
Wideband Peak Power Meter	Anritsu	ML2495A	220.23.35	2014/07/06	2015/07/05
Climate Chamber	ESPEC	EL-10KA	A20120523	2014/07/06	2015/07/05
High-Pass Filter	K&L	9SH10- 2700/X12750 -O/O	1000	2014/07/06	2015/07/05
High-Pass Filter	K&L 703	41H10- 1375/U12750 -O/O	SCHI	2014/07/06	2015/07/05

V1.0 Page 10 of 51 Report No.: CTL1410272589-WF02

4. TEST CONDITIONS AND RESULTS

4.1. Conducted Emissions Test

TEST CONFIGURATION



TEST PROCEDURE

- 1 The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. The EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.4.
- 2 Support equipment, if needed, was placed as per ANSI C63.4.
- 3 All I/O cables were positioned to simulate typical actual usage as per ANSI C63.4.
- 4 If a EUT received DC power from the USB Port of Notebook PC, the PC's adapter received AC120V/60Hz power through a Line Impedance Stabilization Network (LISN) which supplied power source and was grounded to the ground plane.
- 5 All support equipments received AC power from a second LISN, if any.
- 6 The EUT test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- 7 Analyzer / Receiver scanned from 150 KHz to 30MHz for emissions in each of the test modes.
- 8 During the above scans, the emissions were maximized by cable manipulation.

The RBW/VBW for 150KHz to 30MHz: 9KHz

CONDUCTED POWER LINE EMISSION LIMIT

For unintentional device, according to § 15.107(a) Line Conducted Emission Limits is as following:

F	Maximum RF Line Voltage (dBμV)					
Frequency (MHz)	CLASS A		CLASS B			
(111112)	Q.P. Ave. Q.P.		Q.P.	Ave.		
0.15 - 0.50	79	66	66-56*	56-46*		
0.50 - 5.00	73	60	56	46		
5.00 - 30.0	73	60	60	50		

^{*} Decreasing linearly with the logarithm of the frequency

For intentional device, according to §15.207(a) Line Conducted Emission Limit is same as above table.

TEST RESULTS


See next pages.



V1.0 Page 12 of 51 Report No.: CTL1410272589-WF02

SCAN TABLE: "Voltage (9K-30M)FIN"

Short Description: 150K-30M Voltage




MEASUREMENT RESULT: "CTL141028624_fin"

10/28/2014 5: Frequency MHz		Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.178000 0.246000	44.60 31.80	10.2 10.2	65 62	20.0 30.1	QP QP	N N	GND GND
25.628000	32.90	11.1	60	27.1	_	N	GND
25.748000 25.874000	33.20 31.30	11.1	60 60	28.7	QP QP	N N	GND
26.420000	22.80	11.2	60	37.2	QP	N	GND

MEASUREMENT RESULT: "CTL141028624_fin2"

10/28/2014 5 Frequency MHz	5:26PM Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
1.328000	17.70	10.3	46	28.3	AV	N	GND
1.448000	19.70	10.3	46	26.3	AV	N	GND
1.544000	18.20	10.3	46	27.8	AV	N	GND
1.580000	17.40	10.3	46	28.6	AV	N	GND
1.724000	17.00	10.3	46	29.0	AV	N	GND
1.994000	15.30	10.3	46	30.7	AV	N	GND

SCAN TABLE: "Voltage (9K-30M) FIN"
Short Description: 150K-30M Voltage



MEASUREMENT RESULT: "CTL141028625_fin"

10/28/2014	5:30PM						
Frequenc Mi	cy Level Hz dBµV		Limit dBµV	Margin dB	Detector	Line	PE
0.1940	00 43.20	10.2	64	20.7	QP	L1	GND
0.2740	00 34.30	10.2	61	26.7	QP	L1	GND
25.3280	00 32.60	11.1	60	27.4	QP	L1	GND
25.6880	00 32.60	11.1	60	27.4	QP	L1	GND
25.8080	00 32.70	11.1	60	27.3	QP	L1	GND
26.4140	00 32.20	11.2	60	27.8	QP	L1	GND


MEASUREMENT RESULT: "CTL141028625 fin2"

10/28/2014 5: Frequency MHz	30PM Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.162000	18.20	10.2	55	37.2	AV	L1	GND
0.282000	20.70	10.2	51	30.1	AV	L1	GND
0.362000	18.40	10.2	49	30.3	AV	L1	GND
1.016000	13.30	10.3	46	32.7	AV	L1	GND
1.502000	14.50	10.3	46	31.5	AV	L1	GND
1.610000	14.70	10.3	46	31.3	AV	L1	GND

V1.0 Page 14 of 51 Report No.: CTL1410272589-WF02

4.2. Fundamental Emissions

TEST CONFIGURATION



Fundamental Emissions Limit

2400-2483.5 MHz Band: 94 dBuV/m (average)

For the transmitter emissions shall be measured using following options below:

Remark: RBW 3MHz VBW 3MHz PK detector is for PK value;

RBW 3MHz VBW 3MHz RMS detector is for AV value.

TEST RESULTS

	Field Strength of Fundamental Emissions Result											
Modulation	Frequency	Max.Fundamental	Margin	Limit	Type							
Mode	(MHz)	(dBuV/m)@3m	(dB)	(dBuV/m)@3m								
GFSK	2402	93.14	20.86	114	peak							
GFSK	2402	72.29	21.71	94	average							
GFSK	2440	92.89	21.11	114	peak							
GFSK	2440	73.15	20.85	94	average							
GFSK	2480	92.81	21.19	114	peak							
GFSK	2480	73.04	20.96	94	average							


Note 1: Horizontal and Vertical polarity all have been tested, Vertical polarity is the worst case and reported.

V1.0 Page 15 of 51 Report No.: CTL1410272589-WF02


4.3. Transmitter Radiated Unwanted Emissions

TEST CONFIGURATION


(A) Radiated Emission Test Set-Up, Frequency Below 30MHz



(B) Radiated Emission Test Set-Up, Frequency below 1000MHz



(C) Radiated Emission Test Set-Up, Frequency above 1000MHz



FIELD STRENGTH CALCULATION

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor(if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CL - AG$$

Where FS = Field Strength	CL = Cable Attenuation Factor (Cable Loss)
RA = Reading Amplitude	AG = Amplifier Gain
AF = Antenna Factor	

RADIATION LIMIT

For unintentional device, according to § 15.109(a), except for Class A digital devices, the field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values:

Frequency (MHz)	Distance (Meters)	Radiated (dBµV/m)	Radiated (μV/m)
30-88	3	40.0	100
88-216	3	43.5	150
216-960	3	46.0	200
Above 960	3	54.0	500

For intentional device, according to § 15.209(a), the general requirement of field strength of radiated emissions from intentional radiators at a distance of 3 meters shall not exceed the above table.

TEST PROCEDURE

- 1. The EUT is placed on a turntable, which is 0.8m above ground plane.
- 2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
- 3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
- 4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
- 5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
- 6. Repeat above procedures until the measurements for all frequencies are complete.
- 7. Based on the Frequency Generator in the device include 26MHz. The test frequency range from 9KHz to 25GHz per FCC PART 15.33(a).

Note:

Three axes are chosen for pretest, the Y axis is the worst mode for final test. For battery operated equipment, the equipment tests shall be performed using a fully battery.

V1.0 Page 17 of 51 Report No.: CTL1410272589-WF02


TEST RESULTS

All the test modes (TM1, TM2, TM3 and TM4) completed for test. The worst case of Radiated Emission is TM1; the test data of this mode was reported.

Below 1GHz Test Results:

SWEEP TABLE: "test (30M-1G)"

Short Description: Field Strength
Start Stop Detector Meas. IF Transducer
Frequency Frequency Time Bandw.
30.0 MHz 1.0 GHz MaxPeak 300.0 ms 120 kHz JB1



MEASUREMENT RESULT: "CTL141127239 red"


:58PM							
Level	Transd	Limit	Margin	Det.	Height	Azimuth	Polarization
dBµV/m	dB	dΒμV/m	dB		cm	deg	
22.50	21.1	40.0	17.5		0.0	0.00	VERTICAL
22.30	10.6	43.5	21.2		0.0	0.00	VERTICAL
31.80	12.9	43.5	11.7		0.0	0.00	VERTICAL
28.40	14.1	46.0	17.6		0.0	0.00	VERTICAL
33.80	20.6	46.0	12.2		0.0	0.00	VERTICAL
30.70	26.1	46.0	15.3		0.0	0.00	VERTICAL
	Level dBµV/m 22.50 22.30 31.80 28.40 33.80	Level Transd dB dB	Level Transd Limit dBμV/m dB dBμV/m 22.50 21.1 40.0 22.30 10.6 43.5 31.80 12.9 43.5 28.40 14.1 46.0 33.80 20.6 46.0	Level Transd Limit Margin dBμV/m dB dBμV/m dB dBμV/m dB 22.50 21.1 40.0 17.5 22.30 10.6 43.5 21.2 31.80 12.9 43.5 11.7 28.40 14.1 46.0 17.6 33.80 20.6 46.0 12.2	Level Transd Limit Margin Det. dBμV/m dB dBμV/m dB 22.50 21.1 40.0 17.5 22.30 10.6 43.5 21.2 31.80 12.9 43.5 11.7 28.40 14.1 46.0 17.6 33.80 20.6 46.0 12.2	Level dBμV/m Transd dB dBμV/m Limit dBμV/m Margin dB Det. Height dB m 22.50 21.1 40.0 17.5 0.0 22.30 10.6 43.5 21.2 0.0 31.80 12.9 43.5 11.7 0.0 28.40 14.1 46.0 17.6 0.0 33.80 20.6 46.0 12.2 0.0	Level dBμV/m Transd dB dBμV/m Limit dB dBμV/m Det. Height deg Azimuth deg 22.50 21.1 40.0 17.5 0.0 0.00 22.30 10.6 43.5 21.2 0.0 0.00 31.80 12.9 43.5 11.7 0.0 0.00 28.40 14.1 46.0 17.6 0.0 0.00 33.80 20.6 46.0 12.2 0.0 0.00

Remark:

- (1) Measuring frequencies from 9 KHz to the 1 GHz, Radiated emission test from 9KHz to 30MHz was verified, and no any emission was found except system noise floor.
- * denotes emission frequency which appearing within the Restricted Bands specified in provision of 15.205, then the general radiated emission limits in 15.209 apply.
- (3) The IF bandwidth of EMI Test Receiver between 30MHz to 1GHz was 120KHz, 1 MHz for measuring above 1 GHz, below 30MHz was 10KHz.

SWEEP TABLE: "test (30M-1G)"

Short Description: Field Strength
Start Stop Detector Meas. IF Transducer
Frequency Frequency Time Bandw.
30.0 MHz 1.0 GHz MaxPeak 300.0 ms 120 kHz JB1



MEASUREMENT RESULT: "CTL141127238_red"

11/27/2014	1:57PM							
Frequency MHz			Limit dBµV/m	Margin dB	Det.	Height cm	Azimuth deg	Polarization
30.000000	23.90	21.1	40.0	16.1		0.0	0.00	VERTICAL
95.960000	25.30	10.6	43.5	18.2		0.0	0.00	VERTICAL
103.720000	32.20	12.5	43.5	11.3		0.0	0.00	VERTICAL
235.640000	31.70	14.1	46.0	14.3		0.0	0.00	VERTICAL
532.460000	31.60	20.6	46.0	14.4		0.0	0.00	VERTICAL
800.180000	32.20	24.8	46.0	13.8		0.0	0.00	VERTICAL


Remark:

- (1) Measuring frequencies from 9 KHz to the 1 GHz, Radiated emission test from 9KHz to 30MHz was verified, and no any emission was found except system noise floor.
- * denotes emission frequency which appearing within the Restricted Bands specified in provision of 15.205, then the general radiated emission limits in 15.209 apply.
- (3) The IF bandwidth of EMI Test Receiver between 30MHz to 1GHz was 120KHz, 1 MHz for measuring above 1 GHz, below 30MHz was 10KHz.

V1.0 Page 19 of 51 Report No.: CTL1410272589-WF02

Above 1 GHz Test Results:

Bottom Channel (2402MHz):




Site no. : 3m Chamber Dis. / Ant. : 3m DRH-118

Dis. / Ant. : 3m DRH-118 Ant. pol. : HORIZONTAL

Limit : 74DB Env. / Ins. : 23*C/54%

		Ant.	Cable		Emission	,		
	Freq.	Factor	Loss	Reading	Level	Limits	Margin	Remark
	(MHz)	(dB)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)	
1	4804.00	33.48	6.91	43.91	49.96	74.00	24.04	Peak
2	7206.00	36.92	9.18	44.91	55.98	74.00	18.02	Peak
3	9608.00	38.53	10.97	42.60	56.11	74.00	17.89	Peak




Site no. : 3m Chamber Dis. / Ant. : 3m DRH-118 Data no. : 969 Ant. pol. : VERTICAL

Limit : 74DB Env. / Ins. : 23*C/54%

Engineer EUT Power M/NTest Mode :

	Freq. (MHz)	Ant. Factor (dB)	Cable Loss (dB)	Reading	Emission Level (dBuV/m)	Limits	Margin (dB)	Remark
1 2 3		36.92	6.91 9.18 10.97	47.77 47.76 46.16	53.82 58.83 59.67	74.00 74.00 74.00	20.18 15.17 14.33	Peak Peak Peak Peak





Site no. : 3m Chamber Data no. : 968

Dis. / Ant. : 3m DRH-118 Ant. pol. : HORIZONTAL

Limit : 54DB Env. / Ins. : 23*C/54%

		Ant.	Cable		Emission			
	Freq. (MHz)	Factor (dB)	Loss (dB)	_	Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	4804.00	33.48	6.91	30.71	36.76	54.00	17.24	Average
2	7206.00	36.92	9.18	30.97	42.04	54.00	11.96	Average
3	9608.00	38.53	10.97	28.66	42.17	54.00	11.83	Average






Site no. : 3m Chamber Data no. : 970

Dis. / Ant. : 3m DRH-118 Ant. pol. : VERTICAL

Limit : 54DB Env. / Ins. : 23*C/54%

		Ant.	Cable		Emission	L		
	Freq.	Factor	Loss	Reading	Level	Limits	Margin	Remark
	(MHz)	(dB)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)	
1	4804.00	33.48	6.91	30.64	36.69	54.00	17.31	Average
2	7206.00	36.92	9.18	30.93	42.00	54.00	12.00	Average
3	9608.00	38.53	10.97	28.43	41.94	54.00	12.06	Average

V1.0 Report No.: CTL1410272589-WF02 Page 23 of 51




Data no. : 973

Site no. : 3m Chamber Dis. / Ant. : 3m DRH-118 Ant. pol. : HORIZONTAL

Limit : 74DB Env. / Ins. : 23*C/54%

Engineer EUT Power M/NTest Mode

		Ant.	Cable		Emission	L .		
	Freq. (MHz)	Factor (dB)		_		Limits (dBuV/m)	_	Remark
1	4880.00	33.60	6.95	46.07	52.32	74.00	21.68	Peak
2	7230.00	37.00	9.19	49.48	60.65	74.00	13.35	Peak
3	9760.00	38.65	11.03	45.86	59.85	74.00	14.15	Peak



Ant. pol. : VERTICAL

Site no. : 3m Chamber Dis. / Ant. : 3m DRH-118


Limit : 74DB Env. / Ins. : 23*C/54%

Env. / Ins. : 23*0
Engineer :
EUT :
Power :

M/N : Test Mode :

		Ant.	Cable		Emission			
	Freq. (MHz)	Factor (dB)		_		Limits (dBuV/m)	_	Remark
1	4880.00	33.60	6.95	47.02	53.27	74.00	20.73	Peak
2	7320.00	37.46	9.23	46.20	57.89	74.00	16.11	Peak
3	9760.00	38.65	11.03	45.22	59.21	74.00	14.79	Peak






Site no. : 3m Chamber Dis. / Ant. : 3m DRH-118 Data no. : 972

Ant. pol. : VERTICAL

: 54DB Limit Env. / Ins. : 23*C/54%

Engineer EUT Power : M/N Test Mode

		Ant.	Cable		Emission			
	Freq. (MHz)	Factor (dB)	Loss (dB)	_	Level (dBuV/m)		Margin (dB)	Remark
1	4880.00	33.60	6.95	30.32	36.57	54.00	17.43	Average
2	7320.00	37.46	9.23	30.58	42.27	54.00	11.73	Average
3	9760.00	38.65	11.03	29.26	43.25	54.00	10.75	Average



Frequency (MHz)

6400.

8200.

10000

Site no. : 3m Chamber Data no. : 974

2800.

Dis. / Ant. : 3m DRH-118 Ant. pol. : HORIZONTAL


4600.

: 54DB Env. / Ins. : 23*C/54%

Engineer EUT Power M/NTest Mode

Freq.	Factor		Reading		Limits	_	Remark
4880.00	33.60	6.95	30.32	36.57	54.00	17.43	Average
7320.00	37.46	9.23	30.58	42.27	54.00	11.73	Average
9760.00	38.65	11.03	29.29	43.28	54.00	10.72	Average
	(MHz) 4880.00 7320.00	Freq. Factor (MHz) (dB) 4880.00 33.60 7320.00 37.46	Freq. Factor Loss (MHz) (dB) (dB) 4880.00 33.60 6.95 7320.00 37.46 9.23	Freq. Factor Loss Reading (MHz) (dB) (dB) (dBuV) 4880.00 33.60 6.95 30.32 7320.00 37.46 9.23 30.58	Freq. Factor Loss Reading Level (MHz) (dB) (dB) (dBuV) (dBuV/m) 4880.00 33.60 6.95 30.32 36.57 7320.00 37.46 9.23 30.58 42.27	Freq. Factor Loss Reading Level Limits (MHz) (dB) (dB) (dBuV) (dBuV/m) (dBuV/m) 4880.00 33.60 6.95 30.32 36.57 54.00 7320.00 37.46 9.23 30.58 42.27 54.00	Freq. Factor Loss Reading Level Limits Margin (MHz) (dB) (dB) (dBuV) (dBuV/m) (dBuV/m) (dB) 4880.00 33.60 6.95 30.32 36.57 54.00 17.43 7320.00 37.46 9.23 30.58 42.27 54.00 11.73

Top Channel (2480MHz):




Site no. : 3m Chamber Data no. : 977

Dis. / Ant. : 3m DRH-118 Ant. pol. : HORIZONTAL

Limit : 74DB Env. / Ins. : 23*C/54%

		Ant.	Cable		Emission	L		
	Freq.	Factor	Loss	Reading	Level	Limits	Margin	Remark
	(MHz)	(dB)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)	
1	4960.00	33.86	7.01	46.92	53.54	74.00	20.46	Peak
2	7440.00	37.64	9.28	47.92	59.87	74.00	14.13	Peak
3	9920.00	38.90	11.10	46.25	60.88	74.00	13.12	Peak




Data no. : 975 Ant. pol. : VERTICAL

Site no. : 3m Chamber Dis. / Ant. : 3m DRH-118

Limit : 74DB Env. / Ins. : 23*C/54%

		Ant.	Cable		Emission			
	Freq. (MHz)	Factor (dB)		_	Level (dBuV/m)		_	Remark
1	4960.00	33.86	7.01	46.71	53.33	74.00	20.67	Peak
2	7440.00	37.64	9.28	46.64	58.59	74.00	15.41	Peak
3	9920.00	38.90	11.10	46.46	61.09	74.00	12.91	Peak





Site no. : 3m Chamber Data no. : 978

Dis. / Ant. : 3m DRH-118 Ant. pol. : HORIZONTAL

Limit : 54DB Env. / Ins. : 23*C/54%

		Ant.	Cable		Emission			
	Freq.	Factor			Level			Remark
	(MHz)	(dB)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)	
1	4960.00	33.86	7.01	30.47	37.09	54.00	16.91	Average
2	7440.00	37.64	9.28	30.68	42.63	54.00	11.37	Average
3	9920.00	38.90	11.10	29.56	44.19	54.00	9.81	Average





Site no. : 3m Chamber Dis. / Ant. : 3m DRH-118

80 _____BuV/m)

Limit : 54DB Env. / Ins. : 23*C/54%

Engineer :
EUT :
Power :
M/N :
Test Mode :

Data no. : 976 Ant. pol. : VERTICAL

		Ant.	Cable		Emission	ı		
	Freq. (MHz)	Factor (dB)	Loss (dB)	Reading (dBuV)		Limits (dBuV/m)	Margin (dB)	Remark
1	4960.00	33.86	7.01	30.50	37.12	54.00	16.88	Average
2	7440.00	37.64	9.28	30.68	42.63	54.00	11.37	Average
3	9920.00	38.90	11.10	29.55	44.18	54.00	9.82	Average

Note: above 10GHz up to 25GHz was verified, and no any emission was found except system noise floor.

4.4. Band Edge Measurement

TEST CONFIGURATION

Same as Section 4.2

TEST PROCEDURE

The band edge compliance of RF radiated emission should be measured by following the guidance in ANSI C63.4 with respect to maximizing the emission by rotating the EUT, measuring the emission while the EUT is situated in three orthogonal planes (if appropriate), adjusting the measurement antenna height and polarization etc.

RBW 1MHz VBW 3MHz PK detector is for PK value;

RBW 1MHz VBW 3MHz RMS detector is for AV value.

LIMIT

FCC PART 15.249(d) Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in §15.209, whichever is the lesser attenuation.

TEST RESULTS

See next pages.




Report No.: CTL1410272589-WF02

Radiated Test:

Operation Mode: TX on Bot Channel

Polarity: Hor.



Data no. : 938


Site no. : 3m Chamber Dis. / Ant. : 3m DRH-118 Ant. pol. : HORIZONTAL

Limit : 74DB Env. / Ins. : 23*C/54%

Engineer EUT Power M/N Test Mode

		Ant.	Cable		Emission			
	Freq. (MHz)	Factor (dB)		_	Level (dBuV/m)		Margin (dB)	Remark
1	2390.00	28.78	4.61	40.64	38.67	74.00	35.33	Peak
2	2400.00	28.78	4.61	71.37	69.40	74.00	4.60	Peak
3	2402.20	28.78	4.61	92.48	90.51	74.00	-16.51	Peak

Page 35 of 51



Data no. : 939

Site no. : 3m Chamber Dis. / Ant. : 3m DRH-118 Ant. pol. : HORIZONTAL

: 54DB Limit Env. / Ins. : 23*C/54%


Engineer EUT Power M/NTest Mode

		Ant.	Cable		Emission			
	Freq.	Factor	Loss	Reading	Level	Limits	Margin	Remark
	(MHz)	(dB)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)	
1	2390.00	28.78	4.61	18.76	16.79	54.00	37.21	Average
2	2400.00	28.78	4.61	45.83	43.86	54.00	10.14	Average
3	2401.90	28.78	4.61	71.33	69.36	54.00	-15.36	Average

Page 36 of 51 Report No.: CTL1410272589-WF02

Operation Mode: TX on Bot Channel

Polarity: Ver.




Site no. : 3m Chamber Data no. : 937

Dis. / Ant. : 3m DRH-118 Ant. pol. : VERTICAL

: 74DB Limit Env. / Ins. : 23*C/54%

Engineer EUT Power M/NTest Mode :

	Freq. (MHz)	Factor		Reading		Limits (dBuV/m)	_	Remark
1 2 3	2390.00 2400.00 2402.20	28.78	4.61	74.49	72.52	74.00	34.84 1.48 -19.71	Peak Peak Peak



Site no. : 3m Chamber Data no. : 940

Dis. / Ant. : 3m DRH-118 Ant. pol. : VERTICAL

Limit : 54DB Env. / Ins. : 23*C/54%


Engineer : EUT : Power : M/N : Test Mode :

		Ant.	Cable		Emission			
	Freq. (MHz)	Factor (dB)	Loss (dB)	_	Level (dBuV/m)		Margin (dB)	Remark
1	2390.00	28.78	4.61	18.82	16.85	54.00	37.15	Average
2	2400.00	28.78	4.61	48.33	46.36	54.00	7.64	Average
3	2401.90	28.78	4.61	73.78	71.81	54.00	-17.81	Average

Note: The field strength of any emissions which appear outside of this band shall not exceed the general radiated emission limits in Section 15.209.

Operation Mode: TX on Top Channel

Polarity: Hor.



Site no. : 3m Chamber


Dis. / Ant. : 3m DRH-118


Limit : 74DB Env. / Ins. : 23*C/54%

Engineer : EUT : Power : M/N : Test Mode : Data no. : 941

Ant. pol. : HORIZONTAL

		Ant.	Cable		Emission			
	Freq. (MHz)			_		Limits (dBuV/m)	_	Remark
1	2480.18	28.93	4.70	93.24	91.49	74.00	-17.49	Peak
2	2483.50	28.93	4.70	60.03	58.28	74.00	15.72	Peak





Site no. : 3m Chamber
Dis. / Ant. : 3m DRH-118
Limit : 54DB
Env. / Ins. : 23*C/54%

Engineer EUT Power : M/N Test Mode : Data no. : 933


Ant. pol. : HORIZONTAL

		Ant.	Cable		Emission			
	Freq.	Factor (dB)		_		Limits (dBuV/m)	_	Remark
1	2480.05	28.93	4.70	74.73	72.98	54.00	-18.98	Average
2	2483.50	28.93	4.70	39.95	38.20	54.00	15.80	Average

Page 40 of 51 Report No.: CTL1410272589-WF02

Operation Mode: TX on Top Channel

Polarity: Ver.



Site no. : 3m Chamber Data no. : 942


Dis. / Ant. : 3m DRH-118 Ant. pol. : VERTICAL

: 74DB Limit Env. / Ins. : 23*C/54%

Engineer EUT Power M/N Test Mode

		Ant.	Cable		Emission			
	Freq. (MHz)	Factor (dB)		_	Level (dBuV/m)		_	Remark
1	2480.18	28.93	4.70	94.98	93.23	74.00	-19.23	Peak
2	2483.50	28.93	4.70	61.26	59.51	74.00	14.49	Peak





Site no. : 3m Chamber Dis. / Ant. : 3m DRH-118

Limit : 54DB Env. / Ins. : 23*C/54%

Engineer : EUT : Power : M/N : Test Mode : Data no. : 934 Ant. pol. : VERTICAL

		Ant.	Cable		Emission				
	Freq.	Factor	Loss	Reading	Level	Limits	Margin	Remark	
	(MHz)	(dB)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)		
1	2480.05	28.93	4.70	70.55	68.80	54.00	-14.80	Average	
2	2483.50	28.93	4.70	34.88	33.13	54.00	20.87	Average	

Note: The field strength of any emissions which appear outside of this band shall not exceed the general radiated emission limits in Section 15.209.

V1.0 Page 42 of 51 Report No.: CTL1410272589-WF02

4.5. Occupied Bandwidth Measurement

Measurement Procedure

- 1. The EUT was placed on a turn table which is 0.8m above ground plane.
- 2. Set EUT as normal operation.
- 3. Based on FCC Part15 C Section 15.239(a): RBW= 10KHz. VBW= 30 KHz, Span=3MHz.
- 4. The useful radiated emission from the EUT was detected by the spectrum analyser with peak detector.


Test SET-UP (Block Diagram of Configuration)

Same as 4.2 Radiated Emission Measurement.

Measurement Equipment Used:

Same as 4.2 Radiated Emission Measurement.

Measurement Results




20dB Bandwidth: 1102KHz

Agilent Freq/Channel Center Freq 2.44000000 GHz Occupied Bandwidth Start Freq 2.43850000 GHz Ref 0 dBm Atten 10 dB #Peal Stop Freq 2.44150000 GHz Log 10 dB/ CF Step 300.000000 kHz Freq Offset 0.00000000 Hz Center 2.44 GHz #Res BW 10 kHz Span 3 MHz #VBW 30 kHz Sweep 31.08 ms (401 pts) Signal Track Occupied Bandwidth Occ BW % Pwr 99.00 % -20.00 dB 1.0131 MHz 7.488 kHz Transmit Freq Error x dB Bandwidth 1.120 MHz

2440MHz

20dB Bandwidth: 1120KHz

2480MHz





V1.0 Page 44 of 51 Report No.: CTL1410272589-WF02

5. Antenna Requirement

Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to FCC 47 CFR Section 15.247 (c), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

Refer to statement below for compliance.

The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited. Further, this requirement does not apply to intentional radiators that must be professionally installed.


Antenna Connected Construction

The antenna used in this product is an internal Antenna, The directional gains of antenna used for transmitting is 0 dBi.



V1.0 Page 45 of 51 Report No.: CTL1410272589-WF02

6. Test Setup Photos of the EUT









7. External and Internal Photos of the EUT

External Photos of EUT













V1.0 Page 49 of 51 Report No.: CTL1410272589-WF02


Internal Photos of EUT


















V1.0 Page 51 of 51 Report No.: CTL1410272589-WF02



.....End of Report.....

