RF EXPOSURE REPORT



Report No.: 15070727-FCC-H2
Supersede Report No.: N/A

Applicant	Worldlinks Communications, L.L.C.		
Product Name	RedDot Phone		
Model No.	R50		
Serial No.	N/A		
Test Standard	FCC 2.109	3.2014	
Test Date	August 24 to September 24, 2015		
Issue Date	September 28, 2015		
Test Result	Pass Fail		
Equipment complied with the specification			
Equipment did not comply with the specification			
Winnie Zheng David Huang			
Winnie Zhang Test Engineer		David Huang Checked By	

This test report may be reproduced in full only

Test result presented in this test report is applicable to the tested sample only

Issued by:

SIEMIC (SHENZHEN-CHINA) LABORATORIES

Zone A, Floor 1, Building 2 Wan Ye Long Technology Park
South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong China 518108
Phone: +86 0755 2601 4629801 Email: China@siemic.com.cn



Test Report	15070727-FCC-H2
Page	2 of 10

Laboratories Introduction

SIEMIC, headquartered in the heart of Silicon Valley, with superior facilities in US and Asia, is one of the leading independent testing and certification facilities providing customers with one-stop shop services for Compliance Testing and Global Certifications.



In addition to testing and certification, SIEMIC provides initial design reviews and compliance management throughout a project. Our extensive experience with China, Asia Pacific, North America, European, and International compliance requirements, assures the fastest, most cost effective way to attain regulatory compliance for the global markets.

Accreditations for Conformity Assessment

Country/Region	Scope
USA	EMC, RF/Wireless, SAR, Telecom
Canada	EMC, RF/Wireless, SAR, Telecom
Taiwan	EMC, RF, Telecom, SAR, Safety
Hong Kong	RF/Wireless, SAR, Telecom
Australia	EMC, RF, Telecom, SAR, Safety
Korea	EMI, EMS, RF, SAR, Telecom, Safety
Japan	EMI, RF/Wireless, SAR, Telecom
Singapore	EMC, RF, SAR, Telecom
Europe	EMC, RF, SAR, Telecom, Safety



Test Report	15070727-FCC-H2
Page	3 of 10

This page has been left blank intentionally.



Test Report	15070727-FCC-H2
Page	4 of 10

CONTENTS

1.	REPORT REVISION HISTORY	.5
	CUSTOMER INFORMATION	
3.	TEST SITE INFORMATION	.5
4.	EQUIPMENT UNDER TEST (EUT) INFORMATION	.6
5.	FCC §2.1093 - RADIOFREQUENCY RADIATION EXPOSURE EVALUATION: PORTABLE DEVICES.	8
5.1	RF EXPOSURE	.8
5.2	TEST RESULT	.9



Test Report	15070727-FCC-H2
Page	5 of 10

1. Report Revision History

Report No.	Report Version	Description	Issue Date
15070727-FCC-H2	NONE	Original	September 28, 2015

2. Customer information

Applicant Name	Worldlinks Communications, L.L.C.	
Applicant Add	270 Center Drive Suite 230, Vernon Hills, IL. 60061	
Manufacturer	SHENZHEN NEWCHABRIDGE COMMUNICATION CO.,LTD	
Manufacturer Add	New Bridge Industrial Park, Baolong Six Road, Baolong Industrial City, Longgang	
	District, Shenzhen	

3. Test site information

Lab performing tests	SIEMIC (Shenzhen-China) LABORATORIES	
	Zone A, Floor 1, Building 2 Wan Ye Long Technology Park	
Lab Address	South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong	
	China 518108	
FCC Test Site No.	718246	
IC Test Site No.	4842E-1	
Test Software	Radiated Emission Program-To Shenzhen v2.0	



Test Report	15070727-FCC-H2
Page	6 of 10

4. Equipment under Test (EUT) Information

Description of EUT: RedDot Phone

Main Model: R50

Serial Model: N/A

Date EUT received: August 24, 2015

Test Date(s): August 24 to September 24, 2015

GSM850: 0.37 dBi PCS1900: 1.01 dBi

UMTS-FDD Band V: 0.37 dBi

Antenna Gain: UMTS-FDD Band II: 1.01 dBi

Bluetooth/BLE: 1.34 dBi

WIFI: 1.34 dBi GPS: 0.46 dBi

GSM / GPRS: GMSK

EGPRS: GMSK

UMTS-FDD: QPSK, 16QAM 802.11b/g/n: DSSS, OFDM

Type of Modulation:

Bluetooth: GFSK, π /4DQPSK, 8DPSK

BLE: GFSK

LTE Band: QPSK, 16QAM

GPS:BPSK

GSM850 TX: 824.2 ~ 848.8 MHz; RX: 869.2 ~ 893.8 MHz

PCS1900 TX: 1850.2 ~ 1909.8 MHz; RX: 1930.2 ~ 1989.8 MHz

UMTS-FDD Band V TX: 826.4 ~ 846.6 MHz; RX: 871.4 ~ 891.6 MHz

UMTS-FDD Band II TX:1852.4 ~ 1907.6 MHz;

RF Operating Frequency (ies): RX: 1932.4 ~ 1987.6 MHz

WIFI:802.11b/g/n(20M): 2412-2462 MHz WIFI:802.11n(40M): 2422-2452 MHz Bluetooth& BLE: 2402-2480 MHz

____.

GPS RX:1575.42 MHz



Test Report	15070727-FCC-H2
Page	7 of 10

GSM 850: 124CH PCS1900: 299CH

UMTS-FDD Band V : 102CH UMTS-FDD Band II : 277CH

Number of Channels: WIFI:802.11b/g/n(20M): 11CH

WIFI:802.11n(40M):7CH

Bluetooth: 79CH

BLE: 40CH GPS:1CH

Port: Power Port, Earphone Port, USB Port

Battery: Model:R50

Spec: 2200mAh(9.57Wh)

Limited Charging Voltage: 4.35V

Input Power: Adapter:

riduptor.

Model:HJ-0501000

Input: 100-240V; 50/60Hz; 0.15A

Output: DC 5.0V,1000mA

Trade Name: N/A

GPRS/EGPRS Multi-slot class 8/10/12

FCC ID: 2ADNIR50



Test Report	15070727-FCC-H2
Page	8 of 10

5. FCC §2.1093 - Radiofrequency radiation exposure evaluation: portable devices.

5.1 RF Exposure

Standard Requirement:

According to §15.247 (i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] $\cdot [\sqrt{f_{(GHz)}}] \le 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, 16 where

- f_(GHz) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation¹⁷
- The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is ≤ 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

Routine SAR evaluation refers to that specifically required by § 2.1093, using measurements or computer simulation. When routine SAR evaluation is not required, portable transmitters with output power greater than the applicable low threshold require SAR evaluation to qualify for TCB approval.

result = $P\sqrt{F}/D$

P= Maximum turn-up power in mW

F= Channel frequency in GHz

D= Minimum test separation distance in mm



Test Report	15070727-FCC-H2			
Page	9 of 10			

5.2 Test Result

Bluetooth Mode:

Modulation	СН	Freq (MHz)	Conducted Power	Tune Up Power	Max Tune Up Power	Max Tune Up Power	Result	Limit
			(dBm)	(dBm)	(dBm)	(mW)		
GFSK	Low	2402	1.918	2±1	3	1.995	0.62	3
	Mid	2441	2.797	2±1	3	1.995	0.62	3
	High	2480	2.639	2±1	3	1.995	0.63	3
π /4 DQPSK	Low	2402	1.855	2±1	3	1.995	0.62	3
	Mid	2441	2.716	2±1	3	1.995	0.62	3
	High	2480	2.581	2±1	3	1.995	0.63	3
8-DPSK	Low	2402	2.018	2±1	3	1.995	0.62	3
	Mid	2441	2.922	2±1	3	1.995	0.62	3
	High	2480	2.762	2±1	3	1.995	0.63	3

WIFI Mode:

Modulation	СН	Freq (MHz)	Conducted Power (dBm)	Tune Up Power (dBm)	Max Tune Up Power (dBm)	Max Tune Up Power (mW)	Result	Limit
	Low	2412	8.69	8.5±1	9.5	8.913	2.77	3
802.11b	Mid	2437	8.87	8.5±1	9.5	8.913	2.78	3
	High	2462	8.50	8.5±1	9.5	8.913	2.80	3
802.11g	Low	2412	9.03	8 .5±1	9.5	8.913	2.77	3
	Mid	2437	9.05	8.5±1	9.5	8.913	2.78	3
	High	2462	8.63	8.5±1	9.5	8.913	2.80	3
802.11n (20M)	Low	2412	8.70	8 .5±1	8.5	7.079	2.20	3
	Mid	2437	9.06	8.5±1	9.5	8.913	2.78	3
	High	2462	8.53	8.5±1	9.5	8.913	2.80	3
802.11n (40M)	Low	2422	9.11	8.5±1	9.5	8.913	2.77	3
	Mid	2437	8.87	8.5±1	9.5	8.913	2.78	3
	High	2452	8.42	8.5±1	9.5	8.913	2.79	3



Test Report	15070727-FCC-H2
Page	10 of 10

BLE Mode:

Modulation	СН	Freq (MHz)	Conducted Power (dBm)	Tune Up Power (dBm)	Max Tune Up Power (dBm)	Max Tune Up Power (mW)	Result	Limit
GFSK	Low	2402	-5.913	-5±1	-4	0.398	0.12	3
	Mid	2440	-5.194	-5±1	-4	0.398	0.12	3
	High	2480	-5.414	-5±1	-4	0.398	0.13	3

Result: Compliance

No SAR measurement is required.