

TEST REPORT FOR SAR TESTING

Report No.: SRTC2020-9004(F)-20022801(H)

Product Name: Smartphone

Marketing Name: Hisense E40

Product Model: HLTE229E

Applicant: Hisense International Co., Ltd.

Manufacturer: Hisense Communications Co., Ltd.

Specification: Part 2.1093

IEEE Std 1528

KDB Procedures

FCC ID: 2ADOBHLTE229E

The State Radio_monitoring_center Testing Center (SRTC)

15th Building, No.30 Shixing Street, Shijingshan District, Beijing, P.R. China

Tel: 86-10-57996183 Fax: 86-10-57996388

Contents

1. GENERAL INFORMATION.....	2
1.1 NOTES OF THE TEST REPORT	2
1.2 INFORMATION ABOUT THE TESTING LABORATORY	2
1.3 APPLICANT’S DETAILS	2
1.4 MANUFACTURER’S DETAILS	2
1.5 TEST ENVIRONMENT	3
2. DESCRIPTION OF THE DEVICE UNDER TEST	3
2.1 FINAL EQUIPMENT BUILD STATUS.....	3
2.2 SUPPORT EQUIPMENT	4
3. REFERENCE SPECIFICATION.....	6
4. TEST CONDITIONS	7
4.1 PICTURE TO DEMONSTRATE THE REQUIRED LIQUID DEPTH	7
4.2 TEST SIGNAL, FREQUENCIES AND OUTPUT POWER	7
4.3 SAR MEASUREMENT SET-UP	7
4.4 PHANTOMS	8
4.5 TISSUE SIMULANTS	8
4.6 DESCRIPTION OF THE TEST PROCEDURE	9
5 RESULT SUMMAR	12
6 TEST RESULT	14
6.1 MANUFACTURING TOLERANCE.....	14
6.2 GSM MEASUREMENT RESULT	28
6.3 WCDMA MEASUREMENT RESULT	31
6.4 LTE MEASUREMENT RESULT	39
6.5 BLUETOOTH MEASUREMENT RESULT	65
6.6 WI-FI MEASUREMENT RESULT	65
6.7 STANDALONE SAR TEST EXCLUSION CONSIDERATIONS.....	66
6.8 RF EXPOSURE CONDITIONS	68
6.9 SYSTEM CHECKING	71
6.10 SAR TEST RESULT	72
6.11 SAR MEASUREMENT VARIABILITY	90
6.12 SIMULTANEOUS TRANSMISSION SAR ANALYSIS.....	91
7 MEASUREMENT UNCERTAINTY.....	92
8 TEST EQUIPMENTS.....	94
ANNEX A – TEST PLOTS	101
ANNEX B – RELEVANT PAGES FROM CALIBRATION REPORTS	131

1. GENERAL INFORMATION

1.1 Notes of the test report

The test report may only be reproduced or published in full. Reproduction or publication of extracts from the report requires the prior written permission of The State Radio_monitoring_center Testing Center (SRTC).

The test results relate only to individual items of the samples which have been tested.

The certification and accreditation identifiers used in this report shall not be applicable to the tested or calibrated samples thereof. The manufacturer shall not mark the tested samples or items (or a separate part of the item) with the identifiers of certification and accreditation to mislead relevant parties about the tested samples or items.

1.2 Information about the testing laboratory

Company:	The State Radio_monitoring_center Testing Center (SRTC)
Address:	15th Building, No.30 Shixing Street, Shijingshan District, Beijing P.R. China
City:	Beijing
Country or Region:	P.R. China
Contacted person:	Liu Jia
Tel:	+86 10 57996183
Fax:	+86 10 57996388
Email:	liujiaf@srtc.org.cn

1.3 Applicant's details

Company:	Hisense International Co., Ltd.
Address:	Floor 22, Hisense Tower, 17 Donghai Xi Road, Qingdao, 266071, China
City:	Qingdao
Country or Region:	P.R. China
Contacted person:	Geng Ruifeng
Tel:	+86-532-80877742
Fax:	---
Email:	gengruifeng@hisense.com

1.4 Manufacturer's details

Company:	Hisense Communications Co., Ltd.
Address:	No.218 Qianwangang Road, Economic & Technological Development Zone, Qingdao, China
City:	Qingdao
Country or Region:	P.R. China
Contacted person:	Deng Tingting
Tel:	+86-532-55753708
Fax:	---
Email:	dengtingting@hisense.com

1.5 Test Environment

Date of Receipt of test sample at SRTC:	2020.02.28
Testing Start Date:	2020.02.29
Testing End Date:	2020.03.15

Environmental Data:	Temperature (°C)	Humidity (%)
Ambient	25	40

Normal Supply Voltage (Vdc.):	3.85
-------------------------------	------

2. DESCRIPTION OF THE DEVICE UNDER TEST

2.1 Final Equipment Build Status

Wireless Technology and Frequency Bands	☒ GSM Band: GSM850/GSM1900 ☒ WCDMA Band: FDD II/IV/V ☒ LTE Band: 2/4/5/7/12 ☒ Wi-Fi Band: 2.4GHz ☒ BT/BLE
Mode	GSM ☒ GPRS (GMSK) ☒ EGPRS (GMSK/8PSK) WCDMA ☒ UMTS Rel. 99 ☒ HSDPA (Rel. 5) ☒ HSUPA (Rel. 6) ☒ HSPA+ (Rel.7) ☒ DC-HSDPA (Rel.8) Wi-Fi 2.4GHz ☒ 802.11b ☒ 802.11g ☒ 802.11n HT20 ☒ 802.11n HT40 LTE ☒ QPSK ☒ 16QAM ☒ 64QAM
Duty Cycle*	GPRS: 12.5% (1 Slot), 25% (2 Slots), 37.5% (3 Slots), 50% (4 Slots) EDGE(GMSK/8PSK) 12.5% (1 Slot), 25% (2 Slots), 37.5% (3 Slots), 50% (4 Slots) WCDMA: 100% LTE(FDD): 100% LTE(TDD): 63.3% maximum

	unlicensed network	Data Rate (Mbps)	Test Result (%)
	802.11b	1	99.5
	802.11g	6	97.2
	802.11n (HT20)	MCS0	97.0
	BT-BR	1	46.4
	BT-EDR	2	46.2
	BT-EDR	3	46.2
	BT-LE	1	87.4
Multi-Slot Class for GPRS/EDGE	☐ Class 8 - One Up ☐ Class 10 - Two Up ☒ Class 12 - Four Up ☐ Class 33- Four Up		
Mobile Phone Capability	☐ Class A - Mobile phones can be connected to both GPRS and GSM services simultaneously. ☒ Class B - Mobile phones can be attached to both GPRS and GSM services, using one service at a time. ☐ Class C - Mobile phones are attached to either GPRS or GSM voice service. You need to switch manually between services		
DTM	Not Supported		
Note	For licensed cellular network duty cycle is inherent. For unlicensed network WLAN Duty cycle is depends on the data traffic, and the traffic allocation in operating mode could be the most conservative condition which with 100% duty cycle. SAR measurement also use non signalling mode, so the duty factor shall be taken into consideration.		

2.2 Support Equipment

The following support equipment was used to exercise the DUT during testing:

State of sample	Normal
H/W Version	V0.1
S/W Version	Hisense_HLTE229E_10_S02_03
IMEI	Main supply: 867400020316612 Secondary supply:867400020316612
Notes	For all the test samples provided by applicant, IMEI are the same. That's weird but distinguishable. As the information described above, we use test sample offered by the customer. The relevant tests have been performed in order to verify in which combination case the EUT would have the worst features.

Main Supply

Part Name	Model	Supplier(Brand)	Description
Memory	UNMEN05GC1C31AS12T00	UNIC	eMMC5.1 Module,32GB,FBGA-153 Ball
Memory	SU512M32Z11ND2DNP-053BT	SPITECK(SPREADT RUM)	LPDDR4X,16Gb(512 Meg x 32 (2 channels x 16 I/O)),VFBGA-200Ball
Camera	H8B8-KS229FF	Kingcome	HI-846,CSP,S0876A
Camera	BM15907V2	CXT	GC5035,COM,PC5401-6 5HD-60
Camera	H9B13-KS230BA	Kingcome	HI1336,COB,3933C-400
Camera	BC12903V0	CXT	GC02M1B,CSP,HX-M020 7B-H201
LCD+TP	HTF065H029	HOLITECH	ICNL9911S,MLAF065WE 51
fingerprin t	TW-SW331B-KS230-V1	TOWO	SW331B
Battery	LPN385400A	ShenzhenAerospace ElectronicCo.,Ltd	

Secondary Supply

Part Name	Model Name	supplier	Remark
Memory	NCEMASLD-32G	FORESEE	eMMC5.1 Module,32GB,FBGA-153 Ball
Memory	SU512M32Z11ND2DNP-053BT	SPITECK(SPREADT RUM)	LPDDR4X,16Gb(512 Meg x 32 (2 channels x 16 I/O)),VFBGA-200Ball
Camera	TW-08GC34-KS229-V1	TOWO	GC8034,COB,S0876A
Camera	ST-CFLS051BF-V1.0	Union Image co.,ltd	GC5035,COM
Camera	TW-13OV53-KS230B-V1	TOWO	OV13853,COB,50064B17
Camera	ST-CFKS230-JSBF-V1	Union Image co.,ltd	GC2375H,CSP,DL2002B 10-BP
LCD+TP	EQT651WKF003G	easyquick	FT8006 MLAF065WE51X
fingerprin t	FS22483BJN	HOLITECH	ICNF7332-A2
Battery	LPN385400A	Shenzhen Tianjin New Energy Technology Co., Ltd.	

3. REFERENCE SPECIFICATION

Specification	Version	Title
Part 2.1093	2019	Radiofrequency radiation exposure evaluation: portable devices.
IEEE Std 1528	2013	IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques
KDB 447498 D01	v06	General RF Exposure Guidance
KDB 447498 D02	v02r01	SAR MEASUREMENT PROCEDURES FOR USB DONGLE TRANSMITTERS
KDB 648474 D04	v01r03	Handset SAR
KDB 941225 D01	v03r01	3G SAR Procedures
KDB 248227 D01	v02r02	SAR GUIDANCE FOR IEEE 802.11 (Wi-Fi) TRANSMITTERS
KDB 865664 D01	v01r04	SAR Measurement from 100 MHz to 6 GHz
KDB 865664 D02	v01r02	RF Exposure Reporting
KDB 941225 D05	v02r05	SAR for LTE Devices

4. TEST CONDITIONS

4.1 Picture to demonstrate the required liquid depth

The liquid depth is large than 15cm in the used SAM phantoms in flat section, and the depth of the tissue simulant was 15.0 ± 0.5 cm measured from the ear reference point during system checking and device measurements.



Liquid depth for SAR Measurement

4.2 Test Signal, Frequencies and Output Power

The device was put into operation by using a call tester. Communication between the device and the call tester was established by air link.

The device output power was set to maximum power level for all tests; a fully charged battery was used for every test sequence.

In all operating bands the measurements were performed on middle channel, and few of them were also performed on lowest and highest channels.

4.3 SAR Measurement Set-up

The system is based on a high precision robot (working range greater than 0.9m), which positions the probes with a positional repeatability of better than ± 0.02 mm. Special E-field probes have been developed for measurements close to material discontinuity, the sensors of which are directly loaded with a Schottky diode and connected via highly resistive lines (length =300mm) to the data acquisition unit. A cell controller system contains the power supply, robot controller, teaches pendant (Joystick), and remote control, is used to drive the robot motors.

The PC consists of the Micron Pentium IV computer with Win7 system and SAR Measurement Software DASY5 Professional, A/D interface card, monitor, mouse, and keyboard. The Stäubli Robot is connected to the cell controller to allow software manipulation of the robot.

A data acquisition electronic (DAE) circuit performs the signal amplification; signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. is connected to the Electro-optical coupler (EOC). The EOC performs the conversion from the optical into digital electric signal of the DAE and transfers data to the PC plug-in card. The DAE consists of a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16bit AD-converter and a command decoder and control logic unit. Transmission to the PC-card is accomplished through an optical downlink for data and status information and an optical uplink for commands and clock lines.

The mechanical probe mounting device includes two different sensor systems for frontal and sidewise probe contacts. They are also used for mechanical surface detection and probe collision detection

The robot uses its own controller with a built in VME-bus computer.

4.4 Phantoms

The phantom used for all tests i.e. for both system checks and device testing, was the twin headed "SAM Phantom", manufactured by SPEAG. The phantom conforms to the requirements of IEEE 1528.

System checking was performed using the flat section, whilst Head SAR tests used the left and right head profile sections. Body SAR testing also used the flat section between the head profiles.

The SPEAG device holder was used to position the device in all tests whilst a tripod was used to position the validation dipoles against the flat section of phantom.

4.5 Tissue Simulants

Recommended values for the dielectric parameters of the tissue simulants are given in IEEE 1528. All tests were carried out using simulants whose dielectric parameters were within $\pm 10\%$ below 3GHz and $\pm 5\%$ above 3GHz of the recommended values when use DASY system according to KDB865664D01. All tests were carried out within 24 hours of measuring the dielectric parameters.

Tissue Stimulant Recipes	
Name	Broadband tissue-equivalent liquid
Type	HBBL600-6000V6 Simulating Liquid
Note: The stimulant could be the same for head and body.	

4.6 DESCRIPTION OF THE TEST PROCEDURE

4.6.1 Device Holder

The device was placed in the device holder (illustrated below) that is supplied by SPEAG as an integral part of the Dasy system.



Device holder supplied by SPEAG

4.6.2 Test Exposure Conditions

4.6.2.1 Head Configuration

Measurements were made in “cheek” and “tilt” positions on both the left hand and right-hand sides of the phantom.

The positions used in the measurements were according to IEEE 1528 "IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques".

4.6.2.2 Body Worn Configuration

The device was placed in the SPEAG holder below the flat section of the phantom. The distance between the device and the phantom was kept at the separation distance using a separate flat spacer that was removed before the start of the measurements. And the distance is normally determined according to the actual scene which might be the worst use condition for general exposure. The device's front and rear were oriented facing the phantom since these orientations give higher results for most regular portable devices.

4.6.2.3 Hotspot Configuration

Hotspot mode SAR is measured for all edges and surfaces of the device with a transmitting antenna located within 25 mm from that surface or edge; for the data modes, wireless technologies and frequency bands supporting hotspot mode.

4.6.3 Scan Procedure

First, area scans were used for determination of the field distribution and the approximate location of the local peak SAR values. The SAR distribution is scanned along the inside surface, at least for an area larger than the projection of the handset and antenna. The angle between the probe axis and the surface normal line is recommended but not required to be less than 30°. The SAR distribution is first measured on a 2-D coarse grid. The scan region should cover all areas that are exposed and encompassed by the projection of the handset. There are 15 mm × 15 mm (equal or less than 2GHz), 12 mm × 12 mm (from 2GHz~4GHz) and 10mm x 10mm (from 4GHz~6GHz) measurement grid used when two staggered one-dimensional cubic splines are used to estimate the maximum SAR location.

When the reported 1g-SAR estimated by area scan is less than 1.40 w/kg.

Zoom scan was performed by using the configuration mentioned below or more conservative scan area and step to determine the averaged SAR value. Drift was determined by measuring the same point at the start of the area scan and again at the end of the zoom scan.

Below 3GHz: 32mmX32mmX30mm scan area with 8 mm X8 mm X5 mm steps

2GHz-3GHz: 32mmX32mmX30mm scan area with 8 mm X8 mm X5 mm steps

3GHz-4GHz: 28mmX28mmX28mm scan area with 7 mm X7 mm X4 mm steps

4GHz-5GHz: 25mmX25mmX24mm scan area with 5 mm X5 mm X3 mm steps

5GHz-6GHz: 25mmX25mmX22mm scan area with 5 mm X5 mm X2 mm steps

4.6.4 SAR Averaging Methods

The maximum SAR value was averaged over a cube of tissue using interpolation and extrapolation.

The interpolation, extrapolation and maximum search routines within DASY5 are all based on the modified Quadratic Shepard's method (Robert J. Renka, "Multivariate Interpolation of Large Sets of Scattered Data", University of North Texas ACM Transactions on Mathematical Software, vol. 14, no. 2, June 1988, pp. 139-148).

The interpolation scheme combines a least-square fitted function method with a weighted average method. A triradiate 3-D / bivariate 2-D quadratic function is computed for each measurement point and fitted to neighboring points by a least-square method. For the zoom scan, inverse distance weighting is incorporated to fit distant points more accurately. The interpolating function is finally calculated as a weighted average of the quadratics.

In the zoom scan, the interpolation function is used to extrapolate the Peak SAR from the deepest measurement points to the inner surface of the phantom.


5 RESULT SUMMAR

The maximum reported SAR values for Head configuration and Body Worn configuration are given as follows. The device conforms to the requirements of the standard(s) when the maximum reported SAR value is less than or equal to the limit.

Exposure Position	Frequency Band	Main supply 1g-SAR Result(W/kg)	Secondary Supply 1g-SAR Result(W/kg)	Highest 1g-SAR Result(W/kg)		Limit(W/kg)/1g	Result
Head	GSM 850	0.21	---	1.04			
	GSM 1900	1.04	0.98				
	WCDMA Band II	0.51	---				
	WCDMA Band IV	0.39	---				
	WCDMA Band V	0.15	---				
	LTE Band 2	0.33	---				
	LTE Band 4	0.19	---				
	LTE Band 5	0.13	---				
	LTE Band 7	0.78	---				
	LTE Band 12	0.10	---				
	WLAN 2.4GHz	0.45	---				
	BT/BLE	0.07	---				
Body-Worn (10mm Gap)	GSM 850	0.34	---	0.40	1.04	1.6	Pass
	GSM 1900	0.32	---				
	WCDMA Band II	0.36	---				
	WCDMA Band IV	0.25	---				
	WCDMA Band V	0.27	---				
	LTE Band 2	0.38	---				
	LTE Band 4	0.30	---				
	LTE Band 5	0.22	---				
	LTE Band 7	0.40	0.34				
	LTE Band 12	0.12	---				
	WLAN 2.4GHz	0.19	---				
	BT/BLE	0.03	---				
Hotspot (10mm Gap)	GSM 850	0.34	---	0.40			
	GSM 1900	0.32	---				
	WCDMA Band II	0.36	---				
	WCDMA Band IV	0.25	---				
	WCDMA Band V	0.27	---				
	LTE Band 2	0.38	---				
	LTE Band 4	0.30	---				
	LTE Band 5	0.22	---				
	LTE Band 7	0.40	0.34				
	LTE Band 12	0.19	---				
	WLAN 2.4GHz	0.20	---				

Simultaneous Transmission Summary

Exposure Position	Frequency Band	1g-SAR Result (W/kg)	Highest 1g-SAR Result(W/kg)		Limit (W/kg)/1g	Result
Head	GSM & Wi-Fi	1.25	1.25	1.25	1.6	Pass
	WCDMA & Wi-Fi	0.74				
	LTE & Wi-Fi	1.02				
	GSM & BT/BLE	1.10				
	WCDMA & BT/BLE	0.58				
	LTE & BT/BLE	0.84				
Body-Worn (10mm Gap)	GSM & Wi-Fi	0.54	0.59	1.25	1.6	Pass
	WCDMA & Wi-Fi	0.55				
	LTE & Wi-Fi	0.59				
	GSM & BT/BLE	0.38				
	WCDMA & BT/BLE	0.39				
	LTE & BT/BLE	0.43				
Hotspot (10mm Gap)	GSM & Wi-Fi	0.54	0.59	1.25	1.6	Pass
	WCDMA & Wi-Fi	0.55				
	LTE & Wi-Fi	0.59				

This Test Report Is Approved by: Mr. Peng Zhen 	Review by: Mr. Li Bin 
Tested and issued by: Mr. Chang Tianyu 	Approved date: 2020/03/23

6 TEST RESULT

6.1 Manufacturing Tolerance

GSM

GSM850

Carrier frequency (MHz)	Channel No.	Tolerance (dBm)
824.2	128	29.5~33.5
836.4	189	
848.8	251	

GPRS/EGPRS (GMSK):

Carrier frequency (MHz)	Channel No.	TX Mode	Tolerance (dBm)
824.2	128	4Downlink1uplink	29.5~33.5
836.4	189		
848.8	251		
824.2	128	3Downlink2uplink	27.5~31.5
836.4	189		
848.8	251		
824.2	128	2Downlink3uplink	25.5~29.5
836.4	189		
848.8	251		
824.2	128	1Downlink4uplink	23.5~27.5
836.4	189		
848.8	251		

EGPRS (8PSK):

Carrier frequency (MHz)	Channel No.	TX Mode	Tolerance (dBm)
824.2	128	8PSK 4Downlink1uplink	22.5~26.5
836.4	189		
848.8	251		
824.2	128	8PSK 3Downlink2uplink	21.5~25.5
836.4	189		
848.8	251		
824.2	128	8PSK 2Downlink3uplink	19.0~23.0
836.4	189		
848.8	251		
824.2	128	8PSK 1Downlink4uplink	16.5~20.5
836.4	189		
848.8	251		

PCS1900:

Carrier frequency (MHz)	Channel No.	Tolerance (dBm)
1850.2	512	24.5~28.5
1880.0	661	
1909.8	810	

GPRS/EGPRS (GMSK):

Carrier frequency (MHz)	Channel No.	TX Mode	Tolerance (dBm)
1850.2	512	4Downlink1uplink	24.5~28.5
1880.0	661		
1909.8	810		
1850.2	512	3Downlink2uplink	23.0~27.0
1880.0	661		
1909.8	810		
1850.2	512	2Downlink3uplink	21.5~25.5
1880.0	661		
1909.8	810		
1850.2	512	1Downlink4uplink	20.0~24.0
1880.0	661		
1909.8	810		

EGPRS (8PSK):

Carrier frequency (MHz)	Channel No.	TX Mode	Tolerance (dBm)
1850.2	512	8PSK 4Downlink1uplink	24.5~28.5
1880.0	661		
1909.8	810		
1850.2	512	8PSK 3Downlink2uplink	23.0~27.0
1880.0	661		
1909.8	810		
1850.2	512	8PSK 2Downlink3uplink	21.5~25.5
1880.0	661		
1909.8	810		
1850.2	512	8PSK 1Downlink4uplink	20.0~24.0
1880.0	661		
1909.8	810		

WCDMA

WCDMA band II

Mode		Carrier frequency (MHz)	Channel No.	Tolerance (dBm)
Release 99	RMC,12.2kbps	1852.4	9262	12.5~16.5
		1880.0	9400	
		1907.6	9538	
	RMC,64kbps	1852.4	9262	
		1880.0	9400	
		1907.6	9538	
	RMC,144kbps	1852.4	9262	
		1880.0	9400	
		1907.6	9538	
	RMC,384kbps	1852.4	9262	
		1880.0	9400	
		1907.6	9538	
	AMR,12.2kbps	1852.4	9262	
		1880.0	9400	
		1907.6	9538	
HSDPA	Subtest 1	1852.4	9262	12.0~16.0
		1880.0	9400	
		1907.6	9538	
	Subtest 2	1852.4	9262	
		1880.0	9400	
		1907.6	9538	
	Subtest 3	1852.4	9262	
		1880.0	9400	
		1907.6	9538	
	Subtest 4	1852.4	9262	
		1880.0	9400	
		1907.6	9538	
HSUPA	Subtest 1	1852.4	9262	12.0~16.0
		1880.0	9400	
		1907.6	9538	
	Subtest 2	1852.4	9262	
		1880.0	9400	
		1907.6	9538	
	Subtest 3	1852.4	9262	
		1880.0	9400	
		1907.6	9538	
	Subtest 4	1852.4	9262	
		1880.0	9400	
		1907.6	9538	
	Subtest 5	1852.4	9262	
		1880.0	9400	
		1907.6	9538	

Mode		Carrier frequency (MHz)	Channel No.	Tolerance (dBm)
HSPA+	QPSK	1852.4	9262	12.0~16.0
		1880.0	9400	
		1907.6	9538	
	16QAM	1852.4	9262	
		1880.0	9400	
		1907.6	9538	
DC-HSDPA	Subtest 1	1852.4	9262	12.0~16.0
		1880.0	9400	
		1907.6	9538	
	Subtest 2	1852.4	9262	
		1880.0	9400	
		1907.6	9538	
	Subtest 3	1852.4	9262	
		1880.0	9400	
		1907.6	9538	
	Subtest 4	1852.4	9262	
		1880.0	9400	
		1907.6	9538	

WCDMA band IV

Mode		Carrier frequency (MHz)	Channel No.	Tolerance (dBm)
Release 99	RMC,12.2kbps	1712.4	1312	12.0~16.0
		1732.4	1412	
		1752.6	1513	
	RMC,64kbps	1712.4	1312	
		1732.4	1412	
		1752.6	1513	
	RMC,144kbps	1712.4	1312	
		1732.4	1412	
		1752.6	1513	
	RMC,384kbps	1712.4	1312	
		1732.4	1412	
		1752.6	1513	
	AMR,12.2kbps	1712.4	1312	
		1732.4	1412	
		1752.6	1513	
HSDPA	Subtest 1	1712.4	1312	11.0~15.0
		1732.4	1412	
		1752.6	1513	
	Subtest 2	1712.4	1312	
		1732.4	1412	
		1752.6	1513	
	Subtest 3	1712.4	1312	
		1732.4	1412	
		1752.6	1513	
	Subtest 4	1712.4	1312	
		1732.4	1412	
		1752.6	1513	
HSUPA	Subtest 1	1712.4	1312	11.0~15.0
		1732.4	1412	
		1752.6	1513	
	Subtest 2	1712.4	1312	
		1732.4	1412	
		1752.6	1513	
	Subtest 3	1712.4	1312	
		1732.4	1412	
		1752.6	1513	
	Subtest 4	1712.4	1312	
		1732.4	1412	
		1752.6	1513	
	Subtest 5	1712.4	1312	
		1732.4	1412	
		1752.6	1513	
HSPA+	QPSK	1712.4	1312	11.0~15.0
		1732.4	1412	

Mode		Carrier frequency (MHz)	Channel No.	Tolerance (dBm)
	16QAM	1752.6	1513	
		1712.4	1312	
		1732.4	1412	
		1752.6	1513	
DC-HSDPA	Subtest 1	1712.4	1312	11.0~15.0
		1732.4	1412	
		1752.6	1513	
	Subtest 2	1712.4	1312	
		1732.4	1412	
		1752.6	1513	
	Subtest 3	1712.4	1312	
		1732.4	1412	
		1752.6	1513	
	Subtest 4	1712.4	1312	
		1732.4	1412	
		1752.6	1513	

WCDMA band V

Mode		Carrier frequency (MHz)	Channel No.	RF Power Output (dBm)
Release 99	RMC,12.2kbps	826.4	4132	19.0~23.0
		836.6	4183	
		846.6	4233	
	RMC,64kbps	826.4	4132	
		836.6	4183	
		846.6	4233	
	RMC,144kbps	826.4	4132	
		836.6	4183	
		846.6	4233	
	RMC,384kbps	826.4	4132	
		836.6	4183	
		846.6	4233	
	AMR,12.2kbps	826.4	4132	
		836.6	4183	
		846.6	4233	
HSDPA	Subtest 1	826.4	4132	18.0~22.0
		836.6	4183	
		846.6	4233	
	Subtest 2	826.4	4132	
		836.6	4183	
		846.6	4233	
	Subtest 3	826.4	4132	
		836.6	4183	
		846.6	4233	
	Subtest 4	826.4	4132	
		836.6	4183	
		846.6	4233	
HSUPA	Subtest 1	826.4	4132	18.0~22.0
		836.6	4183	
		846.6	4233	
	Subtest 2	826.4	4132	
		836.6	4183	
		846.6	4233	
	Subtest 3	826.4	4132	
		836.6	4183	
		846.6	4233	
	Subtest 4	826.4	4132	
		836.6	4183	
		846.6	4233	
	Subtest 5	826.4	4132	
		836.6	4183	
		846.6	4233	
HSPA+	QPSK	826.4	9262	18.0~22.0

Mode		Carrier frequency (MHz)	Channel No.	RF Power Output (dBm)
	16QAM	836.6	9400	
		846.6	9538	
		826.4	9262	
		836.6	9400	
		846.6	9538	
DC-HSDPA	Subtest 1	826.4	9262	18.0~22.0
		836.6	9400	
		846.6	9538	
	Subtest 2	826.4	9262	
		836.6	9400	
		846.6	9538	
	Subtest 3	826.4	9262	
		836.6	9400	
		846.6	9538	
	Subtest 4	826.4	9262	
		836.6	9400	
		846.6	9538	

LTE

Note: RB allocation mentioned below is for all Bandwidths, and the Frequency Range are divided to 3 ranges (Low, Mid, High)

Band 2

BW	Modulation	RB allocation with different offset	Frequency range	Tolerance (dBm)
All Bandwidth	QPSK	1	Low	13.0~17.0
			Mid	
			High	
		50%	Low	12.0~16.0
			Mid	
			High	
		100%	Low	12.0~16.0
			Mid	
			High	
	16QAM	1	Low	12.5~16.5
			Mid	
			High	
		50%	Low	11.5~15.5
			Mid	
			High	
		100%	Low	11.5~15.5
			Mid	
			High	
	64QAM	1	Low	12.5~16.5
			Mid	
			High	
		50%	Low	11.5~15.5
			Mid	
			High	
		100%	Low	11.5~15.5
			Mid	
			High	

Band 4

BW	Modulation	RB allocation with different offset	Frequency range	Tolerance (dBm)
All Bandwidth	QPSK	1	Low	13.0~17.0
			Mid	
			High	
		50%	Low	12.0~16.0
			Mid	
			High	
		100%	Low	11.5~15.5
			Mid	
			High	
	16QAM	1	Low	12.5~16.5
			Mid	
			High	
		50%	Low	12.0~16.0
			Mid	
			High	
		100%	Low	11.5~15.5
			Mid	
			High	
	64QAM	1	Low	12.5~16.5
			Mid	
			High	
		50%	Low	12.0~16.0
			Mid	
			High	
		100%	Low	11.5~15.5
			Mid	
			High	

Band 5

BW	Modulation	RB allocation with different offset	Frequency range	Tolerance (dBm)
All Bandwidth	QPSK	1	Low	19.0~23.0
			Mid	
			High	
		50%	Low	18.5~22.5
			Mid	
			High	
		100%	Low	18.5~22.5
			Mid	
			High	
	16QAM	1	Low	19.0~23.0
			Mid	
			High	
		50%	Low	18.5~22.5
			Mid	
			High	
		100%	Low	18.5~22.5
			Mid	
			High	
	64QAM	1	Low	19.0~23.0
			Mid	
			High	
		50%	Low	18.5~22.5
			Mid	
			High	
		100%	Low	18.5~22.5
			Mid	
			High	

Band 7

BW	Modulation	RB allocation with different offset	Frequency range	Tolerance (dBm)
All Bandwidth	QPSK	1	Low	11.5~15.5
			Mid	
			High	
		50%	Low	11.0~15.0
			Mid	
			High	
		100%	Low	11.0~15.0
			Mid	
			High	
	16QAM	1	Low	11.5~15.5
			Mid	
			High	
		50%	Low	11.0~15.0
			Mid	
			High	
		100%	Low	11.0~15.0
			Mid	
			High	
	64QAM	1	Low	11.5~15.5
			Mid	
			High	
		50%	Low	11.0~15.0
			Mid	
			High	
		100%	Low	11.0~15.0
			Mid	
			High	

Band 12

BW	Modulation	RB allocation with different offset	Frequency range	Tolerance (dBm)
All Bandwidth	QPSK	1	Low	19.0~23.0
			Mid	
			High	
		50%	Low	18.5~22.5
			Mid	
			High	
		100%	Low	18.5~22.5
			Mid	
			High	
	16QAM	1	Low	19.0~23.0
			Mid	
			High	
		50%	Low	18.5~22.5
			Mid	
			High	
		100%	Low	18.5~22.5
			Mid	
			High	
	64QAM	1	Low	19.0~23.0
			Mid	
			High	
		50%	Low	18.5~22.5
			Mid	
			High	
		100%	Low	18.5~22.5
			Mid	
			High	

Bluetooth

Modulation type	Tolerance (dBm)		
	2402MHz(Ch0)	2441MHz(Ch39)	2480MHz(Ch78)
GFSK	-2.0~2.0		
$\pi/4$ DQPSK	-2.0~2.0		
8DPSK	-2.0~2.0		

Bluetooth (BLE)

Modulation type	Average Power Output (dBm)		
	2402MHz (Ch0)	2440MHz (Ch19)	2480MHz (Ch39)
GFSK (LE 1Mbps)	-4.0~0.0		

WLAN 2.4GHz

Modulation type	Tolerance (dBm)		
	2412MHz	2437MHz	2462MHz
11b	13.5~17.5		
11g	14.0~18.0		
11n HT20	13.0~17.0		

6.2 GSM Measurement result

GSM850

GSM Measured Power:

Carrier frequency (MHz)	Channel No.	RF Power Output (dBm)	Frame average power(dBm)
824.2	128	33.26	24.23
836.4	189	33.15	24.12
848.8	251	33.14	24.11

GPRS/EGPRS (GMSK) Measured Power:

Carrier frequency (MHz)	Channel No.	TX Mode	RF Power Output (dBm)	Frame average power(dBm)
824.2	128	4Downlink1uplink	33.26	24.23
836.4	189		33.15	24.12
848.8	251		33.14	24.11
824.2	128	3Downlink2uplink	31.18	25.16
836.4	189		31.05	25.03
848.8	251		30.93	24.91
824.2	128	2Downlink3uplink	29.27	25.01
836.4	189		29.14	24.88
848.8	251		29.04	24.78
824.2	128	1Downlink4uplink	27.14	24.13
836.4	189		27.06	24.05
848.8	251		26.98	23.97

EGPRS (8PSK) Measured Power:

Carrier frequency (MHz)	Channel No.	TX Mode	RF Power Output (dBm)	Frame average power(dBm)
824.2	128	8PSK 4Downlink1uplink	26.31	17.28
836.4	189		26.56	17.53
848.8	251		26.41	17.38
824.2	128	8PSK 3Downlink2uplink	25.25	19.23
836.4	189		25.32	19.30
848.8	251		25.14	19.12
824.2	128	8PSK 2Downlink3uplink	22.75	18.49
836.4	189		22.84	18.58
848.8	251		22.68	18.42
824.2	128	8PSK 1Downlink4uplink	20.43	17.42
836.4	189		20.48	17.47
848.8	251		20.16	17.15

PCS1900

GSM Measured Power:

Carrier frequency (MHz)	Channel No.	RF Power Output (dBm)	Frame average power(dBm)
1850.2	512	28.14	19.11
1880.0	661	28.13	19.10
1909.8	810	28.15	19.12

GPRS/EGPRS (GMSK) Measured Power:

Carrier frequency (MHz)	Channel No.	TX Mode	RF Power Output (dBm)	Frame average power(dBm)
1850.2	512	4Downlink1uplink	28.14	19.11
1880.0	661		28.01	18.98
1909.8	810		28.00	18.97
1850.2	512	3Downlink2uplink	26.97	20.95
1880.0	661		26.79	20.77
1909.8	810		26.72	20.70
1850.2	512	2Downlink3uplink	25.40	21.14
1880.0	661		25.21	20.95
1909.8	810		25.11	20.85
1850.2	512	1Downlink4uplink	23.81	20.80
1880.0	661		23.65	20.64
1909.8	810		23.52	20.51

EGPRS (8PSK) Measured Power:

Carrier frequency (MHz)	Channel No.	TX Mode	RF Power Output (dBm)	Frame average power(dBm)
1850.2	512	8PSK 4Downlink1uplink	28.10	19.07
1880.0	661		28.03	19.00
1909.8	810		27.97	18.94
1850.2	512	8PSK 3Downlink2uplink	26.91	20.89
1880.0	661		26.79	20.77
1909.8	810		26.67	20.65
1850.2	512	8PSK 2Downlink3uplink	25.32	21.06
1880.0	661		25.21	20.95
1909.8	810		25.04	20.78
1850.2	512	8PSK 1Downlink4uplink	23.78	20.77
1880.0	661		23.65	20.64
1909.8	810		23.50	20.49

Division Factors (for Measured Power and Frame Average Power):

To average the power, the division factor is as follows:

1TX-slot (1uplink) = 1 transmit time slot out of 8 time slots=> conducted power divided by (8/1) => -9.03dB

2TX-slots(2uplink) = 2 transmit time slots out of 8 time slots=> conducted power divided by (8/2) => -6.02dB

3TX-slots (3uplink) = 3 transmit time slots out of 8 time slots=> conducted power divided by (8/3) => -4.26dB

4TX-slots (4uplink) = 4 transmit time slots out of 8 time slots=> conducted power divided by (8/4) => -3.01dB

According to the frame average conducted power, Body-worn SAR measurements are performed with **2Txslots (2uplink)** of GPRS850 (GMSK) and **3Txslots (3uplink)** of GPRS1900 (GMSK).

6.3 WCDMA Measurement result

Release 99

The following procedures are according to FCC KDB Publication 941225 D01.

The following tests were completed according to the test requirements outlined in section 5.2 of the 3GPP TS34.121-1 specification. The DUT supports power Class 3, which has a nominal maximum output power of 24 dBm (+1.7/-3.7).

Mode	Subtest	Rel99
WCDMA General Settings	Loopback Mode	Test Mode 1
	RMC mode AMR mode	12.2kbps RMC 12.2kbps RMC in 3.4 kbps SRB
	Power Control Algorithm	Algorithm2
	β_c/β_d	8/15

Release 5

The following 4 Sub-tests were completed according to Release 5 procedures in section 5.2 of 3GPP TS34.121.

Sub-test	β_c	β_d	β_d (SF)	β_c/β_d	$\beta_{hs}^{(1)}$	CM(dB) ⁽²⁾
1	2/15	15/15	64	2/15	4/15	0.0
2	12/15 ⁽³⁾	15/15 ⁽³⁾	64	12/15 ⁽³⁾	24/15	1.0
3	15/15	8/15	64	15/18	30/15	1.5
4	15/15	4/15	64	15/4	30/15	1.5

Note1: Δ_{ACK} , Δ_{NACK} and $\Delta_{CQI} = 8 \Leftrightarrow A_{hs} = \beta_{hs}/\beta_c = 30/15 \Leftrightarrow \beta_{hs} = 30/15 * \beta_c$.

Note2: CM=1 for $\beta_c/\beta_d = 12/15$, $\beta_{hs}/\beta_c = 24/15$.

Note3: For subtest 2 the β_c/β_d ratio of 12/15 for the TFC during the measurement period(TF1,TF0) is achieved by setting the signaled gain factors for the reference TFC(TF1,TF1) to $\beta_c = 11/15$ and $\beta_d = 15/15$.

Release 6

The following 5 Sub-tests were completed according to Release 6 procedures in section 5.2 of 3GPP TS34.121.

Sub-test	β_c	β_d	β_d (S F)	β_c/β_d	$\beta_{hs}^{(1)}$	β_{ec}	β_{ed}	β_{ed} (S F)	β_{ed} (code s)	CM ⁽²⁾ (dB)	MP R (dB)	AG ⁽⁴⁾ Index	E-TF CI
1	11/15 ⁽³⁾	15/15 ⁽³⁾	64	11/15 ⁽³⁾	22/15	209/25	1039/25	4	1	1.0	2.0	20	75
2	6/15	15/15	64	6/15	12/15	12/15	94/75	4	1	3.0	2.0	12	67
3	15/15	9/15	64	15/9	30/15	30/15	$\beta_{ed1}:47/15$ $\beta_{ed2}:47/15$	4	2	2.0	2.0	15	92
4	2/15	15/15	64	2/15	4/15	2/15	56/75	4	1	3.0	2.0	17	71
5	15/15 ⁽⁴⁾	15/15 ⁽⁴⁾	64	15/15 ⁽⁴⁾	30/15	24/15	134/15	4	1	1.0	2.0	21	81

Note1: Δ_{ACK} , Δ_{NACK} and $\Delta_{CQI} = 8 \Leftrightarrow A_{hs} = \beta_{hs}/\beta_c = 30/15 \Leftrightarrow \beta_{hs} = 30/15 * \beta_c$.

Note2: CM=1 for $\beta_c/\beta_d = 12/15$, $\beta_{hs}/\beta_c = 24/15$. For all other combinations of DPDCH, DPCCH, HS-DPCCH, E-DPDCH and E-DPCCH the MPR is based on the relative CM difference.

Note3: For subtest 1 the β_c/β_d ratio of 11/15 for the TFC during the measurement period(TF1,TF0) is achieved by setting the signaled gain factors for the reference TFC(TF1,TF1) to $\beta_c=10/15$ and $\beta_d=15/15$.

Note4: For subtest 5 the β_c/β_d ratio of 15/15 for the TFC during the measurement period(TF1,TF0) is achieved by setting the signaled gain factors for the reference TFC(TF1,TF1) to $\beta_c=14/15$ and $\beta_d=15/15$.

NOTE5: Testing UE using E-DPDCH Physical layer category 1 Sub-test 3 is not required according to TS 25.306 Table 5.1g.

NOTE6: β_{ed} can not be set directly; it is set by Absolute Grant Value.

Release 7

The following 1 Sub-test was completed according to Release 7 procedures in section 5.2 of 3GPP TS34.121.

Table C.11.1.4: β values for transmitter characteristics tests with HS-DPCCH and E-DCH with 16QAM

Sub-test	β_c (Note 3)	β_d	β_{HS} (Note 1)	β_{ec}	β_{ed} (2xSF2) (Note 4)	β_{ed} (2xSF4) (Note 4)	CM (dB) (Note 2)	MPR (dB) (Note 2)	AG Index (Note 4)	E-TFCI (Note 5)	E-TFCI (boost)
1	1	0	30/15	30/15	β_{ed1} : 30/15 β_{ed2} : 30/15	β_{ed3} : 24/15 β_{ed4} : 24/15	3.5	2.5	14	105	105

Note 1: Δ_{ACK} , Δ_{NACK} and $\Delta_{CQI} = 30/15$ with $\beta_{hs} = 30/15 * \beta_c$.

Note 2: CM = 3.5 and the MPR is based on the relative CM difference, MPR = MAX(CM-1,0).

Note 3: DPDCH is not configured, therefore the β_c is set to 1 and $\beta_d = 0$ by default.

Note 4: β_{ed} can not be set directly; it is set by Absolute Grant Value.

Note 5: All the sub-tests require the UE to transmit 2SF2+2SF4 16QAM EDCH and they apply for UE using E-DPDCH category 7. E-DCH TTI is set to 2ms TTI and E-DCH table index = 2. To support these E-DCH configurations DPDCH is not allocated. The UE is signalled to use the extrapolation algorithm.

Release 8

Table E.5.0: Levels for HSDPA connection setup

Parameter During Connection setup	Unit	Value
P-CPICH_Ec/Ior	dB	-10
P-CCPCH and SCH_Ec/Ior	dB	-12
PICH_Ec/Ior	dB	-15
HS-PDSCH	dB	off
HS-SCCH_1	dB	off
DPCH_Ec/Ior	dB	-5
OCNS_Ec/Ior	dB	-3.1

Table C.8.1.12: Fixed Reference Channel H-Set 12

Parameter	Unit	Value
Nominal Avg. Inf. Bit Rate	kbps	60
Inter-TTI Distance	TTI's	1
Number of HARQ Processes	Processes	6
Information Bit Payload (N_{INF})	Bits	120
Number Code Blocks	Blocks	1
Binary Channel Bits Per TTI	Bits	960
Total Available SML's in UE	SML's	19200
Number of SML's per HARQ Proc.	SML's	3200
Coding Rate		0.15
Number of Physical Channel Codes	Codes	1
Modulation		QPSK

Note 1: The RMC is intended to be used for DC-HSDPA mode and both cells shall transmit with identical parameters as listed in the table.

Note 2: Maximum number of transmission is limited to 1, i.e., retransmission is not allowed. The redundancy and constellation version 0 shall be used.

Inf. Bit Payload

CRC Addition CRC

Code Block Segmentation

Turbo-Encoding (R=1/3) Tail Bits

1st Rate Matching

RV Selection

Physical Channel Segmentation

Figure C.8.19: Coding rate for Fixed reference Channel H-Set 12 (QPSK)

The following 4 Sub-tests for HSDPA were completed according to Release 8 procedures in section 5.2 of 3GPP TS34.121.

Sub-test	β_c	β_d	β_d (SF)	β_c/β_d	$\beta_{hs}^{(1)}$	CM(dB) ⁽²⁾
1	2/15	15/15	64	2/15	4/15	0.0
2	12/15 ⁽³⁾	15/15 ⁽³⁾	64	12/15 ⁽³⁾	24/15	1.0
3	15/15	8/15	64	15/18	30/15	1.5
4	15/15	4/15	64	15/4	30/15	1.5

Note1: Δ_{ACK} , Δ_{NACK} and $\Delta_{CQI} = 8 \Leftrightarrow A_{hs} = \beta_{hs}/\beta_c = 30/15 \Leftrightarrow \beta_{hs} = 30/15 * \beta_c$.

Note2: CM=1 for $\beta_c/\beta_d = 12/15$, $\beta_{hs}/\beta_c = 24/15$.

Note3: For subtest 2 the β_c/β_d ratio of 12/15 for the TFC during the measurement period(TF1,TF0) is achieved by setting the signaled gain factors for the reference TFC(TF1,TF1) to $\beta_c = 11/15$ and $\beta_d = 15/15$.

WCDMA band II

Mode		Carrier frequency (MHz)	Channel No.	RF Power Output (dBm)
Release 99	RMC,12.2kbps	1852.4	9262	16.25
		1880.0	9400	16.21
		1907.6	9538	16.13
	RMC,64kbps	1852.4	9262	16.25
		1880.0	9400	16.18
		1907.6	9538	16.08
	RMC,144kbps	1852.4	9262	16.23
		1880.0	9400	16.14
		1907.6	9538	16.12
	RMC,384kbps	1852.4	9262	16.19
		1880.0	9400	16.15
		1907.6	9538	16.05
	AMR,12.2kbps	1852.4	9262	16.20
		1880.0	9400	16.16
		1907.6	9538	16.11
HSDPA	Subtest 1	1852.4	9262	15.23
		1880.0	9400	15.45
		1907.6	9538	15.25
	Subtest 2	1852.4	9262	15.10
		1880.0	9400	15.11
		1907.6	9538	15.27
	Subtest 3	1852.4	9262	15.18
		1880.0	9400	15.26
		1907.6	9538	15.41
	Subtest 4	1852.4	9262	15.14
		1880.0	9400	15.30
		1907.6	9538	15.15
HSUPA	Subtest 1	1852.4	9262	15.30
		1880.0	9400	15.30
		1907.6	9538	15.38

Mode		Carrier frequency (MHz)	Channel No.	RF Power Output (dBm)
	Subtest 2	1852.4	9262	15.33
		1880.0	9400	15.36
		1907.6	9538	15.42
	Subtest 3	1852.4	9262	15.22
		1880.0	9400	15.10
		1907.6	9538	15.17
	Subtest 4	1852.4	9262	15.45
		1880.0	9400	15.15
		1907.6	9538	15.20
	Subtest 5	1852.4	9262	15.10
		1880.0	9400	15.13
		1907.6	9538	15.14
HSPA+	QPSK	1852.4	9262	15.38
		1880.0	9400	15.09
		1907.6	9538	15.40
	16QAM	1852.4	9262	15.15
		1880.0	9400	15.32
		1907.6	9538	15.20
DC-HSDPA	Subtest 1	1852.4	9262	15.43
		1880.0	9400	15.45
		1907.6	9538	15.09
	Subtest 2	1852.4	9262	15.25
		1880.0	9400	15.24
		1907.6	9538	15.36
	Subtest 3	1852.4	9262	15.33
		1880.0	9400	15.31
		1907.6	9538	15.28
	Subtest 4	1852.4	9262	15.08
		1880.0	9400	15.42
		1907.6	9538	15.22

WCDMA band IV

Mode		Carrier frequency (MHz)	Channel No.	RF Power Output (dBm)
Release 99	RMC,12.2kbps	1712.4	1312	15.85
		1732.4	1412	15.90
		1752.6	1513	15.95
	RMC,64kbps	1712.4	1312	15.81
		1732.4	1412	15.84
		1752.6	1513	15.90
	RMC,144kbps	1712.4	1312	15.81
		1732.4	1412	15.82
		1752.6	1513	15.86
	RMC,384kbps	1712.4	1312	15.84
		1732.4	1412	15.82
		1752.6	1513	15.94
	AMR,12.2kbps	1712.4	1312	15.80
1732.4		1412	15.87	
1752.6		1513	15.88	
HSDPA	Subtest 1	1712.4	1312	14.63
		1732.4	1412	14.74
		1752.6	1513	14.69
	Subtest 2	1712.4	1312	14.64
		1732.4	1412	14.59
		1752.6	1513	14.69
	Subtest 3	1712.4	1312	14.69
		1732.4	1412	14.74
		1752.6	1513	14.73
Subtest 4	1712.4	1312	14.69	
	1732.4	1412	14.58	
	1752.6	1513	14.60	
HSUPA	Subtest 1	1712.4	1312	14.62
		1732.4	1412	14.70
		1752.6	1513	14.60
	Subtest 2	1712.4	1312	14.71
		1732.4	1412	14.66
		1752.6	1513	14.64
	Subtest 3	1712.4	1312	14.63
		1732.4	1412	14.64
		1752.6	1513	14.63
	Subtest 4	1712.4	1312	14.63
		1732.4	1412	14.62
		1752.6	1513	14.75
Subtest 5	1712.4	1312	14.73	
	1732.4	1412	14.73	
	1752.6	1513	14.64	
HSPA+	QPSK	1712.4	1312	14.75
		1732.4	1412	14.69

Mode		Carrier frequency (MHz)	Channel No.	RF Power Output (dBm)
	16QAM	1752.6	1513	14.73
		1712.4	1312	14.59
		1732.4	1412	14.75
		1752.6	1513	14.66
DC-HSDPA	Subtest 1	1712.4	1312	14.69
		1732.4	1412	14.60
		1752.6	1513	14.61
	Subtest 2	1712.4	1312	14.64
		1732.4	1412	14.68
		1752.6	1513	14.65
	Subtest 3	1712.4	1312	14.68
		1732.4	1412	14.73
		1752.6	1513	14.63
	Subtest 4	1712.4	1312	14.59
		1732.4	1412	14.69
		1752.6	1513	14.74

WCDMA band V

Mode		Carrier frequency (MHz)	Channel No.	RF Power Output (dBm)
Release 99	RMC,12.2kbps	826.4	4132	22.66
		836.6	4183	22.59
		846.6	4233	22.70
	RMC,64kbps	826.4	4132	22.60
		836.6	4183	22.53
		846.6	4233	22.68
	RMC,144kbps	826.4	4132	22.57
		836.6	4183	22.55
		846.6	4233	22.64
	RMC,384kbps	826.4	4132	22.59
		836.6	4183	22.56
		846.6	4233	22.63
HSDPA	AMR,12.2kbps	826.4	4132	22.62
		836.6	4183	22.50
		846.6	4233	22.62
	Subtest 1	826.4	4132	21.72
		836.6	4183	21.66
		846.6	4233	21.65
	Subtest 2	826.4	4132	21.63
		836.6	4183	21.68
		846.6	4233	21.60
	Subtest 3	826.4	4132	21.70
		836.6	4183	21.60
		846.6	4233	21.72
	Subtest 4	826.4	4132	21.65


Mode		Carrier frequency (MHz)	Channel No.	RF Power Output (dBm)
HSUPA		836.6	4183	21.59
		846.6	4233	21.60
	Subtest 1	826.4	4132	21.66
		836.6	4183	21.68
		846.6	4233	21.58
		826.4	4132	21.74
	Subtest 2	836.6	4183	21.70
		846.6	4233	21.62
		826.4	4132	21.60
		836.6	4183	21.68
	Subtest 3	846.6	4233	21.75
		826.4	4132	21.64
		836.6	4183	21.69
		846.6	4233	21.59
	Subtest 4	826.4	4132	21.74
		836.6	4183	21.64
		846.6	4233	21.65
		826.4	4132	21.71
	QPSK	836.6	9400	21.72
		846.6	9538	21.70
		826.4	9262	21.63
		836.6	9400	21.61
	16QAM	846.6	9538	21.62
		826.4	9262	21.71
DC-HSDPA		836.6	9400	21.74
		846.6	9538	21.69
	Subtest 1	826.4	9262	21.73
		836.6	9400	21.60
		846.6	9538	21.65
		826.4	9262	21.66
	Subtest 2	836.6	9400	21.60
		846.6	9538	21.67
		826.4	9262	21.63
		836.6	9400	21.59
	Subtest 3	846.6	9538	21.73
		826.4	9262	21.63

Note: UMTS SAR was tested under Rel.99 RMC 12.2kbps mode per KDB Publication 941225 D01. for other higher release configuration, SAR was not required since any average output power was not more than 0.25 dB higher than the RMC level and SAR was less than 1.2 W/kg with RMC mode.

6.4 LTE Measurement result

General description:

TDD-LTE frame structure



Uplink-downlink configuration

Uplink-downlink configuration	Downlink-to-Uplink Switch-point periodicity	Subframe number									
		0	1	2	3	4	5	6	7	8	9
0	5 ms	D	S	U	U	U	D	S	U	U	U
1	5 ms	D	S	U	U	D	D	S	U	U	D
2	5 ms	D	S	U	D	D	D	S	U	D	D
3	10 ms	D	S	U	U	U	D	D	D	D	D
4	10 ms	D	S	U	U	D	D	D	D	D	D
5	10 ms	D	S	U	D	D	D	D	D	D	D
6	5 ms	D	S	U	U	U	D	S	U	U	D

Special sub-frame configuration

Special subframe configuration	Normal cyclic prefix in downlink			Extended cyclic prefix in downlink		
	DwPTS	UpPTS		DwPTS	UpPTS	
		Normal cyclic prefix in uplink	Extended cyclic prefix in uplink		Normal cyclic prefix in uplink	Extended cyclic prefix in uplink
0	$6592 \cdot T_s$	$2192 \cdot T_s$	$2560 \cdot T_s$	$7680 \cdot T_s$	$2192 \cdot T_s$	$2560 \cdot T_s$
1	$19760 \cdot T_s$			$20480 \cdot T_s$		
2	$21952 \cdot T_s$			$23040 \cdot T_s$		
3	$24144 \cdot T_s$			$25600 \cdot T_s$		
4	$26336 \cdot T_s$	$4384 \cdot T_s$	$5120 \cdot T_s$	$7680 \cdot T_s$	$4384 \cdot T_s$	$5120 \cdot T_s$
5	$6592 \cdot T_s$			$20480 \cdot T_s$		
6	$19760 \cdot T_s$			$23040 \cdot T_s$		
7	$21952 \cdot T_s$			-	-	-
8	$24144 \cdot T_s$			-	-	-

Special sub-frame with cyclic prefix uplink

Special sub-frame configuration		Duty factor with normal cyclic prefix in uplink	Duty factor with extended cyclic prefix in uplink
Normal cyclic prefix in downlink	0~4	7.13%	8.33%
	5~9	14.3%	16.7%
Extended cyclic prefix in downlink	0~3	7.13%	8.33%
	4~7	14.3%	16.7%

So we perform SAR test with maximum duty factor equal to 63.3% by using uplink-downlink configuration 0.

Note: One sub-frame is $30720T_s=1\text{ms}$, when UpPTS(uplink) in special sub-frame with extended cyclic prefix, duty factor = $5120/30720=0.167$. There are 5 sub-frames in half frame(3up link), so the final duty factor is $(30720 \cdot 3 + 5120) / (30720 \cdot 5) = 63.3\%$ which we used to evaluate the SAR compliance (worst case)

LTE Band 2

Modulation	Carrier frequency (MHz)	UL Channel	BW	RB Size	RB Offset	Conducted power (dBm)
QPSK	1850.7	18607	1.4	1	0	16.44
				1	5	16.29
				3	2	15.85
				6	0	15.68
	1880	18900		1	0	16.46
				1	5	16.50
				3	2	15.76
				6	0	15.75
	1909.3	19193		1	0	16.43
				1	5	16.50
				3	2	15.66
				6	0	15.39
16QAM	1850.7	18607	1.4	1	0	16.24
				1	5	16.31
				3	2	15.02
				6	0	14.89
	1880	18900		1	0	15.83
				1	5	15.83
				3	2	14.95
				6	0	14.87
	1909.3	19193		1	0	16.24
				1	5	16.30
				3	2	14.83
				6	0	14.79
64QAM	1850.7	18607	1.4	1	0	16.17
				1	5	16.22
				3	2	15.10
				6	0	14.84
	1880	18900		1	0	15.65
				1	5	15.66
				3	2	14.90
				6	0	14.88
	1909.3	19193		1	0	16.10
				1	5	16.11
				3	2	14.83
				6	0	14.79

Modulation	Carrier frequency (MHz)	UL Channel	BW	RB Size	RB Offset	Conducted power (dBm)
QPSK	1851.5	18615	3	1	0	16.36
				1	14	16.34
				8	4	15.73
				15	0	15.73
	1880	18900		1	0	16.57
				1	14	16.55
				8	4	15.83
				15	0	15.80
	1908.5	19185		1	0	16.42
				1	14	16.45
				8	4	15.65
				15	0	15.46
16QAM	1851.5	18615	3	1	0	16.22
				1	14	16.23
				8	4	14.91
				15	0	14.88
	1880	18900		1	0	15.79
				1	14	15.77
				8	4	14.85
				15	0	14.94
	1908.5	19185		1	0	16.37
				1	14	16.23
				8	4	14.90
				15	0	14.86
64QAM	1851.5	18615	3	1	0	16.22
				1	14	16.19
				8	4	15.09
				15	0	14.88
	1880	18900		1	0	15.67
				1	14	15.74
				8	4	14.86
				15	0	14.82
	1908.5	19185		1	0	16.03
				1	14	16.03
				8	4	14.84
				15	0	14.85

Modulation	Carrier frequency (MHz)	UL Channel	BW	RB Size	RB Offset	Conducted power (dBm)
QPSK	1852.5	18625	5	1	0	16.35
				1	24	16.38
				12	6	15.78
				25	0	15.69
	1880	18900		1	0	16.49
				1	24	16.54
				12	6	15.83
				25	0	15.77
	1907.5	19175		1	0	16.40
				1	24	16.46
				12	6	15.57
				25	0	15.52
16QAM	1852.5	18625	5	1	0	16.22
				1	24	16.29
				12	6	14.95
				25	0	14.87
	1880	18900		1	0	15.80
				1	24	15.78
				12	6	14.95
				25	0	14.91
	1907.5	19175		1	0	16.31
				1	24	16.26
				12	6	14.82
				25	0	14.78
64QAM	1852.5	18625	5	1	0	16.16
				1	24	16.14
				12	6	14.99
				25	0	14.84
	1880	18900		1	0	15.72
				1	24	15.67
				12	6	14.81
				25	0	14.80
	1907.5	19175		1	0	16.06
				1	24	16.06
				12	6	14.84
				25	0	14.78

Modulation	Carrier frequency (MHz)	UL Channel	BW	RB Size	RB Offset	Conducted power (dBm)
QPSK	1855	18650	10	1	0	16.29
				1	49	16.42
				24	12	15.82
				50	0	15.73
	1880	18900		1	0	16.49
				1	49	16.61
				24	12	15.77
				50	0	15.77
	1905	19150		1	0	16.50
				1	49	16.50
				24	12	15.67
				50	0	15.42
16QAM	1855	18650	10	1	0	16.25
				1	49	16.26
				24	12	14.94
				50	0	14.87
	1880	18900		1	0	15.81
				1	49	15.83
				24	12	14.88
				50	0	14.87
	1905	19150		1	0	16.27
				1	49	16.28
				24	12	14.79
				50	0	14.77
64QAM	1855	18650	10	1	0	16.18
				1	49	16.13
				24	12	15.09
				50	0	14.83
	1880	18900		1	0	15.70
				1	49	15.67
				24	12	14.93
				50	0	14.78
	1905	19150		1	0	16.09
				1	49	16.04
				24	12	14.83
				50	0	14.79

Modulation	Carrier frequency (MHz)	UL Channel	BW	RB Size	RB Offset	Conducted power (dBm)
QPSK	1857.5	18675	15	1	0	16.36
				1	74	16.35
				40	18	15.71
				75	0	15.79
	1880	18900		1	0	16.55
				1	74	16.60
				40	18	15.82
				75	0	15.75
	1902.5	19125		1	0	16.48
				1	74	16.42
				40	18	15.62
				75	0	15.45
16QAM	1857.5	18675	15	1	0	16.22
				1	74	16.32
				40	18	14.93
				75	0	14.91
	1880	18900		1	0	15.82
				1	74	15.73
				40	18	14.85
				75	0	14.97
	1902.5	19125		1	0	16.26
				1	74	16.31
				40	18	14.76
				75	0	14.88
64QAM	1857.5	18675	15	1	0	16.22
				1	74	16.22
				40	18	15.00
				75	0	14.84
	1880	18900		1	0	15.78
				1	74	15.73
				40	18	14.88
				75	0	14.80
	1902.5	19125		1	0	16.11
				1	74	16.11
				40	18	14.81
				75	0	14.74

Modulation	Carrier frequency (MHz)	UL Channel	BW	RB Size	RB Offset	Conducted power (dBm)
QPSK	1860	18700	20	1	0	16.44
				1	99	16.44
				50	25	15.86
				100	0	15.83
	1880	18900		1	0	16.61
				1	99	16.61
				50	25	15.90
				100	0	15.89
	1900	19100		1	0	16.55
				1	99	16.55
				50	25	15.69
				100	0	15.53
16QAM	1860	18700	20	1	0	16.34
				1	99	16.34
				50	25	15.02
				100	0	14.95
	1880	18900		1	0	15.85
				1	99	15.85
				50	25	14.99
				100	0	14.97
	1900	19100		1	0	16.37
				1	99	16.37
				50	25	14.90
				100	0	14.89
64QAM	1860	18700	20	1	0	16.24
				1	99	16.24
				50	25	15.12
				100	0	14.94
	1880	18900		1	0	15.79
				1	99	15.79
				50	25	14.93
				100	0	14.92
	1900	19100		1	0	16.17
				1	99	16.17
				50	25	14.87
				100	0	14.86

LTE Band 4

Modulation	Carrier frequency (MHz)	UL Channel	BW	RB Size	RB Offset	Conducted power (dBm)
QPSK	1710.7	19957	1.4	1	0	16.44
				1	5	16.48
				3	2	15.59
				6	0	15.51
	1732.5	20175		1	0	16.40
				1	5	16.49
				3	2	15.43
				6	0	15.35
	1754.3	20393		1	0	16.14
				1	5	16.14
				3	2	15.47
				6	0	15.34
16QAM	1710.7	19957	1.4	1	0	16.01
				1	5	15.98
				3	2	14.61
				6	0	14.62
	1732.5	20175		1	0	16.13
				1	5	16.18
				3	2	14.59
				6	0	14.59
	1754.3	20393		1	0	15.98
				1	5	15.98
				3	2	14.71
				6	0	14.55
64QAM	1710.7	19957	1.4	1	0	15.95
				1	5	15.97
				3	2	14.38
				6	0	14.45
	1732.5	20175		1	0	15.97
				1	5	15.96
				3	2	14.59
				6	0	14.58
	1754.3	20393		1	0	16.03
				1	5	16.04
				3	2	14.57
				6	0	14.59

Modulation	Carrier frequency (MHz)	UL Channel	BW	RB Size	RB Offset	Conducted power (dBm)
QPSK	1711.5	19965	3	1	0	16.54
				1	14	16.51
				8	4	15.66
				15	0	15.51
	1732.5	20175		1	0	16.50
				1	14	16.49
				8	4	15.46
				15	0	15.36
	1753.5	20385		1	0	16.14
				1	14	16.13
				8	4	15.43
				15	0	15.38
16QAM	1711.5	19965	3	1	0	15.91
				1	14	16.02
				8	4	14.50
				15	0	14.58
	1732.5	20175		1	0	16.07
				1	14	16.14
				8	4	14.60
				15	0	14.48
	1753.5	20385		1	0	15.99
				1	14	16.03
				8	4	14.66
				15	0	14.59
64QAM	1711.5	19965	3	1	0	15.85
				1	14	15.85
				8	4	14.46
				15	0	14.39
	1732.5	20175		1	0	15.96
				1	14	15.99
				8	4	14.59
				15	0	14.50
	1753.5	20385		1	0	16.02
				1	14	15.99
				8	4	14.66
				15	0	14.54

Modulation	Carrier frequency (MHz)	UL Channel	BW	RB Size	RB Offset	Conducted power (dBm)
QPSK	1712.5	19975	5	1	0	16.43
				1	24	16.46
				12	6	15.59
				25	0	15.47
	1732.5	20175		1	0	16.47
				1	24	16.51
				12	6	15.38
				25	0	15.31
	1752.5	20375		1	0	16.12
				1	24	16.13
				12	6	15.34
				25	0	15.40
16QAM	1712.5	19975	5	1	0	15.95
				1	24	15.92
				12	6	14.62
				25	0	14.59
	1732.5	20175		1	0	16.14
				1	24	16.10
				12	6	14.54
				25	0	14.58
	1752.5	20375		1	0	15.95
				1	24	16.06
				12	6	14.65
				25	0	14.63
64QAM	1712.5	19975	5	1	0	15.92
				1	24	15.86
				12	6	14.37
				25	0	14.33
	1732.5	20175		1	0	16.02
				1	24	16.02
				12	6	14.51
				25	0	14.50
	1752.5	20375		1	0	15.95
				1	24	16.04
				12	6	14.59
				25	0	14.58

Modulation	Carrier frequency (MHz)	UL Channel	BW	RB Size	RB Offset	Conducted power (dBm)
QPSK	1715	20000	10	1	0	16.49
				1	49	16.56
				24	12	15.59
				50	0	15.53
	1732.5	20175		1	0	16.47
				1	49	16.47
				24	12	15.42
				50	0	15.40
	1750	20350		1	0	16.08
				1	49	16.07
				24	12	15.46
				50	0	15.40
16QAM	1715	20000	10	1	0	15.93
				1	49	15.96
				24	12	14.53
				50	0	14.51
	1732.5	20175		1	0	16.17
				1	49	16.06
				24	12	14.54
				50	0	14.52
	1750	20350		1	0	16.04
				1	49	16.08
				24	12	14.63
				50	0	14.56
64QAM	1715	20000	10	1	0	15.96
				1	49	15.83
				24	12	14.46
				50	0	14.41
	1732.5	20175		1	0	15.99
				1	49	16.08
				24	12	14.53
				50	0	14.61
	1750	20350		1	0	16.01
				1	49	16.02
				24	12	14.65
				50	0	14.62

Modulation	Carrier frequency (MHz)	UL Channel	BW	RB Size	RB Offset	Conducted power (dBm)
QPSK	1717.5	20025	15	1	0	16.48
				1	74	16.49
				40	18	15.64
				75	0	15.47
	1732.5	20175		1	0	16.44
				1	74	16.45
				40	18	15.44
				75	0	15.40
	1747.5	20325		1	0	16.11
				1	74	16.10
				40	18	15.41
				75	0	15.47
16QAM	1717.5	20025	15	1	0	15.92
				1	74	15.91
				40	18	14.50
				75	0	14.53
	1732.5	20175		1	0	16.07
				1	74	16.17
				40	18	14.56
				75	0	14.48
	1747.5	20325		1	0	16.05
				1	74	15.97
				40	18	14.62
				75	0	14.56
64QAM	1717.5	20025	15	1	0	15.94
				1	74	15.98
				40	18	14.36
				75	0	14.45
	1732.5	20175		1	0	16.02
				1	74	16.06
				40	18	14.63
				75	0	14.50
	1747.5	20325		1	0	16.00
				1	74	16.01
				40	18	14.57
				75	0	14.51

Modulation	Carrier frequency (MHz)	UL Channel	BW	RB Size	RB Offset	Conducted power (dBm)
QPSK	1720	20050	20	1	0	16.56
				1	99	16.56
				50	25	15.66
				100	0	15.59
	1732.5	20175		1	0	16.54
				1	99	16.54
				50	25	15.52
				100	0	15.43
	1745	20300		1	0	16.14
				1	99	16.14
				50	25	15.49
				100	0	15.48
16QAM	1720	20050	20	1	0	16.05
				1	99	16.05
				50	25	14.65
				100	0	14.63
	1732.5	20175		1	0	16.18
				1	99	16.18
				50	25	14.62
				100	0	14.61
	1745	20300		1	0	16.09
				1	99	16.09
				50	25	14.71
				100	0	14.69
64QAM	1720	20050	20	1	0	15.98
				1	99	15.98
				50	25	14.47
				100	0	14.46
	1732.5	20175		1	0	16.08
				1	99	16.08
				50	25	14.63
				100	0	14.62
	1745	20300		1	0	16.08
				1	99	16.08
				50	25	14.67
				100	0	14.64

LTE Band 5

Modulation	Carrier frequency (MHz)	UL Channel	BW	RB Size	RB Offset	Conducted power (dBm)
QPSK	824.7	20407	1.4	1	0	22.92
				1	5	22.85
				3	2	22.19
				6	0	22.18
	836.5	20525		1	0	22.57
				1	5	22.58
				3	2	22.22
				6	0	22.07
	848.3	20643		1	0	22.76
				1	5	22.75
				3	2	22.22
				6	0	22.14
16QAM	824.7	20407	1.4	1	0	22.51
				1	5	22.48
				3	2	21.20
				6	0	21.20
	836.5	20525		1	0	22.51
				1	5	22.49
				3	2	21.35
				6	0	21.20
	848.3	20643		1	0	22.46
				1	5	22.42
				3	2	21.43
				6	0	21.35
64QAM	824.7	20407	1.4	1	0	22.48
				1	5	22.52
				3	2	21.13
				6	0	21.04
	836.5	20525		1	0	22.48
				1	5	22.48
				3	2	21.34
				6	0	21.28
	848.3	20643		1	0	22.24
				1	5	22.24
				3	2	21.42
				6	0	21.36

Modulation	Carrier frequency (MHz)	UL Channel	BW	RB Size	RB Offset	Conducted power (dBm)
QPSK	825.5	20415	3	1	0	22.86
				1	14	22.88
				8	4	22.17
				15	0	22.06
	836.5	20525		1	0	22.52
				1	14	22.55
				8	4	22.18
				15	0	21.98
	847.5	20635		1	0	22.75
				1	14	22.70
				8	4	22.13
				15	0	22.04
16QAM	825.5	20415	3	1	0	22.46
				1	14	22.50
				8	4	21.21
				15	0	21.23
	836.5	20525		1	0	22.48
				1	14	22.52
				8	4	21.30
				15	0	21.16
	847.5	20635		1	0	22.40
				1	14	22.43
				8	4	21.40
				15	0	21.26
64QAM	825.5	20415	3	1	0	22.49
				1	14	22.51
				8	4	21.17
				15	0	21.07
	836.5	20525		1	0	22.34
				1	14	22.36
				8	4	21.34
				15	0	21.37
	847.5	20635		1	0	22.25
				1	14	22.28
				8	4	21.37
				15	0	21.30

Modulation	Carrier frequency (MHz)	UL Channel	BW	RB Size	RB Offset	Conducted power (dBm)
QPSK	826.5	20425	5	1	0	22.97
				1	24	22.96
				12	6	22.21
				25	0	22.13
	836.5	20525		1	0	22.64
				1	24	22.59
				12	6	22.17
				25	0	22.13
	846.5	20625		1	0	22.74
				1	24	22.84
				12	6	22.23
				25	0	22.12
16QAM	826.5	20425	5	1	0	22.42
				1	24	22.46
				12	6	21.22
				25	0	21.17
	836.5	20525		1	0	22.55
				1	24	22.47
				12	6	21.43
				25	0	21.15
	846.5	20625		1	0	22.38
				1	24	22.34
				12	6	21.49
				25	0	21.36
64QAM	826.5	20425	5	1	0	22.41
				1	24	22.49
				12	6	21.14
				25	0	21.17
	836.5	20525		1	0	22.44
				1	24	22.42
				12	6	21.27
				25	0	21.33
	846.5	20625		1	0	22.37
				1	24	22.30
				12	6	21.39
				25	0	21.22

Modulation	Carrier frequency (MHz)	UL Channel	BW	RB Size	RB Offset	Conducted power (dBm)
QPSK	829	20450	10	1	0	22.98
				1	49	22.98
				24	12	22.24
				50	0	22.21
	836.5	20525		1	0	22.65
				1	49	22.65
				24	12	22.29
				50	0	22.13
	844	20600		1	0	22.84
				1	49	22.84
				24	12	22.26
				50	0	22.18
16QAM	829	20450	10	1	0	22.56
				1	49	22.56
				24	12	21.32
				50	0	21.23
	836.5	20525		1	0	22.57
				1	49	22.57
				24	12	21.45
				50	0	21.24
	844	20600		1	0	22.47
				1	49	22.47
				24	12	21.55
				50	0	21.38
64QAM	829	20450	10	1	0	22.54
				1	49	22.54
				24	12	21.27
				50	0	21.18
	836.5	20525		1	0	22.49
				1	49	22.49
				24	12	21.42
				50	0	21.38
	844	20600		1	0	22.38
				1	49	22.38
				24	12	21.47
				50	0	21.36

LTE Band 7

Modulation	Carrier frequency (MHz)	UL Channel	BW	RB Size	RB Offset	Conducted power (dBm)
QPSK	2502.5	20775	5	1	0	15.22
				1	24	15.12
				12	6	14.64
				25	0	14.63
	2535	21100		1	0	15.23
				1	24	15.13
				12	6	14.59
				25	0	14.74
	2567.5	21425		1	0	15.12
				1	24	15.17
				12	6	14.76
				25	0	14.61
16QAM	2502.5	20775	5	1	0	14.88
				1	24	14.99
				12	6	13.62
				25	0	13.42
	2535	21100		1	0	14.85
				1	24	14.87
				12	6	13.71
				25	0	13.67
	2567.5	21425		1	0	14.87
				1	24	14.87
				12	6	13.75
				25	0	13.40
64QAM	2502.5	20775	5	1	0	14.59
				1	24	14.85
				12	6	13.07
				25	0	13.34
	2535	21100		1	0	14.64
				1	24	14.89
				12	6	13.33
				25	0	13.54
	2567.5	21425		1	0	14.79
				1	24	14.89
				12	6	13.04
				25	0	13.49

Modulation	Carrier frequency (MHz)	UL Channel	BW	RB Size	RB Offset	Conducted power (dBm)
QPSK	2505	20800	10	1	0	15.02
				1	49	14.96
				24	12	14.71
				50	0	14.62
	2535	21100		1	0	15.20
				1	49	15.27
				24	12	14.72
				50	0	14.75
	2565	21400		1	0	15.18
				1	49	15.17
				24	12	14.62
				50	0	14.63
16QAM	2505	20800	10	1	0	15.04
				1	49	14.77
				24	12	13.56
				50	0	13.57
	2535	21100		1	0	15.05
				1	49	14.89
				24	12	13.83
				50	0	13.51
	2565	21400		1	0	14.84
				1	49	14.90
				24	12	13.56
				50	0	13.66
64QAM	2505	20800	10	1	0	14.58
				1	49	14.90
				24	12	13.08
				50	0	13.58
	2535	21100		1	0	14.86
				1	49	14.93
				24	12	13.36
				50	0	13.39
	2565	21400		1	0	14.76
				1	49	14.78
				24	12	13.15
				50	0	13.38

Modulation	Carrier frequency (MHz)	UL Channel	BW	RB Size	RB Offset	Conducted power (dBm)
QPSK	2507.5	20825	15	1	0	15.04
				1	74	14.97
				40	18	14.49
				75	0	14.51
	2535	21100		1	0	15.17
				1	74	15.19
				40	18	14.80
				75	0	14.58
	2562.5	21375		1	0	15.19
				1	74	15.02
				40	18	14.65
				75	0	14.66
16QAM	2507.5	20825	15	1	0	14.92
				1	74	15.01
				40	18	13.57
				75	0	13.57
	2535	21100		1	0	15.08
				1	74	14.91
				40	18	13.74
				75	0	13.45
	2562.5	21375		1	0	14.93
				1	74	15.01
				40	18	13.68
				75	0	13.63
64QAM	2507.5	20825	15	1	0	14.61
				1	74	14.97
				40	18	13.24
				75	0	13.65
	2535	21100		1	0	14.73
				1	74	14.86
				40	18	13.32
				75	0	13.71
	2562.5	21375		1	0	14.81
				1	74	15.04
				40	18	13.07
				75	0	13.59

Modulation	Carrier frequency (MHz)	UL Channel	BW	RB Size	RB Offset	Conducted power (dBm)
QPSK	2510	20850	20	1	0	15.24
				1	99	15.22
				50	25	14.74
				100	0	14.64
	2535	21100		1	0	15.09
				1	99	15.06
				50	25	14.66
				100	0	14.68
	2560	21350		1	0	15.13
				1	99	14.95
				50	25	14.66
				100	0	14.58
16QAM	2510	20850	20	1	0	14.88
				1	99	15.00
				50	25	13.55
				100	0	13.62
	2535	21100		1	0	14.97
				1	99	14.83
				50	25	13.65
				100	0	13.70
	2560	21350		1	0	14.98
				1	99	14.87
				50	25	13.64
				100	0	13.44
64QAM	2510	20850	20	1	0	14.62
				1	99	15.00
				50	25	13.27
				100	0	13.52
	2535	21100		1	0	14.69
				1	99	15.05
				50	25	13.26
				100	0	13.60
	2560	21350		1	0	14.92
				1	99	14.83
				50	25	13.08
				100	0	13.30

LTE Band 12

Modulation	Carrier frequency (MHz)	UL Channel	BW	RB Size	RB Offset	Conducted power (dBm)
QPSK	699.7	23017	1.4	1	0	22.93
				1	5	22.95
				3	2	22.35
				6	0	22.10
	707.5	23095		1	0	22.76
				1	5	22.74
				3	2	22.35
				6	0	22.24
	715.3	23173		1	0	22.72
				1	5	22.70
				3	2	22.14
				6	0	22.02
16QAM	699.7	23017	1.4	1	0	22.76
				1	5	22.73
				3	2	21.65
				6	0	21.38
	707.5	23095		1	0	22.56
				1	5	22.48
				3	2	21.53
				6	0	21.35
	715.3	23173		1	0	22.47
				1	5	22.53
				3	2	21.44
				6	0	21.42
64QAM	699.7	23017	1.4	1	0	22.65
				1	5	22.67
				3	2	21.63
				6	0	21.45
	707.5	23095		1	0	22.39
				1	5	22.45
				3	2	21.50
				6	0	21.45
	715.3	23173		1	0	22.56
				1	5	22.52
				3	2	21.23
				6	0	21.25

Modulation	Carrier frequency (MHz)	UL Channel	BW	RB Size	RB Offset	Conducted power (dBm)
QPSK	700.5	23025	3	1	0	22.90
				1	14	22.98
				8	4	22.35
				15	0	22.09
	707.5	23095		1	0	22.71
				1	14	22.68
				8	4	22.37
				15	0	22.09
	714.5	23165		1	0	22.78
				1	14	22.68
				8	4	22.05
				15	0	22.11
16QAM	700.5	23025	3	1	0	22.74
				1	14	22.79
				8	4	21.52
				15	0	21.41
	707.5	23095		1	0	22.57
				1	14	22.50
				8	4	21.52
				15	0	21.42
	714.5	23165		1	0	22.53
				1	14	22.52
				8	4	21.39
				15	0	21.42
64QAM	700.5	23025	3	1	0	22.70
				1	14	22.64
				8	4	21.58
				15	0	21.50
	707.5	23095		1	0	22.42
				1	14	22.37
				8	4	21.44
				15	0	21.37
	714.5	23165		1	0	22.55
				1	14	22.45
				8	4	21.37
				15	0	21.27

Modulation	Carrier frequency (MHz)	UL Channel	BW	RB Size	RB Offset	Conducted power (dBm)
QPSK	701.5	23035	5	1	0	22.84
				1	24	22.98
				12	6	22.22
				25	0	22.09
	707.5	23095		1	0	22.70
				1	24	22.67
				12	6	22.24
				25	0	22.19
	713.5	23155		1	0	22.70
				1	24	22.70
				12	6	22.15
				25	0	22.05
16QAM	701.5	23035	5	1	0	22.66
				1	24	22.74
				12	6	21.65
				25	0	21.38
	707.5	23095		1	0	22.49
				1	24	22.43
				12	6	21.52
				25	0	21.37
	713.5	23155		1	0	22.47
				1	24	22.60
				12	6	21.39
				25	0	21.33
64QAM	701.5	23035	5	1	0	22.64
				1	24	22.71
				12	6	21.56
				25	0	21.43
	707.5	23095		1	0	22.41
				1	24	22.46
				12	6	21.40
				25	0	21.36
	713.5	23155		1	0	22.52
				1	24	22.50
				12	6	21.28
				25	0	21.32

Modulation	Carrier frequency (MHz)	UL Channel	BW	RB Size	RB Offset	Conducted power (dBm)
QPSK	704	23060	10	1	0	22.98
				1	49	22.98
				24	12	22.36
				50	0	22.24
	707.5	23095		1	0	22.79
				1	49	22.79
				24	12	22.38
				50	0	22.24
	711	23130		1	0	22.82
				1	49	22.82
				24	12	22.17
				50	0	22.16
16QAM	704	23060	10	1	0	22.81
				1	49	22.81
				24	12	21.67
				50	0	21.50
	707.5	23095		1	0	22.58
				1	49	22.58
				24	12	21.61
				50	0	21.45
	711	23130		1	0	22.61
				1	49	22.61
				24	12	21.46
				50	0	21.43
64QAM	704	23060	10	1	0	22.78
				1	49	22.78
				24	12	21.64
				50	0	21.56
	707.5	23095		1	0	22.49
				1	49	22.49
				24	12	21.53
				50	0	21.47
	711	23130		1	0	22.58
				1	49	22.58
				24	12	21.37
				50	0	21.34

6.5 Bluetooth Measurement result

BT

Modulation type	Average Power Output (dBm)		
	2402MHz(Ch0)	2441MHz(Ch39)	2480MHz(Ch78)
GFSK	1.36	1.91	1.16
$\pi/4$ DQPSK	1.14	1.09	1.15
8DPSK	1.22	1.23	1.24

BLE

Modulation type	Average Power Output (dBm)		
	2402MHz (Ch0)	2440MHz (Ch19)	2480MHz (Ch39)
GFSK (LE 1Mbps)	-3.29	-0.93	-0.37

6.6 Wi-Fi Measurement result

WIFI 2.4GHz

Modulation type	Average power output (dBm)		
	2412MHz	2437MHz	2462MHz
11b	16.81	17.37	16.29
11g	16.32	17.75	17.02
11n HT20	15.35	16.98	16.43

6.7 Standalone SAR Test Exclusion Considerations

Standalone 1-g head or body SAR evaluation by measurement or numerical simulation is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied.

SAR Test Exclusion Thresholds for 100 MHz – 6 GHz and ≤ 50 mm

Method1:

According to the KDB447498 4.3.1 (1)

For 100 MHz to 6 GHz and test separation distances ≤ 50 mm, the 1-g and 10-g SAR test exclusion thresholds are determined by the following:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f} \text{ (GHz)}] \leq 3.0$ for 1-g SAR, where

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm, and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

This is equivalent to $[(\text{max. power of channel, including tune-up tolerance, mW}) / (60 / \sqrt{f}(\text{GHz}) \text{ mW})] \cdot [20 \text{ mm} / (\text{min. test separation distance, mm})] \leq 1.0$ for 1-g SAR; also see Appendix A for approximate exclusion threshold values at selected frequencies and distances.

Method2:

According to the KDB447498 appendix A

Approximate SAR Test Exclusion Power Thresholds at Selected Frequencies and Test Separation Distances are illustrated in the following Table.


MHz	5	10	15	20	25	mm
150	39	77	116	155	194	SAR Test Exclusion Threshold (mW)
300	27	55	82	110	137	
450	22	45	67	89	112	
835	16	33	49	66	82	
900	16	32	47	63	79	
1500	12	24	37	49	61	
1900	11	22	33	44	54	
2450	10	19	29	38	48	
3600	8	16	24	32	40	
5200	7	13	20	26	33	
5400	6	13	19	26	32	
5800	6	12	19	25	31	

Summary of Transmitters

Band/Mode	Max conducted power adjusted for tune-up tolerance(mW)	Position	SAR test exclusion threshold (mW)	Standalone SAR Required
2.4GHz BT/BLE	1.6	Head	10	No
		Body	19	No
2.4GHz Wi-Fi	63.1	Head	10	Yes
		Body	19	Yes

6.8 RF exposure conditions

Refer to the follow picture “Antenna information” for the specific details of the antenna-to-antenna and antenna-to-edge(s) distances.



Main antenna (Antenna Label:A):

LTE FDD B5/12 TX

WCDMA B5 TX

GSM 850 TX

DIV antenna (Antenna Label:B):

LTE FDD 2/4/7 TX

WCDMA B2/4 TX

GSM 1900 TX

WiFi/BT/GPS antenna

2.4G 2412MHz~2472MHz & GPS: 1570 MHz~1620 MHz

Note: we defined these position when we face the screen of EUT, the reason why we perform SAR test for these edges is that the structures of antennas is close to our body, and for the other edges do not necessary cause we already consider the worst case.

6.8.1 Head Exposure Conditions For WWAN

Test Configurations	SAR Required	Note
Left Touch	Yes	/
Left Tilt (15°)	Yes	/
Right Touch	Yes	/
Right Tilt (15°)	Yes	/

For WLAN

Test Configurations	SAR Required	Note
Left Touch	Yes	/
Left Tilt (15°)	Yes	/
Right Touch	Yes	/
Right Tilt (15°)	Yes	/

For BT/BLE

Test Configurations	Estimated SAR	Note
Left Touch	Yes	Excluded from SAR test
Left Tilt (15°)	Yes	
Right Touch	Yes	
Right Tilt (15°)	Yes	

6.8.2 Body Worn Exposure conditions

For WWAN

Test Configurations	SAR Required	Note
Back	Yes	/
Front	Yes	/

For WLAN

Test Configurations	SAR Required	Note
Back	Yes	/
Front	Yes	/

For BT/BLE

Test Configurations	Estimated SAR	Note
Back	Yes	Excluded from SAR test
Front	Yes	

6.8.3 Hotspot Exposure conditions

For WWAN (frequency band below 1GHz)

Test Configurations	SAR Required	Antenna-to-edge(s) distances
Back	Yes*	<25mm
Front	Yes*	<25mm
Top	No	>25mm
Bottom	Yes	<25mm
Left	Yes	<25mm
Right	Yes	<25mm

For WWAN (frequency band above 1GHz)

Test Configurations	SAR Required	Antenna-to-edge(s) distances
Back	Yes*	<25mm
Front	Yes*	<25mm
Top	Yes	<25mm
Bottom	No	>25mm
Left	Yes	<25mm
Right	No	>25mm

For WLAN

Test Configurations	SAR Required	Antenna-to-edge(s) distances
Back	Yes*	<25mm
Front	Yes*	<25mm
Top	Yes	<25mm
Bottom	No	>25mm
Left	No	>25mm
Right	Yes	<25mm

For BT/BLE

Test Configurations	SAR evaluation	Note
Back	No	There is no hotspot mode for BT/BLE
Front		
Top		
Bottom		
Left		
Right		

Note*: For hotspot mode, it's not necessary test Rear and Front position cause we already test the these position without hotspot mode in Body Exposure conditions, Normally if the hotspot mode opened, the technology “power reduction” used for mobile, so we consider the worst condition, and remain the data of body worn as hotspots mode.

6.9 System Checking

The manufacturer calibrates the probes annually. Dielectric parameters of the tissue simulants were measured every day using the dielectric probe kit and the network analyser.

For the measurement of the following parameters the SPEAG DAKS-3.5 dielectric parameter probe is used, representing the open-ended coaxial probe measurement procedure.

Date Tested	Freq. (MHz)	Liquid parameters	measured	Target	Delta (%)	Tolerance (%)
2020.02.29	750	ϵ_r	41.352	41.90	-1.3	± 10
		σ [S/m]	0.923	0.89	3.7	± 10
2020.03.02	835	ϵ_r	40.266	41.50	-3.0	± 10
		σ [S/m]	0.911	0.90	1.2	± 10
2020.03.06	1800	ϵ_r	40.688	40.00	1.7	± 10
		σ [S/m]	1.418	1.40	1.3	± 10
2020.03.09	2000	ϵ_r	39.844	40.00	-0.4	± 10
		σ [S/m]	1.427	1.40	1.9	± 10
2020.03.12	2450	ϵ_r	38.343	39.20	-2.2	± 10
		σ [S/m]	1.866	1.80	3.7	± 10
2020.03.15	2600	ϵ_r	39.672	39.00	1.7	± 10
		σ [S/m]	1.951	1.96	-0.5	± 10

Note: For DASY system, the conservative tolerance 5% could expand to 10% when the frequency under 3GHz

A system check measurement was made following once the determination of the dielectric parameters of the simulant, using the dipole validation kit. The system checking results (dielectric parameters and SAR values) are given in the table below.

Date Tested	System dipole	T.S. Liquid	SAR measured (normalized to 1W)		Target (Ref. Value)	Delta (%)	Tolerance (%)
2020.02.29	D750V3	Head	1g	8.24	8.26	-0.2	± 10
2020.03.02	D835V2	Head	1g	9.56	9.37	2.0	± 10
2020.03.06	D1800V2	Head	1g	37.96	38.9	-2.4	± 10
2020.03.09	D2000V2	Head	1g	39.28	40.3	-2.5	± 10
2020.03.12	D2450V2	Head	1g	54.0	52.4	3.1	± 10
2020.03.15	D2600V2	Head	1g	56.4	56.6	-0.4	± 10

6.10 SAR TEST RESULT

In order to determine the largest value of the peak spatial-average SAR of a handset, all device positions, configurations, and operational modes should be tested for each frequency band according to Steps 1 to 3 below.

Step 1: The tests should be performed at the channel that is closest to the center of the transmit frequency band.

a) All device positions (cheek and tilt, for both left and right sides of the SAM phantom),
b) All configurations for each device position in a), e.g., antenna extended and retracted, and
c) All operational modes for each device position in item a) and configuration in item b) in each frequency band, e.g., analog and digital, If more than three frequencies need to be tested (i.e., $N_c > 3$), then all frequencies, configurations and modes shall be tested for all of the above test conditions.

Step 2: For the condition providing the highest peak spatial-average SAR determined in Step 1 for each frequency, perform all tests at all other test frequency channels, e.g., lowest and highest frequencies. In addition, for all other conditions (device position, configuration, and operational mode) where the peak spatial-average SAR value determined in Step 1 is within 3 dB of the applicable SAR limit, it is recommended that all other test frequencies should be tested as well.

Step 3: Examine all data to determine the largest value of the peak.

Note:

1. Per KDB 447498 D01v06, the reported SAR is the measured SAR value adjusted for maximum tune-up tolerance.

Scaling Factor = tune-up limit power (mW) / EUT RF power (mW), where tune-up limit is the maximum rated power among all production units.

Duty Factor = 1 / Duty Cycle(%)

For cellular network:

Reported SAR (W/kg) = Measured SAR (W/kg) * Scaling Factor

For WLAN

Reported SAR (W/kg) = Measured SAR (W/kg) * Scaling Factor * Duty factor

2. Per KDB 447498 D01v06, for each exposure position, if the highest output channel reported SAR ≤ 0.8 W/kg, other channels SAR testing are not necessary.

3. The distance between the EUT and the phantom bottom is 10mm.

Mode		Duty cycle	Duty factor	Note
Licensed Frequency	GSM Band	Depends on UP slots	NA	According to the theory, we configured duty cycle with relevant value on the communication tester, so correction factor do not need such as “duty factor”
	WCDMA Band	100%		
	FDD-LTE Band	100%		
	TDD-LTE Band	63.3%		
Unlicensed Frequency	WIFI 2.4GHz 802.11g	97.2%	1.03	SRTC perform SAR test with non-signaling mode, and duty factor shall be considered because of the uncertainty of data traffic.

There are two supplies are different on the supplier of Memory/Camera/LCD/ fingerprint/ Battery. So there's no influence on radio exposure. And we check the worst case of each exposure condition among all the frequency bands of secondary supply based on main supply.

Exposure condition	Worst case of Main supply	Secondary supply
Head	GSM1900	Check GSM1900
Body-worn& Hotspot	LTE B7	Check LTE B7

The measured and reported Head/body SAR values for the test device are tabulated below:

Mode: GSM 850

fL(MHz)=824.2MHz

fM(MHz)=836.5MHz

fH(MHz)= 848.8MHz

Limit of SAR (W/kg): <1.6W/kg (1g Average)

Test case				Meas power	Tune-up	Scaling factor	Meas SAR	Report SAR
Mode	Exposure condition	Position	Channel				First	First
GSM Voice	Head	Left touch	L	33.26	33.50	1.06	---	---
			M	33.15	33.50	1.08	0.162	0.175
			H	33.14	33.50	1.09	---	---
		Left tilt	L	33.26	33.50	1.06	---	---
			M	33.15	33.50	1.08	0.103	0.111
			H	33.14	33.50	1.09	---	---
		Right touch	L	33.26	33.50	1.06	---	---
			M	33.15	33.50	1.08	0.195	0.211
			H	33.14	33.50	1.09	---	---
		Right tilt	L	33.26	33.50	1.06	---	---
			M	33.15	33.50	1.08	0.098	0.106
			H	33.14	33.50	1.09	---	---
GPRS/EDGE GMSK 2slot	Body worn & Hotspot	Back	L	31.18	31.50	1.08	---	---
			M	31.05	31.50	1.11	0.310	0.344
			H	30.93	31.50	1.14	---	---
		Front	L	31.18	31.50	1.08	---	---
			M	31.05	31.50	1.11	0.236	0.262
			H	30.93	31.50	1.14	---	---
	Hotspot	Top	L	31.18	31.50	1.08	---	---
			M	31.05	31.50	1.11	---	---
			H	30.93	31.50	1.14	---	---
		Bottom	L	31.18	31.50	1.08	---	---
			M	31.05	31.50	1.11	0.240	0.266
			H	30.93	31.50	1.14	---	---
		Left	L	31.18	31.50	1.08	---	---
			M	31.05	31.50	1.11	0.096	0.107
			H	30.93	31.50	1.14	---	---
		Right	L	31.18	31.50	1.08	---	---
			M	31.05	31.50	1.11	0.207	0.230
			H	30.93	31.50	1.14	---	---

Note: When use 3rd VOIP APP, normally the Qos is pretty bad, so this product do not support VOIP sheme under GSM network.

Mode: GSM1900

fL (MHz)=1850.2MHz

fM (MHz)=1880.0MHz

fH (MHz)=1909.8MHz

Limit of SAR (W/kg): <1.6W/kg (1g Average)

Test case				Meas power	Tune-up	Scaling factor	Meas SAR	Report SAR
Mode	Exposure condition	Position	Channel				First	First
GSM Voice	Head	Left touch	L	28.14	28.50	1.09	---	---
			M	28.13	28.50	1.09	0.410	0.447
			H	28.15	28.50	1.08	---	---
		Left tilt	L	28.14	28.50	1.09	---	---
			M	28.13	28.50	1.09	0.424	0.462
			H	28.15	28.50	1.08	---	---
		Right touch	L	28.14	28.50	1.09	0.933	1.017
			M	28.13	28.50	1.09	0.950	1.036
			H	28.15	28.50	1.08	0.946	1.022
			L2	28.14	28.50	1.09	0.833	0.908
			M2	28.13	28.50	1.09	0.903	0.984
			H2	28.15	28.50	1.08	0.852	0.920
		Right tilt	L	28.14	28.50	1.09	---	---
			M	28.13	28.50	1.09	0.727	0.792
			H	28.15	28.50	1.08	---	---
GPRS/EDGE GMSK 3slot	Body worn & Hotspot	Back	L	25.40	25.50	1.02	---	---
			M	25.21	25.50	1.07	0.301	0.322
			H	25.11	25.50	1.09	---	---
		Front	L	25.40	25.50	1.02	---	---
			M	25.21	25.50	1.07	0.259	0.277
	Hotspot	Top	L	25.40	25.50	1.02	---	---
			M	25.21	25.50	1.07	0.288	0.308
			H	25.11	25.50	1.09	---	---
		Bottom	L	25.40	25.50	1.02	---	---
			M	25.21	25.50	1.07	---	---
			H	25.11	25.50	1.09	---	---
		Left	L	25.40	25.50	1.02	---	---
			M	25.21	25.50	1.07	0.210	0.225
			H	25.11	25.50	1.09	---	---
		Right	L	25.40	25.50	1.02	---	---
			M	25.21	25.50	1.07	---	---
			H	25.11	25.50	1.09	---	---

Note1: When use 3rd VOIP APP, normally the Qos is pretty bad, so this product do not support VOIP scheme under GSM network.

Note2: L2/M2/H2 means secondary supply.

Mode: WCDMA BAND II

fL (MHz)= 1852.4MHz fM (MHz)= 1880.0MHz fH (MHz)= 1907.6MHz

Limit of SAR (W/kg): <1.6W/kg (1g Average)

Test case				Meas power	Tune-up	Scaling factor	Meas SAR	Report SAR
Mode	Exposure condition	Position	Channel				First	First
Rel.99	Head	Left touch	L	16.25	16.50	1.06	---	---
			M	16.21	16.50	1.07	0.262	0.280
			H	16.13	16.50	1.09	---	---
		Left tilt	L	16.25	16.50	1.06	---	---
			M	16.21	16.50	1.07	0.203	0.217
			H	16.13	16.50	1.09	---	---
		Right touch	L	16.25	16.50	1.06	---	---
			M	16.21	16.50	1.07	0.478	0.511
			H	16.13	16.50	1.09	---	---
		Right tilt	L	16.25	16.50	1.06	---	---
			M	16.21	16.50	1.07	0.305	0.326
			H	16.13	16.50	1.09	---	---
	Body worn & Hotspot	Back	L	16.25	16.50	1.06	---	---
			M	16.21	16.50	1.07	0.334	0.357
			H	16.13	16.50	1.09	---	---
		Front	L	16.25	16.50	1.06	---	---
			M	16.21	16.50	1.07	0.320	0.342
			H	16.13	16.50	1.09	---	---
	Hotspot	Top	L	16.25	16.50	1.06	---	---
			M	16.21	16.50	1.07	0.324	0.347
			H	16.13	16.50	1.09	---	---
		Bottom	L	16.25	16.50	1.06	---	---
			M	16.21	16.50	1.07	---	---
			H	16.13	16.50	1.09	---	---
		Left	L	16.25	16.50	1.06	---	---
			M	16.21	16.50	1.07	0.179	0.192
			H	16.13	16.50	1.09	---	---
		Right	L	16.25	16.50	1.06	---	---
			M	16.21	16.50	1.07	---	---
			H	16.13	16.50	1.09	---	---

Mode: WCDMA BAND IV

fL (MHz)=1712.4MHz fM (MHz)=1732.4MHz fH (MHz)= 1752.6MHz

Limit of SAR (W/kg): <1.6W/kg (1g Average)

Test case				Meas power	Tune-up	Scaling factor	Meas SAR	Report SAR
Mode	Exposure condition	Position	Channel				First	First
Rel.99	Head	Left touch	L	15.85	16.00	1.04	---	---
			M	15.90	16.00	1.02	0.216	0.220
			H	15.95	16.00	1.01	---	---
		Left tilt	L	15.85	16.00	1.04	---	---
			M	15.90	16.00	1.02	0.149	0.152
			H	15.95	16.00	1.01	---	---
		Right touch	L	15.85	16.00	1.04	---	---
			M	15.90	16.00	1.02	0.383	0.391
			H	15.95	16.00	1.01	---	---
		Right tilt	L	15.85	16.00	1.04	---	---
			M	15.90	16.00	1.02	0.112	0.114
			H	15.95	16.00	1.01	---	---
	Body worn & Hotspot	Back	L	15.85	16.00	1.04	---	---
			M	15.90	16.00	1.02	0.242	0.247
			H	15.95	16.00	1.01	---	---
			L2	15.85	16.00	1.04	---	---
			M2	15.90	16.00	1.02	0.181	0.185
			H2	15.95	16.00	1.01	---	---
		Front	L	15.85	16.00	1.04	---	---
			M	15.90	16.00	1.02	0.239	0.244
			H	15.95	16.00	1.01	---	---
	Hotspot	Top	L	15.85	16.00	1.04	---	---
			M	15.90	16.00	1.02	---	---
			H	15.95	16.00	1.01	---	---
		Bottom	L	15.85	16.00	1.04	---	---
			M	15.90	16.00	1.02	0.141	0.144
			H	15.95	16.00	1.01	---	---
		Left	L	15.85	16.00	1.04	---	---
			M	15.90	16.00	1.02	---	---
			H	15.95	16.00	1.01	---	---
		Right	L	15.85	16.00	1.04	---	---
			M	15.90	16.00	1.02	0.216	0.220
			H	15.95	16.00	1.01	---	---

Mode: WCDMA BAND V

fL (MHz)=826.4MHz

fM (MHz)=836.4MHz

fH (MHz)= 846.6MHz

Limit of SAR (W/kg): <1.6W/kg (1g Average)

Test case				Meas power	Tune-up	Scaling factor	Meas SAR	Report SAR
Mode	Exposure condition	Position	Channel				First	First
Rel.99	Head	Left touch	L	22.66	23.00	1.08	---	---
			M	22.59	23.00	1.10	0.100	0.110
			H	22.70	23.00	1.07	---	---
		Left tilt	L	22.66	23.00	1.08	---	---
			M	22.59	23.00	1.10	0.070	0.077
			H	22.70	23.00	1.07	---	---
		Right touch	L	22.66	23.00	1.08	---	---
			M	22.59	23.00	1.10	0.132	0.145
			H	22.70	23.00	1.07	---	---
		Right tilt	L	22.66	23.00	1.08	---	---
			M	22.59	23.00	1.10	0.073	0.080
			H	22.70	23.00	1.07	---	---
	Body worn & Hotspot	Back	L	22.66	23.00	1.08	---	---
			M	22.59	23.00	1.10	0.244	0.268
			H	22.70	23.00	1.07	---	---
		Front	L	22.66	23.00	1.08	---	---
			M	22.59	23.00	1.10	0.193	0.212
			H	22.70	23.00	1.07	---	---
	Hotspot	Top	L	22.66	23.00	1.08	---	---
			M	22.59	23.00	1.10	---	---
			H	22.70	23.00	1.07	---	---
		Bottom	L	22.66	23.00	1.08	---	---
			M	22.59	23.00	1.10	0.216	0.238
			H	22.70	23.00	1.07	---	---
		Left	L	22.66	23.00	1.08	---	---
			M	22.59	23.00	1.10	0.077	0.085
			H	22.70	23.00	1.07	---	---
		Right	L	22.66	23.00	1.08	---	---
			M	22.59	23.00	1.10	0.168	0.185
			H	22.70	23.00	1.07	---	---

Mode: LTE Band 2

fL (MHz)= 1860MHz

fM (MHz)= 1880MHz

fH (MHz)= 1900MHz

Limit of SAR (W/kg): <1.6W/kg (1g Average)

Test case				Meas power	Tune-up	Scaling factor	Meas SAR	Report SAR
Mode	Exposure condition	Position	Channel				First	First
BW=20M Hz QPSK 1RB	Head	Left touch	L	16.44	17.00	1.14	---	---
			M	16.61	17.00	1.09	0.165	0.180
			H	16.55	17.00	1.11	---	---
		Left tilt	L	16.44	17.00	1.14	---	---
			M	16.61	17.00	1.09	0.105	0.114
			H	16.55	17.00	1.11	---	---
		Right touch	L	16.44	17.00	1.14	---	---
			M	16.61	17.00	1.09	0.306	0.334
			H	16.55	17.00	1.11	---	---
		Right tilt	L	16.44	17.00	1.14	---	---
			M	16.61	17.00	1.09	0.205	0.223
			H	16.55	17.00	1.11	---	---
	Body worn & Hotspot	Back	L	16.44	17.00	1.14	---	---
			M	16.61	17.00	1.09	0.345	0.376
			H	16.55	17.00	1.11	---	---
		Front	L	16.44	17.00	1.14	---	---
			M	16.61	17.00	1.09	0.202	0.220
	Hotspot	Top	L	16.44	17.00	1.14	---	---
			M	16.61	17.00	1.09	0.279	0.304
			H	16.55	17.00	1.11	---	---
		Bottom	L	16.44	17.00	1.14	---	---
			M	16.61	17.00	1.09	---	---
			H	16.55	17.00	1.11	---	---
		Left	L	16.44	17.00	1.14	---	---
			M	16.61	17.00	1.09	0.090	0.098
			H	16.55	17.00	1.11	---	---
		Right	L	16.44	17.00	1.14	---	---
			M	16.61	17.00	1.09	---	---
			H	16.55	17.00	1.11	---	---
BW=20M Hz QPSK 50%RB	Head	Left touch	L	15.86	16.00	1.03	---	---
			M	15.90	16.00	1.02	0.145	0.148
			H	15.69	16.00	1.07	---	---
		Left tilt	L	15.86	16.00	1.03	---	---
			M	15.90	16.00	1.02	0.098	0.100
			H	15.69	16.00	1.07	---	---
		Right touch	L	15.86	16.00	1.03	---	---
			M	15.90	16.00	1.02	0.278	0.284
			H	15.69	16.00	1.07	---	---

Test case				Meas power	Tune-up	Scaling factor	Meas SAR	Report SAR
Mode	Exposure condition	Position	Channel				First	First
		Right tilt	L	15.86	16.00	1.03	---	---
			M	15.90	16.00	1.02	0.186	0.190
			H	15.69	16.00	1.07	---	---
	Body worn & Hotspot	Back	L	15.86	16.00	1.03	---	---
			M	15.90	16.00	1.02	0.305	0.311
			H	15.69	16.00	1.07	---	---
		Front	L	15.86	16.00	1.03	---	---
			M	15.90	16.00	1.02	0.160	0.163
			H	15.69	16.00	1.07	---	---
	Hotspot	Top	L	15.86	16.00	1.03	---	---
			M	15.90	16.00	1.02	0.191	0.195
			H	15.69	16.00	1.07	---	---
		Bottom	L	15.86	16.00	1.03	---	---
			M	15.90	16.00	1.02	---	---
			H	15.69	16.00	1.07	---	---
		Left	L	15.86	16.00	1.03	---	---
			M	15.90	16.00	1.02	0.076	0.078
			H	15.69	16.00	1.07	---	---
		Right	L	15.86	16.00	1.03	---	---
			M	15.90	16.00	1.02	---	---
			H	15.69	16.00	1.07	---	---

Mode: LTE Band 4

fL (MHz)= 1720MHz

fM (MHz)= 1732.5MHz

fH (MHz)= 1745MHz

Limit of SAR (W/kg): <1.6W/kg (1g Average)

Test case				Meas power	Tune-up	Scaling factor	Meas SAR	Report SAR
Mode	Exposure condition	Position	Channel				First	First
BW=20MHz QPSK 1RB	Head	Left touch	L	16.56	17.00	1.11	---	---
			M	16.54	17.00	1.11	0.112	0.124
			H	16.14	17.00	1.22	---	---
		Left tilt	L	16.56	17.00	1.11	---	---
			M	16.54	17.00	1.11	0.086	0.095
			H	16.14	17.00	1.22	---	---
		Right touch	L	16.56	17.00	1.11	---	---
			M	16.54	17.00	1.11	0.170	0.189
			H	16.14	17.00	1.22	---	---
		Right tilt	L	16.56	17.00	1.11	---	---
			M	16.54	17.00	1.11	0.107	0.119
			H	16.14	17.00	1.22	---	---
	Body worn & Hotspot	Back	L	16.56	17.00	1.11	---	---
			M	16.54	17.00	1.11	0.274	0.304
			H	16.14	17.00	1.22	---	---
		Front	L	16.56	17.00	1.11	---	---
			M	16.54	17.00	1.11	0.196	0.218
			H	16.14	17.00	1.22	---	---
	Hotspot	Top	L	16.56	17.00	1.11	---	---
			M	16.54	17.00	1.11	0.130	0.144
			H	16.14	17.00	1.22	---	---
		Bottom	L	16.56	17.00	1.11	---	---
			M	16.54	17.00	1.11	---	---
			H	16.14	17.00	1.22	---	---
		Left	L	16.56	17.00	1.11	---	---
			M	16.54	17.00	1.11	0.099	0.110
			H	16.14	17.00	1.22	---	---
		Right	L	16.56	17.00	1.11	---	---
			M	16.54	17.00	1.11	---	---
			H	16.14	17.00	1.22	---	---
BW=20MHz QPSK 50%RB	Head	Left touch	L	15.66	16.00	1.08	---	---
			M	15.52	16.00	1.12	0.101	0.113
			H	15.49	16.00	1.12	---	---
		Left tilt	L	15.66	16.00	1.08	---	---
			M	15.52	16.00	1.12	0.075	0.084
			H	15.49	16.00	1.12	---	---
		Right touch	L	15.66	16.00	1.08	---	---
			M	15.52	16.00	1.12	0.156	0.175
			H	15.49	16.00	1.12	---	---

Test case				Meas power	Tune-up	Scaling factor	Meas SAR	Report SAR
Mode	Exposure condition	Position	Channel				First	First
		Right tilt	L	15.66	16.00	1.08	---	---
			M	15.52	16.00	1.12	0.101	0.113
			H	15.49	16.00	1.12	---	---
	Body worn & Hotspot	Back	L	15.66	16.00	1.08	---	---
			M	15.52	16.00	1.12	0.189	0.212
			H	15.49	16.00	1.12	---	---
		Front	L	15.66	16.00	1.08	---	---
			M	15.52	16.00	1.12	0.149	0.167
			H	15.49	16.00	1.12	---	---
	Hotspot	Top	L	15.66	16.00	1.08	---	---
			M	15.52	16.00	1.12	0.108	0.121
			H	15.49	16.00	1.12	---	---
		Bottom	L	15.66	16.00	1.08	---	---
			M	15.52	16.00	1.12	---	---
			H	15.49	16.00	1.12	---	---
		Left	L	15.66	16.00	1.08	---	---
			M	15.52	16.00	1.12	0.061	0.068
			H	15.49	16.00	1.12	---	---
		Right	L	15.66	16.00	1.08	---	---
			M	15.52	16.00	1.12	---	---
			H	15.49	16.00	1.12	---	---

Mode: LTE Band 5

fL (MHz)=829 MHz

fM (MHz)=836.5MHz

fH (MHz)= 844MHz

Limit of SAR (W/kg) : <1.6W/kg (1g Average)

Test case				Meas power	Tune-up	Scaling factor	Meas SAR	Report SAR
Mode	Exposure condition	Position	Channel				First	First
BW=10MH z QPSK 1RB	Head	Left touch	L	22.98	23.00	1.00	---	---
			M	22.65	23.00	1.08	0.091	0.098
			H	22.84	23.00	1.04	---	---
		Left tilt	L	22.98	23.00	1.00	---	---
			M	22.65	23.00	1.08	0.052	0.056
			H	22.84	23.00	1.04	---	---
		Right touch	L	22.98	23.00	1.00	---	---
			M	22.65	23.00	1.08	0.121	0.131
			H	22.84	23.00	1.04	---	---
		Right tilt	L	22.98	23.00	1.00	---	---
			M	22.65	23.00	1.08	0.103	0.111
			H	22.84	23.00	1.04	---	---
	Body worn & Hotspot	Back	L	22.98	23.00	1.00	---	---
			M	22.65	23.00	1.08	0.206	0.222
			H	22.84	23.00	1.04	---	---
		Front	L	22.98	23.00	1.00	---	---
			M	22.65	23.00	1.08	0.156	0.168
	Hotspot	Top	L	22.98	23.00	1.00	---	---
			M	22.65	23.00	1.08	---	---
			H	22.84	23.00	1.04	---	---
		Bottom	L	22.98	23.00	1.00	---	---
			M	22.65	23.00	1.08	0.169	0.183
			H	22.84	23.00	1.04	---	---
		Left	L	22.98	23.00	1.00	---	---
			M	22.65	23.00	1.08	0.067	0.072
			H	22.84	23.00	1.04	---	---
		Right	L	22.98	23.00	1.00	---	---
			M	22.65	23.00	1.08	0.144	0.156
			H	22.84	23.00	1.04	---	---
BW=10MH z QPSK 50%RB	Head	Left touch	L	22.24	22.50	1.06	---	---
			M	22.29	22.50	1.05	0.078	0.082
			H	22.26	22.50	1.06	---	---
		Left tilt	L	22.24	22.50	1.06	---	---
			M	22.29	22.50	1.05	0.048	0.050
			H	22.26	22.50	1.06	---	---
		Right touch	L	22.24	22.50	1.06	---	---
			M	22.29	22.50	1.05	0.105	0.110
			H	22.26	22.50	1.06	---	---
		Right tilt	L	22.24	22.50	1.06	---	---
			M	22.29	22.50	1.05	0.097	0.102
			H	22.26	22.50	1.06	---	---

Test case				Meas power	Tune-up	Scaling factor	Meas SAR	Report SAR
Mode	Exposure condition	Position	Channel				First	First
	Body worn & Hotspot	Back	H	22.26	22.50	1.06	---	---
			L	22.24	22.50	1.06	---	---
			M	22.29	22.50	1.05	0.195	0.205
		Front	H	22.26	22.50	1.06	---	---
			L	22.24	22.50	1.06	---	---
			M	22.29	22.50	1.05	0.144	0.151
		Top	H	22.26	22.50	1.06	---	---
			L	22.24	22.50	1.06	---	---
			M	22.29	22.50	1.05	---	---
	Hotspot	Bottom	H	22.26	22.50	1.06	---	---
			L	22.24	22.50	1.06	---	---
			M	22.29	22.50	1.05	0.156	0.164
		Left	H	22.26	22.50	1.06	---	---
			L	22.24	22.50	1.06	---	---
			M	22.29	22.50	1.05	0.062	0.065
		Right	H	22.26	22.50	1.06	---	---
			L	22.24	22.50	1.06	---	---
			M	22.29	22.50	1.05	0.129	0.135
			H	22.26	22.50	1.06	---	---
			L	22.24	22.50	1.06	---	---
			M	22.29	22.50	1.05	---	---

Mode: LTE Band 7

fL (MHz)=2510 MHz

fM (MHz)=2535MHz

fH (MHz)= 2560MHz

Limit of SAR (W/kg): <1.6W/kg (1g Average)

Test case				Meas power	Tune-up	Scaling factor	Meas SAR	Report SAR
Mode	Exposure condition	Position	Channel				First	First
QPSK 1RB	Head	Left touch	L	15.24	15.50	1.06	---	---
			M	15.09	15.50	1.10	0.510	0.561
			H	15.13	15.50	1.09	---	---
		Left tilt	L	15.24	15.50	1.06	---	---
			M	15.09	15.50	1.10	0.320	0.352
			H	15.13	15.50	1.09	---	---
		Right touch	L	15.24	15.50	1.06	---	---
			M	15.09	15.50	1.10	0.705	0.776
			H	15.13	15.50	1.09	---	---
		Right tilt	L	15.24	15.50	1.06	---	---
			M	15.09	15.50	1.10	0.614	0.675
			H	15.13	15.50	1.09	---	---
	Body worn & Hotspot	Back	L	15.24	15.50	1.06	---	---
			M	15.09	15.50	1.10	0.362	0.398
			H	15.13	15.50	1.09	---	---
			L2	15.24	15.50	1.06	---	---
			M2	15.09	15.50	1.10	0.308	0.339
			H2	15.13	15.50	1.09	---	---
		Front	L	15.24	15.50	1.06	---	---
			M	15.09	15.50	1.10	0.254	0.279
			H	15.13	15.50	1.09	---	---
	Hotspot	Top	L	15.24	15.50	1.06	---	---
			M	15.09	15.50	1.10	0.097	0.107
			H	15.13	15.50	1.09	---	---
		Bottom	L	15.24	15.50	1.06	---	---
			M	15.09	15.50	1.10	---	---
			H	15.13	15.50	1.09	---	---
		Left	L	15.24	15.50	1.06	---	---
			M	15.09	15.50	1.10	0.126	0.139
			H	15.13	15.50	1.09	---	---
		Right	L	15.24	15.50	1.06	---	---
			M	15.09	15.50	1.10	---	---
			H	15.13	15.50	1.09	---	---
QPSK 50%RB	Head	Left touch	L	14.74	15.00	1.06	---	---
			M	14.66	15.00	1.08	0.493	0.532

		Left tilt	H	14.66	15.00	1.08	---	---
			L	14.74	15.00	1.06	---	---
			M	14.66	15.00	1.08	0.306	0.330
		Right touch	H	14.66	15.00	1.08	---	---
			L	14.74	15.00	1.06	---	---
			M	14.66	15.00	1.08	0.677	0.731
		Right tilt	H	14.66	15.00	1.08	---	---
			L	14.74	15.00	1.06	---	---
			M	14.66	15.00	1.08	0.586	0.633
	Body worn & Hotspot	Back	L	14.74	15.00	1.06	---	---
			M	14.66	15.00	1.08	0.241	0.260
			H	14.66	15.00	1.08	---	---
		Front	L	14.74	15.00	1.06	---	---
			M	14.66	15.00	1.08	0.208	0.225
			H	14.66	15.00	1.08	---	---
	Hotspot	Top	L	14.74	15.00	1.06	---	---
			M	14.66	15.00	1.08	0.066	0.071
			H	14.66	15.00	1.08	---	---
		Bottom	L	14.74	15.00	1.06	---	---
			M	14.66	15.00	1.08	---	---
			H	14.66	15.00	1.08	---	---
		Left	L	14.74	15.00	1.06	---	---
			M	14.66	15.00	1.08	0.112	0.121
			H	14.66	15.00	1.08	---	---
		Right	L	14.74	15.00	1.06	---	---
			M	14.66	15.00	1.08	---	---
			H	14.66	15.00	1.08	---	---

Note: L2/M2/H2 means secondary supply.

Mode: LTE Band 12

fL (MHz)=704 MHz

fM (MHz)=707.5MHz

fH (MHz)= 711MHz

Limit of SAR (W/kg): <1.6W/kg (1g Average)

Test case				Meas power	Tune-up	Scaling factor	Meas SAR	Report SAR
Mode	Exposure condition	Position	Channel				First	First
BW=10MHz QPSK 1RB	Head	Left touch	L	22.98	23.00	1.00	---	---
			M	22.79	23.00	1.05	0.062	0.065
			H	22.82	23.00	1.04	---	---
		Left tilt	L	22.98	23.00	1.00	---	---
			M	22.79	23.00	1.05	0.030	0.031
			H	22.82	23.00	1.04	---	---
		Right touch	L	22.98	23.00	1.00	---	---
			M	22.79	23.00	1.05	0.097	0.102
			H	22.82	23.00	1.04	---	---
		Right tilt	L	22.98	23.00	1.00	---	---
			M	22.79	23.00	1.05	0.046	0.049
			H	22.82	23.00	1.04	---	---
	Body worn & Hotspot	Back	L	22.98	23.00	1.00	---	---
			M	22.79	23.00	1.05	0.119	0.125
			H	22.82	23.00	1.04	---	---
		Front	L	22.98	23.00	1.00	---	---
			M	22.79	23.00	1.05	0.104	0.109
			H	22.82	23.00	1.04	---	---
	Hotspot	Top	L	22.98	23.00	1.00	---	---
			M	22.79	23.00	1.05	---	---
			H	22.82	23.00	1.04	---	---
		Bottom	L	22.98	23.00	1.00	---	---
			M	22.79	23.00	1.05	0.073	0.077
			H	22.82	23.00	1.04	---	---
		Left	L	22.98	23.00	1.00	---	---
			M	22.79	23.00	1.05	0.080	0.084
			H	22.82	23.00	1.04	---	---
		Right	L	22.98	23.00	1.00	---	---
			M	22.79	23.00	1.05	0.185	0.194
			H	22.82	23.00	1.04	---	---
BW=10MHz QPSK 50%RB	Head	Left touch	L	22.36	22.50	1.03	---	---
			M	22.38	22.50	1.03	0.059	0.061
			H	22.17	22.50	1.08	---	---
		Left tilt	L	22.36	22.50	1.03	---	---
			M	22.38	22.50	1.03	0.027	0.028
			H	22.17	22.50	1.08	---	---
		Right touch	L	22.36	22.50	1.03	---	---
			M	22.38	22.50	1.03	0.087	0.090
			H	22.17	22.50	1.08	---	---

Test case				Meas power	Tune-up	Scaling factor	Meas SAR	Report SAR
Mode	Exposure condition	Position	Channel				First	First
		Right tilt	L	22.36	22.50	1.03	---	---
			M	22.38	22.50	1.03	0.036	0.037
			H	22.17	22.50	1.08	---	---
	Body worn & Hotspot	Back	L	22.36	22.50	1.03	---	---
			M	22.38	22.50	1.03	0.117	0.121
			H	22.17	22.50	1.08	---	---
		Front	L	22.36	22.50	1.03	---	---
			M	22.38	22.50	1.03	0.101	0.104
			H	22.17	22.50	1.08	---	---
	Hotspot	Top	L	22.36	22.50	1.03	---	---
			M	22.38	22.50	1.03	---	---
			H	22.17	22.50	1.08	---	---
		Bottom	L	22.36	22.50	1.03	---	---
			M	22.38	22.50	1.03	0.075	0.077
			H	22.17	22.50	1.08	---	---
		Left	L	22.36	22.50	1.03	---	---
			M	22.38	22.50	1.03	0.083	0.085
			H	22.17	22.50	1.08	---	---
		Right	L	22.36	22.50	1.03	---	---
			M	22.38	22.50	1.03	0.164	0.169
			H	22.17	22.50	1.08	---	---

Mode: BT

Limit of SAR (W/kg): <1.6W/kg (1g Average)

Estimated SAR					
MAX power		Head distance	Body-worn distance	Head SAR	Body-worn SAR
dBm	mw	mm	mm	w/kg	w/kg
2.00	1.58	5	10	0.067	0.033

- $$\frac{(max. \text{ power of channel, including tune-up tolerance, } mW)}{(min. \text{ test separation distance, } mm)} \cdot [\sqrt{f_{GHz}/x}] \text{ W/kg for test separation distances } \leq 50 \text{ mm};$$

where $x = 7.5$ for 1-g SAR, and $x = 18.75$ for 10-g SAR.

Mode: Wi-Fi 2.4GHz

fL (MHz)=2412MHz fM (MHz)=2437MHz

fH (MHz)= 2462MHz

Limit of SAR (W/kg): <1.6W/kg (1g Average)

Test case				Meas power	Tune-up	Scaling factor	Duty factor	Meas SAR	Report SAR
Mode	Exposure condition	Position	Channel					First	First
802.11g	Head	Left touch	L	16.32	18.00	1.47	1.03	---	---
			M	17.75	18.00	1.06	1.03	0.417	0.455
			H	17.02	18.00	1.25	1.03	---	---
		Left tilt	L	16.32	18.00	1.47	1.03	---	---
			M	17.75	18.00	1.06	1.03	0.389	0.424
			H	17.02	18.00	1.25	1.03	---	---
		Right touch	L	16.32	18.00	1.47	1.03	---	---
			M	17.75	18.00	1.06	1.03	0.201	0.219
			H	17.02	18.00	1.25	1.03	---	---
		Right tilt	L	16.32	18.00	1.47	1.03	---	---
			M	17.75	18.00	1.06	1.03	0.193	0.210
			H	17.02	18.00	1.25	1.03	---	---
	Body worn & Hotspot	Back	L	16.32	18.00	1.47	1.03	---	---
			M	17.75	18.00	1.06	1.03	0.178	0.194
			H	17.02	18.00	1.25	1.03	---	---
		Front	L	16.32	18.00	1.47	1.03	---	---
			M	17.75	18.00	1.06	1.03	0.156	0.170
			H	17.02	18.00	1.25	1.03	---	---
	Hotspot	Top	L	16.32	18.00	1.47	1.03	---	---
			M	17.75	18.00	1.06	1.03	0.180	0.196
			H	17.02	18.00	1.25	1.03	---	---
		Bottom	L	16.32	18.00	1.47	1.03	---	---
			M	17.75	18.00	1.06	1.03	---	---
			H	17.02	18.00	1.25	1.03	---	---
		Left	L	16.32	18.00	1.47	1.03	---	---
			M	17.75	18.00	1.06	1.03	---	---
			H	17.02	18.00	1.25	1.03	---	---
		Right	L	16.32	18.00	1.47	1.03	---	---
			M	17.75	18.00	1.06	1.03	0.167	0.182
			H	17.02	18.00	1.25	1.03	---	---

6.11 SAR Measurement Variability

SAR measurement variability must be assessed for each frequency band, which is determined by the SAR probe calibration point and tissue-equivalent medium used for the device measurements. When both head and body tissue-equivalent media are required for SAR measurements in a frequency band, the variability measurement procedures should be applied to the tissue medium with the highest measured SAR, using the highest measured SAR configuration for that tissue-equivalent medium.

The following procedures are applied to determine if repeated measurements are required.

- 1) Repeated measurement is not required when the original highest measured SAR is < 0.80 W/kg; steps 2) through 4) do not apply.
- 2) When the original highest measured SAR is ≥ 0.80 W/kg, repeat that measurement once.
- 3) Perform a second repeated measurement only if the ratio of largest to smallest SAR for the original and first repeated measurements is > 1.20 or when the original or repeated measurement is ≥ 1.45 W/kg ($\sim 10\%$ from the 1-g SAR limit).
- 4) Perform a third repeated measurement only if the original, first or second repeated measurement is ≥ 1.5 W/kg and the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20 .

The Highest Reported/Estimated SAR configuration in Each Frequency Band

Frequency band	Air interface	Head SAR(w/kg)	Body-worn SAR(w/kg)	Hotspot SAR(w/kg)
Below 1GHz	GSM850 WCDMA BANDV LTE BAND5 LTE BAND12	<0.8	<0.8	<0.8
1GHz-2GHz	GSM1900 WCDMA BANDII WCDMA BANDIV LTE BAND2 LTE BAND4	>0.8	<0.8	<0.8
2GHz-3GHz	BT WIFI 2.4GHz LTE BAND7	<0.8	<0.8	<0.8

6.12 Simultaneous Transmission SAR Analysis

Antenna numbers of Simultaneous Transmission	Antennas of Simultaneous Transmission	Simultaneous Transmission Modes
2	DIV ANT+ WLAN/BT ANT	Celluar2/3/4G(mid and high frequency band) +WIFI 2.4GHz Celluar2/3/4G(mid and high frequency band) + BT
	MAIN ANT+ WLAN/BT ANT	Celluar2/3/4G(low frequency band)+ WIFI 2.4GHz Celluar2/3/4G(low frequency band)+BT

Head exposure

Position of worst case	Licensed band	Unlicensed band	Simultaneous SAR(w/kg)
Right cheek	GSM1900	WIFI 2.4G	1.25

Body-worn exposure

Position of worst case	Licensed band	Unlicensed band	Simultaneous SAR(w/kg)
Back	LTE Band7	WIFI 2.4G	0.59

Hotspot exposure

Position of worst case	Licensed band	Unlicensed band	Simultaneous SAR(w/kg)
Back	LTE Band7	WIFI 2.4G	0.59

According to the above tables, all the exposure condition of SAR values < 1.6W/kg.

7 MEASUREMENT UNCERTAINTY

(0.3 - 3 GHz range)								
Error Description	Uncert. value	Prob. Dist.	Div.	(c _i) 1g	(c _i) 10g	Std. Unc. (1g)	Std. Unc. (10g)	(v _i) v _{eff}
Measurement System								
Probe Calibration	±6.0 %	N	1	1	1	±6.0 %	±6.0 %	∞
Axial Isotropy	±4.7 %	R	√3	0.7	0.7	±1.9 %	±1.9 %	∞
Hemispherical Isotropy	±9.6 %	R	√3	0.7	0.7	±3.9 %	±3.9 %	∞
Boundary Effects	±1.0 %	R	√3	1	1	±0.6 %	±0.6 %	∞
Linearity	±4.7 %	R	√3	1	1	±2.7 %	±2.7 %	∞
System Detection Limits	±1.0 %	R	√3	1	1	±0.6 %	±0.6 %	∞
Modulation Response ^m	±2.4 %	R	√3	1	1	±1.4 %	±1.4 %	∞
Readout Electronics	±0.3 %	N	1	1	1	±0.3 %	±0.3 %	∞
Response Time	±0.8 %	R	√3	1	1	±0.5 %	±0.5 %	∞
Integration Time	±2.6 %	R	√3	1	1	±1.5 %	±1.5 %	∞
RF Ambient Noise	±3.0 %	R	√3	1	1	±1.7 %	±1.7 %	∞
RF Ambient Reflections	±3.0 %	R	√3	1	1	±1.7 %	±1.7 %	∞
Probe Positioner	±0.4 %	R	√3	1	1	±0.2 %	±0.2 %	∞
Probe Positioning	±2.9 %	R	√3	1	1	±1.7 %	±1.7 %	∞
Max. SAR Eval.	±2.0 %	R	√3	1	1	±1.2 %	±1.2 %	∞
Test Sample Related								
Device Positioning	±2.9 %	N	1	1	1	±2.9 %	±2.9 %	145
Device Holder	±3.6 %	N	1	1	1	±3.6 %	±3.6 %	5
Power Drift	±5.0 %	R	√3	1	1	±2.9 %	±2.9 %	∞
Power Scaling ^p	±0 %	R	√3	1	1	±0.0 %	±0.0 %	∞
Phantom and Setup								
Phantom Uncertainty	±6.1 %	R	√3	1	1	±3.5 %	±3.5 %	∞
SAR correction	±1.9 %	R	√3	1	0.84	±1.1 %	±0.9 %	∞
Liquid Conductivity (mea.) ^{DAK}	±2.5 %	R	√3	0.78	0.71	±1.1 %	±1.0 %	∞
Liquid Permittivity (mea.) ^{DAK}	±2.5 %	R	√3	0.26	0.26	±0.3 %	±0.4 %	∞
Temp. unc. - Conductivity ^{BB}	±3.4 %	R	√3	0.78	0.71	±1.5 %	±1.4 %	∞
Temp. unc. - Permittivity ^{BB}	±0.4 %	R	√3	0.23	0.26	±0.1 %	±0.1 %	∞
Combined Std. Uncertainty						±11.2 %	±11.1 %	361
Expanded STD Uncertainty						±22.3 %	±22.2 %	

(3 - 6 GHz range)								
Error Description	Uncert. value	Prob. Dist.	Div.	(c_i) 1g	(c_i) 10g	Std. Unc. (1g)	Std. Unc. (10g)	(v_i) v_{eff}
Measurement System								
Probe Calibration	±6.55 %	N	1	1	1	±6.55 %	±6.55 %	∞
Axial Isotropy	±4.7 %	R	$\sqrt{3}$	0.7	0.7	±1.9 %	±1.9 %	∞
Hemispherical Isotropy	±9.6 %	R	$\sqrt{3}$	0.7	0.7	±3.9 %	±3.9 %	∞
Boundary Effects	±2.0 %	R	$\sqrt{3}$	1	1	±1.2 %	±1.2 %	∞
Linearity	±4.7 %	R	$\sqrt{3}$	1	1	±2.7 %	±2.7 %	∞
System Detection Limits	±1.0 %	R	$\sqrt{3}$	1	1	±0.6 %	±0.6 %	∞
Modulation Response ^m	±2.4 %	R	$\sqrt{3}$	1	1	±1.4 %	±1.4 %	∞
Readout Electronics	±0.3 %	N	1	1	1	±0.3 %	±0.3 %	∞
Response Time	±0.8 %	R	$\sqrt{3}$	1	1	±0.5 %	±0.5 %	∞
Integration Time	±2.6 %	R	$\sqrt{3}$	1	1	±1.5 %	±1.5 %	∞
RF Ambient Noise	±3.0 %	R	$\sqrt{3}$	1	1	±1.7 %	±1.7 %	∞
RF Ambient Reflections	±3.0 %	R	$\sqrt{3}$	1	1	±1.7 %	±1.7 %	∞
Probe Positioner	±0.8 %	R	$\sqrt{3}$	1	1	±0.5 %	±0.5 %	∞
Probe Positioning	±6.7 %	R	$\sqrt{3}$	1	1	±3.9 %	±3.9 %	∞
Max. SAR Eval.	±4.0 %	R	$\sqrt{3}$	1	1	±2.3 %	±2.3 %	∞
Test Sample Related								
Device Positioning	±2.9 %	N	1	1	1	±2.9 %	±2.9 %	145
Device Holder	±3.6 %	N	1	1	1	±3.6 %	±3.6 %	5
Power Drift	±5.0 %	R	$\sqrt{3}$	1	1	±2.9 %	±2.9 %	∞
Power Scaling ^p	±0 %	R	$\sqrt{3}$	1	1	±0.0 %	±0.0 %	∞
Phantom and Setup								
Phantom Uncertainty	±6.6 %	R	$\sqrt{3}$	1	1	±3.8 %	±3.8 %	∞
SAR correction	±1.9 %	R	$\sqrt{3}$	1	0.84	±1.1 %	±0.9 %	∞
Liquid Conductivity (mea.) ^{DAK}	±2.5 %	R	$\sqrt{3}$	0.78	0.71	±1.1 %	±1.0 %	∞
Liquid Permittivity (mea.) ^{DAK}	±2.5 %	R	$\sqrt{3}$	0.26	0.26	±0.3 %	±0.4 %	∞
Temp. unc. - Conductivity ^{BB}	±3.4 %	R	$\sqrt{3}$	0.78	0.71	±1.5 %	±1.4 %	∞
Temp. unc. - Permittivity ^{BB}	±0.4 %	R	$\sqrt{3}$	0.23	0.26	±0.1 %	±0.1 %	∞
Combined Std. Uncertainty						±12.3 %	±12.2 %	748
Expanded STD Uncertainty						±24.6 %	±24.5 %	

8 TEST EQUIPMENTS

The measurements were performed using an automated near-field scanning system, DASY5, manufactured by Schmid & Partner Engineering AG (SPEAG) in Switzerland. The SAR extrapolation algorithm used in all measurements was the ‘advanced extrapolation’ algorithm.

The following table lists calibration dates of SPEAG components:

Test Equipment	Model	Serial Number	Calibration date	Calibration Due data
DAE	DAE4	546	2019.08.28	2020.08.27
Dosimetric E-field Probe	ES3DV3	3127	2019.08.27	2020.08.26
Dipole Validation Kit	D750V3	4d023	2017.09.13	2020.09.12
Dipole Validation Kit	D835V2	4d023	2017.09.13	2020.09.12
Dipole Validation Kit	D1800V2	2d084	2017.09.15	2020.09.14
Dipole Validation Kit	D2000V2	1009	2018.02.01	2021.01.31
Dipole Validation Kit	D2450V2	738	2017.09.18	2020.09.17
Dipole Validation Kit	D2600V2	1166	2019.11.08	2022.11.08

Additional test equipment used in testing:

Test Equipment	Model	Serial Number	Calibration date	Calibration Due data
Signal Generator	E4428C	MY45280865	2019.08.20	2020.08.19
Signal Generator	SML 03	103514	2019.08.20	2020.08.19
Power meter	E4417A	MY45101182	2019.08.20	2020.08.19
Power Sensor	E4412A	MY41502214	2019.08.20	2020.08.19
Power Sensor	E4412A	MY41502130	2019.08.20	2020.08.19
Power meter	E4417A	MY45101004	2019.08.20	2020.08.19
Power Sensor	E9300B	MY41496001	2019.08.20	2020.08.19
Power Sensor	E9300B	MY41496003	2019.08.20	2020.08.19
Communication Tester	E5515C	MY48367401	2019.08.20	2020.08.19
Communication Tester	CMU500	114666	2019.08.20	2020.08.19
Communication Tester	MT8820C	6201300660	2019.08.20	2020.08.19
Communication Tester	MT8821C	6201547819	2019.08.20	2020.08.19
Vector Network Analyzer	VNA R140	0011213	2019.09.18	2020.09.17
Dielectric Parameter Probe	DAKS-3.5	1042	2019.09.17	2020.09.16

Detailed information of Isotropic E-field Probe Type ES3DV3

Construction	Symmetrical design with triangular core Interleaved sensors Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g., DGBE)
Calibration	Calibration certificate in Appendix C
Frequency	10 MHz to 4 GHz; Linearity: ± 0.2 dB (30 MHz to 4 GHz)
Optical Surface Detection	± 0.2 mm repeatability in air and clear liquids over diffuse reflecting surfaces
Dimensions	Overall length: 337 mm (Tip: 20 mm) Tip diameter: 3.9 mm (Body: 12 mm) Distance from probe tip to dipole centers: 2.0 mm
Dynamic Range	5 μ W/g to > 100 W/kg; Linearity: ± 0.2 dB
Application	General dosimetry up to 4 GHz Dosimetry in strong gradient fields Compliance tests of mobile phones

Detailed information of Isotropic E-field Probe Type EX3DV4

Construction	Symmetrical design with triangular core Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g., DGBE)
Calibration	Calibration certificate in Appendix C
Frequency	10 MHz to > 6 GHz Linearity: ± 0.2 dB (30 MHz to 6 GHz)
Optical Surface Detection	± 0.3 mm repeatability in air and clear liquids over diffuse reflecting surfaces
Dimensions	Overall length: 337 mm (Tip: 20 mm) Tip diameter: 2.5 mm (Body: 12 mm) Typical distance from probe tip to dipole centers: 1 mm
Dynamic Range	10 μ W/g to > 100 W/kg Linearity: ± 0.2 dB (noise: typically < 1 μ W/g)
Application	High precision dosimetric measurements in any exposure scenario (e.g., very strong gradient fields); the only probe that enables compliance testing for frequencies up to 6 GHz with precision of better 30%.

According to KDB 865664 D01 section 3.2.2, instead of the typical annual calibration recommended by measurement standards, longer calibration intervals of up to three years may be considered when it is demonstrated that the **SAR target, impedance and return loss** of a dipole have remain stable according to the following requirements.

- 1) The test laboratory must ensure that the required supporting information and documentation are included in the SAR report to qualify for the three-year extended calibration interval; otherwise, the IEEE Std 1528-2013 recommended annual calibration applies.
- 2) Immediate re-calibration is required for the following conditions.
 - a) After a dipole is damaged and properly repaired to meet required specifications.
 - b) When the measured SAR deviates from the calibrated SAR value by more than 10% due to changes in physical, mechanical, electrical or other relevant dipole conditions; i.e., the error is not introduced by incorrect measurement procedures or other issues relating to the SAR measurement system.
 - c) When the most recent return-loss result, measured at least annually, deviates by more than 20% from the previous measurement (i.e. value in dB $\times$ 0.2) or not meeting the required 20 dB minimum return-loss requirement.
 - d) When the most recent measurement of the real or imaginary parts of the impedance, measured at least annually, deviates by more than 5 Ω from the previous measurement.

Dipole 750

SAR target


Refers to system check, measured SAR (1g and 10g) deviates from the Target SAR value of calibration report within 10%.

Impedance and Return loss measured by Network analyzer

The most recent measurement of the real or imaginary parts of the impedance, deviates within 5 Ω from the previous measurement. (Data from the last calibration report)

The most recent return-loss result deviates within 20% from the previous measurement. (Data from the last calibration report)

Head TSL Parameters			
Parameters	Target (Ref. Value)	Measured data	Deviation
Impedance	53.9 Ω +0.24j Ω	49.5 Ω -2.15j Ω	<5 Ω
Return loss	-28.4dB	-29.8dB	<20%



Dipole 835

SAR target


Refers to system check, measured SAR (1g and 10g) deviates from the Target SAR value of calibration report within 10%.

Impedance and Return loss measured by Network analyzer

The most recent measurement of the real or imaginary parts of the impedance, deviates within 5 Ω from the previous measurement. (Data from the last calibration report)

The most recent return-loss result deviates within 20% from the previous measurement. (Data from the last calibration report)

TSL Parameters			
Parameters	Target (Ref. Value)	Measured data	Deviation
Impedance	51.0 Ω -2.79j Ω	49.5 Ω -2.15j Ω	<5 Ω
Return loss	-30.7 dB	-33.1 dB	<20%



Dipole1800

SAR target


Refers to system check, measured SAR (1g and 10g) deviates from the Target SAR value of calibration report within 10%.

Impedance and Return loss measured by Network analyzer

The most recent measurement of the real or imaginary parts of the impedance, deviates within 5 Ω from the previous measurement. (Data from the last calibration report)

The most recent return-loss result deviates within 20% from the previous measurement. (Data from the last calibration report)

TSL Parameters			
Parameters	Target (Ref. Value)	Measured data	Deviation
Impedance	49.3 Ω -1.55j Ω	51.9 Ω -4.41j Ω	<5 Ω
Return loss	-35.4 dB	-36.0dB	<20%



Dipole2000

SAR target


Refers to system check, measured SAR (1g and 10g) deviates from the Target SAR value of calibration report within 10%.

Impedance and Return loss measured by Network analyzer

The most recent measurement of the real or imaginary parts of the impedance, deviates within 5 Ω from the previous measurement. (Data from the last calibration report)

The most recent return-loss result deviates within 20% from the previous measurement. (Data from the last calibration report)

TSL Parameters			
Parameters	Target (Ref. Value)	Measured data	Deviation
Impedance	49.8 Ω -2.08j Ω	52.6 Ω -3.44j Ω	<5 Ω
Return loss	-33.6dB	-36.0dB	<20%



Dipole2450

SAR target


Refers to system check, measured SAR (1g and 10g) deviates from the Target SAR value of calibration report within 10%.

Impedance and Return loss measured by Network analyzer

The most recent measurement of the real or imaginary parts of the impedance deviates within 5 Ω from the previous measurement. (Data from the last calibration report)

The most recent return-loss result deviates within 20% from the previous measurement. (Data from the last calibration report)

TSL Parameters			
Parameters	Target (Ref. Value)	Measured data	Deviation
Impedance	51.3 Ω +5.92j Ω	48.9 Ω +4.78j Ω	<5 Ω
Return loss	-24.5 dB	-22.6dB	<20%




ANNEX A – TEST PLOTS


Please refer to the attachment.


ANNEX B – RELEVANT PAGES FROM CALIBRATION REPORTS


Please refer to the attachment.


ANNEX A – TEST PLOTS


System check	750MHz
Communication System: UID 0, CW (0) Frequency: 750 MHz; Medium parameters used: $f = 750 \text{ MHz}$; $\sigma = 0.923 \text{ S/m}$; $\epsilon_r = 41.352$; $\rho = 1000 \text{ kg/m}^3$ Phantom section: Flat Section DASY Configuration: - Probe: ES3DV3 - SN3127; ConvF(6.34, 6.34, 6.34) @ 707.5 MHz; Calibrated: 8/27/2019 - Sensor-Surface: 3mm (Mechanical Surface Detection (Locations From Previous Scan Used)), Sensor-Surface: 3mm (Mechanical Surface Detection) - Electronics: DAE4 Sn546; Calibrated: 8/28/2019 - Phantom: 1660; Type: QD 000 P40 CD; Serial: xxxx - Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373) System Performance Check at Frequencies 750MHz/d=15mm, Pin=250 mW, dist=3.0mm (ES-Probe)/Area Scan (8x15x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (measured) = 2.16 W/kg System Performance Check at Frequencies 750MHz/d=15mm, Pin=250 mW, dist=3.0mm (ES-Probe)/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm Reference Value = 41.00 V/m; Power Drift = 0.13 dB Peak SAR (extrapolated) = 3.26 W/kg SAR(1 g) = 2.06 W/kg; SAR(10 g) = 1.37 W/kg Maximum value of SAR (measured) = 2.49 W/kg 	

System check	835MHz
Communication System: UID 0, CW (0); Frequency: 835 MHz Medium parameters used (interpolated): $f = 835 \text{ MHz}$; $\sigma = 0.911 \text{ S/m}$; $\epsilon_r = 40.266$ $\rho = 1000 \text{ kg/m}^3$ Phantom section: Flat Section DASY5 Configuration: - Probe: ES3DV3 - SN3127; ConvF(6.20, 6.20, 6.20); Calibrated: 8/27/2019; - Sensor-Surface: 3mm (Mechanical Surface Detection) - Electronics: DAE4 Sn546; Calibrated: 8/28/2019 - Phantom: 1660; Type: QD 000 P40 CD; Serial: xxxx - Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373) Configuration 835/835/Area Scan (8x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$ Maximum value of SAR (measured) = 2.72 W/kg Configuration 835/835/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$ Reference Value = 51.67 V/m; Power Drift = 0.08 dB Peak SAR (extrapolated) = 3.58 W/kg SAR(1 g) = 2.39 W/kg; SAR(10 g) = 1.51 W/kg Maximum value of SAR (measured) = 2.75 W/kg	
	

System check	1800MHz
Communication System: UID 0, CW (0); Frequency: 1800 MHz Medium parameters used: $f = 1800 \text{ MHz}$; $\sigma = 1.418 \text{ S/m}$; $\epsilon_r = 40.688$; $\rho = 1000 \text{ kg/m}^3$ Phantom section: Flat Section DASY5 Configuration: - Probe: ES3DV3 - SN3127; ConvF(5.10, 5.10, 5.10); Calibrated: 8/27/2019; - Sensor-Surface: 3mm (Mechanical Surface Detection) - Electronics: DAE4 Sn546; Calibrated: 8/28/2019 - Phantom: 1660; Type: QD 000 P40 CD; Serial: xxxx - Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373) Configuration 1800/1800/Area Scan (7x10x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$ Maximum value of SAR (measured) = 8.31 W/kg Configuration 1800/1800/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$ Reference Value = 76.60 V/m; Power Drift = 0.01 dB Peak SAR (extrapolated) = 17.5 W/kg SAR(1 g) = 9.49 W/kg; SAR(10 g) = 4.97 W/kg Maximum value of SAR (measured) = 12.1 W/kg 	


System check	2000MHz
Communication System: UID 0, CW (0); Frequency: 2000 MHz Medium parameters used: $f = 2000 \text{ MHz}$; $\sigma = 1.427 \text{ S/m}$; $\epsilon_r = 39.844$; $\rho = 1000 \text{ kg/m}^3$ Phantom section: Flat Section DASY5 Configuration: - Probe: ES3DV3 - SN3127; ConvF(5.02, 5.02, 5.02); Calibrated: 8/27/2019; - Sensor-Surface: 3mm (Mechanical Surface Detection) - Electronics: DAE4 Sn546; Calibrated: 8/28/2019 - Phantom: 1660; Type: QD 000 P40 CD; Serial: xxxx - Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373) Configuration 2000/2000/Area Scan (7x10x1): Measurement grid: $dx=10\text{mm}$, $dy=10\text{mm}$ Maximum value of SAR (measured) = 8.40 W/kg Configuration 2000/2000/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$ Reference Value = 76.22 V/m; Power Drift = 0.07 dB Peak SAR (extrapolated) = 18.7 W/kg SAR(1 g) = 9.82 W/kg; SAR(10 g) = 4.96 W/kg Maximum value of SAR (measured) = 12.9 W/kg 	


System check	2450MHz
Communication System: UID 0, CW (0); Frequency: 2450 MHz Medium parameters used: $f = 2450 \text{ MHz}$; $\sigma = 1.866 \text{ S/m}$; $\epsilon_r = 38.343$; $\rho = 1000 \text{ kg/m}^3$ Phantom section: Flat Section DASY5 Configuration: - Probe: ES3DV3 - SN3127; ConvF(4.50, 4.50, 4.50); Calibrated: 8/27/2019; - Sensor-Surface: 3mm (Mechanical Surface Detection), $z = -3.0, 32.0$ - Electronics: DAE4 Sn546; Calibrated: 8/28/2019 - Phantom: 1660; Type: QD 000 P40 CD; Serial: xxxx - DASY52 52.8.8(1258); SEMCAD X 14.6.10(7373) System Performance Check at Frequencies 2450 MHz/2450/Area Scan (8x11x1): Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$ Maximum value of SAR (measured) = 21.2 W/kg System Performance Check at Frequencies 2450 MHz/2450/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$ Reference Value = 108.3 V/m; Power Drift = 0.19 dB Peak SAR (extrapolated) = 28.2 W/kg SAR(1 g) = 13.5 W/kg; SAR(10 g) = 6.14 W/kg Maximum value of SAR (measured) = 22.6 W/kg 	

System check	2600MHz
Communication System: UID 0, CW (0); Frequency: 2600 MHz;Duty Cycle: 1:1 Medium parameters used: $f = 2600 \text{ MHz}$; $\sigma = 1.951 \text{ S/m}$; $\epsilon_r = 39.672$; $\rho = 1000 \text{ kg/m}^3$ Phantom section: Flat Section DASY5 Configuration: - Probe: ES3DV3 - SN3127; ConvF(4.32, 4.32, 4.32) @ 2600 MHz; Calibrated: 8/27/2019 - Sensor-Surface: 3mm (Mechanical Surface Detection) - Electronics: DAE4 Sn546; Calibrated: 8/28/2019 - Phantom: 1660; Type: QD 000 P40 CD; Serial: xxxx - Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.12 (7450) SYSTEM CHECK 2600/Area Scan (5x11x1): Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$ Maximum value of SAR (measured) = 22.7 W/kg SYSTEM CHECK 2600/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$ Reference Value = 102.2 V/m; Power Drift = 0.11 dB Peak SAR (extrapolated) = 33.7 W/kg SAR(1 g) = 14.1 W/kg; SAR(10 g) = 6.52 W/kg Maximum value of SAR (measured) = 26.6 W/kg 	


Main supply


GSM850

Head	Right cheek
Communication System: UID 0, Generic GSM (0); Frequency: 836.6 MHz;Duty Cycle: 1:8.30042 Medium parameters used (interpolated): $f = 836.6$ MHz; $\sigma = 0.905$ S/m; $\epsilon_r = 41.528$; $\rho = 1000$ kg/m³ Phantom section: Right Section DASY5 Configuration: - Probe: ES3DV3 - SN3127; ConvF(6.2, 6.2, 6.2); Calibrated: 2019/8/27; - Sensor-Surface: 3mm (Mechanical Surface Detection) - Electronics: DAE4 Sn546; Calibrated: 2019/8/28 - Phantom: 1660; Type: QD 000 P40 CD; Serial: xxxx - Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373) RC/GSM850/Area Scan (8x9x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (measured) = 0.198 W/kg RC/GSM850/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm Reference Value = 7.024 V/m; Power Drift = 0.19 dB Peak SAR (extrapolated) = 0.226 W/kg SAR(1 g) = 0.195 W/kg; SAR(10 g) = 0.128 W/kg Maximum value of SAR (measured) = 0.192 W/kg	
	


Body-worn& Hotspot	Back
Communication System: UID 0, Generic GSM (0); Frequency: 836.6 MHz;Duty Cycle: 2:8.30042 Medium parameters used (interpolated): $f = 836.6 \text{ MHz}$; $\sigma = 0.905 \text{ S/m}$; $\epsilon_r = 41.528$; $\rho = 1000 \text{ kg/m}^3$ Phantom section: Flat Section DASY5 Configuration: - Probe: ES3DV3 - SN3127; ConvF(6.2, 6.2, 6.2); Calibrated: 2019/8/27; - Sensor-Surface: 3mm (Mechanical Surface Detection) - Electronics: DAE4 Sn546; Calibrated: 2019/8/28 - Phantom: 1660; Type: QD 000 P40 CD; Serial: xxxx - Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373) BACK/GSM 850/Area Scan (8x13x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$ Maximum value of SAR (measured) = 0.384 W/kg BACK/GSM 850/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$ Reference Value = 13.25 V/m; Power Drift = -0.06 dB Peak SAR (extrapolated) = 0.545 W/kg SAR(1 g) = 0.310 W/kg; SAR(10 g) = 0.227 W/kg Maximum value of SAR (measured) = 0.406 W/kg 	


GSM1900

Head	Right cheek
Communication System: UID 0, Generic GSM (0); Frequency: 1880 MHz;Duty Cycle: 1:8.30042 Medium parameters used (interpolated): $f = 1880$ MHz; $\sigma = 1.4$ S/m; $\epsilon_r = 40$; $\rho = 1000$ kg/m³ Phantom section: Left Section DASY5 Configuration: - Probe: ES3DV3 - SN3127; ConvF(5.1, 5.1, 5.1); Calibrated: 2019/8/27; - Sensor-Surface: 3mm (Mechanical Surface Detection) - Electronics: DAE4 Sn546; Calibrated: 2019/8/28 - Phantom: 1660; Type: QD 000 P40 CD; Serial: xxxx - Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373) Configuration 2/GSM1900/Area Scan (8x9x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (measured) = 1.51 W/kg Configuration 2/GSM1900/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm Reference Value = 17.69 V/m; Power Drift = 0.11 dB Peak SAR (extrapolated) = 2.04 W/kg SAR(1 g) = 0.950 W/kg; SAR(10 g) = 0.455 W/kg Maximum value of SAR (measured) = 1.43 W/kg	
	


Body-worn& Hotspot	Back
Communication System: UID 0, Generic GSM (0); Frequency: 1880 MHz;Duty Cycle: 3:8.30042 Medium parameters used (interpolated): $f = 1880 \text{ MHz}$; $\sigma = 1.4 \text{ S/m}$; $\epsilon_r = 40$; $\rho = 1000 \text{ kg/m}^3$ Phantom section: Flat Section DASY5 Configuration: - Probe: ES3DV3 - SN3127; ConvF(5.1, 5.1, 5.1); Calibrated: 2019/8/27; - Sensor-Surface: 3mm (Mechanical Surface Detection (Locations From Previous Scan Used)), Sensor-Surface: 3mm (Mechanical Surface Detection) - Electronics: DAE4 Sn546; Calibrated: 2019/8/28 - Phantom: 1660; Type: QD 000 P40 CD; Serial: xxxx - Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373) BACK/GSM 1900/Area Scan (8x13x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$ Maximum value of SAR (measured) = 0.193 W/kg BACK/GSM 1900/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$ Reference Value = 1.266 V/m; Power Drift = 0.01 dB Peak SAR (extrapolated) = 0.334 W/kg SAR(1 g) = 0.301 W/kg; SAR(10 g) = 0.178 W/kg Maximum value of SAR (measured) = 0.320 W/kg 	


WCDMA Band II

Head	Right cheek
Communication System: UID 0, WCDMA BAND2 (0); Frequency: 1880 MHz;Duty Cycle: 1:1 Medium parameters used (interpolated): $f = 1880$ MHz; $\sigma = 1.4$ S/m; $\epsilon_r = 40$; $\rho = 1000$ kg/m³ Phantom section: Left Section DASY5 Configuration: - Probe: ES3DV3 - SN3127; ConvF(5.1, 5.1, 5.1); Calibrated: 2019/8/27; - Sensor-Surface: 3mm (Mechanical Surface Detection (Locations From Previous Scan Used)), Sensor-Surface: 3mm (Mechanical Surface Detection) - Electronics: DAE4 Sn546; Calibrated: 2019/8/28 - Phantom: 1660; Type: QD 000 P40 CD; Serial: xxxx - Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373) RC/WCDMA 2/Area Scan (8x9x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (measured) = 0.679 W/kg RC/WCDMA 2/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm Reference Value = 10.23 V/m; Power Drift = 0.00 dB Peak SAR (extrapolated) = 0.950 W/kg SAR(1 g) = 0.478 W/kg; SAR(10 g) = 0.253 W/kg Maximum value of SAR (measured) = 0.669 W/kg 	


Body-worn& Hotspot	Back
Communication System: UID 0, WCDMA BAND2 (0); Frequency: 1880 MHz;Duty Cycle: 1:1 Medium parameters used (interpolated): $f = 1880 \text{ MHz}$; $\sigma = 1.4 \text{ S/m}$; $\epsilon_r = 40$; $\rho = 1000 \text{ kg/m}^3$ Phantom section: Flat Section DASY5 Configuration: - Probe: ES3DV3 - SN3127; ConvF(5.1, 5.1, 5.1); Calibrated: 2019/8/27; - Sensor-Surface: 3mm (Mechanical Surface Detection (Locations From Previous Scan Used)), Sensor-Surface: 3mm (Mechanical Surface Detection) - Electronics: DAE4 Sn546; Calibrated: 2019/8/28 - Phantom: 1660; Type: QD 000 P40 CD; Serial: xxxx - Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373) BACK/WCDMA 2/Area Scan (8x13x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$ Maximum value of SAR (measured) = 0.242 W/kg BACK/WCDMA 2/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$ Reference Value = 1.580 V/m; Power Drift = 0.15 dB Peak SAR (extrapolated) = 0.414 W/kg SAR(1 g) = 0.334 W/kg; SAR(10 g) = 0.199 W/kg Maximum value of SAR (measured) = 0.374 W/kg 	


WCDMA Band IV

Head	Right cheek
Communication System: UID 0, WCDMA BAND4 (0); Frequency: 1732.4 MHz;Duty Cycle: 1:1 Medium parameters used (interpolated): $f = 1732.4$ MHz; $\sigma = 1.375$ S/m; $\epsilon_r = 40.07$; $\rho = 1000$ kg/m³ Phantom section: Left Section DASY5 Configuration: - Probe: ES3DV3 - SN3127; ConvF(5.1, 5.1, 5.1); Calibrated: 2019/8/27; - Sensor-Surface: 3mm (Mechanical Surface Detection (Locations From Previous Scan Used)), Sensor-Surface: 3mm (Mechanical Surface Detection) - Electronics: DAE4 Sn546; Calibrated: 2019/8/28 - Phantom: 1660; Type: QD 000 P40 CD; Serial: xxxx - Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373) RC/WCDMA 4/Area Scan (8x9x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (measured) = 0.537 W/kg RC/WCDMA 4/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm Reference Value = 8.988 V/m; Power Drift = 0.07 dB Peak SAR (extrapolated) = 0.739 W/kg SAR(1 g) = 0.383 W/kg; SAR(10 g) = 0.205 W/kg Maximum value of SAR (measured) = 0.527 W/kg	
	


Body-worn& Hotspot	Back
Communication System: UID 0, WCDMA BAND4 (0); Frequency: 1732.4 MHz;Duty Cycle: 1:1 Medium parameters used (interpolated): $f = 1732.4$ MHz; $\sigma = 1.375$ S/m; $\epsilon_r = 40.07$; $\rho = 1000$ kg/m³ Phantom section: Flat Section DASY5 Configuration: - Probe: ES3DV3 - SN3127; ConvF(5.1, 5.1, 5.1); Calibrated: 2019/8/27; - Sensor-Surface: 3mm (Mechanical Surface Detection (Locations From Previous Scan Used)), Sensor-Surface: 3mm (Mechanical Surface Detection) - Electronics: DAE4 Sn546; Calibrated: 2019/8/28 - Phantom: 1660; Type: QD 000 P40 CD; Serial: xxxx - Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373) BACK/WCDMA 4/Area Scan (8x13x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (measured) = 0.422 W/kg BACK/WCDMA 4/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm Reference Value = 10.61 V/m; Power Drift = -0.02 dB Peak SAR (extrapolated) = 0.372 W/kg SAR(1 g) = 0.242 W/kg; SAR(10 g) = 0.125 W/kg Maximum value of SAR (measured) = 0.314 W/kg	
	


WCDMA Band V

Head	Right cheek
Communication System: UID 0, WCDMA BAND 5 (0); Frequency: 836.6 MHz;Duty Cycle: 1:1 Medium parameters used (interpolated): $f = 836.6$ MHz; $\sigma = 0.905$ S/m; $\epsilon_r = 41.528$; $\rho = 1000$ kg/m³ Phantom section: Right Section DASY5 Configuration: - Probe: ES3DV3 - SN3127; ConvF(6.2, 6.2, 6.2); Calibrated: 2019/8/27; - Sensor-Surface: 3mm (Mechanical Surface Detection (Locations From Previous Scan Used)), Sensor-Surface: 3mm (Mechanical Surface Detection) - Electronics: DAE4 Sn546; Calibrated: 2019/8/28 - Phantom: 1660; Type: QD 000 P40 CD; Serial: xxxx - Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373) RC/WCMA 5/Area Scan (8x9x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (measured) = 0.187 W/kg RC/WCMA 5/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm Reference Value = 7.032 V/m; Power Drift = 0.02 dB Peak SAR (extrapolated) = 0.215 W/kg SAR(1 g) = 0.132 W/kg; SAR(10 g) = 0.084 W/kg Maximum value of SAR (measured) = 0.185 W/kg	
	


Body-worn& Hotspot	Back
Communication System: UID 0, WCDMA BAND 5 (0); Frequency: 836.6 MHz;Duty Cycle: 1:1 Medium parameters used (interpolated): $f = 836.6 \text{ MHz}$; $\sigma = 0.905 \text{ S/m}$; $\epsilon_r = 41.528$; $\rho = 1000 \text{ kg/m}^3$ Phantom section: Flat Section DASY5 Configuration: - Probe: ES3DV3 - SN3127; ConvF(6.2, 6.2, 6.2); Calibrated: 2019/8/27; - Sensor-Surface: 3mm (Mechanical Surface Detection (Locations From Previous Scan Used)), Sensor-Surface: 3mm (Mechanical Surface Detection) - Electronics: DAE4 Sn546; Calibrated: 2019/8/28 - Phantom: 1660; Type: QD 000 P40 CD; Serial: xxxx - Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373) BACK/WCDMA 5/Area Scan (8x13x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$ Maximum value of SAR (measured) = 0.251 W/kg BACK/WCDMA 5/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$ Reference Value = 10.75 V/m; Power Drift = -0.02 dB Peak SAR (extrapolated) = 0.417 W/kg SAR(1 g) = 0.244 W/kg; SAR(10 g) = 0.135 W/kg Maximum value of SAR (measured) = 0.295 W/kg 	


LTE Band 2

Head	Right cheek
Communication System: UID 0, LTE band 02 (0); Frequency: 1880 MHz;Duty Cycle: 1:1 Medium parameters used (interpolated): $f = 1880$ MHz; $\sigma = 1.4$ S/m; $\epsilon_r = 40$; $\rho = 1000$ kg/m³ Phantom section: Left Section DASY5 Configuration: - Probe: ES3DV3 - SN3127; ConvF(5.1, 5.1, 5.1); Calibrated: 2019/8/27; - Sensor-Surface: 3mm (Mechanical Surface Detection (Locations From Previous Scan Used)), Sensor-Surface: 3mm (Mechanical Surface Detection) - Electronics: DAE4 Sn546; Calibrated: 2019/8/28 - Phantom: 1660; Type: QD 000 P40 CD; Serial: xxxx - Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373) RC/LTE2/Area Scan (8x9x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (measured) = 0.431 W/kg RC/LTE2/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm Reference Value = 8.632 V/m; Power Drift = -0.09 dB Peak SAR (extrapolated) = 0.615 W/kg SAR(1 g) = 0.306 W/kg; SAR(10 g) = 0.163 W/kg Maximum value of SAR (measured) = 0.444 W/kg	
	


Body-worn& Hotspot	Back
Communication System: UID 0, LTE band 02 (0); Frequency: 1880 MHz;Duty Cycle: 1:1 Medium parameters used (interpolated): $f = 1880 \text{ MHz}$; $\sigma = 1.4 \text{ S/m}$; $\epsilon_r = 40$; $\rho = 1000 \text{ kg/m}^3$ Phantom section: Flat Section DASY5 Configuration: - Probe: ES3DV3 - SN3127; ConvF(5.1, 5.1, 5.1); Calibrated: 2019/8/27; - Sensor-Surface: 3mm (Mechanical Surface Detection (Locations From Previous Scan Used)), Sensor-Surface: 3mm (Mechanical Surface Detection) - Electronics: DAE4 Sn546; Calibrated: 2019/8/28 - Phantom: 1660; Type: QD 000 P40 CD; Serial: xxxx - Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373) BACK/LTE2/Area Scan (8x13x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$ Maximum value of SAR (measured) = 0.418 W/kg BACK/LTE2/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$ Reference Value = 1.285 V/m; Power Drift = 0.40 dB Peak SAR (extrapolated) = 0.370 W/kg SAR(1 g) = 0.345 W/kg; SAR(10 g) = 0.188 W/kg Maximum value of SAR (measured) = 0.442 W/kg 	


LTE Band 4

Head	Right cheek
Communication System: UID 0, LTE band 4 (0); Frequency: 1732.5 MHz;Duty Cycle: 1:1 Medium parameters used (interpolated): $f = 1732.5$ MHz; $\sigma = 1.375$ S/m; $\epsilon_r = 40.07$; $\rho = 1000$ kg/m³ Phantom section: Left Section DASY5 Configuration: - Probe: ES3DV3 - SN3127; ConvF(5.1, 5.1, 5.1); Calibrated: 2019/8/27; - Sensor-Surface: 3mm (Mechanical Surface Detection (Locations From Previous Scan Used)), Sensor-Surface: 3mm (Mechanical Surface Detection) - Electronics: DAE4 Sn546; Calibrated: 2019/8/28 - Phantom: 1660; Type: QD 000 P40 CD; Serial: xxxx - Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373) RC/LTE4/Area Scan (8x9x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (measured) = 0.229 W/kg RC/LTE4/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm Reference Value = 5.499 V/m; Power Drift = -0.16 dB Peak SAR (extrapolated) = 0.339 W/kg SAR(1 g) = 0.170 W/kg; SAR(10 g) = 0.091 W/kg Maximum value of SAR (measured) = 0.242 W/kg 	


Body-worn& Hotspot	Back
Communication System: UID 0, LTE band 4 (0); Frequency: 1732.5 MHz;Duty Cycle: 1:1 Medium parameters used (interpolated): $f = 1732.5 \text{ MHz}$; $\sigma = 1.375 \text{ S/m}$; $\epsilon_r = 40.07$; $\rho = 1000 \text{ kg/m}^3$ Phantom section: Flat Section DASY5 Configuration: - Probe: ES3DV3 - SN3127; ConvF(5.1, 5.1, 5.1); Calibrated: 2019/8/27; - Sensor-Surface: 3mm (Mechanical Surface Detection (Locations From Previous Scan Used)), Sensor-Surface: 3mm (Mechanical Surface Detection) - Electronics: DAE4 Sn546; Calibrated: 2019/8/28 - Phantom: 1660; Type: QD 000 P40 CD; Serial: xxxx - Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373) BACK/LTE4/Area Scan (8x13x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$ Maximum value of SAR (measured) = 0.474 W/kg BACK/LTE4/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$ Reference Value = 10.74 V/m; Power Drift = 0.18 dB Peak SAR (extrapolated) = 0.646 W/kg SAR(1 g) = 0.274 W/kg; SAR(10 g) = 0.148 W/kg Maximum value of SAR (measured) = 0.470 W/kg 	


LTE Band 5

Head	Right cheek
Communication System: UID 0, LTE Band 5 (0); Frequency: 836.5 MHz; Duty Cycle: 1:1 Medium parameters used (interpolated): $f = 836.5 \text{ MHz}$; $\sigma = 0.905 \text{ S/m}$; $\epsilon_r = 41.528$; $\rho = 1000 \text{ kg/m}^3$ Phantom section: Right Section DASY5 Configuration: - Probe: ES3DV3 - SN3127; ConvF(6.2, 6.2, 6.2); Calibrated: 2019/8/27; - Sensor-Surface: 3mm (Mechanical Surface Detection (Locations From Previous Scan Used)), Sensor-Surface: 3mm (Mechanical Surface Detection) - Electronics: DAE4 Sn546; Calibrated: 2019/8/28 - Phantom: 1660; Type: QD 000 P40 CD; Serial: xxxx - Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373) RC/LTE 5/Area Scan (8x9x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$ Maximum value of SAR (measured) = 0.143 W/kg RC/LTE 5/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$ Reference Value = 3.768 V/m; Power Drift = 0.10 dB Peak SAR (extrapolated) = 0.164 W/kg SAR(1 g) = 0.121 W/kg; SAR(10 g) = 0.097 W/kg	
	


Body-worn& Hotspot	Back
Communication System: UID 0, LTE Band 5 (0); Frequency: 836.5 MHz;Duty Cycle: 1:1 Medium parameters used (interpolated): $f = 836.5 \text{ MHz}$; $\sigma = 0.905 \text{ S/m}$; $\epsilon_r = 41.528$; $\rho = 1000 \text{ kg/m}^3$ Phantom section: Flat Section DASY5 Configuration: - Probe: ES3DV3 - SN3127; ConvF(6.2, 6.2, 6.2); Calibrated: 2019/8/27; - Sensor-Surface: 3mm (Mechanical Surface Detection (Locations From Previous Scan Used)), Sensor-Surface: 3mm (Mechanical Surface Detection) - Electronics: DAE4 Sn546; Calibrated: 2019/8/28 - Phantom: 1660; Type: QD 000 P40 CD; Serial: xxxx - Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373) BACK/LTE5/Area Scan (8x13x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$ Maximum value of SAR (measured) = 0.267 W/kg BACK/LTE5/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$ Reference Value = 10.86 V/m; Power Drift = -0.02 dB Peak SAR (extrapolated) = 0.428 W/kg SAR(1 g) = 0.206 W/kg; SAR(10 g) = 0.138 W/kg Maximum value of SAR (measured) = 0.302 W/kg 	


LTE Band 7

Head	Right cheek
Communication System: UID 0, LTE Band 7 (0); Frequency: 2535 MHz;Duty Cycle: 1:1 Medium parameters used (interpolated): $f = 2535 \text{ MHz}$; $\sigma = 1.888 \text{ S/m}$; $\epsilon_r = 39.084$; $\rho = 1000 \text{ kg/m}^3$ Phantom section: Right Section DASY5 Configuration: - Probe: ES3DV3 - SN3127; ConvF(4.32, 4.32, 4.32) @ 2535 MHz; Calibrated: 8/27/2019 - Sensor-Surface: 3mm (Mechanical Surface Detection) - Electronics: DAE4 Sn546; Calibrated: 8/28/2019 - Phantom: 1660; Type: QD 000 P40 CD; Serial: xxxx - Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.12 (7450) Configuration/LTE7 2 2/Area Scan (10x11x1): Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$ Maximum value of SAR (measured) = 1.21 W/kg Configuration/LTE7 2 2/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$ Reference Value = 9.012 V/m; Power Drift = 0.11 dB Peak SAR (extrapolated) = 1.69 W/kg SAR(1 g) = 0.705 W/kg; SAR(10 g) = 0.402 W/kg Maximum value of SAR (measured) = 1.01 W/kg 	


Body-worn& Hotspot	Back
Communication System: UID 0, LTE Band 7 (0); Frequency: 2535 MHz;Duty Cycle: 1:1 Medium parameters used (interpolated): $f = 2535 \text{ MHz}$; $\sigma = 1.888 \text{ S/m}$; $\epsilon_r = 39.084$; $\rho = 1000 \text{ kg/m}^3$ Phantom section: Flat Section DASY5 Configuration: - Probe: ES3DV3 - SN3127; ConvF(4.32, 4.32, 4.32) @ 2535 MHz; Calibrated: 8/27/2019 - Sensor-Surface: 3mm (Mechanical Surface Detection) - Electronics: DAE4 Sn546; Calibrated: 8/28/2019 - Phantom: 1660; Type: QD 000 P40 CD; Serial: xxxx - Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.12 (7450) Configuration/LTE7/Area Scan (10x16x1): Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$ Maximum value of SAR (measured) = 0.433 W/kg Configuration/LTE7/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$ Reference Value = 6.087 V/m; Power Drift = 0.11 dB Peak SAR (extrapolated) = 0.445 W/kg SAR(1 g) = 0.362 W/kg; SAR(10 g) = 0.106 W/kg Maximum value of SAR (measured) = 0.476 W/kg 	


LTE Band 12

Head	Right cheek
Communication System: UID 0, LTE Band 12 (0); Frequency: 707.5 MHz;Duty Cycle: 1:1 Medium parameters used (interpolated): $f = 707.5 \text{ MHz}$; $\sigma = 0.887 \text{ S/m}$; $\epsilon_r = 42.115$; $\rho = 1000 \text{ kg/m}^3$ Phantom section: Right Section DASY5 Configuration: - Probe: ES3DV3 - SN3127; ConvF(6.34, 6.34, 6.34); Calibrated: 2019/8/27; - Sensor-Surface: 3mm (Mechanical Surface Detection (Locations From Previous Scan Used)), Sensor-Surface: 3mm (Mechanical Surface Detection) - Electronics: DAE4 Sn546; Calibrated: 2019/8/28 - Phantom: 1660; Type: QD 000 P40 CD; Serial: xxxx - Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373) RC/LTE 12/Area Scan (8x9x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$ Maximum value of SAR (measured) = 0.105 W/kg RC/LTE 12/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$ Reference Value = 3.314 V/m; Power Drift = 0.08 dB Peak SAR (extrapolated) = 0.129 W/kg SAR(1 g) = 0.097 W/kg; SAR(10 g) = 0.079 W/kg Maximum value of SAR (measured) = 0.112 W/kg 	


Hotspot	Right
Communication System: UID 0, LTE Band 12 (0); Frequency: 707.5 MHz;Duty Cycle: 1:1 Medium parameters used (interpolated): $f = 707.5 \text{ MHz}$; $\sigma = 0.887 \text{ S/m}$; $\epsilon_r = 42.115$; $\rho = 1000 \text{ kg/m}^3$ Phantom section: Flat Section DASY5 Configuration: - Probe: ES3DV3 - SN3127; ConvF(6.34, 6.34, 6.34); Calibrated: 2019/8/27; - Sensor-Surface: 3mm (Mechanical Surface Detection) - Electronics: DAE4 Sn546; Calibrated: 2019/8/28 - Phantom: 1660; Type: QD 000 P40 CD; Serial: xxxx - Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373) RIGHT/LTE 12/Area Scan (4x13x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$ Maximum value of SAR (measured) = 0.276 W/kg RIGHT/LTE 12/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$ Reference Value = 12.43 V/m; Power Drift = 0.08 dB Peak SAR (extrapolated) = 0.228 W/kg SAR(1 g) = 0.185 W/kg; SAR(10 g) = 0.124 W/kg Maximum value of SAR (measured) = 0.287 W/kg 	


WIFI 2.4GHz

Head	Left cheek
Communication System: UID 0, WIFI 2.4GHz (0); Frequency: 2437 MHz;Duty Cycle: 0.972:1 Medium parameters used (interpolated): $f = 2437$ MHz; $\sigma = 1.788$ S/m; $\epsilon_r = 39.219$; $\rho = 1000$ kg/m³ Phantom section: Left Section DASY5 Configuration: - Probe: ES3DV3 - SN3127; ConvF(4.5, 4.5, 4.5); Calibrated: 2019/8/27; - Sensor-Surface: 3mm (Mechanical Surface Detection) - Electronics: DAE4 Sn546; Calibrated: 2019/8/28 - Phantom: 1660; Type: QD 000 P40 CD; Serial: xxxx - Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373) LC/WIFI 2.4/Area Scan (10x11x1): Measurement grid: dx=12mm, dy=12mm Maximum value of SAR (measured) = 0.472 W/kg LC/WIFI 2.4/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm Reference Value = 8.429 V/m; Power Drift = -0.02 dB Peak SAR (extrapolated) = 0.783 W/kg SAR(1 g) = 0.417 W/kg; SAR(10 g) = 0.182 W/kg Maximum value of SAR (measured) = 0.486 W/kg 	

Hotspot	Top
Communication System: UID 0, WIFI 2.4GHz (0); Frequency: 2437 MHz;Duty Cycle: 0.972:1 Medium parameters used (interpolated): $f = 2437 \text{ MHz}$; $\sigma = 1.788 \text{ S/m}$; $\epsilon_r = 39.219$; $\rho = 1000 \text{ kg/m}^3$ Phantom section: Flat Section DASY5 Configuration: - Probe: ES3DV3 - SN3127; ConvF(4.5, 4.5, 4.5); Calibrated: 2019/8/27; - Sensor-Surface: 3mm (Mechanical Surface Detection) - Electronics: DAE4 Sn546; Calibrated: 2019/8/28 - Phantom: 1660; Type: QD 000 P40 CD; Serial: xxxx - Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373) top/WIFI 2.4/Area Scan (6x8x1): Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$ Maximum value of SAR (measured) = 0.199 W/kg top/WIFI 2.4/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$ Reference Value = 4.824 V/m; Power Drift = 0.11 dB Peak SAR (extrapolated) = 0.279 W/kg SAR(1 g) = 0.178 W/kg; SAR(10 g) = 0.065 W/kg Maximum value of SAR (measured) = 0.212 W/kg 	

Secondary supply (worst case among all the frequency bands)

Head	Right cheek
Communication System: UID 0, Generic GSM (0); Frequency: 1880 MHz;Duty Cycle: 1:8.30042 Medium parameters used (interpolated): $f = 1880 \text{ MHz}$; $\sigma = 1.4 \text{ S/m}$; $\epsilon_r = 40$; $\rho = 1000 \text{ kg/m}^3$ Phantom section: Left Section DASY5 Configuration: - Probe: ES3DV3 - SN3127; ConvF(5.1, 5.1, 5.1); Calibrated: 2019/8/27; - Sensor-Surface: 3mm (Mechanical Surface Detection) - Electronics: DAE4 Sn546; Calibrated: 2019/8/28 - Phantom: 1660; Type: QD 000 P40 CD; Serial: xxxx - Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373) Configuration 2/GSM1900 2/Area Scan (8x9x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$ Maximum value of SAR (measured) = 1.03 W/kg Configuration 2/GSM1900 2/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$ Reference Value = 13.25 V/m; Power Drift = 0.18 dB Peak SAR (extrapolated) = 1.72 W/kg SAR(1 g) = 0.903 W/kg; SAR(10 g) = 0.399 W/kg Maximum value of SAR (measured) = 1.29 W/kg	
	

Body-worn& Hotspot	Back
Communication System: UID 0, LTE Band 7 (0); Frequency: 2535 MHz;Duty Cycle: 1:1 Medium parameters used (interpolated): $f = 2535 \text{ MHz}$; $\sigma = 1.888 \text{ S/m}$; $\epsilon_r = 39.084$; $\rho = 1000 \text{ kg/m}^3$ Phantom section: Flat Section DASY5 Configuration: - Probe: ES3DV3 - SN3127; ConvF(4.32, 4.32, 4.32) @ 2535 MHz; Calibrated: 8/27/2019 - Sensor-Surface: 3mm (Mechanical Surface Detection) - Electronics: DAE4 Sn546; Calibrated: 8/28/2019 - Phantom: 1660; Type: QD 000 P40 CD; Serial: xxxx - Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.12 (7450) Configuration/LTE7/Area Scan (10x16x1): Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$ Maximum value of SAR (measured) = 0.416 W/kg Configuration/LTE7/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$ Reference Value = 7.241 V/m; Power Drift = 0.16 dB Peak SAR (extrapolated) = 0.398 W/kg SAR(1 g) = 0.308 W/kg; SAR(10 g) = 0.092 W/kg Maximum value of SAR (measured) = 0.396 W/kg 	

ANNEX B – RELEVANT PAGES FROM CALIBRATION REPORTS

DAE4 Sn:546

Calibration Laboratory of
Schmid & Partner
Engineering AG
Zeughausstrasse 43, 8004 Zurich, Switzerland



S Schweizerischer Kalibrierdienst
C Service suisse d'étalonnage
S Servizio svizzero di taratura
S Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: SCS 0108

Client **SRTC (Auden)**

Certificate No: DAE4-546_Aug19

CALIBRATION CERTIFICATE																							
Object	DAE4 - SD 000 D04 BM - SN: 546																						
Calibration procedure(s)	QA CAL-06.v29 Calibration procedure for the data acquisition electronics (DAE)																						
Calibration date:	August 28, 2019																						
This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI). The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate. All calibrations have been conducted in the closed laboratory facility: environment temperature (22 ± 3)°C and humidity < 70%. Calibration Equipment used (MATE critical for calibration) <table border="1"> <thead> <tr> <th>Primary Standards</th> <th>ID #</th> <th>Cal Date (Certificate No.)</th> <th>Scheduled Calibration</th> </tr> </thead> <tbody> <tr> <td>Kethley Multimeter Type 2001</td> <td>SN: 0610276</td> <td>03-Sep-16 (No.23488)</td> <td>Sep-19</td> </tr> </tbody> </table> <table border="1"> <thead> <tr> <th>Secondary Standards</th> <th>ID #</th> <th>Check Date (in house)</th> <th>Scheduled Check</th> </tr> </thead> <tbody> <tr> <td>Auto DAE Calibration Unit</td> <td>SE UWS 053 AA 1001</td> <td>07-Jan-19 (in house check)</td> <td>In house check: Jan-20</td> </tr> <tr> <td>Calibrator Box V2.1</td> <td>SF UMS 006 AA 1002</td> <td>07-Jan-19 (in house check)</td> <td>In house check: Jan-20</td> </tr> </tbody> </table>				Primary Standards	ID #	Cal Date (Certificate No.)	Scheduled Calibration	Kethley Multimeter Type 2001	SN: 0610276	03-Sep-16 (No.23488)	Sep-19	Secondary Standards	ID #	Check Date (in house)	Scheduled Check	Auto DAE Calibration Unit	SE UWS 053 AA 1001	07-Jan-19 (in house check)	In house check: Jan-20	Calibrator Box V2.1	SF UMS 006 AA 1002	07-Jan-19 (in house check)	In house check: Jan-20
Primary Standards	ID #	Cal Date (Certificate No.)	Scheduled Calibration																				
Kethley Multimeter Type 2001	SN: 0610276	03-Sep-16 (No.23488)	Sep-19																				
Secondary Standards	ID #	Check Date (in house)	Scheduled Check																				
Auto DAE Calibration Unit	SE UWS 053 AA 1001	07-Jan-19 (in house check)	In house check: Jan-20																				
Calibrator Box V2.1	SF UMS 006 AA 1002	07-Jan-19 (in house check)	In house check: Jan-20																				
Calibrated by:	Name Eric Hainfeld	Function Laboratory Technician	Signature 																				
Approved by:	Sven Kühn	Deputy Manager																					
This calibration certificate shall not be reproduced except in full without written approval of the laboratory.			Issued: August 28, 2019																				

Certificate No: DAE4-546_Aug19

Page 1 of 5

Calibration Laboratory of
Schmid & Partner
Engineering AG
Zeughausstrasse 43, 8004 Zurich, Switzerland



S Schweizerischer Kalibrierdienst
C Service suisse d'étalonnage
S Servizio svizzero di taratura
S Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

Glossary

DAE data acquisition electronics
Connector angle information used in DASY system to align probe sensor X to the robot coordinate system.

Methods Applied and Interpretation of Parameters

- **DC Voltage Measurement:** Calibration Factor assessed for use in DASY system by comparison with a calibrated instrument traceable to national standards. The figure given corresponds to the full scale range of the voltmeter in the respective range.
- **Connector angle:** The angle of the connector is assessed measuring the angle mechanically by a tool inserted. Uncertainty is not required.
- The following parameters as documented in the Appendix contain technical information as a result from the performance test and require no uncertainty.
 - **DC Voltage Measurement Linearity:** Verification of the Linearity at +10% and -10% of the nominal calibration voltage. Influence of offset voltage is included in this measurement.
 - **Common mode sensitivity:** Influence of a positive or negative common mode voltage on the differential measurement.
 - **Channel separation:** Influence of a voltage on the neighbor channels not subject to an input voltage.
 - **AD Converter Values with inputs shorted:** Values on the internal AD converter corresponding to zero input voltage
 - **Input Offset Measurement:** Output voltage and statistical results over a large number of zero voltage measurements.
 - **Input Offset Current:** Typical value for information; Maximum channel input offset current, not considering the input resistance.
 - **Input resistance:** Typical value for information: DAE input resistance at the connector, during internal auto-zeroing and during measurement.
 - **Low Battery Alarm Voltage:** Typical value for information. Below this voltage, a battery alarm signal is generated.
 - **Power consumption:** Typical value for information. Supply currents in various operating modes.

DC Voltage Measurement

A/D - Converter Resolution nominal

High Range: 1LSB = 6.1 μ V, full range = -100...+300 mV

Low Range: 1LSB = 61nV, full range = -1.....+3mV

DASY measurement parameters: Auto Zero Time: 3 sec; Measuring time: 3 sec

Calibration Factors	X	Y	Z
High Range	405.352 $\pm$ 0.02% (k=2)	404.098 $\pm$ 0.02% (k=2)	404.222 $\pm$ 0.02% (k=2)
Low Range	3.98830 $\pm$ 1.50% (k=2)	3.95641 $\pm$ 1.50% (k=2)	3.97961 $\pm$ 1.50% (k=2)

Connector Angle

Connector Angle to be used in DASY system	237.0 $^{\circ}$ $\pm$ 1 $^{\circ}$
---	-------------------------------------

Appendix (Additional assessments outside the scope of SCS0108)

1. DC Voltage Linearity

High Range	Reading (μV)	Difference (μV)	Error (%)
Channel X + Input	199995.19	-1.38	-0.00
Channel X + Input	20000.83	-0.80	-0.00
Channel X - Input	-19997.26	4.75	-0.02
Channel Y + Input	199969.47	-7.29	-0.00
Channel Y + Input	20002.52	0.88	0.00
Channel Y - Input	-20001.62	0.45	-0.00
Channel Z + Input	199996.94	0.28	0.00
Channel Z + Input	19998.55	-3.07	-0.02
Channel Z - Input	-20002.95	-0.90	0.00

Low Range	Reading (μV)	Difference (μV)	Error (%)
Channel X + Input	2001.48	0.50	0.03
Channel X + Input	201.14	-0.15	-0.07
Channel X - Input	-198.97	-0.38	0.19
Channel Y + Input	2000.52	-0.41	-0.02
Channel Y + Input	200.95	-0.13	-0.07
Channel Y - Input	-199.00	-0.30	0.15
Channel Z + Input	2000.96	-0.05	-0.00
Channel Z + Input	200.01	-1.11	-0.55
Channel Z - Input	-199.97	-1.27	0.64

2. Common mode sensitivity

DASY measurement parameters: Auto Zero Time: 3 sec; Measuring time: 3 sec

	Common mode Input Voltage (mV)	High Range Average Reading (μV)	Low Range Average Reading (μV)
Channel X	200	2.12	-0.11
	-200	0.79	-0.91
Channel Y	200	1.95	0.12
	-200	-0.90	-1.27
Channel Z	200	1.15	1.74
	-200	-4.83	-4.14

3. Channel separation

DASY measurement parameters: Auto Zero Time: 3 sec; Measuring time: 3 sec

	Input Voltage (mV)	Channel X (μV)	Channel Y (μV)	Channel Z (μV)
Channel X	200	-	-2.05	-3.29
Channel Y	200	9.27	-	-0.65
Channel Z	200	4.64	6.99	-

4. AD-Converter Values with inputs shorted

DASY measurement parameters: Auto Zero Time: 3 sec; Measuring time: 3 sec

	High Range (LSB)	Low Range (LSB)
Channel X	15840	15900
Channel Y	16134	12789
Channel Z	15911	16844

5. Input Offset Measurement

DASY measurement parameters: Auto Zero Time: 3 sec; Measuring time: 3 sec

Input 10MΩ

	Average (μV)	min. Offset (μV)	max. Offset (μV)	Std. Deviation (μV)
Channel X	1.16	0.11	3.01	0.45
Channel Y	0.12	-0.63	1.50	0.46
Channel Z	-0.42	-1.61	0.51	0.42

6. Input Offset Current

Nominal Input circuitry offset current on all channels: <25fA

7. Input Resistance (Typical values for information)

	Zeroing (kΩ)	Measuring (MΩ)
Channel X	200	200
Channel Y	200	200
Channel Z	200	200

8. Low Battery Alarm Voltage (Typical values for information)

Typical values	Alarm Level (VDC)
Supply (+ Vcc)	+7.9
Supply (- Vcc)	-7.6

9. Power Consumption (Typical values for information)

Typical values	Switched off (mA)	Stand by (mA)	Transmitting (mA)
Supply (+ Vcc)	+0.01	+6	+14
Supply (- Vcc)	-0.01	-6	-9

ES3DV3 Sn:3127

Calibration Laboratory of
Schmid & Partner
Engineering AG
Zeughausstrasse 43, 8004 Zurich, Switzerland



S Schweizerischer Kalibrierdienst
C Service suisse d'étalonnage
S Servizio svizzero di taratura
S Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: SCS 0108

Client **SRTC (Auden)**

Certificate No: **ES3-3127_Aug19**

CALIBRATION CERTIFICATE

Object: **ES3DV3 - SN:3127**

Calibration procedure(s): **QA CAL-01.v9, QA CAL-23.v5, QA CAL-25.v7**
Calibration procedure for dosimetric E-field probes

Calibration date: **August 27, 2019**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature $(22 \pm 3)^{\circ}\text{C}$ and humidity $< 70\%$.

Calibration Equipment used (N/A is critical for calibration)

Primary Standards	ID	Cal Date (Certificate No.)	Scheduled Calibration
Power meter NRP	SN: 104778	03-Apr-19 (No. 217-02892/02893)	Apr-20
Power sensor NRP-Z91	SN: 103244	03-Apr-19 (No. 217-02892)	Apr-20
Power sensor NRP-Z91	SN: 103245	03-Apr-19 (No. 217-02893)	Apr-20
Reference 20 dB Attenuator	SN: SS277 (23x)	04-Apr-19 (No. 217-02894)	Apr-20
D4F4	SN: 880	18-Dec-18 (No. DAE4 880_Dec18)	Dec-19
Reference Probe ES3DV2	SN: 3013	31-Dec-19 (No. ES3-3013_Dec18)	Dec-19
Secondary Standards	ID	Check Date (in house)	Scheduled Check
Power meter E4413B	SN: G0412938/4	06-Apr-16 (in house check Jun-19)	In house check: Jun-20
Power sensor E4412A	SN: MY41498087	06-Apr-16 (in house check Jun-19)	In house check: Jun-20
Power sensor E4412A	SN: 003110210	06-Apr-16 (in house check Jun-19)	In house check: Jun-20
RF generator HP 8648C	SN: J53642001700	04-Aug-99 (in house check Jun-16)	In house check: Jun-20
Network Analyzer E8368A	SN: U841080477	31-Mar-14 (in house check Oct-18)	In house check: Oct-19

	Name	Function	Signature
Calibrated by	Manu Soltz	Laboratory Technician	
Approved by	Karja Pakovic	Technical Manager	
This calibration certificate shall not be reproduced except in full without written approval of the laboratory.			Issued: August 29, 2019

Certificate No: ES3-3127_Aug19

Page 1 of 3

Calibration Laboratory of
Schmid & Partner
Engineering AG
Zeughausstrasse 43, 8004 Zurich, Switzerland



S Schweizerischer Kalibrierdienst
C Service suisse d'étalonnage
S Servizio svizzero di taratura
S Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)

Accreditation No.: SCS 0108

The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Glossary:

TSL	tissue simulating liquid
NORM _{x,y,z}	sensitivity in free space
ConvF	sensitivity in TSL / NORM _{x,y,z}
DCP	diode compression point
CF	crest factor (1/duty_cycle) of the RF signal
A, B, C, D	modulation dependent linearization parameters
Polarization φ	φ rotation around probe axis
Polarization θ	θ rotation around an axis that is in the plane normal to probe axis (at measurement center), i.e., $\theta = 0$ is normal to probe axis
Connector Angle	information used in DASY system to align probe sensor X to the robot coordinate system

Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- IEC 62209-1, "Measurement procedure for the assessment of Specific Absorption Rate (SAR) from hand-held and body-mounted devices used next to the ear (frequency range of 300 MHz to 6 GHz)", July 2016
- IEC 62209-2, "Procedure to determine the Specific Absorption Rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz)", March 2010
- KDB 865604, "SAR Measurement Requirements for 100 MHz to 6 GHz"

Methods Applied and Interpretation of Parameters:

- NORM_{x,y,z}**: Assessed for E-field polarization $\theta = 0$ ($f \leq 900$ MHz in TEM-cell; $f > 1800$ MHz: R22 waveguide). NORM_{x,y,z} are only intermediate values, i.e., the uncertainties of NORM_{x,y,z} does not affect the E²-field uncertainty inside TSL (see below ConvF).
- NORM(f)_{x,y,z}** = NORM_{x,y,z} * frequency_response (see Frequency Response Chart). This linearization is implemented in DASY4 software versions later than 4.2. The uncertainty of the frequency response is included in the stated uncertainty of ConvF.
- DCP_{x,y,z}**: DCP are numerical linearization parameters assessed based on the data of power sweep with CW signal (no uncertainty required). DCP does not depend on frequency nor media.
- PAR**: PAR is the Peak to Average Ratio that is not calibrated but determined based on the signal characteristics.
- A_{x,y,z}; B_{x,y,z}; C_{x,y,z}; D_{x,y,z}; VR_{x,y,z}**: A, B, C, D are numerical linearization parameters assessed based on the data of power sweep for specific modulation signal. The parameters do not depend on frequency nor media. VR is the maximum calibration range expressed in RMS voltage across the diode.
- ConvF and Boundary Effect Parameters**: Assessed in flat phantom using E-field (or Temperature Transfer Standard for $f \leq 600$ MHz) and inside waveguide using analytical field distributions based on power measurements for $f > 800$ MHz. The same setups are used for assessment of the parameters applied for boundary compensation (alpha, depth) of which typical uncertainty values are given. These parameters are used in DASY4 software to improve probe accuracy close to the boundary. The sensitivity in TSL corresponds to NORM_{x,y,z} * ConvF whereby the uncertainty corresponds to that given for ConvF. A frequency dependent ConvF is used in DASY version 4.4 and higher which allows extending the validity from ± 50 MHz to ± 100 MHz.
- Spherical isotropy (3D deviation from isotropy)**: in a field of low gradients realized using a flat phantom exposed by a patch antenna.
- Sensor Offset**: The sensor offset corresponds to the offset of virtual measurement center from the probe tip (on probe axis). No tolerance required.
- Connector Angle**: The angle is assessed using the information gained by determining the NORM_x (no uncertainty required).

ES3DV3 - SN:3127

August 27, 2019

DASY/EASY - Parameters of Probe: ES3DV3 - SN:3127

Basic Calibration Parameters

	Sensor X	Sensor Y	Sensor Z	Unc (k=2)
Norm. $(\mu V/(V/m)^2)^{1/2}$	1.26	1.23	1.19	$\pm 10.1\%$
DCP (mV) ¹	103.2	103.9	103.8	

Calibration Results for Modulation Response

UID	Communication System Name		A dB	B dB $\sqrt{\mu V}$	C	D dB	VR mV	Max dev.	Unc (k=2)
0	CW	X	0.0	0.0	1.0	0.00	216.9	13.5 %	+4.7 %
		Y	0.0	0.0	1.0		214.8		
		Y	0.0	0.0	1.0		213.3		

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor $k=2$, which for a normal distribution corresponds to a coverage probability of approximately 95%.

* The uncertainties of Norm. X,Y,Z do not affect the $E^{1/2}$ field uncertainty inside TSL (see Page 5).

* Numerical linearization parameter: uncertainty not required.

* Uncertainty is determined using the max. deviation from linear response applying rectangular distribution and is expressed for the square of the field value.

ES3DV3- SN:3127

August 27, 2019

DASY/EASY - Parameters of Probe: ES3DV3 - SN:3127

Other Probe Parameters

Sensor Arrangement	Triangular
Connector Angle (°)	-19
Mechanical Surface Detection Mode	enabled
Optical Surface Detection Mode	disabled
Probe Overall Length	337 mm
Probe Body Diameter	10 mm
Tip Length	10 mm
Tip Diameter	4 mm
Probe Tip to Sensor X Calibration Point	2 mm
Probe Tip to Sensor Y Calibration Point	2 mm
Probe Tip to Sensor Z Calibration Point	2 mm
Recommended Measurement Distance from Surface	3 mm

ES3DV3- SN:3127

August 27, 2019

DASY/EASY - Parameters of Probe: ES3DV3 - SN:3127

Calibration Parameter Determined in Head Tissue Simulating Media

f (MHz) ^C	Relative Permittivity ^F	Conductivity (S/m) ^F	ConvF X	ConvF Y	ConvF Z	Alpha ^G	Depth (mm)	Unc (k=2)
750	41.9	0.69	6.34	6.34	6.34	0.60	1.25	± 12.0 %
835	41.5	0.90	6.20	6.20	6.20	0.42	1.61	± 12.0 %
1810	40.0	1.40	5.10	5.10	5.10	0.70	1.20	± 12.0 %
2000	40.0	1.40	5.02	5.02	5.02	0.69	1.27	± 12.0 %
2300	39.5	1.57	4.68	4.68	4.68	0.63	1.38	± 12.0 %
2450	39.2	1.80	4.50	4.50	4.50	0.67	1.37	± 12.0 %
2600	39.0	1.96	4.32	4.32	4.32	0.70	1.35	± 12.0 %

^C Frequency validity above 300 MHz of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2); else it is restricted to ± 50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band. Frequency validity below 300 MHz is ± 10, 25, 40, 50 and 70 MHz for ConvF assessments at 30, 84, 125, 150 and 220 MHz respectively. Validity of ConvF assessed at 6 MHz is 4-9 MHz, and ConvF assessed at 13 MHz is 9-19 MHz. Above 5 GHz frequency validity can be extended to ± 110 MHz.


^F At frequencies below 3 GHz, the validity of tissue parameters (ε and σ) can be relaxed to ± 10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of SAR parameters (ε and σ) is restricted to ± 5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.

^G Alpha/Depth are determined during calibration. SPEAG warrants that the remaining deviation due to the boundary effect after compensation is always less than ± 1% for frequencies below 3 GHz and below ± 2% for frequencies between 3-6 GHz at any distance larger than half the probe tip diameter from the boundary.

ES3DV3- SN:3127

August 27, 2019

Frequency Response of E-Field (TEM-Cell:ifi110 EXX, Waveguide: R22)



Uncertainty of Frequency Response of E-field: $\pm 6.3\%$ (k=2)


Certificate No: ES3-3127_Aug19

Page 6 of 9

ES3DV3- SN:3127

August 27, 2019

Receiving Pattern (ϕ), $\theta = 0^\circ$



Uncertainty of Axial Isotropy Assessment: $\pm 0.5\%$ ($k=2$)



Certificate No: ES3-3127_Aug19

Page 7 of 9

ES3DV3- SN:3127

August 27, 2019

Dynamic Range $f(\text{SAR}_{\text{head}})$ (TEM cell, $f_{\text{eval}} = 1900 \text{ MHz}$)



Uncertainty of Linearity Assessment: $\pm 0.6\%$ ($k=2$)


Certificate No: ES3-3127_Aug19

Page 8 of 9


ES3DV3-SN:3127

August 27, 2019

Conversion Factor Assessment



Deviation from Isotropy in Liquid Error (ϕ , θ), $f = 900 \text{ MHz}$



Certificate No: ES3-3127_Aug19

Page 9 of 9

D750V3 Sn:1101



In Collaboration with
s p e a g
CALIBRATION LABORATORY



中国认可
国际互认
校准
CALIBRATION
CNAS L0570

Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62304633-2079 Fax: +86-10-62304633-2504
E-mail: cttl@chinattl.com http://www.chinattl.cn

Client **SRTC**

Certificate No: **Z17-97134**

CALIBRATION CERTIFICATE

Object **D750V3 - SN: 1101**

Calibration Procedure(s) **FF-Z11-003-01**
Calibration Procedures for dipole validation kits

Calibration date: **September 13, 2017**

This calibration Certificate documents the traceability to national standards, which realize the physical units of measurements(SI). The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature(22±3)℃ and humidity<70%.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID #	Cal Date(Calibrated by, Certificate No.)	Scheduled Calibration
Power Meter NRVD	102196	02-Mar-17 (CTTL, No.J17X01254)	Mar-18
Power sensor NRV-Z5	100596	02-Mar-17 (CTTL, No.J17X01254)	Mar-18
Reference Probe EX3DV4	SN 7433	26-Sep-16(SPEAG,No.EX3-7433_Sep16)	Sep-17
DAE4	SN 1331	19-Jan-17(CTTL-SPEAG,No.Z17-97015)	Jan-18
Secondary Standards	ID #	Cal Date(Calibrated by, Certificate No.)	Scheduled Calibration
Signal Generator E4438C	MY49071430	13-Jan-17 (CTTL, No.J17X00286)	Jan-18
Network Analyzer E5071C	MY46111013	13-Jan-17 (CTTL, No.J17X00285)	Jan-18

	Name	Function	Signature
Calibrated by:	Zhao Jing	SAR Test Engineer	
Reviewed by:	Yu Zongying	SAR Test Engineer	
Approved by:	Qi Dianyuan	SAR Project Leader	

Issued: September 16, 2017

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.

Certificate No: Z17-97134

Page 1 of 8



Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62304633-2079 Fax: +86-10-62304633-2504
E-mail: cttl@chinattl.com http://www.chinattl.cn

Glossary:

TSL	tissue simulating liquid
ConvF	sensitivity in TSL / NORM _{x,y,z}
N/A	not applicable or not measured

Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- IEC 62209-1, "Measurement procedure for assessment of specific absorption rate of human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices- Part 1: Device used next to the ear (Frequency range of 300MHz to 6GHz)", July 2016
- IEC 62209-2, "Procedure to measure the Specific Absorption Rate (SAR) For wireless communication devices used in close proximity to the human body (frequency range of 30MHz to 6GHz)", March 2010
- KDB865664, SAR Measurement Requirements for 100 MHz to 6 GHz

Additional Documentation:

- DASY4/5 System Handbook

Methods Applied and Interpretation of Parameters:

- Measurement Conditions:** Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- Antenna Parameters with TSL:** The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- Feed Point Impedance and Return Loss:** These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- Electrical Delay:** One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- SAR measured:** SAR measured at the stated antenna input power.
- SAR normalized:** SAR as measured, normalized to an input power of 1 W at the antenna connector.
- SAR for nominal TSL parameters:** The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of Measurement multiplied by the coverage factor $k=2$, which for a normal distribution Corresponds to a coverage probability of approximately 95%.



In Collaboration with
s p e a g
CALIBRATION LABORATORY

Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62304633-2079 Fax: +86-10-62304633-2504
E-mail: cttl@chinattl.com http://www.chinattl.cn

Measurement Conditions

DASY system configuration, as far as not given on page 1.

DASY Version	DASY52	52.10.0.1446
Extrapolation	Advanced Extrapolation	
Phantom	Triple Flat Phantom 5.1C	
Distance Dipole Center - TSL	15 mm	with Spacer
Zoom Scan Resolution	dx, dy, dz = 5 mm	
Frequency	750 MHz $\pm$ 1 MHz	

Head TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Head TSL parameters	22.0 °C	41.9	0.89 mho/m
Measured Head TSL parameters	(22.0 $\pm$ 0.2) °C	41.5 $\pm$ 6 %	0.88 mho/m $\pm$ 6 %
Head TSL temperature change during test	<1.0 °C	----	----

SAR result with Head TSL

SAR averaged over 1 cm ³ (1 g) of Head TSL	Condition	
SAR measured	250 mW input power	2.05 mW / g
SAR for nominal Head TSL parameters	normalized to 1W	8.26 mW / g $\pm$ 18.8 % (k=2)
SAR averaged over 10 cm ³ (10 g) of Head TSL	Condition	
SAR measured	250 mW input power	1.34 mW / g
SAR for nominal Head TSL parameters	normalized to 1W	5.39 mW / g $\pm$ 18.7 % (k=2)

Body TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Body TSL parameters	22.0 °C	55.5	0.96 mho/m
Measured Body TSL parameters	(22.0 $\pm$ 0.2) °C	55.4 $\pm$ 6 %	0.95 mho/m $\pm$ 6 %
Body TSL temperature change during test	<1.0 °C	----	----

SAR result with Body TSL

SAR averaged over 1 cm ³ (1 g) of Body TSL	Condition	
SAR measured	250 mW input power	2.15 mW / g
SAR for nominal Body TSL parameters	normalized to 1W	8.69 mW / g $\pm$ 18.8 % (k=2)
SAR averaged over 10 cm ³ (10 g) of Body TSL	Condition	
SAR measured	250 mW input power	1.42 mW / g
SAR for nominal Body TSL parameters	normalized to 1W	5.73 mW / g $\pm$ 18.7 % (k=2)



Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62304633-2079 Fax: +86-10-62304633-2504
E-mail: cttl@chinattl.com http://www.chinattl.cn

Appendix (Additional assessments outside the scope of CNAS L0570)

Antenna Parameters with Head TSL

Impedance, transformed to feed point	53.9Ω+ 0.24jΩ
Return Loss	- 28.4dB

Antenna Parameters with Body TSL

Impedance, transformed to feed point	52.0Ω- 2.22jΩ
Return Loss	- 30.6dB

General Antenna Parameters and Design

Electrical Delay (one direction)	1.136 ns
----------------------------------	----------

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard. No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

Additional EUT Data

Manufactured by	SPEAG
-----------------	-------



In Collaboration with
s p e a g
CALIBRATION LABORATORY

Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62304633-2079 Fax: +86-10-62304633-2504
E-mail: cttl@chinattl.com http://www.chinattl.cn

DASY5 Validation Report for Head TSL

Date: 09.13.2017

Test Laboratory: CTTL, Beijing, China

DUT: Dipole 750 MHz; Type: D750V3; Serial: D750V3 - SN: 1101

Communication System: UID 0, CW; Frequency: 750 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 750$ MHz; $\sigma = 0.879$ S/m; $\epsilon_r = 41.54$; $\rho = 1000$ kg/m³

Phantom section: Left Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: EX3DV4 - SN7433; ConvF(10.01, 10.01, 10.01); Calibrated: 9/26/2016;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1331; Calibrated: 1/19/2017
- Phantom: Triple Flat Phantom 5.1C; Type: QD 000 P51 CA; Serial: 1161/1
- Measurement SW: DASY52, Version 52.10 (0); SEMCAD X Version 14.6.10 (7417)


Dipole Calibration/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 53.10 V/m; Power Drift = -0.05 dB

Peak SAR (extrapolated) = 3.17 W/kg

SAR(1 g) = 2.05 W/kg; SAR(10 g) = 1.34 W/kg

Maximum value of SAR (measured) = 2.77 W/kg




0 dB = 2.77 W/kg = 4.42 dBW/kg



In Collaboration with
s p e a g
CALIBRATION LABORATORY

Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62304633-2079 Fax: +86-10-62304633-2504
E-mail: cttl@chinattl.com http://www.chinattl.cn

Impedance Measurement Plot for Head TSL





In Collaboration with
s p e a g
CALIBRATION LABORATORY

Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62304633-2079 Fax: +86-10-62304633-2504
E-mail: cttl@chinattl.com http://www.chinattl.cn

DASY5 Validation Report for Body TSL

Date: 09.13.2017

Test Laboratory: CTTL, Beijing, China

DUT: Dipole 750 MHz; Type: D750V3; Serial: D750V3 - SN: 1101

Communication System: UID 0, CW; Frequency: 750 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 750 \text{ MHz}$; $\sigma = 0.946 \text{ S/m}$; $\epsilon_r = 55.41$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Center Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: EX3DV4 - SN7433; ConvF(9.83, 9.83, 9.83); Calibrated: 9/26/2016;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1331; Calibrated: 1/19/2017
- Phantom: Triple Flat Phantom 5.1C; Type: QD 000 P51 CA; Serial: 1161/1
- Measurement SW: DASY52, Version 52.10 (0); SEMCAD X Version 14.6.10 (7417)


Dipole Calibration/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 53.35 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 3.27 W/kg

SAR(1 g) = 2.15 W/kg; SAR(10 g) = 1.42 W/kg

Maximum value of SAR (measured) = 2.88 W/kg






In Collaboration with
s p e a g
CALIBRATION LABORATORY

Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62304633-2079 Fax: +86-10-62304633-2504
E-mail: cttl@chinattl.com http://www.chinattl.cn

Impedance Measurement Plot for Body TSL



Certificate No: Z17-97134

Page 8 of 8

D835V2 Sn:4d0232



In Collaboration with
s p e a g
CALIBRATION LABORATORY

Add: No.31 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62304633-2079 Fax: +86-10-62304633-2504
E-mail: crtl@chinart.com http://www.chinart.com



中国认可
国际互认
校准
CALIBRATION
CNAS L0570

Client **SRTC**

Certificate No: **Z17-97135**

CALIBRATION CERTIFICATE

Object **D835V2 - SN: 4d023**

Calibration Procedure(s) **FF-Z11-003-01**
Calibration Procedures for dipole validation kits

Calibration date: **September 13, 2017**

This calibration Certificate documents the traceability to national standards, which realize the physical units of measurements(SI). The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature(22±3)°C and humidity<70%.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID #	Cal Date/(Calibrated by, Certificate No.)	Scheduled Calibration
Power Meter NRVD	102196	02-Mar-17 (CTTL, No.J17X01254)	Mar-18
Power sensor NR-VZ5	100596	02-Mar-17 (CTTL, No.J17X01254)	Mar-18
Reference Probe EX3DV4	SN 7433	26-Sep-16(SPEAG,No.EX3-7433_Sep16)	Sep-17
DAL4	SN 1331	19-Jan-17(CTTL-SPEAG,No.Z17-97015)	Jan-18
Secondary Standards	ID #	Cal Date/(Calibrated by, Certificate No.)	Scheduled Calibration
Signal Generator E4438C	MY49071430	13-Jan-17 (CTTL, No.J17X00286)	Jan-18
Network Analyzer E5071C	MY46110673	13-Jan-17 (CTTL, No.J17X00285)	Jan-18

	Name	Function	Signature
Calibrated by:	Zhao Jing	SAR Test Engineer	
Reviewed by:	Yu Zongying	SAR Test Engineer	
Approved by:	Qi Dianyan	SAR Project Leader	

Issued: September 16, 2017

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.

Certificate No: Z17-97135

Page 1 of 8



Add: No 51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62304633-2079 Fax: +86-10-62304633-2504
E-mail: srl@chinartl.com http://www.chinartl.cn

Glossary:

TSL	tissue simulating liquid
ConvF	sensitivity in TSL / NORM _{x,y,z}
N/A	not applicable or not measured

Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- IEC 62209-1, "Measurement procedure for assessment of specific absorption rate of human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices- Part 1: Device used next to the ear (Frequency range of 300MHz to 6GHz)", July 2016
- IEC 62209-2, "Procedure to measure the Specific Absorption Rate (SAR) For wireless communication devices used in close proximity to the human body (frequency range of 30MHz to 6GHz)", March 2010
- KDB865664, SAR Measurement Requirements for 100 MHz to 6 GHz

Additional Documentation:

- DASY4/5 System Handbook

Methods Applied and Interpretation of Parameters:

- Measurement Conditions:** Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- Antenna Parameters with TSL:** The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- Feed Point Impedance and Return Loss:** These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- Electrical Delay:** One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- SAR measured:** SAR measured at the stated antenna input power.
- SAR normalized:** SAR as measured, normalized to an input power of 1 W at the antenna connector.
- SAR for nominal TSL parameters:** The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of Measurement multiplied by the coverage factor $k=2$, which for a normal distribution corresponds to a coverage probability of approximately 95%.



Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62304633-2079 Fax: +86-10-62304633-2564
E-mail: ctd@chinatll.com http://www.chinatll.cn

Measurement Conditions

DASY system configuration, as far as not given on page 1

DASY Version	DASY52	52.10.0.1446
Extrapolation	Advanced Extrapolation	
Phantom	Triple Flat Phantom 5.1C	
Distance Dipole Center - TSL	15 mm	with Spacer
Zoom Scan Resolution	dx, dy, dz = 5 mm	
Frequency	835 MHz $\pm$ 1 MHz	

Head TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Head TSL parameters	22.0 °C	41.5	0.90 mho/m
Measured Head TSL parameters	(22.0 $\pm$ 0.2) °C	41.3 $\pm$ 6 %	0.90 mho/m $\pm$ 6 %
Head TSL temperature change during test	<1.0 °C	---	---

SAR result with Head TSL

SAR averaged over 1 cm^3 (1 g) of Head TSL	Condition	
SAR measured	250 mW input power	2.35 mW / g
SAR for nominal Head TSL parameters	normalized to 1W	9.37 mW / g $\pm$ 18.8 % (k=2)
SAR averaged over 10 cm^3 (10 g) of Head TSL	Condition	
SAR measured	250 mW input power	1.52 mW / g
SAR for nominal Head TSL parameters	normalized to 1W	6.06 mW / g $\pm$ 18.7 % (k=2)

Body TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Body TSL parameters	22.0 °C	55.2	0.97 mho/m
Measured Body TSL parameters	(22.0 $\pm$ 0.2) °C	55.7 $\pm$ 6 %	0.96 mho/m $\pm$ 6 %
Body TSL temperature change during test	<1.0 °C	---	---

SAR result with Body TSL

SAR averaged over 1 cm^3 (1 g) of Body TSL	Condition	
SAR measured	250 mW input power	2.34 mW / g
SAR for nominal Body TSL parameters	normalized to 1W	9.47 mW / g $\pm$ 18.8 % (k=2)
SAR averaged over 10 cm^3 (10 g) of Body TSL	Condition	
SAR measured	250 mW input power	1.53 mW / g
SAR for nominal Body TSL parameters	normalized to 1W	6.17 mW / g $\pm$ 18.7 % (k=2)

Certificate No: Z17-97135

Page 3 of 8



Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62304633-2079 Fax: +86-10-62304633-2504
E-mail: crtl@chinasatl.com http://www.chinasatl.com

Appendix (Additional assessments outside the scope of CNAS L0570)

Antenna Parameters with Head TSL

Impedance, transformed to feed point	51.0Ω- 2.79jΩ
Return Loss	- 30.7dB

Antenna Parameters with Body TSL

Impedance, transformed to feed point	46.6Ω- 3.61jΩ
Return Loss	- 25.8dB

General Antenna Parameters and Design

Electrical Delay (one direction)	1.485 ns
----------------------------------	----------

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard.
No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

Additional EUT Data

Manufactured by	SPEAG
-----------------	-------



Add: No.51 Xueyuan Road, Hejiaman District, Beijing, 100191, China
Tel: +86-10-62304633-2079 Fax: +86-10-62304633-2504
E-mail: ctri@chinaatl.com http://www.chinaatl.com

DASY5 Validation Report for Head TSL

Date: 09.13.2017

Test Laboratory: CTTI, Beijing, China

DUT: Dipole 835 MHz; Type: D835V2; Serial: D835V2 - SN: 4d023

Communication System: UID 0, CW; Frequency: 835 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 835 \text{ MHz}$; $\sigma = 0.903 \text{ S/m}$; $\epsilon_r = 41.34$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: EX3DV4 - SN7433; ConvF(9.82, 9.82, 9.82); Calibrated: 9/26/2016;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1331; Calibrated: 1/19/2017
- Phantom: Triple Flat Phantom 5.1C; Type: QD 000 P51 CA; Serial: 1161/1
- Measurement SW: DASY52, Version 52.10 (0); SEMCAD X Version 14.6.10 (7417)


Dipole Calibration/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 56.28V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 3.66 W/kg

SAR(1 g) = 2.35 W/kg; SAR(10 g) = 1.52 W/kg

Maximum value of SAR (measured) = 3.21 W/kg



0 dB = 3.21 W/kg = 5.07 dBW/kg



Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62304633-2079 Fax: +86-10-62304633-2504
E-mail: ttl@chinaTTL.com http://www.chinaTTL.cn

Impedance Measurement Plot for Head TSL

