
TEST REPORT FOR WLAN TESTING

Report No.: SRTC2019-9004(F)-19122601(F)

Product Name: Smartphone

Product Model: HLTE230E

Applicant: Hisense International Co., Ltd.

Manufacturer: Hisense Communications Co., Ltd.

Specification: FCC Part 15 Subpart C (2019)

FCC ID: 2ADOBHLTE230E

The State Radio_monitoring_center Testing Center (SRTC)

15th Building, No.30 Shixing Street, Shijingshan District,

Beijing, P.R.China

Tel: 86-10-57996183 Fax: 86-10-57996388

CONTENTS

1. GENERAL INFORMATION	2
1.1 NOTES OF THE TEST REPORT	2
1.2 INFORMATION ABOUT THE TESTING LABORATORY	2
1.3 APPLICANT'S DETAILS	2
1.4 MANUFACTURER'S DETAILS	2
1.5 TEST ENVIRONMENT	3
2 DESCRIPTION OF THE DEVICE UNDER TEST	4
2.1 FINAL EQUIPMENT BUILD STATUS	4
2.2 DESCRIPTION OF TEST MODES	6
2.2.1 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL	6
2.3 DUTY CYCLE OF TEST SIGNAL	7
2.4 EUT OPERATING CONDITIONS	8
2.5 SUPPORT EQUIPMENT	8
3 REFERENCE SPECIFICATION	9
4 KEY TO NOTES AND RESULT CODES	9
5 RESULT SUMMARY	10
6 TEST RESULT	11
6.1 PEAK POWER OUTPUT	11
6.2 6dB BANDWIDTH	12
6.3 TRANSMITTER POWER SPECTRAL DENSITY	13
6.4 CONDUCTED OUT OF BAND EMISSION MEASUREMENT	14
6.5 BAND-EDGE MEASUREMENT	15
6.6 SPURIOUS RADIATED EMISSIONS	16
6.7 AC POWER LINE CONDUCTED EMISSION	21
7 MEASUREMENT UNCERTAINTIES	23
8 TEST EQUIPMENTS	24
APPENDIX A – TEST DATA OF CONDUCTED EMISSION	25
APPENDIX B – TEST DATA OF RADIATED EMISSION	42

1. GENERAL INFORMATION

1.1 Notes of the test report

The test report may only be reproduced or published in full. Reproduction or publication of extracts from the report requires the prior written permission of The State Radio_monitoring_center Testing Center (SRTC). The test results relate only to individual items of the samples which have been tested. The certification and accreditation identifiers used in this report shall not be applicable to the tested or calibrated samples thereof. The manufacturer shall not mark the tested samples or items (or a separate part of the item) with the identifiers of certification and accreditation to mislead relevant parties about the tested samples or items.

1.2 Information about the testing laboratory

Company:	The State Radio_monitoring_center Testing Center (SRTC)
Address:	15th Building, No.30 Shixing Street, Shijingshan District, P.R.China
City:	Beijing
Country or Region:	P.R.China
Contacted person:	Liu Jia
Tel:	+86 10 57996183
Fax:	+86 10 57996388
Email:	liujiat@srtc.org.cn

1.3 Applicant's details

Company:	Hisense International Co., Ltd.
Address:	Floor 22, Hisense Tower, 17 Donghai Xi Road, Qingdao, 266071, China
City:	Qingdao
Country or Region:	China
Contacted person:	Geng Ruifeng
Tel:	+86-532-80877742
Fax:	---
Email:	gengruifeng@hisense.com

1.4 Manufacturer's details

Company:	Hisense Communications Co., Ltd.
Address:	No.218 Qianwangang Road, Economic & Technological Development Zone, Qingdao, China
City:	Qingdao
Country or Region:	China
Contacted person:	Deng Tingting
Tel:	+86-532-55753708
Fax:	---
Email:	dengtingting@hisense.com

1.5 Test Environment

Date of Receipt of test sample at SRTC:	2019-12-26
Testing Start Date:	2019-12-26
Testing End Date:	2020-02-11

Environmental Data:	Temperature (°C)	Humidity (%)
Ambient	25	30

Normal Supply Voltage (V d.c.):	3.80
---------------------------------	------

2 DESCRIPTION OF THE DEVICE UNDER TEST

2.1 Final Equipment Build Status

Frequency Band	2.412GHz~2.462GHz
Number of Channel For 20MHz	11
Modulation Type	DBPSK/DQPSK/CCK/BPSK/QPSK/16QAM/64QAM
Duplex Mode	TDD
Channel Spacing	5MHz
Data Rate	802.11b:1Mbps-11Mbps 802.11g:6Mbps-54Mbps 802.11n HT20:MCS0-MCS7
Power Supply	Battery/Charger
Hardware Version	V0.1
Software Version	Hisense_HLTE230E_11_S02_03
IMEI	867400020316612
Antenna type	Refer to Note
Antenna connector	Refer to Note

Note: Antenna requirement (FCC part 15.203)

An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

- The antenna(s) of the EUT are permanently attached.
- There are no provisions for connection to an external antenna.

Note: The antenna provide to the EUT, please refer to the following table:

Brand	Model	Antenna gain	Frequency range(GHz)	Antenna type	Connector Type
N/A	N/A	-0.5dBi	2.412GHz~2.462GHz	Fixed Internal Antenna	N/A
Manufacturers ensure that their designs will not be modified by the user or third parties arbitrary antenna parameters and performance. The EUT complies with the requirement of §15.203.					

Note: The equipments have two supplies, is different on the supplier of Memory/Camera/LCD.

Main Supply

Part Name	Model	Supplier(Brand)	Description
Memory	UNMEN06GC2C31AS	UNIC2	eMMC5.1 Module,64GB,FBGA-153Ball
Memory	MT53E768M32D2NP-053 RS	Micron	LPDDR4X,24Gb(768 Meg x 32 (2 channels x 16 I/O)),WFBGA-200Ball
Camera	H8B13-KS230FF	Kingcome	HI1336,COB,S1326A
Camera	H7B8-KS230BF	Kingcome	HI-846,COB,S0883A
Camera	H9B13-KS230BA	Kingcome	HI1336,COB,3933C-400
Camera	BC12903V0	CXT	GC2385,CSP,HX-M0207H-H306
Camera	BC12904V0	CXT	GC02M1B,CSP,HX-M0207B-H201
LCD+TP	HTF065H029	HOLITECH	ICNL9911S,MLAF065WE51
fingerprint	TW-SW331B-KS230-V1	TOWO	SW331B
Battery	PLV436190	ShenzhenAerospaceElectronicCo.,Ltd	

Secondary Supply

Part Name	Model Name	supplier	Remark
Memory	NCEMASLD-64G	FORESEE	eMMC5.1 Module,64GB,FBGA-153Ball
Memory	RS768M32LB4D2BDS-53BT	RAYSON	LPDDR4X,24Gb(768Mb x 16I/O x 2 channels),WFBGA-200Ball
Camera	TW-13OV53-KS230F-V1	TOWO	OV13853,COB,S1326
Camera	TW-08GC34-KS230B-V1	TOWO	GC8034,COB,1368XX
Camera	TW-13OV53-KS230B-V1	TOWO	OV13853,COB,50064B17
Camera	ST-CFKS230-WJBF-V1	Union Image co.,ltd	GC2375H,CSP,HX-M0207H-H306
Camera	ST-CFKS230-JSBF-V1	Union Image co.,ltd	GC2375H,CSP,DL2002B10-BP
LCD+TP	EQT651WKF003G	easyquick	FT8006, MLAF065WE51X
fingerprint	FS22483BJN	HOLITECH	ICNF7332-A2
Battery	436191P	Shenzhen Tianjin New Energy Technology Co., Ltd.	

2.2 Description of Test Modes

11 channels are provided to this EUT:

CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)
1	2412	7	2442
2	2417	8	2447
3	2422	9	2452
4	2427	10	2457
5	2432	11	2462
6	2437	---	---

2.2.1 Test Mode Applicability and Tested Channel Detail

EUT CONFIGURE MODE	APPLICABLE TO				DESCRIPTION
	RE $\geq$ 1G	RE<1G	PLC	APCM	
-	√	√	√	√	-

Where

RE $\geq$ 1G: Radiated Emission above 1GHz

RE<1G: Radiated Emission below 1GHz

PLC: Power Line Conducted Emission

APCM: Antenna Port Conducted Measurement

Radiated Emission Test (Above 1GHz):

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below.

AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TYPE	DATA RATE (Mbps)
1 to 11	6	DBPSK/ BPSK	1,6,6.5

Radiated Emission Test (Below 1GHz):

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below.

AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TYPE	DATA RATE (Mbps)
1 to 11	6	DBPSK/ BPSK	1,6,6.5

Power Line Conducted Emission Test:

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below.

AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TYPE	DATA RATE (Mbps)
1 to 11	6	DBPSK	1

Antenna Port Conducted Measurement:

This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below.

AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TYPE	DATA RATE (Mbps)
1 to 11	1,3, 6,9, 11	DBPSK/ BPSK	1,6,6.5

2.3 Duty Cycle of Test Signal

Modulation Type	Data Rate	Duty Cycle	Correction factor
11b	1Mbps	99.5%	0.01dB
11g	6Mbps	97.2%	0.11dB
11n(HT20)	6.5Mbps	97.0%	0.11dB
Duty cycle of test signal is > 98 %, duty factor shall not be considered. Correction factor = $10 \cdot \log (1/\text{duty cycle})$			

2.4 EUT Operating conditions

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

2.5 Support Equipment

The following support equipment was used to exercise the DUT during testing:

Equipment	Battery 1
Manufacturer	ShenzhenAerospaceElectronicCo.,Ltd
Model Number	PLV436190

Equipment	Battery 2
Manufacturer	Shenzhen Tianjin New Energy Technology Co., Ltd.
Model Number	436191P

Equipment	Charger
Manufacturer	SHENZHENTIANYIN ELECTRONICS CO., LTD.
Model Number	TPA-46050200UU

Equipment	USB Cable
Manufacturer	kelinDongguan Keling Electronic Technology Co., Ltd
Model Number	KS230B

Equipment	Headset
Manufacturer	kelinDongguan Keling Electronic Technology Co., Ltd
Model Number	KS230B

3 REFERENCE SPECIFICATION



Specification	Version	Title
FCC part15 Subpart C	2019	Intentional radiators
ANSI C63.10	2013	Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices
KDB 558074D01 V05R02r02	April 2, 2019	Guidance for compliance measurements on Digital transmission system, frequency hopping spread spectrum system, and hybrid system devices operating under section 15.247 of the FCC rules

4 KEY TO NOTES AND RESULT CODES

Code	Meaning
PASS	Test result shows that the requirements of the relevant specification have been met.
FAIL	Test result shows that the requirements of the relevant specification have not been met.
N/T	Test case is not tested.

5 RESULT SUMMARY

No.	Test case	Reference	Verdict
1	Transmitter Output Power	15.247(b)(3)	Pass
2	6dB Bandwidth	15.247(a)(2)	Pass
3	Transmitter Power Spectral Density	15.247(e))	Pass
4	Conducted Out of band emission measurement	15.247(d)	Pass
5	Band Edge	15.247(d)	Pass
6	Spurious Radiated Emissions	15.205/15.209	Pass
7	AC Power line Conducted Emission	15.207	Pass
8	Antenna requirement	15.203	Pass(refer to section 2.1)

This Test Report Is Issued by: Mr. Peng Zhen 	Checked by: Mr. Li Bin 
Tested by: Mr. He Dengshun 	Issued date: 20200212

6 TEST RESULT

6.1 Peak Power Output

6.1.1 Ambient condition

Temperature	Relative humidity	Pressure
22°C	40%	101.5kPa

6.2.2 Test limit

Part15.247 (b) (3)

The maximum permissible conducted output power is 1 Watt.

6.2.3 Test Procedure Used

ANSI C63.10-2013 – Section 11.9.1.3

ANSI C63.10-2013 – Section 11.9.2.3.2

KDB 558074 D01 v05r02 – Section 8.3.1.3

6.2.4 Test Settings

Peak Power Measurement


The maximum peak conducted output power may be measured using a broadband peak RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall utilize a fast-responding diode detector.

Average Power Measurement

Average power measurements were performed only when the EUT was transmitting at its maximum power control level using a broadband power meter with a pulse sensor. The power meter implemented triggering and gating capabilities which were set up such that power measurements were recorded only during the ON time of the transmitter. The trace was averaged over 100 traces to obtain the final measured average power.

6.2.5 Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



6.2.6 Test result

The test results are shown in Appendix A.

6.2 6dB Bandwidth

6.2.1 Ambient condition

Temperature	Relative humidity	Pressure
25°C	30%	101.5kPa

6.1.2 Test limit

Part15.247 (a) (2)

The minimum permissible 6dB bandwidth is 500 kHz

6.1.3 Test Procedure Used

ANSI C63.10-2013 – Section 11.8.2 Option 2

KDB 558074 D01 v05r02 – Section 8.2

6.1.4 Test Settings

1. The signal analyzers' automatic bandwidth measurement capability of the spectrum analyzer was used to perform the 6dB bandwidth measurement. The "X" dB bandwidth parameter was set to X = 6. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.

2. RBW = 100 kHz

3. VBW $\geq 3 \times$ RBW

4. Detector = Peak


5. Trace mode = max hold

6. Sweep = auto couple

7. The trace was allowed to stabilize

6.1.5 Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



6.1.6 Test result

The test results are shown in Appendix A.

6.3 Transmitter Power Spectral Density

6.3.1 Ambient condition

Temperature	Relative humidity	Pressure
25°C	30%	101.5kPa

6.3.2 Test limit

Part15.247 (e)

The maximum permissible power spectral density is 8.0dBm in any 3 kHz band.

6.3.3 Test Procedure Used

ANSI C63.10-2013 – Section 11.10.2 Method PKPSD


KDB 558074 D01 v05r02 – Section 8.4

6.3.4 Test Settings

1. Analyzer was set to the center frequency of the DTS channel under investigation
2. Span = 1.5 times the DTS channel bandwidth
3. RBW = 3 kHz
4. VBW = 10 kHz
5. Detector = peak
6. Sweep time = auto couple
7. Trace mode = max hold
8. Trace was allowed to stabilize

6.3.5 Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



6.3.7 Test result

The test results are shown in Appendix A.

6.4 Conducted Out of band emission measurement

6.4.1 Ambient condition

Temperature	Relative humidity	Pressure
25°C	30%	101.5kPa

6.4.2 Test limit

Part 15.247(d): The limit for out-of-band spurious emissions at the band edge is 20dB below the fundamental emission level, as determined from the in-band power measurement of the DTS channel performed in a 100 kHz bandwidth.

6.4.3 Test Procedure Used

ANSI C63.10-2013 – Section 11.11.3

KDB 558074 D01 v05r02 – Section 8.5

6.4.4 Reference level measurement Settings

Establish a reference level by using the following procedure:


- Set instrument center frequency to DTS channel center frequency.
- Set the span to ≥ 1.5 MHz
- Set the RBW = 100 kHz.
- Set the VBW ≥ 300 kHz.
- Detector = peak.
- Sweep time = auto couple.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum PSD level.

6.4.5 Test Settings

- Set the center frequency and span to encompass frequency range to be measured.
- Set the RBW = 100 kHz.
- Set the VBW ≥ 300 kHz.
- Detector = peak.
- Set span to encompass the spectrum to be examined
- Sweep time = auto couple.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum amplitude level.

6.4.6 Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



6.4.7 Test result

The spectrum plots are attached on the following pages. D1 line indicates the highest level, and D2 line indicates the 20dB offset below D1. It shows compliance with the requirement. The test results are shown in Appendix A.

6.5 Band-edge measurement

6.5.1 Ambient condition

Temperature	Relative humidity	Pressure
25°C	30%	101.5kPa

6.5.2 Test limit

Part 15.247(d): The limit for out-of-band spurious emissions at the band edge is 20dB below the fundamental emission level, as determined from the in-band power measurement of the DTS channel performed in a 100 kHz bandwidth.

6.5.3 Test Procedure Used

ANSI C63.10-2013 – Section 11.11.3

KDB 558074 D01 v05r02 – Section 8.7.2

6.5.4 Reference level measurement Settings

Establish a reference level by using the following procedure:


- Set instrument center frequency to DTS channel center frequency.
- Set the span to ≥ 1.5 MHz
- Set the RBW = 100 kHz.
- Set the VBW ≥ 300 kHz.
- Detector = peak.
- Sweep time = auto couple.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum PSD level.

6.5.5 Test Settings

- Set the center frequency and span to encompass frequency range to be measured.
- Set the RBW = 100 kHz.
- Set the VBW ≥ 300 kHz.
- Detector = peak.
- Set span to encompass the spectrum to be examined
- Sweep time = auto couple.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum amplitude level.

6.5.6 Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



6.5.7 Test result

The spectrum plots are attached on the following pages. D1 line indicates the highest level, and D2 line indicates the 20dB offset below D1. It shows compliance with the requirement. The test results are shown in Appendix A.

6.6 Spurious Radiated Emissions

6.6.1 Ambient condition

Temperature	Relative humidity	Pressure
25°C	30%	101.5kPa

6.6.2 Test Description

All out of band radiated spurious emissions are measured with a spectrum analyzer connected to a receive antenna while the EUT is operating at maximum power and at the appropriate frequencies. Only the radiated emissions of the configuration that produced the worst case emissions are reported in this section.

6.6.3 Test limit

Part15.205, 15.209, 15.247(d)

All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47 CFR must not exceed the limits shown in below Table per Section 15.209. The spectrum shall be investigated from the lowest radio frequency signal generated in the device

Frequency [MHz]	Field strength [$\mu\text{V/m}$]	Measured Distance [meters]
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

Radiated Limits

Part15.35(b):

There is also a limit on the radio frequency emissions, as measured using instrumentation with a peak detector function, corresponding to 20 dB above the maximum permitted average limit

Used conversion factor: Limit (dB $\mu\text{V/m}$) = 20 log (Limit ($\mu\text{V/m}$)/1 $\mu\text{V/m}$)

Frequency [MHz]	Detector	Unit (dB $\mu\text{V/m}$)
30~88	Quasi-peak	40.0
88~216	Quasi-peak	43.5
216~960	Quasi-peak	46.0
960~1000	Quasi-peak	54.0
1000~5th harmonic of the highest frequency or 40GHz, whichever is lower	Average	54.0
	Peak	74.0

Conversion Radiated limits

6.6.4 Test Procedure Used

KDB 558074 D01 DTS Meas Guidance v05r02r02 – Section 12.2.7

For Radiated emission below 30MHz

- The EUT was placed on the top of a rotating table 0.8 meters above the ground at chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- Both X and Y axes of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Quasi-Peak Detect Function and recorded the reading with Maximum Hold Mode.

NOTE:

- The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer complied the following setting:

Frequency	RBW
9-150kHz	200-300Hz
0.15-30MHz	9-10kHz

For Radiated emission above 30MHz

- The EUT was placed on the top of a rotating table 0.8 meters (for 30MHz ~ 1GHz) / 1.5 meters (for above 1GHz) above the ground in chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to quasi-peak detect function and recorded the reading with Maximum Hold Mode when the test frequency is below 1 GHz.
- The test-receiver system was set to peak and average detector and recorded the reading with Maximum Hold Mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

For the radiated emission test above 1GHz:

Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.

NOTE:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Average detection (AV) at frequency above 1GHz. If duty cycle of test signal is < 98%, the duty factor need added to measured value.
4. All modes of operation were investigated and the worst-case emissions are reported.

6.6.5 Test Settings

Average Field Strength Measurements per Section 12.2.7 of KDB 558074 (Part 15.35)

Frequency	Detector
<1000MHz	Quasi-peak
>1000MHz	Peak and average

Peak Field Strength Measurements per Section 12.2.7 of KDB 558074 (Part 15.35)


1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW is set depending on measurement frequency, as specified in following table

Frequency	RBW
9-150kHz	200-300Hz
0.15-30MHz	9-10kHz
30-1000MHz	100-120kHz
>1000MHz	1MHz


3. VBW = 3MHz
4. Detector = peak
5. Sweep time = auto couple
6. Trace mode = max hold
7. Trace was allowed to stabilize

6.6.6 Test Setup


For Radiated emission below 30MHz



For Radiated emission 30MHz to 1GHz



For Radiated emission above 1GHz



6.6.7 Test result

The test results are shown in Appendix B.

6.7 AC Power line Conducted Emission

6.7.1 Ambient condition

Temperature	Relative humidity	Pressure
25°C	30%	101.5kPa

6.7.2 Test limit

FCC Part15.207

Frequency of Emission (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56 *	56 to 46 *
0.5-5	56	46
5-30	60	50

* Decreases with the logarithm of the frequency.

The measurement is made according to ANSI C63.10-2013

6.7.3 Test Procedures

a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.


b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.

c. The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) were not recorded.

NOTE: The resolution bandwidth and video bandwidth of test receiver is 9kHz for quasi-peak detection (QP) and average detection (AV) at frequency 0.15MHz-30MHz.

The EUT shall test under the power AC120V/60Hz.

6.7.4 Test Setup



For the actual test configuration, please refer to the attached file (Test Setup Photo).

6.7.5 Test result

The test results are shown in Appendix B.

7 MEASUREMENT UNCERTAINTIES

Items	Uncertainty	
Occupied Bandwidth	3kHz	
Peak power output	0.67dB	
Band edge compliance	1.20dB	
Spurious emissions	30MHz~1GHz	2.83dB
	1GHz~12.75GHz	2.50dB
	12.75GHz~25GHz	2.75dB

8 TEST EQUIPMENTS

No.	Name/ Model	Manufacturer	S/N	Cal date	Cal Due date
1.	Spectrum Analyzer FSV	ROHDE&SCHWARZ	101065	2019.08.20	2020.08.19
2.	Power Meter E4416A	Agilent	MY52370013	2019.03.01	2020.02.29
3.	Power Sensor E9327A	Agilent	MY52420006	2019.03.01	2020.02.29
4.	Attenuator 6810.17.B	HUBER+SUHNER	768710	2019.08.20	2020.08.19
5.	23.18m×16.88m×9.60m Semi-Anechoic Chamber	FRANKONIA	---	----	----
6.	Turn table Diameter:5m	FRANKONIA	----	----	----
7.	Antenna master SAC(MA4.0)	MATURO	----	----	----
8.	9.080m×5.255m×3.525m Shielding room	FRANKONIA	----	----	----
9.	HF 907 Double-Ridged Waveguide Horn Antenna	R&S	100512	2019.08.20	2020.08.19
10.	3160-09 Receive antenna	SCHWARZ-BECK	002058-002	2019.08.20	2020.08.19
11.	ESI 40 EMI test receiver	R&S	100015	2019.08.20	2020.08.19
12.	ESCS30 EMI test receiver	R&S	100029	2019.08.20	2020.08.19
13.	HL562 Receive antenna	R&S	100167	2019.08.20	2020.08.19
14.	ENV216 AMN	R&S	3560.6550.12	2019.08.20	2020.08.19

APPENDIX A – TEST DATA OF CONDUCTED EMISSION

In order to find the worst case condition, Pre-tests are needed at the presence of different data rate. Data rate below means worst-case rate of each test item.

Worst-case data rates are shown as following table.

Test Mode	Data Rate
802.11b	1Mbps
802.11g	6Mbps
802.11n HT20	MCS0(6.5 Mbps)

Conducted power

Modulation type	Peak power output (dBm)		
	2412MHz	2437MHz	2462MHz
11b	19.06	20.31	19.16
11g	23.23	25.19	22.19
11n HT20	22.86	24.37	23.77


Modulation type	Average power output (dBm)		
	2412MHz	2437MHz	2462MHz
11b	16.81	17.37	16.29
11g	15.82	17.75	17.02
11n HT20	15.35	16.98	16.43

6dB Bandwidth


Offset 11.2dB = Attenuator 10dB+ Temporary antenna connector loss 0.2dB+ Cable loss 1dB

Test Mode: 802.11b


Carrier frequency (MHz)	Channel No.	6 dB bandwidth(kHz)
2412	1	9083.1
2437	6	9092.0
2462	11	9092.1



Carrier frequency (MHz): 2412
Channel No.:1
Test Mode: 802.11b




Carrier frequency (MHz): 2437
Channel No.:6
Test Mode: 802.11b




Carrier frequency (MHz): 2462
Channel No.:11
Test Mode: 802.11b

Test Mode: 802.11g


Carrier frequency (MHz)	Channel No.	6 dB bandwidth(kHz)
2412	1	16330.3
2437	6	16342.4
2462	11	16342.4



Carrier frequency (MHz): 2412
Channel No.:1
Test Mode: 802.11g




Carrier frequency (MHz): 2437
Channel No.:6
Test Mode: 802.11g



Carrier frequency (MHz): 2462
Channel No.:11
Test Mode: 802.11g

Test Mode: 802.11n (HT20)


Carrier frequency (MHz)	Channel No.	6 dB bandwidth(kHz)
2412	1	17293.2
2437	6	17581.2
2462	11	17578.2




Carrier frequency (MHz): 2412

Channel No.:1

Test Mode: 802.11n (HT20)



Carrier frequency (MHz): 2437
Channel No.:6
Test Mode: 802.11n (HT20)




Carrier frequency (MHz): 2462
Channel No.:11
Test Mode: 802.11n (HT20)

Transmitter Power Spectral Density


Offset 11.2dB = Attenuator 10dB+ Temporary antenna connector loss 0.2dB+ Cable loss 1.0dB

Test Mode: 802.11b


Carrier frequency (MHz)	Channel No	Power Density (dBm)
2412	1	6.31
2437	6	7.62
2462	11	6.32



Carrier frequency (MHz): 2412
Channel No.1
Test Mode: 802.11b




Carrier frequency (MHz): 2437
Channel No.6
Test Mode: 802.11b




Carrier frequency (MHz): 2462
Channel No.11
Test Mode: 802.11b

Test Mode: 802.11g


Carrier frequency (MHz)	Channel No	Power Density (dBm)
2412	1	-9.31
2442	6	-8.08
2472	11	-8.10



Carrier frequency (MHz): 2412
Channel No.1
Test Mode: 802.11g




Carrier frequency (MHz): 2437
Channel No.6
Test Mode: 802.11g




Carrier frequency (MHz): 2462
Channel No.11
Test Mode: 802.11g

Test Mode: 802.11n (HT20)


Carrier frequency (MHz)	Channel No	Power Density (dBm)
2412	1	-9.20
2437	6	-7.77
2462	11	-8.76



Carrier frequency (MHz): 2412
Channel No.1
Test Mode: 802.11n (HT20)



Carrier frequency (MHz): 2437
Channel No.6
Test Mode: 802.11n (HT20)





Carrier frequency (MHz): 2462
Channel No.11
Test Mode: 802.11n (HT20)

Conducted Out of band emission measurement



Offset 11.2dB = Attenuator 10dB+ Temporary antenna connector loss 0.2dB+ Cable loss 1.0dB

802.11b



CH1



CH6





CH11





802.11g



CH1



CH6





CH11





802.11n (HT20)



CH1



CH6



CH11




Band edge measurement (RF Conducted measurement)


Offset 11.2dB = Attenuator 10dB+ Temporary antenna connector loss 0.2dB+ Cable loss 1.0dB

802.11b

CH1




CH11




802.11g

CH1




CH11




802.11n (HT20)

CH1



CH11



APPENDIX B – TEST DATA OF RADIATED EMISSION

Radiated Emission Band Edge

The worst case attitude: The mobile lay down.

The measurement results are obtained as described below:

Measure Level = Reading Level + cable loss + antenna factor

Sample calculation: (107.18 dBuV/m) = (73.18 dBμV) + (8.90 dB) + (25.10 dB), the corresponding frequency is 2412MHz.

Carrier frequency (MHz): 2412

Channel No.:1

Test Mode: 802.11b

Polarity:Vertical

Detector: Peak

No	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	cable loss (dB)	antenna factor (dB)
1	2412	105.08	71.08	N/A	N/A	8.90	25.10
2	2390	51.52	17.52	-22.48	74.00	8.90	25.10

Carrier frequency (MHz): 2412

Channel No.:1

Test Mode: 802.11b

Polarity:Horizontal

Detector: Peak

No	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	cable loss (dB)	antenna factor (dB)
1	2412	100.09	66.09	N/A	N/A	8.90	25.10
2	2390	47.72	13.72	-26.28	74.00	8.90	25.10

Carrier frequency (MHz): 2412

Channel No.:1

Test Mode: 802.11b

Polarity:Vertical

Detector: Average

No	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	cable loss (dB)	antenna factor (dB)
1	2412	91.21	57.21	N/A	N/A	8.90	25.10
2	2390	39.96	5.96	-14.04	54.00	8.90	25.10

Carrier frequency (MHz): 2412
Channel No.:1
Test Mode: 802.11b
Polarity:Horizontal
Detector: Average

No	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	cable loss (dB)	antenna factor (dB)
1	2412	90.03	56.03	N/A	N/A	8.90	25.10
2	2390	36.21	2.21	-17.79	54.00	8.90	25.10

Carrier frequency (MHz): 2462
Channel No.:11
Test Mode: 802.11b
Polarity:Vertical
Detector: Peak

No	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	cable loss (dB)	antenna factor (dB)
1	2462	104.94	70.94	N/A	N/A	8.90	25.10
2	2483.5	51.94	17.94	-22.06	74.00	8.90	25.10

Carrier frequency (MHz): 2462
Channel No.:11
Test Mode: 802.11b
Polarity:Horizontal
Detector: Peak

No	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	cable loss (dB)	antenna factor (dB)
1	2462	100.34	66.34	N/A	N/A	8.90	25.10
2	2483.5	48.30	14.30	-25.70	74.00	8.90	25.10

Carrier frequency (MHz): 2462
Channel No.:11
Test Mode: 802.11b
Polarity:Vertical
Detector: Average

No	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	cable loss (dB)	antenna factor (dB)
1	2462	91.09	57.09	N/A	N/A	8.90	25.10
2	2483.5	39.19	5.19	-14.81	54.00	8.90	25.10

Carrier frequency (MHz): 2462
Channel No.:11
Test Mode: 802.11b
Polarity:Horizontal
Detector: Average

No	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	cable loss (dB)	antenna factor (dB)
1	2462	89.47	55.47	N/A	N/A	8.90	25.10
2	2483.5	35.56	1.56	-18.44	54.00	8.90	25.10

Carrier frequency (MHz): 2412
Channel No.:1
Test Mode: 802.11g
Polarity: Vertical
Detector: Peak

No	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	cable loss (dB)	antenna factor (dB)
1	2412	105.59	71.59	N/A	N/A	8.90	25.10
2	2390	51.07	17.07	-22.93	74.00	8.90	25.10

Carrier frequency (MHz): 2412
Channel No.:1
Test Mode: 802.11g
Polarity:Horizontal
Detector: Peak

No	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	cable loss (dB)	antenna factor (dB)
1	2412	99.01	65.01	N/A	N/A	8.90	25.10
2	2390	48.29	14.29	-25.71	74.00	8.90	25.10

Carrier frequency (MHz): 2412
Channel No.:1
Test Mode: 802.11g
Polarity: Vertical
Detector: Average

No	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	cable loss (dB)	antenna factor (dB)
1	2412	93.34	59.34	N/A	N/A	8.90	25.10
2	2390	41.02	7.02	-12.98	54.00	8.90	25.10

Carrier frequency (MHz): 2412
Channel No.:1
Test Mode: 802.11g
Polarity:Horizontal
Detector: Average

No	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	cable loss (dB)	antenna factor (dB)
1	2412	87.93	53.93	N/A	N/A	8.90	25.10
2	2390	35.09	1.09	-18.91	54.00	8.90	25.10

Carrier frequency (MHz): 2462
Channel No.:11
Test Mode: 802.11g
Polarity: Vertical
Detector: Peak

No	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	cable loss (dB)	antenna factor (dB)
1	2462	106.47	72.47	N/A	N/A	8.90	25.10
2	2483.5	52.17	18.17	-21.83	74.00	8.90	25.10

Carrier frequency (MHz): 2462
Channel No.:11
Test Mode: 802.11g
Polarity:Horizontal
Detector: Peak

No	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	cable loss (dB)	antenna factor (dB)
1	2462	98.71	64.71	N/A	N/A	8.90	25.10
2	2483.5	48.61	14.61	-25.39	74.00	8.90	25.10

Carrier frequency (MHz): 2462
Channel No.:11
Test Mode: 802.11g
Polarity: Vertical
Detector: Average

No	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	cable loss (dB)	antenna factor (dB)
1	2462	89.67	55.67	N/A	N/A	8.90	25.10
2	2483.5	40.20	6.20	-13.80	54.00	8.90	25.10

Carrier frequency (MHz): 2462
Channel No.:11
Test Mode: 802.11g
Polarity:Horizontal
Detector: Average

No	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	cable loss (dB)	antenna factor (dB)
1	2462	87.67	53.67	N/A	N/A	8.90	25.10
2	2483.5	35.80	1.80	-18.20	54.00	8.90	25.10

Carrier frequency (MHz): 2412
Channel No.:1
Test Mode: 802.11n(HT20)
Polarity: Vertical
Detector: Peak

No	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	cable loss (dB)	antenna factor (dB)
1	2412	106.31	72.31	N/A	N/A	8.90	25.10
2	2390	53.68	19.68	-20.32	74.00	8.90	25.10

Carrier frequency (MHz): 2412
Channel No.:1
Test Mode: 802.11n(HT20)
Polarity:Horizontal
Detector: Peak

No	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	cable loss (dB)	antenna factor (dB)
1	2412	98.26	64.26	N/A	N/A	8.90	25.10
2	2390	47.30	13.30	-26.70	74.00	8.90	25.10

Carrier frequency (MHz): 2412
Channel No.:1
Test Mode: 802.11n(HT20)
Polarity: Vertical
Detector: Average

No	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	cable loss (dB)	antenna factor (dB)
1	2412	91.74	57.74	N/A	N/A	8.90	25.10
2	2390	40.85	6.85	-13.15	54.00	8.90	25.10

Carrier frequency (MHz): 2412
Channel No.:1
Test Mode: 802.11n(HT20)
Polarity:Horizontal
Detector: Average

No	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	cable loss (dB)	antenna factor (dB)
1	2412	89.36	55.36	N/A	N/A	8.90	25.10
2	2390	36.52	2.52	-17.48	54.00	8.90	25.10

Carrier frequency (MHz): 2462
Channel No.:11
Test Mode: 802.11n(HT20)
Polarity: Vertical
Detector: Peak

No	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	cable loss (dB)	antenna factor (dB)
1	2462	107.24	73.24	N/A	N/A	8.90	25.10
2	2483.5	51.92	17.92	-22.08	74.00	8.90	25.10

Carrier frequency (MHz): 2462
Channel No.:11
Test Mode: 802.11n(HT20)
Polarity:Horizontal
Detector: Peak

No	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	cable loss (dB)	antenna factor (dB)
1	2462	99.34	65.34	N/A	N/A	8.90	25.10
2	2483.5	47.91	13.91	-26.09	74.00	8.90	25.10

Carrier frequency (MHz): 2462
Channel No.:11
Test Mode: 802.11n(HT20)
Polarity: Vertical
Detector: Average

No	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	cable loss (dB)	antenna factor (dB)
1	2462	93.34	59.34	N/A	N/A	8.90	25.10
2	2483.5	40.51	6.51	-13.49	54.00	8.90	25.10

Carrier frequency (MHz): 2462
Channel No.:11
Test Mode: 802.11n(HT20)
Polarity:Horizontal
Detector: Average

No	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	cable loss (dB)	antenna factor (dB)
1	2462	88.49	54.49	N/A	N/A	8.90	25.10
2	2483.5	36.67	2.67	-17.33	54.00	8.90	25.10

Sample Calculations

Determining Spurious Emissions Levels

A “reference path loss” is established and the AR_{pl} is the attenuation of “reference path loss”, and including the gain of receive antenna, the gain of the preamplifier, the cable loss.

The measurement results are obtained as described below:

Result= $P_{mea} + AR_{pl}$

Sample calculation: $(28.43 \text{ dB}\mu\text{V/m}) = (46.13 \text{ dB}\mu\text{V}) + (-17.7 \text{ dB/m})$, the corresponding frequency is 43.677000MHz.

The worst case attitude: The mobile lay down.

For 802.11b Channel No.:1

Frequency(MHz)	Result(dBuV/m)	AR_{pl} (dB)	P_{mea} (dBuV/m)	Polarity	Limit (dBuV/m)
43.677000	28.43	-17.7	46.13	Vertical	40.00
89.364000	24.78	-20.8	45.58	Vertical	43.50
96.639000	24.05	-19.3	43.35	Vertical	43.50
310.281500	14.39	-14.8	29.19	Vertical	46.00
408.833500	16.57	-11.5	28.07	Vertical	46.00
903.097000	19.87	-1.4	21.27	Vertical	46.00

For 802.11g Channel No.:1

Frequency(MHz)	Result(dBuV/m)	AR_{pl} (dB)	P_{mea} (dBuV/m)	Polarity	Limit (dBuV/m)
40.573000	27.70	-18.1	45.8	Vertical	40.00
94.844500	24.82	-19.6	44.42	Vertical	43.50
96.881500	23.87	-19.2	43.07	Vertical	43.50
310.281500	13.30	-14.8	28.1	Vertical	46.00
407.912000	16.67	-11.5	28.17	Vertical	46.00
904.212500	19.97	-1.4	21.37	Vertical	46.00

For 802.11n(HT20) Channel No.:1

Frequency(MHz)	Result(dBuV/m)	AR_{pl} (dB)	P_{mea} (dBuV/m)	Polarity	Limit (dBuV/m)
41.785500	28.43	-17.9	46.33	Vertical	40.00
93.244000	24.86	-19.9	44.76	Vertical	43.50
96.590500	24.28	-19.3	43.58	Vertical	43.50
309.020500	12.85	-14.8	27.65	Vertical	46.00
508.743500	15.45	-9.1	24.55	Vertical	46.00
939.472000	20.27	-1.0	21.27	Vertical	46.00

For 802.11b Channel No.:6

Frequency(MHz)	Result(dBuV/m)	ARpl (dB)	Pmea (dBuV/m)	Polarity	Limit (dBuV/m)
41.834000	28.48	-17.9	46.38	Vertical	40.00
94.553500	24.80	-19.7	44.5	Vertical	43.50
96.590500	24.22	-19.3	43.52	Vertical	43.50
308.099000	12.80	-14.9	27.7	Vertical	46.00
503.748000	15.99	-9.2	25.19	Vertical	46.00
950.287500	20.25	-0.9	21.15	Vertical	46.00

For 802.11g Channel No.:6

Frequency(MHz)	Result(dBuV/m)	ARpl (dB)	Pmea (dBuV/m)	Polarity	Limit (dBuV/m)
41.931000	28.31	-17.9	46.21	Vertical	40.00
90.043000	24.87	-20.6	45.47	Vertical	43.50
96.590500	23.96	-19.3	43.26	Vertical	43.50
301.697000	11.19	-15.1	26.29	Vertical	46.00
411.695000	16.43	-11.4	27.83	Vertical	46.00
892.184500	19.84	-1.7	21.54	Vertical	46.00

For 802.11n(HT20) Channel No.:6

Frequency(MHz)	Result(dBuV/m)	ARpl (dB)	Pmea (dBuV/m)	Polarity	Limit (dBuV/m)
41.543000	28.18	-18.0	46.18	Vertical	40.00
95.038500	24.83	-19.6	44.43	Vertical	43.50
96.833000	23.72	-19.2	42.92	Vertical	43.50
308.147500	13.49	-14.9	28.39	Vertical	46.00
405.826500	16.40	-11.5	27.9	Vertical	46.00
913.912500	19.99	-1.3	21.29	Vertical	46.00

For 802.11b Channel No.:11

Frequency(MHz)	Result(dBuV/m)	ARpl (dB)	Pmea (dBuV/m)	Polarity	Limit (dBuV/m)
40.912500	27.86	-18.0	45.86	Vertical	40.00
90.528000	24.81	-20.5	45.31	Vertical	43.50
96.784500	23.63	-19.2	42.83	Vertical	43.50
309.554000	13.27	-14.8	28.07	Vertical	46.00
512.429500	14.95	-8.9	23.85	Vertical	46.00
921.430000	20.06	-1.2	21.26	Vertical	46.00

For 802.11g Channel No.:11

Frequency(MHz)	Result(dBuV/m)	ARpl (dB)	Pmea (dBuV/m)	Polarity	Limit (dBuV/m)
41.009500	27.43	-18.0	45.43	Vertical	40.00
87.715000	20.04	-21.3	41.34	Vertical	40.00
96.930000	20.01	-19.2	39.21	Vertical	43.50
304.607000	11.42	-15.0	26.42	Vertical	46.00
476.636500	14.58	-9.9	24.48	Vertical	46.00
934.622000	20.01	-1.0	21.01	Vertical	46.00

For 802.11n(HT20) Channel No.:11

Frequency(MHz)	Result(dBuV/m)	ARpl (dB)	Pmea (dBuV/m)	Polarity	Limit (dBuV/m)
41.155000	26.57	-18.0	44.57	Vertical	40.00
87.957500	18.98	-21.2	40.18	Vertical	40.00
96.736000	14.38	-19.2	33.58	Vertical	43.50
303.152000	10.65	-15.0	25.65	Vertical	46.00
506.464000	15.27	-9.1	24.37	Vertical	46.00
889.371500	19.48	-1.7	21.18	Vertical	46.00


802.11b MODE Channel 6 is selected as the worst point for RSE.

Channel No.:6

Frequency(MHz)	Result(dBuV/m)	ARpl (dB)	Pmea (dBuV/m)	Polarity	Limit (dBuV/m)
33.540500	24.62	-20.1	44.72	Vertical	40.00
94.505000	22.54	-19.7	42.24	Vertical	43.50
97.415000	22.25	-19.1	41.35	Vertical	43.50
310.233000	13.27	-14.8	28.07	Vertical	46.00
318.769000	16.54	-14.5	31.04	Vertical	46.00
940.539000	18.91	-1.0	19.91	Vertical	46.00


Carrier frequency (MHz): 2412
Channel No.:1

Full Spectrum




Frequency Range: 30MHz -1GHz
Detector: QP mode
Test Mode: 802.11b

Full Spectrum



Frequency Range: 1GHz -6GHz
Detector: Av mode and PK mode
Modulation type: 802.11b


Full Spectrum



Comment


Frequency Range: 6GHz -18GHz
Detector: Av mode and PK mode
Modulation type: 802.11b

Full Spectrum




Frequency Range: 18GHz -40GHz
Detector: Av mode and PK mode
Modulation type: 802.11b

Full Spectrum




Frequency Range: 30MHz -1GHz
Detector: QP mode
Modulation type: 802.11g

Full Spectrum



Frequency Range: 1GHz -6GHz
Detector: Av mode and PK mode
Modulation type: 802.11g


Full Spectrum



Comment


Frequency Range: 6GHz -18GHz
Detector: Av mode and PK mode
Modulation type: 802.11g

Full Spectrum




Frequency Range: 18GHz -40GHz
Detector: Av mode and PK mode
Modulation type: 802.11g

Full Spectrum




Frequency Range: 30MHz -1GHz
Detector: QP mode
Test Mode: 802.11n(HT20)

Full Spectrum



Frequency Range: 1GHz -6GHz
Detector: Av mode and PK mode
Modulation type: 802.11n(HT20)


Full Spectrum



Comment

Frequency Range: 6GHz -18GHz
Detector: Av mode and PK mode
Modulation type: 802.11n(HT20)

Full Spectrum



Frequency Range: 18GHz -40GHz
Detector: Av mode and PK mode
Modulation type: 802.11n(HT20)

Carrier frequency (MHz): 2437

The State Radio_monitoring_center Testing Center (SRTC)

Tel: 86-10-57996183


Fax: 86-10-57996388

Page number: 58 of 73

V1.0.0

Channel No.:6

Full Spectrum




Frequency Range: 30MHz -1GHz

Detector: QP mode

Test Mode: 802.11b

Full Spectrum




Frequency Range: 1GHz -6GHz

Detector: Av mode and PK mode

Modulation type: 802.11b


Full Spectrum



Comment


Frequency Range: 6GHz -18GHz
Detector: Av mode and PK mode
Modulation type: 802.11b

Full Spectrum




Frequency Range: 18GHz -40GHz
Detector: Av mode and PK mode
Modulation type: 802.11b

Full Spectrum




Frequency Range: 30MHz -1GHz
Detector: QP mode
Modulation type: 802.11g

Full Spectrum



Frequency Range: 1GHz -6GHz
Detector: Av mode and PK mode
Modulation type: 802.11g


Full Spectrum



Comment


Frequency Range: 6GHz -18GHz
Detector: Av mode and PK mode
Modulation type: 802.11g

Full Spectrum




Frequency Range: 18GHz -40GHz
Detector: Av mode and PK mode
Modulation type: 802.11g

Full Spectrum




Frequency Range: 30MHz -1GHz
Detector: QP mode
Test Mode: 802.11n(HT20)

Full Spectrum



Frequency Range: 1GHz -6GHz
Detector: Av mode and PK mode
Modulation type: 802.11n(HT20)


Full Spectrum



Comment

Frequency Range: 6GHz -18GHz
Detector: Av mode and PK mode
Modulation type: 802.11n(HT20)


Full Spectrum



Frequency Range: 18GHz -40GHz
Detector: Av mode and PK mode
Modulation type: 802.11n(HT20)


Carrier frequency (MHz): 2462
Channel No.:11

Full Spectrum




Frequency Range: 30MHz -1GHz
Detector: QP mode
Test Mode: 802.11b

Full Spectrum



Frequency Range: 1GHz -6GHz
Detector: Av mode and PK mode
Modulation type: 802.11b


Full Spectrum



Comment


Frequency Range: 6GHz -18GHz
Detector: Av mode and PK mode
Modulation type: 802.11b

Full Spectrum




Frequency Range: 18GHz -40GHz
Detector: Av mode and PK mode
Modulation type: 802.11b

Full Spectrum




Frequency Range: 30MHz -1GHz
Detector: QP mode
Modulation type: 802.11g

Full Spectrum



Frequency Range: 1GHz -6GHz
Detector: Av mode and PK mode
Modulation type: 802.11g


Full Spectrum



Comment


Frequency Range: 6GHz -18GHz
Detector: Av mode and PK mode
Modulation type: 802.11g

Full Spectrum




Frequency Range: 18GHz -40GHz
Detector: Av mode and PK mode
Modulation type: 802.11g

Full Spectrum




Frequency Range: 30MHz -1GHz
Detector: QP mode
Test Mode: 802.11n(HT20)

Full Spectrum



Frequency Range: 1GHz -6GHz
Detector: Av mode and PK mode
Modulation type: 802.11n(HT20)


Full Spectrum



Comment

Frequency Range: 6GHz -18GHz
Detector: Av mode and PK mode
Modulation type: 802.11n(HT20)


Full Spectrum



Frequency Range: 18GHz -40GHz
Detector: Av mode and PK mode
Modulation type: 802.11n(HT20)


Carrier frequency (MHz): 2437 for secondary supply
Channel No.:6

Full Spectrum




Frequency Range: 30MHz-1000MHz
Detector: QP mode
Test Mode: 802.11b

Full Spectrum



Frequency Range: 1GHz-3GHz
Detector: Av mode and PK mode
Modulation type: 802.11b


Full Spectrum



Comment

Frequency Range: 3GHz- 18GHz
Detector: Av mode and PK mode
Modulation type: 802.11b

Full Spectrum



Frequency Range: 18GHz-25GHz
Detector: Av mode and PK mode
Modulation type: 802.11b

AC Power line Conducted Emission


A "reference path loss" Corr.(dB) is established and the $L_{\text{cable}} + \text{ATT} + \text{VDF}$ is the attenuation of "reference path loss", and including the cable loss, the attenuation of the attenuator, the voltage division factor of AMN.

The measurement results are obtained as described below:

$$P_{\text{result}} = P_{\text{mea}} + \text{Corr. (dB)}$$

Sample calculation: $(33.94 \text{ dB}\mu\text{V}) = (4.24 \text{ dB}\mu\text{V}) + (29.7 \text{ dB})$, the corresponding frequency is 0.674507MHz.

Full Spectrum



L+N Line

MEASUREMENT RESULT:

Frequency (MHz)	QuasiPeak (dBμV)	Average (dBμV)	Limit (dBμV)	Margin (dB)	Line	Corr. (dB)	Pmea QuasiPeak (dBμV)	Pmea Average (dBμV)
0.674507	---	33.94	46.00	12.06	L1	29.7	---	4.24
0.678771	42.72	---	56.00	13.28	L1	29.7	13.02	---
0.691564	43.28	---	56.00	12.72	L1	29.7	13.58	---
0.734207	---	35.91	46.00	10.09	L1	29.7	---	6.21
0.734207	45.42	---	56.00	10.58	L1	29.7	15.72	---
0.755529	---	34.95	46.00	11.05	L1	29.7	---	5.25
0.755529	43.73	---	56.00	12.27	L1	29.7	14.03	---
9.915214	---	30.37	50.00	19.63	N	29.9	---	0.47
9.915214	36.85	---	60.00	23.15	N	29.9	6.95	---
11.919429	---	30.47	50.00	19.53	N	29.9	---	0.57
12.038829	---	30.68	50.00	19.32	L1	29.9	---	0.78
12.038829	39.60	---	60.00	20.40	N	29.9	9.7	---

---End of Test Report---