

## **Electromagnetic Emission**

## FCC MEASUREMENT REPORT

### CERTIFICATION OF COMPLIANCE

**FCC Part 15 Certification Measurement** 

**PRODUCT** 

Polaroid Mini Printer

MODEL/Serial No.

POLMP01W / Proto type

MULTIPLE MODEL

: POLMP01B, POLMP01BL, POLMP01R

**BRAND NAME** 

Polaroid

FCC ID

: 2ADOC-POLMP01W

**APPLICANT** 

C&A Licensing LLC

2 Bergen Turnpike, Ridgefield Park, New Jersey, 07660, USA

Attn.: Shlomo Engel / Director

**MANUFACTURER** 

DSGLOBAL.CO,.LTD

(Gasan-dong) 107, Gasan digital 2-ro, Geumcheon-gu, Seoul, KOREA

**FCC CLASSIFICATION** 

: DSS (Part 15 Spread Spectrum Transmitter)

TYPE OF MODULATION

: FHSS (GFSK (BDR), 8DPSK (EDR))

FREQUENCY CHANNEL

2 402 MHz to 2 480 MHz and Channel Spacing 1 MHz (79 Ch)

AIR DATE RATE

BDR (1 Mbps), EDR (2 Mbps, 3 Mbps)

**ANTENNA TYPE** 

Chip Antenna (Integral)

**ANTENNA GAIN** 

: 2.10 dBi max 1.585 mW

**RF POWER RULE PART(S)** 

: FCC Part 15 Subpart C

**FCC PROCEDURE** 

ANSI C63.4-2009

**TEST REPORT No.** 

: ETLE141105.1586

**DATES OF TEST** 

November 19, 2014 to November 21, 2014

REPORT ISSUE DATE

December 01, 2014

**TEST LABORATORY** 

ETL Inc. (FCC Designation Number: KR0022)

The Polaroid Mini Printer, Model POLMP01W has been tested in accordance with the measurement procedures specified in ANSI C63.4-2009 at the ETL Test Laboratory and has been shown to be complied with the electromagnetic radiated emission limits specified in FCC Rule Part15 Subpart C section 15.247. I attest to the accuracy of data. All measurement herein was performed by me or was made under my supervision and is correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

The results of testing in this report apply to the product/system which was tested only. Other similar equipment will not necessarily produce the same results due to production tolerance and measurement

uncertainties.

Prepared by:

Reviewed by:

Jeong Hwan, Pyo (Test Engineer)

Kug Kyoung, Yoon (Chief Engineer)

December 01, 2014

December 01, 2014

ETL Inc.

Head office: #371-51, Gasan-dong, Geumcheon-gu, Seoul, 153-803, Korea

Open site: #499-1, Sagot-ri, Seosin-myeon, Hwaseong-si, Gyeonggi-do, 445-882, Korea

Tel: 82-2-858-0786 Fax: 82-2-858-0788



FCC ID: 2ADOC-POLMP01W

### **Table of Contents**

### **FCC Measurement Report**

- 1. Introduction
- 2. Product Information
- 3. Description of Tests
- 4. Test Condition
- 5. Test Results
  - 5.1 Summary of Test Results
  - 5.2 Channel Bandwidth and Frequency Separation
  - **5.3 Maximum Peak Output Power**
  - 5.4 Bandwidth of Frequency Band Edges
  - **5.5 Number of Hopping Channels**
  - 5.6 Time of Occupancy (Dwell time)
  - **5.7 Spurious Emissions**
  - 5.8 Conducted Emissions Test
  - 5.9 Radio Frequency Exposure
- 6. Sample Calculation
- 7. List of test Equipment used for Measurement

Appendix A. FCC ID Label and Location

**Appendix B. Test Setup Photographs** 

Appendix C. External Photographs

**Appendix D. Internal Photographs** 

Appendix E. Block Diagram

**Appendix F. Circuit Diagram** 

**Appendix G. User Manual** 

**Appendix H. Operational Description** 

Appendix I. Antenna Requirement

Appendix J. Radio Frequency Exposure

Report no. ETLE141105.1586, Page 2 of 56



FCC ID: 2ADOC-POLMP01W

### FCC MEASUREMENT REPORT

**Scope** – Measurement and determination of electromagnetic emission (EME) of radio frequency devices including intentional radiators and/or unintentional radiators for compliance with the technical rules and regulations of the U.S Federal Communications Commission(FCC)

#### **General Information**

Applicant Name : C&A Licensing LLC

Address : 2 Bergen Turnpike, Ridgefield Park,

New Jersey, 07660, USA

Attention : Shlomo Engel / Director

EUT Type : Polaroid Mini Printer

Model Number : POLMP01W

• S/N : NONE

Freq. Range : 2 402 MHz - 2 480 MHz

Number of Channels : 79

Modulation Technique : FHSS (GFSK (BDR), 8DPSK (EDR))

• Frequency Channel : 2 402 MHz to 2 480 MHz and Channel Spacing 1 MHz (79 Ch)

Air Data Rate : BDR (1 Mbps), EDR (2 Mbps, 3 Mbps)

Antenna Type : Chip Antenna (Integral)

Antenna Gain : 2.10 dBi max
 RF Power : 1.585 mW

Environmental of Tests : Temperature: (15.9 ± 6.9) °C

Humidity: (51 ± 13) % R.H.

Atmospheric Pressure: (102.7 ± 0.1) kPa

• FCC Rule Part(s) : FCC Part 15 Subpart C

• Test Procedure : ANSI C63.4-2009

FCC Classification : DSS (Part 15 Spread Spectrum Transmitter)

Place of Tests : ETL Inc. Testing Lab. (FCC Designation Number : KR0022)

Radiated Emission test 1;

#499-1, Sagot-ri, Seosin-myeon, Hwaseong-si,

Gyeonggi-do, 445-882, Korea

Radiated Emission test 2 and Conducted Emission test; #371-51, Gasan-dong, Geumcheon-gu, Seoul, 153-803, Korea

Report no. ETLE141105.1586, Page 3 of 56

**Head Office:** #371-51, Gasan-dong, Geumcheon-gu, Seoul, 153-803, Korea Tel: 82-2-858-0786 Fax: 82-2-858-0788



FCC ID: 2ADOC-POLMP01W

### 1. INTRODUCTION

The measurement test for radiated and conducted emission test was conducted at the ETL Inc. The site is constructed in conformance with the requirements of the ANSI C63.4-2009 and CISPR Publication 16. The ETL has site descriptions on file with the FCC for 3 m and 10 m site configurations. Detailed description of test facility was found to be in compliance with FCC Rules according to the ANSI C63.4-2009 and registered to the Federal Communications Commission (FCC Designation Number: KR0022).

The measurement procedure described in American National Standard for Method of Measurement of Radio-Noise Emission from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz (ANSI C63.4-2009) was used in determining radiated and conducted emissions from the C&A Licensing LLC Model: POLMP01W



FCC ID: 2ADOC-POLMP01W

### 2. PRODUCT INFORMATION

### 2.1 Equipment Description

The Equipment Under Test (EUT) is the Polaroid Mini Printer (model: POLMP01W).

The model POLMP01W is basic model that was tested.

The multi models POLMP01B, POLMP01BL and POLMP01R are identical to basic model, except for model designation and color.

Model name	Color
POLMP01W (Basic model)	White
POLMP01B	Black
POLMP01BL	Blue
POLMP01R	Red

## 2.2 General Specification

Item	Specification
Paper size	50 mm x 76 mm
Type of supported image file/size	PNG (2 550 x 3 300), JPEG (baseline) Within a maximum of 10 M Byte Progressive JPEG not supported
Paper used	ZINK Paper (for Pomini only)
Dan and the same of the same	Temperature: (22.5 ± 2.5) °C
Paper storage conditions	Humidity: (47.5 ± 7.5) % R.H.
Draduat aparating conditions	Temperature: (22.5 ± 17.5) °C
Product operating conditions	Humidity: Less than 70 % R.H. (35 °C)
Optimal print conditions	Temperature: (23.5 ± 8.5) °C
Optimal print conditions	Humidity: Less than 70 % (32 °C)
LED display	Power on/Standby/Communication/Charge/Error/Print/Update
Communication	Bluetooth 4.0

Report no. ETLE141105.1586, Page 5 of 56



FCC ID: 2ADOC-POLMP01W

Item	Specification
External connection terminal	Micro USB port (charging only)
USB power supply	Rated DC 5 V / 1.0 A adapter (optional)
Built-in battery	500 mAh Lithium polymer (rechargeable)
Proper image resolution	More than 1 280 x 2 448 pixel
Weight	186 g
Support App version	Android: 4.0 or higher iOS: 5.1 or higher (Support may not be provided depending on the user's Smart phone version and environment.)
High Internal Frequency	Bluetooth Module → 26.000 MHz

### - Frequency Channel Table

CH	MHz														
1	2402	11	2412	21	2422	31	2432	41	2442	51	2452	61	2462	71	2472
2	2403	12	2413	22	2423	32	2433	42	2443	52	2453	62	2463	72	2473
3	2404	13	2414	23	2424	33	2434	43	2444	53	2454	63	2464	73	2474
4	2405	14	2415	24	2425	34	2435	44	2445	54	2455	64	2465	74	2475
5	2406	15	2416	25	2426	35	2436	45	2446	55	2456	65	2466	75	2476
6	2407	16	2417	26	2427	36	2437	46	2447	56	2457	66	2467	76	2477
7	2408	17	2418	27	2428	37	2438	47	2448	57	2458	67	2468	77	2478
8	2409	18	2419	28	2429	38	2439	48	2449	58	2459	68	2469	78	2479
9	2410	19	2420	29	2430	39	2440	49	2450	59	2460	69	2470	79	2480
10	2411	20	2421	30	2431	40	2441	50	2451	60	2461	70	2471		



FCC ID: 2ADOC-POLMP01W

### 3. DESCRIPTION OF TESTS

The tests documented in this report were performed in accordance with ANSI C63.4-2009 and FCC CFR 47 2.1046, 2.1047, 2.1049, 2.1051, 2.1053, 2.1055, 2.1057, 15.207, 15.209 and 15.247.

#### 3.1 Radiated Emission Measurement

Radiated emission measurements were made in accordance with § 13 in ANSI C63.4-2009 "Measurement of Intentional radiators" The measurements were performed over the frequency range of 30 MHz to 40 GHz using antenna as the input transducer to a Spectrum analyzer or a Field Intensity Meter. The measurements were made with the detector set for "Peak, Quasi-peak, Average" within a bandwidth of 120 kHz and above 1 GHz is 1 MHz.

Preliminary measurements were made at 3 m using broadband antennas, and spectrum analyzer to determine the frequency producing the maximum emission in shielded room. Appropriate precaution was taken to ensure that all emission from the EUT were maximized and investigated. The system configuration, mode of operation, turntable azimuth and height with respect to the antenna were noted for each frequency found. The spectrum was scanned from 30 MHz to 1 000 MHz using Log-Bicon antenna. Above 1 GHz, linearly polarized double ridge horn antennas were used. Final measurements were made open site or SVSWR chamber at 3 m. The test equipment was placed on a styrofoam table. Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. Each frequency found during prescan measurements was re-examined by manual. The EUT, support equipment and interconnecting cables were re-configured to the set-up producing the maximum emission for the frequency and were placed on top of a 0.8 m high nonmetallic 1.0 m x 1.5 m table. The EUT, support equipment, and interconnecting cables were rearranged and manipulated to maximize each emission. The turntable containing the system was rotated; the antenna height was varied 1 m to 4 m and stopped at the azimuth or height producing the maximum emission.

Varying the mode of operating frequencies of the EUT maximized each emission. The system was tested in all the three orthogonal planes and changing the polarity of the antenna. The worst-case emissions are recorded in the data tables. If necessary, the radiated emission measurement could be performed at a closer distance to ensure higher accuracy and the results were extrapolated to the specified distance using an inverse linear distance extrapolation factor (20 dB/decade) as per section 15.31(f).

Photographs of the worst-case emission can be seen in Photographs of the worst-case emission test setup can be seen in Appendix B.



FCC ID: 2ADOC-POLMP01W

#### 3.2 Conducted Emission Measurement

Conducted emissions measurements were made in accordance with section § 13 in ANSI C63.4-2009 "measurement of intentional radiators" The measurements were performed over the frequency range of 0.15 MHz to 30 MHz using a 50  $\Omega$ /50  $\mu$ H LISN as the input transducer to a Spectrum Analyzer or a Test Receiver. The measurements were made with the detector set for "Peak" amplitude within a bandwidth of 9 kHz or for "quasi-peak" within a bandwidth of 9 kHz.

The line-conducted emission test is conducted inside a shielded anechoic chamber room with 1 m x 1.5 m x 0.8 m wooden table which is placed 0.4 m away from the vertical wall and 1.5 m away from the side wall of the chamber room. Two LISN are bonded to the shielded room. The EUT is powered from the LISN and the support equipment is powered from the other LISN. Power to the LISNs are filtered by a noise cut power line filters. If the EUT is a DC-powered device, power will be derived from the source power supply it normally will be powered from and these supply lines will be connected to the LISN. Non-inductive bundling to a 1 m length shortened all interconnecting cables more than 1 m. Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The RF output of the LISN was connected to the EMI Test Receiver to determine the frequency producing the maximum emission from the EUT. The frequency producing the maximum level was reexamined using to set Quasi-Peak mode by manual, after scanned by automatic Peak mode from 0.15 MHz to 30 MHz. The bandwidth of the spectrum analyzer was set to 9 kHz. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission.

Photographs of the worst-case emission can be seen in Photographs of the worst-case emission test setup can be seen in Appendix B.



FCC ID: 2ADOC-POLMP01W

### 3.3 FCC Part 15.205 Restricted Bands of Operations

(a) Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090 - 0.110  10.495 - 0.505 2.173 5 - 2.190 5 4.125 - 4.128 4.177 25 - 4.177 75 4.207 25 - 4.207 75 6.215 - 6.218 6.267 75 - 6.268 25 6.311 75 - 6.312 25 8.291 - 8.294 8.362 - 8.366 8.376 25 - 8.386 75 8.414 25 - 8.414 75 12.29 - 12.293 12.519 75 - 12.520 25 12.576 75 - 12.577 25 13.36 - 13.41	16.42 - 16.423	399.9 - 410	4.5 - 5.15
	16.694 75 - 16.695 25	608 - 614	5.35 - 5.46
	16.804 25 - 16.804 75	960 - 1 240	7.25 - 7.75
	25.5 - 25.67	1 300 - 1 427	8.025 - 8.5
	37.5 - 38.25	1 435 - 1 626.5	9.0 - 9.2
	73 - 74.6	1 645.5 - 1 646.5	9.3 - 9.5
	74.8 - 75.2	1 660 - 1 710	10.6 - 12.7
	108 - 121.94	1 718.8 - 1 722.2	13.25 - 13.4
	123 - 138	2 200 - 2 300	14.47 - 14.5
	149.9 - 150.05	2 310 - 2 390	15.35 - 16.2
	156.524 75 - 156.525 25	2 483.5 - 2 500	17.7 - 21.4
	156.7 - 156.9	2 690 - 2 900	22.01 - 23.12
	162.012 5 - 167.17	3 260 - 3 267	23.6 - 24.0
	167.72 - 173.2	3 332 - 3 339	31.2 - 31.8
	240 - 285	3 345.8 - 3 358	36.43 - 36.5
	322 - 335.4	3 600 - 4 400	( <sup>2</sup> )

<sup>&</sup>lt;sup>1</sup> Until February 1, 1999, this restricted band shall be 0.490 MHz - 0.510 MHz.

(b) Except as provided in paragraphs (d) and (e), the field strength of emissions appearing within these frequency bands shall not exceed the limits shown in Section 15.209. At frequencies equal to or less than 1 000 MHz, compliance with the limits in Section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1 000 MHz, compliance with the emission limits in Section 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in Section 15.35 apply to these measurements.

<sup>&</sup>lt;sup>2</sup> Above 38.6



FCC ID: 2ADOC-POLMP01W

### 4. TEST CONDITION


### **4.1 Test Configuration**

The device was configured for testing in a typical fashion (as a customer would normally use it). During the tests, the following conditions and configurations were used.

## 4.2 Description of Test modes

Polaroid Mini Printer that has the control software.

### 4.3 The setup drawing(s)





FCC ID: 2ADOC-POLMP01W

### 5. TEST RESULTS

### 5.1 Summary of Test Results

The measurement results were obtained with the EUT tested in the conditions described in this report. Detailed measurement data and plots showing the maximum emission of the EUT are reported.

47 CFR Part 15, Subpart C	Measurement Required	Result
15.247(a)(1)	Channel Bandwidth, Frequency Separation	Pass
15.247(b)(3)	Maximum Peak Output Power	Pass
15.247(d)	Bandwidth of Frequency Band Edges	Pass
15.247(a)(1)(iii)	Number of Hopping Channels	Pass
15.247(a)(1)(iii)	Time of Occupancy (Dwell time)	Pass
15.209(a)	Spurious Emissions	Pass
15.207	Conducted Emissions	Pass
15.247(i) 1.1307(b)(1)	RF Exposure	Pass

The data collected shows that the **C&A Licensing LLC / Polaroid Mini Printer / POLMP01W** complied with technical requirements of above rules part 15.207, 209 and 15.247 Limits.

The equipment is not modified anything, mechanical or circuits to improve EMI status during a measurement. No EMI suppression device(s) was added and/or modified during testing.



FCC ID: 2ADOC-POLMP01W

### 5.2 Channel Bandwidth and Frequency Separation

EUT	Polaroid Mini Printer / POLMP01W
Limit apply to	FCC Part 15.247(a)(1)
Test Date	November 20, 2014
Environmental of Test	(22.6 ± 0.0) °C, (38 ± 0) % R.H., (102.6 ± 0.0) kPa
Operating Condition	RF transmitting continuously during the tested.
Result	Passed

#### 5.2.1 Channel Bandwidth

Type of Modulation	Frequency [MHz]	20 dB Bandwidth [MHz]	Limit
	2 402	0.881	
BDR	2 441	0.872	
	2 480	0.871	2/3 of the 20 dB Bandwidth
	2 402	1.171	< Carrier frequency separation
EDR	2 441	1.174	
	2 480	1.167	

#### NOTES:

- 1. Measure frequency separation of relevant channel using spectrum analyzer.
- 2. Please see the measured plot in next page.

#### 5.2.2 Frequency Separation

Frequency hopping systems operating in the 2 400.0 MHz - 2 483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater.

Type of Modulation	EUT Channel Separation [MHz]	20 dB bandwidth [MHz]	Limit
BDR	1.000 (Worst)	0.881 (Worst)	> 25 kHz or
EDR	1.000 (Worst)	1.174 (Worst)	> 2/3 of the 20 dB Bandwidth

#### NOTES:


- 1. Measure frequency separation of relevant channel using spectrum analyzer.
- 2. Please see the measured plot in next page.

Report no. ETLE141105.1586, Page 12 of 56


FCC ID: 2ADOC-POLMP01W

### Plots of 20 dB Bandwidth (BDR)

#### [2 402 MHz]




#### [2 441 MHz]



Report no. ETLE141105.1586, Page 13 of 56




### [2 480 MHz]



### **Plots of Frequency Separation (BDR)**

#### [Channel Separation]




Open site: #499-1, Sagot-ri, Seosin-myeon, Hwaseong-si, Gyeonggi-do, 445-882, Korea


FCC ID: 2ADOC-POLMP01W

### Plots of 20 dB Bandwidth (EDR)

#### [2 402 MHz]



#### [2 441 MHz]




Report no. ETLE141105.1586, Page 15 of 56

Open site: #499-1, Sagot-ri, Seosin-myeon, Hwaseong-si, Gyeonggi-do, 445-882, Korea




### [2 480 MHz]



### **Plots of Frequency Separation (EDR)**

#### [Channel Separation]



Report no. ETLE141105.1586, Page 16 of 56



FCC ID: 2ADOC-POLMP01W

## **5.3 Maximum Peak Conducted Output Power**

EUT	Polaroid Mini Printer / POLMP01W	
Limit apply to	FCC Part 15.247(b)(3)	
Test Date	November 20, 2014	
Environmental of Test	(22.7 ± 0.0) °C, (38 ± 0) % R.H., (102.6 ± 0.0) kPa	
Operating Condition	RF transmitting continuously during the tested.	
Result	Passed	

#### Limit

The maximum peak conducted output power of the intentional radiator shall not exceed the following:

For frequency hopping systems operating in the 2 400.0 MHz - 2 483.5 MHz band employing at least 75 non-overlapping hopping channels: 1 Watt

#### **Test Data**

Type of Modulation	Channel	Frequency [MHz]	Output Power [dBm]	Limit
	Low	2 402	2.00	
BDR	Mid	2 441	0.90	
	High	2 480	-0.60	4 20 dDm (4 M)
	Low	2 402	0.97	< 30 dBm (1 W)
EDR	Mid	2 441	-0.15	
	High	2 480	-1.82	


#### NOTES:

- 1. Measure conducted Channel power of relevant channel using Spectrum analyzer
- 2. RBW 1 MHz, VBW 1 MHz
- 3. Please see the measured plot in next page.


FCC ID: 2ADOC-POLMP01W

### Plots of Maximum Peak Output Power (BDR)






#### [2 441 MHz]






FCC ID: 2ADOC-POLMP01W





### Plots of Maximum Peak Output Power (EDR)


#### [2 402 MHz]






FCC ID: 2ADOC-POLMP01W

#### [2 441 MHz]



#### [2 480 MHz]





FCC ID: 2ADOC-POLMP01W

### 5.4 Bandwidth of Frequency Band Edges

EUT	Polaroid Mini Printer / POLMP01W
Limit apply to	FCC Part 15.247(d)
Test Date	November 21, 2014
Environmental of Test	(22.2 ± 0.1) °C, (40 ± 0) % R.H., (102.7 ± 0.0) kPa
Operating Condition	RF transmitting continuously during the tested.
Result	Passed

#### Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

#### **Test Results**

- Refer to see the measured plot in next page.

#### NOTES:

 The test was performed to make a direct field strength measurement at the band edge frequencies.





FCC ID: 2ADOC-POLMP01W

### Plots of Bandwidth of Frequency Band Edges (BDR)

#### [Non-hopping mode]

#### Conducted






Report no. ETLE141105.1586, Page 22 of 56




FCC ID: 2ADOC-POLMP01W


#### Radiated


Peak Detector: RBW: 1 MHz, VBW: 1 MHz (2 310 MHz - 2 390 MHz), Worst case (Low, Vertical)





AV Detector: RBW: 1 MHz, VBW: 10 Hz (2 310 MHz - 2 390 MHz), Worst case (Low, Vertical)








FCC ID: 2ADOC-POLMP01W


Peak Detector: RBW: 1 MHz, VBW: 1 MHz (2 483.5 MHz - 2 500.0 MHz), Worst case (High, Vertical)





AV Detector: RBW: 1 MHz, VBW: 10 Hz (2 483.5 MHz - 2 500.0 MHz), Worst case (High, Vertical)









FCC ID: 2ADOC-POLMP01W

### Plots of Bandwidth of Frequency Band Edges (EDR)

#### [Non-hopping mode]

#### Conducted





Report no. ETLE141105.1586, Page 25 of 56




FCC ID: 2ADOC-POLMP01W

#### Radiated


Peak Detector: RBW: 1 MHz, VBW: 1 MHz (2 310 MHz - 2 390 MHz), Worst case (Low, Vertical)





AV Detector: RBW: 1 MHz, VBW: 10 Hz (2 310 MHz - 2 390 MHz), Worst case (Low, Vertical)









FCC ID: 2ADOC-POLMP01W


Peak Detector: RBW: 1 MHz, VBW: 1 MHz (2 483.5 MHz - 2 500.0 MHz), Worst case (High, Vertical)





AV Detector: RBW: 1 MHz, VBW: 10 Hz (2 483.5 MHz - 2 500.0 MHz), Worst case (High, Vertical)









FCC ID: 2ADOC-POLMP01W

### Plots of Bandwidth of Frequency Band Edges (BDR)

#### [Hopping mode]

#### Conducted






Report no. ETLE141105.1586, Page 28 of 56




FCC ID: 2ADOC-POLMP01W


#### Radiated


Peak Detector: RBW: 1 MHz, VBW: 1 MHz (2 310 MHz - 2 390 MHz), Worst case (Low, Vertical)





AV Detector: RBW: 1 MHz, VBW: 10 Hz (2 310 MHz - 2 390 MHz), Worst case (Low, Vertical)








FCC ID: 2ADOC-POLMP01W


Peak Detector: RBW: 1 MHz, VBW: 1 MHz (2 483.5 MHz - 2 500.0 MHz), Worst case (High, Vertical)





AV Detector: RBW: 1 MHz, VBW: 10 Hz (2 483.5 MHz - 2 500.0 MHz), Worst case (High, Vertical)









FCC ID: 2ADOC-POLMP01W

### Plots of Bandwidth of Frequency Band Edges (EDR)

#### [Hopping mode]

#### Conducted





Report no. ETLE141105.1586, Page 31 of 56




FCC ID: 2ADOC-POLMP01W

ETLQP-21-F22-0

#### Radiated


Peak Detector: RBW: 1 MHz, VBW: 1 MHz (2 310 MHz - 2 390 MHz), Worst case (Low, Vertical)





AV Detector: RBW: 1 MHz, VBW: 10 Hz (2 310 MHz - 2 390 MHz), Worst case (Low, Vertical)






Report no. ETLE141105.1586, Page 32 of 56



FCC ID: 2ADOC-POLMP01W


Peak Detector: RBW: 1 MHz, VBW: 1 MHz (2 483.5 MHz - 2 500.0 MHz), Worst case (High, Vertical)





AV Detector: RBW: 1 MHz, VBW: 10 Hz (2 483.5 MHz - 2 500.0 MHz), Worst case (High, Vertical)







FCC ID: 2ADOC-POLMP01W

## 5.5 Number of Hopping Channels

EUT	Polaroid Mini Printer / POLMP01W	
Limit apply to	FCC Part 15.247(a)(1)(iii)	
Test Date	November 20, 2014	
Environmental of Test	(22.5 ± 0.0) °C, (39 ± 0) % R.H., (102.6 ± 0.0) kPa	
Operating Condition	RF transmitting continuously during the tested.	
Result	Passed	

#### Limit

Frequency hopping systems in the 2 400.0 MHz - 2 483.5 MHz band shall use at least 15 channels.

#### **Test Data**

Type of Modulation	Result	Limit	
BDR	79	- > 15 Channel	
EDR	79		


#### NOTES:

- 1. Measure number of hopping channel of relevant channel using spectrum analyzer.
- 2. Please see the measured plot in next page.




### Plots of Number of Hopping Channels (BDR)

#### [Hopping Channels]



#### **Plots of Number of Hopping Channels (EDR)**

#### [Hopping Channels]



Report no. ETLE141105.1586, Page 35 of 56

**Head Office:** #371-51, Gasan-dong, Geumcheon-gu, Seoul, 153-803, Korea Tel: 82-2-858-0786 Fax: 82-2-858-0788



FCC ID: 2ADOC-POLMP01W

## 5.6 Time of Occupancy

EUT	Polaroid Mini Printer / POLMP01W	
Limit apply to	FCC Part 15.247(a)(1)(iii)	
Test Date	November 20, 2014	
Environmental of Test	(22.7 ± 0.0) °C, (39 ± 0) % R.H., (102.6 ± 0.0) kPa	
Operating Condition	RF transmitting continuously during the tested.	
Result	Passed	

#### Limit

Frequency hopping systems in the 2 400.0 MHz - 2 483.5 MHz band. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

#### **Test Data**

Time of Occupancy

Test period = 0.4 [seconds/channel] x 79 [channel]

Actual = Reading x (Hopping rate/Number of channels) x Test period

- Hopping rate (DH5 Packet) = 1 600 [hopping/second] / 6 [time slot] = 266.667
- Hopping rate (3DH5 Packet) = 1 600 [hopping/second] / 6 [time slot] = 266.667
- Type of Modulation: BDR

0.4 s x 79 (CH) = 31.6 s

2.890 ms x (266.667/79) x 31.6 s = 308.267 ms

- Type of Modulation: EDR

0.4 s x 79 (CH) = 31.6 s

2.890 ms x (266.667/79) x 31.6 s = 308.267 ms

Type of Modulation	Pulse Time [ms]	Total of Dwell [ms]	Limit [ms]
BDR	2.890	308.267	400.000
EDR	2.890	308.267	400.000

#### NOTES:


- 1. BDR: This test was applied both to DH1, DH3 and DH5. (Worst case: DH5)
- 2. EDR: This test was applied both to 2DH1, 2DH3, 2DH5, 3DH1, 3DH3 and 3DH5. (Worst case: 3DH5)
- 3. Measure time of occupancy of relevant channel using spectrum analyzer.
- 4. Please see the measured plot in next page.

Report no. ETLE141105.1586, Page 36 of 56


FCC ID: 2ADOC-POLMP01W

## Plots of Time of Occupancy (BDR)

### [Continuous Time]



### [Hopping Period]




Report no. ETLE141105.1586, Page 37 of 56


FCC ID: 2ADOC-POLMP01W

## Plots of Time of Occupancy (EDR)

### [Continuous Time]



### [Hopping Period]



Report no. ETLE141105.1586, Page 38 of 56



FCC ID: 2ADOC-POLMP01W

## 5.7 Spurious Emissions

EUT	Polaroid Mini Printer / POLMP01W
Limit apply to	FCC Part 15.209
Test Date	November 19, 2014 to November 20, 2014
Environmental of Test	(15.8 ± 6.8) °C, (51 ± 12) % R.H., (102.7 ± 0.1) kPa
Operating Condition	Low CH, Middle CH, High CH Transmission
Result	Passed

### Limit

Except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequencies [MHz]	Field Strength [μV/m]	Measurement Distance [m]		
0.009 - 0.490	2 400/F(kHz)	300		
0.490 - 1.705	24 000/F(kHz)	30		
1.705 - 30.0	30	30		
30 - 88	100	3		
88 - 216	150	3		
216 - 960	200	3		
Above 960	500	3		

<sup>\*</sup> Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54 MHz - 72 MHz, 76 MHz - 88 MHz, 174 MHz - 216 MHz or 470 MHz - 806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.

### **Test Results**

- Refer to see the measured plot in next page.



FCC ID: 2ADOC-POLMP01W

### **Radiated Emissions Test data**

#### - 9 kHz to 30 MHz

Test Date	November 19, 2014
Environmental of Test	(9.4 ± 0.4) °C, (58 ± 5) % R.H., (102.7 ± 0.1) kPa

The following table shows the highest levels of radiated emissions on both polarizations of horizontal and vertical. Detector mode: CISPR Quasi-Peak mode (100 Hz, 9 kHz)

- Type of Modulation: BDR, EDR

Frequency [MHz]	Reading [dB(µV)]	Polarization (*H/**V)	Ant. Factor [dB/m]	Cable Loss [dB]	Result [dB(µV/m)]	Limit [dB(µV/m)]	Margin [dB]					
	Emission attenuated more than											

Result: All emissions below noise floor of 20 dB( $\mu$ V/m).

#### NOTES:

- 1. \* H : Horizontal polarization , \*\* V : Vertical polarization
- 2. Result = Reading + Antenna factor + Cable loss
- 3. Margin = Limit Result
- The measurement was performed for the frequency range 9 kHz to 30 MHz according to FCC Part 15.209.



FCC ID: 2ADOC-POLMP01W

## - Below 1 GHz (30 MHz to 1 GHz)

Test Date	November 19, 2014
Environmental of Test	(11.4 ± 1.2) °C, (50 ± 6) % R.H., (102.6 ± 0.0) kPa


The following table shows the highest levels of radiated emissions on both polarizations of horizontal and vertical. Detector mode: CISPR Quasi-Peak mode (6 dB Bandwidth: 120 kHz)

### - Type of Modulation: BDR (Worst case)

71	71											
Frequency [MHz]	Reading [dB(µV)]	Polarization (*H/**V)	Ant. Factor [dB/m]	Cable Loss [dB(µV)]	Height [cm]	Result [dB(µV/m)]	Limit [dB(µV/m)]	Margin [dB]				
32.04	23.64	V	10.41	0.95	100	35.00	40.00	5.00				
47.92	24.10	V	11.82	1.08	101	37.00	40.00	3.00				
128.19	26.66	V	11.33	1.51	121	39.50	43.50	4.00				
160.39	26.46	V	12.40	1.64	140	40.50	43.50	3.00				
175.89	27.12	V	11.45	1.73	142	40.30	43.50	3.20				
400.74	19.43	Н	15.63	2.54	154	37.60	46.00	8.40				
464.39	22.69	Н	17.37	2.84	131	42.90	46.00	3.10				

### NOTES:

- 1. \* H : Horizontal polarization, \*\* V : Vertical polarization
- 2. Result = Reading + Antenna factor + Cable loss
- 3. Margin value = Limit Result
- 4. The measurement was performed for the frequency range above 30 MHz according to FCC Part 15.209.



Report no. ETLE141105.1586, Page 41 of 56



FCC ID: 2ADOC-POLMP01W

## - Above 1 GHz (1 GHz to 25 GHz)

Test Date	November 20, 2014
Environmental of Test	(22.5 ± 0.0) °C, (39 ± 0) % R.H., (102.6 ± 0.0) kPa

- Type of Modulation: BDR

### 1. Low CH

Frequency [MHz]	Reading [dB(µV)]		Polarity	Ant. Factor	Cable Loss	Result [dB(μV/m)]		Limit [dB(μV/m)]		Margin [dB]	
	Peak	Average	(*H/**V)	[dB/m]	[dB]	Peak	Average	Peak	Average	Peak	Average
2 648.32	59.59	44.49	V	27.76	-35.65	51.70	36.60	73.97	53.97	22.27	17.37
4 804.80	45.14	40.14	V	31.81	-34.64	42.30	37.30	73.97	53.97	31.67	16.67

### 2. Middle CH

Frequency		Reading [dB(µV)]		Ant. Factor	Cable Loss	Result [dB(μV/m)]		Limit [dB(µV/m)]		Margin [dB]	
[MHz]	Peak	Average	(*H/**V)	[dB/m]	[dB]	Peak	Average	Peak	Average	Peak	Average
2 648.32	59.79	44.69	V	27.76	-35.65	51.90	36.80	73.97	53.97	22.07	17.17
4 881.60	44.48	39.78	V	32.08	-34.66	41.90	37.20	73.97	53.97	32.07	16.77

## 3. High CH

Frequency	7	Polarity	Ant. Factor	Cable Loss	Result [dB(μV/m)]		Limit [dB(µV/m)]		Margin [dB]		
[MHz]	Peak	Average	(*H/**V)	[dB/m]	[dB]	Peak	Average	Peak	Average	Peak	Average
2 648.32	59.79	44.59	V	27.76	-35.65	51.90	36.70	73.97	53.97	22.07	17.27
4 960.00	44.12	39.62	٧	32.36	-34.67	41.80	37.30	73.97	53.97	32.17	16.67

Result: No signal detect above second harmonic.



FCC ID: 2ADOC-POLMP01W

- Type of Modulation: EDR

#### 1. Low CH

Frequency		ding μV)]	Polarity (*H/**V)	,	Ant. Factor	Cable Loss	Result [dB(μV/m)]		Limit [dB(µV/m)]		Margin [dB]	
[MHz]	Peak	Average		[dB/m]	[dB]	Peak	Average	Peak	Average	Peak	Average	
2 648.32	59.39	44.59	V	27.76	-35.65	51.50	36.70	73.97	53.97	22.47	17.27	
4 804.80	44.34	39.94	٧	31.81	-34.64	41.50	37.10	73.97	53.97	32.47	16.87	

#### 2. Middle CH

	uency		ding (μV)]	Polarity	Ant. Factor	Cable Loss	Result [dB(μV/m)]		Limit [dB(μV/m)]		Margin [dB]	
[MHz]	Peak	Average	(*H/**V)	[dB/m]	[dB]	Peak	Average	Peak	Average	Peak	Average	
2 64	8.32	59.49	44.59	V	27.76	-35.65	51.60	36.70	73.97	53.97	22.37	17.27
4 88	31.60	42.78	39.78	V	32.08	-34.66	40.20	37.20	73.97	53.97	33.77	16.77

### 3. High CH

Frequency			Polarity	Ant. Cable Factor Loss		Result [dB(µV/m)]		Limit [dB(µV/m)]		Margin [dB]	
[MHz]	Peak	Average	(*H/**V) [dB/m	[dB/m]	[dB]	Peak	Average	Peak	Average	Peak	Average
2 648.32	59.69	44.69	V	27.76	-35.65	51.80	36.80	73.97	53.97	22.17	17.17
4 960.00	42.32	39.32	V	32.36	-34.67	40.00	37.00	73.97	53.97	33.97	16.97

### Result: No signal detect above second harmonic.

### NOTES:

- 1. \* H : Horizontal polarization , \*\* V : Vertical polarization
- 2. Cable loss = Cable loss + Amp. Gain
- 3. Result = Reading + Antenna factor + Cable loss
- 4. Margin value = Limit Result
- 5. Measuring frequencies from 1 GHz to the 10<sup>th</sup> harmonic of highest fundamental frequency.
- 6. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded(ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.
- 7. Spectrum setting:
  - a. Peak Setting 1 GHz to 10<sup>th</sup> harmonics of fundamental, RBW = 1 MHz, VBW = 1 MHz, Sweep = Auto
  - b. AV Setting 1 GHz to 10<sup>th</sup> harmonics of fundamental, RBW = 1 MHz, VBW = 10 Hz, Sweep = Auto

Report no. ETLE141105.1586, Page 43 of 56





FCC ID: 2ADOC-POLMP01W

Test Date	November 20, 2014
Environmental of Test	(22.4 ± 0.0) °C, (39 ± 0) % R.H., (102.6 ± 0.0) kPa

## Plots of Spurious Emissions (Conducted Measurement) (BDR)

[CH Low]







Report no. ETLE141105.1586, Page 44 of 56



FCC ID: 2ADOC-POLMP01W

## [CH Mid]









FCC ID: 2ADOC-POLMP01W

## [CH High]







FCC ID: 2ADOC-POLMP01W

## Plots of Spurious Emissions (Conducted Measurement) (EDR)

[CH Low]









FCC ID: 2ADOC-POLMP01W

## [CH Mid]









FCC ID: 2ADOC-POLMP01W

## [CH High]







FCC ID: 2ADOC-POLMP01W

### 5.8 Conducted Emissions Measurement

EUT	Polaroid Mini Printer / POLMP01W
Limit apply to	FCC Part 15.207
Test Date	November 20, 2014
Environmental of Test	(22.7 ± 0.0) °C, (41 ± 0) % R.H., (102.6 ± 0.0) kPa
Operating Condition	RF transmitting continuously during the tested.
Result	Passed by 17.60 dB

#### Limit

For an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50  $\mu$ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequencies ranges.

Frequency of Emission	Conducted limit [dB(μV)]				
[MHz]	Quasi-peak	Average			
0.15 - 0.5	66 to 56 *	56 to 46 *			
0.5 - 5	56	46			
5 - 30	60	50			

<sup>\*</sup> Decreases with the logarithm of the frequency.

#### **Test Results**

- Refer to see the measured plot in next page.



FCC ID: 2ADOC-POLMP01W

### **Conducted Emission Test Data**

The following data and graph shows the highest levels of conducted emissions on both polarizations of hot and neutral line.

Detector mode: CISPR Quasi-Peak mode (6 dB Bandwidth: 9 kHz)


### NOTES:

- 1. Please see the measured data and graph in next page.
- 2. The c.f value was included the antenna factor and cable loss.
- 3. Result value = Reading + c.f
- 4. Margin value = Limit Result
- 5. Measurements were performed at the AC Power Inlet in the frequency band of 150 kHz  $\sim$  30 MHz according to the FCC Part 15 Class B.



FCC ID: 2ADOC-POLMP01W

### Line: HOT




#### Final Result

	L1 Phase	_								
No.	Frequency	Reading	Reading	c.f	Result	Result	Limit	Limit	Margin	Margin
		QP	AV		QP	ΑV	QP	AV	QP	ΑV
	[MHz]	[dB(µV)]	[dB(µV)]	[dB]	[dB(µV)]	[dB(µV)]	[dB(µV)]	[dB(µV)]	[dB]	[dB]
1	0.15718	31.1	21.6	10.1	41.2	31.7	65.6	55.6	24.4	23.9
2	0.20846	29.2	23.0	10.0	39.2	33.0	63.3	53.3	24.1	20.3
3	0.28065	25.8	20.0	9.9	35.7	29.9	60.8	50.8	25.1	20.9
4	0.54285	23.6	16.8	10.1	33.7	26.9	56.0	46.0	22.3	19.1
5	1.25425	24.5	17.5	9.9	34.4	27.4	56.0	46.0	21.6	18.6
6	1.57335	23.4	16.0	9.9	33.3	25.9	56.0	46.0	22.7	20.1
7	5.06208	25.2	17.5	9.9	35.1	27.4	60.0	50.0	24.9	22.6
8	9.24968	24.4	17.4	10.0	34.4	27.4	60.0	50.0	25.6	22.6
9	9.94856	24.2	17.4	10.0	34.2	27.4	60.0	50.0	25.8	22.6
10	19.1028	23.5	16.5	10.1	33.6	26.6	60.0	50.0	26.4	23.4



FCC ID: 2ADOC-POLMP01W

### **Line: Neutral**



#### Final Result

	N Phase									
No.	Frequency	Reading	Reading	c.f	Result	Result	Limit	Limit	Margin	Margin
		QP	AV		QP	ΑV	QP	ΑV	QP	AV
	[MHz]	[dB(µV)]	[dB(µV)]	[dB]	[dB(µV)]	[dB(µV)]	[dB(µV)]	[dB(µV)]	[dB]	[dB]
1	0.15958	29.8	21.1	10.7	40.5	31.8	65.5	55.5	25.0	23.7
2	0.20366	26.0	19.8	10.3	36.3	30.1	63.5	53.5	27.2	23.4
3	0.2441	23.9	17.5	10.1	34.0	27.6	62.0	52.0	28.0	24.4
4	0.47955	23.7	17.2	9.9	33.6	27.1	56.3	46.3	22.7	19.2
5	1.22105	25.1	18.6	9.8	34.9	28.4	56.0	46.0	21.1	17.6
6	3.15162	21.1	14.0	9.8	30.9	23.8	56.0	46.0	25.1	22.2
7	5.12382	25.4	18.1	9.8	35.2	27.9	60.0	50.0	24.8	22.1
8	9.44896	26.4	18.2	10.0	36.4	28.2	60.0	50.0	23.6	21.8
9	16.048	23.9	14.7	10.2	34.1	24.9	60.0	50.0	25.9	25.1
10	17.7424	24.8	15.5	10.2	35.0	25.7	60.0	50.0	25.0	24.3

Open site: #499-1, Sagot-ri, Seosin-myeon, Hwaseong-si, Gyeonggi-do, 445-882, Korea



FCC ID: 2ADOC-POLMP01W

## 5.9 Radio Frequency Exposure

### Standard Applicable:

According to §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

This is a Portable device with its physical nature to be used nearby, the distance between radiating structure and human is less than 20 cm.

As per KDB 447498 D01, The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW) / (min. test separation distance, mm)] \*  $[\sqrt{f(GHz)}] \le 3.0$  for 1-g SAR and  $\le 7.5$  for 10-g extremity SAR, where

f (GHz) is the RF channel transmit frequency in GHz Power and distance are rounded to the nearest mW and mm before calculation The result is rounded to one decimal place for comparison

#### **Measurement Result:**

This is a portable device and the Max peak output power is (1.59 mW) lower than the threshold given and derived as above, where

### = 1.59 (mW) / 5 (mm) \* $\sqrt{2.480}$ (GHz) = 0.50 < 3.00

As the result of calculation result indicates, the RF exposure generating from given transmitter (transmitter employed digital modulation) can be excluded from SAR measurement, and is deemed compliant with RF exposure as per FCC.

Type of Modulation	Frequency [MHz]	Output Power [dBm]	Target power W/ tolerance [dBm]	Max tune up power [dBm]	Max tune up power [mW]	Separation distance [mm]	RF exposure	Limit
	2 402	2.00	-1 ~ 2	2	1.59	5	0.49	3.00
BDR	2 441	0.90	-1 ~ 2	2	1.59	5	0.50	3.00
	2 480	-0.60	-1 ~ 2	2	1.59	5	0.50	3.00
	2 402	0.97	-2 ~1	1	1.26	5	0.39	3.00
EDR	2 441	-0.15	-2 ~1	1	1.26	5	0.39	3.00
	2 480	-1.82	-2 ~1	1	1.26	5	0.40	3.00



FCC ID: 2ADOC-POLMP01W

## 6. SAMPLE CALCULATION

## **Sample Field Strength Calculation**

The field strength is calculated by adding the Antenna Factor and Cable Factor. The basic equation with a sample calculation is as follows:

FS = RA + AF + CF - PA

Where FS = Field Strength

RA = Receiver Amplitude

AF = Antenna Factor

CF = Cable Attenuation Factor

PA\* = Preamplifier Factor

\* PA is only be used for the measuring frequency above 1 GHz.

 $dB(\mu V) = 20 \log_{10} (\mu V)$ : Equation

 $dB(\mu V) = dBm + 107$ 

Example : @ 160.39 MHz

Class B Limit =  $43.50 \text{ dB}(\mu\text{V/m})$ 

Reading =  $26.46 \text{ dB}(\mu\text{V})$ 

Antenna Factor + Cable Loss =  $12.40 + 1.64 = 14.04 \text{ dB}(\mu\text{V/m})$ 

Total =  $40.50 \text{ dB}(\mu\text{V/m})$ 

Margin = 43.50 - 40.50 = 3.00 dB

= 3.00 dB below Limit



FCC ID: 2ADOC-POLMP01W

# 7. List of test equipments used for measurements

Test Equipment		Model	Mfg.	Serial No.	Cal. Date	Cal. Due Date
$\boxtimes$	EMI Test Receiver	ESVS 10	R&S	835165/001	14.03.18	15.03.18
	EMI Test Receiver	ESPI3	R&S	100478	14.09.03	15.09.03
$\boxtimes$	EMI Test Receiver	ESCS30	R&S	847793/005	14.03.18	15.03.18
$\boxtimes$	EMI Test Receiver	ESCI7	R&S	100851	14.09.03	15.09.03
$\boxtimes$	Two-Line V-Network	ENV216	R&S	958599/106	14.03.18	15.03.18
$\boxtimes$	Loop Antenna	AL-130	COM-POWER	121025	14.04.08	16.04.08
	LogBicon Antenna	VULB9160	Schwarzbeck	3082	13.07.25	15.07.25
$\boxtimes$	Horn Antenna	BBHA 9120D	Schwarzbeck	826	14.04.02	16.04.02
$\boxtimes$	PSA Series Spectrum Analyzer	E4440A	Agilent	US40420382	14.09.13	15.09.13
$\boxtimes$	Amplifier	TK-PA18	TESTEK.	120020	14.09.04	15.09.04
$\boxtimes$	Band Reject Filter	WRCGV 2402/2480- 2382/2500-52/10SS	Wainwright Instrument	2	14.09.03	15.09.03
$\boxtimes$	DC Power Supply	HYP-3030	Han Young	990554	14.03.17	15.03.17
$\boxtimes$	Highpass Filter	WHKX3.0 /18G-6SS	Wainwright Instrument	15	14.03.18	15.03.18
$\boxtimes$	Turn-Table	DS1200-S	Innco Systems GmbH	2740311	N/A	N/A
$\boxtimes$	Turn-Table	TT 1.35 SI	SES	-	N/A	N/A
$\boxtimes$	Antenna Master	AM 4.5	SES	-	N/A	N/A