Report No: C180305Z03-RP\_MPE

FCC ID: 2ADQOMDWF01

Date of Issue: March 23, 2018

# **MPE Report**

Exposure category: General population/uncontrolled environment

EUT Type: Production Unit Device Type: Mobile Device

Refer Standard: KDB 447498 D01 General RF Exposure Guidance v06

FCC Part 2 §2.1091

#### 1. Evaluation method

Systems operating under the provisions of FCC 47 CFR section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as mobile device whereby a distance of 0.2m normally can be maintained between the user and the device, and below RF Permissible Exposure limit shall comply with.

In accordance with HWB1BLE40AWH for Simultaneous transmission MPE test exclusion applies when the sum of the MPE ratios for all simultaneous transmitting antennas incorporated in a host device, based on the calculated/estimated, numerically modeled or measured field strengths or power density, is ≤ 1.0. The MPE ratio of each antenna is determined at the minimum test separation distance required by the operating configurations and exposure conditions of the host device, according to the ratio of field strengths or power density to MPE limit, at the test frequency. Either the maximum peak or spatially averaged results from measurements or numerical simulations may be used to determine the MPE ratios. Spatial averaging does not apply when MPE is estimated using simple calculations based on far-field plane-wave equivalent conditions. The antenna installation and operating requirements for the host device must meet the minimum test separation distances required by all antennas, in both standalone and simultaneous transmission operations, to satisfy compliance.

### 2. Limits for General Population/Uncontrolled Exposure

(B) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Magnetic Field Strength (E) (V/m) (A/m)		Power Density (S) (mW/cm <sup>2</sup> )	Averaging Time $ \mathbf{E} ^2$ , $ \mathbf{H} ^2$ or S (minutes)	
0.3-1.34	614	1.63	(100)*	30	
1.34-30	824/f	2.19/f	(180/f)*	30	
30-300	27.5	0.073	0.2	30	
300-1500			F/1500	30	
1500-100,000			1.0	30	

Note: f = frequency in MHz; \*Plane-wave equivalent power density

### 3. Calculation Method

Predication of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

 $S=PG/4\pi R^2$ 

Where: S=power density



P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator

Date of Issue: March 23, 2018

R=distance to the center of radiation of the antenna

From the EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the maximum gain of the used 4.90dBi for 2.4GWLAN, the RF power density can be obtained.

Frequency	Antenna type and antenna	Maximum antenna
Band	number	gain
2.4G	WLAN Antenna	4.90dBi

### 4. Estimation Result

### **4.1 Conducted Power Results**

### 2.4GHz WIFI

Mode	Frequency(MHz)	Peak Conducted Output Power (dBm)
	2412	17.76
IEEE 802.11b	2437	18.26
	2462	18.72
	2412	20.72
IEEE 802.11g	2437	21.09
	2462	21.15
	2412	21.65
IEEE 802.11n HT20	2437	22.16
	2462	22.63
	2412	20.66
IEEE 802.11n HT40	2437	20.23
	2462	21.35

# 4.2 Manufacturing tolerance

### 2.4GHz WIFI

IEEE 802.11b					
Frequency(MHz) 2412 2437 2462					
Maximum Output Power (dBm)	17.76	18.26	18.72		

IEEE 802.11 g					
Frequency(MHz) 2412 2437 2462					
Maximum Output Power (dBm)	20.72	21.09	21.15		

IEEE 802.11n HT20					
Frequency(MHz) 2412 2437 246					
Maximum Output Power (dBm)	21.65	22.16	22.63		



# Compliance Certification Services (Shenzhen) Inc.

Report No: C180305Z03-RP\_MPE

FCC ID: 2ADQOMDWF01

Date of Issue: March 23, 2018

IEEE 802.11n HT40						
Frequency(MHz) 2412 2437 2462						
Maximum Output Power (dBm)	20.66	20.23	21.35			

### **4.3 Measurement Results**

### 4.3.1 Standalone MPE

#### 2.4GWLAN

Mode	Outpu	t power	Antenna Gain	Antenna Gain	Duty	MPE	MPE Limits
	(dBm)	(mW)	(dBi)	(linear)	Cycle	(mW/cm <sup>2</sup> )	$(mW/cm^2)$
IEEE 802.11 b	18.72	74.4732	4.90	3.0903	100%	0.04581	1.0000
IEEE 802.11 g	21.15	130.3167	4.90	3.0903	100%	0.08016	1.0000
IEEE 802.11 n HT20	22.63	183.2314	4.90	3.0903	100%	0.11271	1.0000
IEEE 802.11 n HT40	21.35	136.4583	4.90	3.0903	100%	0.08394	1.0000

#### Remark:

- 1. Maximum average power including tune-up tolerance;
- 2. MPE use distance is 20cm from manufacturer declaration of user manual.
- 3. We choose and 2412MHz (lowest frequency operate at 2.4GHz)to calculate M PE limit as higher frequency will have higher MPE limits

According to KDB447498 for Transmitters used in mobile exposure conditions for simultaneous transmission operations;

### Conclusion

The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure of mobile device.

----- END OF REPORT-----