

2/F., Garment Centre, 576 Castle Peak Road, Kowloon, Hong Kong.

Telephone: (852) 2173 8888 Facsimile: (852) 2785 5487

www.intertek.com

TEST REPORT

Report No.: 17070643HKG-002R1

Wachsmuth & Krogmann, Inc.

Application For Certification (Original Grant)

FCC ID: 2ADQU-54180

Transmitter

This report supersedes previous report with report number 17070643HKG-002 dated August 17, 2017. Please refer RS-S17-0002 Letter issued on September 06, 2017 for amendment/ supersede notification.

PREPARED AND CHECKED BY:

APPROVED BY:

Signed On File Leung Sung Tak, Andy Engineer

Koo Wai Ip Technical Supervisor Date: September 06, 2017

Intertek's standard Terms and Conditions can be obtained at our website http://www.intertek.com/terms/.

The test report only allows to be revised within the retention period unless further standard or the requirement was noticed

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.



GENERAL INFORMATION

Grantee: Wachsmuth & Krogmann, Inc.

Grantee Address: 1015 Hawthorn Drive

Itasca, IL 60143 USA.

Contact Person: Dirk Niedermann
Tel: 847-290-7401 x222

Fax: 847-290-7402

e-mail: N/A

Manufacturer: Neworiental Plastic Industry Co., Ltd.

Manufacturer Address: Binhai Industrial Park, Xidian Town, Ninghai, Zhejiang, China

Brand Name: EASY HOME
Model: SL-3886-RF
Type of EUT: Transmitter
Description of EUT: Puck Light

Serial Number: N/A

FCC ID: 2ADQU-54180

Date of Sample Submitted: July 11, 2017

Date of Test: July 11, 2017 to August 14, 2017

Report No.: 17070643HKG-002R1
Report Date: September 06, 2017

Environmental Conditions: Temperature: +10 to 40°C

Humidity: 10 to 90%



SUMMARY OF TEST RESULT

TEST SPECIFICATION	REFERENCE	RESULTS
Transmitter Field Strength, Bandwidth and Timing Requirement	15.231(a)	Pass

The equipment under test is found to be complying with the following standards: FCC Part 15, October 1, 2015 Edition

Note: 1. The EUT uses a permanently attached antenna which, in accordance to section 15.203, is considered sufficient to comply with the pervisions of this section.

2. Pursuant to FCC part 15 Section 15.215(c), the 20 dB bandwidth of the emission was contained within the frequency band designated (mentioned as above) which the EUT operated. The effects, if any, from frequency sweeping, frequency hopping, other modulation techniques and frequency stability over excepted variations in temperature and supply voltage were considered.



TABLE OF CONTENTS

1.0	GENERAL DESCRIPTION	5
1.1	Product Description	5
1.2	Related Submittal(s) Grants	5
1.3	Test Methodology	5
1.4	Test Facility	5
2.0	SYSTEM TEST CONFIGURATION	6
2.1	Justification	6
2.2	EUT Exercising Software	6
2.3	Special Accessories	6
2.4	Measurement Uncertainty	6
2.5	Support Equipment List and Description	6
3.0	EMISSION RESULTS	7
3.1	Field Strength Calculation	7
3.2	Radiated Emission Configuration Photograph	8
3.3	Radiated Emission Data	8
4.0	EQUIPMENT PHOTOGRAPHS	0
5.0	PRODUCT LABELLING	0
5.0 6.0	TECHNICAL SPECIFICATIONS	
		.0
6.0	TECHNICAL SPECIFICATIONS	.0
6.0 7.0	TECHNICAL SPECIFICATIONS	.0
6.0 7.0 8.0	TECHNICAL SPECIFICATIONS	.0
6.0 7.0 8.0 8.1	TECHNICAL SPECIFICATIONS	.0 .0 .1 .2
6.0 7.0 8.0 8.1 8.2	TECHNICAL SPECIFICATIONS	.0 .0 .1 .2 .3
6.0 7.0 8.0 8.1 8.2 8.3	TECHNICAL SPECIFICATIONS	.0 .0 .1 .2 .3



1.0 **GENERAL DESCRIPTION**

1.1 Product Description

The Equipment Under Test (EUT) is a 433MHz transmitter. The EUT is powered by 3.0VDC (1 x 3.0V CR2032 battery). After pressing the button on the EUT, it will transmit a signal to turn on the receiver (Puck Light).

Antenna Type: Internal, Integral

For electronic filing, the brief circuit description is saved with filename: descri.pdf.

1.2 Related Submittal(s) Grants

This is a single application for certification of a transmitter.

1.3 Test Methodology

Radiated emission measurements was performed according to the procedures in ANSI C63.10 (2013). All radiated measurements were performed in an 3m Chamber. Preliminary scans were performed in the 3m Chamber only to determine worst case modes. All radiated tests were performed at an antenna to EUT distance of 3 meters, unless stated otherwise in the "Justification Section" of this Application.

1.4 Test Facility

The 3m Chamber facility used to collect the radiated data is located at Workshop No. 3, G/F., World-Wide Industrial Centre, 43-47 Shan Mei Street, Fo Tan, Sha Tin, N.T., Hong Kong. This test facility and site measurement data have been placed on file with the FCC.



2.0 SYSTEM TEST CONFIGURATION

2.1 Justification

The system was configured for testing in a typical fashion (as a customer would normally use it), and in the confines as outlined in ANSI C63.10 (2013).

The device was powered by new 3.0VDC (1 x 3.0V CR2032 battery).

For maximizing emissions, the EUT was rotated through 360°, the antenna height was varied from 1 meter to 4 meters above the ground plane, and the antenna polarization was changed. This step by step procedure for maximizing emissions led to the data reported in Exhibit 3.0.

The unit was operated standalone and placed in the center of the turntable.

The equipment under test (EUT) was configured for testing in a typical fashion (as a customer would normally use it). The EUT was mounted to a plastic stand if necessary and placed on the wooden turntable, which enabled the engineer to maximize emissions through its placement in the three orthogonal axes.

2.2 EUT Exercising Software

There was no special software to exercise the device. Once the unit is powered up, it transmits the RF signal continuously.

2.3 Special Accessories

There are no special accessories necessary for compliance of this product.

2.4 Measurement Uncertainty

When determining of the test conclusion, the Measurement Uncertainty of test has been considered.

2.5 Support Equipment List and Description

N/A.



3.0 **EMISSION RESULTS**

Data is included of the worst case configuration (the configuration which resulted in the highest emission levels). A sample calculation, configuration photographs and data tables of the emissions are included.

3.1 Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain (if any), Average Factor (optional) from the measured reading. The basic equation with a sample calculation is as follows:

FS = RA + AF + CF - AG - AV

where $FS = Field Strength in dB\mu V/m$

RA = Receiver Amplitude (including preamplifier) in dBμV

CF = Cable Attenuation Factor in dB

AF = Antenna Factor in dB AG = Amplifier Gain in dB AV = Average Factor in dB

In the following table(s), the reading shown on the data table reflects the preamplifier gain. An example for the calculations in the following table is as follows:

FS = RR + LF

where $FS = Field Strength in dB\mu V/m$

 $RR = RA - AG - AV in dB\mu V$

LF = CF + AF in dB

Assume a receiver reading of 52.0 dB μ V is obtained. The antenna factor of 7.4 dB and cable factor of 1.6 dB are added. The amplifier gain of 29 dB and average factor of 5 dB are subtracted, giving a field strength of 27 dB μ V/m. This value in dB μ V/m was converted to its corresponding level in μ V/m.

 $RA = 52.0 \, dB\mu V/m$

 $AF = 7.4 \; dB \hspace{1cm} RR = 18.0 \; dB \mu V \\ CF = 1.6 \; dB \hspace{1cm} LF = 9.0 \; dB \label{eq:equation:equation}$

AG = 29.0 dB AV = 5.0 dBFS = RR + LF

 $FS = 18 + 9 = 27 \, dB\mu V/m$

Level in $\mu V/m = Common Antilogarithm [(27 dB<math>\mu V/m)/20] = 22.4 \mu V/m$



3.2 Radiated Emission Configuration Photograph

The worst case in radiated emission was found at 433.967 MHz

For electronic filing, the worst case radiated emission configuration photographs are saved with filename: radiated photos.pdf.

3.3 Radiated Emission Data

The data on the following page lists the significant emission frequencies, the limit and the margin of compliance. Numbers with a minus sign are below the limit.

Judgment: Passed by 9.8 dB



RADIATED EMISSIONS

Model: SL-3886-RF

Date of Test: August 14, 2017

Worst-Case Operating Mode: Transmitting

Table 1

Pursuant to FCC Part 15 Section 15.231(a) Requirement

			Pre-Amp	Antenna	Net at	Average	Calculated	Average Limit	
Polari-	Frequency	Reading	Gain	Factor	3m - Peak	Factor	at 3m	at 3m	Margin
zation	(MHz)	(dBµV)	(dB)	(dB)	(dBµV/m)	(dB)	(dBµV/m)	(dBµV/m)	(dB)
Н	433.967	69.3	16	25.0	78.3	7.3	71.0	80.8	-9.8
Н	867.935	33.2	16	31.0	48.2	7.3	40.9	60.8	-19.9
Н	1301.902	49.4	33	26.1	42.5	7.3	35.2	54.0	-18.8
Н	1735.870	52.6	33	27.2	46.8	7.3	39.5	60.8	-21.3
Н	2169.837	57.1	33	29.4	53.5	7.3	46.2	60.8	-14.6
V	2603.805	36.8	33	30.4	34.2	7.3	26.9	60.8	-33.9
Н	3037.773	36.6	33	31.9	42.8	7.3	35.5	60.8	-25.3
Н	3471.740	31.6	33	31.9	37.8	7.3	30.5	60.8	-30.3
Н	3905.708	29.4	33	33.3	37.0	7.3	29.7	54.0	-24.3
V	4339.675	29.3	33	34.8	38.4	7.3	31.1	54.0	-22.9

			Pre-	Antenna		Peak Limit	
Polari-	Frequency	Reading	Amp	factor	Net at 3m	at 3m	Margin
zation	(MHz)	(dBµV)	(dB)	(dB)	(dBµV/m)	(dBµV/m)	(dB)
Н	433.967	69.3	16	25.0	78.3	100.8	-22.5
Н	867.935	33.2	16	31.0	48.2	80.8	-32.6
Н	1301.902	50.4	34	26.1	42.5	74.0	-31.5
Н	1735.870	53.6	34	27.2	46.8	80.8	-34.0
Н	2169.837	58.1	34	29.4	53.5	80.8	-27.3
V	2603.805	37.8	34	30.4	34.2	80.8	-46.6
Н	3037.773	44.9	34	31.9	42.8	80.8	-38.0
Н	3471.740	39.9	34	31.9	37.8	80.8	-43.0
Н	3905.708	37.7	34	33.3	37.0	74.0	-37.0
V	4339.675	37.6	34	34.8	38. <i>4</i>	74.0	-35.6

NOTES: 1. Peak Detector Data unless otherwise stated.

- 2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distances were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
- 3. Negative sign in the column shows value below limit.
- 4. Horn antenna is used for the emission over 1000MHz.
- 5. Emission (the row indicated by **bold italic**) within the restricted band meets the requirement of FCC Part 15 Section 15.205.
- 6. Measurement Uncertainty is ±5.3dB at a level of confidence of 95%.



4.0 **EQUIPMENT PHOTOGRAPHS**

For electronic filing, the photographs are saved with filename: external photos.pdf and internal photos.pdf.

5.0 **PRODUCT LABELLING**

For electronics filing, the FCC ID label artwork and the label location are saved with filename: label.pdf.

6.0 **TECHNICAL SPECIFICATIONS**

For electronic filing, the block diagram and schematic of the tested EUT are saved with filename: block.pdf and circuit.pdf respectively.

7.0 **INSTRUCTION MANUAL**

For electronic filing, a preliminary copy of the Instruction Manual is saved with filename: manual.pdf.

This manual will be provided to the end-user with each unit sold/leased in the United States.




8.0 MISCELLANEOUS INFORMATION

The miscellaneous information includes details of the test procedure and measured bandwidth / calculation of factor such as pulse desensitization and averaging factor (calculation and timing diagram).

Timing Plot – Pursuant to FCC Part 15 Section 15.231(a1)- A manually operated transmitter shall employ a switch that will automatically deactivate the transmitter within not more than 5 seconds of being released.


Result: Transmission Duration = 1.98s (Pass)





8.1 Measured Bandwidth

The plot shows the fundamental emission when modulated. From the plot, the bandwidth is observed to be 190kHz, at 20dBc where the bandwidth limit is 1082.5kHz.





8.2 Discussion of Pulse Desensitization

Pulse desensitivity is not applicable for this device. The effective period (Teff) is approximately 4.8ms for a digital "1" bit which illustrated on technical specification, with a resolution bandwidth (3dB) of 1MHz, so the pulse desensitivity factor is 0dB.

8.3 Calculation of Average Factor

The duty cycle is simply the on-time divided by the period:

The duration of one cycle = 23.6 ms


Effective period of the cycle = $0.8 \times 3 + 3 \times 1 + 4.8 \times 1 \text{ms} = 10.2 \text{ ms}$


DC = 10.2/23.6 = 0.43

Therefore, the averaging factor is found by $20\log 0.43 = -7.3$ dB.




Average Factor









Average Factor








Average Factor







8.4 Emissions Test Procedures

The following is a description of the test procedure used by Intertek Testing Services Hong Kong Ltd. in the measurements of transmitter operating under the Part 15, Subpart C rules.

The transmitting equipment under test (EUT) is placed on a wooden turntable which is four feet in diameter and approximately 0.8m in height above the ground plane for emission measurement at or below 1GHz and 1.5m in height above the ground plane for emission measurement above 1GHz. During the radiated emissions test, the turntable is rotated and any cables leaving the EUT are manipulated to find the configuration resulting in maximum emissions. The EUT is adjusted through all three orthogonal axis to obtain maximum emission levels. The antenna height and polarization are also varied during the testing to search for maximum signal levels. The height of the antenna is varied from one to four meters.

Detector function for radiated emissions is in peak mode. Average readings, when required, are taken by measuring the duty cycle of the equipment under test and subtracting the corresponding amount in dB from the measured peak readings. A detailed description for the calculation of the average factor can be found in Exhibit 8.3.

The frequency range scanned is from the lowest radio frequency signal generated in the device which is greater than 9 kHz to the tenth harmonic of the highest fundamental frequency or 40 GHz, whichever is lower.



8.4 Emissions Test Procedures (cont'd)

The EUT is warmed up for 15 minutes prior to the test.

AC power to the unit is varied from 85% to 115% nominal and variation in the fundamental emission field strength is recorded. If battery powered, a new, fully charged battery is used.

Conducted measurements were made as described in ANSI C63.10 (2013).


The IF bandwidth used for measurement of radiated signal strength was 100 kHz or greater when frequency is below 1000 MHz. Where pulsed transmissions of short enough pulse duration warrant, a greater bandwidth is selected according to the recommendations of Hewlett Packard Application Note 150-2. A discussion of whether pulse desensitivity is applicable to this unit is included in this report (See Exhibit 8.1). Above 1000 MHz, a resolution bandwidth of 3 MHz is used.

Transmitter measurements are normally conducted at a measurement distance of three meters. However, to assure low enough noise floor in the forbidden bands and above 1 GHz, signals are acquired at a distance of one meter or less. All measurements are extrapolated to three meters using inverse scaling, unless otherwise reported. Measurements taken at a closer distance are so marked.




8.4.1 Radiated Emission Test Setup

The figure below shows the test setup, which is utilized to make these measurements.



Test setup of radiated emissions up to 1GHz



Test setup of radiated emissions above 1GHz



9.0 CONFIDENTIALITY REQUEST

For electronic filing, a preliminary copy of the confidentiality request is saved with filename: request.pdf.

10.0 EQUIPMENT LIST

1) Radiated Emissions Test

EQUIPMENT	Spectrum Analyzer	Log Periodic Antenna	Solid State Low Noise Preamplifier Assembly (1 - 18)GHz
Registration No.	EW-2466	EW-0447	EW-3229
Manufacturer	R&S	EMCO	BONN ELEKTRO
Model No.	FSP30	3146	BLMA 0118-5G
Calibration Date	Oct. 03, 2016	May 18, 2016	Oct. 24, 2016
Calibration Due Date	Aug. 20, 2017	Nov 18, 2017	Oct. 24, 2017

Equipment	Biconical Antenna	EMI Test Receiver	Double Ridged Guide Antenna
Registration No.	EW-0571	EW-3156	EW-0194
Manufacturer	EMCO	ROHDESCHWARZ	EMCO
Model No.	3104C	ESR26	3115
Calibration Date	May. 18, 2016	Dec. 06. 2016	Aug. 10, 2016
Calibration Due Date	Nov. 18, 2017	Dec. 06, 2017	Feb. 10, 2018

Equipment	Active Loop H-field (9kHz to 30MHz)	RF Cable 9kHz to 1000MHz	RF Cable (up to 40GHz)
Registration No.	EW-2313	EW-3170	EW-3155
Manufacturer	ELECTROMETRI	N/A	N/A
Model No.	EM-6876	9kHz to 1000MHz	1-40 GHz
Calibration Date	May. 18, 2016	Mar. 20, 2017	Dec. 05, 2016
Calibration Due Date	Nov. 18, 2017	Mar. 20, 2018	Dec. 05, 2017

Equipment	RF Pre-amplifier 3 pcs (9kHz to 40GHz)
Registration No.	EW-3006
Manufacturer	SCHWARZBECK
Model No.	BBV 9744
Calibration Date	Mar. 23, 2017
Calibration Due Date	Mar. 23, 2018

2) Bandedge Measurement

,	
EQUIPMENT	SPECTRUM ANALYZER
Registration No.	EW-2329
Manufacturer	R&S
Model No.	FSP3
Calibration Date	Aug. 26, 2016
Calibration Due Date	Aug. 26, 2017

END OF TEST REPORT