

Date: 2014-12-15

Page 1 of 88

No.: DM117676

Applicant:

CREATIVISION LIMITED

Rm 2003, 20/F, 303 Hennessy Road, Wanchai, Hong Kong

Manufacturer:

Shenzhen Adition Audio Science & Technology Co., Ltd.
Mingzhuo Industry Park, Guangming Main Street,
Guangming New District, Shenzhen, 518107, China

Description of Sample(s):

Product: Bluetooth Speaker
Brand Name: KS
Model Number: KSPKBOOM
FCC ID: 2ADRB-POCKETBOOM

Date Sample(s) Received:

2014-11-18

Date Tested:

2014-11-26 to 2014-12-12

Investigation Requested:

Perform ElectroMagnetic Interference measurement in accordance with FCC 47 CFR [Codes of Federal Regulations] Part 15: 2014 and ANSI C63.4: 2009 for FCC Certification.

Conclusion(s):

The submitted product COMPLIED with the requirements of Federal Communications Commission [FCC] Rules and Regulations Part 15. The tests were performed in accordance with the standards described above and on Section 2.2 in this Test Report.

Remark(s):

For additional model(s) details, see page 3



LONG Yun Jian, Along
Authorized Signatory
ElectroMagnetic Compatibility Department
For and on behalf of
STC (Dongguan) Company Limited

CONTENT:

Cover	Page 1 of 88
Content	Page 2-3 of 88
<u>1.0 General Details</u>	
1.1 Test Laboratory	Page 4 of 88
1.2 Equipment Under Test [EUT] Description of EUT operation	Page 4 of 88
1.3 Date of Order	Page 4 of 88
1.4 Submitted Sample	Page 4 of 88
1.5 Test Duration	Page 4 of 88
1.6 Country of Origin	Page 4 of 88
1.7 RF Module Details	Page 5 of 88
1.8 Antenna Details	Page 5 of 88
<u>2.0 Technical Details</u>	
2.1 Investigations Requested	Page 6 of 88
2.2 Test Standards and Results Summary	Page 6 of 88
2.3 Table for Test Modes	Page 7 of 88
<u>3.0 Test Results</u>	
3.1 Emission	Page 8 - 83 of 88

Date: 2014-12-15
No.: DM117676

Page 3 of 88

Appendix A

List of Measurement Equipment

Page 84 of 88

Appendix B

Ancillary Equipment

Page 84 of 88

Appendix C

Photographs

Page 85- 88 of 88

1.0 General Details

1.1 Test Laboratory

STC (Dongguan) Company Limited
EMC Laboratory
68 Fumin Nan Road, Dalang, Dongguan, Guangdong, China

Telephone: (86 769) 81119888
Fax: (86 769) 81116222

1.2 Equipment Under Test [EUT]

Description of Sample(s)

Product:	Bluetooth Speaker
Manufacturer:	Shenzhen Adition Audio Science & Technology Co., Ltd.
Brand Name:	KS
Model Number:	KSPKBOOM
Additional Model Number(s):	KSPBWH, KSPBRD, KSPBPI, KSPBPU, KSPBGN, KSPBBL, KSPBOR
Rating:	5.0Vd.c. (Powered by PC USB port) / Li-ion rechargeable battery x1 = 3.7Vd.c

1.2.1 Description of EUT Operation

The Equipment Under Test (EUT) is a Bluetooth Speaker of CREATIVISION LIMITED, it is Audio System, modulation by IC; and type is frequency hopping spread spectrum Modulation.

1.3 Date of Order

2014-11-18

1.4 Submitted Sample(s):

1 Sample

1.5 Test Duration

2014-11-26 to 2014-12-12

1.6 Country of Origin

China

1.7 RF Module Details

Module Model Number:	F-6288
Module FCC ID:	N/A
Module Transmission Type:	Bluetooth V2.1+EDR
Modulation:	FHSS (GFSK / $\pi/4$ -DQPSK / 8DPSK)
Data Rates:	1Mbps: GFSK 2 Mbps: $\pi/4$ -DQPSK 3 Mbps: 8DPSK
Frequency Range:	2400-2483.5MHz
Carrier Frequencies:	2402MHz – 2480MHz

Module Specification (specification provided by manufacturer)

1.8 Antenna Details

Antenna Type:	Meander line antenna
Antenna Gain:	0dBi

2.0 Technical Details**2.1 Investigations Requested**

Perform Electromagnetic Interference measurements in accordance with FCC 47CFR [Codes of Federal Regulations] Part 15: 2014 Regulations. FCC Public Notice DA 00-705 and ANSI C63.4: 2009 for FCC Certification.

2.2 Test Standards and Results Summary Tables

EMISSION Results Summary						
Test Condition	Test Requirement	Test Method	Class /	Test Result		
			Severity	Pass	Fail	N/A
Maximum Peak Conducted Output Power	FCC 47CFR 15.247(b)(1)	FCC Public Notice DA 00-705	N/A	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Radiated Spurious Emissions	FCC 47CFR 15.209	ANSI C63.4:2009	N/A	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
AC Mains Conducted Emissions	FCC 47CFR 15.207	ANSI C63.4:2009	N/A	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Number of Hopping Frequency	FCC 47CFR 15.247(a)(2)(b)(1)	FCC Public Notice DA 00-705	N/A	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
20dB Bandwidth	FCC 47CFR 15.247(a)(2)	FCC Public Notice DA 00-705	N/A	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Hopping Channel Separation	FCC 47CFR 15.247(a)(1)	FCC Public Notice DA 00-705	N/A	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Band-edge measurement (Radiated)	FCC 47CFR 15.247(d)	FCC Public Notice DA 00-705	N/A	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Pseudorandom Hopping Algorithm	FCC 47CFR 15.247(a)(1)	N/A	N/A	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Time of Occupancy (Dwell Time)	FCC 47CFR 15.247(a)(1)(iii)	FCC Public Notice DA 00-705	N/A	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Antenna requirement	FCC 47CFR 15.203	N/A	N/A	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
RF Exposure	FCC 47CFR 15.247(i)	N/A	N/A	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

Note: N/A – Not Applicable

2.3 Table for Test Modes

Preliminary tests were performed in different data rate to find the worst radiated emission. The data rate in the table below is the worst case rate with respect to the specific test item. Investigation has been done on all the possible configurations for searching the worst cases. The following table is a list of the test modes shown in this test report.

Test Items	Mode	Data Rate
Maximum Peak Conducted Output Power	GFSK / $\pi/4$ -DQPSK / 8DPSK	1MBps / 2MBps / 3MBps
Hopping Channel Separation	GFSK / $\pi/4$ -DQPSK / 8DPSK	1MBps / 2MBps / 3MBps
Number of Hopping Frequency	GFSK / $\pi/4$ -DQPSK / 8DPSK	2MBps
Time of Occupancy(Dwell Time)	8DPSK (DH1 / DH3 / DH5)	2MBps
Radiated Spurious Emissions	GFSK / $\pi/4$ -DQPSK / 8DPSK	1MBps / 2MBps / 3MBps
Band-edge compliance of Conducted Emission	GFSK / $\pi/4$ -DQPSK / 8DPSK	2MBps

3.0 Test Results

3.1 Emission

3.1.1 Maximum Peak Conducted Output Power

Test Requirement: FCC 47CFR 15.247(b)(1)
Test Method: FCC Pubic Notice DA 00-705
Test Date: 2014-11-26
Mode of Operation: Tx mode


Test Method:

The RF output of the EUT was connected to the spectrum analyzer. All the attenuation or cable loss will be added to the measured maximum output power. The results are recorded in dBm.

Spectrum Analyzer Setting:

RBW = 3 MHz, VBW= 3MHz, Sweep = Auto, Span = 10MHz
Detector = Peak, Trace = Max. hold

Test Setup:



Limits for Maximum Peak Conducted Output Power [FCC 47CFR 15.247]:

The maximum peak output power shall not exceed the following limits:

For frequency hopping systems employing at least 75 hopping channels: 1 Watt

For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 Watts

For Digital Transmission systems in 2400-2483.5 MHz Band: 1 Watt

Results of Bluetooth Communication mode (GFSK) (Fundamental Power): Pass

Transmitter Frequency (MHz)	Maximum conducted output power (Watt)
2402	0.000859

Transmitter Frequency (MHz)	Maximum conducted output power (Watt)
2441	0.000592

Transmitter Frequency (MHz)	Maximum conducted output power (Watt)
2480	0.000480

Results of Bluetooth Communication mode ($\pi/4$ -DQPSK) (Fundamental Power): Pass

Transmitter Frequency (MHz)	Maximum conducted output power (Watt)
2402	0.000839

Transmitter Frequency (MHz)	Maximum conducted output power (Watt)
2441	0.000578

Transmitter Frequency (MHz)	Maximum conducted output power (Watt)
2480	0.000459

Results of Bluetooth Communication mode (8 DPSK) (Fundamental Power): Pass

Transmitter Frequency (MHz)	Maximum conducted output power (Watt)
2402	0.000813

Transmitter Frequency (MHz)	Maximum conducted output power (Watt)
2441	0.000604

Transmitter Frequency (MHz)	Maximum conducted output power (Watt)
2480	0.000469

Calculated measurement uncertainty : 30MHz to 1GHz 1.7dB
1GHz to 18GHz 1.7dB

Remark:


1. All test data for each data rate were verified, but only the worst case was reported.
2. The EUT is programmed to transmit signals continuously for all testing.

Date: 2014-12-15

Page 10 of 88


No.: DM117676

**Test plot of Maximum Peak Conducted Output Power :
Bluetooth Communication mode (GFSK, 2402MHz)**



Date: 26.NOV.2014 19:41:03

Bluetooth Communication mode (GFSK, 2441MHz)




Date: 26.NOV.2014 19:46:30

Date: 2014-12-15
No.: DM117676


Page 11 of 88

Bluetooth Communication mode (GFSK, 2480MHz)



Date: 26.NOV.2014 19:49:53

Bluetooth Communication mode ($\pi/4$ -DQPSK, 2402MHz)




Date: 26.NOV.2014 19:41:55

Date: 2014-12-15
No.: DM117676


Page 12 of 88

Bluetooth Communication mode ($\pi/4$ -DQPSK, 2441MHz)



Date: 26.NOV.2014 19:47:03

Bluetooth Communication mode ($\pi/4$ -DQPSK, 2480MHz)




Date: 26.NOV.2014 19:49:30

Date: 2014-12-15
No.: DM117676


Page 13 of 88

Bluetooth Communication mode (8DPSK, 2402MHz)



Date: 26.NOV.2014 19:45:45

Bluetooth Communication mode (8DPSK, 2441MHz)




Date: 26.NOV.2014 19:47:52

Date: 2014-12-15
No.: DM117676

Page 14 of 88

Bluetooth Communication mode (8DPSK, 2480MHz)



Date: 26.NOV.2014 19:48:27

3.1.2 Radiated Spurious Emissions

Test Requirement:	FCC 47CFR 15.209
Test Method:	ANSI C63.4:2009
Test Date:	2014-12-12
Mode of Operation:	Tx mode/ Bluetooth +Charging mode (GFSK / $\pi/4$ -DQPSK/ 8DPSK)

Test Method:

The sample was placed 0.8m above the ground plane of semi-anechoic Chamber*. Measurements in both horizontal and vertical polarities were performed. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, considered typical configuration to obtain worst position, manipulating interconnecting cables, rotating turntable, varying antenna height from 1m to 4m in both horizontal and vertical polarizations. The emissions worst-case are shown in Test Results of the following pages.

*: Semi-anechoic chamber located on the STC (Dongguan) Company Ltd. 68 Fumin Nan Road, Dalang, Dongguan, Guangdong, PRC with a metal ground plane filed with the FCC pursuant to section 2.948 of the FCC rules, with Registration Number: 629686.

Spectrum Analyzer Setting:

9KHz – 30MHz (Pk & Av)


RBW: 10kHz
VBW: 30kHz
Sweep: Auto
Span: Fully capture the emissions being measured
Trace: Max. hold

30MHz – 1GHz (QP)

RBW: 120kHz
VBW: 120kHz
Sweep: Auto
Span: Fully capture the emissions being measured
Trace: Max. hold

Above 1GHz (Pk & Av)

RBW: 1MHz
VBW: 3MHz
Sweep: Auto
Span: Fully capture the emissions being measured
Trace: Max. hold

Test Setup:

- Absorbers placed on top of the ground plane are for measurements above 1000MHz only.
- Measurements between 30MHz to 1000MHz made with Bi-log antennas, above 1000MHz horn antennas are used, 9kHz to 30MHz loop antennas are used.

Limits for Radiated Emissions [FCC 47 CFR 15.209 Class B]:

Frequency Range		Quasi-Peak Limits
[MHz]		[μ V/m]
0.009-0.490		2400/F (kHz)
0.490-1.705		24000/F (kHz)
1.705-30		30
30-88		100
88-216		150
216-960		200
Above 960		500

The emission limits shown in the above table are based on measurement employing a CISPR quasi-peak detector and above 1000MHz are based on measurements employing an average detector.

Result of Tx mode (2402.0 MHz) (GFSK mode) (9kHz – 30MHz): Pass

Field Strength of Spurious Emissions						
Peak Value						
Frequency	Measured Level	Correction Factor	Field Strength	Field Strength	Limit	E-Field Polarity
MHz	dB μ V	dB/m	dB μ V/m	uV/m	uV/m	
Emissions detected are more than 20 dB below the FCC Limits						

Result of Tx mode (2402.0 MHz) (GFSK mode) (30MHz – 1GHz): Pass

Field Strength of Spurious Emissions						
Quasi-Peak Value						
Frequency	Measured Level	Correction Factor	Field Strength	Field Strength	Limit	E-Field Polarity
MHz	dB μ V	dB/m	dB μ V/m	uV/m	uV/m	
Emissions detected are more than 20 dB below the FCC Limits						

Result of Tx mode (2402.0 MHz) (GFSK mode) (Above 1GHz): Pass

Field Strength of Spurious Emissions						
Peak Value						
Frequency	Measured Level @3m	Correction Factor	Field Strength	Limit @3m	Margin	E-Field Polarity
MHz	dB μ V	dB/m	dB μ V/m	dB μ V/m	dB μ V/m	
4804.0	15.7	41.5	57.2	74.0	16.8	Vertical
4804.0	14.5	42.4	56.9	74.0	17.1	Horizontal
7206.0	7.3	45.1	52.4	74.0	21.6	Vertical
7206.0	5.9	46.2	52.1	74.0	21.9	Horizontal
9608.0	2.1	48.0	50.1	74.0	23.9	Vertical
9608.0	1.0	48.8	49.8	74.0	24.2	Horizontal
12010.0	-1.4	51.5	50.1	74.0	23.9	Vertical
12010.0	-2.9	52.4	49.5	74.0	24.5	Horizontal

Date: 2014-12-15

No.: DM117676

Page 18 of 88

Result of Tx mode (2402.0 MHz) (GFSK mode) (Above 1GHz): Pass

Field Strength of Spurious Emissions						
Average Value						
Frequency	Measured Level @3m	Correction Factor	Field Strength	Limit @3m	Margin	E-Field Polarity
MHz	dBuV	dB/m	dBuV/m	dBuV/m	dBuV/m	
4804.0	-0.4	41.5	41.1	54.0	12.9	Vertical
4804.0	-1.7	42.4	40.7	54.0	13.3	Horizontal
7206.0	-9.0	45.1	36.1	54.0	17.9	Vertical
7206.0	-10.2	46.2	36.0	54.0	18.0	Horizontal
9608.0	-14.0	48.0	34.0	54.0	20.0	Vertical
9608.0	-15.2	48.8	33.6	54.0	20.4	Horizontal
12010.0	-17.7	51.5	33.8	54.0	20.2	Vertical
12010.0	-19.0	52.4	33.4	54.0	20.6	Horizontal

Result of Tx mode (2441.0 MHz) (GFSK mode) (9kHz – 30MHz): Pass

Results of Tx mode (2441.0 MHz) (GFSK mode) (30MHz – 1000MHz): PASS

Date: 2014-12-15

Page 19 of 88

No.: DM117676

Result of Tx mode (2441.0 MHz) (GFSK mode) (Above 1GHz): Pass

Field Strength of Spurious Emissions						
Peak Value						
Frequency MHz	Measured Level @3m dBuV	Correction Factor dB/m	Field Strength dBuV/m	Limit @3m dBuV/m	Margin dBuV/m	E-Field Polarity
4882.0	17.3	41.6	58.9	74.0	15.1	Vertical
4882.0	15.8	42.5	58.3	74.0	15.7	Horizontal
7323.0	5.6	45.2	50.8	74.0	23.2	Vertical
7323.0	3.5	46.3	49.8	74.0	24.2	Horizontal
9764.0	1.8	48.1	49.9	74.0	24.1	Vertical
9764.0	-0.3	48.9	48.6	74.0	25.4	Horizontal
12205.0	-2.4	51.6	49.2	74.0	24.8	Vertical
12205.0	-4.4	52.5	48.1	74.0	25.9	Horizontal

Result of Tx mode (2441.0 MHz) (GFSK mode) (Above 1GHz): Pass

Field Strength of Spurious Emissions						
Average Value						
Frequency MHz	Measured Level @3m dBuV	Correction Factor dB/m	Field Strength dBuV/m	Limit @3m dBuV/m	Margin dBuV/m	E-Field Polarity
4882.0	1.2	41.6	42.8	54.0	11.2	Vertical
4882.0	-0.4	42.5	42.1	54.0	11.9	Horizontal
7323.0	-10.7	45.2	34.5	54.0	19.5	Vertical
7323.0	-13.6	46.3	32.7	54.0	21.3	Horizontal
9764.0	-14.3	48.1	33.8	54.0	20.2	Vertical
9764.0	-16.5	48.9	32.4	54.0	21.6	Horizontal
12205.0	-18.7	51.6	32.9	54.0	21.1	Vertical
12205.0	-20.5	52.5	32.0	54.0	22.0	Horizontal

Date: 2014-12-15

Page 20 of 88

No.: DM117676

Result of Tx mode (2480.0 MHz) (GFSK mode) (9kHz – 30MHz): Pass

Field Strength of Spurious Emissions						
Peak Value						
Frequency MHz	Measured Level dBuV	Correction Factor dB/m	Field Strength dBuV/m	Field Strength uV/m	Limit uV/m	E-Field Polarity
Emissions detected are more than 20 dB below the FCC Limits						

Results of Tx mode (2480.0 MHz) (GFSK mode) (30MHz – 1000MHz): PASS

Field Strength of Spurious Emissions						
Quasi-Peak Value						
Frequency MHz	Measured Level dBuV	Correction Factor dB/m	Field Strength dBuV/m	Field Strength uV/m	Limit uV/m	E-Field Polarity
Emissions detected are more than 20 dB below the FCC Limits						

Result of Tx mode (2480.0 MHz) (GFSK mode) (Above 1GHz): Pass

Field Strength of Spurious Emissions						
Peak Value						
Frequency MHz	Measured Level @3m dBuV	Correction Factor dB/m	Field Strength dBuV/m	Limit @3m dBuV/m	Margin dBuV/m	E-Field Polarity
4960.0	15.3	41.4	56.7	74.0	17.3	Vertical
4960.0	13.8	42.7	56.5	74.0	17.5	Horizontal
7440.0	6.1	45.6	51.7	74.0	22.3	Vertical
7440.0	3.9	46.5	50.4	74.0	23.6	Horizontal
9920.0	1.9	48.6	50.5	74.0	23.5	Vertical
9920.0	-0.5	49.7	49.2	74.0	24.8	Horizontal
12400.0	-1.9	51.7	49.8	74.0	24.2	Vertical
12400.0	-4.3	52.7	48.4	74.0	25.6	Horizontal

Date: 2014-12-15

Page 21 of 88

No.: DM117676

Result of Tx mode (2480.0 MHz) (GFSK mode) (Above 1GHz): Pass

Field Strength of Spurious Emissions						
Average Value						
Frequency MHz	Measured Level @3m dBuV	Correction Factor dB/m	Field Strength dBuV/m	Limit @3m dBuV/m	Margin dBuV/m	E-Field Polarity
4960.0	-0.8	41.4	40.6	54.0	13.4	Vertical
4960.0	-2.4	42.7	40.3	54.0	13.7	Horizontal
7440.0	-10.2	45.6	35.4	54.0	18.6	Vertical
7440.0	-12.2	46.5	34.3	54.0	19.7	Horizontal
9920.0	-15.2	48.6	33.4	54.0	20.6	Vertical
9920.0	-17.7	49.7	32.0	54.0	22.0	Horizontal
12400.0	-19.2	51.7	32.5	54.0	21.5	Vertical
12400.0	-21.4	52.7	31.3	54.0	22.7	Horizontal

Result of Tx mode (2402.0 MHz) ($\pi/4$ -DQPSK mode) (9kHz – 30MHz): Pass

Result of Tx mode (2402.0 MHz) ($\pi/4$ -DQPSK mode) (30MHz – 1GHz): Pass

Date: 2014-12-15

Page 22 of 88

No.: DM117676

Result of Tx mode (2402.0 MHz) ($\pi/4$ -DQPSK mode) (Above 1GHz): Pass

Field Strength of Spurious Emissions						
Peak Value						
Frequency MHz	Measured Level @3m dBuV	Correction Factor dB/m	Field Strength dBuV/m	Limit @3m dBuV/m	Margin dBuV/m	E-Field Polarity
4804.0	16.8	41.5	58.3	74.0	15.7	Vertical
4804.0	15.1	42.4	57.5	74.0	16.5	Horizontal
7206.0	6.5	45.1	51.6	74.0	22.4	Vertical
7206.0	5.0	46.2	51.2	74.0	22.8	Horizontal
9608.0	1.7	48.0	49.7	74.0	24.3	Vertical
9608.0	0.7	48.8	49.5	74.0	24.5	Horizontal
12010.0	-3.2	51.5	48.3	74.0	25.7	Vertical
12010.0	-4.2	52.4	48.2	74.0	25.8	Horizontal

Result of Tx mode (2402.0 MHz) ($\pi/4$ -DQPSK mode) (Above 1GHz): Pass

Field Strength of Spurious Emissions						
Average Value						
Frequency MHz	Measured Level @3m dBuV	Correction Factor dB/m	Field Strength dBuV/m	Limit @3m dBuV/m	Margin dBuV/m	E-Field Polarity
4804.0	0.7	41.5	42.2	54.0	11.8	Vertical
4804.0	-1.1	42.4	41.3	54.0	12.7	Horizontal
7206.0	-9.8	45.1	35.3	54.0	18.7	Vertical
7206.0	-11.1	46.2	35.1	54.0	18.9	Horizontal
9608.0	-14.4	48.0	33.6	54.0	20.4	Vertical
9608.0	-15.5	48.8	33.3	54.0	20.7	Horizontal
12010.0	-19.5	51.5	32.0	54.0	22.0	Vertical
12010.0	-20.3	52.4	32.1	54.0	21.9	Horizontal

Date: 2014-12-15

Page 23 of 88

No.: DM117676

Result of Tx mode (2441.0 MHz) ($\pi/4$ -DQPSK mode) (9kHz – 30MHz): Pass

Field Strength of Spurious Emissions						
Peak Value						
Frequency MHz	Measured Level dBuV	Correction Factor dB/m	Field Strength dBuV/m	Field Strength uV/m	Limit uV/m	E-Field Polarity
Emissions detected are more than 20 dB below the FCC Limits						

Results of Tx mode (2441.0 MHz) ($\pi/4$ -DQPSK mode) (30MHz – 1000MHz): PASS

Field Strength of Spurious Emissions						
Quasi-Peak Value						
Frequency MHz	Measured Level dBuV	Correction Factor dB/m	Field Strength dBuV/m	Field Strength uV/m	Limit uV/m	E-Field Polarity
Emissions detected are more than 20 dB below the FCC Limits						

Result of Tx mode (2441.0 MHz) ($\pi/4$ -DQPSK mode) (Above 1GHz): Pass

Field Strength of Spurious Emissions						
Peak Value						
Frequency MHz	Measured Level @3m dBuV	Correction Factor dB/m	Field Strength dBuV/m	Limit @3m dBuV/m	Margin dBuV/m	E-Field Polarity
4882.0	17.5	41.6	59.1	74.0	14.9	Vertical
4882.0	16.2	42.5	58.7	74.0	15.3	Horizontal
7323.0	0.1	45.2	45.3	74.0	28.7	Vertical
7323.0	5.4	46.3	51.7	74.0	22.3	Horizontal
9764.0	2.5	48.1	50.6	74.0	23.4	Vertical
9764.0	0.8	48.9	49.7	74.0	24.3	Horizontal
12205.0	-2.4	51.6	49.2	74.0	24.8	Vertical
12205.0	-4.4	52.5	48.1	74.0	25.9	Horizontal

Date: 2014-12-15

No.: DM117676

Page 24 of 88

Result of Tx mode (2441.0 MHz) ($\pi/4$ -DQPSK mode) (Above 1GHz): Pass

Field Strength of Spurious Emissions						
Average Value						
Frequency MHz	Measured Level @3m dBuV	Correction Factor dB/m	Field Strength dBuV/m	Limit @3m dBuV/m	Margin dBuV/m	E-Field Polarity
4882.0	1.4	41.6	43.0	54.0	11.0	Vertical
4882.0	0.0	42.5	42.5	54.0	11.5	Horizontal
7323.0	-8.2	45.2	37.0	54.0	17.0	Vertical
7323.0	-11.7	46.3	34.6	54.0	19.4	Horizontal
9764.0	-13.6	48.1	34.5	54.0	19.5	Vertical
9764.0	-15.4	48.9	33.5	54.0	20.5	Horizontal
12205.0	-2.5	51.6	49.1	54.0	4.9	Vertical
12205.0	-20.5	52.5	32.0	54.0	22.0	Horizontal

Result of Tx mode (2480.0 MHz) ($\pi/4$ -DQPSK mode) (9kHz – 30MHz): Pass

Results of Tx mode (2480.0 MHz) ($\pi/4$ -DQPSK mode) (30MHz – 1000MHz): PASS

Date: 2014-12-15

Page 25 of 88

No.: DM117676

Result of Tx mode (2480.0 MHz) ($\pi/4$ -DQPSK mode) (Above 1GHz): Pass

Field Strength of Spurious Emissions						
Peak Value						
Frequency MHz	Measured Level @3m dBuV	Correction Factor dB/m	Field Strength dBuV/m	Limit @3m dBuV/m	Margin dBuV/m	E-Field Polarity
4960.0	18.1	41.4	59.5	74.0	14.5	Vertical
4960.0	15.8	42.7	58.5	74.0	15.5	Horizontal
7440.0	6.3	45.6	51.9	74.0	22.1	Vertical
7440.0	3.7	46.5	50.2	74.0	23.8	Horizontal
9920.0	0.7	48.6	49.3	74.0	24.7	Vertical
9920.0	-2	49.7	47.7	74.0	26.3	Horizontal
12400.0	-3.1	51.7	48.6	74.0	25.4	Vertical
12400.0	-5.4	52.7	47.3	74.0	26.7	Horizontal

Result of Tx mode (2480.0 MHz) ($\pi/4$ -DQPSK mode) (Above 1GHz): Pass

Field Strength of Spurious Emissions						
Average Value						
Frequency MHz	Measured Level @3m dBuV	Correction Factor dB/m	Field Strength dBuV/m	Limit @3m dBuV/m	Margin dBuV/m	E-Field Polarity
4960.0	2.0	41.4	43.4	54.0	10.6	Vertical
4960.0	-0.4	42.7	42.3	54.0	11.7	Horizontal
7440.0	-10.0	45.6	35.6	54.0	18.4	Vertical
7440.0	-12.4	46.5	34.1	54.0	19.9	Horizontal
9920.0	-16.4	48.6	32.2	54.0	21.8	Vertical
9920.0	-19.2	49.7	30.5	54.0	23.5	Horizontal
12400.0	-20.4	51.7	31.3	54.0	22.7	Vertical
12400.0	-22.5	52.7	30.2	54.0	23.8	Horizontal

Date: 2014-12-15

Page 26 of 88

No.: DM117676

Result of Tx mode (2402.0 MHz) (8DPSK) (9kHz – 30MHz): Pass

Field Strength of Spurious Emissions						
Peak Value						
Frequency MHz	Measured Level dBuV	Correction Factor dB/m	Field Strength dBuV/m	Field Strength uV/m	Limit uV/m	E-Field Polarity
Emissions detected are more than 20 dB below the FCC Limits						

Result of Tx mode (2402.0 MHz) (8DPSK) (30MHz – 1GHz): Pass

Field Strength of Spurious Emissions						
Quasi-Peak Value						
Frequency MHz	Measured Level dBuV	Correction Factor dB/m	Field Strength dBuV/m	Field Strength uV/m	Limit uV/m	E-Field Polarity
Emissions detected are more than 20 dB below the FCC Limits						

Result of Tx mode (2402.0 MHz) (8DPSK) (Above 1GHz): Pass

Field Strength of Spurious Emissions						
Peak Value						
Frequency MHz	Measured Level @3m dBuV	Correction Factor dB/m	Field Strength dBuV/m	Limit @3m dBuV/m	Margin dBuV/m	E-Field Polarity
4804.0	16.6	41.5	58.1	74.0	15.9	Vertical
4804.0	14.3	42.4	56.7	74.0	17.3	Horizontal
7206.0	6.1	45.1	51.2	74.0	22.8	Vertical
7206.0	4.6	46.2	50.8	74.0	23.2	Horizontal
9608.0	2.7	48.0	50.7	74.0	23.3	Vertical
9608.0	0.1	48.8	48.9	74.0	25.1	Horizontal
12010.0	-2.6	51.8	49.2	74.0	24.8	Vertical
12010.0	-4.8	52.4	47.6	74.0	26.4	Horizontal

Date: 2014-12-15

No.: DM117676

Page 27 of 88

Result of Tx mode (2402.0 MHz) (8DPSK) (Above 1GHz): Pass

Field Strength of Spurious Emissions						
Average Value						
Frequency	Measured Level @3m	Correction Factor	Field Strength	Limit @3m	Margin	E-Field Polarity
MHz	dBuV	dB/m	dBuV/m	dBuV/m	dBuV/m	
4804.0	0.5	41.5	42.0	54.0	12.0	Vertical
4804.0	-1.9	42.4	40.5	54.0	13.5	Horizontal
7206.0	-10.2	45.1	34.9	54.0	19.1	Vertical
7206.0	-11.5	46.2	34.7	54.0	19.3	Horizontal
9608.0	-13.4	48.0	34.6	54.0	19.4	Vertical
9608.0	-16.1	48.8	32.7	54.0	21.3	Horizontal
12010.0	-18.9	51.8	32.9	54.0	21.1	Vertical
12010.0	-20.9	52.4	31.5	54.0	22.5	Horizontal

Result of Tx mode (2441.0 MHz) (8DPSK) (9kHz – 30MHz): Pass

Results of Tx mode (2441.0 MHz) (8DPSK) (30MHz – 1000MHz): PASS

Date: 2014-12-15

Page 28 of 88

No.: DM117676

Result of Tx mode (2441.0 MHz) (8DPSK) (Above 1GHz): Pass

Field Strength of Spurious Emissions						
Peak Value						
Frequency MHz	Measured Level @3m dBuV	Correction Factor dB/m	Field Strength dBuV/m	Limit @3m dBuV/m	Margin dBuV/m	E-Field Polarity
4882.0	17.1	41.6	58.7	74.0	15.3	Vertical
4882.0	14.1	42.5	56.6	74.0	17.4	Horizontal
7323.0	-2.4	45.2	42.8	74.0	31.2	Vertical
7323.0	3.2	46.3	49.5	74.0	24.5	Horizontal
9764.0	0.7	48.1	48.8	74.0	25.2	Vertical
9764.0	-1.7	48.9	47.2	74.0	26.8	Horizontal
12205.0	-4.7	51.6	46.9	74.0	27.1	Vertical
12205.0	-6.3	52.5	46.2	74.0	27.8	Horizontal

Result of Tx mode (2441.0 MHz) (8DPSK) (Above 1GHz): Pass

Field Strength of Spurious Emissions						
Average Value						
Frequency MHz	Measured Level @3m dBuV	Correction Factor dB/m	Field Strength dBuV/m	Limit @3m dBuV/m	Margin dBuV/m	E-Field Polarity
4882.0	1.0	41.6	42.6	54.0	11.4	Vertical
4882.0	-2.1	42.5	40.4	54.0	13.6	Horizontal
7323.0	-10.7	45.2	34.5	54.0	19.5	Vertical
7323.0	-13.9	46.3	32.4	54.0	21.6	Horizontal
9764.0	-15.4	48.1	32.7	54.0	21.3	Vertical
9764.0	-17.9	48.9	31	54.0	23.0	Horizontal
12205.0	-2.5	51.6	49.1	54.0	4.9	Vertical
12205.0	-22.4	52.5	30.1	54.0	23.9	Horizontal

Date: 2014-12-15

Page 29 of 88

No.: DM117676

Result of Tx mode (2480.0 MHz) (8DPSK) (9kHz – 30MHz): Pass

Field Strength of Spurious Emissions						
Peak Value						
Frequency MHz	Measured Level dBuV	Correction Factor dB/m	Field Strength dBuV/m	Field Strength uV/m	Limit uV/m	E-Field Polarity
Emissions detected are more than 20 dB below the FCC Limits						

Results of Tx mode (2480.0 MHz) (8DPSK) (30MHz – 1000MHz): PASS

Field Strength of Spurious Emissions						
Quasi-Peak Value						
Frequency MHz	Measured Level dBuV	Correction Factor dB/m	Field Strength dBuV/m	Field Strength uV/m	Limit uV/m	E-Field Polarity
Emissions detected are more than 20 dB below the FCC Limits						

Result of Tx mode (2480.0 MHz) (8DPSK) (Above 1GHz): Pass

Field Strength of Spurious Emissions						
Peak Value						
Frequency MHz	Measured Level @3m dBuV	Correction Factor dB/m	Field Strength dBuV/m	Limit @3m dBuV/m	Margin dBuV/m	E-Field Polarity
4960.0	16.5	41.4	57.9	74.0	16.1	Vertical
4960.0	13.7	42.7	56.4	74.0	17.6	Horizontal
7440.0	6.8	45.6	52.4	74.0	21.6	Vertical
7440.0	4.6	46.5	51.1	74.0	22.9	Horizontal
9920.0	1.5	48.6	50.1	74.0	23.9	Vertical
9920.0	-1.0	49.7	48.7	74.0	25.3	Horizontal
12400.0	-3.2	51.7	48.5	74.0	25.5	Vertical
12400.0	-5.8	52.7	46.9	74.0	27.1	Horizontal

Result of Tx mode (2480.0 MHz) (8DPSK) (Above 1GHz): Pass

Field Strength of Spurious Emissions						
Average Value						
Frequency MHz	Measured Level @3m dBuV	Correction Factor dB/m	Field Strength dBuV/m	Limit @3m dBuV/m	Margin dBuV/m	E-Field Polarity
4960.0	0.4	41.4	41.8	54.0	12.2	Vertical
4960.0	-2.5	42.7	40.2	54.0	13.8	Horizontal
7440.0	-9.5	45.6	36.1	54.0	17.9	Vertical
7440.0	-11.5	46.5	35.0	54.0	19.0	Horizontal
9920.0	-15.6	48.6	33.0	54.0	21.0	Vertical
9920.0	-18.2	49.7	31.5	54.0	22.5	Horizontal
12400.0	-20.5	51.7	31.2	54.0	22.8	Vertical
12400.0	-22.9	52.7	29.8	54.0	24.2	Horizontal

Remarks:

* Denotes restricted band of operation.

Measurements were made using a peak detector. Any emission less than 1000MHz and falling within the restricted bands of FCC Rules Part 15 Section 15.205 and the limits of FCC Rules Part 15 Section 15.209 were applied.

Correction Factor included Antenna Factor and Cable Attenuation.

Calculated measurement uncertainty: (9kHz - 30MHz): 3.3dB

(30MHz - 1GHz): 4.6dB

(1GHz - 26GHz): 4.4dB

Emissions in the vertical and horizontal polarizations have been investigated and the worst-case test results are recorded in this report.


Limits for Radiated Emissions [FCC 47 CFR 15.209 Class B]:

Frequency Range [MHz]	Quasi-Peak Limits [μ V/m]
0.009-0.490	2400/F (kHz)
0.490-1.705	24000/F (kHz)
1.705-30	30
30-88	100
88-216	150
216-960	200
Above 960	500

The emission limits shown in the above table are based on measurement employing a CISPR quasi-peak detector and above 1000MHz are based on measurements employing an average detector.

Result of Bluetooth Communication mode(GFSK / $\pi/4$ -DQPSK/ 8DPSK) (30MHz – 1GHz): Pass
Please refer to the following table for result details

Horizontal



Date: 2014-12-15

Page 32 of 88

No.: DM117676

Result of Bluetooth Communication mode (GFSK / $\pi/4$ -DQPSK/ 8DPSK) (30MHz – 1GHz): Pass

Radiated Emissions Quasi-Peak					
Emission Frequency MHz	E-Field Polarity	Level @3m dBμV/m	Limit @3m dBμV/m	Level @3m μV/m	Limit @3m μV/m
30.4	Horizontal	31.2	40.0	36.3	100
406.4	Horizontal	36.2	46.0	64.6	200
713.6	Horizontal	41.2	46.0	114.8	200


Limits for Radiated Emissions [FCC 47 CFR 15.209 Class B]:

Frequency Range [MHz]	Quasi-Peak Limits [μ V/m]
0.009-0.490	2400/F (kHz)
0.490-1.705	24000/F (kHz)
1.705-30	30
30-88	100
88-216	150
216-960	200
Above 960	500

The emission limits shown in the above table are based on measurement employing a CISPR quasi-peak detector and above 1000MHz are based on measurements employing an average detector.

Result of Bluetooth Communication mode (GFSK / $\pi/4$ -DQPSK/ 8DPSK) (30MHz – 1GHz): Pass
Please refer to the following table for result details

Vertical



Result of Bluetooth Communication mode (GFSK / $\pi/4$ -DQPSK/ 8DPSK) (30MHz – 1GHz): Pass

Radiated Emissions Quasi-Peak					
Emission Frequency MHz	E-Field Polarity	Level @3m dB μ V/m	Limit @3m dB μ V/m	Level @3m μ V/m	Limit @3m μ V/m
30.8	Vertical	37.3	40.0	73.3	100
64.9	Vertical	26.7	40.0	21.6	100
619.6	Vertical	37.3	46.0	73.3	200

Remarks:

Calculated measurement uncertainty (30MHz – 1GHz): 4.6dB


Emissions in the vertical and horizontal polarizations have been investigated and the worst-case test results are recorded in this report.

3.1.3 AC Mains Conducted Emissions (0.15MHz to 30MHz)

Test Requirement:	FCC 47CFR 15.207
Test Method:	ANSI C63.4:2009
Test Date:	2014-11-28
Mode of Operation:	Bluetooth + Charge mode
Test Voltage:	120V a.c. 60Hz

Test Method:

The test was performed in accordance with ANSI C63.4: 2009, with the following: an initial measurement was performed in peak and average detection mode on the live line, any emissions recorded within 30dB of the relevant limit line were re-measured using quasi-peak and average detection on the live and neutral lines with the worst case recorded in the table of results.

Test Setup:

Limit for Conducted Emissions (FCC 47 CFR 15.207):


Frequency Range [MHz]	Quasi-Peak Limits [dB μ V]	Average [dB μ V]
0.15-0.5	66 to 56*	56 to 46*
0.5-5.0	56	46
5.0-30.0	60	50

* Decreases with the logarithm of the frequency.

Limits for Conducted Emissions Test, please refer to limit lines (Quasi-Peak and Average) in the following diagram.

Result of Bluetooth Communication+ Charging mode (USB connect to PC) (L): PASS

Please refer to the following diagram for individual results.



Conductor Live or Neutral	Frequency MHz	Quasi-peak		Average	
		Level dB μ V	Limit dB μ V	Level dB μ V	Limit dB μ V
Live	0.550	26.0	56.0	-*-	-*-
Live	1.235	26.9	56.0	-*-	-*-
Live	17.315	30.5	60.0	-*-	-*-
Live	0.745	-*-	-*-	20.2	46.0
Live	2.230	-*-	-*-	17.2	46.0
Live	19.930	-*-	-*-	20.6	50.0

Limit for Conducted Emissions (FCC 47 CFR 15.207):


Frequency Range [MHz]	Quasi-Peak Limits [dB μ V]	Average [dB μ V]
0.15-0.5	66 to 56*	56 to 46*
0.5-5.0	56	46
5.0-30.0	60	50

* Decreases with the logarithm of the frequency.

Limits for Conducted Emissions Test, please refer to limit lines (Quasi-Peak and Average) in the following diagram.

Result of Bluetooth Communication+ Charging mode (USB connect to PC) (N): PASS

Please refer to the following diagram for individual results.



Conductor Live or Neutral	Frequency MHz	Quasi-peak		Average	
		Level dB μ V	Limit dB μ V	Level dB μ V	Limit dB μ V
Neutral	0.395	30.1	56.0	-*-	-*-
Neutral	1.740	25.8	56.0	-*-	-*-
Neutral	18.925	31.2	60.0	-*-	-*-
Neutral	0.745	-*-	-*-	22.0	46.0
Neutral	1.240	-*-	-*-	21.8	46.0
Neutral	18.875	-*-	-*-	21.3	50.0

Remarks:

Calculated measurement uncertainty (0.15MHz – 30MHz): 3.2dB

-*- Emission(s) that is far below the corresponding limit line.

3.1.4 Number of Hopping Frequency**Limit of Number of Hopping Frequency**

Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels

Test Method:


The RF output of the EUT was connected to the spectrum analyzer by a low loss cable.

Spectrum Analyzer Setting:

RBW = 1MHz, VBW \geq RBW, Sweep = Auto, Span = the frequency band of operation
Detector = Peak, Trace = Max. hold

Test Setup:


As Test Setup of clause 3.1.1 in this test report.

Measurement Data:**GFSK: 79 of 79 Channel**

Date: 2014-12-15
No.: DM117676

Page 39 of 88

Pi/4 DQPSK: 79 of 79 Channel




Date: 26.NOV.2014 10:02:38

Date: 2014-12-15
No.: DM117676

Page 40 of 88

8DPSK: 79 of 79 Channel



Date: 26.NOV.2014 10:09:33

3.1.5 20dB Bandwidth

Test Requirement:	FCC 47CFR 15.247(a)(1)
Test Method:	ANSI C63.4:2009
Test Date:	2014-11-26
Mode of Operation:	Communication mode

Remark:

The result has been done on all the possible configurations for searching the worst cases.

Test Method:

The bandwidth is measured at an amplitude level reduced from the reference level by a specified ratio. The reference level is the level of the highest amplitude signal observed from the transmitter at the fundamental frequency. Once the reference level is established, the equipment is conditioned with typical modulating signal to produce the worst-case (i.e. the widest) bandwidth.

Test Setup:

As Test Setup of clause 3.1.1 in this test report.


Date: 2014-12-15

Page 42 of 88

No.: DM117676

Fundamental Frequency [MHz]	20dB Bandwidth [MHz]	FCC Limits [MHz]
2402	0.915	Within 2400-2483.5

(Lowest Operating Frequency) - (GFSK)



Date: 26.NOV.2014 10:13:18


Date: 2014-12-15

Page 43 of 88

No.: DM117676

Fundamental Frequency [MHz]	20dB Bandwidth [MHz]	FCC Limits [MHz]
2441	0.910	Within 2400-2483.5

(Middle Operating Frequency) - (GFSK)



Date: 26.NOV.2014 10:21:49


Date: 2014-12-15

Page 44 of 88

No.: DM117676

Fundamental Frequency [MHz]	20dB Bandwidth [MHz]	FCC Limits [MHz]
2480	0.905	Within 2400-2483.5

(Highest Operating Frequency) - (GFSK)



Date: 26.NOV.2014 10:28:39


Date: 2014-12-15

Page 45 of 88

No.: DM117676

Fundamental Frequency [MHz]	20dB Bandwidth [MHz]	FCC Limits [MHz]
2402	1.185	Within 2400-2483.5

(Lowest Operating Frequency) - ($\pi/4$ -DQPSK)



Date: 26.NOV.2014 10:14:40


Date: 2014-12-15

Page 46 of 88

No.: DM117676

Fundamental Frequency [MHz]	20dB Bandwidth [MHz]	FCC Limits [MHz]
2441	1.180	Within 2400-2483.5

(Middle Operating Frequency) - ($\pi/4$ -DQPSK)



Date: 26.NOV.2014 10:20:47


Date: 2014-12-15

Page 47 of 88

No.: DM117676

Fundamental Frequency [MHz]	20dB Bandwidth [MHz]	FCC Limits [MHz]
2480	1.180	Within 2400-2483.5

(Highest Operating Frequency) - ($\pi/4$ -DQPSK)



Date: 26.NOV.2014 10:29:34


Date: 2014-12-15

Page 48 of 88

No.: DM117676

Fundamental Frequency [MHz]	20dB Bandwidth [MHz]	FCC Limits [MHz]
2402	1.220	Within 2400-2483.5

(Lowest Operating Frequency) - (8DPSK)



Date: 26.NOV.2014 10:15:59


Date: 2014-12-15

Page 49 of 88

No.: DM117676

Fundamental Frequency [MHz]	20dB Bandwidth [MHz]	FCC Limits [MHz]
2441	1.215	Within 2400-2483.5

(Middle Operating Frequency) - (8DPSK)



Date: 26.NOV.2014 10:19:17


Date: 2014-12-15

Page 50 of 88

No.: DM117676

Fundamental Frequency [MHz]	20dB Bandwidth [MHz]	FCC Limits [MHz]
2480	1.215	Within 2400-2483.5

(Highest Operating Frequency) - (8DPSK)



Date: 26.NOV.2014 10:31:41

3.1.6 Hopping Channel Separation

Requirements:

Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

Limit:

The measured maximum bandwidth * 2/3 = 1.220MHz * 2/3 = 813.3kHz


Date: 2014-12-15

Page 52 of 88

No.: DM117676

Channel separation = 1MHz (>813.3kHz) (GFSK)

Channel 0 – Channel 1, Pass




Date: 26.NOV.2014 10:34:42

Date: 2014-12-15
No.: DM117676

Page 53 of 88

Channel 39 – Channel 40, Pass




Date: 26.NOV.2014 10:44:43

Date: 2014-12-15

Page 54 of 88

No.: DM117676

Channel 77 – Channel 78, Pass



Date: 26.NOV.2014 10:47:09


Date: 2014-12-15

Page 55 of 88

No.: DM117676

Channel separation = 1MHz (>813.3kHz) ($\pi/4$ - DQPSK)

Channel 0 – Channel 1, Pass




Date: 26.NOV.2014 10:36:57

Date: 2014-12-15

Page 56 of 88

No.: DM117676

Channel 39 – Channel 40, Pass




Date: 26.NOV.2014 10:43:01

Date: 2014-12-15

Page 57 of 88

No.: DM117676

Channel 77 – Channel 78, Pass



Date: 26.NOV.2014 10:48:26


Date: 2014-12-15

Page 58 of 88

No.: DM117676

Channel separation = 1MHz (>813.3kHz) (8DPSK)

Channel 0 – Channel 1, Pass




Date: 26.NOV.2014 10:39:02

Date: 2014-12-15
No.: DM117676

Page 59 of 88

Channel 39 – Channel 40, Pass




Date: 26.NOV.2014 10:41:06

Date: 2014-12-15

Page 60 of 88

No.: DM117676

Channel 77 – Channel 78, Pass




Date: 26.NOV.2014 10:50:29

3.1.7 Band-edge Compliance of RF Conducted Emissions Measurement:**Limit :**

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required.

Frequency Range [MHz]	Radiated Emission Attenuated below the Fundamental [dB]
2400 – Lowest Fundamental (2402)	27.60




Date: 2014-12-15

Page 62 of 88

No.: DM117676

Band-edge Compliance of RF Conducted Emissions Measurement:

Frequency Range [MHz]	Radiated Emission Attenuated below the Fundamental [dB]
Highest Fundamental (2480) - 2483.5	29.97



Date: 26.NOV.2014 20:03:45


Date: 2014-12-15

Page 63 of 88

No.: DM117676

Band-edge Compliance of RF Conducted Emissions Measurement:

Frequency Range [MHz]	Radiated Emission Attenuated below the Fundamental [dB]
2400 - Lowest Fundamental (2402)	27.76



Date: 26.NOV.2014 19:55:07


Date: 2014-12-15

Page 64 of 88

No.: DM117676

Band-edge Compliance of RF Conducted Emissions Measurement:

Frequency Range [MHz]	Radiated Emission Attenuated below the Fundamental [dB]
Highest Fundamental (2480) - 2483.5	30.66



Date: 26.NOV.2014 20:01:26


Date: 2014-12-15

Page 65 of 88

No.: DM117676

Band-edge Compliance of RF Conducted Emissions Measurement:

Frequency Range [MHz]	Radiated Emission Attenuated below the Fundamental [dB]
2400 - Lowest Fundamental (2402)	27.44



Date: 26.NOV.2014 19:56:50


Date: 2014-12-15

Page 66 of 88

No.: DM117676

Band-edge Compliance of RF Conducted Emissions Measurement:

Frequency Range [MHz]	Radiated Emission Attenuated below the Fundamental [dB]
Highest Fundamental (2480) - 2483.5	31.22



Date: 26.NOV.2014 19:58:58

Band-edge Compliance of RF Radiated Emissions Measurement:**Limit :**

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 5.205(c)).

Result: Band-edge Compliance of RF Radiated Emissions (GFSK Lowest)

Field Strength of Band-edge Compliance Peak Value						
Frequency MHz	Measured Level @3m dB μ V	Correction Factor dB/m	Field Strength dB μ V/m	Limit @3m dB μ V/m	Margin dB μ V/m	E-Field Polarity
2400.0	30.8	36.8	67.6	74.0	6.4	Vertical

Field Strength of Band-edge Compliance Average Value						
Frequency MHz	Measured Level @3m dB μ V	Correction Factor dB/m	Field Strength dB μ V/m	Limit @3m dB μ V/m	Margin dB μ V/m	E-Field Polarity
2400.0	10.7	36.8	47.5	54.0	6.5	Vertical

Result: Band-edge Compliance of RF Radiated Emissions (GFSK Highest)

Field Strength of Band-edge Compliance						
Peak Value						
Frequency MHz	Measured Level @3m dB μ V	Correction Factor dB/m	Field Strength dB μ V/m	Limit @3m dB μ V/m	Margin dB μ V/m	E-Field Polarity
2483.5	28.5	36.8	65.3	74.0	8.7	Horizontal

Field Strength of Band-edge Compliance						
Average Value						
Frequency MHz	Measured Level @3m dB μ V	Correction Factor dB/m	Field Strength dB μ V/m	Limit @3m dB μ V/m	Margin dB μ V/m	E-Field Polarity
2483.5	9.3	36.8	46.1	54.0	7.9	Horizontal

Result: Band-edge Compliance of RF Radiated Emissions ($\pi/4$ -DQPSK Lowest)

Field Strength of Band-edge Compliance						
Peak Value						
Frequency MHz	Measured Level @3m dB μ V	Correction Factor dB/m	Field Strength dB μ V/m	Limit @3m dB μ V/m	Margin dB μ V/m	E-Field Polarity
2400.0	30.6	36.8	67.4	74.0	6.6	Vertical

Field Strength of Band-edge Compliance						
Average Value						
Frequency MHz	Measured Level @3m dB μ V	Correction Factor dB/m	Field Strength dB μ V/m	Limit @3m dB μ V/m	Margin dB μ V/m	E-Field Polarity
2400.0	10.5	36.8	47.3	54.0	6.7	Vertical

Result: Band-edge Compliance of RF Radiated Emissions ($\pi/4$ -DQPSK Highest)

Field Strength of Band-edge Compliance						
Peak Value						
Frequency MHz	Measured Level @3m dB μ V	Correction Factor dB/m	Field Strength dB μ V/m	Limit @3m dB μ V/m	Margin dB μ V/m	E-Field Polarity
2483.5	28.0	36.8	64.8	74.0	9.2	Horizontal

Field Strength of Band-edge Compliance						
Average Value						
Frequency MHz	Measured Level @3m dB μ V	Correction Factor dB/m	Field Strength dB μ V/m	Limit @3m dB μ V/m	Margin dB μ V/m	E-Field Polarity
2483.5	8.8	36.8	45.6	54.0	8.4	Horizontal

Date: 2014-12-15

Page 69 of 88

No.: DM117676

Result: Band-edge Compliance of RF Radiated Emissions (8DPSK Lowest)

Field Strength of Band-edge Compliance						
Peak Value						
Frequency MHz	Measured Level @3m dB μ V	Correction Factor dB/m	Field Strength dB μ V/m	Limit @3m dB μ V/m	Margin dB μ V/m	E-Field Polarity
2400.0	31.1	36.8	67.9	74.0	6.1	Vertical

Field Strength of Band-edge Compliance						
Average Value						
Frequency MHz	Measured Level @3m dB μ V	Correction Factor dB/m	Field Strength dB μ V/m	Limit @3m dB μ V/m	Margin dB μ V/m	E-Field Polarity
2400.0	11.0	36.8	47.8	54.0	6.2	Vertical

Result: Band-edge Compliance of RF Radiated Emissions (8DPSK Highest)

Field Strength of Band-edge Compliance						
Peak Value						
Frequency MHz	Measured Level @3m dB μ V	Correction Factor dB/m	Field Strength dB μ V/m	Limit @3m dB μ V/m	Margin dB μ V/m	E-Field Polarity
2483.5	27.0	36.8	63.8	74.0	10.2	Horizontal

Field Strength of Band-edge Compliance						
Average Value						
Frequency MHz	Measured Level @3m dB μ V	Correction Factor dB/m	Field Strength dB μ V/m	Limit @3m dB μ V/m	Margin dB μ V/m	E-Field Polarity
2483.5	7.8	36.8	44.6	54.0	9.4	Horizontal

3.1.8 Time of Occupancy (Dwell Time)**Requirements:**

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channel employed.


No requirements for Digital Transmission System.

Dwell Time = Pulse Duration * hop rate / number of channel * observation duration

Observed duration: 0.4s x 79 = 31.6s

Measurement Data:

Channel Occupied in 8DPSK: 79 of 79 Channel




Date: 26.NOV.2014 10:09:33

DH5 Packet:


DH5 Packet permit maximum $1600/79/6 = 3.37$ hops per second in each channel (5 time slots RX, 1 time slot TX). The Dwell time is the time duration of the pulse times $3.37 \times 31.6 = 106.6$ within 31.6 seconds

Fig. A
[Pulse duration of Lowest Channel]




Date: 26.NOV.2014 15:33:59

Fig. B
[Pulse duration of Middle Channel]



Date: 26.NOV.2014 15:35:35

Fig. C
[Pulse duration of Highest Channel]




Date: 26.NOV.2014 15:37:11

DH3 Packet:


DH3 Packet permit maximum $1600/79/4 = 5.06$ hops per second in each channel (3 time slots RX, 1 time slot TX). The Dwell time is the time duration of the pulse times $5.06 \times 31.6 = 160$ within 31.6 seconds

Fig. D
[Pulse duration of Lowest Channel]




Date: 26.NOV.2014 15:30:01

Fig. E
[Pulse duration of Middle Channel]



Date: 26.NOV.2014 15:29:00

Fig. F
[Pulse duration of Highest Channel]




Date: 26.NOV.2014 15:27:58

DH1 Packet:


DH1 Packet permit maximum $1600/79/2 = 10.12$ hops per second in each channel (3 time slots RX, 1 time slot TX). The Dwell time is the time duration of the pulse times $10.12 \times 31.6 = 320$ within 31.6 seconds

Fig. G
[Pulse duration of Lowest Channel]




Date: 26.NOV.2014 11:39:40

Fig. H
[Pulse duration of Middle Channel]



Date: 26.NOV.2014 13:54:20

Fig. I
[Pulse duration of Highest Channel]



Date: 26.NOV.2014 13:55:51

Time of occupancy (Dwell Time):

Data Packet	Frequency (MHz)	Pulse Duration (ms)	Dwell Time (s)	Limits (s)	Test Results
DH5	2402	2.909	0.310	0.400	Complies
DH5	2441	2.909	0.310	0.400	Complies
DH5	2480	2.909	0.310	0.400	Complies
DH3	2402	1.645	0.263	0.400	Complies
DH3	2441	1.645	0.263	0.400	Complies
DH3	2480	1.645	0.263	0.400	Complies
DH1	2402	0.395	0.126	0.400	Complies
DH1	2441	0.395	0.126	0.400	Complies
DH1	2480	0.395	0.126	0.400	Complies

3.1.9 Channel Centre Frequency

Requirements:

Frequency hopping system in the 2400-2483.5MHz band shall use at least 79 (Channel 0 to 78) non-overlapping channels.

The EUT operates in according with the Bluetooth system specification within the 2400 - 2483.5 MHz frequency band.

RF channels for Bluetooth systems are spaced 1 MHz and are ordered in channel number k. In order to comply with out-of-band regulations, a lower frequency guard band of 2.0 MHz and a higher frequency guard band of 3.5MHz is used.

The operating frequencies of each channel are as follows:

First RF channel start from 2400MHz + 2MHz guard band = 2402MHz

Frequency of RF Channel = $2402+k$ MHz, $k = 0, \dots, 78$ (Channel separation = 1MHz)

3.1.10 Pseudorandom Hopping Algorithm

Requirements:

The channel frequencies shall be selected from a pseudorandom ordered list of hopping frequencies. Each frequency must be used equally by the transmitter.

EUT Pseudorandom Hopping Algorithm

The EUT is a Bluetooth device, the Pseudo-random hopping pattern; hopping characteristics and algorithm are based on the Bluetooth specification.

3.1.11 Antenna Requirement

Test Requirements: § 15.203

Test Specification:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Test Results:

This is Meander line antenna. There is no external antenna, the antenna gain = 0dBi. User is unable to remove or changed the Antenna.

3.1.12 RF Exposure

Test Requirement: FCC 47CFR 15.247(i)
Test Date: 2014-11-26
Mode of Operation: Tx mode

Requirements:

In 15.247(i), an equipment shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the limits in §§ 1.1310 and 2.1093 of this chapter. Applications to the Commission for construction permits, licenses to transmit or renewals thereof, equipment authorizations or modifications in existing facilities must contain a statement confirming compliance with the limits unless the facility, operation, or transmitter is categorically excluded, as discussed below. Technical information showing the basis for this statement must be submitted to the Commission upon request.

According to KDB447498 D01 General RF Exposure Guidance v05, unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Exclusion Threshold condition.

Test Results:**RF Exposure Evaluation**

The Maximum conducted output power = 0.859 mW (at frequency = 2.402 GHz)

It's Conducted source-based time-averaging output power = 0.812 mW (at frequency = 2.402 GHz)

Since the SAR test exclusion thresholds for 2450MHz at test separation distances \leq 5mm = 10mW and the Conducted source-based time-averaging output power is less than 10mW.

Therefore. the SAR evaluation can be exempted.

Date: 2014-12-15

No.: DM117676

Page 84 of 88

Appendix A

List of Measurement Equipment

EQP NO.	DESCRIPTION	MANUFACTURER	MODEL NO.	SERIAL NO.	LAST CAL	DUE CAL
EMD004	LISN	ROHDE & SCHWARZ	ESH3-Z5	100102	2014.03.21	2015.03.21
EMD022	EMI Test Receiver	ROHDE & SCHWARZ	ESCS30	100314	2014.03.21	2015.03.21
EMD035	EMI Test Receiver	ROHDE & SCHWARZ	ESCI	100441	2014.06.10	2015.06.10
EMD036	EMI Test Receiver	ROHDE & SCHWARZ	ESIB 26	100388	2014.06.10	2015.06.10
EMD041	TWO-LINE V-NETWORK	ROHDE & SCHWARZ	ENV216	100261	2014.03.21	2015.03.21
EMD061	Biconilog Antenna	ETS.LINDGREN	3142C	00060439	2014.11.29	2016.11.29
EMD062	Double-Ridged Waveguide (1GHz – 18GHz)	ETS.LINDGREN	3117	00075933	2014.11.15	2015.11.15
EMD084	MULTI-DVICE CONTROLLER	ETS.LINDGREN	2090	00060107	N/A	N/A
EMD088	Video Control Unit	ETS.LINDGREN	Y21953A	2601073	N/A	N/A
EMD093	Monitor	ViewSonic	VA9036	Q8X064201876	N/A	N/A
EMD102	Intelligent Frequency	Ainuo Instrument Co., Ltd	AN97005SS	79707454	N/A	N/A
EMD103	Intelligent Frequency	Ainuo Instrument Co., Ltd	AN97005SS	79707455	N/A	N/A
EMD105	FACT-3 EMC Chamber	ETS.LINDGREN	FACT-3	3803	N/A	N/A
EMD106	Shielding Room #1	ETS.LINDGREN	RFD-100	3802	N/A	N/A
EMD111	Power meter	ROHDE & SCHWARZ	NRVD	102051	2014.03.21	2015.03.21
	100V Insertion Unit	ROHDE & SCHWARZ	URV5-Z4	100464	2014.03.21	2015.03.21
EMD113	Pre-Amplifier	ROHDE & SCHWARZ	N/A	1129588	2014.03.21	2015.03.21
EMD124	Loop Antenna	ETS-Lindgren	6502	00104905	2014.04.28	2016.04.28
EMD131	Standard Gain Horn Antenna (18GHz – 26.5GHz)	Chengdu AINFO Inc.	JXTXLB-42-15-C-KF	J2021100721001	2013.04.09	2015.04.09

Remarks:-

N/A Not Applicable or Not Available

Appendix B

Ancillary Equipment

ITEM NO.	DESCRIPTION	MODEL NO.	FCC ID	REMARK
1	DELL COMPUTER	DMC	N/A	N/A
2	DELL MONITOR	E177FPB	ARSCM356N	RESOLUTION 1024*768 (DURING TESTING) 1.0M UNSHIELDED POWER VORD CONNECTED TO THE COMPUTER 1.5M SHIELDED CABLE CONNECTED TO THE COMPUTER
3	DELL KEYBOARD	SK-8110	N/A	1.8M SHIELDED COILED CABLE CONNECTED TO THE COMPUTER
4	DELL MOUSE	N/A	N/A	2.4M UNSHIELDED CABLE CONNECTED TO THE COMPUTER

Appendix C

Photographs of EUT


Front View of the product




Rear View of the product




Inside View of the product




Inner Circuit Top View



Inner Circuit Bottom View



Inner Circuit Bottom View



Date: 2014-12-15
No.: DM117676

Page 86 of 88

Photographs of EUT

Inner Circuit Top View



Inner Circuit Bottom View




Date: 2014-12-15
No.: DM117676


Page 87 of 88

Photographs of EUT

Measurement of Radiated Emission Test Set Up




Measurement of Radiated Emission Test Set Up



Photographs of EUT

Measurement of Radiated Emission Test Set Up



Measurement of Conducted Emission Test Set Up



******* End of Test Report *******