## **Analysis Report**

The Equipment Under Test (EUT) is a Robot Car.

The EUT is powered by 1 x 3.7V rechargeable battery. After switching on the EUT and being paired with the smart phone via Bluetooth 3.0 protocol, the user can press a sequence of commands via the smart phone app. Each command is either one forward/backward movement, left/right turn, or a pause. When the <Go> button is pressed, the unit will execute all the commands stored in order with a short pause between each command.

Antenna Type: Internal, Integral

Antenna Type: Internal antenna

Antenna Gain: 0dBi

Nominal rated field strength is 95.2 dBµV/m at 3m Maximum allowed production tolerance: +/- 3dB

According to the KDB 447498:

Based on the Maximum allowed field strength of production tolerance was  $98.2 dB\mu V/m$  at 3m in frequency 2.402 GHz, thus;

```
The EIRP = [(FS*D)^2*1000 / 30] = 1.982 \text{mW}
```

Conducted power = Radiated Power (EIRP) – Antenna Gain So;

Conducted Power = 1.982mW.

The SAR Exclusion Threshold Level:

- = 3.0 \* (min. test separation distance, mm) / sqrt(freq. in GHz)
- = 3.0 \* 5 / sqrt (2.480) mW
- = 9.525 mW

Since the above conducted output power is well below the SAR Exclusion threshold level, so the EUT is considered to comply with SAR requirement without testing.