

588 West Jindu Road, Xinqiao, Songjiang, 201612 Shanghai, China

Telephone: +86 (0) 21 6191 5666 Fax: +86 (0) 21 6191 5678

ee.shanghai@sgs.com

Report No.: SHEM160400238702

_

1 Cover Page

FCC MPE REPORT

Application No.:	SHEM1604002387CR			
Applicant:	Hangzhou Hikvision Digital Technology Co., Ltd.			
FCC ID:	2ADTD-CVX0Y			
IC:	20199-CVX0Y			
Equipment Under Tes	t (EUT):			
NOTE: The following sa	ample(s) was/were submitted and identified by the client as			
Product Name:	Internet Camera			
Model No.(EUT):	CS-CV200			
Add Model No.:	CS-CV206, CS-CV208, CS-CV300, CS-CV306, CS-CV308, CS-CV106, CS-CV108			
Standards: FCC Rules 47 CFR §2.1091 KDB447498 D01 General RF Exposure Guidance v05r02 RSS-102 Issue 5				
Date of Receipt:	2016-04-26			
Date of Test:	2016-04-26 to 2016-05-25			
Date of Issue:	2016-05-25			
Test Result:	Pass*			

* In the configuration tested, the EUT complied with the standards specified above.

Parlam Zhan
E&E Section Manager
SGS-CSTC (Shanghai) Co., Ltd.

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government. All test results in this report can be traceable to National or International Standards.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms and conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms.e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only



Report No.: SHEM160400238702

Page: 2 of 8

2 Version

Revision Record					
Version	Chapter	Date	Modifier	Remark	
00	1	2016-05-25	/	Original	

Authorized for issue by:		
Engineer	Eddy Zong	Eddy Zong
	Print Name	
Clerk	Susie Liu	Suite Liu
	Print Name	
Reviewer	Parlam Zhan	Darlam Zhan
	Print Name	



Report No.: SHEM160400238702

Page: 3 of 8

3 Contents

			Page
1	C	COVER PAGE	1
2	V	VERSION	2
3	C	CONTENTS	3
4	(GENERAL INFORMATION	4
	4.1	CLIENT INFORMATION	4
	4.2	GENERAL DESCRIPTION OF E.U.T.	4
	4.3	DETAILS OF E.U.T.	4
	4.4	TEST LOCATION	5
	4.5	TEST FACILITY	5
5	T	TEST STANDARDS AND LIMITS	6
	5.1	FCC RADIOFREQUENCY RADIATION EXPOSURE LIMITS:	6
	5.2	IC RADIOFREQUENCY RADIATION EXPOSURE LIMITS:	6
6	N	MEASUREMENT AND CALCULATION	7
	6.1	MAXIMUM TRANSMIT POWER	7
	6.2	MPE CALCULATION	8
7	E	EUT CONSTRUCTIONAL DETAILS	8



Report No.: SHEM160400238702

Page: 4 of 8

4 General Information

4.1 Client Information

Applicant:	Hangzhou Hikvision Digital Technology Co., Ltd.	
Address of Applicant:	No. 555 Qianmo Road, Binjiang District, Hangzhou 310052, China	
Manufacturer:	Hangzhou Hikvision Digital Technology Co., Ltd.	
Address of Manufacturer:	No. 555 Qianmo Road, Binjiang District, Hangzhou 310052, China	
Factory:	Hangzhou Hikvision Digital Technology Co., Ltd.	
Address of Factory:	No. 700 Dongliu Road, Binjiang District, Hangzhou 310052, Zhejiang, China	

4.2 General Description of E.U.T.

Brand Name	Brand Name:		eZVIZ		
Product Des	Product Description:		Fixed product with WiFi function		
Rated Input:	Rated Input:		DC 5V Via adapter		
Adapter:	Model No.:	ED1-0501	00UA		
	Rated Input:		240V 50/60Hz 0.2A		
	Rated Output:	DC 5.0V 1	.0A		
	Cable length:	AC port:	2 wires		
		DC port:	300 cm		

4.3 Details of E.U.T.

Operation Frequency:	2412MHz-2462MHz
Modulation Type:	802.11 b: DSSS(CCK, DQPSK, DBPSK) 802.11 g/n(HT20): OFDM(64QAM, 16QAM, QPSK, BPSK)
Number of Channel:	11 Channels
Data Rate:	802.11 b: 1/2/5.5/11Mbps 802.11 g: 6/9/12/18/24/36/48/54Mbps 802.11 n(HT20): MCS0-MCS7
Antenna Gain:	2.4 dBi



Report No.: SHEM160400238702

Page: 5 of 8

4.4 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd.

588 West Jindu Road, Xinqiao, Songjiang, 201612 Shanghai, China

Tel: +86 21 6191 5666 Fax: +86 21 6191 5678

4.5 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

CNAS (No. CNAS L0599)

CNAS has accredited SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing. Date of expiry: 2017-07-14.

FCC – Registration No.: 402683

SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. has been registered and fully described in a report filed with the Federal Communications Commission (FCC). The acceptance letter from the FCC is maintained in our files. Registration No.: 402683, Expiry Date: 2017-09-16.

Industry Canada (IC) – IC Assigned Code: 8617A

The 3m Semi-anechoic chamber of SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 8617A-1. Expiry Date: 2017-06-18.

VCCI (Member No.: 3061)

The 3m Semi-anechoic chamber and Shielded Room of SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. has been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-3868, C-4336, T-2221, G-830 respectively. Date of Expiry: 2017-11-16.



Report No.: SHEM160400238702

Page: 6 of 8

5 Test Standards and Limits

5.1 FCC Radiofrequency radiation exposure limits:

According to §1.1310, the limit for general population/uncontrolled exposures

Frequency	Power density(mW/cm²)	Averaging time(minutes)
300MHz~1.5GHz	f/1500	30
1.5GHz~100GHz	1.0	30

5.2 IC Radiofrequency radiation exposure limits:

According to RSS-102 section 2.5.2, RF exposure evaluation is required if the separation distance between the user and/or bystander and the device's radiating element is greater than 20 cm, except when the device operates as follows:

below 20 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 1 W (adjusted for tune-up tolerance);

- at or above 20 MHz and below 48 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than $4.49/f^{0.5}$ W (adjusted for tune-up tolerance), where f is in MHz;
- at or above 48 MHz and below 300 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 0.6 W (adjusted for tune-up tolerance);
- at or above 300 MHz and below 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than $1.31 \times 10^{-2} f^{0.6834}$ W (adjusted for tune-up tolerance), where f is in MHz;
- at or above 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 5 W (adjusted for tune-up tolerance).

For 2.4G device, the limit of worse case is 2.68 W



Report No.: SHEM160400238702

Page: 7 of 8

6 Measurement and Calculation

6.1 Maximum transmit power

The Power Data is based on the RF Test Report SHEM160400238701.

Test mode	Test Frequency (MHz)	Output Power (dBm)	Output Power (mW)
	2412	17.81	60.39
802.11b	2437	18.20	66.07
	2462	18.66	73.45
	2412	17.02	50.35
802.11g	2437	17.69	58.75
	2462	17.80	60.26
	2412	16.66	46.34
802.11 n(HT20)	2437	16.99	50.00
	2462	17.58	57.28



Report No.: SHEM160400238702

Page: 8 of 8

6.2 MPE Calculation

The Max Conducted Peak Output Power is 73.45mW in lowest channel;

The best case gain of the antenna is 2.4dBi. 2.4dB logarithmic terms convert to numeric result is nearly 1.74.

For FCC:

According to the formula S= $\frac{PG}{4R^2\pi}$, we can calculate S which is MPE.

Note

dBm

- 1) P (Watts) = Power Input to antenna = 10^{10} / 1000
- 2) G (Antenna gain in numeric) = 10[^] (Antenna gain in dBi /10)
- 3) R = distance to the center of radiation of antenna (in meter) = 20cm
- 4) MPE limit = 1mW/cm²

$$S = \frac{PG}{4R^2\pi} = \frac{73.45 \times 1.74}{4 \times 400 \times 3.14} = 0.02544 \text{ mW/cm}^2$$

For IC:

MPE limit:0.5423mW/cm²

So the device is exclusion from SAR test.

7 EUT Constructional Details

Refer to the < CS-CV200_External Photos > & < CS-CV200_Internal Photos>.

-- End of the Report--