

588 West Jindu Road, Xinqiao, Songjiang, 201612 Shanghai, China

Telephone: +86 (0) 21 6191 5666 Fax: +86 (0) 21 6191 5678

ee.shanghai@sgs.com

Report No.: SHEM180900813602

Page: 1 of 8

1 Cover Page

RF Exposure Evaluation Report

Application No.:	SHEM1809008136CR		
Applicant:	Hangzhou Hikvision Digital Technology Co., Ltd.		
FCC ID:	2ADTD-H2TP23		
Equipment Under Tes	Equipment Under Test (EUT):		
NOTE: The following sample(s) submitted was/were identified on behalf of the client as			
Product Name:	Handheld thermography camera		
Model No.:	DS-2TP23-10VM/W		
Add Model No.:	Refer to page 2		
Standards:	FCC Rules 47 CFR §2.1093		
	KDB447498 D01 General RF Exposure Guidance v06		
Date of Receipt:	2018-09-13		
Date of Test:	2018-09-21		
Date of Issue:	2018-10-16		
Test Result:	Pass*		

^{*} In the configuration tested, the EUT complied with the standards specified above.



Parlam Zhan E&E Section Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-end-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-end-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.



Report No.: SHEM180900813602

Page: 2 of 8

Model No.:

DS-2TPH36-10VMW, DS-2TPH32-10VMW, DS-2TPH38-10VMW, DS-2TPH38-10VFW, DS-2TPH36-10VFW, DS-2TPH36-10VFW, DS-2TPH38-10VFW, DS-2TPH36-15VMW, DS-2TPH32-15VMW, DS-2TPH38-15VMW, DS-2TPH36-15VFW, DS-2TPH36-15VFW, DS-2TPH36-07VMW, DS-2TPH36-07VMW, DS-2TPH32-07VMW, DS-2TPH38-07VMW, DS-2TPH36-07VFW, DS-2TPH36-07VFW, DS-2TPH32-07VFW, DS-2TPH38-13VMW, DS-2TPH38-13VMW, DS-2TPH38-13VFW, DS-2TPH36-13VFW, DS-2TPH36-13VFW, DS-2TPH38-13VFW, DS-2TPH36-19VMW, DS-2TPH38-19VMW, DS-2TPH38-19VFW, DS-2TPH36-19VFW, DS-2TPH38-19VFW



Report No.: SHEM180900813602

Page: 3 of 8

Revision Record				
Version	Description	Date	Remark	
00	Original	2018-10-16	/	

Authorized for issue by:		
	Vincent Zhu	
	Vincent Zhu /Project Engineer	
	Parlam Zhan	
	Parlam Zhan /Reviewer	



Report No.: SHEM180900813602

Page: 4 of 8

2 Contents

		F	age
1	C	COVER PAGE	1
2	2 CONTENTS		4
3	G	GENERAL INFORMATION	5
	3.1	CLIENT INFORMATION	5
	3.2	GENERAL DESCRIPTION OF E.U.T.	5
	3.3	TEST LOCATION	6
	3.4	TEST FACILITY	6
4	T	EST STANDARDS AND LIMITS	7
	4.1	FCC RADIOFREQUENCY RADIATION EXPOSURE LIMITS:	7
5	N	MEASUREMENT AND CALCULATION	8
	5.1	MAXIMUM TRANSMIT POWER	8
	5.2	MPE CALCULATION	8



Report No.: SHEM180900813602

Page: 5 of 8

3 General Information

3.1 Client Information

Applicant:	Hangzhou Hikvision Digital Technology Co., Ltd.
Address of Applicant:	No. 555 Qianmo Road, Binjiang District, Hangzhou 310052, China
Manufacturer:	Hangzhou Hikvision Digital Technology Co., Ltd.
Address of Manufacturer:	No. 555 Qianmo Road, Binjiang District, Hangzhou 310052, China
Factory:	1.Hangzhou Hikvision Technology Co., Ltd. 2.Hangzhou Hikvision Electronics Co., Ltd.
Address of Factory:	 No.700, Dongliu Road, Binjiang District, Hangzhou City, Zhejiang, 310052, China No.299, Qiushi Road, Tonglu Economic Development Zone, Tonglu County, Hangzhou, Zhejiang,310052, China

3.2 General Description of E.U.T.

Power supply:	Rechargeable Li-ion Battery 3.7V 5Ah 18Wh
Test voltage:	DC 3.6V
Antenna Gain	3.37 dBi
Antenna Type	PCB Antenna
Channel Spacing	5MHz
Modulation Type	802.11b: DSSS (CCK, DQPSK, DBPSK) 802.11g/n: OFDM (64QAM, 16QAM, QPSK, BPSK)
Number of Channels	802.11b/g/n(HT20):11 802.11n(HT40):7
Operation Frequency	802.11b/g/n(HT20): 2412MHz to 2462MHz 802.11n(HT40): 2422MHz to 2452MHz



Report No.: SHEM180900813602

Page: 6 of 8

3.3 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd.

588 West Jindu Road, Xinqiao, Songjiang, 201612 Shanghai, China.

Tel: +86 21 6191 5666 Fax: +86 21 6191 5678

3.4 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

CNAS (No. CNAS L0599)

CNAS has accredited SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

NVLAP (Certificate No. 201034-0)

SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. is accredited by the National Voluntary Laboratory Accreditation Program(NVLAP). Certificate No. 201034-0.

• FCC -Designation Number: CN5033

SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. has been recognized as an accredited testing laboratory.

Designation Number: CN5033. Test Firm Registration Number: 479755.

• Industry Canada (IC) - IC Assigned Code: 8617A

The 3m Semi-anechoic chamber of SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 8617A-1.

• VCCI (Member No.: 3061)

The 3m Semi-anechoic chamber and Shielded Room of SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. has been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-13868, C-14336, T-12221, G-10830 respectively.



Report No.: SHEM180900813602

Page: 7 of 8

4 Test Standards and Limits

4.1 FCC Radiofrequency radiation exposure limits:

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

[(max power of channel)/(min test separation distance)]*[$\sqrt{f(GHz)}$] \leq 3.0 for 1-g SAR and \leq 7.5 for 10-g extremity SAR, where

- f(GHz) is the RF channel transmit frequency in GHz
- · Power and distance are rounded to the nearest mW and mm
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm, and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm according to 4.1 f) is applied to determine SAR test exclusion.

The practical use condition for this device is as a handheld device. So the applicable limit is 10-g extremity SAR

For 2.4G band device, the limit of worse case is $P_{max} \le 7.5 \cdot D_{min} / \sqrt{f} = 7.5 \cdot 5 / \sqrt{2.462} = 23.9 \text{mW}$



Report No.: SHEM180900813602

Page: 8 of 8

5 Measurement and Calculation

5.1 Maximum transmit power

The Power Data is based on the RF Test Report SHEM180900813601

Test Mode	Test Channel	Power [dBm]	Power [mW]
11B	2412	12.77	18.92
11B	2437	12.94	19.68
11B	2462	12.71	18.66
11G	2412	12.83	19.19
11G	2437	12.81	19.10
11G	2462	12.77	18.92
11N20SISO	2412	12.24	16.75
11N20SISO	2437	12.40	17.38
11N20SISO	2462	12.35	17.18
11N40SISO	2422	12.38	17.30
11N40SISO	2437	12.34	17.14
11N40SISO	2452	12.45	17.58

5.2 MPE Calculation

The Max Conducted average Output Power is 19.68mW, So the device is exclusion from SAR test.;

-- End of the Report--