

588 West Jindu Road, Songjiang District, Shanghai, China

+86 (0) 21 6191 5666 Telephone: +86 (0) 21 6191 5678 Fax:

ee.shanghai@sgs.com

Report No.: SHEM151000384204

#### 1 **Cover Page**

### FCC MPE REPORT

Application No.:	SHEM1510003842CR		
Applicant:	Hangzhou Hikvision Digital Technology Co., Ltd.		
FCC ID:	2ADTD-K1E		
<b>Equipment Under T</b>	est (EUT):		
NOTE: The following	sample(s) submitted was/were identified on behalf of the client as		
Product Name:	Fingerprint Access Control Terminal		
Model No.(EUT):	DS-K1T200EF-C		
Add Model No.:  DS-K1T200EF, DS-K1T300EF, DS-K1T300EF-C, DS-K1F100-D8, DS-K1T400EF-C, DS-K1T400EF-C, DS-K1T500EF, DS-K1T500EF-C, DS-K1T600EF, DS-K1T600EF-C, DS-K1TXYZ-X, DS-K1F100-D8E, DS-K1F120-A, DS-K1F180-EM, DS-K1F180-A, DS-K1F810-F, DS-K1F310-F, DS-K1TXYZABCD, DS-K2801, DS-K2802, DS-K2804, DS-K2901, DS-K2902, DS-K2904, DS-K1T901E, DS-K1T902E, DS-K1T903E, DS-K1T904E, DS-K1T905E, DS-K1T906E, DS-K1T907E, DS-K1T908E, DS-K1903E, DS-K1903EK, DS-K1904EK, DS-K1904EK, DS-K1905E, DS-K1906E, DS-K1906EK, DS-K1907E, DS-K1907EK, DS-K1908E, DS-K1909E, DS-K1909EK, DS-K1F100-D8E, DS-K1F100-E, DS-K1F180-EM, DS-K1F180-A, DS-K1F810-F, DS-K1F310-F			
Standards:	FCC Rules 47 CFR §2.1091 KDB447498 D01 General RF Exposure Guidance v05r02		
Date of Receipt:	October 28, 2015		
Date of Test:	December 04, 2015 to December 09, 2015		
Date of Issue:	January 12, 2016		
Test Result:	Pass*		

In the configuration tested, the EUT detailed in this report complied with the standards specified above.

Parlam Zhan E&E Section Manager

SGS-CSTC (Shanghai) Co., Ltd.

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government. All test results in this report can be traceable to National or International Standards.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="https://www.sgs.com/terms">www.sgs.com/terms</a> and conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="https://www.sgs.com/terms">www.sgs.com/terms</a> e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this www.sgs.com/terms e-ocument.ntm. Attention is drawn to the limitation or liability, indemnification and jurisdiction issues defined therein. Any noiser of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only



Report No.: SHEM151000384204

Page: 2 of 8

### 2 Version

Revision Record				
Version	Chapter	Date	Modifier	Remark
00	/	January 12, 2016	/	Original

Authorized for issue by:		
Engineer	Eddy Zong	Eddy Zong
	Print Name	
Clerk	Susie Liu	Suite Liv
	Print Name	
Reviewer	Keny Xu	Keny xu
	Print Name	



Report No.: SHEM151000384204

Page: 3 of 8

#### 3 Contents

		Page
1	COVER PAGE	1
2	VERSION	2
3	CONTENTS	3
4	GENERAL INFORMATION	4
4.1	1 Client Information	4
4.2	2 GENERAL DESCRIPTION OF E.U.T	4
4.3	3 DETAILS OF E.U.T.	4
4.4	4 TEST LOCATION	5
4.5	5 TEST FACILITY	5
5	TEST STANDARDS AND LIMITS	6
6	MEASUREMENT AND CALCULATION	7
6.1	1 Maximum transmit power	7
	2 MPE CALCULATION	
	EUT CONSTRUCTIONAL DETAILS	



Report No.: SHEM151000384204

Page: 4 of 8

#### 4 General Information

#### 4.1 Client Information

Applicant:	Hangzhou Hikvision Digital Technology Co., Ltd.		
Address of Applicant:	No.700 Dongliu Road, Binjiang District, Hangzhou 310052, Zhejiang, China		
Manufacturer:	Hangzhou Hikvision Digital Technology Co., Ltd.		
Address of Manufacturer:	No.700 Dongliu Road, Binjiang District, Hangzhou 310052, Zhejiang, China		
Factory:	Hangzhou Hikvision Digital Technology Co., Ltd.		
Address of Factory:	No.700 Dongliu Road, Binjiang District, Hangzhou 310052, Zhejiang, China		

#### 4.2 General Description of E.U.T.

Product Description:	Fixed product with WiFi function		
Brand Name:	HIKVISION		
Rated Input:	DC 12V 2A		
	Model No.:	KPL-040F	
	Rated Input:	AC 100V-240V 50/60Hz 1.7A	
Adapter:	Rated Output:	DC 12V 3.33A	
	Cable length:	AC port:	140cm (3 wires)
		DC port:	120 cm

#### 4.3 Details of E.U.T.

Operation Frequency:	802.11 b/g/n(HT20): 2412MHz-2462MHz 802.11 n(HT40): 2422MHz-2452MHz
Modulation Type:	802.11 b: DSSS(CCK, DQPSK, DBPSK) 802.11 g/n(HT20/HT40): OFDM(64QAM, 16QAM, QPSK, BPSK)
Number of Channel:	802.11 b/g/n(HT20): 11 Channels 802.11 n(HT40): 7 Channels
Data Rate:	802.11 b: 1/2/5.5/11Mbps 802.11 g: 6/9/12/18/24/36/48/54Mbps 802.11 n(HT20): 13/26/39/52/78/104/117/135Mbps 802.11 n(HT40): 27/54/81/108/162/216/243/270Mbps
Antenna Type:	Integral
Antenna Gain:	2.4 dBi



Report No.: SHEM151000384204

Page: 5 of 8

#### 4.4 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd.

No.588 West Jindu Road, Songjiang District, Shanghai, China.201612.

Tel: +86 21 6191 5666 Fax: +86 21 6191 5678

#### 4.5 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

#### CNAS (No. CNAS L0599)

CNAS has accredited SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing. Date of expiry: 2017-07-14.

#### FCC – Registration No.: 402683

SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. has been registered and fully described in a report filed with the Federal Communications Commission (FCC). The acceptance letter from the FCC is maintained in our files. Registration No.: 402683, Expiry Date: 2017-09-16.

#### Industry Canada (IC) – IC Assigned Code: 8617A

The 3m Semi-anechoic chamber of SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 8617A-1. Expiry Date: 2017-06-18.

#### VCCI (Member No.: 3061)

The 3m Semi-anechoic chamber and Shielded Room of SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. has been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-3868, C-4336, T-2221, G-830 respectively. Date of Expiry: 2017-11-16.



Report No.: SHEM151000384204

Page: 6 of 8

#### 5 Test Standards and Limits

According to §1.1310 Radiofrequency radiation exposure limits:

The limit for general population/uncontrolled exposures

Frequency	Power density(mW/cm²)	Averaging time(minutes)
300MHz~1.5GHz	f/1500	30
1.5GHz~100GHz	1.0	30



Report No.: SHEM151000384204

Page: 7 of 8

#### 6 Measurement and Calculation

#### 6.1 Maximum transmit power

The Power Data is based on the RF Test Report SHEM151000384202

Test mode	Test Frequency (MHz)	Output Power (dBm)	Output Power (mW)
	2412	16.98	49.89
802.11b	2437	17.49	56.10
	2462	18.03	63.53
802.11g	2412	17.00	50.12
	2437	17.50	56.23
	2462	18.03	63.53
	2412	16.78	47.64
802.11 n(HT20)	2437	17.30	53.70
	2462	17.86	61.09
	2422	16.80	47.86
802.11 n(HT40)	2437	17.18	52.24
	2452	17.43	55.34



Report No.: SHEM151000384204

Page: 8 of 8

#### 6.2 MPE Calculation

According to the formula S=  $\frac{PG}{4R^2\pi}$  , we can calculate S which is MPE.

Note:

dBm

- 1) P (Watts) = Power Input to antenna =  $10^{-10}$  / 1000
- 2) G (Antenna gain in numeric) = 10<sup>^</sup> (Antenna gain in dBi /10)
- 3) R = distance to the center of radiation of antenna (in meter) = 20cm
- 4) MPE limit = 1mW/cm<sup>2</sup>

The Max Conducted Peak Output Power is 63.53mW in highest channel;

The best case gain of the antenna is 2.4dBi. 2.4dB logarithmic terms convert to numeric result is nearly 1.74.

$$S = \frac{PG}{4R^2\pi} = \frac{63.53 \times 1.74}{4 \times 400 \times 3.14} = 0.0219 \text{ mW/cm}^2$$

So the device is exclusion from SAR test.

#### 7 EUT Constructional Details

Refer to the < DS-K1T200EF-C External Photos > & < DS-K1T200EF-C Internal Photos>.

-- End of the Report--