

No. 1 Workshop, M-10, Middle section, Science & Technology Park,

Shenzhen, Guangdong, China 518057
Telephone: +86 (0) 755 2601 2053
Fax: +86 (0) 755 2671 0594
Email: ee.shenzhen@sgs.com

Report No.: SZEM170800857402

Page: 1 of 21

1 Cover Page

RF Test Report

Application No.:	SZEM1708008574CR				
Applicant:	Hangzhou Hikvision Digital Technology Co., Ltd				
FCC ID:	2ADTD-K1T803EF				
	Equipment Under Test (EUT): NOTE: The following sample(s) was/were submitted and identified by the client as				
Product Name:	Fingerprint Access Control Terminal				
Model No.(EUT):	DS-K1T803EF				
Add Model No.: DS-K1T803F, DS-K1T803EF-1, DS-K1T803F-1, DS-K1T804F, DS-K1T804E DS-K1T804EF-1, DS-K1T804F-1, DS-K1T804EF-E, DS-K1T804F-E, DS-K1T803XYZ-UVW, DS-K1T804XYZ-UVW					
Standards: FCC PART 15 Subpart C: 2016					
Date of Receipt:	2017-02-13				
Date of Test:	e of Test: 2017-06-27 to 2017-08-08				
Date of Issue:	2017-08-18				
Test Result:	Pass*				

^{*}In the configuration tested, the EUT detailed in this report complied with the standards specified above.

Jack Zhang EMC Laboratory Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government. All test results in this report can be traceable to National or International Standards.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sqs.com/terms and conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sqs.com/terms-e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only



Report No.: SZEM170800857402

Page: 2 of 21

Revision Record						
Version Chapter Date Modifier Remark						
00	/	2017-08-18	/	Original		

Authorized for issue by:		
Engineer	Vincent Zhu Vincent Zhu /Project Engineer	2017-08-10 Date
Reviewer	Parlam Zhan /Reviewer	2017-08-10 Date



Report No.: SZEM170800857402

Page: 3 of 21

2 Test Summary

Test Item	Test Requirement	Test Method	Result
Antenna Requirement 47 CFR Part 15, Subpart C Section 15.203		/	PASS
AC Power Line Conducted Emission	47 CFR Part 15, Subpart C Section 15.207	ANSI C63.10 (2013) Section 6.2	PASS
Radiated Emissions	47 CFR Part 15, Subpart C Section 15.209	ANSI C63.10 (2013) Section 6.4	PASS
20dB Bandwidth	47 CFR Part 15, Subpart C Section 15.215	ANSI C63.10 (2013) Section 6.8	PASS



Report No.: SZEM170800857402

Page: 4 of 21

3 Contents

2 TEST SUMMARY	1	•	COVER PAGE	Page
3 CONTENTS				
4 GENERAL INFORMATION. 4.1 CLIENT INFORMATION. 4.2 GENERAL DESCRIPTION OF E.U.T. 4.3 TECHNICAL SPECIFICATIONS. 4.4 SUPPORT UNITS / ASSOCIATED EQUIPMENTS. 4.5 E.U.T OPERATION MODE. 4.6 TEST LOCATION. 4.7 TEST FACILITY. 4.8 MEASUREMENT UNCERTAINTY. 5 EQUIPMENTS LIST. 6 TEST RESULTS AND MEASUREMENT DATA 6.1 ANTENNA REQUIREMENT. 6.2 CONDUCTED EMISSIONS. 6.3 RADIATED EMISSIONS. 6.4 20DB BANDWIDTH. 7 TEST SETUP PHOTOGRAPHS.				
4.1 CLIENT INFORMATION. 4.2 GENERAL DESCRIPTION OF E.U.T. 4.3 TECHNICAL SPECIFICATIONS 4.4 SUPPORT UNITS / ASSOCIATED EQUIPMENTS 4.5 E.U.T OPERATION MODE. 4.6 TEST LOCATION. 4.7 TEST FACILITY. 4.8 MEASUREMENT UNCERTAINTY. 5 EQUIPMENTS LIST. 6 TEST RESULTS AND MEASUREMENT DATA 6.1 ANTENNA REQUIREMENT. 6.2 CONDUCTED EMISSIONS. 6.3 RADIATED EMISSIONS. 6.4 20DB BANDWIDTH. 7 TEST SETUP PHOTOGRAPHS.	3			
4.2 GENERAL DESCRIPTION OF E.U.T. 4.3 TECHNICAL SPECIFICATIONS. 4.4 SUPPORT UNITS / ASSOCIATED EQUIPMENTS. 4.5 E.U.T OPERATION MODE. 4.6 TEST LOCATION. 4.7 TEST FACILITY. 4.8 MEASUREMENT UNCERTAINTY. 5 EQUIPMENTS LIST. 6 TEST RESULTS AND MEASUREMENT DATA 6.1 ANTENNA REQUIREMENT. 6.2 CONDUCTED EMISSIONS. 6.3 RADIATED EMISSIONS. 6.4 20DB BANDWIDTH. 7 TEST SETUP PHOTOGRAPHS.	4	G	GENERAL INFORMATION	
4.2 GENERAL DESCRIPTION OF E.U.T. 4.3 TECHNICAL SPECIFICATIONS. 4.4 SUPPORT UNITS / ASSOCIATED EQUIPMENTS. 4.5 E.U.T OPERATION MODE. 4.6 TEST LOCATION. 4.7 TEST FACILITY. 4.8 MEASUREMENT UNCERTAINTY. 5 EQUIPMENTS LIST. 6 TEST RESULTS AND MEASUREMENT DATA 6.1 ANTENNA REQUIREMENT. 6.2 CONDUCTED EMISSIONS. 6.3 RADIATED EMISSIONS. 6.4 20DB BANDWIDTH. 7 TEST SETUP PHOTOGRAPHS.		4.1	CLIENT INFORMATION	
4.4 SUPPORT UNITS / ASSOCIATED EQUIPMENTS 4.5 E.U.T OPERATION MODE		4.2		
4.5 E.U.T OPERATION MODE 4.6 TEST LOCATION 4.7 TEST FACILITY 4.8 MEASUREMENT UNCERTAINTY 5 EQUIPMENTS LIST 6 TEST RESULTS AND MEASUREMENT DATA 6.1 ANTENNA REQUIREMENT 6.2 CONDUCTED EMISSIONS 6.3 RADIATED EMISSIONS 6.4 20DB BANDWIDTH 7 TEST SETUP PHOTOGRAPHS		4.3	TECHNICAL SPECIFICATIONS	5
4.6 TEST LOCATION 4.7 TEST FACILITY 4.8 MEASUREMENT UNCERTAINTY 5 EQUIPMENTS LIST 6 TEST RESULTS AND MEASUREMENT DATA 6.1 ANTENNA REQUIREMENT 6.2 CONDUCTED EMISSIONS 6.3 RADIATED EMISSIONS 6.4 20DB BANDWIDTH 7 TEST SETUP PHOTOGRAPHS		4.4		
4.7 TEST FACILITY 4.8 MEASUREMENT UNCERTAINTY 5 EQUIPMENTS LIST 6 TEST RESULTS AND MEASUREMENT DATA 6.1 ANTENNA REQUIREMENT 6.2 CONDUCTED EMISSIONS 6.3 RADIATED EMISSIONS 6.4 20DB BANDWIDTH 7 TEST SETUP PHOTOGRAPHS		4.5		
4.8 MEASUREMENT UNCERTAINTY 5 EQUIPMENTS LIST				
5 EQUIPMENTS LIST				
6.1 Antenna Requirement		4.8	MEASUREMENT UNCERTAINTY	
6.1 Antenna Requirement	5	F	EQUIPMENTS LIST	8
6.2 CONDUCTED EMISSIONS	6	T	TEST RESULTS AND MEASUREMENT DATA	
6.2 CONDUCTED EMISSIONS		6.1	Antenna Requirement	
6.3 RADIATED EMISSIONS 6.4 20DB BANDWIDTH 7 TEST SETUP PHOTOGRAPHS		6.2		
6.4 20DB BANDWIDTH TEST SETUP PHOTOGRAPHS		6.3		
			20dB Bandwidth	19
O FUT CONCEDUCTIONAL DETAILS	7	T	TEST SETUP PHOTOGRAPHS	21
	8	E	EUT CONSTRUCTIONAL DETAILS	21



Report No.: SZEM170800857402

Page: 5 of 21

4 General Information

4.1 Client Information

Applicant: Hangzhou Hikvision Digital Technology Co., Ltd.

Address of Applicant: No. 555 Qianmo Road, Binjiang District, Hangzhou 310052, China

Manufacturer: Hangzhou Hikvision Digital Technology Co., Ltd.

Address of Manufacturer: No. 555 Qianmo Road, Binjiang District, Hangzhou 310052, China

Factory:

1. Hangzhou Hikvision Technology Co., Ltd.

2. Hangzhou Hikvision Electronics Co., Ltd.

1. No.700, Dongliu Road, Binjiang District, Hangzhou Ctiy, Zhejiang,

Address of Factory: 310052, China

2. No.299, Qiushi Road, Tonglu Economic Development Zone, Tonglu

County, Hangzhou, Zhejiang, 310052, China.

4.2 General Description of E.U.T.

Product Description: Fixed product with 125KHz RFID

4.3 Technical Specifications

Test Voltage: AC 120V 60Hz for adapter

Operation Frequency: 125KHz Modulation Type: ASK

Antenna Type: Integral Loop Antenna

4.4 Support Units / Associated Equipments

Description	Manufacturer	Model No.	Supplied by
Adapter	DVE	DSA-12G-12FEU	Client

	Rated Input:	AC 100~240V, 50/60Hz	
	Rated Output:	DC 12V 1.0A	
Adapter:	Cable length:	AC port:	2 wires
		DC port:	150 cm

4.5 E.U.T Operation Mode

Test Mode	Description of Test Mode
Engineering Mode	Keep EUT working in continuous transmitting mode.



Report No.: SZEM170800857402

Page: 6 of 21

4.6 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch

No. 1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, Guangdong, China. 518057

Tel: +86 755 2601 2053 Fax: +86 755 2671 0594

No tests were sub-contracted.

4.7 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

· CNAS (No. CNAS L2929)

CNAS has accredited SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

A2LA (Certificate No. 3816.01)

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 3816.01.

· VCCI

The 10m Semi-anechoic chamber and Shielded Room of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-823, R-4188, T-1153 and C-2383 respectively.

• FCC –Designation Number: CN1178

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized as an accredited testing laboratory.

Designation Number: CN1178. Test Firm Registration Number: 406779.

Industry Canada (IC)

Two 3m Semi-anechoic chambers and the 10m Semi-anechoic chamber of SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab have been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 4620C-1, 4620C-2, 4620C-3.



Report No.: SZEM170800857402

Page: 7 of 21

4.8 Measurement Uncertainty

No.	Parameter	Measurement Uncertainty
1	Radio Frequency	< ±1 x 10 ⁻⁵
2	Total RF power, conducted	< ±1.5 dB
3	RF power density, conducted	< ±3 dB
4	Spurious emissions, conducted	< ±3 dB
5	All emissions, radiated	< ±6 dB (Below 1GHz) < ±6 dB (Above 1GHz)
6	Temperature	< ±1°C
7	Humidity	< ±5 %
8	DC and low frequency voltages	< ±3 %



Report No.: SZEM170800857402

Page: 8 of 21

5 Equipments List

Item	Test Equipment	Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Due date
1	Spectrum Analyzer	R&S	FSP-30	2705121009	2017-01-14	2018-01-13
2	Spectrum Analyzer	Agilent	N9020A	MY51240197	2017-07-03	2018-07-02
3	Power meter	R&S	NRP	101641	2017-01-14	2018-01-13
4	Power Sensor	R&S	NRP-Z22	101096	2017-08-06	2018-08-05
5	Signal Generator	R&S	SMR40	100555	2017-07-03	2018-07-02
6	Signal Generator	Agilent	N5182A	MY50143776	2017-07-03	2018-07-02
7	Communication Tester	R&S	CMW500	1201.0002K75	2016-12-24	2017-12-23
8	Switcher	Tonscend	JS0806	JS0806-2	/	/
9	Splitter	Anritsu	MA1612A	M12265	/	/
10	Coupler	e-meca	803-S-1	900-M01	/	/
11	High-low Temperature Cabinet	Suzhou Zhihe	TL-40	50110050	2016-09-11	2017-09-10
12	AC Power Stabilizer	WOCEN	6100	51122	2017-01-14	2018-01-13
13	DC Power Supply	QJE	QJ30003SII	3573/4/3	2017-01-14	2018-01-13
14	EMI Test Receiver	R&S	ESU40	100109	2017-02-13	2018-01-15
15	Active Loop Antenna (9kHz to 30MHz)	R&S	FMZB1519	1519-034	2017-02-13	2018-01-15
16	Broadband Antenna (25MHz to 2GHz)	Schwarzbeck	VULB9168	9168-313	2017-02-13	2018-01-15
17	Broadband Antenna (25MHz to 3GHz)	R&S	HL562	100227	2016-08-30	2017-08-29
18	Horn Antenna (1 -18GHz)	R&S	HF906	100284	2017-02-13	2018-01-15
19	Horn Antenna (1 - 18GHz)	Schwarzbeck	BBHA9120D	9120D-679	2017-02-13	2018-01-15
20	Horn Antenna (14 - 40GHz)	Schwarzbeck	BBHA 9170	BBHA917-0373	2017-02-13	2018-01-15
21	Pre-amplifier (9KHz – 2GHz)	LNA6900	TESEQ	71033	2017-02-13	2018-01-15
22	Pre-amplifier (1 – 26.5GHz)	Schwarzbeck	SCU-F0118-G40- BZ4-CSS(F)	10001	2017-01-14	2018-01-13
23	Pre-amplifier (14 – 40GHz)	Schwarzbeck	SCU-F1840-G35- BZ3-CSS(F)	10001	2017-01-14	2018-01-13
24	Tunable Notch Filter	Wainwright	WRCT800.0/880.0- 0.2/40-5SSK	170397 169777 169780 192507	/	/
25	High pass Filter	FSCW	HP 12/2800-5AA2	19A45-02	/	/
26	EMI test receiver	Rohde & Schwarz	ESR7	101391	2016-12-29	2017-12-28
27	Line impedance stabilization network	SCHWARZBECK	NSLK8127	8127490	2017-01-14	2018-01-13
28	Line impedance stabilization network	EMCO	3816/2	00034161	2017-01-14	2018-01-13



Report No.: SZEM170800857402

Page: 9 of 21

6 Test results and Measurement Data

6.1 Antenna Requirement

Standard requirement: 47 CFR Part 15C Section 15.203

15.203 Requirement: An intentional radiator shall be designed to ensure that no antenna other


than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a

standard antenna jack or electrical connector is prohibited.

EUT Antenna:

The antenna is integrated loop antenna and no consideration of replacement.

Antenna Configuration:





Report No.: SZEM170800857402

Page: 10 of 21

6.2 Conducted Emissions

Frequency Range: 150 KHz to 30 MHz

Class/Severity: Class B

Limit:

Frequency range	Class B Limits: dB (μV)		
MHz	Quasi-peak	Average	
0.15 to 0.50	66 to 56	56 to 46	
0.50 to 5	56	46	
5 to 30	60	50	

Note1: The limit decreases linearly with the logarithm of the frequency in the range


0.15 MHz to 0.50MHz.

Note2: The lower limit is applicable at the transition frequency.

Test site/setup:

Test instrumentation set-up:

Frequency Range	Detector	RBW	VBW
9KHz to 150Hz	Quasi-peak	200Hz	500Hz
150KHz to 30MHz	Quasi-peak	9kHz	30kHz



Test Procedure:

- 1. The mains terminal disturbance voltage was measured with the EUT in a shielded room.
- 2. The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides $50\Omega/50\mu H + 5\Omega$ linear impedance. The power cables of all other units of the EUT were connected to a second LISN, which was bonded to the ground reference plane in the same way as the LISN for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded
- 3. The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference



Report No.: SZEM170800857402

Page: 11 of 21

plane, but separated from metallic contact with the ground reference plane by 0.1m of insulation.

4. The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISN mounted on top of the ground reference plane. This distance was between the closest points of the LISN and the EUT. The mains lead of EUT excess 0.8m was folded back and forth parallel to the lead so as to form a horizontal bundle with a length between 0.3m and 0.4m. All other units of the EUT and associated equipment were at least 0.8 m from the LISN.

Remark: Pre-scan was performed with peak detected on all ports, Quasi-peak & average measurements were performed at the frequencies at which maximum peak emission level were detected. Please see the attached Quasi-peak and Average test results.

Test Result: Pass




Report No.: SZEM170800857402

Page: 12 of 21

Test data:

Live Line:




Item	Freq.	Read Level	LISN Factor	Cable Loss	Level	Limit Line	Over Limit	Detector
(Mark)	(MHz)	(dBµV)	(dB)	(dB)	(dBµV)	(dBµV)	(dB)	
1	0.152	19.77	0.11	9.81	29.69	55.87	-26.18	Average
2	0.152	33.37	0.11	9.81	43.29	65.87	-22.58	QP
3	0.170	21.08	0.11	9.81	31.00	54.94	-23.94	Average
4	0.170	33.61	0.11	9.81	43.53	64.94	-21.41	QP
5	0.222	17.20	0.11	9.81	27.12	52.74	-25.62	Average
6	0.222	27.74	0.11	9.81	37.66	62.74	-25.08	QP
7	0.249	16.41	0.11	9.81	26.33	51.78	-25.45	Average
8	0.249	27.25	0.11	9.81	37.17	61.78	-24.61	QP
9	4.549	17.28	0.11	9.86	27.25	46.00	-18.75	Average
10	4.549	27.96	0.11	9.86	37.93	56.00	-18.07	QP
11	5.031	17.81	0.11	9.86	27.78	50.00	-22.22	Average
12	5.031	28.37	0.11	9.86	38.34	60.00	-21.66	QP



Report No.: SZEM170800857402

Page: 13 of 21

Neutral Line:



Item	Freq.	Read Level	LISN Factor	Cable Loss	Level	Limit Line	Over Limit	Detector
(Mark	(MHz)	(dBµV)	(dB)	(dB)	(dBµV)	(dBµV)	(dB)	
1	0.152	17.20	0.12	9.81	27.13	55.87	-28.74	Average
2	0.152	33.00	0.12	9.81	42.93	65.87	-22.94	QP
3	0.204	18.21	0.12	9.81	28.14	53.45	-25.31	Average
4	0.204	28.17	0.12	9.81	38.10	63.45	-25.35	QP
5	0.229	18.03	0.11	9.81	27.95	52.48	-24.53	Average
6	0.229	27.05	0.11	9.81	36.97	62.48	-25.51	QP
7	0.502	5.61	0.11	9.82	15.54	46.00	-30.46	Average
8	0.502	15.61	0.11	9.82	25.54	56.00	-30.46	QP
9	4.224	12.05	0.13	9.85	22.03	46.00	-23.97	Average
10	4.224	23.41	0.13	9.85	33.39	56.00	-22.61	QP
11	5.362	12.65	0.13	9.86	22.64	50.00	-27.36	Average
12	5.362	24.20	0.13	9.86	34.19	60.00	-25.81	QP

Notes

- 1. The following Quasi-Peak and Average measurements were performed on the EUT:
- 2. Final Test Level = Receiver Reading + LISN Factor + Cable Loss.



Report No.: SZEM170800857402

Page: 14 of 21

6.3 Radiated Emissions

Test frequency range: 9KHz – 1GHz

Test Site: Measurement Distance: 3m

Receiver Setup:

Frequency (MHz) RBW		VBW	Detector
0.009-0.015 200Hz		1KHz	Quasi-peak
0.015-30 9kHz		30KHz	Quasi-peak
30-1000 120 kHz		300KHz	Quasi-peak

Note: The emission limits shown in the above table are based on measurement instrumentation employing a CISPR quasi-peak detector. For the frequency bands 9~90 kHz, 110~490 kHz and above 1000 MHz, the radiated emission limits are based on measurements employing an average detector.

Frequency (MHz) Field strength (µV/m)		Measurement distance (m)	Limit @3m (dBµV/m)
0.009-0.490	2400/F(kHz)	300	128.5 ~ 93.8
0.490-1.705	24000/F(kHz)	30	73.8 ~63.0
1.705-30	30	30	69.5
30-88	100	3	40.0
88-216	150	3	43.5
216-960	216-960 200		46.0
960-1000 500		3	54.0

NOTE:

(1) For test distance other than what is specified, but fulfilling the requirements of section 15.31(f) (2) the field strength is calculated by adding additionally an extrapolation factor of 40dB/decade (inverse linear distance for field strength measurements). So the Distance Extrapolation Factor in dB is 40*log (D_{TEST} / D_{SPEC}) where D_{TEST} = Test Distance and D_{SPEC} = Specified Distance. Field strength limit (dBµV/m)@test distance= Field strength limit (dBµV/m)@specified distance -Distance Extrapolation Factor

(2) The lower limit shall apply at the transition frequencies.

Limit: (Fundamental signal)

Test Procedure:

Frequency	Limit (dBuV/m @3m)	Remark
13.56MHz	124	Quasi-peak Value

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic camber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms and conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms.e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



Report No.: SZEM170800857402

Page: 15 of 21

the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.

- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- g. The radiation measurements are performed in X, Y, Z axis positioning. And found the X axis positioning which it is worse case, only the test worst case mode is recorded in the report.

Test Setup:




Figure 1. Below 30MHz




Figure 2. 30MHz to 1GHz

Test Results: Pass




Report No.: SZEM170800857402

Page: 16 of 21

Measurement Data

9kHz - 30MHz:

Z:



Item	Freq.	Read	Antenna	Cable	Result	Limit	Over	Detect
		Level	Factor	Loss	Level	Line	Limit	or
(Mark)	(MHz)	(dBμV)	(dBμA/μVm)	(dB)	(dBμV/ m)	(dBμV/ m)	(dB)	
1	0.12	41.25	19.90	0.05	61.20	105.83	-44.63	QP
2	0.30	19.56	19.80	0.06	39.42	98.01	-58.59	QP
3	0.57	18.00	19.70	0.07	37.77	72.45	-34.68	QP
4	1.46	13.94	19.35	0.08	33.37	64.37	-31.00	QP
5	6.12	11.53	19.60	0.09	31.22	69.50	-38.28	QP
6	14.69	9.95	19.22	0.13	29.30	69.50	-40.20	QP
7	20.33	10.53	19.04	0.15	29.72	69.50	-39.78	QP




Report No.: SZEM170800857402

Page: 17 of 21

30MHz-1GHz:

Vertical




Item	Freq.	Read	Antenna	Preamp	Cable	Result	Limit	Over	Detector
цеш	1 164.	Level	Factor	Factor	Loss	Level	Line	Limit	Detector
(Mark)	(MHz)	(dBµV)	(dB/m)	(dB)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	
1	43.20	59.81	14.34	42.68	0.23	31.70	40.00	-8.30	QP
2	55.03	63.60	11.64	42.68	0.28	32.84	40.00	-7.16	QP
3	216.02	59.70	10.12	42.47	0.72	28.07	46.00	-17.93	QP
4	408.95	57.43	15.30	42.06	1.01	31.68	46.00	-14.32	QP
5	605.66	54.12	19.45	42.19	1.38	32.76	46.00	-13.24	QP
6	654.23	55.38	19.85	42.22	1.55	34.56	46.00	-11.44	QP



Report No.: SZEM170800857402

Page: 18 of 21

Horizontal



Item	Freq.	Read	Antenna	Preamp	Cable	Result	Limit	Over	Detector
пеш	rieq.	Level	Factor	Factor	Loss	Level	Line	Limit	Detector
(Mark)	(MHz)	(dBµV)	(dB/m)	(dB)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	
1	55.61	52.08	11.75	42.69	0.28	21.42	40.00	-18.58	QP
2	383.93	62.71	14.82	42.13	0.97	36.37	46.00	-9.63	QP
3	408.95	68.36	15.30	42.06	1.01	42.61	46.00	-3.39	QP
4	432.55	65.22	15.83	42.03	1.06	40.08	46.00	-5.92	QP
5	455.91	59.54	16.33	42.09	1.10	34.88	46.00	-11.12	QP
6	766.06	46.11	21.36	42.62	1.91	26.76	46.00	-19.24	QP

Remark:

- 1) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:
- 2) Final Test Level = Receiver Reading + Antenna Factor + Cable Factor Preamplifier Factor




Report No.: SZEM170800857402

Page: 19 of 21

6.4 20dB Bandwidth

Test Setup:



Ground Reference Plane

Requirements:

Intentional radiators operating under the alternative provisions to the general emission limits, as contained in §15.217 through §15.257 and in subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission is contained within the frequency band designated in the rule section under which the equipment is operated. The requirement to contain the 20 dB bandwidth of the emission within the specified frequency band includes the effects from frequency sweeping, frequency hopping and other modulation techniques that may be employed as well as the frequency stability of the transmitter over expected variations in temperature and supply voltage. If frequency stability is not specified in the regulations, it is recommended that the fundamental emission be kept within at least the central 80% of the permitted band in order to minimize the possibility of out-of-band operation.

Test Data:


20dB bandwidth (Hz)	Result
389.205	Pass

Test plot as follows:



Report No.: SZEM170800857402

Page: 20 of 21





Report No.: SZEM170800857402

Page: 21 of 21

7 Test Setup Photographs

Refer to the < Test Setup Photos-FCC >

8 EUT Constructional Details

Refer to the < External Photos> & < Internal Photos>.

-- End of the Report--