

588 West Jindu Road, Xinqiao, Songjiang, 201612 Shanghai, China

Telephone: +86 (0) 21 6191 5666 Fax: +86 (0) 21 6191 5678

ee.shanghai@sgs.com

Report No.: SHEM170400212003

1 Cover Page

FCC MPE REPORT

Application No.: SHEM1704002120CR					
Applicant:	Hangzhou Hikvision Digital Technology Co., Ltd.				
FCC ID:	2ADTD-T03C2N00				
Equipment Under Tes	t (EUT):				
NOTE: The following sa	ample(s) was/were submitted and identified by the client as				
Product Name:	Wireless Transmitter & Receiver				
Model No.(EUT): DS-3WF01C-2N					
Standards:	FCC Rules 47 CFR §2.1091				
	KDB447498 D01 General RF Exposure Guidance v06				
Date of Receipt: 2017-04-14					
Date of Test: 2017-04-14 to 2017-05-05					
Date of Issue: 2017-06-18					
Test Result:	Pass*				

^{*} In the configuration tested, the EUT detailed in this report complied with the standards specified above.



The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_edocument.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction. documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to thesample(s) tested and such sample(s) are retained for 90 days only



Report No.: SHEM170400212003

Page: 2 of 8

2 Version

Revision Record						
Version	Chapter	Date	Modifier	Remark		
00	/	2017-06-18	1	Original		

Authorized for issue by:		
Engineer	Eddy Zong Print Name	Eddy Zong
Clerk	Vincent Zhu	Vincent Zhu
	Print Name	
Reviewer	Parlam Zhan	Parlam Zhan
	Print Name	



Report No.: SHEM170400212003

Page: 3 of 8

3 Contents

	P	age
C	OVER PAGE	1
V	ERSION	2
C	CONTENTS	3
G	ENERAL INFORMATION	4
4.1	CLIENT INFORMATION	4
4.1	GENERAL DESCRIPTION OF E.U.T.	4
4.2	TECHNICAL SPECIFICATIONS	4
4.3	TEST LOCATION	5
4.4	TEST FACILITY	5
T	EST STANDARDS AND LIMITS	6
5.1	FCC RADIOFREQUENCY RADIATION EXPOSURE LIMITS:	6
M	IEASUREMENT AND CALCULATION	7
6.1	MAXIMUM TRANSMIT POWER	7
6.2	MPE CALCULATION	8
E	UT CONSTRUCTIONAL DETAILS	8
	V G G 4.1 4.2 4.3 4.4 T 5.1 M 6.1 6.2	COVER PAGE



Report No.: SHEM170400212003

Page: 4 of 8

4 General Information

4.1 Client Information

Applicant:	Hangzhou Hikvision Digital Technology Co., Ltd.		
Address of Applicant:	No. 555 Qianmo Road, Binjiang District, Hangzhou 310052, China		
Manufacturer:	Hangzhou Hikvision Digital Technology Co., Ltd.		
Address of Manufacturer:	No. 555 Qianmo Road, Binjiang District, Hangzhou 310052, China		
Factory:	1. Hangzhou Hikvision Technology Co., Ltd.		
	2. Hangzhou Hikvision Electronics Co., Ltd.		
Address of Factory:	1. No.700, Dongliu Road, Binjiang District, Hangzhou Ctiy,Zhejiang, 310052, China		
	2. No.299, Qiushi Road,Tonglu Economic Development Zone,Tonglu County, Hangzhou,Zhejiang,310052,China.		

4.1 General Description of E.U.T.

Product Description:	Fixed product with WiFi function					
Power Supply:	DC 12V 1A	DC 12V 1A				
Test Voltage:	AC 120V 60Hz for a	AC 120V 60Hz for adapter				
	Manufacturer:	DVE				
	Model No.:	DSA-12G-12FEU				
	Rated Input:	AC 100~240	AC 100~240V, 50/60Hz 0.3A			
Adapter:	Rated Output:	DC 12V 1.0A	A			
	Cable length:	AC port:	2 wires			
	Cable length.	DC port:	150 cm			

4.2 Technical Specifications

-	
Operation Frequency:	802.11 b/g/n(HT20): 2412MHz~2462MHz 802.11 n(HT40): 2422MHz~2452MHz
Modulation Technique:	802.11 b: DSSS(CCK, DQPSK, DBPSK) 802.11 g/n(HT20/n(HT40): OFDM(64QAM, 16QAM, QPSK, BPSK)
Data Rate:	802.11b: 1/2/5.5/11Mbps, 802.11g: 6/9/12/18/24/36/48/54Mbps 802.11n: MCS0-15 up to 300Mbps (2T X 2R MIMO)
Number of Channel:	802.11 b/g/n(HT20): 11 802.11 n(HT40): 7
Antenna Type:	Antenna A:Integral antenna Antenna B:Integral antenna
Antenna Gain:	Antenna A: 6 dBi Antenna B: 6 dBi



Report No.: SHEM170400212003

Page: 5 of 8

4.3 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd.

588 West Jindu Road, Xingiao, Songjiang, 201612 Shanghai, China

Tel: +86 21 6191 5666 Fax: +86 21 6191 5678

4.4 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

CNAS (No. CNAS L0599)

CNAS has accredited SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

FCC – Registration No.: 402683

SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. has been registered and fully described in a report filed with the Federal Communications Commission (FCC). The acceptance letter from the FCC is maintained in our files. Registration No.: 402683.

Industry Canada (IC) – IC Assigned Code: 8617A

The 3m Semi-anechoic chamber of SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 8617A-1.

VCCI (Member No.: 3061)

The 3m Semi-anechoic chamber and Shielded Room of SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. has been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-3868, C-4336, T-2221, G-830 respectively.



Report No.: SHEM170400212003

Page: 6 of 8

5 Test Standards and Limits

5.1 FCC Radiofrequency radiation exposure limits:

According to §1.1310, the limit for general population/uncontrolled exposures

Frequency	Power density(mW/cm ²)	Averaging time(minutes)	
300MHz~1.5GHz	f/1500	30	
1.5GHz~100GHz	1.0	30	



Report No.: SHEM170400212003

Page: 7 of 8

6 Measurement and Calculation

6.1 Maximum transmit power

The Power Data is based on the RF Test Report SHEM170400212002.

Test Mode	Channel	Antenna A Power[dBm]	Antenna B Power[dBm]	MIMO Power[dBm]	Antenna A Power[mW]	Antenna B Power[mW]	MIMO Power[mW]
11B	2412	17.86	16.82	N/A	61.09	48.08	N/A
11B	2437	17.58	16.28	N/A	57.28	42.46	N/A
11B	2462	16.19	16.21	N/A	41.59	41.78	N/A
11G	2412	19.15	17.89	N/A	82.22	61.52	N/A
11G	2437	18.98	17.76	N/A	79.07	59.70	N/A
11G	2462	17.71	17.56	N/A	59.02	57.02	N/A
11N20SISO	2412	18.91	17.65	N/A	77.80	58.21	N/A
11N20SISO	2437	18.76	17.37	N/A	75.16	54.58	N/A
11N20SISO	2462	17.48	17.27	N/A	55.98	53.33	N/A
11N40SISO	2422	19.26	15.74	N/A	84.33	37.50	N/A
11N40SISO	2437	17.65	15.88	N/A	58.21	38.73	N/A
11N40SISO	2452	16.7	15.9	N/A	46.77	38.90	N/A
11N20MIMO	2412	17.28	16.43	19.89	53.46	43.95	97.41
11N20MIMO	2437	17.01	15.72	19.42	50.23	37.33	87.56
11N20MIMO	2462	15.62	15.46	18.55	36.48	35.16	71.63
11N40MIMO	2422	17.85	15.95	20.01	60.95	39.36	100.31
11N40MIMO	2437	17.31	15.85	19.65	53.83	38.46	92.29
11N40MIMO	2452	16.29	15.9	19.11	42.56	38.90	81.46



Report No.: SHEM170400212003

Page: 8 of 8

6.2 MPE Calculation

The Max Conducted Peak Output Power is 20.01dBm (100.31mW) in lowest channel;

The best case gain of the antenna is 6dBi. 6dB logarithmic terms convert to numeric result is nearly 3.98, in MIMO mode is nearly 7.96

For FCC:

According to the formula S= $\frac{PG}{4R^2\pi}$, we can calculate S which is MPE.

Note

dBm

- 1) P (Watts) = Power Input to antenna = 10^{10} / 1000
- 2) G (Antenna gain in numeric) = 10[^] (Antenna gain in dBi /10)
- 3) R = distance to the center of radiation of antenna (in meter) = 20cm
- 4) MPE limit = 1mW/cm²

$$S = \frac{PG}{4R^2\pi} = \frac{100.31 \times 7.96}{4 \times 400 \times 3.14} = 0.159 \text{ mW/cm}^2$$

So the device is exclusion from SAR test.

7 EUT Constructional Details

Refer to the < DS-3WF01C-2N _External Photos > & < DS-3WF01C-2N _Internal Photos >.

-- End of the Report--