

Regarding Requirements of Paragraph 15.212(a)(1)**Shielding 15.212(a)(1)(i)**

The oscillator/transmitter circuitry is housed under a metal shield soldered to the circuit board.

Buffered Modulation/Data Input 15.212(a)(1)(ii)

All signals are buffered as required.

Power Regulation 15.212(a)(1)(iii)

The RF components are powered by regulated 2.85 and 3.3 V sources taking power from a 3.6 to 6.0 V battery.

Antenna Construction 15.212(a)(1)(iv)

The antenna ports use U.FL style connectors. Antenna(s) supplied for use with this module are listed in the user's manual.

Test Configuration 15.212(a)(1)(v)

The device was tested stand-alone with no external shielding. All power is self-contained.

Labeling 15.212(a)(1)(vi)

The module is labeled with the FCC ID using a permanently applied label as depicted in other supporting documentation. The user manual contains instructions for external labeling when the module is enclosed in a final configuration.

Applicable Requirements on Final Configuration 15.212(a)(1)(vii)

The user manual includes instructions that explain the requirements of marking and the instructions that need to be conveyed to the final configuration.

Compliance to RF Exposure Requirements in Final Configuration 15.212(a)(1)(viii)

The user manual includes instructions on the warnings required for the final configuration.
