

FCC RADIO TEST REPORT-BT FCC ID:2ADWUP4006A

Product: Smart phone

Trade Mark: Turbo D4

Model No.: P4006A

Serial Model: N/A

Report No.: NTEK-2017NT05113227F3

Issue Date: 01 Jun. 2017

Prepared for

ONE DIAMOND ELECTRONICS INC.

1450 Frazee Road, Suite 303, San Diego, California, United States

Prepared by

Shenzhen NTEK Testing Technology Co., Ltd.

1/F, Building E, Fenda Science Park, Sanwei Community,
Xixiang Street Bao'an District, Shenzhen P.R. China
Tel.: +86-755-6115 9388

Fax.: +86-755-6115 6599 Website:http://www.ntek.org.cn



TABLE OF CONTENTS

1	TE	ST RESULT CERTIFICATION	3
2	SU	MMARY OF TEST RESULTS	4
3	FA	CILITIES AND ACCREDITATIONS	5
	3.1 FA 3.2 LA 3.3	ACILITIESABORATORY ACCREDITATIONS AND LISTINGS	5
4	GE	ENERAL DESCRIPTION OF EUT	6
5	DE	SCRIPTION OF TEST MODES	8
6	SE'	TUP OF EQUIPMENT UNDER TEST	10
	6.1 6.2 6.3	BLOCK DIAGRAM CONFIGURATION OF TEST SYSTEMSUPPORT EQUIPMENTEQUIPMENTS LIST FOR ALL TEST ITEMS	11
7	TE	ST REQUIREMENTS	14
	7.1 7.2 7.3 7.4 7.5	CONDUCTED EMISSIONS TEST	
	7.6 7.7 7.8 7.9	MAXIMUM OUTPUT POWER POWER SPECTRAL DENSITY CONDUCTED BAND EDGE MEASUREMENT SPURIOUS RF CONDUCTED EMISSIONS	
	7.10	ANTENNA APPLICATION	61



1 TEST RESULT CERTIFICATION

Applicant's name:	ONE DIAMOND ELECTRONICS INC.		
Address:	1450 Frazee Road, Suite 303, San Diego, California, United States		
Manufacturer's Name:	Shanghai Wind Communication Technologies Co.,Ltd.		
Address	3rd Floor, Building F1, TCL International E City, No. 1001, Zhongshan Park Road, Nanshan District, Shenzhen, P.R.China		
Product description			
Product name:	Smart phone		
Model and/or type reference:	P4006A		
Serial Model:	N/A		

Measurement Procedure Used:

Date of Test

APPLICABLE STANDARDS				
APPLICABLE STANDARD/ TEST PROCEDURE	TEST RESULT			
FCC 47 CFR Part 2, Subpart J:2016				
FCC 47 CFR Part 15, Subpart C:2016				
KDB 174176 D01 Line Conducted FAQ v01r01	Complied			
ANSI C63.10-2013				
FCC KDB 558074 D01 DTS Meas Guidance v03r05				

This device described above has been tested by Shenzhen NTEK Testing Technology Co., Ltd., and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of Shenzhen NTEK Testing Technology Co., Ltd., this document may be altered or revised by Shenzhen NTEK Testing Technology Co., Ltd., personnel only, and shall be noted in the revision of the document.

11 May. 2017 ~ 01 Jun. 2017

The test results of this report relate only to the tested sample identified in this report.

Testing Engineer	:	Eileen Wu.	
	-	(Eileen Liu)	
Technical Manager	:	Jason chen	
Ŭ		(Jason Chen)	
		Sam. Chen	
Authorized Signatory	:	7.8.15 92124211	
		(Sam Chen)	



2 SUMMARY OF TEST RESULTS

FCC Part15 (15.247), Subpart C						
Standard Section	Standard Section Test Item					
15.207	Conducted Emission	PASS				
15.247 (a)(2)	6dB Bandwidth	PASS				
15.247 (b)	Maximum Output Power	PASS				
15.247 (c)	Radiated Spurious Emission	PASS				
15.247 (d)	Power Spectral Density	PASS				
15.205	Band Edge Emission	PASS				
15.203	Antenna Requirement	PASS				

Remark:

- 1. "N/A" denotes test is not applicable in this Test Report.
- 2. All test items were verified and recorded according to the standards and without any deviation during the test.
- This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.



3 FACILITIES AND ACCREDITATIONS

3.1 FACILITIES

All measurement facilities used to collect the measurement data are located at 1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street Bao'an District, Shenzhen 518126 P.R. China

The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.10 and CISPR Publication 22.

3.2 LABORATORY ACCREDITATIONS AND LISTINGS

Site Description

EMC Lab. : Accredited by CNAS, 2014.09.04

The Laboratory has been assessed and proved to be in compliance with

CNAS-CL01:2006 (identical to ISO/IEC 17025:2005)

The Certificate Registration Number is L5516.

Accredited by Industry Canada, August 29, 2012 The Certificate Registration Number is 9270A-1.

Accredited by FCC, September 6, 2013

The Certificate Registration Number is 238937.

Name of Firm : Shenzhen NTEK Testing Technology Co., Ltd

Site Location : 1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang

Street, Bao'an District, Shenzhen 518126 P.R. China.

3.3 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement y±U, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of k=2, providing a level of confidence of approximately 95 %.

No. Item		Uncertainty
1	Conducted Emission Test	±1.38dB
2	RF power, conducted	±0.16dB
3 Spurious emissions, conducted		±0.21dB
4 All emissions, radiated(<1G)		±4.68dB
5 All emissions, radiated(>1G)		±4.89dB
6 Temperature		±0.5°C
7	Humidity	±2%



4 GENERAL DESCRIPTION OF EUT

Product Feature and Specification						
Equipment	Smart phone					
Trade Mark	Turbo D4					
FCC ID	2ADWUP4006A					
Model No.	P4006A					
Serial Model	N/A					
Model Difference	N/A					
Operating Frequency	2412-2462MHz for 802.11b/g/11n(HT20); 2422-2452MHz for 802.11n(HT40);					
Modulation	DSSS with DBPSK/DQPSK/CCK for 802.11b; OFDM with BPSK/QPSK/16QAM/64QAM for 802.11g/n;					
Number of Channels	11 channels for 802.11b/g/11n(HT20); 7 channels for 802.11n(HT40);					
Antenna Type	FPCB Antenna					
Antenna Gain	2.1 dBi					
Power supply	☐Adapter supply: Model: DCS67-0500500 Input:100~240V 50~60Hz 0.2A Output:5V, 500mA					
HW Version WG2M81C1-2						
SW Version P4006A_LATAM_V1.3						

Note: Based on the application, features, or specification exhibited in User's Manual, the EUT is considered as an ITE/Computing Device. More details of EUT technical specification, please refer to the User's Manual.



Revision History

Report No.	Version	Description	Issued Date
NTEK-2017NT05113227F3	Rev.01	Initial issue of report	Jun 01, 2017



5 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

The Transmitter was operated in the normal operating mode. The TX frequency was fixed which was for the purpose of the measurements.

Test of channel included the lowest and middle and highest frequency to perform the test, then record on this report.

Those data rates (802.11b: 1 Mbps; 802.11g: 6 Mbps; 802.11n (HT20): MCS0; 802.11n (HT40): MCS0) were used for all test.

The EUT was pretested with 3 orientations placed on the table for the radiated emission measurement –X, Y, and Z-plane. The Y-plane results were found as the worst case and were shown in this report.

Frequency and Channel list for 802.11b/g/n (HT20/HT40):

Channel	Frequency(MHz)
1	2412
2	2417
	···
5	2432
6	2437

10	2457
11	2462

Note: fc=2412MHz+k×5MHz k=0 to 10

EUT built-in battery-powered, fully-charged battery use of the test battery



Test Items	Mode	Data Rate	Channel	Ant
AC Power Line Conducted Emissions	Normal Link	-	-	-
	11b/CCK	1 Mbps	1/6/11	1
Maximum Conducted Output	11g/BPSK	6 Mbps	1/6/11	1
Power	11n HT20	MCS0	1/6/11	1
	11n HT40	MCS0	3/6/9	1
	11b/CCK	1 Mbno	1/6/11	1
		1 Mbps		1
Power Spectral Density	11g/BPSK 11n HT20	6 Mbps MCS0	1/6/11 1/6/11	1 1
	11n HT40	MCS0	3/6/9	1
			1 57 57 5	
6dB Spectrum Bandwidth	11b/CCK	1 Mbps	1/6/11	1
	11g/BPSK	6 Mbps	1/6/11	1
	11n HT20	MCS0	1/6/11	1
	11n HT40	MCS0	3/6/9	1
Radiated Emissions Below 1GHz	Normal Link	-	-	-
Radiated Emissions Above	11b/CCK	1 Mbps	1/6/11	1
1GHz	11g/BPSK	6 Mbps	1/6/11	1
	11n HT20	MCS0	1/6/11	1
	11n HT40	MCS0	3/6/9	1
Danid Edon End	11b/CCK	1 Mbps	1/6/11	1
Band Edge Emissions	11g/BPSK	6 Mbps	1/6/11	1
	11n HT20	MCS0	1/6/11	1
	11n HT40	MCS0	3/6/9	1



6 SETUP OF EQUIPMENT UNDER TEST

6.1 BLOCK DIAGRAM CONFIGURATION OF TEST SYSTEM

For AC Conducted Emission Mode

AC PLUG

C-1

E-1

EUT


C-2


Adapter

C-2

E-3

Earphone





Note:The temporary antenna connector is soldered on the PCB board in order to perform conducted tests and this temporary antenna connector is listed in the equipment list.



6.2 SUPPORT EQUIPMENT

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

tooto.					
Item	Equipment	Mfr/Brand	Model/Type No.	FCC ID	Note
E-1.	Smart phone	Turbo D4	P4006A	2ADWUP4006A	EUT
E-2	Adapter	N/A	DCS67-0500500	N/A	Peripherals
E-3	Earphone	N/A	2688	N/A	Peripherals

Item	Cable Type	Shielded Type	Ferrite Core	Length
C-1	USB Cable	NO	NO	1.2m
C-2	Earphone Cable	NO	NO	0.8m
C-3	RF Cable	NO	NO	0.5m

Notes:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in [Length] column.
- (3) "YES" is means "shielded" "with core"; "NO" is means "unshielded" "without core".



6.3 EQUIPMENTS LIST FOR ALL TEST ITEMS

Radiation Test equipment

Kadiatio	adiation Test equipment						
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibrati on period
1	Spectrum Analyzer	Agilent	E4407B	MY45108040	2016.07.06	2017.07.05	1 year
2	Spectrum Analyzer	Agilent	N9020A	MY49100060	2016.07.06	2017.07.05	1 year
3	EMI Test Receiver	Agilent	N9038A	MY53227146	2016.06.06	2017.06.05	1 year
4	Test Receiver	R&S	ESPI	101318	2016.06.06	2017.06.05	1 year
5	Bilog Antenna	TESEQ	CBL6111D	31216	2016.07.06	2017.07.05	1 year
6	50Ω Coaxial Switch	Anritsu	MP59B	6200264416	2016.06.06	2017.06.05	1 year
7	Horn Antenna	EM	EM-AH-1018 0	2011071402	2016.07.06	2017.07.05	1 year
8	Horn Ant	Schwarzbeck	BBHA 9170	9170-181	2016.07.06	2017.07.05	1 year
9	Amplifier	EM	EM-30180	060538	2016.12.22	2017.12.21	1 year
10	Amplifier	MITEQ	TTA1840-35- HG	177156	2016.06.06	2017.06.05	1 year
11	Loop Antenna	ARA	PLA-1030/B	1029	2016.06.06	2017.06.05	1 year
12	Power Meter	DARE	RPR3006W	100696	2016.07.06	2017.07.05	1 year
13	Test Cable (9KHz-30MHz)	N/A	R-01	N/A	2016.07.06	2017.07.05	1 year
14	Test Cable (30MHz-1GHz)	N/A	R-02	N/A	2016.07.06	2017.07.05	1 year
15	High Test Cable(1G-40G Hz)	N/A	R-03	N/A	2016.06.06	2017.06.05	1 year
16	High Test Cable(1G-40G Hz)	N/A	R-04	N/A	2016.06.06	2017.06.05	1 year
17	temporary antenna connector (Note)	NTS	R001	N/A	N/A	N/A	N/A

Note:

We will use the temporary antenna connector (soldered on the PCB board) When conducted test And this temporary antenna connector is listed within the instrument list



Condu	Conduction Test equipment						
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
1	Test Receiver	R&S	ESCI	101160	2016.06.06	2017.06.05	1 year
2	LISN	R&S	ENV216	101313	2016.08.24	2017.08.23	1 year
3	LISN	EMCO	3816/2	00042990	2016.08.24	2017.08.23	1 year
4	50Ω Coaxial Switch	Anritsu	MP59B	6200264417	2016.06.07	2017.06.06	1 year
5	Test Cable (9KHz-30MH z)	N/A	C01	N/A	2016.06.08	2017.06.07	1 year
6	Test Cable (9KHz-30MH z)	N/A	C02	N/A	2016.06.08	2017.06.07	1 year
7	Test Cable (9KHz-30MH z)	N/A	C03	N/A	2016.06.08	2017.06.07	1 year

Note: Each piece of equipment is scheduled for calibration once a year.



7 TEST REQUIREMENTS

7.1 CONDUCTED EMISSIONS TEST

7.1.1 Applicable Standard

According to FCC Part 15.207(a) and KDB 174176 D01 Line Conducted FAQ v01r01

7.1.2 Conformance Limit

Fraguency/MHz)	Conducted Emission Limit			
Frequency(MHz)	Quasi-peak	Average		
0.15-0.5	66-56*	56-46*		
0.5-5.0	56	46		
5.0-30.0	60	50		


Note: 1. *Decreases with the logarithm of the frequency

- 2. The lower limit shall apply at the transition frequencies
- 3. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

7.1.3 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

7.1.4 Test Configuration



7.1.5 Test Procedure

According to the requirements in Section 13.1.4.1 of ANSI C63.10-2013 Conducted emissions the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-Peak and average detector mode.

- 1. The EUT was placed 0.4 meter from the conducting wall of the shielding room.
- 2. The EUT was placed on a table which is 0.8m above ground plane.
- 3. Connect EUT to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- 4. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40cm long.
- 5. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- 6. LISN at least 80 cm from nearest part of EUT chassis.
- 7. The frequency range from 150KHz to 30MHz was searched.
- Set the test-receiver system to Peak Detect Function and specified bandwidth(IF bandwidth=9KHz) with Maximum Hold Mode
- 9. For the actual test configuration, please refer to the related Item –EUT Test Photos.




7.1.6 Test Results

EUT:	Smart phone	Model Name:	P4006A
Temperature:	26 ℃	Relative Humidity:	54%
Pressure:	1010hPa	Phase :	L
Test Voltage:	DC 5V from Adapter AC 120V/60Hz	Test Mode:	Normal Link

Frequency	Reading Level	Correct Factor	Measure-ment	Limits	Margin	Domostic
(MHz)	(dBµV)	(dB)	(dBµV)	(dBµV)	(dB)	Remark
0.1700	45.77	9.70	55.47	64.96	-9.49	QP
0.1700	31.15	9.70	40.85	54.96	-14.11	AVG
0.2260	40.64	9.70	50.34	62.59	-12.25	QP
0.2260	26.28	9.70	35.98	52.59	-16.61	AVG
0.4500	38.16	9.71	47.87	56.87	-9.00	QP
0.4500	27.35	9.71	37.06	46.87	-9.81	AVG
0.5580	37.67	9.71	47.38	56.00	-8.62	QP
0.5580	24.62	9.71	34.33	46.00	-11.67	AVG
0.7258	31.19	9.72	40.91	56.00	-15.09	QP
0.7298	17.17	9.72	26.89	46.00	-19.11	AVG
1.4538	30.03	9.77	39.80	56.00	-16.20	QP
1.4538	15.20	9.77	24.97	46.00	-21.03	AVG

Remark:

- All readings are Quasi-Peak and Average values.
 Factor = Insertion Loss + Cable Loss.






EUT:	Smart phone	Model Name:	P4006A
Temperature:	26 ℃	Relative Humidity:	54%
Pressure:	1010hPa	Phase :	Ν
Test Voltage:	DC 5V from Adapter AC 120V/60Hz	Test Mode:	Normal Link

Frequency	Reading Level	Correct Factor	Measure-ment	Limits	Margin	Damada
(MHz)	(dBµV)	(dB)	(dBµV)	(dBµV)	(dB)	Remark
0.1700	45.76	9.80	55.56	64.96	-9.40	QP
0.1700	30.09	9.80	39.89	54.96	-15.07	AVG
0.2260	40.59	9.80	50.39	62.59	-12.20	QP
0.2260	27.26	9.80	37.06	52.59	-15.53	AVG
0.4620	34.78	9.81	44.59	56.66	-12.07	QP
0.4620	21.08	9.81	30.89	46.66	-15.77	AVG
0.5220	34.97	9.81	44.78	56.00	-11.22	QP
0.5220	22.04	9.81	31.85	46.00	-14.15	AVG
0.9858	31.73	9.82	41.55	56.00	-14.45	QP
0.9858	12.09	9.82	21.91	46.00	-24.09	AVG
2.4980	27.70	9.84	37.54	56.00	-18.46	QP
2.4980	12.04	9.84	21.88	46.00	-24.12	AVG

All readings are Quasi-Peak and Average values.
 Factor = Insertion Loss + Cable Loss.






EUT:	Smart phone	Model Name:	P4006A
Temperature:	26 ℃	Relative Humidity:	54%
Pressure:	1010hPa	Phase :	L
Test Voltage:	DC 5V from Adapter AC 240V/60Hz	Test Mode:	Normal Link

Frequency	Reading Level	Correct Factor	Measure-ment	Limits	Margin	Remark
(MHz)	(dBµV)	(dB)	(dBµV)	(dBµV)	(dB)	Remark
0.1660	41.30	9.70	51.00	65.15	-14.15	QP
0.1660	25.81	9.70	35.51	55.15	-19.64	AVG
0.4500	36.87	9.71	46.58	56.87	-10.29	QP
0.4500	29.17	9.71	38.88	46.87	-7.99	AVG
0.5060	38.08	9.71	47.79	56.00	-8.21	QP
0.5060	30.32	9.71	40.03	46.00	-5.97	AVG
0.5580	37.08	9.71	46.79	56.00	-9.21	QP
0.5580	27.20	9.71	36.91	46.00	-9.09	AVG
1.0100	34.68	9.82	44.50	56.00	-11.50	QP
1.0100	25.41	9.82	35.23	46.00	-10.77	AVG
1.6220	34.13	9.77	43.90	56.00	-12.10	QP
1.6220	24.70	9.77	34.47	46.00	-11.53	AVG

- All readings are Quasi-Peak and Average values.
 Factor = Insertion Loss + Cable Loss.






EUT:	Smart phone	Model Name:	P4006A
Temperature:	26 ℃	Relative Humidity:	54%
Pressure:	1010hPa	Phase :	N
Test Voltage:	DC 5V from Adapter AC 240V/60Hz	Test Mode:	Normal Link

Frequency	Reading Level	Correct Factor	Measure-ment	Limits	Margin	Domonic
(MHz)	(dBµV)	(dB)	(dBµV)	(dBµV)	(dB)	Remark
0.1660	41.55	9.80	51.35	65.15	-13.80	QP
0.1660	23.39	9.80	33.19	55.15	-21.96	AVG
0.4500	35.14	9.81	44.95	56.87	-11.92	QP
0.4500	23.74	9.81	33.55	46.87	-13.32	AVG
0.5060	36.19	9.81	46.00	56.00	-10.00	QP
0.5060	25.34	9.81	35.15	46.00	-10.85	AVG
0.5580	32.96	9.81	42.77	56.00	-13.23	QP
0.5580	22.94	9.81	32.75	46.00	-13.25	AVG
1.0660	31.81	9.82	41.63	56.00	-14.37	QP
1.0660	21.26	9.82	31.08	46.00	-14.92	AVG
1.5700	32.00	9.83	41.83	56.00	-14.17	QP
1.5700	20.11	9.83	29.94	46.00	-16.06	AVG

- All readings are Quasi-Peak and Average values.
 Factor = Insertion Loss + Cable Loss.





7.2 RADIATED SPURIOUS EMISSION

7.2.1 Applicable Standard

According to FCC Part 15.247(d) and 15.209 and ANSI C63.10-2013

7.2.2 Conformance Limit

According to FCC Part 15.247(d): radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

According to FCC Part15.205, Restricted bands

recording to 1 00 1 artioize	decorating to 1 00 1 dr. 10:200; receitloited bands						
MHz	MHz	MHz	GHz				
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15				
10.495-0.505	16.69475-16.69525	608-614	5.35-5.46				
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75				
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5				
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2				
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5				
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7				
6.26775-6.26825	123-138	2200-2300	14.47-14.5				
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2				
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4				
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12				
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0				
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8				
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5				
12.57675-12.57725	322-335.4	3600-4400	(2)				
13.36-13.41							

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

D	1	1 /		
Restricted Frequency(MHz)	Field Strength (μV/m)	Field Strength (dBµV/m)	Measurement Distance	
0.009~0.490	2400/F(KHz)	20 log (uV/m)	300	
0.490~1.705	2400/F(KHz)	20 log (uV/m)	30	
1.705~30.0	30	29.5	30	
30-88	100	40	3	
88-216	150	43.5	3	
216-960	200	46	3	
Above 960	500	54	3	

Limits of Radiated Emission Measurement(Above 1000MHz)

Frequency(MHz)	Class B (dBuV/m) (at 3M)				
	PEAK	AVERAGE			
Above 1000	74	54			

Remark :1. Emission level in dBuV/m=20 log (uV/m)

- 2. Measurement was performed at an antenna to the closed point of EUT distance of meters.
- 3. Distance extrapolation factor =40log(Specific distance/ test distance)(dB); Limit line=Specific limits(dBuV) + distance extrapolation factor.


7.2.3 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.




7.2.4 Test Configuration


(a) For radiated emissions below 30MHz



(b) For radiated emissions from 30MHz to 1000MHz



(c) For radiated emissions above 1000MHz





7.2.5 Test Procedure

The test site semi-anechoic chamber has met the requirement of NSA tolerance 4 dB according to the standards: ANSI C63.10-2013. The test distance is 3m.The setup is according to the requirements in Section 13.1.4.1 of ANSI C63.10-2013 and CAN/CSA-CEI/IEC CISPR 22.

Page 21 of 61

This test is required for any spurious emission that falls in a Restricted Band, as defined in Section 15.205. It must be performed with the highest gain of each type of antenna proposed for use with the EUT. Use the following spectrum analyzer settings:

Spectrum Parameter	Setting			
Attenuation	Auto			
Start Frequency	1000 MHz			
Stop Frequency	10th carrier harmonic			
RB / VB (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average			

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

- a. The measuring distance of at 3 m shall be used for measurements at frequency up to 1GHz and frequencies above 1GHz,
- b. The EUT was placed on the top of a rotating table 0.8 m for below 1GHz and 1.5m for above 1GHz the ground at a 3 meter. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The height of the equipment or of the substitution antenna shall be 0.8 m for below 1GHz and 1.5m for above 1GHz; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For the radiated emission test above 1GHz:
 - Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
- e. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- f. If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- g For the actual test configuration, please refer to the related Item –EUT Test Photos.

Note:

Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

During the radiated emission test, the Spectrum Analyzer was set with the following configurations: For peak measurement:

Set RBW=100 kHz for f < 1 GHz; VBW≥RBW; Sweep = auto; Detector function = peak; Trace = max hold; Set RBW = 1 MHz, VBW= 3MHz for f≥1 GHz

For average measurement:

VBW = 10 Hz, when duty cycle is no less than 98 percent.

VBW \geq 1/T, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.



Note: for the frequency ranges below 30 MHz, a narrower RBW is used for these ranges but the measured value should add a RBW correction factor (RBWCF) where RBWCF [dB] =10*lg(100 [kHz]/narrower RBW [kHz])., the narrower RBW is 1 kHz and RBWCF is 20 dB for the frequency 9 kHz to 150 kHz, and the narrower RBW is 10 kHz and RBWCF is 10 dB for the frequency 150 kHz to 30 MHz.

7.2.6 Test Results

■ Spurious Emission below 30MHz (9KHz to 30MHz)

	01011 201011 001111 12 (0111 12 10 001111	:=/	
EUT:	Smart phone	Model No.:	P4006A
Temperature:	20 ℃	Relative Humidity:	48%
Test Mode:	802.11b/g/n(HT20, HT40)	Test By:	Eileen Liu

	Freq.	Ant.Pol.	Emission L	.evel(dBuV/m)	Limit 3	m(dBuV/m)	Over(dB)		
	(MHz)	H/V	PK	AV	PK	AV	PK	AV	
Γ									

Note: the amplitude of spurious emission that is attenuated by more than 20dB below the permissible limit has no need to be reported.

Distance extrapolation factor =20log(Specific distance/ test distance)(dB);

Limit line=Specific limits(dBuV) + distance extrapolation factor




■ Spurious Emission below 1GHz (30MHz to 1GHz)
All the modulation modes have been tested, and the worst result was report as below:

EUT:	Smart phone	Model Name:	P4006A
Temperature:	20 ℃	Relative Humidity:	48%
Pressure:	1010hPa	Test Mode:	Normal Link
Test Voltage:	DC 3.7V		

Polar	Frequency	Meter Reading	Factor	Emission Level	l I I I I Mai		Remark
(H/V)	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
V	33.2112	9.41	19.76	29.17	40.00	-10.83	QP
V	54.6429	8.54	12.26	20.80	40.00	-19.20	QP
V	97.1148	8.40	11.04	19.44	43.50	-24.06	QP
V	195.1365	11.51	13.74	25.25	43.50	-18.25	QP
V	431.0316	6.29	16.57	22.86	46.00	-23.14	QP
V	1000.0000	6.94	28.25	35.19	54.00	-18.81	QP


Remark:

Absolute Level= ReadingLevel+ Factor, Margin= Absolute Level - Limit





Polar	Frequency	Meter Reading Factor		Emission Level	Limits	Margin	Remark	
(H/V)	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)		
Н	30.4238	5.56	21.02	26.58	40.00	-13.42	QP	
Н	34.2760	6.51	19.24	25.75	40.00	-14.25	QP	
Н	93.4402	9.58	12.00	21.58	43.50	-21.92	QP	
Н	203.5227	6.21	13.85	20.06	43.50	-23.44	QP	
Н	304.6099	7.83	14.05	21.88	46.00	-24.12	QP	
Н	1000.0000	7.02	28.25	35.27	54.00	-18.73	QP	





Spurious Emission Above 1GHz (1GHz to 27GHz)

EUT:	Smart phone	Model No.:	P4006A
Temperature:	20 ℃	Relative Humidity:	48%
Test Mode:	802.11b/g/n(HT20, HT40)	Test By:	Eileen Liu

All the modulation modes have been tested, and the worst result was report as below:

Frequency	Read Level	Cable loss	Antenna Factor	Preamp Factor	Emission Level	Limits	Margin	Remark	Commont	
(MHz)	(dBµV)	(dB)	dB/m	(dB)	(dBµV/m)	(dBµV/m)	(dB)	Remark	Comment	
Low Channel (2412 MHz)(802.11b)Above 1G										
4824.526	69.65	5.21	35.59	44.30	66.15	74.00	-7.85	Pk	Vertical	
4824.526	42.25	5.21	35.59	44.30	38.75	54.00	-15.25	AV	Vertical	
7236.221	63.37	6.48	36.27	44.60	61.52	74.00	-12.48	Pk	Vertical	
7236.221	45.41	6.48	36.27	44.60	43.56	54.00	-10.44	AV	Vertical	
4824.108	65.58	5.21	35.55	44.30	62.04	74.00	-11.96	Pk	Horizontal	
4824.108	45.57	5.21	35.55	44.30	42.03	54.00	-11.97	AV	Horizontal	
7236.239	66.23	6.48	36.27	44.52	64.46	74.00	-9.54	Pk	Horizontal	
7236.239	48.52	6.48	36.27	44.52	46.75	54.00	-7.25	AV	Horizontal	
		L	ow Channe	el (2437 MF	Hz)(802.11b)	Above 1G				
4874.421	63.34	5.21	35.66	44.20	60.01	74.00	-13.99	Pk	Vertical	
4874.421	49.74	5.21	35.66	44.20	46.41	54.00	-7.59	AV	Vertical	
7311.338	61.54	7.10	36.50	44.43	60.71	74.00	-13.29	Pk	Vertical	
7311.338	44.51	7.10	36.50	44.43	43.68	54.00	-10.32	AV	Vertical	
4874.197	64.23	5.21	35.66	44.20	60.90	74.00	-13.10	Pk	Horizontal	
4874.197	47.62	5.21	35.66	44.20	44.29	54.00	-9.71	AV	Horizontal	
7311.198	65.52	7.10	36.50	44.43	64.69	74.00	-9.31	Pk	Horizontal	
7311.198	42.33	7.10	36.50	44.43	41.50	54.00	-12.50	AV	Horizontal	
		L	ow Channe	el (2462 MF	Hz)(802.11b)	Above 1G				
4924.342	68.95	5.21	35.52	44.21	65.47	74.00	-8.53	Pk	Vertical	
4924.342	47.41	5.21	35.52	44.21	43.93	54.00	-10.07	AV	Vertical	
7386.336	69.65	7.10	36.53	44.60	68.68	74.00	-5.32	Pk	Vertical	
7386.336	42.23	7.10	36.53	44.60	41.26	54.00	-12.74	AV	Vertical	
4924.198	69.98	5.21	35.52	44.21	66.50	74.00	-7.50	Pk	Horizontal	
4924.198	48.41	5.21	35.52	44.21	44.93	54.00	-9.07	AV	Horizontal	
7386.364	62.25	7.10	36.53	44.60	61.28	74.00	-12.72	Pk	Horizontal	
7386.364	46.67	7.10	36.53	44.60	45.70	54.00	-8.3	AV	Horizontal	

Note: (1) All Readings are Peak Value (VBW=3MHz) and Peak Value (VBW=10Hz).

(4)"802.11b" mode is the worst mode. When PK value is lower than the Average value limit, average don't record.

⁽²⁾ Emission Level= Antenna Factor + Cable Loss + Read Level - Preamp Factor (3) Data of measurement within this frequency range shown " -- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.



■ Spurious Emission in Restricted Band 2310MHz -18000MHz

All the modulation modes have been tested, and the worst result was report as below:

						esult was	report as l	below:	
Frequenc	Meter Reading	Cable Loss	Antenna Factor	Preamp Factor	Emission Level	Limits	Margin	Detector	Comment
(MHz)	(dBµV)	(dB)	dB/m	(dB)	(dBµV/m)	(dBµV/m)	(dB)	Type	
				802	.11b				
2310.00	60.59	2.97	27.80	43.80	47.56	74	-26.44	Pk	Horizontal
2310.00	41.13	2.97	27.80	43.80	28.10	54	-25.90	AV	Horizontal
2310.00	59.98	2.97	27.80	43.80	46.95	74	-27.05	Pk	Vertical
2310.00	42.23	2.97	27.80	43.80	29.20	54	-24.80	AV	Vertical
2390.00	63.37	3.14	27.21	43.80	49.92	74	-24.08	Pk	Vertical
2390.00	42.22	3.14	27.21	43.80	28.77	54	-25.23	AV	Vertical
2390.00	60.51	3.14	27.21	43.80	47.06	74	-26.94	Pk	Horizontal
2390.00	42.69	3.14	27.21	43.80	29.24	54	-24.76	AV	Horizontal
2483.50	63.35	3.58	27.70	44.00	50.63	74	-23.37	Pk	Vertical
2483.50	42.22	3.58	27.70	44.00	29.50	54	-24.50	AV	Vertical
2483.50	58.95	3.58	27.70	44.00	46.23	74	-27.77	Pk	Horizontal
2483.50	41.01	3.58	27.70	44.00	28.29	54	-25.71	AV	Horizontal
2010.00	22.22	0.0=	07.00	802				l Di	1
2310.00	60.23	2.97	27.80	43.80	47.20	74	-26.80	Pk	Horizontal
2310.00	42.23	2.97	27.80	43.80	29.20	54	-24.80	AV	Horizontal
2310.00	61.23	2.97	27.80	43.80	48.20	74	-25.80	Pk AV	Vertical Vertical
2310.00	42.28 62.77	2.97 3.14	27.80	43.80 43.80	29.25	54	-24.75		
2390.00 2390.00		3.14	27.21	43.80	49.32 28.39	74 54	-24.68 -25.61	Pk AV	Vertical Vertical
2390.00	41.84 61.32	3.14	27.21 27.21	43.80	47.87	74	-26.13	Pk	Horizontal
2390.00	42.21	3.14	27.21	43.80	28.76	54	-25.24	AV	Horizontal
2483.50	59.98	3.58	27.70	44.00	47.26	74	-26.74	Pk	Vertical
2483.50	41.16	3.58	27.70	44.00	28.44	54	-25.56	AV	Vertical
2483.50	61.23	3.58	27.70	44.00	48.51	74	-25.49	Pk	Horizontal
2483.50	42.29	3.58	27.70	44.00	29.57	54	-24.43	AV	Horizontal
	0	0.00		802.1		0.			
2310.00	61.33	2.97	27.80	43.80	48.30	74	-25.70	Pk	Horizontal
2310.00	42.25	2.97	27.80	43.80	29.22	54	-24.78	AV	Horizontal
2310.00	62.74	2.97	27.80	43.80	49.71	74	-24.29	Pk	Vertical
2310.00	42.39	2.97	27.80	43.80	29.36	54	-24.64	AV	Vertical
2390.00	62.12	3.14	27.21	43.80	48.67	74	-25.33	Pk	Vertical
2390.00	42.52	3.14	27.21	43.80	29.07	54	-24.93	AV	Vertical
2390.00	61.12	3.14	27.21	43.80	47.67	74	-26.33	Pk	Horizontal
2390.00	43.29	3.14	27.21	43.80	29.84	54	-24.16	AV	Horizontal
2483.50	60.55	3.58	27.70	44.00	47.83	74	-26.17	Pk	Vertical
2483.50	40.98	3.58	27.70	44.00	28.26	54	-25.74	AV	Vertical
2483.50	59.86	3.58	27.70	44.00	47.14	74	-26.86	Pk	Horizontal
2483.50	43.35	3.58	27.70	44.00	30.63	54	-23.37	AV	Horizontal
	1	,	,		1n40		ı		,
2310.00	59.65	2.97	27.80	43.80	46.62	74	-27.38	Pk	Horizontal
2310.00	41.13	2.97	27.80	43.80	28.10	54	-25.90	AV	Horizontal
2310.00	62.27	2.97	27.80	43.80	49.24	74	-24.76	Pk	Vertical
2310.00	42.27	2.97	27.80	43.80	29.24	54	-24.76	AV	Vertical
2390.00	62.53	3.14	27.21	43.80	49.08	74	-24.92	Pk	Vertical
2390.00	41.15	3.14	27.21	43.80	27.70	54	-26.30	AV	Vertical
2390.00	59.98	3.14	27.21	43.80	46.53	74	-27.47	Pk	Horizontal
2390.00	45.57	3.14	27.21	43.80	32.12	54	-21.88	AV	Horizontal
2483.50	59.85	3.58	27.70	44.00	47.13	74 54	-26.87	Pk AV	Vertical
2483.50 2483.50	43.26 62.22	3.58	27.70 27.70	44.00 44.00	30.54 49.50	54 74	-23.46 -24.50		Vertical
2483.50	41.12	3.58 3.58	27.70	44.00	28.40	74 54	-24.50 -25.60	Pk AV	Horizontal Horizontal
Z 7 03.30	71.1∠	J.J0	21.10	74.00	∠0.4U	J 4	-20.00		i ionzonial



Spurious Emission in Restricted Bands 3260MMHz- 18000MHz

All the modulation modes have been tested, the worst result was report as below:

Frequenc	Reading Level	Cable Loss	Antenna Factor	Preamp Factor	Emission Level	Limits	Margin	Detector	Comment
(MHz)	(dBµV)	(dB)	dB/m	(dB)	(dBµV/m)	(dBµV/m)	(dB)	Туре	
3260	62.54	4.04	29.57	44.70	51.45	74	-22.55	Pk	Vertical
3260	55.56	4.04	29.57	44.70	44.47	54	-9.53	AV	Vertical
3260	61.41	4.04	29.57	44.70	50.32	74	-23.68	Pk	Horizontal
3260	48.87	4.04	29.57	44.70	37.78	54	-16.22	AV	Horizontal
3332	63.32	4.26	29.87	44.40	53.05	74	-20.95	Pk	Vertical
3332	48.77	4.26	29.87	44.40	38.50	54	-15.50	AV	Vertical
3332	63.35	4.26	29.87	44.40	53.08	74	-20.92	Pk	Horizontal
3332	51.12	4.26	29.87	44.40	40.85	54	-13.15	AV	Horizontal
17797	49.96	10.99	43.95	43.50	61.40	74	-12.60	Pk	Vertical
17797	29.65	10.99	43.95	43.50	41.09	54	-12.91	AV	Vertical
17788	48.56	11.81	43.69	44.60	59.46	74	-14.54	Pk	Horizontal
17788	31.12	11.81	43.69	44.60	42.02	54	-11.98	AV	Horizontal

[&]quot;802.11b" mode is the worst mode. When PK value is lower than the Average value limit, average don't record.



7.3 6DB BANDWIDTH

7.3.1 Applicable Standard

According to FCC Part 15.247(a)(2) and KDB 558074 DTS 01 Meas. Guidance v03r05

7.3.2 Conformance Limit

The minimum permissible 6dB bandwidth is 500 kHz.

7.3.3 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

7.3.4 Test Setup

Please refer to Section 6.1 of this test report.

7.3.5 Test Procedure

The testing follows KDB 558074 DTS 01 Meas. Guidance v03r05

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.

The path loss was compensated to the results for each measurement.

Set to the maximum power setting and enable the EUT transmit continuously.

The EUT was operating in controlled its channel.

Use the following spectrum analyzer settings:

Span = the frequency band of operation

RBW = 100KHz

 $VBW \geq 3^*RBW$

Sweep = auto

Detector function = peak

Trace = max hold



7.3.6 Test Results

EUT:	Smart phone	Model No.:	P4006A
Temperature:	20 ℃	Relative Humidity:	48%
Test Mode:	802.11b/g/n20/n40	Test By:	Eileen Liu

Mada	Channal	Frequency	6dB bandwidth	Limit	Result
Mode	Channel	(MHz)	(MHz)	(kHz)	
802.11b	Low	2412	10.04	500	Pass
	Middle	2437	9.581	500	Pass
	High	2462	10.05	500	Pass
802.11g	Low	2412	15.16	500	Pass
	Middle	2437	15.16	500	Pass
	High	2462	15.16	500	Pass
802.11n20	Low	2412	15.16	500	Pass
	Middle	2437	15.16	500	Pass
	High	2462	15.16	500	Pass
802.11n40	Low	2422	35.24	500	Pass
	Middle	2437	35.24	500	Pass
	High	2452	35.24	500	Pass




Test plot

(802.11b) 6dB Bandwidth plot on channel 1



(802.11g) 6dB Bandwidth plot on channel 1



(802.11b) 6dB Bandwidth plot on channel 6




(802.11g) 6dB Bandwidth plot on channel 6



(802.11b) 6dB Bandwidth plot on channel 11



(802.11g) 6dB Bandwidth plot on channel 11








Test plot

Page 31 of 61

(802.11n20) 6dB Bandwidth plot on channel 1









(802.11n20) 6dB Bandwidth plot on channel 6

(802.11n40) 6dB Bandwidth plot on channel 6






(802.11n20) 6dB Bandwidth plot on channel 11

(802.11n40) 6dB Bandwidth plot on channel 9







7.4 20DB BANDWIDTH

7.4.1 Applicable Standard

According to FCC Part 15.247(a)(2) and KDB 558074 DTS 01 Meas. Guidance v03r05

7.4.2 Conformance Limit

No limit requirement.

7.4.3 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

7.4.4 Test Setup

Please refer to Section 6.1 of this test report.

7.4.5 Test Procedure

The testing follows KDB 558074 DTS 01 Meas. Guidance v03r05

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.

The path loss was compensated to the results for each measurement.

Set to the maximum power setting and enable the EUT transmit continuously.

The EUT was operating in controlled its channel.

Use the following spectrum analyzer settings:

Span = the frequency band of operation

RBW = 100KHz

 $VBW \geq 3^*RBW$

Sweep = auto

Detector function = peak

Trace = max hold



7.4.6 Test Results

EUT:	Smart phone	Model No.:	P4006A
Temperature:	20 ℃	Relative Humidity:	48%
Test Mode:	802.11b/g/n20/n40	Test By:	Eileen Liu

All the bands and channels were tested, the data of the worst mode are described in the following table

Mode	Channel	Frequency (MHz)	-20dB bandwidth (MHz)	Limit (kHz)	Result
802.11b	Low	2412	15.10	N/A	Pass
	Middle	2437	15.06	N/A	Pass
	High	2462	15.06	N/A	Pass
802.11g	Low	2412	17.58	N/A	Pass
	Middle	2437	18.40	N/A	Pass
	High	2462	17.62	N/A	Pass
802.11n20	Low	2412	18.41	N/A	Pass
	Middle	2437	19.14	N/A	Pass
	High	2462	18.44	N/A	Pass
802.11n40	Low	2422	37.13	N/A	Pass
	Middle	2437	37.14	N/A	Pass
	High	2452	37.18	N/A	Pass




Test plot

(802.11b) -20dB Bandwidth plot on channel 1




(802.11g) -20dB Bandwidth plot on channel 1



(802.11b) -20dB Bandwidth plot on channel 6



(802.11g) -20dB Bandwidth plot on channel 6



(802.11b) -20dB Bandwidth plot on channel 11




(802.11g) -20dB Bandwidth plot on channel 11






Test plot

(802.11n20) -20dB Bandwidth plot on channel 1




(802.11n40) -20dB Bandwidth plot on channel 3




(802.11n20) -20dB Bandwidth plot on channel 6




(802.11n40) -20dB Bandwidth plot on channel 6



(802.11n20) -20dB Bandwidth plot on channel 11



(802.11n40) -20dB Bandwidth plot on channel 9





7.5 DUTY CYCLE

7.5.1 **Applicable Standard**

According to KDB 558074)6)b), issued 06/09/2015

Conformance Limit

No limit requirement.

7.5.3 **Measuring Instruments**

The Measuring equipment is listed in the section 6.3 of this test report.

7.5.4 **Test Setup**

Please refer to Section 6.1 of this test report.

7.5.5 **Test Procedure**

The zero-span mode on a spectrum analyzer or EMI receiver if the response time and spacing between bins on the sweep are sufficient to permit accurate measurements of the on and off times of the transmitted signal. Set the center frequency of the instrument to the center frequency of the transmission. Set RBW ≥ OBW if possible; otherwise, set RBW to the largest available value. Set VBW ≥ RBW. Set detector = peak or average. The zero-span measurement method shall not be used unless both RBW and VBW are > 50/T and the number of sweep points across duration T exceeds 100. (For example, if VBW and/or RBW are limited to 3 MHz, then the zero-span method of measuring duty cycle shall not be used if T ≤ 16.7 microseconds.)

Page 36 of 61

The transmitter output is connected to the Spectrum Analyzer. We tested accroding to the zero-span measurement method, 6.0)b) in KDB 558074(issued 06/09/2015)

The largest availble value of RBW is 8 MHz and VBW is 50 MHz. The zero-span method of measuring duty cycle shall not be used if T \leq 6.25 microseconds. (50/6.25 = 8)

The zero-span method was used because all measured T data are > 6.25 microseconds and both RBW and VBW are > 50/T.

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.

The path loss was compensated to the results for each measurement.

Set to the maximum power setting and enable the EUT transmit continuously.

The EUT was operating in controlled its channel.

Use the following spectrum analyzer settings:

Span = Zero Span

RBW = 8MHz(the largest available value)

 $VBW = 8MHz (\ge RBW)$

Number of points in Sweep >100

Detector function = peak

Trace = Clear write

Measure T_{total} and T_{on}

Calculate Duty Cycle = Ton / Ttotal



7.5.6 Test Results

EUT:	Smart phone	Model No.:	P4006A
Temperature:	20 ℃	Relative Humidity:	48%
Test Mode:	802.11b/g/n20/n40	Test By:	Eileen Liu

Mode	Data rate	Channel	T _{on}	T _{total}	Duty Cycle	Duty Cycle Factor (dB)	VBW Setting
802.11b	1Mbps	6	-	-	100%	0	10Hz
802.11g	6Mbps	6	-	-	100%	0	1KHz
802.11n HT20	MCS0	6		-	100%	0	1KHz
802.11n HT40	MCS0	6	ı	-	100%	0	3KHz

Note: All the modulation modes were tested, the data of the worst mode are described in the following table.



7.6 MAXIMUM OUTPUT POWER

7.6.1 Applicable Standard

According to FCC Part 15.247(b)(3) and KDB 558074 DTS 01 Meas. Guidance v03r05

7.6.2 Conformance Limit


The maximum peak conducted output power of the intentional radiator for systems using digital modulation in the 2400 - 2483.5 MHz bands shall not exceed: 1 Watt (30dBm). If transmitting antenna of directional gain greater than 6dBi is used, the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.

7.6.3 Measuring Instruments

The following table is the setting of the power meter.

Power Meter Parameter	Setting
Detector	Average

7.6.4 Test Setup



7.6.5 Test Procedure

- 1. Test procedures refer KDB 558074 D01 v03r05 section 9.2.3.2 Measurement using a power meter (PM).
- 2. Alternatively, measurements may be performed using a wideband gated RF power meter provided that the gate parameters are adjusted such that the power is measured only when the EUT is transmitting at its maximum power control level. Since this measurement is made only during the ON time of the transmitter, no duty cycle correction is required.
- 3. Multiple antenna system was performed in accordance with KDB 662911 D01 v02r01 Emissions Testing of Transmitters with Multiple Outputs in the Same Band.

7.6.6 EUT opration during Test

The EUT was programmed to be in continuously transmitting mode.



7.6.7 Test Results

EUT:	Smart phone	Model No.:	P4006A
Temperature:	20 ℃	Relative Humidity:	48%
Test Mode:	802.11b/g/n20/n40	Test By:	Eileen Liu

			D (O)	Δ.				
T (0)	Frequency	Power	Duty Cycle	Average	Maximum	LIMIT		
Test Channel	(MHz)	Setting	Factor	Output Power	Output	(dBm)	Verdict	
	(1411 12)	County	(dB)	(dBm)	Power(dBm)	(42)		
				802.11b				
1	2412	Default	0	17.6	17.6	30	PASS	
6	2437	Default	0	17.6	17.6	30	PASS	
11	2462	Default	0	17.6	17.6	30	PASS	
	802.11g							
1	2412	Default	0	13.8	13.8	30	PASS	
6	2437	Default	0	15.5	15.5	30	PASS	
11	2462	Default	0	15.4	15.4	30	PASS	
		802.11n HT20						
1	2412	Default	0	14.2	14.2	30	PASS	
6	2437	Default	0	15.7	15.7	30	PASS	
11	2462	Default	0	15.8	15.8	30	PASS	
	802.11n HT40							
3	2422	Default	0	13.9	13.9	30	PASS	
6	2437	Default	0	14.3	14.3	30	PASS	
9	2452	Default	0	14.5	14.5	30	PASS	



7.7 POWER SPECTRAL DENSITY

7.7.1 Applicable Standard

According to FCC Part 15.247(e) and KDB 558074 DTS 01 Meas. Guidance v03r05

7.7.2 Conformance Limit

The transmitter power spectral density conducted from the transmitter to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

7.7.3 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

7.7.4 Test Setup

Please refer to Section 6.1 of this test report.

7.7.5 Test Procedure

The testing follows Measurement Procedure 10.3 Method AVGPSD of FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r05

This procedure may be used when the maximum (average) conducted output power was used to demonstrate compliance to the output power limit. This is the baseline method for determining the maximum (average) conducted PSD level. If the instrument has an RMS power averaging detector, it must be used; otherwise, use the sample detector. The EUT must be configured to transmit continuously (duty cycle ≥ 98%); otherwise sweep triggering/signal gating must be implemented to ensure that measurements are made only when the EUT is transmitting at its maximum power control level (no transmitter off time is to be considered).

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.

The path loss was compensated to the results for each measurement.

Set to the maximum power setting and enable the EUT transmit continuously.

The EUT was operating in controlled its channel.

- a) Set instrument center frequency to DTS channel center frequency.
- b) Set span to at least 1.5 times the OBW.
- c) Set RBW to: 3 kHz ≤ RBW ≤ 100 kHz. .
- d) Set VBW ≥3 x RBW.
- e) Detector = power averaging (RMS) or sample detector (when RMS not available).
- f) Ensure that the number of measurement points in the sweep $\geq 2 \times \text{span/RBW}$.
- g) Sweep time = auto couple.
- h) Employ trace averaging (RMS) mode over a minimum of 100 traces.
- i) Use the peak marker function to determine the maximum amplitude level.
- j) If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat (note that this may require zooming in on the emission of interest and reducin



7.7.6 Test Results

EUT:	Smart phone	Model No.:	P4006A
Temperature:	20 ℃	Relative Humidity:	48%
Test Mode:	802.11b/g/n20/n40	Test By:	Eileen Liu

			I				
Test Channel	Frequency	Duty Cycle	Power Density	Limit	Verdict		
1 est Chamilei	(MHz)	Factor(dB)	(dBm/3KHz)	(dBm/3KHz)	Verdict		
	802.11b						
1	2412	0	-6.400	8	PASS		
6	2437	0	-5.580	8	PASS		
11	2462	0	-5.408	8	PASS		
	802.11g						
1	2412	0	-11.296	8	PASS		
6	2437	0	-10.159	8	PASS		
11	2462	0	-9.230	8	PASS		
	802.11n HT20						
1	2412	0	-10.992	8	PASS		
6	2437	0	-9.380	8	PASS		
11	2462	0	-8.572	8	PASS		
	802.11n HT40						
3	2422	0	-14.901	8	PASS		
6	2437	0	-16.005	8	PASS		
9	2452	0	-15.256	8	PASS		



Test plot

(802.11b) PSD plot on channel 1






Avg Type: Pwr(RMS) Avg(Hold: 7/100 arker 1 2.411041307283 GHz Ref 20.00 dBm

(802.11b) PSD plot on channel 6

(802.11g) PSD plot on channel 6






(802.11b) PSD plot on channel 11

(802.11g) PSD plot on channel 11










Test plot

Page 43 of 61

(802.11n20) PSD plot on channel 1









(802.11n20) PSD plot on channel 6


(802.11n40) PSD plot on channel 6






(802.11n20) PSD plot on channel 11

(802.11n40) PSD plot on channel 9







7.8 CONDUCTED BAND EDGE MEASUREMENT

7.8.1 Applicable Standard

According to FCC Part 15.247(d) and KDB 558074 DTS 01 Meas. Guidance v03r05

7.8.2 Conformance Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.

7.8.3 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

7.8.4 Test Setup

Please refer to Section 6.1 of this test report.

7.8.5 Test Procedure

The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r05.

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.

The path loss was compensated to the results for each measurement.

Set to the maximum power setting and enable the EUT transmit continuously.

The EUT was operating in controlled its channel.

Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.

Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.

Repeat above procedures until all measured frequencies were complete.



7.8.6 Test Results

EUT:	Smart phone	Model No.:	P4006A
Temperature:	20 ℃	Relative Humidity:	48%
Test Mode:	802.11b/g/n20/n40	Test By:	Eileen Liu



Test plot For

802.11b: Band Edge-Low Channel



802.11g: Band Edge-Low Channel



802.11b: Band Edge-High Channel




802.11g: Band Edge-High Channel





Test plot For

802.11n20: Band Edge-Low Channel







802.11n20: Band Edge-High Channel

802.11n40: Band Edge-High Channel







7.9 SPURIOUS RF CONDUCTED EMISSIONS

7.9.1 Conformance Limit

- 1. Below -20dB of the highest emission level in operating band.
- 2. Fall in the restricted bands listed in section 15.205. The maximum permitted average field strength is listed in section 15.209.

7.9.2 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

7.9.3 Test Setup

Please refer to Section 6.1 of this test report.

7.9.4 Test Procedure

The Spurious RF conducted emissions compliance of RF radiated emission should be measured by following the guidance in ANSI C63.10-2013 with respect to maximizing the emission by rotating the EUT, measuring the emission while the EUT is situated in three orthogonal planes (if appropriate), adjusting the measurement antenna height and polarization etc. Set RBW=100kHz and VBW= 300KHz to measure the peak field strength, and mwasure frequeny range from 9KHz to 26.5GHz.

7.9.5 Test Results

Remark: The measurement frequency range is from 9KHz to the 10th harmonic of the fundamental frequency. The lowest, middle and highest channels are tested to verify the spurious emissions and bandege measurement data.




802.11b on channel 01



802.11b on channel 01



802.11b on channel 01



802.11b on channel 01





802.11b on channel 06



802.11b on channel 06



802.11b on channel 06



802.11b on channel 06





802.11b on channel 11



802.11b on channel 11



802.11b on channel 11



802.11b on channel 11






802.11g on channel 01





802.11g on channel 01

802.11g on channel 01




802.11g on channel 01





802.11g on channel 06



802.11g on channel 06



802.11g on channel 06



802.11g on channel 06





802.11g on channel 11



802.11g on channel 11



802.11g on channel 11



802.11g on channel 11





802.11n20 on channel 01



802.11n20 on channel 01



802.11 n20 on channel 01



802.11 n20 on channel 01





802.11 n20 on channel 06



802.11 n20 on channel 06



802.11 n20 on channel 06



802.11 n20 on channel 06






802.11 n20 on channel 11



802.11 n20 on channel 11



802.11 n20 on channel 11




802.11 n20 on channel 11





802.11n40 on channel 03



802.11n40 on channel 03



802.11n40 on channel 03



802.11n40 on channel 03





802.11n40 on channel 06







802.11 n40 on channel 06



802.11 n40 on channel 06






802.11 n40 on channel 9



802.11 n40 on channel 9



802.11 n40 on channel 9



802.11 n40 on channel 9





7.10 ANTENNA APPLICATION

7.10.1 Antenna Requirement

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

7.10.2 Result

The EUT antenna is permanent attached FPCB antenna (Gain:2.1dBi). It comply with the standard requirement.

END OF REPORT