



Test Number: 420-17 Issue Date: 12/19/2017

7. Measurement Data (continued)

7.12. Public Exposure to Radio Frequency Energy Levels (15.247(i) (1.1307 (b)(1)) RSS-GEN, ISSUE 4 5.5, RSS 102)

7.12.1. 15.247(i) (1.1307 (b)(1) Requirements

Requirement: Portable devices are subject to radio frequency radiation exposure

requirements.

For a 1-g head or body SAR, the test exclusion result must be \leq 3.0. For a 10-g extremity SAR, the test exclusion result must be \leq 7.5.

Test Notes: The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by the

following formula:

SAR Test Exclusion =
$$\frac{P_{MAX}}{d_{MIN}} \times \sqrt{f_{(GHz)}}$$
 (1)

P_{MAX} mW Maximum power of channel, including tune-up tolerance

 d_{MIN} mm Minimum test separation distance, mm (≤ 50 mm)

 $f_{(GHz)}$ GHz $f_{(GHz)}$ is the RF channel transmit frequency in GHz (>100 MHz and <6 GHz)

 FCC OET 447498 - Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies.

Results:

Passed - The device under test meets the exclusion requirement detailed in FCC OET 447498.

Channel:		37	17	39	
Input ¹ :	P_{MAX}	4.864	3.811	3.899	mW
	d_{MIN}^2	5.00	5.00	5.00	mm
	$f_{(GHz)}$	2.402	2.440	2.480	GHz
Test Exclusion:		1.51	1.19	1.23	_
Limit Exemption:		3.0	3.0	3.0	

¹ Taken from column 3 of the table in Section 7.3 of this test report.

Measurement Result: Compliant Compliant Compliant

Worst Case UWB and BLE Radios Combined

UWB Test Exclusion: 0.094 Channel 3
BLE Test Exclusion: 1.510 Channel 37

TOTAL: 1.604

Limit Exemption: 3.0

When the minimum test separation distance is < 5 mm, a distance of 5 mm according to KDB 447498, 4.1 f) is applied to determine SAR test exclusion.





Test Number: 420-17 Issue Date: 12/19/2017

7. Measurement Data (continued)

7.12. Public Exposure to Radio Frequency Energy Levels (15.247(i) (1.1307 (b)(1)) RSS-GEN, ISSUE 4 5.5, RSS 102) (continued)

7.12.2. RSS-102 Issue 5 Requirements

Requirement: SAR evaluation is required if the separation distance between the

user and/or bystander and the antenna and/or radiating element of the device is less than or equal to 20 cm, except when the device operates at or below the applicable output power level (adjusted for tune-up tolerance) for the specified separation distance defined in Table 1. Portable devices are subject to radio frequency

radiation exposure requirements.

Test Notes: The limit was taken from Table 1 of RSS-102 Issue 5. For limb-

worn devices where the 10 gram value applies, the exemption limits for routine evaluation in Table 1 are multiplied by a factor of

2.5.

Results: Compliant

Bluetooth Radio

Frequency	Separation Distance	Maximum Power	RSS-102 Limit	Result	
MHz	mm	mW	mW		
2402	≤5	4.86	10.65	Compliant	
2440	≤5	3.81	10.14	Compliant	
2480	≤5	3.90	9.86	Compliant	

UWB Radio

OVB Nadio								
Frequency	Separation Distance			Result				
MHz	mm	mW	mW					
3498	≤5	0.186	5.01	Compliant				
4000	≤5	0.185	4.46	Compliant				
4492	≤5	0.221	3.92	Compliant				