

Test Number: 150-17

Issue Date: 8/3/2018

6. Measurement Data (continued)

6.11. Public Exposure to Radio Frequency Energy Levels (1.1307 (b)(1))

6.11.1. SAR Test Exclusion Calculation

Requirement: Portable devices as defined in § 2.1093 of this chapter operating under Part 15 are subject to radio frequency radiation exposure requirements as specified in §§ 1.1307(b) and 2.1093 of this chapter.

For a 1-g SAR, the test exclusion result must be ≤ 3.0 .

Test Notes: The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by the following formula:

$$\text{SAR Test Exclusion} = \frac{P_{\text{MAX}}}{d_{\text{MIN}}} \times \sqrt{f_{(\text{GHz})}} \quad (1)$$

P_{MAX} mW Maximum power of channel, including tune-up tolerance

d_{MIN} mm Minimum test separation distance, mm (≤ 50 mm)

$f_{(\text{GHz})}$ GHz $f_{(\text{GHz})}$ is the RF channel transmit frequency in GHz (>100 MHz and <6 GHz)

(1) FCC OET 447498 - Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies.

Result: The device under test meets the exclusion requirement detailed in FCC OET 447498.

		Channel 1	Channel 2	Channel 3	
Input:	P_{MAX}	0.1205	0.2198	0.1645	mW
	d_{MIN}	5.00	5.00	5.00	mm
	$f_{(\text{GHz})}$	3.4920	4.2448	4.4910	GHz
Test Exclusion:		0.045	0.091	0.070	
Limit Exemption:		3.000	3.000	3.000	

¹ Taken from the peak data in Section 6.5 of this test report (converted to mW).

The device does not exceed the test limit exemption and therefore a routine SAR Evaluation is not required

UWB and BLE radios do not operate simultaneously.

Test Number: 150-17

Issue Date: 8/3/2018

6. Measurement Data (continued)

6.11. Public Exposure to Radio Frequency Energy Levels (1.1307 (b)(1)), RSS-GEN, Issue 4 Section 3.2, RSS 102, Issue 5

6.11.2 RF Exposure for devices that operate above 6 GHz

Center Frequency (GHz)	MPE Distance (cm)	DUT Output Power (dBm)	DUT Antenna Gain (dBi)	Power Density		FCC Limit (mW/cm ²)	IC Limit (W/m ²)
				(mW/cm ²)	(W/m ²)		
(1)	(2)	(3)	(4)	(5)	(6)		
6.490	5	-7.36	0.0	0.0005846	0.0058459	1	10

$$PD = \frac{OP + AG}{(4 \times \pi \times d^2)}$$

1. Reference CFR 2.1093(b): For purposes of this section, a portable device is defined as a transmitting device designed to be used so that the radiating structure(s) of the device is/are within 5 centimeters of the body of the user.
2. Section 6.7 of this test report.
3. Data supplied by the client.
4. Power density is calculated from field strength measurement and antenna gain.
5. Reference CFR 1.1310, Table 1: Limits for Maximum Permissible Exposure (MPE), Section (B): Limits for General Population/Uncontrolled Exposure.
6. Reference IC RSS-102 Section 4 Table 4 RF Field Strength Limits for Devices Used by the General Public (Uncontrolled Environment)

Test Number: 150-17**Issue Date: 8/3/2018****6. Measurement Data (continued)****6.11. Public Exposure to Radio Frequency Energy Levels (1.1307 (b)(1))****Public Exposure to Radio Frequency Energy Levels 1.1307 (b)(1), RSS-GEN, Issue 4
Section 3.2, RSS 102****6.11.3. RSS-102 Issue 5 Requirements**

Requirement: SAR evaluation is required if the separation distance between the user and/or bystander and the antenna and/or radiating element of the device is less than or equal to 20 cm, except when the device operates at or below the applicable output power level (adjusted for tune-up tolerance) for the specified separation distance defined in Table 1. Portable devices are subject to radio frequency radiation exposure requirements.

Test Notes: The limit was taken from Table 1 of RSS-102 Issue 5. For limb-worn devices where the 10 gram value applies, the exemption limits for routine evaluation in Table 1 are multiplied by a factor of 2.5.

Results: Compliant

Frequency	Separation Distance	Maximum Power	RSS-102 Limit	Result
MHz	mm	mW	mW	
3492	≤5	0.121	5.04	Compliant
4245	≤5	0.220	4.19	Compliant
4491	≤5	0.164	3.92	Compliant