

TEST REPORT

Reference No...... : WTH24X11267260W001
FCC ID..... : 2ADXC-QAZWSXTX
Applicant..... : Shenzhen Lenkeng Technology Co.,Ltd
Address..... : West 4F,Jingguangxia Culture&Tech Park, 3 Guangxia Road, Shenzhen ,
China
Manufacturer..... : The same as Applicant
Address..... : The same as Applicant
Product Name..... : HDMI Wireless Extender
Model No..... : LKV699KVM-V2.0-TX
Standards..... : FCC Part 15.407
Date of Receipt sample..... : 2024-11-15
Date of Test..... : 2024-11-15 to 2024-12-09
Date of Issue..... : 2024-12-09
Test Report Form No..... : WTX_Part 15_407W
Test Result..... : **Pass**

Remarks:


The results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of approver.

Prepared By:

Waltek Testing Group (Shenzhen) Co., Ltd.

Address: 1/F., Room 101, Building 1, Hongwei Industrial Park, Liuxian 2nd Road,
Block 70 Bao'an District, Shenzhen, Guangdong, China
Tel.: +86-755-33663308 Fax.: +86-755-33663309 Email: sem@waltek.com.cn

Tested by:



Dashan Chen

Approved by:



Jason Su

TABLE OF CONTENTS

1. GENERAL INFORMATION	5
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	5
1.2 TEST STANDARDS	6
1.3 TEST METHODOLOGY	6
1.4 TABLE FOR PARAMETERS OF TEST SOFTWARE SETTING	6
1.5 EUT OPERATING DURING TEST	8
1.6 TEST FACILITY	8
1.7 EUT SETUP AND TEST MODE	9
1.8 MEASUREMENT UNCERTAINTY	11
1.9 TEST EQUIPMENT LIST AND DETAILS	12
2. SUMMARY OF TEST RESULTS	16
3. ANTENNA REQUIREMENT	17
3.1 STANDARD APPLICABLE	17
3.2 EVALUATION INFORMATION	17
4. AUTOMATICALLY DISCONTINUE TRANSMISSION	18
4.1 STANDARD APPLICABLE	18
4.2 SUMMARY OF TEST RESULTS	18
5. POWER SPECTRAL DENSITY	19
5.1 STANDARD APPLICABLE	19
5.2 TEST PROCEDURE	19
5.3 SUMMARY OF TEST RESULTS/PLOTS	20
6. EMISSION BANDWIDTH AND OCCUPIED BANDWIDTH	21
6.1 STANDARD APPLICABLE	21
6.2 TEST PROCEDURE	21
6.3 SUMMARY OF TEST RESULTS/PLOTS	23
7. MAXIMUM CONDUCTED OUTPUT POWER	24
7.1 STANDARD APPLICABLE	24
7.2 TEST PROCEDURE	24
7.3 SUMMARY OF TEST RESULTS/PLOTS	25
8. RADIATED SPURIOUS EMISSIONS	26
8.1 STANDARD APPLICABLE	26
8.2 TEST PROCEDURE	26
8.3 TEST RECEIVER SETUP	28
8.4 CORRECTED AMPLITUDE & MARGIN CALCULATION	28
8.5 SUMMARY OF TEST RESULTS/PLOTS	29
9. FREQUENCY STABILITY	71
9.1 STANDARD APPLICABLE	71
9.2 TEST PROCEDURE	71
9.3 SUMMARY OF TEST RESULTS/PLOTS	71
10 CONDUCTED EMISSIONS	72
10.1 TEST PROCEDURE	72
10.2 BASIC TEST SETUP BLOCK DIAGRAM	72
10.3 TEST RECEIVER SETUP	72
10.4 SUMMARY OF TEST RESULTS/PLOTS	72
APPENDIX SUMMARY	75
APPENDIX A	76
APPENDIX B	87
APPENDIX C	108
APPENDIX D	119

APPENDIX PHOTOGRAPHS 120

Report version

Version No.	Date of issue	Description
Rev.00	2024-12-09	Original
/	/	/

1. GENERAL INFORMATION

1.1 Product Description for Equipment Under Test (EUT)

General Description of EUT	
Product Name:	HDMI Wireless Extender
Trade Name:	LENKENG
Model No.:	LKV699KVM-V2.0-TX
Adding Model(s):	LKV699-V2.0-TX, LKV677-V2.0-TX, LKV677KVM-V2.0-TX,, LKV655-V2.0-TX, LKV655KVM-V2.0-TX
Rated Voltage:	DC5V
Battery Capacity:	/
Power Adapter:	S012-1D050200VU-V Input:AC100-240 50/60Hz 0.3A Output:DC5V2.0A
<i>Note: The test data is gathered from a production sample, provided by the manufacturer. The appearance of others models listed in the report is different from main-test model LKV699KVM-V2.0-TX, but the circuit and the electronic construction do not change, declared by the manufacturer.</i>	

Technical Characteristics of EUT	
Support Standards:	802.11a, 802.11n(HT20) , 802.11n-HT40, 802.11ac-VHT20, 802.11ac-VHT40,802.11ac-VHT80
Frequency Range:	5180-5240MHz
Max. RF Output Power:	Antenna 1: 15.67dBm (Conducted) Antenna 2: 15.67dBm (Conducted)
Type of Modulation:	QPSK, 16QAM, 64QAM, 256QAM
Type of Antenna:	External Antenna
Antenna Gain:	5.93dBi
<i>Note The Antenna Gain is provided by the customer and can affect the validity of results.</i>	

1.2 Test Standards

The tests were performed according to following standards:

FCC Rules Part 15.407: General technical requirements.

ANSI C63.10-2013: American National Standard for Testing Unlicensed Wireless Devices.

KDB789033 D02 v02r01: Guidelines for Compliance Testing of Unlicensed National Information Infrastructure (U-Nii) Devices Part 15, Subparte.

KDB662911 D01 Multiple Transmitter Output v02r01: Emissions Testing of Transmitters with Multiple Outputs in the Same Band.

Maintenance of compliance is the responsibility of the manufacturer. Any modification of the product, which result in lowering the emission, should be checked to ensure compliance has been maintained.

1.3 Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, KDB789033 D02 v02r01. The equipment under test (EUT) was configured to measure its highest possible emission level. The test modes were adapted accordingly in reference to the Operating Instructions.

1.4 Table for parameters of Test Software setting

Enter the fixed frequency using adb.exe, you can start to test. During testing, Channel and Power Controlling Software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product.

Mode	Test Frequency (MHz)											
	NCB: 20MHz											
	5180	5200	5240									
802.11a 6Mbps	14	14	14									
802.11n-HT20 MCS0	13	13	13									
802.11ac-VHT20 MCS0	13	13	13									
Mode	NCB: 40MHz											
	5190	5230										
802.11n-HT40 MCS0	12	12										
802.11ac-VHT40	12	12										

MCS0										
Mode	NCB: 80MHz									
	5210									
802.11ac-VHT8 0 MCS0/Nss2	11									

1.5 EUT Operating during test

EUT was programmed to be in continuously transmitting mode. During the test, EUT operation to normal function and programs under Android were executed.

1.6 Test Facility

Address of the test laboratory

Laboratory: Waltek Testing Group (Shenzhen) Co., Ltd.

Address: 1/F., Room 101, Building 1, Hongwei Industrial Park, Liuxian 2nd Road, Bao'an District, Shenzhen, P.R.C. (518101)

FCC – Registration No.: 125990

Waltek Testing Group (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files. The Designation Number is CN5010, and Test Firm Registration Number is 125990.

Industry Canada (IC) Registration No.: 11464A

The 3m Semi-anechoic chamber of Waltek Testing Group (Shenzhen) Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 11464A and the CAB identifier is CN0057.

1.7 EUT Setup and Test Mode

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements. All testing shall be performed under maximum output power condition, with a duty cycle equal to 100%, and to measure its highest possible emissions level, more detailed description as follows:

Test Mode List		
Test Mode	Description	Remark
TM1	802.11a	5180MHz,5200MHz,5240MHz
TM2	802.11n-HT20/802.11ac-VHT20	5180MHz,5200MHz,5240MHz
TM3	802.11n-HT40/802.11ac-VHT40	5190MHz,5230MHz
TM4	802.11ac-VHT80	5210MHz
Note1 : All test modes (different data rate and different modulation) are performed, but only the worst case is recorded in this report; Note 2: The 5GHz WIFI has two antennas and support Multiple Outputs for 802.11n/ac mode for this report; For 5150-5250MHz: Antenna 1 Gain is 5.93dBi; Antenna 2 Gain is 5.93dBi; According to KDB 662911, for same directional gain: For 5150-5250MHz: Directional gain = $G_{ANT} + 10 \log(N_{ANT})$ dBi = $5.93 + 10\log(2)$ dBi = 8.94dBi		

Test Conditions	
Temperature:	22~25 °C
Relative Humidity:	45~75 %
ATM Pressure:	1019 mbar

EUT Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
DC Cable	1.15	Unshielded	Without Ferrite
IR blaster extension cable	0.95	Unshielded	Without Ferrite
IR receiver extension cable	0.95	Unshielded	Without Ferrite
USB Cable	1.12	shielded	Without Ferrite

Special Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
HDMI Cable	0.8	Unshielded	Without Ferrite

Auxiliary Equipment List and Details			
Description	Manufacturer	Model	Serial Number
Notebook	ASUS	FA506IC	/
Displayer	Samsung	S32BG854NC	/
HDMI Wireless Extender	Lenkeng	LKV699KVM2.0-RX	/
HDMI Wireless Extender	Lenkeng	LKV699-2.0-RX	/
HDMI Wireless Extender	Lenkeng	LKV677KVM-2.0-RX	/
HDMI Wireless Extender	Lenkeng	LKV677-2.0-RX	/
HDMI Wireless Extender	Lenkeng	LKV655KVM-2.0-RX	/
HDMI Wireless Extender	Lenkeng	LKV655-2.0-RX	/

1.8 Measurement Uncertainty

Measurement uncertainty		
Parameter	Conditions	Uncertainty
RF Output Power	Conducted	$\pm 0.42\text{dB}$
Occupied Bandwidth	Conducted	$\pm 1.5\%$
Power Spectral Density	Conducted	$\pm 1.8\text{dB}$
Conducted Spurious Emission	Conducted	$\pm 2.17\text{dB}$
Conducted Emissions	Conducted	9-150kHz $\pm 3.74\text{dB}$
		0.15-30MHz $\pm 3.34\text{dB}$
Transmitter Spurious Emissions	Radiated	30-200MHz $\pm 4.52\text{dB}$
		0.2-1GHz $\pm 5.56\text{dB}$
		1-6GHz $\pm 3.84\text{dB}$
		6-18GHz $\pm 3.92\text{dB}$

1.9 Test Equipment List and Details

Fixed asset Number	Description	Manufacturer	Model	Serial No.	Cal Date	Due. Date
WTXE1041A 1001	Communication Tester	Rohde & Schwarz	CMW500	148650	2024-02-24	2025-02-23
WTXE1005A 1005	Spectrum Analyzer	Agilent	N9020A	US471401 02	2024-03-19	2025-03-18
WTXE1084A 1001	Spectrum Analyzer	Agilent	N9020A	MY543205 48	2024-02-24	2025-02-23
WTXE1004A 1-001	Spectrum Analyzer	Rohde & Schwarz	FSP40	100612	2024-02-27	2025-02-26
WTXE1103A 1003	Attenuator	Pasternack	PE4007-4	/	2024-02-24	2025-02-23
WTXE1003A 1-005	Coaxial Cable	/	0M4RFC	/	2024-07-03	2025-01-03
☐ Chamber A: Below 1GHz						
WTXE1005A 1003	Spectrum Analyzer	Rohde & Schwarz	FSP30	836079/03 5	2024-02-24	2025-02-23
WTXE1001A 1001	EMI Test Receiver	Rohde & Schwarz	ESPI	101611	2024-03-19	2025-03-18
WTXE1007A 1001	Amplifier	HP	8447F	2805A034 75	2024-02-24	2025-02-23
WTXE1010A 1007	Loop Antenna	Schwarz beck	FMZB 1516	9773	2024-02-26	2025-02-25
WTXE1010A 1006	Broadband Antenna	Schwarz beck	VULB9163	9163-333	2024-02-24	2025-02-23
WTXE1104A 1032-1	Coaxial Cable	/	RC_6G-N-M	/	2024-03-15	2025-03-14
WTXE1104A 1032-2	Coaxial Cable	/	RC_6G-N-M	/	2024-03-15	2025-03-14
WTXE1104A 1032-3	Coaxial Cable	/	RC_6G-N-M	/	2024-03-15	2025-03-14
☐ Chamber A: Above 1GHz						
WTXE1005A 1003	Spectrum Analyzer	Rohde & Schwarz	FSP30	836079/03 5	2024-02-24	2025-02-23
WTXE1001A 1001	EMI Test Receiver	Rohde & Schwarz	ESPI	101611	2024-03-19	2025-03-18
WTXE1065A 1001	Amplifier	C&D	PAP-1G18	2002	2024-02-27	2025-02-26
WTXE1010A 1005	Horn Antenna	ETS	3117	00086197	2024-02-26	2025-02-25

WTXE1010A 1010	DRG Horn Antenna	A.H. SYSTEMS	SAS-574	571	2024-03-17	2025-03-16
WTXE1003A 1001	Pre-amplifier	Schwarzbeck	BBV 9721	9721-031	2024-02-29	2025-02-28
WTXE1104A 1033-1	Coaxial Cable	/	C16-07-07	/	2024-03-15	2025-03-14
WTXE1104A 1033-2	Coaxial Cable	/	C16-07-07	/	2024-03-15	2025-03-14
WTXE1104A 1033-3	Coaxial Cable	/	C16-07-07	/	2024-03-15	2025-03-14
☐ Chamber B:Below 1GHz						
WTXE1010A 1006	Trilog Broadband Antenna	Schwarz beck	VULB9163(B)	9163-635	2024-03-17	2027-03-16
WTXE1038A 1001	Amplifier	Agilent	8447D	2944A104 57	2024-02-24	2025-02-23
WTXE1001A 1002	EMI Test Receiver	Rohde & Schwarz	ESPI	101391	2024-02-24	2025-02-23
WTXE1104A 1031-1	Coaxial Cable	/	1.5MRFC-LWB3	/	2024-07-03	2025-07-02
WTXE1104A 1031-2	Coaxial Cable	/	RG 316	/	2024-07-03	2025-07-02
WTXE1104A 1031-3	Coaxial Cable	/	RG 316	/	2024-07-03	2025-07-02
☒ Chamber C:Below 1GHz						
WTXE1093A 1001	EMI Test Receiver	Rohde & Schwarz	ESIB 26	100401	2024-02-27	2025-02-26
WTXE1010A 1013-1	Trilog Broadband Antenna	Schwarz beck	VULB 9168	1194	2024-04-18	2027-04-17
WTXE1007A 1002	Amplifier	HP	8447F	2944A038 69	2024-02-24	2025-02-23
WTXE1010A 1007	Loop Antenna	Schwarz beck	FMZB 1516	9773	2024-02-26	2025-02-25
WTXE1104A 1034-1	Coaxial Cable	/	RC_6G-N-M	/	2024-07-03	2025-07-02
WTXE1104A 1034-2	Coaxial Cable	/	RC_6G-N-M	/	2024-07-03	2025-07-02
WTXE1104A 1034-3	Coaxial Cable	/	RC_6G-N-M	/	2024-07-03	2025-07-02
☒ Chamber C: Above 1GHz						
WTXE1093A	EMI Test	Rohde &	ESIB 26	100401	2024-02-27	2025-02-26

1001	Receiver	Schwarz				
WTXE1103A 1005	Horn Antenna	POAM	RTF-118A	1820	2023-03-10	2026-03-09
WTXE1103A 1006	Amplifier	Tonscend	TAP01018050	AP22E806 235	2024-02-27	2025-02-26
WTXE1010A 1010	DRG Horn Antenna	A.H. SYSTEMS	SAS-574	571	2024-03-17	2025-03-16
WTXE1003A 1001	Pre-amplifier	Schwarzbeck	BBV 9721	9721-031	2024-02-29	2025-02-28
WTXE1104A 1035-1	Coaxial Cable	/	RC-18G-N-M	/	2024-07-03	2025-07-02
WTXE1104A 1035-2	Coaxial Cable	/	RC-18G-N-M	/	2024-07-03	2025-07-02
WTXE1104A 1035-3	Coaxial Cable	/	RC-18G-N-M	/	2024-07-03	2025-07-02
☐ Conducted Room 1#						
WTXE1104A 1029	EMI Test Receiver	Rohde & Schwarz	ESCI	100525	2023-12-12	2024-12-11
WTXE1002A 1001	Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100911	2024-02-24	2025-02-23
WTXE1003A 1001	AC LISN	Schwarz beck	NSLK8126	8126-279	2024-02-24	2025-02-23
WTXE1104A 1036	Coaxial Cable	/	RG 316	/	2024-07-03	2025-07-02
WTXE1104A 1038	Coaxial Cable	/	6MRFC-DP	/	2024-07-03	2025-07-02
☒ Conducted Room 2#						
WTXE1001A 1004	EMI Test Receiver	Rohde & Schwarz	ESPI	101259	2024-02-24	2025-02-23
WTXE1003A 1003	LISN	Rohde & Schwarz	ENV 216	100097	2024-02-24	2025-02-23
WTXE1104A 1037	Coaxial Cable	/	RG 316	/	2024-07-03	2025-07-02

Software List			
Description	Manufacturer	Model	Version
EMI Test Software (Radiated Emission A)	Farad	EZ-EMC	RA-03A1 (1.1.4.2)
EMI Test Software (Radiated Emission B)	Farad	EZ-EMC	RA-03A1 (1.1.4.2)
EMI Test Software (Radiated Emission C)	Farad	EZ-EMC	RA-03A1-2 (1.1.4.2)
EMI Test Software (Conducted Emission Room 1#)	Farad	EZ-EMC	3A1*CE-RE 1.1.4.3
EMI Test Software (Conducted Emission Room 2#)	Farad	EZ-EMC	3A1*CE-RE 1.1.4.3

*Remark: indicates software version used in the compliance certification testing.

2. SUMMARY OF TEST RESULTS

FCC Rules	Description of Test Item	Result
§15.203; §15.405	Antenna Requirement	Compliant
15.407 (c)	Automatically Discontinue Transmission	Compliant
§15.207; §15.407(b)(6)	Conducted Emission	Compliant
§15.407(a)(1),(2)	Power Spectral Density	Compliant
§15.407(e)	Emission Bandwidth and Occupied Bandwidth	Compliant
§15.407(a)(1),(2)	Maximum Conducted Output Power	Compliant
§15.407(b)(1),(2),(3),(4)	Undesirable emission	Compliant
§15.205; §15.407(b)(1),(2),(3)	Radiated Emission	Compliant
§15.407(g)	Frequency Stability	Compliant
§15.407(h)	Dynamic Frequency Selection (DFS)	Compliant

N/A: Not applicable.

3. Antenna Requirement

3.1 Standard Applicable

According to FCC Part 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

3.2 Evaluation Information

This product has two External antennas, fulfill the requirement of this section.

4. Automatically Discontinue Transmission

4.1 Standard Applicable

According to FCC Part 15.407(c), the device shall automatically discontinue transmission in case of either absence of information to transmit or operational failure. These provisions are not intended to preclude the transmission of control or signaling information or the use of repetitive codes used by certain digital technologies to complete frame or burst intervals. Applicants shall include in their application for equipment authorization to describe how this requirement is met.

4.2 Summary of Test Results

While the EUT is not transmitting any information, the EUT can automatically discontinue transmission and become standby mode for power saving. The EUT can detect the controlling signal of ACK message transmitting from remote device and verify whether it shall resend or discontinue transmission.

5. Power Spectral Density

5.1 Standard Applicable

Section 15.407(a) Power limits:

(1) For the band 5.15-5.25GHz.

(iv) For mobile and portable client devices in the 5.15-5.25GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250mW provided the maximum antenna gain does not exceed 6dBi. In addition, the maximum power spectral density shall not exceed 11dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

(2) For the 5.25-5.35GHz and 5.47-5.725GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250mW or $11\text{dBm} + 10 \log B$, where B is the 26dB emission bandwidth in megahertz. In addition, the maximum power spectral density shall not exceed 11dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

(3) For the band 5.725-5.85GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 30dBm in any 500kHz band. If transmitting antennas of directional gain greater than 6dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

5.2 Test Procedure

According to 789033 D02 v02r01 General UNII Test Procedures New Rules v02, the following is the measurement procedure.

For devices operating in the bands 5.15-5.25GHz, 5.25-5.35GHz, and 5.47-5.725GHz, the above procedures make use of 1MHz RBW to satisfy directly the 1MHz reference bandwidth specified in § 15.407(a)(5). For devices operating in the band 5.725-5.85GHz, the rules specify a measurement bandwidth of 500kHz. Many spectrum analyzers do not have 500kHz RBW, thus a narrower RBW may need to be used. The rules permit the use of a RBWs less than 1MHz, or 500kHz, "provided that the measured power is integrated over the full

reference bandwidth” to show the total power over the specified measurement bandwidth (i.e., 1MHz, or 500kHz). If measurements are performed using a reduced resolution bandwidth ($< 1\text{ MHz}$, or $< 500\text{kHz}$) and integrated over 1 MHz, or 500kHz bandwidth, the following adjustments to the procedures apply:

- a) Set $\text{RBW} \geq 1/T$, where T is defined in section II.B.I.a).
- b) Set $\text{VBW} \geq 3\text{ RBW}$.
- c) If measurement bandwidth of Maximum PSD is specified in 500kHz, add $10\log(500\text{kHz}/\text{RBW})$ to the measured result, whereas $\text{RBW} (< 500\text{kHz})$ is the reduced resolution bandwidth of the spectrum analyzer set during measurement.
- d) If measurement bandwidth of Maximum PSD is specified in 1MHz, add $10\log(1\text{MHz}/\text{RBW})$ to the measured result, whereas $\text{RBW} (< 1\text{MHz})$ is the reduced resolution bandwidth of spectrum analyzer set during measurement.
- e) Care must be taken to ensure that the measurements are performed during a period of continuous transmission or are corrected upward for duty cycle.

Note: As a practical matter, it is recommended to use reduced RBW of 100kHz for the sections 5.c) and 5.d) above, since $\text{RBW}=100\text{kHz}$ is available on nearly all spectrum analyzers.

5.3 Summary of Test Results/Plots

Please refer to Appendix A

6. Emission Bandwidth and Occupied Bandwidth

6.1 Standard Applicable

According to 15.407(a) and (e):

(1) For the band 5.15-5.25GHz.

(iv) For mobile and portable client devices in the 5.15-5.25GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250mW provided the maximum antenna gain does not exceed 6dBi. In addition, the maximum power spectral density shall not exceed 11dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

(2) For the 5.25-5.35GHz and 5.47-5.725GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250mW or $11\text{dBm} + 10 \log B$, where B is the 26dB emission bandwidth in megahertz. In addition, the maximum power spectral density shall not exceed 11dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

(3) For the band 5.725-5.85GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 30dBm in any 500kHz band. If transmitting antennas of directional gain greater than 6dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

(e) Within the 5.725-5.85GHz band, the minimum 6dB bandwidth of U-NII devices shall be at least 500kHz.

6.2 Test Procedure

According to 789033 D02 v02r0r section C&D, the following is the measurement procedure.

1. Emission Bandwidth (EBW)

a) Set RBW = approximately 1% of the emission bandwidth.

b) Set the VBW > RBW.

- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Measure the maximum width of the emission that is 26dB down from the maximum of the emission. Compare this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1%.

2. Minimum Emission Bandwidth for the band 5.725-5.85GHz

Section 15.407(e) specifies the minimum 6dB emission bandwidth of at least 500kHz for the band 5.715-5.85GHz. The following procedure shall be used for measuring this bandwidth:

- a) Set RBW = 100kHz.
- b) Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Sweep = auto couple.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

Note: The automatic bandwidth measurement capability of a spectrum analyzer or EMI receiver may be employed if it implements the functionality described above.

D. 99 Percent Occupied Bandwidth

The 99-percent occupied bandwidth is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers are each equal to 0.5 % of the total mean power of the given emission. Measurement of the 99-percent occupied bandwidth is required only as a condition for using the optional band-edge measurement techniques described in section II.G.3.d). Measurements of 99-percent occupied bandwidth may also optionally be used in lieu of the EBW to 789033 D02 v02r01 General UNII Test Procedures New Rules v01 define the minimum frequency range over which the spectrum is integrated when measuring maximum conducted output power as described in section II.E. However, the EBW must be measured to determine bandwidth dependent limits on maximum conducted output power in accordance with 15.407(a).

The following procedure shall be used for measuring (99 %) power bandwidth:

- 1. Set center frequency to the nominal EUT channel center frequency.
- 2. Set span = 1.5 times to 5.0 times the OBW.
- 3. Set RBW = 1 % to 5 % of the OBW
- 4. Set VBW $\geq 3 \times$ RBW
- 5. Video averaging is not permitted. Where practical, a sample detection and single sweep mode shall be used. Otherwise, peak detection and max hold mode (until the trace stabilizes) shall be used.
- 6. Use the 99 % power bandwidth function of the instrument (if available).
- 7. If the instrument does not have a 99 % power bandwidth function, the trace data points are recovered and directly summed in power units. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5 % of the total is reached; that frequency is recorded as the lower frequency.

Reference No.: WTH24X11267260W001

The process is repeated until 99.5 % of the total is reached; that frequency is recorded as the upper frequency. The 99% occupied bandwidth is the difference between these two frequencies.

6.3 Summary of Test Results/Plots

Please refer to Appendix B

7. Maximum Conducted Output Power

7.1 Standard Applicable

Section 15.407(a) Power limits:

(1) For the band 5.15-5.25GHz.

(iv) For mobile and portable client devices in the 5.15-5.25GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250mW provided the maximum antenna gain does not exceed 6dBi. In addition, the maximum power spectral density shall not exceed 11dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

(2) For the 5.25-5.35GHz and 5.47-5.725GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250mW or $11\text{dBm} + 10 \log B$, where B is the 26dB emission bandwidth in megahertz. In addition, the maximum power spectral density shall not exceed 11dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

(3) For the band 5.725-5.85GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 30dBm in any 500kHz band. If transmitting antennas of directional gain greater than 6dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

7.2 Test Procedure

According to KDB789033 D02 v02r01 section E, the following is the measurement procedure.

- (i) Set span to encompass the entire emission bandwidth (EBW) (or, alternatively, the entire 99% occupied bandwidth) of the signal.
- (ii) Set RBW = 1MHz.
- (iii) Set VBW $\geq$ 3MHz.
- (iv) Number of points in sweep $\geq$ 2 Span / RBW. (This ensures that bin-to-bin spacing is $\leq$ RBW/2, so that

narrowband signals are not lost between frequency bins.)

(v) Sweep time = auto.

(vi) Detector = RMS (i.e., power averaging), if available. Otherwise, use sample detector mode.

(vii) If transmit duty cycle < 98 percent, use a video trigger with the trigger level set to enable triggering only on full power pulses. Transmitter must operate at maximum power control level for the entire duration of every sweep. If the EUT transmits continuously (i.e., with no off intervals) or at duty cycle ≥ 98 percent, and if each transmission is entirely at the maximum power control level, then the trigger shall be set to "free run".

(viii) Trace average at least 100 traces in power averaging (i.e., RMS) mode.

(ix) Compute power by integrating the spectrum across the EBW (or, alternatively, the entire 99% occupied bandwidth) of the signal using the instrument's band power measurement function with band limits set equal to the EBW (or occupied bandwidth) band edges. If the instrument does not have a band power function, sum the spectrum levels (in power units) at 1 MHz intervals extending across the EBW (or, alternatively, the entire 99% occupied bandwidth) of the spectrum.

7.3 Summary of Test Results/Plots

Please refer to Appendix C

8. Radiated Spurious Emissions

8.1 Standard Applicable

According to §15.407(b), undesirable emission limits. Except as shown in paragraph (b)(7) of this section, the maximum emissions outside of the frequency bands of operation shall be attenuated in accordance with the following limits:

- (1) For transmitters operating in the 5.15-5.25GHz band: All emissions outside of the 5.15-5.35GHz band shall not exceed an e.i.r.p. of -27dBm/MHz.
- (2) For transmitters operating in the 5.25-5.35GHz band: All emissions outside of the 5.15-5.35GHz band shall not exceed an e.i.r.p. of -27dBm/MHz.
- (3) For transmitters operating in the 5.47-5.725GHz band: All emissions outside of the 5.47-5.725GHz band shall not exceed an e.i.r.p. of -27dBm/MHz.
- (4) For transmitters operating in the 5.725-5.85GHz band:
 - (i) All emissions shall be limited to a level of -27dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10dBm/MHz at 25MHz above or below the band edge, and from 25MHz above or below the band edge increasing linearly to a level of 15.6dBm/MHz at 5MHz above or below the band edge, and from 5MHz above or below the band edge increasing linearly to a level of 27dBm/MHz at the band edge.

According to §15.407(b)(6), Unwanted emissions below 1GHz must comply with the general field strength limits set forth in §15.209. Further, any U-NII devices using an AC power line are required to comply also with the conducted limits set forth in §15.207.

According to §15.407(b)(7), The provisions of §15.205 apply to intentional radiators operating under this section.

789033 D02 v02r01 General UNII Test Procedures New Rules v01

If radiated measurements are performed, field strength is then converted to EIRP as follows:

$$\text{EIRP} = ((E \cdot d)^2) / 30$$

where:

- E is the field strength in V/m;
- d is the measurement distance in meters;
- EIRP is the equivalent isotropically radiated power in watts.


8.2 Test Procedure

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.205 15.407(b)(6) and FCC Part 15.209 Limit..


The external I/O cables were draped along the test table and formed a bundle 30 to 40cm long in the middle.

The spacing between the peripherals was 10cm.


The test setup for emission measurement below 30MHz.



The test setup for emission measurement from 30 MHz to 1 GHz.



The test setup for emission measurement above 1GHz.



8.3 Test Receiver Setup

During the radiated emission test for above 1GHz, the test receiver was set with the following configurations:

For peak detector:

RBW = 1000kHz, VBW = 3000kHz, Sweep Time = Auto

For average detector:

RBW = 1000kHz, VBW = 10Hz, Sweep Time = Auto

8.4 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated adding the Antenna Factor and the Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Indicated Reading} + \text{Ant. Factor} + \text{Cable Loss} - \text{Ampl. Gain}$$

The "**Margin**" column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of $-6\text{dB}\mu\text{V}$ means the emission is $6\text{dB}\mu\text{V}$ below the maximum limit for Class B. The equation for margin calculation is as follows:


$$\text{Margin} = \text{Corr. Ampl.} - \text{FCC Part 15 Limit}$$

8.5 Summary of Test Results/Plots

Note: this EUT was tested in 3 orthogonal positions and the worst case position data was reported.


- Spurious Emission From 30MHz to 1GHz
Model: LKV699KVM-V2.0-TX
- Antenna 1(Worst case)
- 5150-5250MHz

802.11a			
Test Channel	5180MHz(Worst case)	Polarity:	Horizontal




No.	Frequency (MHz)	Reading (dBuV/m)	Corr. dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Deg. ()	Height (cm)	Remark
1	48.3780	29.12	-7.71	21.41	40.00	-18.59	-	-	peak
2	61.8676	28.49	-8.77	19.72	40.00	-20.28	-	-	peak
3	151.0252	28.77	-8.05	20.72	43.50	-22.78	-	-	peak
4	211.6112	32.35	-11.59	20.76	43.50	-22.74	-	-	peak
5	409.6506	29.29	-6.06	23.23	46.00	-22.77	-	-	peak
6	925.6132	34.66	2.72	37.38	46.00	-8.62	-	-	peak

802.11a			
Test Channel	5180MHz(Worst case)	Polarity:	Vertical




No.	Frequency (MHz)	Reading (dBuV/m)	Corr. dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Deg. ()	Height (cm)	Remark
1	42.9305	29.23	-7.96	21.27	40.00	-18.73	-	-	peak
2	71.2033	29.54	-10.52	19.02	40.00	-20.98	-	-	peak
3	148.9175	29.60	-8.14	21.46	43.50	-22.04	-	-	peak
4	171.3890	30.95	-8.51	22.44	43.50	-21.06	-	-	peak
5	338.8546	27.91	-7.18	20.73	46.00	-25.27	-	-	peak
6	527.5707	29.64	-4.24	25.40	46.00	-20.60	-	-	peak

802.11n-HT20			
Test Channel	5180MHz(worst case)	Polarity:	Horizontal




No.	Frequency (MHz)	Reading (dBuV/m)	Corr. dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Deg. ()	Height (cm)	Remark
1	61.0041	27.72	-8.61	19.11	40.00	-20.89	-	-	peak
2	78.5645	28.14	-12.13	16.01	40.00	-23.99	-	-	peak
3	151.0252	27.96	-8.05	19.91	43.50	-23.59	-	-	peak
4	219.1785	32.51	-11.51	21.00	46.00	-25.00	-	-	peak
5	430.3053	28.69	-5.62	23.07	46.00	-22.93	-	-	peak
6	925.6132	34.56	2.72	37.28	46.00	-8.72	-	-	peak

802.11n-HT20			
Test Channel	5180MHz(worst case)	Polarity:	Vertical




No.	Frequency (MHz)	Reading (dBuV/m)	Corr. dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Deg. ()	Height (cm)	Remark
1	40.5837	28.91	-7.96	20.95	40.00	-19.05	-	-	peak
2	59.3133	27.57	-8.39	19.18	40.00	-20.82	-	-	peak
3	165.4716	28.59	-8.19	20.40	43.50	-23.10	-	-	peak
4	322.5896	27.91	-7.38	20.53	46.00	-25.47	-	-	peak
5	481.5112	28.17	-4.94	23.23	46.00	-22.77	-	-	peak
6	798.6205	31.32	0.98	32.30	46.00	-13.70	-	-	peak

802.11ac-VHT20			
Test Channel	5180MHz(worst case)	Polarity:	Horizontal




No.	Frequency (MHz)	Reading (dBuV/m)	Corr. dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Deg. ()	Height (cm)	Remark
1	37.3017	26.56	-8.53	18.03	40.00	-21.97	-	-	peak
2	58.0759	27.40	-8.32	19.08	40.00	-20.92	-	-	peak
3	124.9249	28.45	-9.67	18.78	43.50	-24.72	-	-	peak
4	216.1197	31.79	-11.55	20.24	46.00	-25.76	-	-	peak
5	452.0013	28.96	-5.17	23.79	46.00	-22.21	-	-	peak
6	925.6132	32.70	2.72	35.42	46.00	-10.58	-	-	peak

802.11ac-VHT20			
Test Channel	5180MHz(worst case)	Polarity:	Vertical




No.	Frequency (MHz)	Reading (dBuV/m)	Corr. dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Deg. ()	Height (cm)	Remark
1	46.7077	27.31	-7.83	19.48	40.00	-20.52	-	-	peak
2	100.4712	30.80	-11.95	18.85	43.50	-24.65	-	-	peak
3	166.6385	29.77	-8.23	21.54	43.50	-21.96	-	-	peak
4	346.0740	28.71	-7.10	21.61	46.00	-24.39	-	-	peak
5	558.0788	29.08	-3.33	25.75	46.00	-20.25	-	-	peak
6	728.8971	29.70	-0.36	29.34	46.00	-16.66	-	-	peak

802.11n-HT40			
Test Channel	5190MHz(worst case)	Polarity:	Horizontal




No.	Frequency (MHz)	Reading (dBuV/m)	Corr. dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Deg. ()	Height (cm)	Remark
1	49.4087	28.37	-7.63	20.74	40.00	-19.26	-	-	peak
2	163.1623	28.28	-8.13	20.15	43.50	-23.35	-	-	peak
3	216.1197	31.28	-11.55	19.73	46.00	-26.27	-	-	peak
4	298.5932	27.89	-7.90	19.99	46.00	-26.01	-	-	peak
5	520.2079	29.11	-4.41	24.70	46.00	-21.30	-	-	peak
6	925.6132	32.38	2.72	35.10	46.00	-10.90	-	-	peak

802.11n-HT40			
Test Channel	5190MHz(worst case)	Polarity:	Vertical




No.	Frequency (MHz)	Reading (dBuV/m)	Corr. dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Deg. ()	Height (cm)	Remark
1	41.4483	29.74	-7.96	21.78	40.00	-18.22	-	-	peak
2	100.4712	30.75	-11.95	18.80	43.50	-24.70	-	-	peak
3	124.9249	28.52	-9.67	18.85	43.50	-24.65	-	-	peak
4	201.4539	32.65	-11.42	21.23	43.50	-22.27	-	-	peak
5	474.7913	29.51	-4.99	24.52	46.00	-21.48	-	-	peak
6	739.2136	29.36	-0.09	29.27	46.00	-16.73	-	-	peak

802.11ac-VHT40			
Test Channel	5190MHz(worst case)	Polarity:	Horizontal




No.	Frequency (MHz)	Reading (dBuV/m)	Corr. dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Deg. ()	Height (cm)	Remark
1	40.5837	26.41	-7.96	18.45	40.00	-21.55	-	-	peak
2	66.3715	27.49	-9.59	17.90	40.00	-22.10	-	-	peak
3	140.7767	28.65	-8.83	19.82	43.50	-23.68	-	-	peak
4	216.1197	32.51	-11.55	20.96	46.00	-25.04	-	-	peak
5	387.2565	28.30	-6.43	21.87	46.00	-24.13	-	-	peak
6	925.6132	32.91	2.72	35.63	46.00	-10.37	-	-	peak

802.11ac-VHT40			
Test Channel	5190MHz(worst case)	Polarity:	Vertical




No.	Frequency (MHz)	Reading (dBuV/m)	Corr. dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Deg. ()	Height (cm)	Remark
1	41.7406	29.77	-7.95	21.82	40.00	-18.18	-	-	peak
2	64.9869	28.61	-9.33	19.28	40.00	-20.72	-	-	peak
3	151.0252	28.81	-8.05	20.76	43.50	-22.74	-	-	peak
4	201.4539	31.78	-11.42	20.36	43.50	-23.14	-	-	peak
5	406.7820	29.31	-6.12	23.19	46.00	-22.81	-	-	peak
6	781.9606	29.71	0.70	30.41	46.00	-15.59	-	-	peak

802.11ac-VHT80			
Test Channel	5210MHz(worst case)	Polarity:	Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Corr. dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Deg. ()	Height (cm)	Remark
1	41.7406	27.82	-7.95	19.87	40.00	-20.13	-	-	peak
2	53.7559	26.76	-7.99	18.77	40.00	-21.23	-	-	peak
3	119.7672	28.72	-10.03	18.69	43.50	-24.81	-	-	peak
4	220.7241	31.63	-11.48	20.15	46.00	-25.85	-	-	peak
5	468.1651	28.65	-5.05	23.60	46.00	-22.40	-	-	peak
6	925.6132	33.62	2.72	36.34	46.00	-9.66	-	-	peak

802.11ac-VHT80			
Test Channel	5210MHz(worst case)	Polarity:	Vertical




No.	Frequency (MHz)	Reading (dBuV/m)	Corr. dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Deg. ()	Height (cm)	Remark
1	51.8999	28.30	-7.79	20.51	40.00	-19.49	-	-	peak
2	86.0796	31.63	-12.53	19.10	40.00	-20.90	-	-	peak
3	175.0404	29.91	-9.03	20.88	43.50	-22.62	-	-	peak
4	255.8226	29.86	-9.47	20.39	46.00	-25.61	-	-	peak
5	452.0013	28.95	-5.17	23.78	46.00	-22.22	-	-	peak
6	887.3978	31.47	1.95	33.42	46.00	-12.58	-	-	peak

Model: LKV699-V2.0-TX


- Antenna 1(Worst case)
- 5150-5250MHz

802.11a			
Test Channel	5180MHz(Worst case)	Polarity:	Horizontal




No.	Frequency (MHz)	Reading (dBuV/m)	Corr. dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Deg. ()	Height (cm)	Remark
1	57.6693	27.78	-8.29	19.49	40.00	-20.51	-	-	peak
2	147.8747	28.22	-8.22	20.00	43.50	-23.50	-	-	peak
3	220.7241	31.68	-11.48	20.20	46.00	-25.80	-	-	peak
4	252.2523	30.48	-9.61	20.87	46.00	-25.13	-	-	peak
5	516.5651	29.32	-4.48	24.84	46.00	-21.16	-	-	peak
6	925.6132	32.44	2.72	35.16	46.00	-10.84	-	-	peak

802.11a			
Test Channel	5180MHz(Worst case)	Polarity:	Vertical




No.	Frequency (MHz)	Reading (dBuV/m)	Corr. dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Deg. ()	Height (cm)	Remark
1	41.1581	29.26	-7.96	21.30	40.00	-18.70	-	-	peak
2	75.3208	28.93	-11.42	17.51	40.00	-22.49	-	-	peak
3	168.9970	28.66	-8.29	20.37	43.50	-23.13	-	-	peak
4	334.1255	28.68	-7.23	21.45	46.00	-24.55	-	-	peak
5	562.0143	31.11	-3.20	27.91	46.00	-18.09	-	-	peak
6	952.0001	31.05	3.31	34.36	46.00	-11.64	-	-	peak

802.11n-HT20			
Test Channel	5180MHz(worst case)	Polarity:	Horizontal




No.	Frequency (MHz)	Reading (dBuV/m)	Corr. dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Deg. ()	Height (cm)	Remark
1	37.0405	27.68	-8.58	19.10	40.00	-20.90	-	-	peak
2	64.5319	26.58	-9.25	17.33	40.00	-22.67	-	-	peak
3	144.7899	27.69	-8.49	19.20	43.50	-24.30	-	-	peak
4	207.1968	31.29	-11.55	19.74	43.50	-23.76	-	-	peak
5	531.2910	28.85	-4.12	24.73	46.00	-21.27	-	-	peak
6	925.6132	33.77	2.72	36.49	46.00	-9.51	-	-	peak

802.11n-HT20			
Test Channel	5180MHz(worst case)	Polarity:	Vertical




No.	Frequency (MHz)	Reading (dBuV/m)	Corr. dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Deg. ()	Height (cm)	Remark
1	43.8452	28.30	-7.96	20.34	40.00	-19.66	-	-	peak
2	60.1528	29.12	-8.46	20.66	40.00	-19.34	-	-	peak
3	128.4862	27.54	-9.43	18.11	43.50	-25.39	-	-	peak
4	162.0197	29.11	-8.10	21.01	43.50	-22.49	-	-	peak
5	461.6313	29.56	-5.09	24.47	46.00	-21.53	-	-	peak
6	749.6761	29.49	0.17	29.66	46.00	-16.34	-	-	peak

802.11ac-VHT20			
Test Channel	5180MHz(worst case)	Polarity:	Horizontal




No.	Frequency (MHz)	Reading (dBuV/m)	Corr. dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Deg. ()	Height (cm)	Remark
1	43.8452	28.84	-7.96	20.88	40.00	-19.12	-	-	peak
2	60.1528	27.15	-8.46	18.69	40.00	-21.31	-	-	peak
3	149.9676	28.22	-8.04	20.18	43.50	-23.32	-	-	peak
4	217.6437	32.34	-11.52	20.82	46.00	-25.18	-	-	peak
5	498.7303	29.35	-4.82	24.53	46.00	-21.47	-	-	peak
6	925.6132	33.41	2.72	36.13	46.00	-9.87	-	-	peak

802.11ac-VHT20			
Test Channel	5180MHz(worst case)	Polarity:	Vertical




No.	Frequency (MHz)	Reading (dBuV/m)	Corr. dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Deg. ()	Height (cm)	Remark
1	40.8699	28.68	-7.95	20.73	40.00	-19.27	-	-	peak
2	89.7866	31.77	-12.59	19.18	43.50	-24.32	-	-	peak
3	151.0252	29.07	-8.05	21.02	43.50	-22.48	-	-	peak
4	255.8226	28.85	-9.47	19.38	46.00	-26.62	-	-	peak
5	546.4368	28.89	-3.65	25.24	46.00	-20.76	-	-	peak
6	925.6132	31.56	2.72	34.28	46.00	-11.72	-	-	peak

802.11n-HT40			
Test Channel	5190MHz(worst case)	Polarity:	Horizontal




No.	Frequency (MHz)	Reading (dBuV/m)	Corr. dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Deg. ()	Height (cm)	Remark
1	41.4483	27.12	-7.96	19.16	40.00	-20.84	-	-	peak
2	70.2096	26.99	-10.30	16.69	40.00	-23.31	-	-	peak
3	170.1888	28.42	-8.34	20.08	43.50	-23.42	-	-	peak
4	207.1968	32.23	-11.55	20.68	43.50	-22.82	-	-	peak
5	520.2079	28.78	-4.41	24.37	46.00	-21.63	-	-	peak
6	925.6132	34.01	2.72	36.73	46.00	-9.27	-	-	peak

802.11n-HT40			
Test Channel	5190MHz(worst case)	Polarity:	Vertical




No.	Frequency (MHz)	Reading (dBuV/m)	Corr. dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Deg. ()	Height (cm)	Remark
1	44.4657	28.06	-7.96	20.10	40.00	-19.90	-	-	peak
2	68.7450	28.01	-10.03	17.98	40.00	-22.02	-	-	peak
3	151.0252	29.79	-8.05	21.74	43.50	-21.76	-	-	peak
4	201.4539	31.03	-11.42	19.61	43.50	-23.89	-	-	peak
5	392.7376	28.11	-6.36	21.75	46.00	-24.25	-	-	peak
6	698.8035	31.70	-1.11	30.59	46.00	-15.41	-	-	peak

802.11ac-VHT40			
Test Channel	5190MHz(worst case)	Polarity:	Horizontal




No.	Frequency (MHz)	Reading (dBuV/m)	Corr. dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Deg. ()	Height (cm)	Remark
1	39.1825	26.89	-8.12	18.77	40.00	-21.23	-	-	peak
2	49.7571	26.67	-7.59	19.08	40.00	-20.92	-	-	peak
3	142.7692	27.59	-8.66	18.93	43.50	-24.57	-	-	peak
4	216.1197	31.99	-11.55	20.44	46.00	-25.56	-	-	peak
5	488.3263	28.69	-4.90	23.79	46.00	-22.21	-	-	peak
6	925.6132	33.97	2.72	36.69	46.00	-9.31	-	-	peak

802.11ac-VHT40			
Test Channel	5190MHz(worst case)	Polarity:	Vertical



No.	Frequency (MHz)	Reading (dBuV/m)	Corr. dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Deg. ()	Height (cm)	Remark
1	39.4588	28.92	-8.07	20.85	40.00	-19.15	-	-	peak
2	86.0796	29.68	-12.53	17.15	40.00	-22.85	-	-	peak
3	151.0252	29.84	-8.05	21.79	43.50	-21.71	-	-	peak
4	201.4539	31.12	-11.42	19.70	43.50	-23.80	-	-	peak
5	353.4472	29.86	-7.00	22.86	46.00	-23.14	-	-	peak
6	582.1122	28.64	-2.68	25.96	46.00	-20.04	-	-	peak

802.11ac-VHT80			
Test Channel	5210MHz(worst case)	Polarity:	Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Corr. dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Deg. ()	Height (cm)	Remark
1	49.7571	26.71	-7.59	19.12	40.00	-20.88	-	-	peak
2	64.9869	27.87	-9.33	18.54	40.00	-21.46	-	-	peak
3	165.4716	28.54	-8.19	20.35	43.50	-23.15	-	-	peak
4	296.5023	29.60	-7.98	21.62	46.00	-24.38	-	-	peak
5	542.6104	29.02	-3.78	25.24	46.00	-20.76	-	-	peak
6	925.6132	34.39	2.72	37.11	46.00	-8.89	-	-	peak


802.11ac-VHT80

Test Channel

5210MHz(worst case)

Polarity:

Vertical




No.	Frequency (MHz)	Reading (dBuV/m)	Corr. dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Deg. ()	Height (cm)	Remark
1	40.5837	28.56	-7.96	20.60	40.00	-19.40	-	-	peak
2	51.8999	27.23	-7.79	19.44	40.00	-20.56	-	-	peak
3	100.4712	29.62	-11.95	17.67	43.50	-25.83	-	-	peak
4	165.4716	28.71	-8.19	20.52	43.50	-22.98	-	-	peak
5	401.1050	28.85	-6.24	22.61	46.00	-23.39	-	-	peak
6	952.0001	29.85	3.31	33.16	46.00	-12.84	-	-	peak

Remark: '-' Means the test Degree and Height are not recorded by the test software and only show the worst case in the test report.


- Spurious Emission above 1GHz
- Antenna 1(worst case)

802.11a- Restricted Bandedge			
Test Channel	band 5.15-5.25GHz	Polarity:	Horizontal(worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Corr. dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Deg. ()	Height (cm)	Remark
1	5148.697	66.53	-12.53	54.00	74.00	-20.00	-	-	peak

802.11a- Restricted Bandedge			
Test Channel	band 5.15-5.25GHz	Polarity:	Horizontal(worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	5150.000	51.57	-12.53	39.04	54.00	-14.96	-	-	AVG

802.11n-HT20- Restricted Bandedge			
Test Channel	band 5.15-5.25GHz	Polarity:	Horizontal(worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	5148.697	68.20	-12.53	55.67	74.00	-18.33	-	-	peak

802.11n-HT20- Restricted Bandedge			
Test Channel	band 5.15-5.25GHz	Polarity:	Horizontal(worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	5150.000	51.45	-12.53	38.92	54.00	-15.08	-	-	AVG

802.11ac-VHT20- Restricted Bandedge			
Test Channel	band 5.15-5.25GHz	Polarity:	Horizontal(worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	5146.092	67.36	-12.55	54.81	74.00	-19.19	-	-	peak

802.11ac-VHT20- Restricted Bandedge			
Test Channel	band 5.15-5.25GHz	Polarity:	Horizontal(worst case)



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	5150.000	51.45	-12.53	38.92	54.00	-15.08	-	-	AVG

802.11n-HT40- Restricted Bandedge			
Test Channel	band 5.15-5.25GHz	Polarity:	Horizontal(worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	5150.000	75.37	-12.53	62.84	74.00	-11.16	-	-	peak

802.11n-HT40- Restricted Bandedge			
Test Channel	band 5.15-5.25GHz	Polarity:	Horizontal(worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	5150.000	53.18	-12.53	40.65	54.00	-13.35	-	-	AVG

802.11ac-VHT40- Restricted Bandedge			
Test Channel	band 5.15-5.25GHz	Polarity:	Horizontal(worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	5147.395	76.35	-12.54	63.81	74.00	-10.19	-	-	peak

802.11ac-VHT40- Restricted Bandedge			
Test Channel	band 5.15-5.25GHz	Polarity:	Horizontal(worst case)



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	5150.000	58.96	-12.53	46.43	54.00	-7.57	-	-	AVG

802.11ac-VHT80- Restricted Bandedge			
Test Channel	band 5.15-5.25GHz	Polarity:	Horizontal(worst case)



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	5150.000	72.86	-12.53	60.33	74.00	-13.67	-	-	peak

802.11ac-VHT80- Restricted Bandedge			
Test Channel	band 5.15-5.25GHz	Polarity:	Horizontal(worst case)



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	5148.697	48.53	-12.53	36.00	54.00	-18.00	-	-	AVG

Note: The Restricted Bandedge was tested in Horizontal /Vertical and the worst case position data was reported.

Remark: ‘-’Means’ the test Degree and Height is not recorded by the test software and only show the worst case in the test report.

- Antenna 1(worst case)
- For the frequency band 5.15-5.25GHz, 5.725-5.850GHz (802.11a)
- Harmonics And Spurious Emissions

Frequency	Reading	Correct	Result	Limit	Margin	Polar	Detector
(MHz)	(dBuV/m)	dB	(dBuV/m)	(dBuV/m)	(dB)	H/V	
Low Channel (5180MHz)							
10360	55.75	7.11	62.86	74	-11.14	H	PK
10360	39.77	7.11	46.88	54	-7.12	H	AV
10360	57.57	7.11	64.68	74	-9.32	V	PK
10360	39.19	7.11	46.30	54	-7.70	V	AV
Middle Channel (5200MHz)							
10400	58.61	7.22	65.83	74	-8.17	H	PK
10400	38.80	7.22	46.02	54	-7.98	H	AV
10400	56.26	7.22	63.48	74	-10.52	V	PK
10400	40.68	7.22	47.90	54	-6.10	V	AV
High Channel (5240MHz)							
10480	57.82	7.69	65.51	74	-8.49	H	PK
10480	39.46	7.69	47.15	54	-6.85	H	AV
10480	55.50	7.69	63.19	74	-10.81	V	PK
10480	39.06	7.69	46.75	54	-7.25	V	AV

- Out of Band edge for 5150-5250MHz

Test CH.	Test Segment	Result	Limit
	MHz	dBm/MHz	dBm/MHz
Lowest	Below 5150	-42.32	-27
Highest	Above 5350	-43.65	-27
Note: the data just list the worst cases			

- For the frequency band 5.15-5.25GHz (802.11n HT20)
- Harmonics And Spurious Emissions

Frequency (MHz)	Reading (dBuV/m)	Correct dB	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Polar H/V	Detector
Low Channel (5180MHz)							
10360	58.72	7.11	65.83	74	-8.17	H	PK
10360	38.41	7.11	45.52	54	-8.48	H	AV
10360	58.79	7.11	65.90	74	-8.10	V	PK
10360	40.70	7.11	47.81	54	-6.19	V	AV
Middle Channel (5200MHz)							
10400	55.35	7.22	62.57	74	-11.43	H	PK
10400	38.29	7.22	45.51	54	-8.49	H	AV
10400	57.99	7.22	65.21	74	-8.79	V	PK
10400	41.61	7.22	48.83	54	-5.17	V	AV
High Channel (5240MHz)							
10480	56.36	7.69	64.05	74	-9.95	H	PK
10480	41.50	7.69	49.19	54	-4.81	H	AV
10480	58.67	7.69	66.36	74	-7.64	V	PK
10480	39.83	7.69	47.52	54	-6.48	V	AV

- Out of Band edge 5150-5250MHz

Test CH.	Test Segment	Result	Limit
	MHz	dBm/MHz	dBm/MHz
Lowest	Below 5150	-38.69	-27
Highest	Above 5350	-39.53	-27
Note: the data just list the worst cases			

- For the frequency band 5.15-5.25GHz (802.11ac-VHT20)
- Harmonics And Spurious Emissions

Frequency (MHz)	Reading (dBuV/m)	Correct dB	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Polar H/V	Detector
Low Channel (5180MHz)							
10360	55.05	7.11	62.16	74	-11.84	H	PK
10360	39.04	7.11	46.15	54	-7.85	H	AV
10360	57.30	7.11	64.41	74	-9.59	V	PK
10360	40.57	7.11	47.68	54	-6.32	V	AV
Middle Channel (5200MHz)							
10400	57.03	7.22	64.25	74	-9.75	H	PK
10400	40.68	7.22	47.90	54	-6.10	H	AV
10400	57.29	7.22	64.51	74	-9.49	V	PK
10400	39.47	7.22	46.69	54	-7.31	V	AV
High Channel (5240MHz)							
10480	56.93	7.69	64.62	74	-9.38	H	PK
10480	40.08	7.69	47.77	54	-6.23	H	AV
10480	57.43	7.69	65.12	74	-8.88	V	PK
10480	39.21	7.69	46.90	54	-7.10	V	AV

- Out of Band edge 5150-5250MHz

Test CH.	Test Segment	Result	Limit
	MHz	dBm/MHz	dBm/MHz
Lowest	Below 5150	-38.70	-27
Highest	Above 5350	-39.63	-27
Note: the data just list the worst cases			

- For the frequency band 5.15-5.25GHz (802.11n HT40)
- Harmonics And Spurious Emissions

Frequency (MHz)	Reading (dBuV/m)	Correct dB	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Polar H/V	Detector
Low Channel (5190MHz)							
10380	55.57	7.89	63.46	74	-10.54	H	PK
10380	38.84	7.89	46.73	54	-7.27	H	AV
10380	55.57	7.89	63.46	74	-10.54	V	PK
10380	40.94	7.89	48.83	54	-5.17	V	AV
High Channel (5230MHz)							
10460	56.91	7.97	64.88	74	-9.12	H	PK
10460	40.17	7.97	48.14	54	-5.86	H	AV
10460	58.71	7.97	66.68	74	-7.32	V	PK
10460	38.25	7.97	46.22	54	-7.78	V	AV

- Out of Band edge for 5150-5250MHz

Test CH.	Test Segment	Result	Limit
	MHz	dBm/MHz	dBm/MHz
Lowest	Below 5150	-38.26	-27
Highest	Above 5350	-37.73	-27
Note: the data just list the worst cases			

- For the frequency band 5.15-5.25GHz (802.11ac-VHT40)
- Harmonics And Spurious Emissions

Frequency (MHz)	Reading (dBuV/m)	Correct dB	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Polar H/V	Detector
Low Channel (5190MHz)							
10380	57.69	7.89	65.58	74	-8.42	H	PK
10380	39.81	7.89	47.70	54	-6.30	H	AV
10380	57.64	7.89	65.53	74	-8.47	V	PK
10380	38.60	7.89	46.49	54	-7.51	V	AV
High Channel (5230MHz)							
10460	55.49	7.97	63.46	74	-10.54	H	PK
10460	39.38	7.97	47.35	54	-6.65	H	AV
10460	58.59	7.97	66.56	74	-7.44	V	PK
10460	41.35	7.97	49.32	54	-4.68	V	AV

- Out of Band edge for 5150-5250MHz

Test CH.	Test Segment	Result	Limit
	MHz	dBm/MHz	dBm/MHz
Lowest	Below 5150	-38.69	-27
Highest	Above 5350	-37.57	-27
Note: the data just list the worst cases			

- For the frequency band 5.15-5.25GHz (802.11ac-VHT80)
- Harmonics And Spurious Emissions

Frequency (MHz)	Reading (dBuV/m)	Correct dB	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Polar H/V	Detector
5210MHz							
10420	56.13	7.53	63.66	74	-10.34	H	PK
10420	38.82	7.53	46.35	54	-7.65	H	AV
10420	57.07	7.53	64.60	74	-9.40	H	PK
10420	39.44	7.53	46.97	54	-7.03	H	AV

- Out of Band edge for 5150-5250MHz

Test CH.	Test Segment	Result	Limit
	MHz	dBm/MHz	dBm/MHz
Lowest	Below 5150	-37.26	-27
Highest	Above 5350	-36.91	-27
Note: the data just list the worst cases			

Note: Testing is carried out with frequency rang 9kHz to 40GHz, other than listed in the table above are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

9. Frequency Stability

9.1 Standard Applicable

According to §15.407(g), manufacturers of U-NII devices are responsible for ensuring frequency stability such that an emission is maintained within the band of operation under all conditions of normal operation as specified in the users manual.

9.2 Test Procedure

According to §2.1055, the following test procedure was performed.

The Frequency Stability is measured directly with a Frequency Domain Analyzer. Frequency Deviation in ppm is calculated from the measured peak to peak value.

The Carrier Frequency Stability over Power Supply Voltage and over Temperature is measured with a Frequency Domain Analyzer in histogram mode.

9.3 Summary of Test Results/Plots

Please refer to Appendix D


10 Conducted Emissions

10.1 Test Procedure

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40cm long in the middle. The spacing between the peripherals was 10cm.

10.2 Basic Test Setup Block Diagram




10.3 Test Receiver Setup

During the conducted emission test, the test receiver was set with the following configurations:

Start Frequency.....	150kHz
Stop Frequency.....	30MHz
Sweep Speed.....	Auto
IF Bandwidth.....	10kHz
Quasi-Peak Adapter Bandwidth.....	9kHz
Quasi-Peak Adapter Mode.....	Normal


10.4 Summary of Test Results/Plots

Test Mode	Communication	AC120V 60Hz	Polarity:	Neutral
-----------	---------------	-------------	-----------	---------



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1*	0.1548	50.25	9.75	60.00	65.73	-5.73	QP
2	0.1548	33.72	9.75	43.47	55.73	-12.26	AVG
3	0.4980	31.96	9.74	41.70	56.03	-14.33	QP
4	0.4980	22.95	9.74	32.69	46.03	-13.34	AVG
5	2.1619	33.85	9.62	43.47	56.00	-12.53	QP
6	2.1860	19.59	9.62	29.21	46.00	-16.79	AVG
7	3.7820	18.95	9.66	28.61	46.00	-17.39	AVG
8	3.8460	36.43	9.66	46.09	56.00	-9.91	QP
9	6.4660	33.09	9.76	42.85	60.00	-17.15	QP
10	6.5700	16.20	9.78	25.98	50.00	-24.02	AVG
11	23.2660	25.43	10.13	35.56	60.00	-24.44	QP
12	24.4540	9.89	10.09	19.98	50.00	-30.02	AVG

Test Mode	Communication	AC120V 60Hz	Polarity:	Line
-----------	---------------	-------------	-----------	------



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1*	0.1500	51.47	9.76	61.23	65.99	-4.76	QP
2	0.1500	36.28	9.76	46.04	55.99	-9.95	AVG
3	0.1940	31.77	9.59	41.36	53.86	-12.50	AVG
4	0.2404	41.80	9.60	51.40	62.08	-10.68	QP
5	0.4740	33.80	9.73	43.53	56.44	-12.91	QP
6	0.5020	21.60	9.74	31.34	46.00	-14.66	AVG
7	2.1500	22.45	9.62	32.07	46.00	-13.93	AVG
8	2.1740	35.78	9.62	45.40	56.00	-10.60	QP
9	3.7820	22.30	9.66	31.96	46.00	-14.04	AVG
10	3.8460	37.46	9.66	47.12	56.00	-8.88	QP
11	6.4460	20.53	9.76	30.29	50.00	-19.71	AVG
12	6.5500	36.78	9.78	46.56	60.00	-13.44	QP

APPENDIX SUMMARY

Project No.	WTH24X11267260W	Test Engineer	Timi Huang
Start date	2024/12/4	Finish date	2024/12/6
Temperature	24℃	Humidity	47%
RF specifications	U-NII		



APPENDIX	Description of Test Item	Result
A	Power Spectral Density	Compliant
B	Emission Bandwidth and Occupied Bandwidth	Compliant
C	Maximum Conducted Output Power	Compliant
D	Frequency Stability	Compliant

APPENDIX A



Power Spectral Density					
U-NII-1:5150-5250MHz					
Operating mode	Test Channel	ANT 1 dBm/MHz	ANT 2 dBm/MHz	Total dBm/MHz	Limit (dBm/MHz)
802.11a	5180	4.03	4.22	/	11
	5200	4.49	4.50	/	11
	5240	4.82	4.72	/	11
802.11n-HT20	5180	2.64	2.74	5.70	11
	5200	3.16	3.14	6.16	11
	5240	3.44	3.35	6.41	11
802.11n-HT40	5190	-0.53	0.03	2.77	11
	5230	-0.47	0.37	2.98	11
802.11ac-VHT20	5180	2.64	2.73	5.70	11
	5200	3.12	3.12	6.13	11
	5240	3.25	3.43	6.35	11
802.11ac-VHT40	5190	-0.61	0.03	2.73	11
	5230	-0.39	0.30	2.98	11
802.11ac-VHT80	5210	-4.87	-4.68	-1.76	11

ANT 1



5150-5250MHz






Date: 6.DEC.2024 10:32:23



Date: 6.DEC.2024 10:32:04



Date: 6.DEC.2024 10:31:48

802.11n-HT20-Low	 Ref 20 dBm *Att 30 dB *RBW 1 MHz Marker 1 [T1] 2.64 dBm *VBW 3 MHz *SWT 1 s 5.180960000 GHz 20 Offset 1 dB Center 5.18 GHz 4 MHz/ Span 40 MHz Date: 6.DEC.2024 10:31:08
802.11n-HT20-Middle	 Ref 20 dBm *Att 30 dB *RBW 1 MHz Marker 1 [T1] 3.16 dBm *VBW 3 MHz *SWT 1 s 5.201040000 GHz 20 Offset 1 dB Center 5.2 GHz 4 MHz/ Span 40 MHz Date: 6.DEC.2024 10:31:23
802.11n-HT20-High	 Ref 20 dBm *Att 30 dB *RBW 1 MHz Marker 1 [T1] 3.44 dBm *VBW 3 MHz *SWT 1 s 5.241040000 GHz 20 Offset 1 dB Center 5.24 GHz 4 MHz/ Span 40 MHz Date: 6.DEC.2024 10:31:37

802.11n-HT40-Low

Ref: 20 dBm, Att: 30 dB, RBW: 1 MHz, VBW: 3 MHz, SWT: 1 s, Marker 1 [T1]: -0.53 dBm, 5.191760000 GHz

Center: 5.19 GHz, Span: 80 MHz

802.11n-HT40-High




Ref: 20 dBm, Att: 30 dB, RBW: 1 MHz, VBW: 3 MHz, SWT: 1 s, Marker 1 [T1]: -0.47 dBm, 5.232400000 GHz

Center: 5.23 GHz, Span: 80 MHz


802.11ac-VHT20-Low

Ref: 20 dBm, Att: 30 dB, RBW: 1 MHz, VBW: 3 MHz, SWT: 1 s, Marker 1 [T1]: -2.64 dBm, 5.181200000 GHz


Center: 5.18 GHz, Span: 40 MHz

Channel	Plot	Ref	Att	RBW	VBW	SWT	Marker 1 [T1]	Center	Span	Date
802.11ac-VHT20-Middle		20 dBm	30 dB	1 MHz	3 MHz	1 s	3.12 dBm	5.200960000 GHz	40 MHz	6.DEC.2024 10:30:39
802.11ac-VHT20-High		20 dBm	30 dB	1 MHz	3 MHz	1 s	3.25 dBm	5.241200000 GHz	40 MHz	6.DEC.2024 10:30:24
802.11ac-VHT40-Low		20 dBm	30 dB	1 MHz	3 MHz	1 s	-0.61 dBm	5.191600000 GHz	80 MHz	6.DEC.2024 10:29:38




802.11ac-VHT40-High









802.11ac-VHT80






ANT 2
5150-5250MHz


802.11a-Low	 Date: 4.DEC.2024 17:44:30
802.11a-Middle	 Date: 4.DEC.2024 17:44:10
802.11a-High	 Date: 4.DEC.2024 17:43:55

802.11n-HT20-Low	 Ref: 20 dBm, Att: 30 dB, RBW: 1 MHz, VSW: 3 MHz, SWT: 1 s, Marker 1 [T1]: 5.181040000 GHz, 2.74 dBm Center: 5.18 GHz, 4 MHz, Span: 40 MHz Date: 4.DEC.2024 17:43:13
802.11n-HT20-Middle	 Ref: 20 dBm, Att: 30 dB, RBW: 1 MHz, VSW: 3 MHz, SWT: 1 s, Marker 1 [T1]: 5.201120000 GHz, 3.14 dBm Center: 5.2 GHz, 4 MHz, Span: 40 MHz Date: 4.DEC.2024 17:43:30
802.11n-HT20-High	 Ref: 20 dBm, Att: 30 dB, RBW: 1 MHz, VSW: 3 MHz, SWT: 1 s, Marker 1 [T1]: 5.241120000 GHz, 3.35 dBm Center: 5.24 GHz, 4 MHz, Span: 40 MHz Date: 4.DEC.2024 17:43:44


802.11n-HT40-Low	 Date: 4.DEC.2024 17:42:10
802.11n-HT40-High	 Date: 4.DEC.2024 17:41:53
802.11ac-VHT20-Low	 Date: 4.DEC.2024 17:43:01

802.11ac-VHT20-Middle	 Date: 4.DEC.2024 17:42:46
802.11ac-VHT20-High	 Date: 4.DEC.2024 17:42:32
802.11ac-VHT40-Low	 Date: 4.DEC.2024 17:41:24

802.11ac-VHT40-High



802.11ac-VHT80



APPENDIX B



Emission Bandwidth and Occupied Bandwidth

U-NII-1:5150-5250MHz						
Test Mode	Test Channel MHz	ANT 1		ANT 2		Result
		26 dB Bandwidth MHz	99% Bandwidth MHz	26 dB Bandwidth MHz	99% Bandwidth MHz	
802.11a	5180	26.76	18.08	26.88	18.08	Pass
	5200	26.88	18.08	26.88	18.08	Pass
	5240	20.30	16.88	20.40	16.88	Pass
802.11n-HT20	5180	27.36	18.80	27.84	18.80	Pass
	5200	27.60	18.72	27.60	18.72	Pass
	5240	20.60	17.76	20.70	17.76	Pass
802.11n-HT40	5190	39.84	36.16	39.84	36.32	Pass
	5230	39.84	36.16	39.84	36.16	Pass
802.11ac-VHT20	5180	27.84	18.72	27.96	18.72	Pass
	5200	27.72	18.72	27.48	18.72	Pass
	5240	20.60	17.76	20.60	17.76	Pass
802.11ac-VHT40	5190	39.68	36.00	39.36	36.00	Pass
	5230	39.68	36.16	39.68	36.16	Pass
802.11ac-VHT80	5210	80.64	75.52	81.00	75.20	Pass



ANT 1

26 dB Bandwidth



5150-5250MHz






Date: 6.DEC.2024 10:52:00



Date: 6.DEC.2024 10:51:36



Date: 6.DEC.2024 10:51:19

802.11n-HT20-Low	 Ref 20 dBm *Att 30 dB SWT 20 ms Marker 1 [T1] 5.181440000 GHz ndB [T1] -19.82 dBm SW 27.360000000 MHz Temp 1 [T1] ndB 5.166560000 GHz 5.193920000 GHz Center 5.18 GHz 6 MHz/ Span 60 MHz Date: 6.DEC.2024 10:50:26
802.11n-HT20-Middle	 Ref 20 dBm *Att 30 dB SWT 20 ms Marker 1 [T1] 5.201440000 GHz ndB [T1] -19.78 dBm SW 27.600000000 MHz Temp 1 [T1] ndB 5.186320000 GHz 5.213920000 GHz Center 5.2 GHz 6 MHz/ Span 60 MHz Date: 6.DEC.2024 10:50:44
802.11n-HT20-High	 Ref 20 dBm *Att 30 dB SWT 20 ms Marker 1 [T1] 5.241400000 GHz ndB [T1] -19.25 dBm SW 20.600000000 MHz Temp 1 [T1] ndB 5.229760000 GHz 5.250300000 GHz Center 5.24 GHz 5 MHz/ Span 50 MHz Date: 6.DEC.2024 10:51:03

802.11n-HT40-Low

802.11n-HT40-High

802.11ac-VHT20-Low

The figure displays three spectral plots, each showing the power spectral density (PSD) of a signal. The plots are arranged vertically, corresponding to different signal types: 802.11n-HT40-Low, 802.11n-HT40-High, and 802.11ac-VHT20-Low. Each plot includes a title, a reference level (Ref), an attenuation level (Att), a voltage standing wave ratio (VSWR), and a standing wave ratio (SWR). The plots also show a center frequency, a span, and a resolution bandwidth (RBW). The x-axis represents frequency in GHz, and the y-axis represents power in dBm. The plots show a signal centered around 5.19 GHz, 5.23 GHz, and 5.18 GHz respectively. The signal is characterized by a flat top and steep skirts, indicating a well-defined channel. The plots also show various parameters such as noise floor, noise power, and signal-to-noise ratio (SNR).

Signal Type	Center Frequency (GHz)	Span (MHz)	Ref (dBm)	Att (dB)	VSWR	SWR	RBW (kHz)	Marker 1 (GHz)	Marker 1 (dBm)
802.11n-HT40-Low	5.19	80	20	30	1	2.65	300	5.19336000	-23.49
802.11n-HT40-High	5.23	80	20	30	1	2.35	300	5.23144000	-23.78
802.11ac-VHT20-Low	5.18	60	20	30	1	5.74	300	5.18144000	-20.73


Date: 6.DEC.2024 10:48:57

Date: 6.DEC.2024 10:49:14


Date: 6.DEC.2024 10:50:11

[illegible]

802.11ac-VHT40-High





802.11ac-VHT80





ANT 2

26 dB Bandwidth



5150-5250MHz






Date: 6.DEC.2024 10:08:11






Date: 6.DEC.2024 10:09:08



Date: 6.DEC.2024 10:09:41

802.11n-HT20-Low	 Date: 6.DEC.2024 10:11:41
802.11n-HT20-Middle	 Date: 6.DEC.2024 10:11:15
802.11n-HT20-High	 Date: 6.DEC.2024 10:10:45

802.11n-HT40-Low	 Date: 6.DEC.2024 10:14:24
802.11n-HT40-High	 Date: 6.DEC.2024 10:14:57
802.11ac-VHT20-Low	 Date: 6.DEC.2024 10:12:03

802.11ac-VHT20-Middle

Ref: 20 dBm, Att: 30 dB, VBW: 1 MHz, RBW: 300 kHz, Marker 1 [T1]: 6.26 dBm, SWT: 20 ms, 5.201440000 GHz

Parameter	Value
ndB [T1]	26.90 dB
BW	27.480000000 MHz
Temp 1 [T1 dBm]	-19.94 dBm
Temp 2 [T2 dBm]	-19.65 dBm
Frequency 1	5.186320000 GHz
Frequency 2	5.213800000 GHz

Center: 5.2 GHz, Span: 60 MHz

Date: 6.DEC.2024 10:12:45

802.11ac-VHT20-High

Ref: 20 dBm, Att: 30 dB, VBW: 1 MHz, RBW: 300 kHz, Marker 1 [T1]: 6.73 dBm, SWT: 20 ms, 5.242100000 GHz

Parameter	Value
ndB [T1]	26.90 dB
BW	20.600000000 MHz
Temp 1 [T1 dBm]	-18.94 dBm
Temp 2 [T2 dBm]	-18.99 dBm
Frequency 1	5.229700000 GHz
Frequency 2	5.250300000 GHz

Center: 5.24 GHz, Span: 50 MHz

Date: 6.DEC.2024 10:13:29

802.11ac-VHT40-Low


Ref: 20 dBm, Att: 30 dB, VBW: 1 MHz, RBW: 300 kHz, Marker 1 [T1]: 3.59 dBm, SWT: 20 ms, 5.194160000 GHz

Parameter	Value
ndB [T1]	26.90 dB
BW	39.360000000 MHz
Temp 1 [T1 dBm]	-21.91 dBm
Temp 2 [T2 dBm]	-21.89 dBm
Frequency 1	5.170320000 GHz
Frequency 2	5.209680000 GHz


Center: 5.19 GHz, Span: 80 MHz

Date: 6.DEC.2024 10:15:51

802.11ac-VHT40-High





802.11ac-VHT80





ANT 1

99% Bandwidth



5150-5250MHz



Date: 6.DEC.2024 10:33:23




Date: 6.DEC.2024 10:33:42




Date: 6.DEC.2024 10:33:58


802.11n-HT20-Low



802.11n-HT20-Middle




802.11n-HT20-High




Configuration	Plot Description	Key Parameters
802.11n-HT40-Low	Power Spectral Density (PSD) plot for 802.11n-HT40-Low. The plot shows a signal centered at 5.19 GHz with a span of 80 MHz. The signal level is approximately -10 dBm. The plot includes a reference level of 20 dBm and a noise floor of -80 dBm. The signal is labeled with a peak level of 10.41 dBm.	Center: 5.19 GHz, Span: 80 MHz, Peak Level: 10.41 dBm
802.11n-HT40-High	Power Spectral Density (PSD) plot for 802.11n-HT40-High. The plot shows a signal centered at 5.23 GHz with a span of 80 MHz. The signal level is approximately -10 dBm. The plot includes a reference level of 20 dBm and a noise floor of -80 dBm. The signal is labeled with a peak level of 10.49 dBm.	Center: 5.23 GHz, Span: 80 MHz, Peak Level: 10.49 dBm
802.11ac-VHT20-Low	Power Spectral Density (PSD) plot for 802.11ac-VHT20-Low. The plot shows a signal centered at 5.18 GHz with a span of 40 MHz. The signal level is approximately -10 dBm. The plot includes a reference level of 20 dBm and a noise floor of -80 dBm. The signal is labeled with a peak level of 6.45 dBm.	Center: 5.18 GHz, Span: 40 MHz, Peak Level: 6.45 dBm

[illegible]

802.11ac-VHT40-High




802.11ac-VHT80




ANT 2
99% Bandwidth
5150-5250MHz

802.11a-Low	Ref 20 dBm Att 30 dB RBW 300 kHz VSW 1 MHz SWT 20 ms Marker 1 [T1] 7.32 dBm 5.182240000 GHz OSW 16.080000000 MHz Temp 1 [T1] 7.32 dBm 5.170880000 GHz Temp 2 [T1] 7.32 dBm 5.188960000 GHz Center 5.18 GHz 4 MHz/ Span 40 MHz Date: 4.DEC.2024 17:45:56
802.11a-Middle	Ref 20 dBm Att 30 dB RBW 300 kHz VSW 1 MHz SWT 20 ms Marker 1 [T1] 7.63 dBm 5.198320000 GHz OSW 16.080000000 MHz Temp 1 [T1] 7.63 dBm 5.190880000 GHz Temp 2 [T1] 7.63 dBm 5.208960000 GHz Center 5.2 GHz 4 MHz/ Span 40 MHz Date: 4.DEC.2024 17:46:40
802.11a-High	Ref 20 dBm Att 30 dB RBW 300 kHz VSW 1 MHz SWT 20 ms Marker 1 [T1] 7.80 dBm 5.238320000 GHz OSW 16.880000000 MHz Temp 1 [T1] 7.80 dBm 5.231520000 GHz Temp 2 [T1] 7.80 dBm 5.248400000 GHz Center 5.24 GHz 4 MHz/ Span 40 MHz Date: 4.DEC.2024 17:47:00


802.11n-HT20-Low









802.11n-HT20-Middle




802.11n-HT20-High




802.11n-HT40-Low	 Ref 20 dBm *Att 30 dB SWT 20 ms Marker 1 [T1] 5.19200000 GHz OSW 30.32000000 MHz Temp 1 [T1] 9.05 dBm Temp 2 [T1] 0.16 dBm 5.171920000 GHz 5.171920000 GHz 5.208240000 GHz Center 5.19 GHz 8 MHz/ Span 80 MHz Date: 4.DEC.2024 17:49:30
802.11n-HT40-High	 Ref 20 dBm *Att 30 dB SWT 20 ms Marker 1 [T1] 5.23192000 GHz OSW 30.16000000 MHz Temp 1 [T1] 9.32 dBm Temp 2 [T1] 0.17 dBm 5.211920000 GHz 5.211920000 GHz 5.248080000 GHz Center 5.23 GHz 8 MHz/ Span 80 MHz Date: 4.DEC.2024 17:49:48
802.11ac-VHT20-Low	 Ref 20 dBm *Att 30 dB SWT 20 ms Marker 1 [T1] 5.18144000 GHz OSW 18.72000000 MHz Temp 1 [T1] 5.89 dBm Temp 2 [T1] -5.88 dBm 5.170640000 GHz 5.170640000 GHz 5.189360000 GHz Center 5.18 GHz 4 MHz/ Span 40 MHz Date: 4.DEC.2024 17:48:20

802.11ac-VHT20-Middle	 Ref: 20 dBm, Att: 30 dB, BW: 20 MHz, Span: 40 MHz, Center: 5.2 GHz	Date: 4.DEC.2024 17:48:42
802.11ac-VHT20-High	 Ref: 20 dBm, Att: 30 dB, BW: 20 MHz, Span: 40 MHz, Center: 5.24 GHz	Date: 4.DEC.2024 17:49:00
802.11ac-VHT40-Low	 Ref: 20 dBm, Att: 30 dB, BW: 20 MHz, Span: 80 MHz, Center: 5.19 GHz	Date: 4.DEC.2024 17:50:19

802.11ac-VHT40-High





802.11ac-VHT80





APPENDIX C

Maximum Conducted Output Power



U-NII-1:5150-5250MHz					
Test mode	Frequency MHz	Output Power dBm		Total dBm	Limit dBm
		ANT 1	ANT 2		
802.11a	5180	15.06	15.12	/	23.98
	5200	15.67	15.61	/	23.98
	5240	15.42	15.67	/	23.98
802.11n-HT20	5180	14.01	14.02	17.03	23.98
	5200	14.49	14.60	17.56	23.98
	5240	14.46	14.66	17.57	23.98
802.11n-HT40	5190	13.03	13.57	16.32	23.98
	5230	13.12	13.86	16.52	23.98
802.11ac-VHT20	5180	14.02	14.04	17.04	23.98
	5200	14.53	14.60	17.58	23.98
	5240	14.36	14.57	17.48	23.98
802.11ac-VHT40	5190	13.01	13.58	16.31	23.98
	5230	13.19	13.93	16.59	23.98
802.11ac-VHT80	5210	12.24	12.46	15.36	23.98






Date: 6.DEC.2024 10:22:49









Date: 6.DEC.2024 10:23:13




Date: 6.DEC.2024 10:23:29

802.11n-HT20-Low	 Date: 6.DEC.2024 10:24:29
802.11n-HT20-Middle	 Date: 6.DEC.2024 10:24:04
802.11n-HT20-High	 Date: 6.DEC.2024 10:23:48

802.11n-HT40-Low	 Ref: 20 dBm Offset: 1 dB Att: 30 dB RBW: 1 MHz VBW: 3 MHz SWT: 20 ms Center: 5.19 GHz Span: 80 MHz Tx Channel Bandwidth: 40 MHz Power: 13.03 dBm Date: 6.DEC.2024 10:25:47
802.11n-HT40-High	 Ref: 20 dBm Offset: 1 dB Att: 30 dB RBW: 1 MHz VBW: 3 MHz SWT: 20 ms Center: 5.23 GHz Span: 80 MHz Tx Channel Bandwidth: 40 MHz Power: 13.12 dBm Date: 6.DEC.2024 10:26:04
802.11ac-VHT20-Low	 Ref: 20 dBm Offset: 1 dB Att: 30 dB RBW: 1 MHz VBW: 3 MHz SWT: 20 ms Center: 5.18 GHz Span: 40 MHz Tx Channel Bandwidth: 20 MHz Power: 14.02 dBm Date: 6.DEC.2024 10:24:49


802.11ac-VHT20-Middle	 Ref: 20 dBm Offset: 1 dB Att: 30 dB RBW: 1 MHz VBW: 3 MHz SWT: 20 ms Center: 5.2 GHz Span: 40 MHz Tx Channel Bandwidth: 20 MHz Power: 14.53 dBm Date: 6.DEC.2024 10:25:06
802.11ac-VHT20-High	 Ref: 20 dBm Offset: 1 dB Att: 30 dB RBW: 1 MHz VBW: 3 MHz SWT: 20 ms Center: 5.24 GHz Span: 40 MHz Tx Channel Bandwidth: 20 MHz Power: 14.36 dBm Date: 6.DEC.2024 10:25:21
802.11ac-VHT40-Low	 Ref: 20 dBm Offset: 1 dB Att: 30 dB RBW: 1 MHz VBW: 3 MHz SWT: 20 ms Center: 5.19 GHz Span: 80 MHz Tx Channel Bandwidth: 40 MHz Power: 13.01 dBm Date: 6.DEC.2024 10:26:46

802.11ac-VHT40-High



Date: 6.DEC.2024 10:26:25


802.11ac-VHT80





Date: 6.DEC.2024 10:27:23

ANT 2



5150-5250MHz






Date: 4.DEC.2024 17:34:38






Date: 4.DEC.2024 17:35:10




Date: 4.DEC.2024 17:35:27

802.11n-HT20-Low	 Date: 4.DEC.2024 17:36:33
802.11n-HT20-Middle	 Date: 4.DEC.2024 17:36:09
802.11n-HT20-High	 Date: 4.DEC.2024 17:35:54

802.11n-HT40-Low	Date: 4.DEC.2024 17:38:33
802.11n-HT40-High	Date: 4.DEC.2024 17:38:48
802.11ac-VHT20-Low	Date: 4.DEC.2024 17:37:05


802.11ac-VHT20-Middle	 Date: 4.DEC.2024 17:37:21
802.11ac-VHT20-High	 Date: 4.DEC.2024 17:37:37
802.11ac-VHT40-Low	 Date: 4.DEC.2024 17:39:39

802.11ac-VHT40-High



Date: 4.DEC.2024 17:39:20

802.11ac-VHT80



Date: 4.DEC.2024 17:40:07

APPENDIX D

Frequency Stability

U-NII-1:5150-5250MHz worst case at 802.11a middle channel				
Voltage(%)	Power(VDC)	TEMP(°C)	Freq.Dev(Hz)	Deviation
100%	5.0	-30	498	0.096
100%		-20	502	0.097
100%		-10	503	0.097
100%		0	499	0.096
100%		+10	500	0.096
100%		+20	498	0.096
100%		+30	504	0.097
100%		+40	497	0.096
100%		+50	505	0.097
Low Battery power	5.50	+20	499	0.096
High Battery power	4.50	+20	501	0.096

APPENDIX PHOTOGRAPHS

Please refer to “ANNEX”

***** END OF REPORT *****