



SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

No. 1 Workshop, M-10, Middle section, Science & Technology Park,
Shenzhen, Guangdong, China 518057

Telephone: +86 (0) 755 2601 2053
Fax: +86 (0) 755 2671 0594
Email: ee.shenzhen@sgs.com

Report No.: SZEM180600535604
Page: 1 of 54

TEST REPORT

Application No.: SZEM1806005356CR
Applicant: Sensoro Co., Ltd.
Address of Applicant: Room 2807, Building 1B, Wangjing SOHO, No.10, Wangjing Street, Chaoyang District, Beijing, China
Manufacturer: Sensoro Co., Ltd.
Address of Manufacturer: Room 2807, Building 1B, Wangjing SOHO, No.10, Wangjing Street, Chaoyang District, Beijing, China
Factory: Sensoro Co., Ltd.
Address of Factory: Room 2807, Building 1B, Wangjing SOHO, No.10, Wangjing Street, Chaoyang District, Beijing, China

Equipment Under Test (EUT):

EUT Name: α Gateway
Model No.: GW-1209
Trade Mark: SENSORO
FCC ID : 2ADYO-S001209
Standard(s) : 47 CFR Part 15, Subpart C 15.249
Date of Receipt: 2018-06-27
Date of Test: 2018-07-03 to 2018-07-22
Date of Issue: 2018-07-25

Test Result:	Pass*
---------------------	--------------

* In the configuration tested, the EUT complied with the standards specified above.




Keny Xu

EMC Laboratory Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

<i>Revision Record</i>				
<i>Version</i>	<i>Chapter</i>	<i>Date</i>	<i>Modifier</i>	<i>Remark</i>
01		2018-07-25		Original

Authorized for issue by:			
		 _____ Harry Wu /Project Engineer	
		 _____ Eric Fu /Reviewer	

2 Test Summary

Radio Spectrum Technical Requirement				
Item	Standard	Method	Requirement	Result
Antenna Requirement	47 CFR Part 15, Subpart C 15.249	N/A	47 CFR Part 15, Subpart C 15.203	Pass

Radio Spectrum Matter Part				
Item	Standard	Method	Requirement	Result
Conducted Emissions at AC Power Line (150kHz-30MHz)	47 CFR Part 15, Subpart C 15.249	ANSI C63.10 (2013) Section 6.2	47 CFR Part 15, Subpart C 15.207	Pass
20dB Bandwidth	47 CFR Part 15, Subpart C 15.249	ANSI C63.10 (2013) Section 6.9	47 CFR Part 15, Subpart C 15.215	Pass
Field Strength of the Fundamental Signal (15.249(a))	47 CFR Part 15, Subpart C 15.249	ANSI C63.10 (2013) Section 6.5&6.6	47 CFR Part 15, Subpart C 15.249(a)	Pass
Restricted Band Around Fundamental Frequency	47 CFR Part 15, Subpart C 15.249	ANSI C63.10 (2013) Section 6.4&6.5&6.6	47 CFR Part 15, Subpart C 15.205 & 15.249(d) & 15.209	Pass
Radiated Emissions	47 CFR Part 15, Subpart C 15.249	ANSI C63.10 (2013) Section 6.4&6.5&6.6	47 CFR Part 15, Subpart C 15.209 & 15.249 (a),(d)	Pass

3 Contents

	Page
1 COVER PAGE	1
2 TEST SUMMARY	3
3 CONTENTS	4
4 GENERAL INFORMATION	6
4.1 DETAILS OF E.U.T	6
4.2 DESCRIPTION OF SUPPORT UNITS	6
4.3 MEASUREMENT UNCERTAINTY	6
4.4 TEST LOCATION	7
4.5 TEST FACILITY	7
4.6 DEVIATION FROM STANDARDS	7
4.7 ABNORMALITIES FROM STANDARD CONDITIONS	7
5 EQUIPMENT LIST	8
6 RADIO SPECTRUM TECHNICAL REQUIREMENT	10
6.1 ANTENNA REQUIREMENT	10
6.1.1 Test Requirement:	10
6.1.2 Conclusion	10
7 RADIO SPECTRUM MATTER TEST RESULTS	11
7.1 CONDUCTED EMISSIONS AT AC POWER LINE (150KHz-30MHz)	11
7.1.1 E.U.T. Operation	11
7.1.2 Measurement Procedure and Data	11
7.2 20dB BANDWIDTH	14
7.2.1 E.U.T. Operation	14
7.2.2 Test Setup Diagram	14
7.2.3 Measurement Procedure and Data	14
7.3 FIELD STRENGTH OF THE FUNDAMENTAL SIGNAL (15.249(A))	15
7.3.1 E.U.T. Operation	16
7.3.2 Test Setup Diagram	16
7.3.3 Measurement Procedure and Data	17
7.3.4 Measurement Procedure and Data	17
7.4 RESTRICTED BAND AROUND FUNDAMENTAL FREQUENCY	18
7.4.1 E.U.T. Operation	19
7.4.2 Test Setup Diagram	19
7.4.3 Measurement Procedure and Data	20
7.4.4 Measurement Procedure and Data	20
7.5 RADIATED EMISSIONS	21
7.5.1 E.U.T. Operation	22
7.5.2 Test Setup Diagram	22
7.5.3 Measurement Procedure and Data	22
8 PHOTOGRAPHS	37
8.1 CONDUCTED EMISSIONS AT AC POWER LINE (150KHz-30MHz) TEST SETUP	37
8.2 RADIATED EMISSIONS	37
8.3 EUT CONSTRUCTIONAL DETAILS (EUT PHOTOS)	38



9 APPENDIX.....	39
9.1 APPENDIX 15.249	39-54

4 General Information

4.1 Details of E.U.T.

Power supply:	AC/DC Adapter Model: GP304C-120-200 Input: AC100-240V, 50/60Hz, 1A Max Output: DC12V, 2A
Operation Frequency:	902.3-927.5MHz
Modulation Type:	CSS
Number of Channels:	16
Antenna Gain:	1.5dBi
Antenna Type:	External Antenna
Module Model:	A: SX1301, B: SX1276

Operation Frequency each of channel			
Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	902.3	9	923.3
2	902.5	10	923.9
3	902.7	11	924.5
4	902.9	12	925.1
5	903.1	13	925.7
6	903.3	14	926.3
7	903.5	15	926.9
8	903.7	16	927.5

4.2 Description of Support Units

The EUT has been tested as an independent unit.

4.3 Measurement Uncertainty

No.	Item	Measurement Uncertainty
1	Radio Frequency	$\pm 7.25 \times 10^{-8}$
2	Duty cycle	$\pm 0.37\%$
3	Occupied Bandwidth	$\pm 3\%$
4	RF conducted power	$\pm 0.75\text{dB}$
5	RF power density	$\pm 2.84\text{dB}$
6	Conducted Spurious emissions	$\pm 0.75\text{dB}$
7	RF Radiated power	$\pm 4.5\text{dB}$ (below 1GHz) $\pm 4.8\text{dB}$ (above 1GHz)
8	Radiated Spurious emission test	$\pm 4.5\text{dB}$ (Below 1GHz) $\pm 4.8\text{dB}$ (Above 1GHz)
9	Temperature test	$\pm 1^\circ\text{C}$
10	Humidity test	$\pm 3\%$
11	Supply voltages	$\pm 1.5\%$
12	Time	$\pm 3\%$

4.4 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch

No. 1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, Guangdong, China.
518057.

Tel: +86 755 2601 2053 Fax: +86 755 2671 0594

No tests were sub-contracted.

4.5 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- CNAS (No. CNAS L2929)**

CNAS has accredited SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

- A2LA (Certificate No. 3816.01)**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 3816.01.

- VCCI**

The 3m Fully-anechoic chamber for above 1GHz, 10m Semi-anechoic chamber for below 1GHz, Shielded Room for Mains Port Conducted Interference Measurement and Telecommunication Port Conducted Interference Measurement of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-20026, R-14188, C-12383 and T-11153 respectively.

- FCC –Designation Number: CN1178**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized as an accredited testing laboratory.

Designation Number: CN1178. Test Firm Registration Number: 406779.

- Industry Canada (IC)**

Two 3m Semi-anechoic chambers and the 10m Semi-anechoic chamber of SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab have been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 4620C-1, 4620C-2, 4620C-3.

4.6 Deviation from Standards

None

4.7 Abnormalities from Standard Conditions

None

5 Equipment List

Conducted Emissions at AC Power Line (150kHz-30MHz)					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
Shielding Room	ZhongYu Electron	GB-88	SEM001-06	2017-05-10	2020-05-09
Measurement Software	AUDIX	e3 V5.4.1221d	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM024-01	2018-07-12	2019-07-11
LISN	Rohde & Schwarz	ENV216	SEM007-01	2017-09-27	2018-09-26
LISN	ETS-LINDGREN	3816/2	SEM007-02	2018-04-02	2019-04-01
EMI Test Receiver	Rohde & Schwarz	ESCI	SEM004-02	2018-04-02	2019-04-01

20dB Bandwidth					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
DC Power Supply	ZhaoXin	RXN-305D	SEM011-02	2017-09-27	2018-09-26
Spectrum Analyzer	Rohde & Schwarz	FSU43	SEM004-08	2018-04-02	2019-04-01
Measurement Software	JS Tonscend	JS1120-2 BT/WIFI V2.	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM031-01	2018-07-12	2019-07-11
Attenuator	Weinschel Associates	WA41	SEM021-09	N/A	N/A
Signal Generator	KEYSIGHT	N5173B	SEM006-05	2017-09-27	2018-09-26
Power Meter	Rohde & Schwarz	NRVS	SEM014-02	2017-09-27	2018-09-26

Field Strength of the Fundamental Signal (15.249(a))					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
3m Semi-Anechoic Chamber	AUDIX	N/A	SEM001-02	2018-03-13	2021-03-12
Measurement Software	AUDIX	e3 V8.2014-6-27	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM026-01	2018-07-12	2019-07-11
Spectrum Analyzer	Rohde & Schwarz	FSU43	SEM004-08	2018-04-02	2019-04-01
BiConiLog Antenna (26-3000MHz)	ETS-Lindgren	3142C	SEM003-01	2017-06-27	2020-06-26
Horn Antenna (1-18GHz)	Rohde & Schwarz	HF907	SEM003-07	2018-04-13	2021-04-12
Horn Antenna (15GHz-40GHz)	Schwarzbeck	BBHA 9170	SEM003-15	2017-10-17	2020-10-16
Pre-amplifier (0.1-1300MHz)	HP	8447D	SEM005-02	2017-09-27	2018-09-26
Low Noise Amplifier (100MHz-18GHz)	Black Diamond Series	BDLNA-0118-352810	SEM005-05	2017-09-27	2018-09-27
Pre-amplifier(18-26GHz)	Rohde & Schwarz	CH14-H052	SEM005-17	2018-04-02	2019-04-01
Pre-amplifier (26GHz-40GHz)	Compliance Directions Systems Inc.	PAP-2640-50	SEM005-08	2018-04-02	2019-04-01



SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

Report No.: SZEM180600535604
Page: 9 of 54

DC Power Supply	Zhao Xin	RXN-305D	SEM011-02	2017-09-27	2018-09-26
Active Loop Antenna	ETS-Lindgren	6502	SEM003-08	2017-08-22	2020-08-21
Band filter	N/A	N/A	SEM023-01	N/A	N/A

Restricted Band Around Fundamental Frequency					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
3m Semi-Anechoic Chamber	AUDIX	N/A	SEM001-02	2018-03-13	2021-03-12
Measurement Software	AUDIX	e3 V8.2014-6-27	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM026-01	2018-07-12	2019-07-11
Spectrum Analyzer	Rohde & Schwarz	FSU43	SEM004-08	2018-04-02	2019-04-01
BiConiLog Antenna (26-3000MHz)	ETS-Lindgren	3142C	SEM003-01	2017-06-27	2020-06-26
Horn Antenna (1-18GHz)	Rohde & Schwarz	HF907	SEM003-07	2018-04-13	2021-04-12
Horn Antenna (15GHz-40GHz)	Schwarzbeck	BBHA 9170	SEM003-15	2017-10-17	2020-10-16
Pre-amplifier (0.1-1300MHz)	HP	8447D	SEM005-02	2017-09-27	2018-09-26
Low Noise Amplifier (100MHz-18GHz)	Black Diamond Series	BDLNA-0118-352810	SEM005-05	2017-09-27	2018-09-27
Pre-amplifier(18-26GHz)	Rohde & Schwarz	CH14-H052	SEM005-17	2018-04-02	2019-04-01
Pre-amplifier (26GHz-40GHz)	Compliance Directions Systems Inc.	PAP-2640-50	SEM005-08	2018-04-02	2019-04-01
DC Power Supply	Zhao Xin	RXN-305D	SEM011-02	2017-09-27	2018-09-26
Active Loop Antenna	ETS-Lindgren	6502	SEM003-08	2017-08-22	2020-08-21
Band filter	N/A	N/A	SEM023-01	N/A	N/A

General used equipment					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
Humidity/ Temperature Indicator	Shanghai Meteorological Industry Factory	ZJ1-2B	SEM002-03	2017-09-29	2018-09-28
Humidity/ Temperature Indicator	Shanghai Meteorological Industry Factory	ZJ1-2B	SEM002-04	2017-09-29	2018-09-28
Humidity/ Temperature Indicator	Mingle	N/A	SEM002-08	2017-09-29	2018-09-28
Barometer	Changchun Meteorological Industry Factory	DYM3	SEM002-01	2018-04-08	2019-04-07

6 Radio Spectrum Technical Requirement

6.1 Antenna Requirement

6.1.1 Test Requirement:

47 CFR Part 15, Subpart C 15.203

Limit:

15.203 requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

6.1.2 Conclusion

Standard Requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

EUT Antenna:

The antenna is dedicated on the main PCB. The best case gain of the antenna is 3dBi.

7 Radio Spectrum Matter Test Results

7.1 Conducted Emissions at AC Power Line (150kHz-30MHz)

Test Requirement 47 CFR Part 15, Subpart C 15.207

Test Method: ANSI C63.10 (2013) Section 6.2

Limit:

Frequency range (MHz)	Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

* Decreases with the logarithm of the frequency.

7.1.1 E.U.T. Operation

Operating Environment:

Temperature: 22.3 °C Humidity: 58.4 % RH Atmospheric Pressure: 1005 mbar

Pretest these modes to find the worst case: d:TX mode(Module A)_Keep the EUT in transmitting with modulation mode.

e:TX mode(Module B)_Keep the EUT in transmitting with modulation mode.

The worst case for final test: d:TX mode(Module A)_Keep the EUT in transmitting with modulation mode.

7.1.2 Measurement Procedure and Data

1) The mains terminal disturbance voltage test was conducted in a shielded room.

2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a 50ohm/50μH + 5ohm linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.


3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane,

4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2.

5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10 on conducted measurement.

Remark: LISN=Read Level+ Cable Loss+ LISN Factor

Mode:d; Line:Live Line



Site : Shielding Room


Condition: Line

Job No. : 05356CR

Test mode: d

Freq	Cable	LISN	Read	Limit	Over	Remark	
	Loss	Factor	Level				
	MHz	dB	dB	dBuV	dBuV	dB	
1	0.16	0.02	9.52	31.64	41.18	55.38	-14.20 Average
2	0.16	0.02	9.52	52.32	61.86	65.38	-3.52 QP
3	0.21	0.03	9.50	21.55	31.08	53.36	-22.28 Average
4	0.21	0.03	9.50	48.50	58.03	63.36	-5.33 QP
5	0.24	0.03	9.51	19.46	29.00	52.26	-23.26 Average
6	0.24	0.03	9.51	46.24	55.78	62.26	-6.48 QP
7	0.28	0.03	9.51	26.87	36.41	50.90	-14.49 Average
8	0.28	0.03	9.51	44.97	54.51	60.90	-6.39 QP
9	0.34	0.03	9.50	23.81	33.34	49.18	-15.84 Average
10	0.34	0.03	9.50	42.76	52.29	59.18	-6.89 QP
11	0.46	0.04	9.49	28.03	37.56	46.76	-9.20 Average
12	0.46	0.04	9.49	41.18	50.71	56.76	-6.05 QP

Mode:d; Line:Neutral Line



Site : Shielding Room

Condition: Neutral

Job No. : 05356CR

Test mode: d

Freq	Cable	LISN	Read	Limit		Over	Remark
	Loss	Factor	Level	Level	Line	Limit	
	MHz	dB	dB	dBuV	dBuV	dB	
1	0.17	0.02	9.59	29.52	39.13	55.12	-15.99 Average
2	0.17	0.02	9.59	51.98	61.59	65.12	-3.53 QP
3	0.20	0.03	9.57	14.73	24.33	53.62	-29.29 Average
4	0.20	0.03	9.57	49.03	58.63	63.62	-4.99 QP
5	0.22	0.03	9.57	25.59	35.19	52.79	-17.60 Average
6	0.22	0.03	9.57	49.78	59.38	62.79	-3.41 QP
7	0.25	0.03	9.58	20.29	29.90	51.64	-21.74 Average
8	0.25	0.03	9.58	47.14	56.75	61.64	-4.89 QP
9	0.28	0.03	9.58	22.25	31.86	50.68	-18.82 Average
10	0.28	0.03	9.58	45.38	54.99	60.68	-5.69 QP
11	0.46	0.04	9.60	28.28	37.92	46.71	-8.79 Average
12	0.46	0.04	9.60	41.14	50.78	56.71	-5.93 QP

7.2 20dB Bandwidth


Test Requirement 47 CFR Part 15, Subpart C 15.215
Test Method: ANSI C63.10 (2013) Section 6.9
Limit: N/A

7.2.1 E.U.T. Operation

Operating Environment:

Temperature: 23.7 °C Humidity: 49.9 % RH Atmospheric Pressure: 1005 mbar
Pretest these modes to find the worst case:
d:TX mode(Module A)_Keep the EUT in transmitting with modulation mode.
e:TX mode(Module B)_Keep the EUT in transmitting with modulation mode.
The worst case for final test:
d:TX mode(Module A)_Keep the EUT in transmitting with modulation mode.
e:TX mode(Module B)_Keep the EUT in transmitting with modulation mode.

7.2.2 Test Setup Diagram



7.2.3 Measurement Procedure and Data

The detailed test data see: Appendix 15.249

7.3 Field Strength of the Fundamental Signal (15.249(a))

Test Requirement 47 CFR Part 15, Subpart C 15.249(a)

Test Method: ANSI C63.10 (2013) Section 6.5&6.6

Measurement Distance: 3m

Limit:

Frequency	Limit (dBuV/m @3m)	Remark
902MHz-928MHz	94.0	Quasi-peak Value

7.3.1 E.U.T. Operation


Operating Environment:

Temperature: 22.3 °C Humidity: 55.6 % RH Atmospheric Pressure: 1005 mbar

Pretest these modes to find the worst case:
d:TX mode(Module A)_Keep the EUT in transmitting with modulation mode.
e:TX mode(Module B)_Keep the EUT in transmitting with modulation mode.

The worst case for final test:
d:TX mode(Module A)_Keep the EUT in transmitting with modulation mode.
e:TX mode(Module B)_Keep the EUT in transmitting with modulation mode.

7.3.2 Test Setup Diagram



7.3.3 Measurement Procedure and Data

- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.

Remark: Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor

7.3.4 Measurement Procedure and Data

The detailed test data see: Appendix 15.249

7.4 Restricted Band Around Fundamental Frequency

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.249(d) & 15.209

Test Method: ANSI C63.10 (2013) Section 6.4&6.5&6.6

Measurement Distance: 3m

Limit:

Frequency	Limit (dBuV/m @3m)	Remark
30MHz-88MHz	40.0	Quasi-peak Value
88MHz-216MHz	43.5	Quasi-peak Value
216MHz-960MHz	46.0	Quasi-peak Value
960MHz-1GHz	54.0	Quasi-peak Value
Above 1GHz	54.0	Average Value
Above 1GHz	74.0	Peak Value

Emission radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in Section 15.209, whichever is the lesser attenuation.

7.4.1 E.U.T. Operation


Operating Environment:

Temperature: 24.5 °C Humidity: 55.5 % RH Atmospheric Pressure: 1005 mbar

Pretest these modes to find the worst case:
d:TX mode(Module A)_Keep the EUT in transmitting with modulation mode.
e:TX mode(Module B)_Keep the EUT in transmitting with modulation mode.

The worst case for final test:
d:TX mode(Module A)_Keep the EUT in transmitting with modulation mode.
e:TX mode(Module B)_Keep the EUT in transmitting with modulation mode.

7.4.2 Test Setup Diagram



7.4.3 Measurement Procedure and Data

- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.

Remark: Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor

7.4.4 Measurement Procedure and Data

The detailed test data see: Appendix 15.249

7.5 Radiated Emissions

Test Requirement 47 CFR Part 15, Subpart C 15.209 & 15.249 (a),(d)

Test Method: ANSI C63.10 (2013) Section 6.4&6.5&6.6

Limit:

Frequency(MHz)	Field strength (microvolts/meter)	Limit (dBuV/m)	Detector	Measurement Distance (meters)
0.009-0.490	2400/F(kHz)	-	-	300
0.490-1.705	24000/F(kHz)	-	-	30
1.705-30	30	-	-	30
30-88	100	40.0	QP	3
88-216	150	43.5	QP	3
216-960	200	46.0	QP	3
960-1000	500	54.0	QP	3
Above 1000	500	54.0	AV	3

7.5.1 E.U.T. Operation


Operating Environment:

Temperature: 22.4 °C Humidity: 61.9 % RH Atmospheric Pressure: 1005 mbar

Pretest these modes to find the worst case:
d:TX mode(Module A)_Keep the EUT in transmitting with modulation mode.
e:TX mode(Module B)_Keep the EUT in transmitting with modulation mode.

The worst case for final test:
d:TX mode(Module A)_Keep the EUT in transmitting with modulation mode.
e:TX mode(Module B)_Keep the EUT in transmitting with modulation mode.

7.5.2 Test Setup Diagram




7.5.3 Measurement Procedure and Data

For testing performed with the loop antenna, the center of the loop was positioned 1 m above the ground and positioned with its plane vertical at the specified distance from the EUT. During testing the loop was rotated about its vertical axis for maximum response at each azimuth and also investigated with the loop positioned in the horizontal plane. Only the worst position of vertical was shown in the report.

Radiated Emission below 1GHz

30MHz~1GHz (QP)

Worst mode: d, Polarization:Horizontal;




Condition: 3m HORIZONTAL

Job No. : 05356CR

Test mode: d

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Limit Level	Limit Line	Over Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	32.86	0.60	20.92	27.45	34.40	28.47	40.00	-11.53
2 pp	55.22	0.80	13.66	27.40	44.51	31.57	40.00	-8.43
3	58.20	0.80	13.37	27.40	44.32	31.09	40.00	-8.91
4	294.11	1.87	19.37	26.65	31.96	26.55	46.00	-19.45
5	399.03	2.20	22.38	27.18	32.31	29.71	46.00	-16.29
6	665.80	2.84	27.48	27.84	29.72	32.20	46.00	-13.80

Polarization:Vertical;




Condition: 3m VERTICAL

Job No. : 05356CR

Test mode: d

Freq	Cable	Ant	Preamp	Read	Limit		Over	
	MHz	Loss	Factor	Factor	Level	Level	Line	Limit
1 pp	32.86	0.60	20.92	27.45	39.50	33.57	40.00	-6.43
2	47.49	0.75	14.96	27.41	41.14	29.44	40.00	-10.56
3	59.03	0.80	13.29	27.40	44.81	31.50	40.00	-8.50
4	96.77	1.17	13.72	27.35	42.62	30.16	43.50	-13.34
5	129.01	1.27	13.38	27.19	33.15	20.61	43.50	-22.89
6	306.75	1.92	19.82	26.68	31.80	26.86	46.00	-19.14

Mode: d; Polarization:Horizontal; ; Channel:Low



Condition: 3m HORIZONTAL


Job No : 05356CR

Mode : 902.3 TX RSE

Note : ANT1 P=10

		Cable Freq	Loss	Ant Factor	Preamp Factor	Read Level	Limit Level	Line Level	Over Limit	Over Remark
		MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1333.521	4.92	25.16	41.29	47.87	36.66	74.00	-37.34	Peak	
2	1804.600	5.11	27.08	41.59	48.19	38.79	74.00	-35.21	Peak	
3	2706.900	5.77	29.65	42.00	46.81	40.23	74.00	-33.77	Peak	
4	3609.200	6.58	31.92	42.24	47.05	43.31	74.00	-30.69	Peak	
5	4613.176	7.68	33.74	42.44	49.72	48.70	74.00	-25.30	Peak	
6 pp	5714.786	9.61	34.82	41.85	49.28	51.86	74.00	-22.14	Peak	

Mode: d; Polarization:Vertical; ; Channel:Low



Condition: 3m VERTICAL


Job No : 05356CR

Mode : 902.3 TX RSE

Note : ANT1 P=10

	Cable Freq	Ant Loss	Preamp Factor	Read Level	Limit Level	Line Level	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	1333.521	4.92	25.16	41.29	48.16	36.95	74.00	-37.05 Peak
2	1804.600	5.11	27.08	41.59	45.54	36.14	74.00	-37.86 Peak
3	2202.927	5.21	28.19	41.79	47.56	39.17	74.00	-34.83 Peak
4	2706.900	5.77	29.65	42.00	46.23	39.65	74.00	-34.35 Peak
5	3609.200	6.58	31.92	42.24	47.42	43.68	74.00	-30.32 Peak
6 pp	4943.107	8.03	34.13	42.49	50.33	50.00	74.00	-24.00 Peak

Mode: d; Polarization:Horizontal; ; Channel:Middle



Condition: 3m HORIZONTAL


Job No : 05356CR

Mode : 923.3 TX RSE

Note : ANT1 P=10

		Cable Freq	Ant Loss	Preamp Factor	Read Level	Limit Level	Over Line	Over Limit	Remark
		MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	1333.521	4.92	25.16	41.29	48.13	36.92	74.00	-37.08	Peak
2	1846.600	5.06	27.24	41.61	47.58	38.27	74.00	-35.73	Peak
3	2769.900	5.82	29.92	42.02	46.12	39.84	74.00	-34.16	Peak
4	3693.200	6.67	32.10	42.26	47.17	43.68	74.00	-30.32	Peak
5	4375.221	7.42	33.39	42.40	50.17	48.58	74.00	-25.42	Peak
6	pp 5345.644	8.62	34.48	42.17	49.59	50.52	74.00	-23.48	Peak

Mode: d; Polarization:Vertical; ; Channel: Middle



Condition: 3m VERTICAL


Job No : 05356CR

Mode : 923.3 TX RSE

Note : ANT1 P=10

Freq	Cable	Ant	Preamp	Read	Limit	Over	Remark
	Freq	Loss	Factor	Factor	Level	Level	Line
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 1333.521	4.92	25.16	41.29	48.58	37.37	74.00	-36.63 Peak
2 1846.600	5.06	27.24	41.61	46.11	36.80	74.00	-37.20 Peak
3 2769.900	5.82	29.92	42.02	46.01	39.73	74.00	-34.27 Peak
4 3693.200	6.67	32.10	42.26	47.85	44.36	74.00	-29.64 Peak
5 4677.352	7.75	33.82	42.45	50.75	49.87	74.00	-24.13 Peak
6 pp 5296.634	8.55	34.44	42.22	49.53	50.30	74.00	-23.70 Peak

Mode: d; Polarization:Horizontal; ; Channel:High



Condition: 3m HORIZONTAL


Job No : 05356CR

Mode : 927.5 TX RSE

Note : ANT1 P=10

Freq	Cable	Ant	Preamp	Read	Limit	Over	Remark	
	Loss	Factor	Factor	Level				
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	1555.966	5.41	26.05	41.44	47.24	37.26	74.00	-36.74 Peak
2	1855.000	5.05	27.27	41.62	46.52	37.22	74.00	-36.78 Peak
3	2782.500	5.83	29.98	42.02	46.25	40.04	74.00	-33.96 Peak
4	3710.000	6.68	32.13	42.27	48.45	44.99	74.00	-29.01 Peak
5	4731.513	7.81	33.89	42.46	49.75	48.99	74.00	-25.01 Peak
6 pp	5662.393	9.43	34.77	41.89	49.80	52.11	74.00	-21.89 Peak

Mode: d; Polarization:Vertical; ; Channel: High



Condition: 3m VERTICAL


Job No : 05356CR

Mode : 927.5 TX RSE

Note : ANT1 P=10

Freq	Cable	Ant	Preamp	Read	Limit	Over	Remark	
	Loss	Factor	Factor	Level				
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	1510.080	5.47	25.85	41.41	47.57	37.48	74.00	-36.52 Peak
2	1855.000	5.05	27.27	41.62	45.10	35.80	74.00	-38.20 Peak
3	2782.500	5.83	29.98	42.02	45.08	38.87	74.00	-35.13 Peak
4	3710.000	6.68	32.13	42.27	46.65	43.19	74.00	-30.81 Peak
5	4808.394	7.89	33.98	42.47	50.15	49.55	74.00	-24.45 Peak
6 pp	5520.774	8.92	34.62	42.02	48.89	50.41	74.00	-23.59 Peak

Mode: e; Polarization:Horizontal; ; Channel:Low



Condition: 3m HORIZONTAL


Job No : 05356CR

Mode : 902.3 TX RSE

Note : ANT2 P=10

		Cable Freq	Ant Loss	Preamp Factor	Read Level	Limit Level	Over Line	Over Limit	Remark
		MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	1448.772	5.31	25.61	41.37	48.10	37.65	74.00	-36.35	Peak
2	1804.600	5.11	27.08	41.59	47.15	37.75	74.00	-36.25	Peak
3	2123.244	5.09	28.04	41.75	48.20	39.58	74.00	-34.42	Peak
4	2706.900	5.77	29.65	42.00	46.87	40.29	74.00	-33.71	Peak
5	3609.200	6.58	31.92	42.24	46.84	43.10	74.00	-30.90	Peak
6 pp	5176.068	8.37	34.35	42.33	49.31	49.70	74.00	-24.30	Peak

Mode: e; Polarization:Vertical; ; Channel:Low



Condition: 3m VERTICAL


Job No : 05356CR

Mode : 902.3 TX RSE

Note : ANT2 P=10

Freq	Cable	Ant	Preamp	Read	Limit	Over	Remark	
	Loss	Factor	Factor	Level				
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	1438.799	5.28	25.57	41.36	47.91	37.40	74.00	-36.60 Peak
2	1804.600	5.11	27.08	41.59	46.15	36.75	74.00	-37.25 Peak
3	2706.900	5.77	29.65	42.00	47.02	40.44	74.00	-33.56 Peak
4	3609.200	6.58	31.92	42.24	46.48	42.74	74.00	-31.26 Peak
5	4698.941	7.78	33.85	42.45	49.88	49.06	74.00	-24.94 Peak
6 pp	5345.644	8.62	34.48	42.17	49.72	50.65	74.00	-23.35 Peak

Mode: e; Polarization:Horizontal; ; Channel:Middle



Condition: 3m HORIZONTAL


Job No : 05356CR

Mode : 923.3 TX RSE

Note : ANT2 P=10

		Cable Freq	Ant Loss	Preamp Factor	Read Level	Limit Level	Over Line	Over Limit	Remark
		MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	1333.521	4.92	25.16	41.29	48.01	36.80	74.00	-37.20	Peak
2	1846.600	5.06	27.24	41.61	46.26	36.95	74.00	-37.05	Peak
3	2769.900	5.82	29.92	42.02	45.69	39.41	74.00	-34.59	Peak
4	3693.200	6.67	32.10	42.26	47.41	43.92	74.00	-30.08	Peak
5	4246.196	7.27	33.16	42.37	49.57	47.63	74.00	-26.37	Peak
6 pp	5470.160	8.81	34.58	42.06	49.37	50.70	74.00	-23.30	Peak

Mode: e; Polarization:Vertical; ; Channel: Middle



Condition: 3m VERTICAL


Job No : 05356CR

Mode : 923.3 TX RSE

Note : ANT2 P=10

Freq	Cable	Ant	Preamp	Read	Limit	Over	Remark
	Freq	Loss	Factor	Factor	Level	Level	Line
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 1333.521	4.92	25.16	41.29	47.99	36.78	74.00	-37.22 Peak
2 1846.600	5.06	27.24	41.61	47.63	38.32	74.00	-35.68 Peak
3 2269.865	5.31	28.31	41.82	51.16	42.96	74.00	-31.04 Peak
4 2769.900	5.82	29.92	42.02	45.47	39.19	74.00	-34.81 Peak
5 3693.200	6.67	32.10	42.26	47.55	44.06	74.00	-29.94 Peak
6 pp 5069.907	8.20	34.26	42.43	50.84	50.87	74.00	-23.13 Peak

Mode: e; Polarization:Horizontal; ; Channel:High



Condition: 3m HORIZONTAL


Job No : 05356CR

Mode : 927.5 TX RSE

Note : ANT2 P=10

Freq	Cable	Ant	Preamp	Read	Limit	Over	Remark	
	Loss	Factor	Factor	Level				
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	1492.794	5.46	25.77	41.40	48.89	38.72	74.00	-35.28 Peak
2	1855.000	5.05	27.27	41.62	47.54	38.24	74.00	-35.76 Peak
3	2782.500	5.83	29.98	42.02	46.22	40.01	74.00	-33.99 Peak
4	3076.097	6.06	31.03	42.12	48.83	43.80	74.00	-30.20 Peak
5	3710.000	6.68	32.13	42.27	47.48	44.02	74.00	-29.98 Peak
6 pp	5236.004	8.46	34.39	42.27	50.54	51.12	74.00	-22.88 Peak

Mode: e; Polarization:Vertical; ; Channel: High



Condition: 3m VERTICAL

Job No : 05356CR

Mode : 927.5 TX RSE

Note : ANT2 P=10


Freq	Cable	Ant	Preamp	Read	Limit	Over	Remark
	Loss	Factor	Factor	Level			
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 1333.521	4.92	25.16	41.29	48.06	36.85	74.00	-37.15 Peak
2 1855.000	5.05	27.27	41.62	47.40	38.10	74.00	-35.90 Peak
3 2782.500	5.83	29.98	42.02	45.78	39.57	74.00	-34.43 Peak
4 3126.079	6.11	31.11	42.13	48.67	43.76	74.00	-30.24 Peak
5 3710.000	6.68	32.13	42.27	47.78	44.32	74.00	-29.68 Peak
6 pp 5482.770	8.82	34.59	42.05	49.55	50.91	74.00	-23.09 Peak


8 Photographs

8.1 Conducted Emissions at AC Power Line (150kHz-30MHz) Test Setup



8.2 Radiated Emissions





8.3 EUT Constructional Details (EUT Photos)


Refer to external and internal photos.


9 Appendix


9.1 Appendix 15.249

1.20 dB Bandwidth

Test Module	Test Channel	EBW[MHz]	Limit[MHz]	Verdict
A	902.3	0.142	---	PASS
A	923.3	0.142	---	PASS
A	927.5	0.142	---	PASS
B	902.3	0.154	---	PASS
B	923.3	0.153	---	PASS
B	927.5	0.153	---	PASS








2. Field Strength of the Fundamental Signal and Restricted Band Around Fundamental Frequency**Module A**

902.3MHz




Condition: 3m HORIZONTAL

Job No. : 05356CR

Test mode: TX

: 902.3M&Module A

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Limit Level	Limit Line	Over Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	902.00	3.60	29.81	27.04	25.46	31.83	46.00	-14.17
2 pp	902.30	3.60	29.81	27.04	85.31	91.68	94.00	-2.32
3	928.00	3.63	29.95	26.90	13.50	20.18	46.00	-25.82



Condition: 3m VERTICAL


Job No. : 05356CR

Test mode: TX

: 902.3M&Module A

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Limit Level	Limit Line	Over Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	902.00	3.60	29.81	27.04	31.10	37.47	46.00	-8.53
2 pp	902.30	3.60	29.81	27.04	83.63	90.00	94.00	-4.00
3	928.00	3.63	29.95	26.90	16.01	22.69	46.00	-23.31

923.3MHz




Condition: 3m HORIZONTAL

Job No. : 05356CR

Test mode: TX

: 923.3M&Module A

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Limit Level	Line Limit	Over Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	902.00	3.60	29.81	27.04	9.00	15.37	46.00	-30.63
2 pp	923.30	3.62	29.92	26.93	85.89	92.50	94.00	-1.50
3 qp	928.00	3.63	29.95	26.90	8.70	15.38	46.00	-30.62



Condition: 3m VERTICAL


Job No. : 05356CR

Test mode: TX

: 923.3M&Module A

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Limit Level	Limit Line	Over Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	902.00	3.60	29.81	27.04	7.78	14.15	46.00	-31.85
2 pp	923.30	3.62	29.92	26.93	85.13	91.74	94.00	-2.26
3 qp	928.00	3.63	29.95	26.90	8.00	14.68	46.00	-31.32

927.5MHz




Condition: 3m HORIZONTAL

Job No. : 05356CR

Test mode: TX

: 927.5M&Module A

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Limit Level	Limit Line	Over Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	902.00	3.60	29.81	27.04	10.11	16.48	46.00	-29.52
2 pp	927.50	3.63	29.94	26.90	85.37	92.04	94.00	-1.96
3 qp	928.00	3.63	29.95	26.90	22.91	29.59	46.00	-16.41



Condition: 3m VERTICAL

Job No. : 05356CR


Test mode: TX

: 927.5M&Module A

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Limit Level	Limit Line	Over Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	902.00	3.60	29.81	27.04	9.26	15.63	46.00	-30.37
2 pp	927.50	3.63	29.94	26.90	85.20	91.87	94.00	-2.13
3 qp	928.00	3.63	29.95	26.90	19.67	26.35	46.00	-19.65

Module B

902.3MHz




Condition: 3m HORIZONTAL

Job No. : 05356CR

Test mode: TX

: 902.3M&Module B

		Cable Freq	Ant Loss	Preamp Factor	Read Level	Limit Level	Limit Line	Over Limit	
		MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1		902.01	3.60	29.81	27.04	21.50	27.87	94.00	-66.13
2 pp		902.28	3.60	29.81	27.04	82.72	89.09	94.00	-4.91
3		928.00	3.63	29.95	26.90	13.50	20.18	46.00	-25.82



Condition: 3m VERTICAL


Job No. : 05356CR

Test mode: TX

: 902.3M&Module B

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Limit Level	Limit Line	Over Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	902.00	3.60	29.81	27.04	20.91	27.28	46.00	-18.72
2 pp	902.28	3.60	29.81	27.04	84.20	90.57	94.00	-3.43
3	928.00	3.63	29.95	26.90	15.04	21.72	46.00	-24.28

923.3MHz




Condition: 3m HORIZONTAL

Job No. : 05356CR

Test mode: TX

: 923.3M&Module B

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Limit Level	Line Limit	Over Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	902.00	3.60	29.81	27.04	13.93	20.30	46.00	-25.70
2 pp	923.30	3.62	29.92	26.93	84.36	90.97	94.00	-3.03
3 qp	928.00	3.63	29.95	26.90	15.01	21.69	46.00	-24.31



Condition: 3m VERTICAL


Job No. : 05356CR

Test mode: TX

: 923.3M&Module B

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Limit Level	Limit Line	Over Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	902.00	3.60	29.81	27.04	12.54	18.91	46.00	-27.09
2 pp	923.30	3.62	29.92	26.93	85.23	91.84	94.00	-2.16
3 qp	928.00	3.63	29.95	26.90	13.30	19.98	46.00	-26.02

927.5MHz




Condition: 3m HORIZONTAL

Job No. : 05356CR

Test mode: TX

: 927.5M&Module B

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Limit Level	Limit Line	Over Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	902.00	3.60	29.81	27.04	13.24	19.61	46.00	-26.39
2 pp	927.50	3.63	29.94	26.90	76.74	83.41	94.00	-10.59
3 qp	928.00	3.63	29.95	26.90	17.03	23.71	46.00	-22.29



Condition: 3m VERTICAL

Job No. : 05356CR

Test mode: TX

: 927.5M&Module B

		Cable Freq	Ant Loss	Preamp Factor	Read Level	Limit Level	Limit Line	Over Limit	
		MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1		902.00	3.60	29.81	27.04	13.44	19.81	46.00	-26.19
2 pp		927.50	3.63	29.94	26.90	82.60	89.27	94.00	-4.73
3 qp		928.00	3.63	29.95	26.90	19.15	25.83	46.00	-20.17

- End of the Report -