

## FCC PART 15.247 TEST REPORT

For

### TECNO MOBILE LIMITED

FLAT 39 8/F BLOCK D WAH LOK INDUSTRIAL CENTRE 31-35 SHAN MEI STREET  
FOTAN NT Hong Kong

**FCC ID: 2ADYY-KF6**

|                                                                                                                                                                                                                                                                                                                         |                                      |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------|
| <b>Report Type:</b><br>Original Report                                                                                                                                                                                                                                                                                  | <b>Product Type:</b><br>Mobile phone |
| <b>Report Number:</b> SZ1210205-04282E-00C                                                                                                                                                                                                                                                                              |                                      |
| <b>Report Date:</b> 2021-04-07                                                                                                                                                                                                                                                                                          |                                      |
| Jacob Kong                                                                                                                                                                                                                         |                                      |
| <b>Reviewed By:</b> RF Engineer                                                                                                                                                                                                                                                                                         |                                      |
| <b>Prepared By:</b> Bay Area Compliance Laboratories Corp. (Shenzhen)<br>5F(B-West) , 6F, 7F, the 3rd Phase of Wan Li Industrial<br>Building D, Shihua Rd, FuTian Free Trade Zone,<br>Shenzhen, China<br>Tel: +86-755-33320018<br>Fax: +86-755-33320008<br><a href="http://www.baclcorp.com.cn">www.baclcorp.com.cn</a> |                                      |

**Note:** This report may contain data that are not covered by the A2LA accreditation and are marked with an asterisk “★”.

BACL is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with an asterisk “\*”. Customer model name, addresses, names, trademarks etc. are not considered data.

This report cannot be reproduced except in full, without prior written approval of the Company. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

## **TABLE OF CONTENTS**

|                                                                          |           |
|--------------------------------------------------------------------------|-----------|
| <b>GENERAL INFORMATION.....</b>                                          | <b>4</b>  |
| PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) .....                 | 4         |
| OBJECTIVE .....                                                          | 4         |
| TEST METHODOLOGY .....                                                   | 4         |
| MEASUREMENT UNCERTAINTY .....                                            | 5         |
| <b>SYSTEM TEST CONFIGURATION .....</b>                                   | <b>6</b>  |
| DESCRIPTION OF TEST CONFIGURATION .....                                  | 6         |
| EQUIPMENT MODIFICATIONS .....                                            | 7         |
| EUT EXERCISE SOFTWARE .....                                              | 7         |
| DUTY CYCLE .....                                                         | 8         |
| SUPPORT EQUIPMENT LIST AND DETAILS .....                                 | 8         |
| EXTERNAL I/O CABLE.....                                                  | 8         |
| BLOCK DIAGRAM OF TEST SETUP .....                                        | 8         |
| <b>SUMMARY OF TEST RESULTS .....</b>                                     | <b>9</b>  |
| <b>TEST EQUIPMENT LIST .....</b>                                         | <b>10</b> |
| <b>FCC§15.247 (i), §1.1307 (b) (1) &amp; §2.1093 – RF EXPOSURE .....</b> | <b>11</b> |
| APPLICABLE STANDARD .....                                                | 11        |
| <b>FCC §15.203 - ANTENNA REQUIREMENT.....</b>                            | <b>12</b> |
| APPLICABLE STANDARD .....                                                | 12        |
| ANTENNA CONNECTOR CONSTRUCTION .....                                     | 12        |
| <b>FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS .....</b>               | <b>13</b> |
| APPLICABLE STANDARD .....                                                | 13        |
| EUT SETUP .....                                                          | 13        |
| EMI TEST RECEIVER SETUP.....                                             | 13        |
| TEST PROCEDURE .....                                                     | 13        |
| CORRECTED FACTOR & MARGIN CALCULATION .....                              | 14        |
| TEST DATA .....                                                          | 14        |
| <b>FCC §15.209, §15.205 &amp; §15.247(d) - SPURIOUS EMISSIONS.....</b>   | <b>17</b> |
| APPLICABLE STANDARD .....                                                | 17        |
| EUT SETUP .....                                                          | 17        |
| EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP .....                        | 18        |
| TEST PROCEDURE .....                                                     | 18        |
| CORRECTED AMPLITUDE & MARGIN CALCULATION .....                           | 18        |
| TEST DATA .....                                                          | 18        |
| <b>FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH.....</b>                 | <b>30</b> |
| APPLICABLE STANDARD .....                                                | 30        |
| TEST PROCEDURE .....                                                     | 30        |
| TEST DATA .....                                                          | 30        |
| <b>FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER.....</b>          | <b>31</b> |
| APPLICABLE STANDARD .....                                                | 31        |
| TEST PROCEDURE .....                                                     | 31        |
| TEST DATA .....                                                          | 31        |

|                                                                       |           |
|-----------------------------------------------------------------------|-----------|
| <b>FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE.....</b> | <b>32</b> |
| APPLICABLE STANDARD .....                                             | 32        |
| TEST PROCEDURE .....                                                  | 32        |
| TEST DATA .....                                                       | 32        |
| <b>FCC §15.247(e) - POWER SPECTRAL DENSITY .....</b>                  | <b>33</b> |
| APPLICABLE STANDARD .....                                             | 33        |
| TEST PROCEDURE .....                                                  | 33        |
| TEST DATA .....                                                       | 33        |
| <b>APPENDIX Wi-Fi.....</b>                                            | <b>34</b> |
| APPENDIX A: DTS BANDWIDTH .....                                       | 34        |
| APPENDIX B: OCCUPIED CHANNEL BANDWIDTH .....                          | 42        |
| APPENDIX C: MAXIMUM CONDUCTED OUTPUT POWER .....                      | 49        |
| APPENDIX D: MAXIMUM POWER SPECTRAL DENSITY .....                      | 50        |
| APPENDIX E: BAND EDGE MEASUREMENTS .....                              | 57        |
| APPENDIX G: DUTY CYCLE.....                                           | 61        |
| <b>APPENDIX BLE.....</b>                                              | <b>64</b> |
| APPENDIX A: DTS BANDWIDTH .....                                       | 64        |
| APPENDIX B: OCCUPIED CHANNEL BANDWIDTH .....                          | 68        |
| APPENDIX C: MAXIMUM CONDUCTED PEAK OUTPUT POWER .....                 | 72        |
| APPENDIX D: MAXIMUM POWER SPECTRAL DENSITY .....                      | 73        |
| APPENDIX E: BAND EDGE MEASUREMENTS .....                              | 77        |
| APPENDIX G: DUTY CYCLE.....                                           | 79        |

## GENERAL INFORMATION

### Product Description for Equipment under Test (EUT)

|                              |                                                                                                                   |
|------------------------------|-------------------------------------------------------------------------------------------------------------------|
| Product                      | Mobile phone                                                                                                      |
| Tested Model                 | KF6                                                                                                               |
| Frequency Range              | BLE: 2402-2480MHz<br>Wi-Fi: 2412-2462MHz/2422-2452MHz                                                             |
| Maximum Conducted Peak Power | BLE: -4.05dBm<br>Wi-Fi: 15.65(802.11b), 19.93dBm(802.11g)<br>19.20dBm(802.11n-HT20), 17.17dBm(802.11n-HT40)       |
| Modulation Technique         | BLE: GFSK<br>Wi-Fi: DSSS, OFDM                                                                                    |
| Antenna Specification*       | 1.2dBi(It is provided by the applicant)                                                                           |
| Voltage Range                | DC 3.87V from battery or DC 5.0V from adapter                                                                     |
| Date of Test                 | 2021-03-04 to 2021-03-19                                                                                          |
| Sample number                | SZ1210205-04282E-RF-S1(RSE&CE Test),<br>SZ1210205-04282E-RF-S2(RF Conducted Test)<br>(Assigned by BACL, Shenzhen) |
| Received date                | 2021-02-05                                                                                                        |
| Sample/EUT Status            | Good condition                                                                                                    |
| Adapter information          | Model: U100TSA<br>Input: AC 100-240V, 50/60Hz, 0.3A<br>Output: DC 5.0V, 2.0A                                      |

### Objective

This report is in accordance with Part 2-Subpart J, Part 15-Subparts A and C of the Federal Communication Commission's rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

### Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

And KDB 558074 D01 15.247 Meas Guidance v05r02.

All emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Shenzhen). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

**Measurement Uncertainty**

| Parameter                          |            | Uncertainty |
|------------------------------------|------------|-------------|
| Occupied Channel Bandwidth         |            | ±5%         |
| RF Output Power with Power meter   |            | ±0.73dB     |
| RF conducted test with spectrum    |            | ±1.6dB      |
| AC Power Lines Conducted Emissions |            | ±1.95dB     |
| Emissions,<br>Radiated             | Below 1GHz | ±4.75dB     |
|                                    | Above 1GHz | ±4.88dB     |
| Temperature                        |            | ±1 °C       |
| Humidity                           |            | ±6%         |
| Supply voltages                    |            | ±0.4%       |

*Note: The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval. Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.*

**Test Facility**

The test site used by Bay Area Compliance Laboratories Corp. (Shenzhen) to collect test data is located on the 5F(B-West) , 6F, 7F, the 3rd Phase of Wan Li Industrial Building D, Shihua Rd, FuTian Free Trade Zone, Shenzhen, China.

The test site has been approved by the FCC under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No.: 342867, the FCC Designation No.: CN1221.

The test site has been registered with ISED Canada under ISED Canada Registration Number 3062B.

## SYSTEM TEST CONFIGURATION

### Description of Test Configuration

For 802.11b, 802.11g and 802.11n-HT20 mode, 11 channels are provided to testing:

| Channel | Frequency (MHz) | Channel | Frequency (MHz) |
|---------|-----------------|---------|-----------------|
| 1       | 2412            | 8       | 2447            |
| 2       | 2417            | 9       | 2452            |
| 3       | 2422            | 10      | 2457            |
| 4       | 2427            | 11      | 2462            |
| 5       | 2432            | /       | /               |
| 6       | 2437            | /       | /               |
| 7       | 2442            | /       | /               |

For 802.11b, 802.11g, 802.11n-HT20 mode, EUT was tested with Channel 1, 6 and 11.

For 802.11n-HT40 mode, 7 channels are provided to testing:

| Channel | Frequency (MHz) | Channel | Frequency (MHz) |
|---------|-----------------|---------|-----------------|
| 1       | 2422            | 6       | 2447            |
| 2       | 2427            | 7       | 2452            |
| 3       | 2432            | /       | /               |
| 4       | 2437            | /       | /               |
| 5       | 2442            | /       | /               |

EUT was tested with Channel 1, 4 and 7.

For BLE mode, 40 channels are provided to testing:

| Channel | Frequency (MHz) | Channel | Frequency (MHz) |
|---------|-----------------|---------|-----------------|
| 0       | 2402            | 20      | 2442            |
| 1       | 2404            | 21      | 2444            |
| 2       | 2406            | 22      | 2446            |
| 3       | 2408            | 23      | 2448            |
| 4       | 2410            | 24      | 2450            |
| 5       | 2412            | 25      | 2452            |
| 6       | 2414            | 26      | 2454            |
| 7       | 2416            | 27      | 2456            |
| 8       | 2418            | 28      | 2458            |
| 9       | 2420            | 29      | 2460            |
| 10      | 2422            | 30      | 2462            |
| 11      | 2424            | 31      | 2464            |
| 12      | 2426            | 32      | 2466            |
| 13      | 2428            | 33      | 2468            |
| 14      | 2430            | 34      | 2470            |
| 15      | 2432            | 35      | 2472            |
| 16      | 2434            | 36      | 2474            |
| 17      | 2436            | 37      | 2476            |
| 18      | 2438            | 38      | 2478            |
| 19      | 2440            | 39      | 2480            |

EUT was tested with Channel 0, 19 and 39.

### Equipment Modifications

No modification was made to the EUT tested.

### EUT Exercise Software

Test in the engineer mode.

The device was tested with the worst case was performed as below:

| Mode         | Data rate     | Power level* |                |              |
|--------------|---------------|--------------|----------------|--------------|
|              |               | Low channel  | Middle channel | High channel |
| 802.11b      | 1 Mbps        | 15           | 15             | 15           |
| 802.11g      | 6 Mbps        | 15           | 15             | 15           |
| 802.11n-HT20 | MCS0          | 15           | 15             | 15           |
| 802.11n-HT40 | MCS0          | 15           | 15             | 15           |
| BLE          | 1Mbps & 2Mbps | Default      | Default        | Default      |

The power level was provided by the applicant.

**Duty cycle**

Test Result Compliant. Please refer to the Appendix BLE & Appendix Wi-Fi.

**Support Equipment List and Details**


| Manufacturer | Description | Model | Serial Number |
|--------------|-------------|-------|---------------|
| /            | /           | /     | /             |

**External I/O Cable**

| Cable Description                    | Length (m) | From Port | To       |
|--------------------------------------|------------|-----------|----------|
| Unshielded Detachable Earphone Cable | 1.2        | EUT       | Earphone |
| Shielded Detachable USB Cable        | 1.0        | EUT       | Adapter  |

**Block Diagram of Test Setup**

For conducted emission:





**SUMMARY OF TEST RESULTS**

| FCC Rules                                | Description of Test                      | Result     |
|------------------------------------------|------------------------------------------|------------|
| §15.247 (i), §1.1307 (b) (1)&<br>§2.1093 | RF Exposure                              | Compliance |
| §15.203                                  | Antenna Requirement                      | Compliance |
| §15.207 (a)                              | AC Line Conducted Emissions              | Compliance |
| §15.205, §15.209,<br>§15.247(d)          | Spurious Emissions                       | Compliance |
| §15.247 (a)(2)                           | 6 dB Emission Bandwidth                  | Compliance |
| §15.247(b)(3)                            | Maximum Conducted Output Power           | Compliance |
| §15.247(d)                               | 100 kHz Bandwidth of Frequency Band Edge | Compliance |
| §15.247(e)                               | Power Spectral Density                   | Compliance |

**TEST EQUIPMENT LIST**

| Manufacturer                    | Description                  | Model                   | Serial Number          | Calibration Date | Calibration Due Date |
|---------------------------------|------------------------------|-------------------------|------------------------|------------------|----------------------|
| <b>Conducted Emissions Test</b> |                              |                         |                        |                  |                      |
| Rohde & Schwarz                 | EMI Test Receiver            | ESCI                    | 101120                 | 2020/08/04       | 2021/08/03           |
| Rohde & Schwarz                 | LISN                         | ENV216                  | 101613                 | 2020/08/04       | 2021/08/03           |
| Rohde & Schwarz                 | Transient Limitor            | ESH3Z2                  | DE25985                | 2020/11/29       | 2021/11/28           |
| Unknown                         | CE Cable                     | CE Cable                | UF A210B-1-0720-504504 | 2020/11/29       | 2021/11/28           |
| Rohde & Schwarz                 | CE Test software             | EMC 32                  | V8.53.0                | NCR              | NCR                  |
| <b>Radiated Emission Test</b>   |                              |                         |                        |                  |                      |
| R&S                             | EMI Test Receiver            | ESR3                    | 102455                 | 2020/08/04       | 2021/08/03           |
| Sonoma instrument               | Pre-amplifier                | 310 N                   | 186238                 | 2020/08/04       | 2021/08/03           |
| Sunol Sciences                  | Broadband Antenna            | JB1                     | A040904-1              | 2020/12/22       | 2023/12/21           |
| Unknown                         | Cable 2                      | RF Cable 2              | F-03-EM197             | 2020/11/29       | 2021/11/28           |
| Unknown                         | Cable                        | Chamber Cable 1         | F-03-EM236             | 2020/11/29       | 2021/11/28           |
| Rohde & Schwarz                 | Auto test software           | EMC 32                  | V9.10                  | NCR              | NCR                  |
| Rohde & Schwarz                 | Spectrum Analyzer            | FSV40-N                 | 102259                 | 2020/08/04       | 2021/08/03           |
| COM-POWER                       | Pre-amplifier                | PA-122                  | 181919                 | 2020/11/29       | 2021/11/28           |
| Quinstar                        | Amplifier                    | QLW-18405536-J0         | 15964001002            | 2020/11/29       | 2021/11/28           |
| Sunol Sciences                  | Horn Antenna                 | 3115                    | 9107-3694              | 2021/01/15       | 2024/01/14           |
| Insulated Wire Inc.             | RF Cable                     | SPS-2503-3150           | 02222010               | 2020/11/29       | 2021/11/28           |
| Unknown                         | RF Cable                     | W1101-EQ1 OUT           | F-19-EM005             | 2020/11/29       | 2021/11/28           |
| SNSD                            | Band Reject filter           | BSF2402-2480MN-0898-001 | 2.4G filter            | 2020/04/20       | 2021/04/20           |
| Ducommun Technologies           | Horn antenna                 | ARH-4223-02             | 1007726-021304         | 2020/12/06       | 2023/12/05           |
| <b>RF Conducted Test</b>        |                              |                         |                        |                  |                      |
| Tonscend Corporation            | RF control Unit              | JS0806-2                | 19D8060154             | 2020/08/04       | 2021/08/03           |
| Rohde & Schwarz                 | Signal and Spectrum Analyzer | FSV40                   | 101473                 | 2020/08/04       | 2021/08/03           |
| Unknown                         | RF Cable                     | Unknown                 | 2301 276               | 2020/11/29       | 2021/11/28           |

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

## **FCC§15.247 (i), §1.1307 (b) (1) & §2.1093 – RF EXPOSURE**

### **Applicable Standard**

According to FCC §2.1093 and §1.1307(b) (1), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

According to KDB 447498 D01 General RF Exposure Guidance

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR, where

1.  $f(\text{GHz})$  is the RF channel transmit frequency in GHz.
2. Power and distance are rounded to the nearest mW and mm before calculation.
3. The result is rounded to one decimal place for comparison.
4. When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm is applied to determine SAR test Exclusion.

### **Measurement Result**

**For worst case:**

| Mode | Frequency (MHz) | Max Tune-up Conducted Power (dBm) | Max Tune-up Conducted Power (mW) | Calculated Distance (mm) | Calculated value | Threshold (1-g SAR) | SAR Test Exclusion |
|------|-----------------|-----------------------------------|----------------------------------|--------------------------|------------------|---------------------|--------------------|
| BLE  | 2402-2480       | -3.0                              | 0.5                              | 5                        | 0.2              | 3.0                 | Yes                |

**Result: No SAR test is required**

For Wi-Fi mode:

Please refer to SAR report SZ1210205-04282E-SA.

---

## **FCC §15.203 - ANTENNA REQUIREMENT**

---

### **Applicable Standard**

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
  - b. Antenna must use a unique type of connector to attach to the EUT.
- Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

And according to FCC 47 CFR section 15.247 (b), if the transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

### **Antenna Connector Construction**

The EUT has one internal antenna arrangement, which was permanently attached and the antenna gain is 1.2 dBi, fulfill the requirement of this section. Please refer to the EUT photos.


**Result:** Compliance.

## FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

### Applicable Standard

FCC§15.207

### EUT Setup



Note: 1. Support units were connected to second LISN.  
2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

### EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

| Frequency Range  | IF B/W |
|------------------|--------|
| 150 kHz – 30 MHz | 9 kHz  |

### Test Procedure

During the conducted emission test, the adapter was connected to the outlet of the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All final data was recorded in the Quasi-peak and average detection mode.

## Corrected Factor & Margin Calculation

The Corrected factor is calculated by adding LISN VDF (Voltage Division Factor), Cable Loss and Transient Limiter Attenuation. The basic equation is as follows:

$$\text{Correction Factor} = \text{LISN VDF} + \text{Cable Loss} + \text{Transient Limiter Attenuation}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7 dB means the emission is 7 dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$


## Test Data

### Environmental Conditions

|                    |           |
|--------------------|-----------|
| Temperature:       | 25 °C     |
| Relative Humidity: | 65 %      |
| ATM Pressure:      | 101.0 kPa |

*The testing was performed by Haiguo Li on 2021-03-09.*


*EUT operation mode: Transmitting & Charging (worst case is 802.11g mode, middle channel)*

**AC 120V/60 Hz, Line****Final Result 1**

| Frequency (MHz) | QuasiPeak (dB $\mu$ V) | Bandwidth (kHz) | Line | Corr. (dB) | Margin (dB) | Limit (dB $\mu$ V) |
|-----------------|------------------------|-----------------|------|------------|-------------|--------------------|
| 2.575210        | 45.8                   | 9.000           | L1   | 19.8       | 10.2        | 56.0               |
| 2.839010        | 46.4                   | 9.000           | L1   | 19.9       | 9.6         | 56.0               |
| 3.238090        | 48.6                   | 9.000           | L1   | 19.9       | 7.4         | 56.0               |
| 3.557410        | 49.9                   | 9.000           | L1   | 19.9       | 6.1         | 56.0               |
| 3.670950        | 49.8                   | 9.000           | L1   | 19.9       | 6.2         | 56.0               |
| 4.001430        | 47.8                   | 9.000           | L1   | 19.9       | 8.2         | 56.0               |

**Final Result 2**

| Frequency (MHz) | Average (dB $\mu$ V) | Bandwidth (kHz) | Line | Corr. (dB) | Margin (dB) | Limit (dB $\mu$ V) |
|-----------------|----------------------|-----------------|------|------------|-------------|--------------------|
| 2.575210        | 38.7                 | 9.000           | L1   | 19.8       | 7.3         | 46.0               |
| 2.839010        | 39.7                 | 9.000           | L1   | 19.9       | 6.3         | 46.0               |
| 3.238090        | 41.6                 | 9.000           | L1   | 19.9       | 4.4         | 46.0               |
| 3.557410        | 42.9                 | 9.000           | L1   | 19.9       | 3.1         | 46.0               |
| 3.670950        | 42.0                 | 9.000           | L1   | 19.9       | 4.0         | 46.0               |
| 4.001430        | 40.6                 | 9.000           | L1   | 19.9       | 5.4         | 46.0               |

**AC 120V/60 Hz, Neutral:****Final Result 1**

| Frequency (MHz) | QuasiPeak (dB µ V) | Bandwidth (kHz) | Line | Corr. (dB) | Margin (dB) | Limit (dB µ V) |
|-----------------|--------------------|-----------------|------|------------|-------------|----------------|
| 2.579450        | 43.4               | 9.000           | N    | 19.8       | 12.6        | 56.0           |
| 2.854530        | 44.8               | 9.000           | N    | 19.9       | 11.2        | 56.0           |
| 3.198210        | 46.9               | 9.000           | N    | 19.9       | 9.1         | 56.0           |
| 3.544990        | 48.9               | 9.000           | N    | 19.9       | 7.1         | 56.0           |
| 3.697690        | 50.1               | 9.000           | N    | 19.9       | 5.9         | 56.0           |
| 4.159930        | 46.1               | 9.000           | N    | 19.9       | 9.9         | 56.0           |



**Final Result 2**

| Frequency (MHz) | Average (dB µ V) | Bandwidth (kHz) | Line | Corr. (dB) | Margin (dB) | Limit (dB µ V) |
|-----------------|------------------|-----------------|------|------------|-------------|----------------|
| 2.622000        | 31.9             | 9.000           | N    | 19.8       | 14.1        | 46.0           |
| 2.870000        | 31.8             | 9.000           | N    | 19.9       | 14.2        | 46.0           |
| 3.190000        | 34.7             | 9.000           | N    | 19.9       | 11.3        | 46.0           |
| 3.534000        | 37.1             | 9.000           | N    | 19.9       | 8.9         | 46.0           |
| 3.814000        | 36.9             | 9.000           | N    | 19.9       | 9.1         | 46.0           |
| 4.022000        | 35.2             | 9.000           | N    | 19.9       | 10.8        | 46.0           |



**FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS****Applicable Standard**

FCC §15.247 (d); §15.209; §15.205;

**EUT Setup****Below 1 GHz:****Above 1GHz:**

The radiated emission tests were performed in the 3 meters test site, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, and FCC 15.247 limits.

## EMI Test Receiver & Spectrum Analyzer Setup

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

| Frequency Range   | RBW     | Video B/W               | IF B/W  | Measurement |
|-------------------|---------|-------------------------|---------|-------------|
| 30 MHz – 1000 MHz | 100 kHz | 300 kHz                 | 120 kHz | QP          |
| Above 1 GHz       | 1MHz    | 3 MHz                   | /       | PK          |
|                   | 1MHz    | 10 Hz <sup>Note 1</sup> | /       | Average     |
|                   | 1MHz    | > 1/T <sup>Note 2</sup> | /       | Average     |

Note 1: when duty cycle is no less than 98%

Note 2: when duty cycle is less than 98%

## Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

## Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

## Test Data


### Environmental Conditions

|                           |                 |
|---------------------------|-----------------|
| <b>Temperature:</b>       | 24~25.1 °C      |
| <b>Relative Humidity:</b> | 44~54 %         |
| <b>ATM Pressure:</b>      | 101.0~101.1 kPa |

*The testing was performed by Kilroy Deng on 2021-03-18 for below 1GHz and Troy Wang on 2021-03-23 for above 1GHz.*

*EUT operation mode: Transmitting*

30 MHz~1 GHz (802.11g mode, middle channel was worst case):



### Critical\_Freqs

| Frequency (MHz) | MaxPeak (dB $\mu$ V/m) | Limit (dB $\mu$ V/m) | Margin (dB) | Height (cm) | Pol | Azimuth (deg) | Corr. (dB) |
|-----------------|------------------------|----------------------|-------------|-------------|-----|---------------|------------|
| 57.645000       | 23.68                  | 40.00                | 16.32       | 100.0       | V   | 20.0          | -16.5      |
| 64.677500       | 23.61                  | 40.00                | 16.39       | 100.0       | V   | 345.0         | -16.4      |
| 91.837500       | 27.32                  | 43.50                | 16.18       | 200.0       | H   | 268.0         | -16.0      |
| 575.988750      | 36.46                  | 46.00                | 9.54        | 200.0       | H   | 21.0          | -3.8       |
| 838.131250      | 29.21                  | 46.00                | 16.79       | 100.0       | H   | 138.0         | 0.0        |
| 947.620000      | 32.58                  | 46.00                | 13.42       | 200.0       | H   | 345.0         | 1.6        |

**1 GHz-25 GHz (Wi-Fi):****802.11b Mode:**

| Frequency<br>(MHz)       | Receiver          |            | Turntable<br>Degree | Rx Antenna    |                | Corrected<br>Factor<br>(dB/m) | Corrected<br>Amplitude<br>(dBμV/m) | Limit<br>(dBμV/m) | Margin<br>(dB) |
|--------------------------|-------------------|------------|---------------------|---------------|----------------|-------------------------------|------------------------------------|-------------------|----------------|
|                          | Reading<br>(dBμV) | PK/QP/Ave. |                     | Height<br>(m) | Polar<br>(H/V) |                               |                                    |                   |                |
| Low Channel (2412 MHz)   |                   |            |                     |               |                |                               |                                    |                   |                |
| 2387.28                  | 28.33             | PK         | 80                  | 2.2           | H              | 31.87                         | 60.20                              | 74                | 13.80          |
| 2387.28                  | 13.75             | Ave.       | 80                  | 2.2           | H              | 31.87                         | 45.62                              | 54                | 8.38           |
| 2493.69                  | 28.54             | PK         | 92                  | 1.9           | H              | 32.13                         | 60.67                              | 74                | 13.33          |
| 2493.69                  | 13.41             | Ave.       | 92                  | 1.9           | H              | 32.13                         | 45.54                              | 54                | 8.46           |
| 4824.00                  | 48.67             | PK         | 187                 | 1.5           | H              | 6.28                          | 54.95                              | 74                | 19.05          |
| 4824.00                  | 43.17             | Ave.       | 187                 | 1.5           | H              | 6.28                          | 49.45                              | 54                | 4.55           |
| Middle Channel (2437MHz) |                   |            |                     |               |                |                               |                                    |                   |                |
| 4874.00                  | 47.93             | PK         | 139                 | 1.4           | H              | 6.76                          | 54.69                              | 74                | 19.31          |
| 4874.00                  | 41.40             | Ave.       | 139                 | 1.4           | H              | 6.76                          | 48.16                              | 54                | 5.84           |
| High Channel (2462 MHz)  |                   |            |                     |               |                |                               |                                    |                   |                |
| 2341.08                  | 28.27             | PK         | 309                 | 1.3           | H              | 31.64                         | 59.91                              | 74                | 14.09          |
| 2341.08                  | 13.51             | Ave.       | 309                 | 1.3           | H              | 31.64                         | 45.15                              | 54                | 8.85           |
| 2493.63                  | 28.35             | PK         | 229                 | 2.0           | H              | 32.13                         | 60.48                              | 74                | 13.52          |
| 2493.63                  | 13.49             | Ave.       | 229                 | 2.0           | H              | 32.13                         | 45.62                              | 54                | 8.38           |
| 4924.00                  | 48.36             | PK         | 242                 | 2.1           | H              | 6.76                          | 55.12                              | 74                | 18.88          |
| 4924.00                  | 44.22             | Ave.       | 242                 | 2.1           | H              | 6.76                          | 50.98                              | 54                | 3.02           |

**802.11g Mode:**

| Frequency<br>(MHz)        | Receiver          |            | Turntable<br>Degree | Rx Antenna    |                | Corrected<br>Factor<br>(dB/m) | Corrected<br>Amplitude<br>(dBμV/m) | Limit<br>(dBμV/m) | Margin<br>(dB) |
|---------------------------|-------------------|------------|---------------------|---------------|----------------|-------------------------------|------------------------------------|-------------------|----------------|
|                           | Reading<br>(dBμV) | PK/QP/Ave. |                     | Height<br>(m) | Polar<br>(H/V) |                               |                                    |                   |                |
| Low Channel (2412 MHz)    |                   |            |                     |               |                |                               |                                    |                   |                |
| 2389.94                   | 32.12             | PK         | 206                 | 1.3           | H              | 31.87                         | 63.99                              | 74                | 10.01          |
| 2389.94                   | 16.09             | Ave.       | 206                 | 1.3           | H              | 31.87                         | 47.96                              | 54                | 6.04           |
| 2488.36                   | 28.36             | PK         | 52                  | 2.1           | H              | 32.13                         | 60.49                              | 74                | 13.51          |
| 2488.36                   | 14.03             | Ave.       | 52                  | 2.1           | H              | 32.13                         | 46.16                              | 54                | 7.84           |
| 4824.00                   | 45.92             | PK         | 355                 | 2.1           | H              | 6.28                          | 52.20                              | 74                | 21.80          |
| 4824.00                   | 30.85             | Ave.       | 355                 | 2.1           | H              | 6.28                          | 37.13                              | 54                | 16.87          |
| Middle Channel (2437 MHz) |                   |            |                     |               |                |                               |                                    |                   |                |
| 4874.00                   | 45.83             | PK         | 331                 | 1.6           | H              | 6.76                          | 52.59                              | 74                | 21.41          |
| 4874.00                   | 30.78             | Ave.       | 331                 | 1.6           | H              | 6.76                          | 37.54                              | 54                | 16.46          |
| High Channel (2462 MHz)   |                   |            |                     |               |                |                               |                                    |                   |                |
| 2384.64                   | 28.35             | PK         | 221                 | 2.2           | H              | 31.87                         | 60.22                              | 74                | 13.78          |
| 2384.64                   | 14.25             | Ave.       | 221                 | 2.2           | H              | 31.87                         | 46.12                              | 54                | 7.88           |
| 2488.67                   | 28.69             | PK         | 32                  | 1.6           | H              | 32.13                         | 60.82                              | 74                | 13.18          |
| 2488.67                   | 14.29             | Ave.       | 32                  | 1.6           | H              | 32.13                         | 46.42                              | 54                | 7.58           |
| 4924.00                   | 46.12             | PK         | 63                  | 1.3           | H              | 6.76                          | 52.88                              | 74                | 21.12          |
| 4924.00                   | 30.92             | Ave.       | 63                  | 1.3           | H              | 6.76                          | 37.68                              | 54                | 16.32          |

**802.11n-HT20 Mode:**

| Frequency<br>(MHz)        | Receiver          |            | Turntable<br>Degree | Rx Antenna    |                | Corrected<br>Factor<br>(dB/m) | Corrected<br>Amplitude<br>(dBμV/m) | Limit<br>(dBμV/m) | Margin<br>(dB) |
|---------------------------|-------------------|------------|---------------------|---------------|----------------|-------------------------------|------------------------------------|-------------------|----------------|
|                           | Reading<br>(dBμV) | PK/QP/Ave. |                     | Height<br>(m) | Polar<br>(H/V) |                               |                                    |                   |                |
| Low Channel (2412 MHz)    |                   |            |                     |               |                |                               |                                    |                   |                |
| 2389.94                   | 35.15             | PK         | 328                 | 2.4           | H              | 31.87                         | 67.02                              | 74                | 6.98           |
| 2389.94                   | 16.97             | Ave.       | 328                 | 2.4           | H              | 31.87                         | 48.84                              | 54                | 5.16           |
| 2493.88                   | 28.65             | PK         | 312                 | 2.3           | H              | 32.13                         | 60.78                              | 74                | 13.22          |
| 2493.88                   | 14.42             | Ave.       | 312                 | 2.3           | H              | 32.13                         | 46.55                              | 54                | 7.45           |
| 4824.00                   | 43.49             | PK         | 13                  | 1.4           | H              | 6.28                          | 49.77                              | 74                | 24.23          |
| 4824.00                   | 29.44             | Ave.       | 13                  | 1.4           | H              | 6.28                          | 35.72                              | 54                | 18.28          |
| Middle Channel (2437 MHz) |                   |            |                     |               |                |                               |                                    |                   |                |
| 4874.00                   | 43.75             | PK         | 74                  | 1.6           | H              | 6.76                          | 50.51                              | 74                | 23.49          |
| 4874.00                   | 29.53             | Ave.       | 74                  | 1.6           | H              | 6.76                          | 36.29                              | 54                | 17.71          |
| High Channel (2462 MHz)   |                   |            |                     |               |                |                               |                                    |                   |                |
| 2324.41                   | 28.51             | PK         | 291                 | 1.6           | H              | 31.64                         | 60.15                              | 74                | 13.85          |
| 2324.41                   | 14.57             | Ave.       | 291                 | 1.6           | H              | 31.64                         | 46.21                              | 54                | 7.79           |
| 2483.54                   | 31.99             | PK         | 257                 | 1.5           | H              | 32.13                         | 64.12                              | 74                | 9.88           |
| 2483.54                   | 15.09             | Ave.       | 257                 | 1.5           | H              | 32.13                         | 47.22                              | 54                | 6.78           |
| 4924.00                   | 43.61             | PK         | 187                 | 1.9           | H              | 6.76                          | 50.37                              | 74                | 23.63          |
| 4924.00                   | 29.49             | Ave.       | 187                 | 1.9           | H              | 6.76                          | 36.25                              | 54                | 17.75          |

**802.11n-HT40 Mode:**

| Frequency<br>(MHz)        | Receiver          |            | Turntable<br>Degree | Rx Antenna    |                | Corrected<br>Factor<br>(dB/m) | Corrected<br>Amplitude<br>(dBμV/m) | Limit<br>(dBμV/m) | Margin<br>(dB) |
|---------------------------|-------------------|------------|---------------------|---------------|----------------|-------------------------------|------------------------------------|-------------------|----------------|
|                           | Reading<br>(dBμV) | PK/QP/Ave. |                     | Height<br>(m) | Polar<br>(H/V) |                               |                                    |                   |                |
| Low Channel (2422 MHz)    |                   |            |                     |               |                |                               |                                    |                   |                |
| 2389.13                   | 33.08             | PK         | 322                 | 2.0           | H              | 31.87                         | 64.95                              | 74                | 9.05           |
| 2389.13                   | 18.70             | Ave.       | 322                 | 2.0           | H              | 31.87                         | 50.57                              | 54                | 3.43           |
| 2489.34                   | 27.73             | PK         | 61                  | 1.6           | H              | 32.13                         | 59.86                              | 74                | 14.14          |
| 2489.34                   | 14.81             | Ave.       | 61                  | 1.6           | H              | 32.13                         | 46.94                              | 54                | 7.06           |
| 4844.00                   | 42.92             | PK         | 225                 | 2.1           | H              | 6.28                          | 49.20                              | 74                | 24.80          |
| 4844.00                   | 29.64             | Ave.       | 225                 | 2.1           | H              | 6.28                          | 35.92                              | 54                | 18.08          |
| Middle Channel (2437 MHz) |                   |            |                     |               |                |                               |                                    |                   |                |
| 4874.00                   | 43.08             | PK         | 10                  | 1.1           | H              | 6.76                          | 49.84                              | 74                | 24.16          |
| 4874.00                   | 29.71             | Ave.       | 10                  | 1.1           | H              | 6.76                          | 36.47                              | 54                | 17.53          |
| High Channel (2452 MHz)   |                   |            |                     |               |                |                               |                                    |                   |                |
| 2389.59                   | 27.74             | PK         | 185                 | 1.3           | H              | 31.87                         | 59.61                              | 74                | 14.39          |
| 2389.59                   | 15.15             | Ave.       | 185                 | 1.3           | H              | 31.87                         | 47.02                              | 54                | 6.98           |
| 2487.81                   | 32.15             | PK         | 171                 | 1.8           | H              | 32.13                         | 64.28                              | 74                | 9.72           |
| 2487.81                   | 16.06             | Ave.       | 171                 | 1.8           | H              | 32.13                         | 48.19                              | 54                | 5.81           |
| 4904.00                   | 43.12             | PK         | 72                  | 1.3           | H              | 6.76                          | 49.88                              | 74                | 24.12          |
| 4904.00                   | 29.75             | Ave.       | 72                  | 1.3           | H              | 6.76                          | 36.51                              | 54                | 17.49          |

**1 GHz-25 GHz (BLE\_1M):**

| Frequency<br>(MHz)        | Receiver          |            | Turntable<br>Degree | Rx Antenna    |                | Corrected<br>Factor<br>(dB/m) | Corrected<br>Amplitude<br>(dBμV/m) | Limit<br>(dBμV/m) | Margin<br>(dB) |
|---------------------------|-------------------|------------|---------------------|---------------|----------------|-------------------------------|------------------------------------|-------------------|----------------|
|                           | Reading<br>(dBμV) | PK/QP/Ave. |                     | Height<br>(m) | Polar<br>(H/V) |                               |                                    |                   |                |
| Low Channel (2402 MHz)    |                   |            |                     |               |                |                               |                                    |                   |                |
| 2384.73                   | 28.08             | PK         | 169                 | 1.1           | H              | 31.87                         | 59.95                              | 74                | 14.05          |
| 2384.73                   | 13.91             | Ave.       | 169                 | 1.1           | H              | 31.87                         | 45.78                              | 54                | 8.22           |
| 2498.77                   | 28.62             | PK         | 262                 | 2.0           | H              | 32.13                         | 60.75                              | 74                | 13.25          |
| 2498.77                   | 13.96             | Ave.       | 262                 | 2.0           | H              | 32.13                         | 46.09                              | 54                | 7.91           |
| 4804.00                   | 42.64             | PK         | 149                 | 2.2           | H              | 6.28                          | 48.92                              | 74                | 25.08          |
| 4804.00                   | 28.60             | Ave.       | 149                 | 2.2           | H              | 6.28                          | 34.88                              | 54                | 19.12          |
| Middle Channel (2440 MHz) |                   |            |                     |               |                |                               |                                    |                   |                |
| 4880.00                   | 42.96             | PK         | 253                 | 1.8           | H              | 6.76                          | 49.72                              | 74                | 24.28          |
| 4880.00                   | 28.68             | Ave.       | 253                 | 1.8           | H              | 6.76                          | 35.44                              | 54                | 18.56          |
| High Channel (2480 MHz)   |                   |            |                     |               |                |                               |                                    |                   |                |
| 2373.15                   | 27.85             | PK         | 204                 | 1.2           | H              | 31.87                         | 59.72                              | 74                | 14.28          |
| 2373.15                   | 13.88             | Ave.       | 204                 | 1.2           | H              | 31.87                         | 45.75                              | 54                | 8.25           |
| 2485.06                   | 28.60             | PK         | 229                 | 1.6           | H              | 32.13                         | 60.73                              | 74                | 13.27          |
| 2485.06                   | 14.05             | Ave.       | 229                 | 1.6           | H              | 32.13                         | 46.18                              | 54                | 7.82           |
| 4960.00                   | 42.77             | PK         | 220                 | 1.5           | H              | 6.80                          | 49.57                              | 74                | 24.43          |
| 4960.00                   | 28.48             | Ave.       | 220                 | 1.5           | H              | 6.80                          | 35.28                              | 54                | 18.72          |



**1 GHz-25 GHz (BLE\_2M):**

| Frequency<br>(MHz)        | Receiver          |            | Turntable<br>Degree | Rx Antenna    |                | Corrected<br>Factor<br>(dB/m) | Corrected<br>Amplitude<br>(dBμV/m) | Limit<br>(dBμV/m) | Margin<br>(dB) |
|---------------------------|-------------------|------------|---------------------|---------------|----------------|-------------------------------|------------------------------------|-------------------|----------------|
|                           | Reading<br>(dBμV) | PK/QP/Ave. |                     | Height<br>(m) | Polar<br>(H/V) |                               |                                    |                   |                |
| Low Channel (2402 MHz)    |                   |            |                     |               |                |                               |                                    |                   |                |
| 2381.06                   | 28.19             | PK         | 82                  | 2.2           | H              | 31.87                         | 60.06                              | 74                | 13.94          |
| 2381.06                   | 14.32             | Ave.       | 82                  | 2.2           | H              | 31.87                         | 46.19                              | 54                | 7.81           |
| 2486.34                   | 27.88             | PK         | 138                 | 1.6           | H              | 32.13                         | 60.01                              | 74                | 13.99          |
| 2486.34                   | 14.26             | Ave.       | 138                 | 1.6           | H              | 32.13                         | 46.39                              | 54                | 7.61           |
| 4804.00                   | 42.78             | PK         | 128                 | 1.5           | H              | 6.28                          | 49.06                              | 74                | 24.94          |
| 4804.00                   | 28.64             | Ave.       | 128                 | 1.5           | H              | 6.28                          | 34.92                              | 54                | 19.08          |
| Middle Channel (2440 MHz) |                   |            |                     |               |                |                               |                                    |                   |                |
| 4880.00                   | 42.69             | PK         | 52                  | 2.4           | H              | 6.76                          | 49.45                              | 74                | 24.55          |
| 4880.00                   | 28.78             | Ave.       | 52                  | 2.4           | H              | 6.76                          | 35.54                              | 54                | 18.46          |
| High Channel (2480 MHz)   |                   |            |                     |               |                |                               |                                    |                   |                |
| 2313.70                   | 27.61             | PK         | 287                 | 1.9           | H              | 31.64                         | 59.25                              | 74                | 14.75          |
| 2313.70                   | 14.26             | Ave.       | 287                 | 1.9           | H              | 31.64                         | 45.90                              | 54                | 8.10           |
| 2492.87                   | 27.90             | PK         | 58                  | 1.5           | H              | 32.13                         | 60.03                              | 74                | 13.97          |
| 2492.87                   | 14.28             | Ave.       | 58                  | 1.5           | H              | 32.13                         | 46.41                              | 54                | 7.59           |
| 4960.00                   | 42.84             | PK         | 35                  | 2.1           | H              | 6.80                          | 49.64                              | 74                | 24.36          |
| 4960.00                   | 28.84             | Ave.       | 35                  | 2.1           | H              | 6.80                          | 35.64                              | 54                | 18.36          |



**Note:**

Corrected Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor


Corrected Amplitude = Corrected Factor + Reading

Margin = Limit - Corrected. Amplitude


The other spurious emission which is 20dB to the limit was not recorded.

**Pre-scan with 802.11b Mode, High channel  
Horizontal**

## Vertical





Date: 20.MAR.2021 07:53:49




Date: 20.MAR.2021 08:38:48


### Average Horizontal



## Vertical



Date: 20.MAR.2021 07:58:08




Date: 20.MAR.2021 08:43:10

**FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH****Applicable Standard**

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

**Test Procedure**

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 6 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.

**Test Data****Environmental Conditions**

|                    |           |
|--------------------|-----------|
| Temperature:       | 27 °C     |
| Relative Humidity: | 57 %      |
| ATM Pressure:      | 101.0 kPa |

*The testing was performed by Coco Liu from 2021-03-04 to 2021-03-19.*

*EUT operation mode: Transmitting*

Test Result Compliant. Please refer to the Appendix BLE & Appendix Wi-Fi.


## FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER

### Applicable Standard

According to FCC §15.247(b) (3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

### Test Procedure

1. Place the EUT on a bench and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to one test equipment.
3. Add a correction factor to the display.



### Test Data

#### Environmental Conditions

|                    |           |
|--------------------|-----------|
| Temperature:       | 27 °C     |
| Relative Humidity: | 57 %      |
| ATM Pressure:      | 101.0 kPa |

*The testing was performed by Coco Liu from 2021-03-04 to 2021-03-19.*

*EUT operation mode: Transmitting*


Test Result Compliant. Please refer to the Appendix BLE & Appendix Wi-Fi.

**FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE****Applicable Standard**

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

**Test Procedure**

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

**Test Data****Environmental Conditions**

|                    |           |
|--------------------|-----------|
| Temperature:       | 27 °C     |
| Relative Humidity: | 57 %      |
| ATM Pressure:      | 101.0 kPa |

*The testing was performed by Coco Liu from 2021-03-04 to 2021-03-19.*

*EUT operation mode: Transmitting*

Test Result Compliant. Please refer to the Appendix BLE & Appendix Wi-Fi.




## FCC §15.247(e) - POWER SPECTRAL DENSITY

### Applicable Standard

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

### Test Procedure

1. Use this procedure when the maximum peak conducted output power in the fundamental emission is used to demonstrate compliance.
2. Set the RBW to:  $3\text{kHz} \leq \text{RBW} \leq 100\text{ kHz}$ .
3. Set the VBW  $\geq 3 \times \text{RBW}$ .
4. Set the span to 1.5 times the DTS bandwidth.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level within the RBW.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.



### Test Data

#### Environmental Conditions

|                    |           |
|--------------------|-----------|
| Temperature:       | 27 °C     |
| Relative Humidity: | 57 %      |
| ATM Pressure:      | 101.0 kPa |

*The testing was performed by Coco Liu from 2021-03-04 to 2021-03-19.*


*EUT operation mode: Transmitting*


Test Result Compliant. Please refer to the Appendix BLE & Appendix Wi-Fi.

**APPENDIX Wi-Fi****Appendix A: DTS Bandwidth  
Test Result**


| Test Mode | Antenna | Channel | DTS BW [MHz] | Limit[MHz] | Verdict |
|-----------|---------|---------|--------------|------------|---------|
| 11B       | Ant1    | 2412    | 8.120        | 0.5        | PASS    |
|           |         | 2437    | 8.120        | 0.5        | PASS    |
|           |         | 2462    | 8.160        | 0.5        | PASS    |
| 11G       | Ant1    | 2412    | 14.520       | 0.5        | PASS    |
|           |         | 2437    | 15.800       | 0.5        | PASS    |
|           |         | 2462    | 15.760       | 0.5        | PASS    |
| 11N20SISO | Ant1    | 2412    | 13.920       | 0.5        | PASS    |
|           |         | 2437    | 16.440       | 0.5        | PASS    |
|           |         | 2462    | 16.360       | 0.5        | PASS    |
| 11N40SISO | Ant1    | 2422    | 17.760       | 0.5        | PASS    |
|           |         | 2437    | 27.120       | 0.5        | PASS    |
|           |         | 2452    | 35.840       | 0.5        | PASS    |

# Test Graphs






## 11G\_Ant1\_2412




Date: 19.MAR.2021 20:48:01

## 11G\_Ant1\_2437




Date: 19.MAR.2021 20:50:03

## 11G\_Ant1\_2462




Date: 19.MAR.2021 20:52:21


## 11N20SISO\_Ant1\_2412



Date: 19.MAR.2021 20:53:58




## 11N40SISO\_Ant1\_2422




Date: 4.APR.2021 21:16:00

## 11N40SISO\_Ant1\_2437



Date: 4.APR.2021 21:10:25







**Appendix B: Occupied Channel Bandwidth  
Test Result**

| Test Mode | Antenna | Channel | OCB [MHz] | Limit[MHz] | Verdict |
|-----------|---------|---------|-----------|------------|---------|
| 11B       | Ant1    | 2412    | 13.387    | ---        | PASS    |
|           |         | 2437    | 13.666    | ---        | PASS    |
|           |         | 2462    | 13.506    | ---        | PASS    |
| 11G       | Ant1    | 2412    | 17.463    | ---        | PASS    |
|           |         | 2437    | 17.622    | ---        | PASS    |
|           |         | 2462    | 17.223    | ---        | PASS    |
| 11N20     | Ant1    | 2412    | 18.222    | ---        | PASS    |
|           |         | 2437    | 18.462    | ---        | PASS    |
|           |         | 2462    | 18.102    | ---        | PASS    |
| 11N40     | Ant1    | 2422    | 35.405    | ---        | PASS    |
|           |         | 2437    | 37.003    | ---        | PASS    |
|           |         | 2452    | 37.403    | ---        | PASS    |

## Test Graphs




## 11B\_Ant1\_2462




Date: 19.MAR.2021 20:46:58

## 11G\_Ant1\_2412




Date: 19.MAR.2021 20:48:53

## 11G\_Ant1\_2437




Date: 19.MAR.2021 20:50:12

## 11G\_Ant1\_2462




Date: 19.MAR.2021 20:52:30


## 11N20\_Ant1\_2412




## 11N20\_Ant1\_2437




## 11N20\_Ant1\_2462



## 11N40\_Ant1\_2422




## 11N40\_Ant1\_2437



Date: 19.MAR.2021 20:40:49

## 11N40\_Ant1\_2452



Date: 19.MAR.2021 20:39:09



### Appendix C: Maximum conducted output power Test Result

#### Peak power:

| Test Mode | Antenna | Channel | Result[dBm] | Limit[dBm] | Verdict |
|-----------|---------|---------|-------------|------------|---------|
| 11B       | Ant1    | 2412    | 14.36       | <=30       | PASS    |
|           |         | 2437    | 15.65       | <=30       | PASS    |
|           |         | 2462    | 15.02       | <=30       | PASS    |
| 11G       | Ant1    | 2412    | 17.43       | <=30       | PASS    |
|           |         | 2437    | 19.93       | <=30       | PASS    |
|           |         | 2462    | 18.05       | <=30       | PASS    |
| 11N20     | Ant1    | 2412    | 17.89       | <=30       | PASS    |
|           |         | 2437    | 19.20       | <=30       | PASS    |
|           |         | 2462    | 17.16       | <=30       | PASS    |
| 11N40     | Ant1    | 2422    | 17.17       | <=30       | PASS    |
|           |         | 2437    | 16.54       | <=30       | PASS    |
|           |         | 2452    | 16.73       | <=30       | PASS    |


#### Average Power:

| Test Mode | Antenna | Channel | Result[dBm] | Limit[dBm] | Verdict |
|-----------|---------|---------|-------------|------------|---------|
| 11B       | Ant1    | 2412    | 12.84       | <=30       | PASS    |
|           |         | 2437    | 13.83       | <=30       | PASS    |
|           |         | 2462    | 13.27       | <=30       | PASS    |
| 11G       | Ant1    | 2412    | 12.54       | <=30       | PASS    |
|           |         | 2437    | 13.60       | <=30       | PASS    |
|           |         | 2462    | 13.00       | <=30       | PASS    |
| 11N20     | Ant1    | 2412    | 12.52       | <=30       | PASS    |
|           |         | 2437    | 13.65       | <=30       | PASS    |
|           |         | 2462    | 12.93       | <=30       | PASS    |
| 11N40     | Ant1    | 2422    | 13.68       | <=30       | PASS    |
|           |         | 2437    | 13.49       | <=30       | PASS    |
|           |         | 2452    | 13.44       | <=30       | PASS    |


**AppendixD: Maximum power spectral density  
Test Result**

| TestMode | Antenna | Channel | Result[dBm/3kHz] | Limit[dBm/3kHz] | Verdict |
|----------|---------|---------|------------------|-----------------|---------|
| 11B      | Ant1    | 2412    | -8.73            | <=8             | PASS    |
|          |         | 2437    | -7.91            | <=8             | PASS    |
|          |         | 2462    | -8.90            | <=8             | PASS    |
| 11G      | Ant1    | 2412    | -9.83            | <=8             | PASS    |
|          |         | 2437    | -10.64           | <=8             | PASS    |
|          |         | 2462    | -11.57           | <=8             | PASS    |
| 11N20    | Ant1    | 2412    | -9.08            | <=8             | PASS    |
|          |         | 2437    | -10.77           | <=8             | PASS    |
|          |         | 2462    | -12.22           | <=8             | PASS    |
| 11N40    | Ant1    | 2422    | -9.85            | <=8             | PASS    |
|          |         | 2437    | -9.61            | <=8             | PASS    |
|          |         | 2452    | -10.14           | <=8             | PASS    |


## Test Graphs




## 11B\_Ant1\_2462



## 11G\_Ant1\_2412




## 11G\_Ant1\_2437




Date: 19.MAR.2021 20:50:31

## 11G\_Ant1\_2462




Date: 19.MAR.2021 20:52:49


11N20\_Ant1\_2412




11N20\_Ant1\_2437




## 11N20\_Ant1\_2462




## 11N40\_Ant1\_2422




11N40\_Ant1\_2437




11N40\_Ant1\_2452






**Appendix E: Band edge measurements****Test Graphs**

## 11G\_Ant1\_Low\_2412




Date: 19.MAR.2021 20:49:19

## 11G\_Ant1\_High\_2462



Date: 19.MAR.2021 20:52:57

11N20\_Ant1\_Low\_2412




Date: 19.MAR.2021 20:54:34

11N20\_Ant1\_High\_2462




Date: 19.MAR.2021 20:59:15




**Appendix G: Duty Cycle  
Test Result**

| Test Mode | Antenna | Channel | Transmission<br>Duration<br>[ms] | Transmission<br>Period<br>[ms] | Duty Cycle<br>[%] |
|-----------|---------|---------|----------------------------------|--------------------------------|-------------------|
| 11B       | Ant1    | 2437    | 8.34                             | 8.42                           | 99.05             |
| 11G       | Ant1    | 2437    | 1.37                             | 1.44                           | 95.14             |
| 11N20     | Ant1    | 2437    | 1.29                             | 1.35                           | 95.56             |
| 11N40     | Ant1    | 2437    | 0.63                             | 0.69                           | 91.30             |

## Test Graphs




## 11N20\_Ant1\_2437



Date: 19.MAR.2021 20:58:04

## 11N40\_Ant1\_2437



Date: 19.MAR.2021 20:40:31


## APPENDIX BLE

### Appendix A: DTS Bandwidth Test Result


| Test Mode | Antenna | Channel | DTS BW [MHz] | Limit[MHz] | Verdict |
|-----------|---------|---------|--------------|------------|---------|
| BLE_1M    | Ant1    | 2402    | 0.672        | 0.5        | PASS    |
|           |         | 2440    | 0.672        | 0.5        | PASS    |
|           |         | 2480    | 0.672        | 0.5        | PASS    |
| BLE_2M    | Ant1    | 2402    | 1.164        | 0.5        | PASS    |
|           |         | 2440    | 1.168        | 0.5        | PASS    |
|           |         | 2480    | 1.168        | 0.5        | PASS    |



# Test Graphs




BLE 1M Ant1 2480




Date: 4.MAR.2021 09:35:12

BLE 2M Ant1 2402




Date: 4.MAR.2021 09:37:02

BLE 2M Ant1 2440



Date: 4.MAR.2021 09:38:17

BLE 2M Ant1 2480




Date: 4.MAR.2021 09:39:07

**Appendix B: Occupied Channel Bandwidth  
Test Result**

| Test Mode | Antenna | Channel | OCB [MHz] | Limit[MHz] | Verdict |
|-----------|---------|---------|-----------|------------|---------|
| BLE_1M    | Ant1    | 2402    | 1.031     | ---        | PASS    |
|           |         | 2440    | 1.031     | ---        | PASS    |
|           |         | 2480    | 1.035     | ---        | PASS    |
| BLE_2M    | Ant1    | 2402    | 2.062     | ---        | PASS    |
|           |         | 2440    | 2.066     | ---        | PASS    |
|           |         | 2480    | 2.062     | ---        | PASS    |

## Test Graphs



BLE 1M Ant1 2480



BLE 2M Ant1 2402



BLE 2M Ant1 2440



Date: 4.MAR.2021 09:38:27

BLE 2M Ant1 2480



Date: 4.MAR.2021 09:39:16

**Appendix C: Maximum conducted Peak output power****Test Result**


| Test Mode | Antenna | Channel | Result[dBm] | Limit[dBm] | Verdict |
|-----------|---------|---------|-------------|------------|---------|
| BLE_1M    | Ant1    | 2402    | -5.11       | <=30       | PASS    |
|           |         | 2440    | -4.25       | <=30       | PASS    |
|           |         | 2480    | -4.05       | <=30       | PASS    |
| BLE_2M    | Ant1    | 2402    | -5.11       | <=30       | PASS    |
|           |         | 2440    | -4.25       | <=30       | PASS    |
|           |         | 2480    | -4.05       | <=30       | PASS    |




**Appendix D: Maximum power spectral density  
Test Result**

| Test Mode | Antenna | Channel | Result[dBm/3kHz] | Limit[dBm/3kHz] | Verdict |
|-----------|---------|---------|------------------|-----------------|---------|
| BLE_1M    | Ant1    | 2402    | -21.99           | <=8             | PASS    |
|           |         | 2440    | -20.96           | <=8             | PASS    |
|           |         | 2480    | -21.26           | <=8             | PASS    |
| BLE_2M    | Ant1    | 2402    | -24.14           | <=8             | PASS    |
|           |         | 2440    | -23.12           | <=8             | PASS    |
|           |         | 2480    | -23.41           | <=8             | PASS    |


## Test Graphs




BLE 1M Ant1 2480




BLE 2M Ant1 2402



BLE 2M Ant1 2440




BLE 2M Ant1 2480



## Appendix E: Band edge measurements Test Graphs




BLE 2M Ant1 Low 2402



Date: 4.MAR.2021 09:37:38

BLE 2M Ant1 High 2480




Date: 4.MAR.2021 09:39:43

**Appendix G: Duty Cycle  
Test Result**

| Test Mode | Antenna | Channel | Transmission<br>Duration<br>[ms] | Transmission<br>Period<br>[ms] | Duty Cycle<br>[%] |
|-----------|---------|---------|----------------------------------|--------------------------------|-------------------|
| BLE_1M    | Ant1    | 2440    | 2.11                             | 2.50                           | 84.40             |
| BLE_2M    | Ant1    | 2440    | 1.07                             | 1.88                           | 56.91             |

# Test Graphs



\*\*\*\*\* END OF REPORT \*\*\*\*\*