GSM Test Report

Application Purpose: Original grant

Applicant Name: : TECNO MOBILE LIMITED

FCC ID : 2ADYY-T420

Equipment Type : Mobile Phone

Model Name : T420

Report Number: FCC15050004-3

Standard(S) : FCC Part 22H & 24E Rules

Date Of Receipt : May 17, 2015

Date Of Issue : May 28, 2015

Test By :

New Wong
(Neil Wong)

Reviewed By :

(Robie Chen)

Authorized by :

(Michal Ling)

Prepared by :

Shenzhen WST Testing Technology Co., Ltd.

1F,No.9 Building,TGK Science & Technology Park Yangtian

Rd., NO.72 Bao'an Dist., GuangDong, China

(Registration Number: 939433)

Report Revise Record					
Report Version	Revise Time	Issued Date	Valid Version	Notes	
V1.0	/	May 28, 2015	Valid	Original Report	

TABLE OF CONTENTS

1. Certification5
2. GENERAL INFORMATION6
2.1 EUT DESCRIPTION6
3. TEST DESCRIPTION8
3.1 TEST FACILITY8
3.3 DESCRIPTION OF TEST CHANNELS AND TEST MODES9
3.4 EQUIPMENT MODIFICATIONS9
4. SUMMARY OF TEST REQUIREMENTS AND RESULTS 10
For GSM850/GPRS850:
For PCS1900/GPRS1900:
5. MEASUREMENT INSTRUMENTS11
6. OUTPUT POWER
6.1 Conducted Output Power
6.3. Peak-to-Average Ratio 18
7. SPURIOUS EMISSION
7.1 CONDUCTED SPURIOUS EMISSION
7.2 Radiated Spurious Emission
8. FREQUENCY STABILITY
8.1 MEASUREMENT METHOD26
8.2 PROVISIONS APPLICABLE
8.3 MEASUREMENT RESULT (WORST)27
9. OCCUPIED BANDWIDTH
9.1 MEASUREMENT METHOD29
9.2 PROVISIONS APPLICABLE
9.3 MEASUREMENT RESULT
10. EMISSION BANDWIDTH
10.1 MEASUREMENT METHOD
10.2 PROVISIONS APPLICABLE

10.3 MEASUREMENT RESULT	30
11. BAND EDGE	31
11.1 MEASUREMENT METHOD	31
11.2 PROVISIONS APPLICABLE	31
11.3 MEASUREMENT RESULT	31
12. EUT TEST PHOTO	32
13. EUT PHOTO	34
APPENDIX A: TEST PLOTS FOR CONDUCTED SPURIOUS EMISSIO	44
APPENDIX B: TEST PLOTS FOR OCCUPIED BANDWIDTH (99% and -26dBc)	51
APPENDIX C: TEST PLOTS FOR BAND EDGES	55

1. Certification

Applicant	TECNO MOBILE LIMITED
Address	RMS 05-15, 13A/F., SOUTH TOWER, WORLD FINANCE CTR, HARBOUR CITY, KLN, HK.
Manufacturer	SHENZHEN SMARTTEL CO., LTD.
Address	6th Floor, Block 15, shatoujiao Free TRADE Zone,Shenyan Road, Yantian District, Shenzhen, Guangdong, P.R. China
Equipment Type	Mobile Phone
Brand Name	TECNO
Test Model	T420
Series Model	N/A
Difference description	N/A
Data of receipt	May 17, 2015
Date of test	May 17, 2015 to May 27, 2015
Deviation	None
Condition of Test Sample	Normal

We hereby certify that:

All measurement facilities used to collect the measurement data are located at

1F,No.9 Building,TGK Science & Technology Park Yangtian Rd., NO.72 Bao'an Dist., GuangDong, China The data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C 63.4:2009 and TIA/EIA 603. The sample tested as described in this report is in compliance with the FCC Rules Part2, 22H and 24E.

The test results of this report relate only to the tested sample identified in this report.

2. GENERAL INFORMATION

2.1 EUT DESCRIPTION

Equ	ipment Type:	Mobile Phone			
Hard	dware	A710_MAIN_PCB_V1.2			
Software		N/A			
Fred	quency Bands:	☐ GSM 850 ☐ PCS 1900 (U.S. Bands) ☐ GSM 900 ☐ DCS 1800 (Non-U.S. Bands) U.S. Bands: ☐ UMTS FDD Band II ☐ UMTS FDD Band V Non-U.S. Bands: ☐ UMTS FDD Band I ☐ UMTS FDD Band VIII			
Ante	enna Type:	Internal Antenna			
Ante	enna gain:	1.0dBi(GSM)			
Pow	er Supply:	DC3.7V by Battery			
Batt	ery information:	Li-ion Battery: BL-5CAT Batterie: 4.255Wh Voltage: 3.7V Capacity: 1150mAh Limited Charge Voltage: 4.2V			
Ada	pter Information:	Adapter : M45 Input: AC 100-240V 50/60Hz 150mA Output: DC 5V 500mA			
Dua	l Card:	Card 1: GSM Card Slot, Card 2: GSM Card Slot			
Max	power:	See note 3			
	Operating Frequency	2402-2480MHz			
	Channels	79			
	Channel Spacing	1MHz			
вт	Modulation Type	GFSK, π/4-DQPSK, 8-DPSK			
	Version	3.0			
	Antenna gain:	1.55dBi			
Antenna Type: Integral Antenna		Integral Antenna			
GPF	RS Class	12			
Extr	eme Temp. Tolerance	-10℃ to +50℃			

Note 1: The High Voltage DC4.2V and Low Voltage DC3.5V were declared by manufacturer, The EUT couldn't be operating normally with higher or lower voltage.

Note 2: Card 1 can't transmit with Card 2 simultaneously.

Note 3:

Card 1:

	Maximum ERP/EIRP	Max. Conducted Power	Max. Average
	(dBm)	(dBm)	Burst Power (dBm)
GSM 850	32.41	32.73	32.39
PCS 1900	29.28	29.84	29.30

Card 2:

	Maximum ERP/EIRP	Max. Conducted Power	Max. Average
	(dBm)	(dBm)	Burst Power (dBm)
GSM 850	32.45	32.88	32.41
PCS 1900	29.49	29.99	29.39

3. TEST DESCRIPTION

3.1 TEST FACILITY

All measurement facilities used to collect the measurement data are located at 1F,No.9 Building,TGK Science & Technology Park Yangtian Rd., NO.72 Bao'an Dist., GuangDong, China

3.2 EUT SYSTEM CONFIGURATION

The EUT configuration for testing is installed on RF field strength measurement to meet the Commission's requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

Fig. 2-1 Configuration of EUT System




Table 2-1 Equipment Used in EUT System

Item	Equipment	Model No.	ID or Specification	Note
1	Mobile Phone	T420	FCC ID: 2ADYY-T420	EUT
2	Adapter	M45	DC5V 150mA	Accessory
3	Battery	BL-5CAT	DC3.7V 1150mAh	Accessory

^{***}Note: All the accessories have been used during the test. The following "EUT" in setup diagram means EUT system.

3.3 DESCRIPTION OF TEST CHANNELS AND TEST MODES

During the testing, the EUT was controlled via Rhode & Schwarz Digital Radio Communication Tester (CMU 200) to ensure max power transmission and proper modulation. Three channels (The top channel, the middle channel and the bottom channel) were chosen for testing on both GSM and PCS frequency band.

Test channels:

Band	Channel		Frequency (MHz)
	Low	128	824.2
GSM850	Middle	190	836.6
	High	251	848.8

Band	Channel		Frequency (MHz)
PCS1900	Low	512	1850.2
	Middle	661	1880
	High	810	1909.8

The worst condition was recorded in the test report if no other modes test data.

3.4 EQUIPMENT MODIFICATIONS

Not available for this EUT intended for grant.

4. SUMMARY OF TEST REQUIREMENTS AND RESULTS

For GSM850/GPRS850:

Item Number	Item D	escription	Test Channel	FCC Rules	Result
	0 4 4 5	Conducted Output Power	128/190/251	0.40.40/00.040() (0)	J
1	Output Power	Radiated Output Power	128/190/251	2.1046/22.913(a) (2)	Pass
2	Spurious	Conducted Spurious Emission	128/190/251	- 2.1051 / 22.917	Pass
2	Emission	Radiated Spurious Emission	128/190/251		
3	Mains Conducted	Emission		15.207	Pass
4	Frequency Stability		190	2.1055/22.355	Pass
5	Occupied Bandwidth		128/190/251	2.1049	Pass
6	Emission Bandwidth		128/190/251	22.917(a)(b)	Pass
7	Band Edge	Band Edge		22.917(a)	Pass

For PCS1900/GPRS1900:

Item Number	Item Description		Test Channel	FCC Rules	Result
1	Outrot Davis	Conducted Output Power	512/661/810	2.1046/24.232(c)	Pass
ľ	Output Power	Radiated Output Power	512/661/810		
2	Peak-to-Average Ratio	Peak-to-Average Ratio	512/661/810	24.232(d)	Pass
3	Spurious	Conducted Spurious Emission	512/661/810	0.4054 (0.4.000()	Pass
3	Emission	Radiated Spurious Emission	512/661/810	2.1051 / 24.238(a)	
4	Mains Conducted	Emission		15.207	Pass
5	Frequency Stability		661	2.1055/24.235	Pass
6	Occupied Bandwidth		512/661/810	2.1049	Pass
7	Emission Bandwidth		512/661/810	24.238(a)(b)	Pass
8	Band Edge		512/661/810	24.238(a)(b)	Pass

5. MEASUREMENT INSTRUMENTS

NAME OF EQUIPMENT	MANUFACTURER	MODEL	SERIAL NUMBER	Calibration Date	Calibration Due.
EMI Test Receiver	R&S	ESCI	100005	08/19/2014	08/18/2015
ESPI Test Receiver	ROHDE&SCHWARZ	ESPI	101139	08/19/2014	08/18/2015
Signal Generator	ROHDE&SCHWARZ	SMT03	100029	08/19/2014	08/18/2015
Signal Generator	ROHDE&SCHWARZ	SMU200A	1141	08/19/2014	08/18/2015
LISN	AFJ	LS16	16010222119	08/19/2014	08/18/2015
LISN(EUT)	Mestec	AN3016	04/10040	08/19/2014	08/18/2015
Universal Radio Communication Tester	R&S	CMU 200	1100.0008.02	08/19/2014	08/18/2015
Coaxial cable	Megalon	LMR400	N/A	08/12/2014	08/11/2015
GPIB cable	Megalon	GPIB	N/A	08/12/2014	08/11/2015
Spectrum Analyzer	Aglient	E4440A	MY42510159	12/02/2014	12/01/2015-
Pre Amplifier	H.P.	HP8447E	2945A02715	10/13/2014	10/12/2015
Pre-Amplifier	CDSI	PAP-1G18-38		10/13/2014	10/12/2015
Bi-log Antenna	SUNOL Sciences	JB3	A021907	09/13/2014	09/12/2015
Bi-log Antenna	Schwarebeck	VULB9163	9163/340	2014-08-19	
9*6*6 Anechoic				08/21/2014	08/20/2015
Horn Antenna	COMPLIANCE ENGINEERING	CE18000		09/13/2014	09/12/2015
Horn Antenna	SCHWARZBECK	BBHA9120D	9120D-631	08/23/2014	08/22/2015
Power meter	Anritsu	ML2487A	6K00003613	08/23/2014	08/22/2015
Power meter	Anritsu	MA2491A	32263	08/23/2014	08/22/2015
Cable	TIME MICROWAVE	LMR-400	N-TYPE04	04/25/2014	04/24/2015
System-Controller	CCS	N/A	N/A	N.C.R	N.C.R
Turn Table	ccs	N/A	N/A	N.C.R	N.C.R
Antenna Tower	CCS	N/A	N/A	N.C.R	N.C.R
RF cable	Murata	MXHQ87WA3000	-	08/21/2014	08/20/2015
Loop Antenna	EMCO	6502	00042960	08/22/2014	08/21/2015
Power sensor	Anritsu	MX248XD		08/19/2014	08/18/2015
Horn Antenna	SCHWARZBECK	BBHA 9170	1123	08/19/2014	08/18/2015

Throc way	Ob a servici Time I				
Three-way connector	Shaanxi Tianzhu Business Co., Ltd.	1506A	A1213	08/19/2014	08/18/2015
Attenuator	MCL	BW-N20W5+	1306	08/19/2014	08/18/2015

6. OUTPUT POWER

6.1 Conducted Output Power

6.1.1 MEASUREMENT METHOD

The EUT was setup for the max output power with pseudo random data modulation. Power was measured with Spectrum Analyzer. The measurements were performed on all modes (GSM/GPRS 850, GSM/GPRS1900) at 3 typical channels described in section 3.3 of this report for each band.

6.1.2 MEASUREMENT RESULT

	Conducted Output Power Limits for GSM850 band							
Mode	Nominal Peak Power	Tolerance(dB)						
GSM	33 dBm (2W)	+/- 1						
	Conducted Output Power Limits for PCS1900 band							
Mode	Nominal Peak Power	Tolerance(dB)						
GSM	30 dBm (1W)	+/- 1						

GSM 850:

Card 1:

Mode	Frequency (MHz)	Peak Power (dBm)	Avg. Burst Power (dBm)	PAPR (dB)	Duty cycle Factor(dB)	Frame Power(dB m)
	824.2	32.43	32.16	0.27	-9	23.16
GSM850	836.6	Power (dBm) Power (dBm) (dBm) Duty cycle Factor(dB) Power Factor(dB) 32.43 32.16 0.27 -9 22 32.73 32.39 0.34 -9 23 32.64 32.25 0.39 -9 23 32.62 32.21 0.41 -9 23 32.70 32.38 0.32 -9 23 32.95 32.41 0.54 -9 23 31.38 31.02 0.36 -6 23 31.83 31.42 0.41 -6 23 32.03 31.46 0.57 -6 23 30.47 29.87 0.60 -4.26 23 30.58 30.21 0.37 -4.26 23 29.01 28.54 0.47 -3 23 29.09 28.89 0.20 -3 23	23.39			
	848.8	32.64	32.25	0.39	-9	23.25
CDDC050	824.2 32.62 32.21 0.41 -9	-9	23.21			
GPRS850	836.6		23.38			
(1 Slot)	848.8	32.95	32.41	0.54	-9	23.41
CDDC050	824.2	31.38	31.02	0.36	-6	25.02
GPRS850	836.6	31.83	31.42	2.41 0.54 -9 1.02 0.36 -6 1.42 0.41 -6	25.42	
(2 Slot)	848.8	32.03	31.46	0.57	-6	25.46
CDDC050	824.2	29.88	29.52	0.36	-4.26	25.26
GPRS850 (3 Slot)	836.6	30.47	29.87	0.60	-4.26	25.61
(3 3101)	848.8	30.58	30.21	0.37	-4.26	25.95
CDDC0E0	824.2	29.01	28.54	0.47	-3	25.54
GPRS850	836.6	29.09	28.89	0.20	-3	25.89
(4 Slot)	848.8	29.51	29.12	0.39	-3	26.12

Card 2:

Mode	Frequency (MHz)	Peak Power (dBm)	Avg. Burst Power (dBm)	PAPR (dB)	Duty cycle Factor(dB)	Frame Power (dBm)
	824.2	32.41	32.13	0.28	-9	23.13
GSM850	836.6	32.88	32.41	0.47	-9	23.41
	848.8	32.83	32.36	0.47	-9	23.36
GPRS850	824.2	32.44	32.18	0.26	-9	23.18
(1 Slot)	836.6	32.71	32.32	0.39	-9	23.32
(1 3101)	848.8	32.98	32.4	0.58	-9 -9 -6	23.4
GPRS850	824.2	31.62	31.19	0.43	-6	25.19
(2 Slot)	836.6	31.70	31.23	0.47	-6	25.23
(2 3101)	848.8	31.85	31.42	0.43	-6	25.42
GPRS850	824.2	29.79	29.48	0.31	-4.26	25.22
	836.6	30.38	29.81	0.57	-4.26	25.55
(3 Slot)	848.8	30.43	30.14	0.29	-4.26	25.88
CDBS950	824.2	28.87	28.44	0.43	-3	25.44
GPRS850 (4 Slot)	836.6	29.19	28.82	0.37	-3	25.82
(4 3101)	848.8	29.61	29.23	0.38	-3	26.23

PCS 1900:

Card 1:

Mode	Frequency (MHz)	Peak Power (dBm)	Avg. Burst Power (dBm)	PAPR (dB)	Duty cycle Factor(dB)	Frame Power (dBm)
	1850.2	29.84	29.30	0.54	-9	20.30
GSM1900	1880	29.77	29.24	0.53	-9	20.24
	1909.8	29.52	29.07	0.45	-9	20.07
CDBS1000	1850.2	29.54	29.18	0.36 -9	20.18	
GPRS1900	1880	29.82	29.29	0.59	-9	20.29
(1 Slot)	1909.8	29.65	29.18	0.47	-9	20.18
GPRS1900	1850.2	28.57	28.13	0.44	-6	22.13
(2 Slot)	1880	28.50	28.04	0.46	-6	22.04
(2 3101)	1909.8	28.71	28.43	0.28	-6	22.43
GPRS1900	1850.2	27.41	27.01	0.40	-4.26	22.75
	1880	27.13	26.74	0.39	-4.26	22.48
(3 Slot)	1909.8	27.67	27.39	0.28	-4.26	23.13
CDB\$1000	1850.2	26.24	25.86	0.38	-3	22.86
GPRS1900	1880	26.20	25.63	0.57	-3	22.63
(4 Slot)	1909.8	26.83	26.37	0.46	-3	23.37

Card 2:

Mode	Frequency (MHz)	Peak Power (dBm)	Avg. Burst Power (dBm)	PAPR (dB)	Duty cycle Factor(dB)	Frame Power (dBm)
	1850.2	29.99	29.39	0.60	-9	20.39
GSM1900	1880	29.61	29.33	0.28	-9	20.33
	1909.8	29.44	29.19	0.25	-9	20.19
GPRS1900	1850.2	29.63	29.42	0.21	-9	20.42
(1 Slot)	1880	29.55	29.31	0.24	-9	20.31
(1 3101)	1909.8	29.53	29.24	0.29	-9 -9 -6	20.24
GPRS1900	1850.2	28.60	28.23	0.37	-6	22.23
(2 Slot)	1880	28.63	28.11	0.52	-6	22.11
(2 3101)	1909.8	28.46	27.99	0.47	-6	21.99
GPRS1900	1850.2	27.33	27.11	0.22	-4.26	22.85
(3 Slot)	1880	26.57	26.05	0.52	-4.26	21.79
(3 3101)	1909.8	27.26	26.67	0.59	-4.26	22.41
GPRS1900	1850.2	26.55	26.04	0.51	-3	23.04
(4 Slot)	1880	26.18	25.72	0.46	-3	22.72
(4 3101)	1909.8	25.73	25.48	0.25	-3	22.48

6.2 RADIATED OUTPUT POWER

6.2.1 MEASUREMENT METHOD

The measurements procedures specified in TIA-603C-2004 were applied.

- In an anechoic antenna test chamber, a half-wave dipole antenna for the frequency band of interest is placed at the reference centre of the chamber. An RF Signal source for the frequency band of interest is connected to the dipole with a cable that has been constructed to not interfere with the radiation pattern of the antenna. A known (measured) power (Pin) is applied to the input of the dipole, and the power received (Pr) at the chamber's probe antenna is recorded.
- 2 The substitution method is used. Substitution values at each frequency are measured before and saved to the test software. A "reference path loss" is established as ARpl=Pin + 2.15 Pr. The ARpl is the attenuation of "reference path loss", and including the gain of receive antenna, the cable loss and the air loss. The measurement results are obtained as described below: Power=PMea+ARpl
- 3 The EUT is substituted for the dipole at the reference centre of the chamber and a scan is performed to obtain the radiation pattern.
- 4 From the radiation pattern, the co-ordinates where the maximum antenna gain occurs are identified.
- 5 The EUT is then put into continuously transmitting mode at its maximum power level.
- Power mode measurements are performed with the receiving antenna placed at the coordinates determined in Step 3 to determine the output power as defined in Rule 24.232 (b) and (c). The "reference path loss" from Step1 is added to this result.
- 7 This value is EIRP since the measurement is calibrated using a half-wave dipole antenna of known gain (2.15 dBi) and known input power (Pin).
- 8 ERP can be calculated from EIRP by subtracting the gain of the dipole, ERP = EIRP -2.15dBi..

6.2.2 MEASUREMENT RESULT

Radiated Power (ERP) for GSM 850 MHZ								
		Res	sult					
Mode	Frequency	Max. Peak ERP	Polarization	Conclusion				
			Of Max. ERP					
	824.2	32.45	Horizontal	Pass				
GSM850	836.6	32.37	Horizontal	Pass				
	848.8	32.35	Horizontal	Pass				

	Radiated Power (E.I.R.P) for PCS 1900 MHZ								
		Res	ult						
Mode	Frequency	Max. Peak	Polarization	Conclusion					
		E.I.R.P.(dBm)	Of Max. E.I.R.P.						
	1850.2	29.49	Horizontal	Pass					
GSM 1900	1880.0	29.44	Horizontal	Pass					
	1909.8	29.38	Horizontal	Pass					

Note: Above is worst mode data.

6.3. Peak-to-Average Ratio

6.3.1 MEASUREMENT METHOD

The following steps outline the procedure used to measure the Peak-to-Average Ratio from the EUT.

- 1. The EUT was connected to Spectrum Analyzer and Base Station via power divider.
- 2. For GSM operating modes:
- a. Set the RBW = 1MHz, VBW = 1MHz, Peak detector in spectrum analyzer.
- b. Set EUT in maximum power output, and triggered the burst signal.
- c. Measured respectively the Peak level and Mean level, and the deviation was recorded as Peak to Average Ratio.
- 3. For UMTS operating modes:
- a. Set the CCDF (Complementary Cumulative Distribution Function) option in spectrum analyzer.
- b. The highest RF powers were measured and recorded the maximum PAPR level associated with a probability of 0.1 %.

6.3.2 PROVISIONS APPLICABLE

Use one of the procedures presented in 5.1 to measure the total peak power and record as PPk. Use one of the applicable procedures presented 5.2 to measure the total average power and record as PAvg. Both the peak and average power levels must be expressed in the same logarithmic units (e.g., dBm). Determine the PAPR from:

PAPR (dB) =
$$P_{Pk}$$
 (dBm) - P_{Avg} (dBm).

6.3.3 MEASUREMENT RESULT

ACCORDING to KDB 971168 D01 5.7

"If peak power or power density is used to demonstrate compliance, a PAPR measurement is not required."

According to section 6.1.2, the PAPR is the difference value of peak power and average power, and it meets the value of the limit.

7. SPURIOUS EMISSION

7.1 CONDUCTED SPURIOUS EMISSION

7.1.1 MEASUREMENT METHOD

The following steps outline the procedure used to measure the conducted emissions from the EUT.

- 1, Determine frequency range for measurements: From CFR 2.1057 the spectrum should be investigated from the lowest radio frequency generated in the equipment up to at least the 10th harmonic of the carrier frequency. For the equipment of PCS1900 band, this equates to a frequency range of 30 MHz to 19.1 GHz, data taken from 30 MHz to 20 GHz. For GSM850, data taken from 30 MHz to 9 GHz.
- 2, Determine EUT transmit frequencies: the following typical channels were chosen to conducted emissions testing.

7.1.2 PROVISIONS APPLICABLE
On any frequency outside frequency band of the USPCS spectrum, the power of any emission shall be attenuated below the transmitter power (P, in Watts) by at least 43+10Log(P) dB. For all power levels +30
dBm to 0 dBm, this becomes a constant specification limit of -13 dBm.
7.1.3 MEASUREMENT RESULT PLEASE REFER TO: APPENDIX I TEST PLOTS FOR CONDUCTED SPURIOUS EMISSION
Note: 1. Below 30MHZ no Spurious found and The GSM modes is the worst condition.


7.2 Radiated Spurious Emission

7.2.1 MEASUREMENT METHOD


The measurements procedures specified in TIA-603C-2004 were used for testing. The spectrum was scanned from 30 MHz to the 10th harmonic of the highest frequency generated within the equipment. The resolution bandwidth is set 1MHz as outlined in Part 24.238. The measurements were performed on all modes(GPRS850, GPRS1900) at 3 typical channels(the Top Channel, the Middle Channel and the Bottom Channel) for each band.

The procedure of radiated spurious emissions is as follows:

a) Pre-calibration With pre-calibration method, the Radiated Spurious Emissions(RSE) is calculated as, RSE=Rx(dBuV)+CL(dB)+SA(dB)+Gain(dBi)-107(dBuV to dBm) The SA is calibrated using following setup.



b) EUT was placed on a 0.8 meter high non-conductive stand at a 3 meter test distance from the receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the test item for emission measurements. The height of receiving antenna is 0.8m. The test setup refers to figure below. Detected emissions were maximized at each frequency by rotating the test item and adjusting the receiving antenna polarization. The radiated emission measurements of all non-harmonic and harmonics of the transmit frequency through the 10th harmonic were measured with peak detector and 1MHz bandwidth.




Radiated emissions measurements were made only at the upper, middle, and lower carrier frequencies of the PCS 1900 band (1850.2 MHz, 1880 MHz and 1909.8 MHz), GSM850 band (824.2MHz, 836.6MHz, 848.8MHz), . It was decided that measurements at these three carrier frequencies would be sufficient to demonstrate compliance with emissions limits because it was seen that all the significant spurs occur well outside the band and no radiation was seen from a carrier in one block of any band into any of the other blocks.

The substitution method is used. Substitution values at each frequency are measured before and saved to the test software. A "reference path loss" is established and the A_{Rpl} is the attenuation of "reference path loss", and including the gain of receive antenna, the gain of the preamplifier, the cable loss and the air loss. The measurement results are obtained as described below: Power=P_{Mea}+A_{Rpl}


7.2.2 PROVISIONS APPLICABLE

(a) On any frequency outside a licensee's frequency block (e.g. A, D, B, etc.) within the USPCS spectrum, the power of any emission shall be attenuated below the transmitter power (P, in Watts) by at least 43+10Log(P) dB. The specification that emissions shall be attenuated below the transmitter power (P) by at least 43 + 10 log (P) dB, translates in the relevant power range (1 to 0.001 W) to -13 dBm. At 1 W the specified minimum attenuation becomes 43 dB and relative to a 30 dBm (1 W) carrier becomes a limit of -13 dBm. At 0.001 W (0 dBm) the minimum attenuation is 13 dB, which again yields a limit of -13 dBm. In this way a translation of the specification from relative to absolute terms is carried out.

Note: only result the worst condition of each test mode:



Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over	
	MHz	dBu∀	dB	dBuV/m	dBuV/m	dB	Detector
*	36.0007	31.41	-0.27	31.14	40.00	-8.86	peak
	47.4917	29.66	-5.19	24.47	40.00	-15.53	peak
1	19.4360	32.46	-4.15	28.31	40.00	-11.69	peak
1	80.0165	29.58	-8.04	21.54	40.00	-18.46	peak
3	321.0605	26.60	-2.37	24.23	47.00	-22.77	peak
5	20.8881	29.82	1.27	31.09	47.00	-15.91	peak
	* 1 1 3	MHz * 36.0007	Mk. Freq. Level MHz dBuV * 36.0007 31.41 47.4917 29.66 119.4360 32.46 180.0165 29.58 321.0605 26.60	Mk. Freq. Level Factor MHz dBuV dB * 36.0007 31.41 -0.27 47.4917 29.66 -5.19 119.4360 32.46 -4.15 180.0165 29.58 -8.04 321.0605 26.60 -2.37	Mk. Freq. Level Factor ment MHz dBuV dB dBuV/m * 36.0007 31.41 -0.27 31.14 47.4917 29.66 -5.19 24.47 119.4360 32.46 -4.15 28.31 180.0165 29.58 -8.04 21.54 321.0605 26.60 -2.37 24.23	Mk. Freq. Level Factor ment Limit MHz dBuV dB dBuV/m dBuV/m * 36.0007 31.41 -0.27 31.14 40.00 47.4917 29.66 -5.19 24.47 40.00 119.4360 32.46 -4.15 28.31 40.00 180.0165 29.58 -8.04 21.54 40.00 321.0605 26.60 -2.37 24.23 47.00	Mk. Freq. Level Factor ment Limit Over MHz dBuV dB dBuV/m dBuV/m dB * 36.0007 31.41 -0.27 31.14 40.00 -8.86 47.4917 29.66 -5.19 24.47 40.00 -15.53 119.4360 32.46 -4.15 28.31 40.00 -11.69 180.0165 29.58 -8.04 21.54 40.00 -18.46 321.0605 26.60 -2.37 24.23 47.00 -22.77



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over	
		MHz	dBu∨	dB	dBuV/m	dBuV/m	dB	Detector
1	*	36.0007	32.41	-0.27	32.14	40.00	-7.86	peak
2		46.0162	29.31	-4.25	25.06	40.00	-14.94	peak
3		61.3462	31.87	-12.84	19.03	40.00	-20.97	peak
4		119.4360	30.96	-4.15	26.81	40.00	-13.19	peak
5	,	520.8881	30.32	1.27	31.59	47.00	-15.41	peak
6		830.4002	25.35	4.64	29.99	47.00	-17.01	peak

7.2.3 MEASUREMENT RESULT

GSM 850:

The Worst Test Results for Channel 251/848.8 MHz					
Frequency(MHz)	Power(dBm)	ARpl (dBm)	PMea(dBm)	Limit (dBm)	Polarity
1697.6	-38.32	-4.99	-33.33	-13	Horizontal
2546.4	-38.25	-2.45	-35.80	-13	Vertical
3395.2	-41.32	3.61	-44.93	-13	Vertical
4244	-39.61	2.82	-42.43	-13	Horizontal

PCS 1900:

The Worst Test Results for Channel 810/1909.8MHz					
Frequency(MHz)	Power(dBm)	ARpl (dBm)	PMea(dBm)	Limit (dBm)	Polarity
3819.6	-41.25	-3.21	-38.04	-13	Horizontal
5729.4	-35.86	0.34	-36.2	-13	Vertical
7639.2	-40.23	3.95	-44.18	-13	Horizontal
9549	-39.61	-2.26	-37.35	-13	Vertical

8. FREQUENCY STABILITY

8.1 MEASUREMENT METHOD

In order to measure the carrier frequency under the condition of AFC lock, it is necessary to make measurements with the EUT in a "call mode". This is accomplished with the use of R&S CMU200 DIGITAL RADIO COMMUNICATION TESTER.

- 1 , Measure the carrier frequency at room temperature.
- 2 , Subject the EUT to overnight soak at -10° C.
- 3 , With the EUT, powered via nominal voltage, connected to the CMU200 and in a simulated call on channel 661 for PCS 1900 band, channel 190 for GSM 850 band, measure the carrier frequency. These measurements should be made within 2 minutes of Powering up the EUT, to prevent significant self-warming.
- 4 , Repeat the above measurements at 10° C increments from - 10° C to + 50° C. Allow at least 1 1/2 hours at each temperature, unpowered, before making measurements.
- 5 , Re-measure carrier frequency at room temperature with nominal voltage. Vary supply voltage from minimum voltage to maximum voltage, in 0.1Volt increments re-measuring carrier frequency at each voltage. Pause at nominal voltage for 1 1/2 hours unpowered, to allow any self-heating to stabilize, before continuing.
- 6 , Subject the EUT to overnight soak at +50°C.
- 7 , With the EUT, powered via nominal voltage, connected to the CMU200 and in a simulated call on the centre channel, measure the carrier frequency. These measurements should be made within 2 minutes of Powering up the EUT, to prevent significant self-warming.
- 8 , Repeat the above measurements at 10° C increments from +50°C to -10°C. Allow at least 1 1/2 hours at each temperature, unpowered, before making measurements.
- 9 , At all temperature levels hold the temperature to \pm 0.5°C during the measurement procedure.

8.2 PROVISIONS APPLICABLE

8.2.1 For Hand carried battery powered equipment

According to the JTC standard the frequency stability of the carrier shall be accurate to within 0.1 ppm of the received frequency from the base station. This accuracy is sufficient to meet Sec. 24.235, Frequency Stability. The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. As this transceiver is considered "Hand carried, battery powered equipment" Section 2.1055(d)(2) applies. This requires that the lower voltage for frequency stability testing be specified by the manufacturer. This transceiver is specified to operate with an input voltage of between 6.3VDC and 8.5VDC, with a nominal voltage of 7.4VDC. Operation above or below these voltage limits is prohibited by transceiver software in order to prevent improper operation as well as to protect components from overstress. These voltages represent a tolerance of -10 % and +12.5 %. For the purposes of measuring frequency stability these voltage limits are to be used.

8.2.2 For equipment powered by primary supply voltage

According to the JTC standard the frequency stability of the carrier shall be accurate to within 0.1 ppm of the received frequency from the base station. This accuracy is sufficient to meet Sec. 24.235, Frequency Stability. The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. For this EUT section 2.1055(d) (1) applies. This requires varying primary supply voltage from 85 to 115 percent of the nominal value for other than hand carried battery equipment, the normal environment temperature is 20°C.

8.3 MEASUREMENT RESULT (WORST)

Frequency Error Against Voltage for GSM 850 band (Mid channel)

		, ,
Voltage(V)	Frequency error(Hz)	Frequency error (ppm)
3.5	38	0.045
3.7	34	0.040
4.2	35	0.042

Frequency Error Against Temperature for GSM 850 band (Mid channel)

1104011107 =1101		
temperature(°C)	Frequency error(Hz)	Frequency error(ppm)
-10	32	0.038
0	29	0.035
10	37	0.044
20	28	0.033
30	31	0.037
40	36	0.043
50	32	0.038

Note: The EUT doesn't work below -10℃

Frequency Error Agains Voltage For PC1900 band (Mid channel)

Voltage(V)	Frequency error(Hz)	Frequency error(ppm)
3.5	42	0.022
3.7	45	0.024
4.2	47	0.025

Frequency Error Agains Temperature For PC1900 band(Mid channel)

temperature(°C)	Frequency error(Hz)	Frequency error(ppm)
-10	48	0.026
0	42	0.022
10	46	0.024
20	54	0.029
30	43	0.023
40	49	0.026
50	40	0.021

Note: The EUT doesn't work below -10℃

9. OCCUPIED BANDWIDTH

9.1 MEASUREMENT METHOD

The test set up and general procedure is similar to conducted peak output power test. Only different for setting the measurement configuration of the measuring instrument of Spectrum Analyzer.

9.2 PROVISIONS APPLICABLE

The emission bandwidth is defined as two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26dB below the transmitter power.

9.3 MEASUREMENT RESULT

Occupied Bandwidth (99%) for GSM850 band				
Mode	Frequency(MHz)	Occupied Bandwidth (99%)(kHz)		
Low Channel	824.2	243.1240		
Middle Channel	836.6	247.4638		
High Channel	848.8	245.0599		

Occupied Bandwidth (99%) for PCS1900 band				
Mode	Frequency(MHz)	Occupied Bandwidth (99%)(kHz)		
Low Channel	1850.2	241.7933		
Middle Channel	1880.0	242.4676		
High Channel	1909.8	243.8348		

10. EMISSION BANDWIDTH

10.1 MEASUREMENT METHOD

The test set up and general procedure is similar to conducted peak output power test. Only different for setting the measurement configuration of the measuring instrument of Spectrum Analyzer.

10.2 PROVISIONS APPLICABLE

The emission bandwidth is defined as two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26dB below the transmitter power

10.3 MEASUREMENT RESULT

Emission Bandwidth (-26dBc) for GSM850 band				
Mode	Frequency(MHz)	Emission Bandwidth (-26dBc)(kHz)		
Low Channel	824.2	318.421		
Middle Channel	836.6	318.345		
High Channel	848.8	313.268		

Emission Bandwidth (-26dBc) for PCS1900 band				
Mode	Frequency(MHz)	Emission Bandwidth (-26dBc)(kHz)		
Low Channel	1850.2	309.212		
Middle Channel	1880.0	312.737		
High Channel	1909.8	310.514		

11. BAND EDGE
11.1 MEASUREMENT METHOD The test set up and general procedure is similar to conducted peak output power test. Only different for setting the measurement configuration of the measuring instrument of Spectrum Analyzer.
11.2 PROVISIONS APPLICABLE As Specified in FCC rules of 22.917(a) and 24.238(a)
11.3 MEASUREMENT RESULT Please refers to Appendix C for compliance test plots for band edges

12. EUT TEST PHOTO





RADIATED EMISSION TEST





RF TEST




13. EUT PHOTO

















































APPENDIX A: TEST PLOTS FOR CONDUCTED SPURIOUS EMISSIO


CONDUCTED EMISSION IN GSM850 BAND
Conducted Emission Transmitting Mode CH 128 30MHz – 1GHz









Conducted Emission Transmitting Mode CH 190 30MHz - 1GHz









Conducted Emission Transmitting Mode CH 251 30MHz - 1GHz









CONDUCTED EMISSION IN PCS1900 BAND
Conducted Emission Transmitting Mode CH 512 30MHz – 1GHz









Conducted Emission Transmitting Mode CH 661 30MHz - 1GHz









Conducted Emission Transmitting Mode CH 810 30MHz - 1GHz







APPENDIX B: TEST PLOTS FOR OCCUPIED BANDWIDTH (99% and -26dBc)


Occupied Bandwidth (99% and -26dBc) GSM 850 BAND CH 128










Occupied Bandwidth (99% and -26dBc) GSM 850 BAND CH 251











Occupied Bandwidth (99% and -26dBc) PCS 1900 BAND CH 810




APPENDIX C: TEST PLOTS FOR BAND EDGES

Low Band Edge GSM 850 BAND CH 128



High Band Edge GSM 850 BAND CH 251





High Band Edge PCS 1900 BAND CH 810

