

Appendix B

2.4G

Test Laboratory: TOWE Lab

Measurement Report for Device, FRONT, 2.4 GHz Band, Channel 0 (2402.000 MHz)

Device Under Test Properties

Model	Dimensions [mm]
M18T	15.0 x 2.5 x 0.8

Exposure Conditions

Phantom Section, TSL	Position, Test Distance [mm]	Band	Group, UID	Frequency [MHz], Channel Number	TSL Conductivity [S/m]	TSL Permittivity
Flat, Head Simulating Liquid	FRONT, 0.00	ISM 2.4 GHz Band	2.4G, 10670-AAA	2402.000, 0	1.72	38.7

Hardware Setup

Phantom	TSL	Probe, Calibration Date	DAE, Calibration Date
Twin-SAM V8.0 (30deg probe tilt) - 2168	HSL2450	EX3DV4 - SN7812, 2024-06-25	DAE4ip Sn1846, 2024-12-10

Scans Setup

	Area Scan	Zoom Scan
Grid Extents [mm]	70.0 x 70.0	30.0 x 30.0 x 30.0
Grid Steps [mm]	12.0 x 12.0	5.0 x 5.0 x 5.0
Sensor Surface [mm]	3.0	1.4
Graded Grid	N/A	Yes
Grading Ratio	N/A	1.5
MAIA	N/A	N/A
Surface Detection	VMS + 6p	VMS + 6p
Scan Method	Measured	Measured

Measurement Results

	Area Scan	Zoom Scan
Date	2025-03-24, 12:21	2025-03-24, 12:26
psSAR1g [W/Kg]	0.323	0.327
psSAR10g [W/Kg]	0.156	0.161
Power Drift [dB]	-0.14	0.00
Power Scaling	Disabled	Disabled
Scaling Factor [dB]		
TSL Correction	No correction	No correction
M2/M1 [%]		43.8
Dist 3dB Peak [mm]		7.3

