

中国认可
国际互认
检测TESTING
CNAS L6791

TEST REPORT

Applicant: Shenzhen Hollyland Technology Co., Ltd
Address: 8F, Building 5D, Skyworth Innovation Valley,
Tangtou Road. Shiyan Street, Baoan District
Shenzhen, China
Equipment Type: WIRELESS VIDEO TRANSMISSION SYSTEM
Model Name: Pyro 5
Brand Name: HOLLYLAND
FCC ID: 2ADZC-V8830
Test Standard: 47 CFR Part 15 Subpart C
(refer to section 3.1)
Sample Arrival Date: Feb. 28, 2025
Test Date: Mar. 21, 2025 - Apr. 08, 2025
Date of Issue: Apr. 18, 2025

ISSUED BY:

Shenzhen BALUN Technology Co., Ltd.

Tested by: Julie Zhu**Checked by:** Ye Hongji**Approved by:** Sunny Zou
(Technical Director)

Revision History

Version	Issue Date	Revisions
<u>Rev. 01</u>	<u>Apr. 18, 2025</u>	<u>Initial Issue</u>

TABLE OF CONTENTS

1	GENERAL INFORMATION	4
1.1	Test Laboratory	4
1.2	Test Location	4
2	PRODUCT INFORMATION	5
2.1	Applicant Information	5
2.2	Manufacturer Information	5
2.3	General Description for Equipment under Test (EUT)	5
2.4	Technical Information	6
3	SUMMARY OF TEST RESULTS	9
3.1	Test Standards	9
3.2	Test Verdict	9
4	GENERAL TEST CONFIGURATIONS	10
4.1	Test Environments	10
4.2	Test Equipment List	10
4.3	Test Software List	10
4.4	Measurement Uncertainty	11
4.5	Description of Test Setup	11
4.6	Measurement Results Explanation Example	14
5	TEST ITEMS	15
5.1	Antenna Requirements	15
5.2	Output Power	16
5.3	Occupied Bandwidth	18
5.4	Conducted Spurious Emission	19
5.5	Band Edge (Authorized-band band-edge)	21

5.6	Conducted Emission.....	23
5.7	Radiated Spurious Emission.....	24
5.8	Band Edge (Restricted-band band-edge).....	29
5.9	Power Spectral density (PSD)	30
ANNEX A	TEST RESULT	31
A.1	Output Power	31
A.2	Occupied Bandwidth.....	41
A.3	Conducted Spurious Emissions	46
A.4	Band Edge (Authorized-band band-edge).....	55
A.5	Conducted Emissions	59
A.6	Radiated Emission.....	61
A.7	Band Edge (Restricted-band band-edge).....	75
A.8	Power Spectral Density (PSD).....	77
ANNEX B	TEST SETUP PHOTOS	80
ANNEX C	EUT EXTERNAL PHOTOS.....	80
ANNEX D	EUT INTERNAL PHOTOS.....	80

1 GENERAL INFORMATION

1.1 Test Laboratory

Name	Shenzhen BALUN Technology Co., Ltd.
Address	Block B, 1/F, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China
Phone Number	+86 755 6685 0100

1.2 Test Location

Name	Shenzhen BALUN Technology Co., Ltd.
Location	☒ Block B, 1/F, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China
	☐ 1/F, Building B, Ganghongji High-tech Intelligent Industrial Park, No. 1008, Songbai Road, Yangguang Community, Xili Sub-district, Nanshan District, Shenzhen, Guangdong Province, P. R. China
Accreditation Certificate	The laboratory is a testing organization accredited by FCC as a accredited testing laboratory. The designation number is CN1196.

2 PRODUCT INFORMATION

2.1 Applicant Information

Applicant	Shenzhen Hollyland Technology Co., Ltd
Address	8F, Building 5D, Skyworth Innovation Valley, Tangtou Road. Shiyan Street, Baoan District Shenzhen, China

2.2 Manufacturer Information

Manufacturer	Shenzhen Hollyland Technology Co., Ltd
Address	8F, Building 5D, Skyworth Innovation Valley, Tangtou Road. Shiyan Street, Baoan District Shenzhen, China

2.3 General Description for Equipment under Test (EUT)

EUT Name	WIRELESS VIDEO TRANSMISSION SYSTEM
Model Name Under Test	Pyro 5
Series Model Name	N/A
Description of Model name differentiation	N/A
Hardware Version	V8830-MB-V28
Software Version	V1.0.1.3
Dimensions (Approx.)	N/A
Weight (Approx.)	N/A

2.4 Technical Information

Network and Wireless connectivity	WIFI 802.11a, 802.11b, 802.11g, 802.11n(HT20/40) and 802.11ac(VHT20/40)
-----------------------------------	---

The requirement for the following technical information of the EUT was tested in this report:

Frequency Range	802.11b/g/n(20 MHz): 2.412 GHz - 2.462 GHz $f_c = 2412 \text{ MHz} + (N-1)*5 \text{ MHz}$, where - f_c = "Operating Frequency" in MHz, - N = "Channel Number" with the range from 1 to 11. 802.11n(40 MHz): 2.422 GHz - 2.452 GHz $f_c = 2412 \text{ MHz} + (N-1)*5 \text{ MHz}$, where - f_c = "Operating Frequency" in MHz, - N = "Channel Number" with the range from 3 to 9.	
Modulation Type	DSSS, OFDM	
Product Type	☒ Mobile ☐ Portable ☐ Fix Location	
Antenna System (eg., MIMO, Smart Antenna)	Cyclic Delay Diversity (CDD) for 802.11b/g Multi Input Multi Output (MIMO) for 802.11n	
Categorization as Correlated or Completely Uncorrelated	Categorization as Correlated for 802.11b/g Categorization as Uncorrelated for 802.11n	
Antenna Type	SISO-Antenna 0 (Only RX)	PCB Antenna
	SISO-Antenna 1	Dipole Antenna
	SISO-Antenna 2	
Antenna Gain	SISO-Antenna 0 (Only RX)	3.32 dBi
	SISO-Antenna 1	4.74 dBi
	SISO-Antenna 2	
Total directional gain	For power spectral density (PSD) measurements	Correlated: 7.75 dBi Formulas: Directional gain = $G_{ANT} + 10 \log(N_{ANT})$ dBi Uncorrelated: 4.74 dBi Formulas: Directional gain = G_{ANT}
	For power measurements	Correlated: 7.75 dBi

	ts	Formulas: Directional gain = $GANT + 10 \log(NANT)$ dBi Uncorrelated: 4.74 dBi Formulas: Directional gain = $GANT$
	For Conducted Out-of-Band and Spurious Measurements	Correlated: 7.75 dBi Formulas: Directional gain = $GANT + 10 \log(NANT)$ dBi Uncorrelated: 4.74 dBi Formulas: Directional gain = $GANT$
About the Product		Only the WIFI 802.11b, 802.11g and 802.11n (HT20/40) was tested in this report.

Mode	Antenna		
	SISO-Antenna 1	SISO-Antenna 2	MIMO
802.11b	√	√	√
802.11g	√	√	√
802.11n20	√	√	√
802.11n40	√	√	√
Note: All the configurations were tested, but only the worst data was shown in this report.			

Modulation technology	Modulation Type	Transfer Rate (Mbps)(Single RF path)
DSSS (802.11b)	DBPSK	1
	DQPSK	2
	CCK	5.5/11
OFDM (802.11g)	BPSK	6/9
	QPSK	12/18
	16QAM	24/36
	64QAM	48/54
OFDM (802.11n-20 MHz)	BPSK	6.5/7.2
	QPSK	13/19.5/14.4/21.7
	16QAM	26/39/28.9/43.3
	64QAM	52/58.5/65/57.8/65/72.2
OFDM (802.11n-40 MHz)	BPSK	13.5/15
	QPSK	27/40.5/30/45
	16QAM	54/81/60/90
	64QAM	108/121.5/135/120/150

Note: Preliminary tests were performed in different data rate in above table to find the worst radiated emission. The data rate shown in the table below is the worst-case rate with respect to the specific test item. Investigation has been done on all the possible configurations for searching the worst cases. The following table is a list of the test modes shown in this test report.

Test Items	Mode	Data Rate	Channel	
Output Power	11b/11g/11n20/11n40	1/6/6.5/13.5 Mbps	1/6/11	3/6/9
Occupied Bandwidth	11b/11g/11n20/11n40	1/6/6.5/13.5 Mbps	1/6/11	3/6/9
Conducted Spurious Emission	11b/11g/11n20/11n40	1/6/6.5/13.5 Mbps	1/6/11	3/6/9
Conducted Emission	11b/11g/11n20/11n40	1/6/6.5/13.5 Mbps	1/6/11	3/6/9
Radiated Spurious Emission	11b/11g/11n20/11n40	1/6/6.5/13.5 Mbps	1/6/11	3/6/9
Band Edge	11b/11g/11n20/11n40	1/6/6.5/13.5 Mbps	1/6/11	3/6/9
Power spectral density (PSD)	11b/11g/11n20/11n40	1/6/6.5/13.5 Mbps	1/6/11	3/6/9

Note: The above EUT information in section 2.4 was declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or user's manual.

3 SUMMARY OF TEST RESULTS

3.1 Test Standards

No.	Identity	Document Title
1	47 CFR Part 15, Subpart C	Intentional radiators of radio frequency equipment
2 ☆	KDB Publication 662911 D01v02r01	Emissions Testing of Transmitters with Multiple Outputs in the Same Band (e.g., MIMO, Smart Antenna, etc)
3	ANSI C63.10-2013	American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices
4 ☆	KDB Publication 558074 D01v05r02	GUIDANCE FOR COMPLIANCE MEASUREMENTS ON DIGITAL TRANSMISSION SYSTEM, FREQUENCY HOPPING SPREAD SPECTRUM SYSTEM, AND HYBRID SYSTEM DEVICES OPERATING UNDER SECTION 15.247 OF THE FCC RULES

3.2 Test Verdict

No.	Description	FCC PART No.	Test Result	Verdict
1	Antenna Requirement	15.203	N/A	Pass ^{Note}
2	Output Power	15.247 (b)	ANNEX A.1	Pass
3	Occupied Bandwidth	15.247 (a)	ANNEX A.2	Pass
4	Conducted Spurious Emission	15.247 (d)	ANNEX A.3	Pass
5	Band Edge(Authorized-band band-edge)	15.247 (d)	ANNEX A.4	Pass
6	Conducted Emission	15.207	ANNEX A.5	Pass
7	Radiated Spurious Emission	15.209; 15.247 (d)	ANNEX A.6	Pass
8	Band Edge(Restricted-band band-edge)	15.209; 15.247 (d)	ANNEX A.7	Pass
9	Power spectral density (PSD)	15.247 (e)	ANNEX A.8	Pass

Note: The EUT has a permanently and irreplaceable attached antenna, which complies with the requirement FCC 15.203.

4 GENERAL TEST CONFIGURATIONS

4.1 Test Environments

During the measurement, the normal environmental conditions were within the listed ranges:

Relative Humidity	38% to 60%	
Atmospheric Pressure	100 kPa to 102 kPa	
Temperature	NT (Normal Temperature)	+20.6℃ to +24.5℃
Working Voltage of the EUT	NV (Normal Voltage)	12 V

4.2 Test Equipment List

Description	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due
Spectrum Analyzer	KEYSIGHT	N9020A	MY46471071	2024.07.04	2025.07.03
Spectrum Analyzer	KEYSIGHT	N9020A	MY52510065	2024.08.01	2025.07.31
Power Sensor	KEYSIGHT	U2063XA	MY58000247	2024.07.04	2025.07.03
Test Antenna-Horn	SCHWARZBECK	BBHA 9120D	01631	2025.02.22	2028.02.21
Test Antenna-Horn	A-INFO	LB-180400KF	J211060273	2024.06.15	2027.06.14
Anechoic Chamber	RAINFORD	9m*6m*6m	144	2022.02.19	2025.09.03
Amplifier	COM-MV	LSCX_LNA1-12G-01	180602	2024.08.01	2025.07.31
Amplifier	COM-MV	XKu_LNA7-18G-01	180601	2024.08.01	2025.07.31
EMI Receiver	ROHDE&SCHWARZ	ESRP	101036	2024.08.01	2025.07.31
Test Antenna-Loop	SCHWARZBECK	FMZB 1519	1519-037	2024.01.23	2027.01.22
Amplifier	COM-MV	ZT30-1000M	B2018054558	2024.11.28	2025.11.27
Anechoic Chamber	EMC Electronic Co., Ltd	20.10*11.60*7.35m	130	2024.07.13	2027.07.12
EMI Receiver	Agilent	N9038A	MY55330120	2024.08.01	2025.07.31
Test Antenna-Bi-Log	SCHWARZBECK	VULB 9168	9168-00867	2022.04.12	2025.04.11
Amplifier	COM-MV	ZT30-1000M	B2017119081	2024.11.28	2025.11.27
Anechoic Chamber	YiHeng	9m*6m*6m	142	2024.07.21	2027.07.20
EMI Receiver	KEYSIGHT	N9010B	MY57110309	2024.08.01	2025.07.31
LISN	SCHWARZBECK	NSLK 8127	8127-687	2024.05.09	2025.05.08
Shielded Enclosure	YiHeng Electronic Co., Ltd	3.5m*3.1m*2.8m	112	2025.02.14	2028.02.13

4.3 Test Software List

Description	Manufacturer	Software Version	Serial No.	Applicable test Setup
BL410R	BALUN	V2.1.1.488	N/A	The section 4.5.1
BL410E	BALUN	V22.930	N/A	The section 4.5.2&4.5.3&4.5.4&4.5.5

4.4 Measurement Uncertainty

The following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2.

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

Parameters	Uncertainty
Occupied Channel Bandwidth	2.8%
RF output power, conducted	1.28 dB
Power Spectral Density, conducted	1.30 dB
Unwanted Emissions, conducted	1.84 dB
All emissions, radiated	5.36 dB
Temperature	0.8℃
Humidity	4%


4.5 Description of Test Setup

4.5.1 For Antenna Port Test

Conducted value (dBm) = Measurement value (dBm) + cable loss (dB)


For example: the measurement value is 10 dBm and the cable 0.5dBm used, then the final result of EUT:

Conducted value (dBm) = 10 dBm + 0.5 dB = 10.5 dBm




(Diagram 1)

4.5.2 For AC Power Supply Port Test




(Diagram 2)

4.5.3 For Radiated Test (Below 30 MHz)




(Diagram 3)

4.5.4 For Radiated Test (30 MHz-1 GHz)



(Diagram 4)

4.5.5 For Radiated Test (Above 1 GHz)



(Diagram 5)

4.6 Measurement Results Explanation Example

4.6.1 For conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

4.6.2 For radiated band edges and spurious emission test:

$$E = \text{EIRP} - 20\log D + 104.8$$

where:

E = electric field strength in dB μ V/m,

EIRP = equivalent isotropic radiated power in dBm

D = specified measurement distance in meters.

EIRP = Measure Conducted output power Value (dBm) + Maximum transmit antenna gain (dBi) + the appropriate maximum ground reflection factor (dB)

5 TEST ITEMS

5.1 Antenna Requirements

5.1.1 Relevant Standards

FCC §15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of § 15.211, § 15.213, § 15.217, § 15.219, or § 15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with § 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

If directional gain of transmitting antennas is greater than 6 dBi, the power shall be reduced by the same level in dB comparing to gain minus 6 dBi. For the fixed point-to-point operation, the power shall be reduced by one dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the FCC rule.

5.1.2 Antenna Anti-Replacement Construction

The Antenna Anti-Replacement as following method:

Protected Method	Description
The antenna is embedded in the product.	An embedded-in antenna design is used.

Reference Documents	Item
Photo	Please refer to the EUT Photo documents.

5.1.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.

5.2 Output Power

5.2.1 Test Limit

FCC § 15.247(b)

For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements.

5.2.2 Test Setup

See section 4.5.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.2.3 Test Procedure

Maximum peak conducted output power

The maximum peak conducted output power may be measured using a broadband peak RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall utilize a fast-responding diode detector.

The EUT shall be transmitted at its maximum power control level.

Maximum conducted (average) output power (Reporting Only)

a) As an alternative to spectrum analyzer or EMI receiver measurements, measurements may be performed using a wideband RF power meter with a thermocouple detector or equivalent if all of the conditions listed below are satisfied.

- 1) The EUT is configured to transmit continuously, or to transmit with a constant duty factor.
 - 2) At all times when the EUT is transmitting, it shall be transmitting at its maximum power control level.
 - 3) The integration period of the power meter exceeds the repetition period of the transmitted signal by at least a factor of five.
- b) If the transmitter does not transmit continuously, measure the duty cycle (x) of the transmitter output signal.
- c) Measure the average power of the transmitter. This measurement is an average over both the on and off periods of the transmitter.
- d) Adjust the measurement in dBm by adding $10\log(1/x)$, where x is the duty cycle.

Measurements of duty cycle

The zero-span mode on a spectrum analyzer or EMI receiver if the response time and spacing between

bins on the sweep are sufficient to permit accurate measurements of the on and off times of the transmitted signal.

Set the center frequency of the instrument to the center frequency of the transmission.

Set $RBW \geq OBW$ if possible; otherwise, set RBW to the largest available value.

Set $VBW \geq RBW$. Set detector = peak or average.

The zero-span measurement method shall not be used unless both RBW and VBW are $> 50/T$ and the number of sweep points across duration T exceeds 100. (For example, if VBW and/or RBW are limited to 3 MHz, then the zero-span method of measuring duty cycle shall not be used if $T \leq 16.7$ microseconds.)

5.2.4 Test Result

Please refer to ANNEX A.1.

5.3 Occupied Bandwidth

5.3.1 Limit

FCC §15.247(a)

Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. In order to make an accurate measurement, set the span greater than RBW. The 6 dB bandwidth must be greater than 500 kHz.

5.3.2 Test Setup

See section 4.5.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.3.3 Test Procedure

Use the following spectrum analyzer settings:

Set RBW = 100 kHz.

Set the video bandwidth (VBW) ≥ 3 RBW.

Detector = Peak.

Trace mode = max hold.

Sweep = auto couple.

Allow the trace to stabilize.

Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

5.3.4 Test Result

Please refer to ANNEX A.2.

5.4 Conducted Spurious Emission

5.4.1 Limit

FCC §15.247(d)

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

5.4.2 Test Setup

See section 4.5.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.4.3 Test Procedure

The DTS rules specify that in any 100 kHz bandwidth outside of the authorized frequency band, the power shall be attenuated according to the following conditions:

- a) If the maximum peak conducted output power procedure was used to demonstrate compliance as described in 9.1, then the peak output power measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz (i.e., 20 dBc).
- b) If maximum conducted (average) output power was used to demonstrate compliance as described in 9.2, then the peak power in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 30 dB relative to the maximum in-band peak PSD level in 100 kHz (i.e., 30 dBc).
- c) In either case, attenuation to levels below the 15.209 general radiated emissions limits is not required.

The following procedures shall be used to demonstrate compliance to these limits. Note that these procedures can be used in either an antenna-port conducted or radiated test set-up. Radiated tests must conform to the test site requirements and utilize maximization procedures defined herein.

Reference level measurement

Establish a reference level by using the following procedure:

Set instrument center frequency to DTS channel center frequency.

Set the span to ≥ 1.5 times the DTS bandwidth.

Set the RBW = 100 kHz.

Set the VBW $\geq 3 \times$ RBW.

Detector = peak.

Sweep time = auto couple.

Trace mode = max hold.

Allow trace to fully stabilize.

Use the peak marker function to determine the maximum PSD level.

Emission level measurement

Use the following spectrum analyzer settings:

Span = wide enough to capture the peak level of the in-band emission and all spurious emissions (e.g., harmonics) from the lowest frequency generated in the EUT up through the 10th harmonic. Typically, several plots are required to cover this entire span.

Set the RBW = 100 kHz.

Set the VBW $\geq 3 \times$ RBW.

Detector = peak.

Sweep time = auto couple.

Trace mode = max hold.

Allow trace to fully stabilize.

Use the peak marker function to determine the maximum amplitude level.

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) are attenuated by at least the minimum requirements specified in 11.1 a) or 11.1 b). Report the three highest emissions relative to the limit.

5.4.4 Test Result

Please refer to ANNEX A.3.

5.5 Band Edge (Authorized-band band-edge)

5.5.1 Limit

FCC §15.247(d)

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

5.5.2 Test Setup

See section 4.5.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.5.3 Test Procedure

The following procedures may be used to determine the peak or average field strength or power of an unwanted emission that is within 2 MHz of the authorized band edge. If a peak detector is utilized, use the procedure described in 13.2.1. Use the procedure described in 13.2.2 when using an average detector and the EUT can be configured to transmit continuously (i.e., duty cycle $\geq 98\%$). Use the procedure described in 13.2.3 when using an average detector and the EUT cannot be configured to transmit continuously but the duty cycle is constant (i.e., duty cycle variations are less than ± 2 percent). Use the procedure described in 13.2.4 when using an average detector for those cases where the EUT cannot be configured to transmit continuously and the duty cycle is not constant (duty cycle variations equal or exceed 2 percent).

When using a peak detector to measure unwanted emissions at or near the band edge (within 2 MHz of the authorized band), the following integration procedure can be used.

Set instrument center frequency to the frequency of the emission to be measured (must be within 2 MHz of the authorized band edge).

Set span to 2 MHz

RBW = 100 kHz.

VBW $\geq 3 \times$ RBW.

Detector = peak.

Sweep time = auto.

Trace mode = max hold.

Allow sweep to continue until the trace stabilizes (required measurement time may increase for low duty cycle applications)

Compute the power by integrating the spectrum over 1 MHz using the analyzer's band power measurement function with band limits set equal to the emission frequency (femission) ± 0.5 MHz. If the instrument does not have a band power function, then sum the amplitude levels (in power units) at 100 kHz intervals extending across the 1 MHz spectrum defined by femission ± 0.5 MHz.

Standard method(The 99% OBW of the fundamental emission is without 2 MHz of the authorized band):

Span: Wide enough to capture the peak level of the emission operating on the channel closest to the band edge, as well as any modulation products that fall outside of the authorized band of operation.

Reference level: As required to keep the signal from exceeding the maximum instrument input mixer level for linear operation. In general, the peak of the spectral envelope shall be more than $[10 \log (\text{OBW/RBW})]$ below the reference level. Specific guidance is given in 4.1.5.2.

Attenuation: Auto (at least 10 dB preferred).

Sweep time: Coupled.

Resolution bandwidth: 100 kHz.

Video bandwidth: 300 kHz.

Detector: Peak.

Trace: Max hold.

5.5.4 Test Result

Please refer to ANNEX A.4.

5.6 Conducted Emission

5.6.1 Limit

FCC §15.207

For an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 Ω line impedance stabilization network (LISN).

Frequency range (MHz)	Conducted Limit (dB μ V)	
	Quai-peak	Average
0.15 - 0.50	66 to 56	56 to 46
0.50 - 5	56	46
0.50 - 30	60	50

5.6.2 Test Setup

See section 4.5.2 for test setup description for the AC power supply port. The photo of test setup please refer to ANNEX B.

5.6.3 Test Procedure

The maximum conducted interference is searched using Peak (PK), if the emission levels more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed. Refer to recorded points and plots below.

Devices subject to Part 15 must be tested for all available U.S. voltages and frequencies (such as a nominal 120 VAC, 50/60 Hz and 240 VAC, 50/60 Hz) for which the device is capable of operation. A device rated for 50/60 Hz operation need not be tested at both frequencies provided the radiated and line conducted emissions are the same at both frequencies.

5.6.4 Test Result

Please refer to ANNEX A.5.

5.7 Radiated Spurious Emission

5.7.1 Limit

FCC §15.209&15.247(d)

Radiated emission outside the frequency band attenuation below the general limits specified in FCC section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in FCC section 15.205(a), must also comply with the radiated emission limits specified in FCC section 15.209(a).

According to FCC section 15.209 (a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength (μV/m)	Measurement Distance (m)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

Note:

1. For Above 1000 MHz, the emission limit in this paragraph is based on measurement instrumentation employing an average detector, measurement using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit.
2. For above 1000 MHz, limit field strength of harmonics: 54dBuV/m@3m (AV) and 74dBuV/m@3m (PK).

5.7.2 Test Setup

See section 4.5.3 to 4.5.5 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.7.3 Test Procedure

Since the emission limits are specified in terms of radiated field strength levels, measurements performed to demonstrate compliance have traditionally relied on a radiated test configuration. Radiated measurements remain the principal method for demonstrating compliance to the specified limits; however antenna-port conducted measurements are also now acceptable to demonstrate compliance (see below for details). When radiated measurements are utilized, test site requirements and procedures for maximizing and measuring radiated emissions that are described in ANSI C63.10 shall be followed.

Antenna-port conducted measurements may also be used as an alternative to radiated measurements for demonstrating compliance in the restricted frequency bands. If conducted measurements are performed, then proper impedance matching must be ensured and an additional radiated test for cabinet/case spurious emissions is required.

General Procedure for conducted measurements in restricted bands

- a) Measure the conducted output power (in dBm) using the detector specified (see guidance regarding measurement procedures for determining quasi-peak, peak, and average conducted output power, respectively).
- b) Add the maximum transmit antenna gain (in dBi) to the measured output power level to determine the EIRP level (see guidance on determining the applicable antenna gain)
- c) Add the appropriate maximum ground reflection factor to the EIRP level (6 dB for frequencies ≤ 30 MHz, 4.7 dB for frequencies between 30 MHz and 1000 MHz, inclusive and 0 dB for frequencies > 1000 MHz).
- d) For devices with multiple antenna-ports, measure the power of each individual chain and sum the EIRP of all chains in linear terms (e.g., Watts, mW).
- e) Convert the resultant EIRP level to an equivalent electric field strength using the following relationship:

$$E = \text{EIRP} - 20\log D + 104.8$$

where:

E = electric field strength in dB μ V/m,

EIRP = equivalent isotropic radiated power in dBm

D = specified measurement distance in meters.

- f) Compare the resultant electric field strength level to the applicable limit.
- g) Perform radiated spurious emission test.

Quasi-Peak measurement procedure

The specifications for measurements using the CISPR quasi-peak detector can be found in Publication 16 of the International Special Committee on Radio Frequency Interference (CISPR) of the International Electrotechnical Commission.

As an alternative to CISPR quasi-peak measurement, compliance can be demonstrated to the applicable emission limits using a peak detector.

Peak power measurement procedure

Peak emission levels are measured by setting the instrument as follows:

- a) RBW = as specified in Table 1.
- b) VBW $\geq 3 \times$ RBW.
- c) Detector = Peak.
- d) Sweep time = auto.
- e) Trace mode = max hold.
- f) Allow sweeps to continue until the trace stabilizes. (Note that the required measurement time may be

longer for low duty cycle applications).

Table 1—RBW as a function of frequency

Frequency	RBW
9-150 kHz	200-300 Hz
0.15-30 MHz	9-10 kHz
30-1000 MHz	100-120 kHz
> 1000 MHz	1 MHz

If the peak-detected amplitude can be shown to comply with the average limit, then it is not necessary to perform a separate average measurement.

Trace averaging across on and off times of the EUT transmissions followed by duty cycle correction

If continuous transmission of the EUT (i.e., duty cycle ≥ 98 percent) cannot be achieved and the duty cycle is constant (i.e., duty cycle variations are less than ± 2 percent), then the following procedure shall be used:

- a) The EUT shall be configured to operate at the maximum achievable duty cycle.
- b) Measure the duty cycle, x , of the transmitter output signal as described in section 6.0.
- c) RBW = 1 MHz (unless otherwise specified).
- d) VBW $\geq 3 \times$ RBW.
- e) Detector = RMS, if $\text{span}/(\# \text{ of points in sweep}) \leq (\text{RBW}/2)$. Satisfying this condition may require increasing the number of points in the sweep or reducing the span. If this condition cannot be satisfied, then the detector mode shall be set to peak.
- f) Averaging type = power (i.e., RMS).
 - 1) As an alternative, the detector and averaging type may be set for linear voltage averaging.
 - 2) Some instruments require linear display mode in order to use linear voltage averaging. Log or dB averaging shall not be used.
- g) Sweep time = auto.
- h) Perform a trace average of at least 100 traces.
- i) A correction factor shall be added to the measurement results prior to comparing to the emission limit in order to compute the emission level that would have been measured had the test been performed at 100 percent duty cycle. The correction factor is computed as follows:
 - 1) If power averaging (RMS) mode was used in step f), then the applicable correction factor is $10 \log(1/x)$, where x is the duty cycle.
 - 2) If linear voltage averaging mode was used in step f), then the applicable correction factor is $20 \log(1/x)$, where x is the duty cycle.
 - 3) If a specific emission is demonstrated to be continuous (≥ 98 percent duty cycle) rather than turning on and off with the transmit cycle, then no duty cycle correction is required for that emission.

NOTE: Reduction of the measured emission amplitude levels to account for operational duty factor is not permitted. Compliance is based on emission levels occurring during transmission - not on an average across on and off times of the transmitter.

Determining the applicable transmit antenna gain

A conducted power measurement will determine the maximum output power associated with a restricted band emission; however, in order to determine the associated EIRP level, the gain of the transmitting antenna (in dBi) must be added to the measured output power (in dBm).

Since the out-of-band characteristics of the EUT transmit antenna will often be unknown, the use of a conservative antenna gain value is necessary. Thus, when determining the EIRP based on the measured conducted power, the upper bound on antenna gain for a device with a single RF output shall be selected as the maximum in-band gain of the antenna across all operating bands, or 2 dBi, whichever is greater. However, for devices that operate in multiple frequency bands while using the same transmit antenna, the highest gain of the antenna within the operating band nearest in frequency to the restricted band emission being measured may be used in lieu of the overall highest gain when the emission is at a frequency that is within 20 percent of the nearest band edge frequency, but in no case shall a value less than 2 dBi be used.

See KDB 662911 for guidance on calculating the additional array gain term when determining the effective antenna gain for a EUT with multiple outputs occupying the same or overlapping frequency ranges in the same band.

Radiated spurious emission test

An additional consideration when performing conducted measurements of restricted band emissions is that unwanted emissions radiating from the EUT cabinet, control circuits, power leads, or intermediate circuit elements will likely go undetected in a conducted measurement configuration. To address this concern, a radiated test shall be performed to ensure that emissions emanating from the EUT cabinet (rather than the antenna port) also comply with the applicable limits.

For these cabinet radiated spurious emission measurements the EUT transmit antenna may be replaced with a termination matching the nominal impedance of the antenna. Procedures for performing radiated measurements are specified in ANSI C63.10. All detected emissions shall comply with the applicable limits.

The measurement frequency range is from 30 MHz to the 10th harmonic of the fundamental frequency. The Turn Table is actuated to turn from 0° to 360°, and both horizontal and vertical polarizations of the Test Antenna are used to find the maximum radiated power. Mid channels on all channel bandwidth verified. Only the worst RB size/offset presented.

The power of the EUT transmitting frequency should be ignored.

All Spurious Emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

Use the following spectrum analyzer settings:

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for $f \geq 1$ GHz, 100 kHz for $f < 1$ GHz

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

5.7.4 Test Result

Please refer to ANNEX A.6.

5.8 Band Edge (Restricted-band band-edge)

5.8.1 Limit

FCC §15.209&15.247(d)

Radiated emission outside the frequency band attenuation below the general limits specified in FCC section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in FCC section 15.205(a), must also comply with the radiated emission limits specified in FCC section 15.209(a).

5.8.2 Test Setup

See section 4.5.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.8.3 Test Procedure

The measurement frequency range is from 9 kHz to the 10th harmonic of the fundamental frequency. The Turn Table is actuated to turn from 0° to 360°, and both horizontal and vertical polarizations of the Test Antenna are used to find the maximum radiated power. Mid channels on all channel bandwidth verified. Only the worst RB size/offset presented.

The power of the EUT transmitting frequency should be ignored.

All Spurious Emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

Use the following spectrum analyzer settings:

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for $f \geq 1$ GHz, 100 kHz for $f < 1$ GHz

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported, Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.

For transmitters operating above 1 GHz repeat the measurement with an average detector.

5.8.4 Test Result

Please refer to ANNEX A.7.

5.9 Power Spectral density (PSD)

5.9.1 Limit

FCC §15.247(e)

The same method of determining the conducted output power shall be used to determine the power spectral density. If a peak output power is measured, then a peak power spectral density measurement is required. If an average output power is measured, then an average power spectral density measurement should be used.

5.9.2 Test Setup

See section 4.5.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.9.3 Test Procedure

Set analyzer center frequency to DTS channel center frequency.

Set the span to 1.5 times the DTS bandwidth.

Set the RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.

Set the VBW $\geq 3 \text{ RBW}$.

Detector = peak.

Sweep time = auto couple.

Trace mode = max hold.

Allow trace to fully stabilize.

Use the peak marker function to determine the maximum amplitude level within the RBW.

If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

5.9.4 Test Result

Please refer to ANNEX A.8.

ANNEX A TEST RESULT

A.1 Output Power

Duty Cycle

Test Mode	On Time (ms)	On+Off time (ms)	Duty Cycle	Duty Factor
802.11b	12.36	12.79	96.64%	0.15
802.11g	2.10	2.25	92.99%	0.32
802.11n-20 MHz	1.92	2.09	91.58%	0.38
802.11n-40 MHz	0.94	1.15	81.74%	0.88

SISO-Antenna 1

Peak Power Test Data

802.11b Mode:

Channel	Measured Output Peak Power		Limit		Verdict
	dBm	mW	dBm	mW	
Low	15.24	33.42	30	1000	Pass
Middle	15.52	35.65			Pass
High	15.83	38.28			Pass

802.11g Mode:

Channel	Measured Output Peak Power		Limit		Verdict
	dBm	mW	dBm	mW	
Low	19.83	96.16	30	1000	Pass
Middle	19.94	98.63			Pass
High	19.12	81.66			Pass

802.11n-20 MHz Mode:

Channel	Measured Output Peak Power		Limit		Verdict
	dBm	mW	dBm	mW	
Low	19.32	85.51	30	1000	Pass
Middle	19.82	95.94			Pass
High	18.06	63.97			Pass

802.11n-40 MHz Mode:

Channel	Measured Output Peak Power		Limit		Verdict
	dBm	mW	dBm	mW	
Low	14.18	26.18	30	1000	Pass
Middle	18.73	74.64			Pass
High	12.56	18.03			Pass

Average Power Test Data

802.11b Mode:

Channel	Measured Output Average Power		Limit		Verdict
	dBm	mW	dBm	mW	
Low	13.37	21.73	30	1000	Pass
Middle	13.28	21.28			Pass
High	13.52	22.49			Pass

802.11g Mode:

Channel	Measured Output Average Power		Limit		Verdict
	dBm	mW	dBm	mW	
Low	13.41	21.93	30	1000	Pass
Middle	13.65	23.17			Pass
High	12.94	19.68			Pass

802.11n-20 MHz Mode:

Channel	Measured Output Average Power		Limit		Verdict
	dBm	mW	dBm	mW	
Low	12.88	19.41	30	1000	Pass
Middle	13.36	21.68			Pass
High	11.54	14.26			Pass

802.11n-40 MHz Mode:

Channel	Measured Output Average Power		Limit		Verdict
	dBm	mW	dBm	mW	
Low	9.29	8.49	30	1000	Pass
Middle	13.65	23.17			Pass
High	7.14	5.18			Pass

SISO-Antenna 2Peak Power Test Data

802.11b Mode:

Channel	Measured Output Peak Power		Limit		Verdict
	dBm	mW	dBm	mW	
Low	15.66	36.81	30	1000	Pass
Middle	15.36	34.36			Pass
High	15.58	36.14			Pass

802.11g Mode:

Channel	Measured Output Peak Power		Limit		Verdict
	dBm	mW	dBm	mW	
Low	19.91	97.95	30	1000	Pass
Middle	20.36	108.64			Pass
High	19.03	79.98			Pass

802.11n-20 MHz Mode:

Channel	Measured Output Peak Power		Limit		Verdict
	dBm	mW	dBm	mW	
Low	18.82	76.21	30	1000	Pass
Middle	20.02	100.46			Pass
High	18.58	72.11			Pass

802.11n-40 MHz Mode:

Channel	Measured Output Peak Power		Limit		Verdict
	dBm	mW	dBm	mW	
Low	14.03	25.29	30	1000	Pass
Middle	19.59	90.99			Pass
High	12.71	18.66			Pass

Average Power Test Data

802.11b Mode:

Channel	Measured Output Average Power		Limit		Verdict
	dBm	mW	dBm	mW	
Low	13.37	21.73	30	1000	Pass
Middle	13.17	20.75			Pass
High	13.38	21.78			Pass

802.11g Mode:

Channel	Measured Output Average Power		Limit		Verdict
	dBm	mW	dBm	mW	
Low	13.46	22.18	30	1000	Pass
Middle	13.61	22.96			Pass
High	12.91	19.54			Pass

802.11n-20 MHz Mode:

Channel	Measured Output Average Power		Limit		Verdict
	dBm	mW	dBm	mW	
Low	12.49	17.74	30	1000	Pass
Middle	13.35	21.63			Pass
High	11.84	15.28			Pass

802.11n-40 MHz Mode:

Channel	Measured Output Average Power		Limit		Verdict
	dBm	mW	dBm	mW	
Low	9.25	8.41	30	1000	Pass
Middle	13.56	22.70			Pass
High	7.32	5.40			Pass

MIMO-Antenna 1Peak Power Test Data

802.11b Mode:

Channel	Measured Output Peak Power		Limit		Verdict
	dBm	mW	dBm	mW	
Low	12.93	19.63	28.25	668.34	Pass
Middle	12.54	17.95			Pass
High	12.71	18.66			Pass

802.11g Mode:

Channel	Measured Output Peak Power		Limit		Verdict
	dBm	mW	dBm	mW	
Low	17.67	58.48	28.25	668.34	Pass
Middle	16.66	46.34			Pass
High	16.44	44.06			Pass

802.11n-20 MHz Mode:

Channel	Measured Output Peak Power		Limit		Verdict
	dBm	mW	dBm	mW	
Low	16.90	48.98	30	1000	Pass
Middle	16.38	43.45			Pass
High	15.93	39.17			Pass

802.11n-40 MHz Mode:

Channel	Measured Output Peak Power		Limit		Verdict
	dBm	mW	dBm	mW	
Low	13.72	23.55	30	1000	Pass
Middle	15.07	32.14			Pass
High	12.91	19.54			Pass

Average Power Test Data

802.11b Mode:

Channel	Measured Output Average Power		Limit		Verdict
	dBm	mW	dBm	mW	
Low	10.65	11.61	28.25	668.34	Pass
Middle	10.43	11.04			Pass
High	10.56	11.38			Pass

802.11g Mode:

Channel	Measured Output Average Power		Limit		Verdict
	dBm	mW	dBm	mW	
Low	10.73	11.83	28.25	668.34	Pass
Middle	10.59	11.46			Pass
High	10.10	10.23			Pass

802.11n-20 MHz Mode:

Channel	Measured Output Average Power		Limit		Verdict
	dBm	mW	dBm	mW	
Low	10.64	11.59	30	1000	Pass
Middle	10.31	10.74			Pass
High	10.52	11.27			Pass

802.11n-40 MHz Mode:

Channel	Measured Output Average Power		Limit		Verdict
	dBm	mW	dBm	mW	
Low	9.03	8.00	30	1000	Pass
Middle	10.37	10.89			Pass
High	7.45	5.56			Pass

MIMO-Antenna 2Peak Power Test Data

802.11b Mode:

Channel	Measured Output Peak Power		Limit		Verdict
	dBm	mW	dBm	mW	
Low	12.88	19.41	28.25	668.34	Pass
Middle	12.95	19.72			Pass
High	12.76	18.88			Pass

802.11g Mode:

Channel	Measured Output Peak Power		Limit		Verdict
	dBm	mW	dBm	mW	
Low	17.61	57.68	28.25	668.34	Pass
Middle	17.68	58.61			Pass
High	17.74	59.43			Pass

802.11n-20 MHz Mode:

Channel	Measured Output Peak Power		Limit		Verdict
	dBm	mW	dBm	mW	
Low	17.31	53.83	30	1000	Pass
Middle	17.65	58.21			Pass
High	17.64	58.08			Pass

802.11n-40 MHz Mode:

Channel	Measured Output Peak Power		Limit		Verdict
	dBm	mW	dBm	mW	
Low	13.92	24.66	30	1000	Pass
Middle	15.64	36.64			Pass
High	12.82	19.14			Pass

Average Power Test Data

802.11b Mode:

Channel	Measured Output Average Power		Limit		Verdict
	dBm	mW	dBm	mW	
Low	10.57	11.40	28.25	668.34	Pass
Middle	10.62	11.53			Pass
High	10.42	11.02			Pass

802.11g Mode:

Channel	Measured Output Average Power		Limit		Verdict
	dBm	mW	dBm	mW	
Low	10.54	11.32	28.25	668.34	Pass
Middle	10.51	11.25			Pass
High	10.48	11.17			Pass

802.11n-20 MHz Mode:

Channel	Measured Output Average Power		Limit		Verdict
	dBm	mW	dBm	mW	
Low	10.59	11.46	30	1000	Pass
Middle	10.22	10.52			Pass
High	10.34	10.81			Pass

802.11n-40 MHz Mode:

Channel	Measured Output Average Power		Limit		Verdict
	dBm	mW	dBm	mW	
Low	9.26	8.43	30	1000	Pass
Middle	10.27	10.64			Pass
High	7.38	5.47			Pass

MIMOPeak Power Test Data

802.11b Mode:

Channel	Measured Output Peak Power		Limit		Verdict
	dBm	mW	dBm	mW	
Low	15.92	39.04	28.25	668.34	Pass
Middle	15.76	37.67			Pass
High	15.75	37.54			Pass

802.11g Mode:

Channel	Measured Output Peak Power		Limit		Verdict
	dBm	mW	dBm	mW	
Low	20.65	116.16	28.25	668.34	Pass
Middle	20.21	104.96			Pass
High	20.15	103.48			Pass

802.11n-20 MHz Mode:

Channel	Measured Output Peak Power		Limit		Verdict
	dBm	mW	dBm	mW	
Low	20.12	102.80	30	1000	Pass
Middle	20.07	101.66			Pass
High	19.88	97.25			Pass

802.11n-40 MHz Mode:

Channel	Measured Output Peak Power		Limit		Verdict
	dBm	mW	dBm	mW	
Low	16.83	48.21	30	1000	Pass
Middle	18.37	68.78			Pass
High	15.88	38.69			Pass

Average Power Test Data

802.11b Mode:

Channel	Measured Output Average Power		Limit		Verdict
	dBm	mW	dBm	mW	
Low	13.62	23.02	28.25	668.34	Pass
Middle	13.54	22.58			Pass
High	13.50	22.39			Pass

802.11g Mode:

Channel	Measured Output Average Power		Limit		Verdict
	dBm	mW	dBm	mW	
Low	13.65	23.15	28.25	668.34	Pass
Middle	13.56	22.70			Pass
High	13.30	21.40			Pass

802.11n-20 MHz Mode:

Channel	Measured Output Average Power		Limit		Verdict
	dBm	mW	dBm	mW	
Low	13.63	23.04	30	1000	Pass
Middle	13.28	21.26			Pass
High	13.44	22.09			Pass

802.11n-40 MHz Mode:

Channel	Measured Output Average Power		Limit		Verdict
	dBm	mW	dBm	mW	
Low	12.16	16.43	30	1000	Pass
Middle	13.33	21.53			Pass
High	10.43	11.03			Pass

A.2 Occupied Bandwidth

Note: All antenna were pre tested, but only the worst case has been reported in this report.

SISO-Antenna 1

Test Data

802.11b Mode:

Channel	6 dB Bandwidth (MHz)	99% Bandwidth (MHz)	6 dB Bandwidth Limits (kHz)
Low	10.300000	14.774000	≥ 500
Middle	10.300000	14.798000	≥ 500
High	10.300000	14.807000	≥ 500

802.11g Mode:

Channel	6 dB Bandwidth (MHz)	99% Bandwidth (MHz)	6 dB Bandwidth Limits (kHz)
Low	16.000000	17.038000	≥ 500
Middle	16.200000	17.043000	≥ 500
High	15.900000	16.959000	≥ 500

802.11n-20MHz Mode:

Channel	6 dB Bandwidth (MHz)	99% Bandwidth (MHz)	6 dB Bandwidth Limits (kHz)
Low	16.800000	18.222000	≥ 500
Middle	16.700000	18.103000	≥ 500
High	16.500000	18.040000	≥ 500

802.11n-40MHz Mode:

Channel	6 dB Bandwidth (MHz)	99% Bandwidth (MHz)	6 dB Bandwidth Limits (kHz)
Low	35.300000	36.208000	≥ 500
Middle	35.300000	36.191000	≥ 500
High	35.300000	36.151000	≥ 500

Test Plots

6 dB Bandwidth

802.11b LOW CHANNEL



802.11b MIDDLE CHANNEL



802.11b HIGH CHANNEL



802.11g LOW CHANNEL



802.11g MIDDLE CHANNEL



802.11g HIGH CHANNEL



802.11n-20 MHz LOW CHANNEL




802.11n-20 MHz MIDDLE CHANNEL




802.11n-20 MHz HIGH CHANNEL




802.11n-40 MHz LOW CHANNEL



802.11n-40 MHz MIDDLE CHANNEL




802.11n-40 MHz HIGH CHANNEL




99% Bandwidth


802.11b LOW CHANNEL



802.11b MIDDLE CHANNEL



802.11b HIGH CHANNEL



802.11g LOW CHANNEL




802.11g MIDDLE CHANNEL



802.11g HIGH CHANNEL



802.11n-20 MHz LOW CHANNEL



802.11n-20 MHz MIDDLE CHANNEL




802.11n-20 MHz HIGH CHANNEL




802.11n-40 MHz LOW CHANNEL



802.11n-40 MHz MIDDLE CHANNEL



802.11n-40 MHz HIGH CHANNEL



A.3 Conducted Spurious Emissions

Note: All antenna were pre tested, but only the worst case has been reported in this report.

SISO-Antenna 1

Test Data

802.11b Mode:

Channel	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 20 dBc Limit	
Low	-38.50	4.78	-15.23	Pass
Middle	-39.40	4.64	-15.36	Pass
High	-42.08	4.93	-15.07	Pass

802.11g Mode:

Channel	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 20 dBc Limit	
Low	-47.15	3.52	-16.48	Pass
Middle	-49.54	3.60	-16.40	Pass
High	-47.69	2.79	-17.21	Pass

802.11n-20MHz Mode:

Channel	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 20 dBc Limit	
Low	-48.23	2.85	-17.15	Pass
Middle	-48.66	3.40	-16.60	Pass
High	-48.96	1.62	-18.38	Pass

802.11n-40MHz Mode:


Channel	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 20 dBc Limit	
Low	-45.93	-3.69	-23.69	Pass
Middle	-46.87	1.13	-18.87	Pass
High	-49.01	-5.89	-25.89	Pass

Test Plots


802.11b LOW CHANNEL CARRIER LEVEL



802.11b LOW CHANNEL, SPURIOUS 30 MHz ~ 3 GHz




802.11b LOW CHANNEL, SPURIOUS 2 GHz ~ 25 GHz




802.11b MIDDLE CHANNEL CARRIER LEVEL



802.11b MIDDLE CHANNEL, SPURIOUS 30 MHz ~ 3 GHz




802.11b MIDDLE CHANNEL, SPURIOUS 2 GHz ~ 25 GHz




802.11b HIGH CHANNEL CARRIER LEVEL



802.11b HIGH CHANNEL, SPURIOUS 30 MHz ~ 3 GHz




802.11b HIGH CHANNEL, SPURIOUS 2 GHz ~ 25 GHz



802.11g LOW CHANNEL CARRIER LEVEL




802.11g LOW CHANNEL, SPURIOUS 30 MHz ~ 3 GHz




802.11g LOW CHANNEL, SPURIOUS 2 GHz ~ 25 GHz



802.11g MIDDLE CHANNEL CARRIER LEVEL




802.11g MIDDLE CHANNEL, SPURIOUS 30 MHz ~ 3 GHz




802.11g MIDDLE CHANNEL, SPURIOUS 2 GHz ~ 25 GHz



802.11g HIGH CHANNEL CARRIER LEVEL





802.11g HIGH CHANNEL, SPURIOUS 30 MHz ~ 3 GHz




802.11g HIGH CHANNEL, SPURIOUS 2 GHz ~ 25 GHz




802.11n-20 MHz LOW CHANNEL CARRIER LEVEL

802.11n-20 MHz LOW CHANNEL, SPURIOUS
30 MHz ~ 3 GHz802.11n-20 MHz LOW CHANNEL, SPURIOUS
2 GHz ~ 25 GHz


802.11n-20 MHz MIDDLE CHANNEL CARRIER LEVEL




802.11n-20 MHz MIDDLE CHANNEL, SPURIOUS 30 MHz ~ 3 GHz




802.11n-20 MHz MIDDLE CHANNEL, SPURIOUS 2 GHz ~ 25 GHz



802.11n-20 MHz HIGH CHANNEL CARRIER LEVEL






802.11n-20 MHz HIGH CHANNEL, SPURIOUS 30 MHz ~ 3 GHz




802.11n-20 MHz HIGH CHANNEL, SPURIOUS 2 GHz ~ 25 GHz




802.11n-40 MHz LOW CHANNEL CARRIER LEVEL

802.11n-40 MHz LOW CHANNEL, SPURIOUS
30 MHz ~ 3 GHz802.11n-40 MHz LOW CHANNEL, SPURIOUS
2 GHz ~ 25 GHz

802.11n-40 MHz MIDDLE CHANNEL CARRIER LEVEL




802.11n-40 MHz MIDDLE CHANNEL, SPURIOUS 30 MHz ~ 3 GHz




802.11n-40 MHz MIDDLE CHANNEL, SPURIOUS 2 GHz ~ 25 GHz



802.11n-40 MHz HIGH CHANNEL CARRIER LEVEL



802.11n-40 MHz HIGH CHANNEL, SPURIOUS 30 MHz ~ 3 GHz



802.11n-40 MHz HIGH CHANNEL, SPURIOUS 2 GHz ~ 25 GHz



A.4 Band Edge (Authorized-band band-edge)

Note ¹: The 99% OBW of the fundamental emission is without 2 MHz of the authorized band.

Note ²: All antenna were pre tested, but only the worst case has been reported in this report.

SISO-Antenna 1

Test Data

802.11b Mode:

Channel	Measured Max. Band Edge Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 20 dBc Limit	
Low Channel	-35.44	4.78	-15.23	Pass
High Channel	-52.46	4.93	-15.07	Pass

802.11g Mode:

Channel	Measured Max. Band Edge Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 20 dBc Limit	
Low Channel	-32.99	3.52	-16.48	Pass
High Channel	-45.17	2.79	-17.21	Pass

802.11n-20 MHz Mode:

Channel	Measured Max. Band Edge Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 20 dBc Limit	
Low Channel	-32.55	2.85	-17.15	Pass
High Channel	-45.46	1.62	-18.38	Pass

802.11n-40 MHz Mode:

Channel	Measured Max. Band Edge Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 20 dBc Limit	
Low Channel	-39.46	-3.69	-23.69	Pass
High Channel	-47.98	-5.89	-25.89	Pass

Test Plots

802.11b LOW CHANNEL, CARRIER LEVEL




802.11b LOW CHANNEL, BAND EDGE




802.11b HIGH CHANNEL, CARRIER LEVEL



802.11b HIGH CHANNEL, BAND EDGE



802.11g LOW CHANNEL, CARRIER LEVEL




802.11g LOW CHANNEL, BAND EDGE




802.11g HIGH CHANNEL, CARRIER LEVEL



802.11g HIGH CHANNEL, BAND EDGE




802.11n-20 MHz LOW CHANNEL, CARRIER LEVEL




802.11n-20 MHz LOW CHANNEL, BAND EDGE




802.11n-20 MHz HIGH CHANNEL, CARRIER LEVEL



802.11n-20 MHz HIGH CHANNEL, BAND EDGE




802.11n-40 MHz LOW CHANNEL, CARRIER LEVEL




802.11n-40 MHz LOW CHANNEL, BAND EDGE



802.11n-40 MHz HIGH CHANNEL, CARRIER LEVEL



802.11n-40 MHz HIGH CHANNEL, BAND EDGE



A.5 Conducted Emissions

Note¹: The EUT is working in the Normal link mode. All modes have been tested and normal link mode is worst.


Note²: Devices subject to Part 15 must be tested for all available U.S. voltages and frequencies (such as a nominal 120 VAC, 60 Hz and 240 VAC, 50 Hz) for which the device is capable of operation. So, The configuration 120 VAC, 60 Hz and 240 VAC, 50 Hz were tested respectively, but only the worst configuration (120 VAC, 60 Hz) shown here.

Note³: Results (dBuV) = Original reading level of Spectrum Analyzer (dBuV) + Factor (dB)

Test Data and Plots

PHASE L


CE Test case_FCC_CE_FCC PART 15C



No.	Frequency (MHz)	Results (dBuV)	Factor (dB)	Limit (dBuV)	Margin (dB)	Detector	Line	Verdict
1	0.158	59.23	9.78	65.57	6.34	Peak	L	Pass
1**	0.158	41.63	9.78	55.57	13.94	AV	L	Pass
2	0.178	56.41	9.78	64.58	8.17	Peak	L	Pass
2**	0.178	40.64	9.78	54.58	13.94	AV	L	Pass
3	0.230	49.84	9.77	62.45	12.61	Peak	L	Pass
3**	0.230	35.80	9.77	52.45	16.65	AV	L	Pass
4	0.350	45.28	10.76	58.96	13.68	Peak	L	Pass
4**	0.350	31.74	10.76	48.96	17.22	AV	L	Pass
5	0.486	43.51	9.99	56.24	12.73	Peak	L	Pass
5**	0.486	32.61	9.99	46.24	13.63	AV	L	Pass
6	1.240	39.39	10.35	56.00	16.61	Peak	L	Pass
6**	1.240	27.25	10.35	46.00	18.75	AV	L	Pass

PHASE N

CE Test case_FCC_CE_FCC PART 15C



No.	Frequency (MHz)	Results (dBuV)	Factor (dB)	Limit (dBuV)	Margin (dB)	Detector	Line	Verdict
1	0.160	57.69	9.78	65.46	7.77	Peak	N	Pass
1**	0.160	41.28	9.78	55.46	14.18	AV	N	Pass
2	0.166	57.59	9.78	65.16	7.57	Peak	N	Pass
2**	0.166	44.08	9.78	55.16	11.08	AV	N	Pass
3	0.210	49.73	9.77	63.21	13.48	Peak	N	Pass
3**	0.210	36.70	9.77	53.21	16.51	AV	N	Pass
4	1.084	38.57	10.05	56.00	17.43	Peak	N	Pass
4**	1.084	26.09	10.05	46.00	19.91	AV	N	Pass
5	2.318	38.69	10.19	56.00	17.31	Peak	N	Pass
5**	2.318	27.19	10.19	46.00	18.81	AV	N	Pass
6	11.136	41.75	10.36	60.00	18.25	Peak	N	Pass
6**	11.136	30.55	10.36	50.00	19.45	AV	N	Pass

A.6 Radiated Emission

Note¹: The symbol of “--” in the table which means not application.

Note²: For the test data above 1 GHz, According the ANSI C63.10-2013, where limits are specified for both average and peak (or quasi-peak) detector functions, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement.


Note³: The low frequency, which started from 9 kHz to 30 MHz, was pre-scanned and the result which was 20 dB lower than the limit line per 15.31(o) was not reported.

Note⁴: The EUT is working in the Normal link mode below 1 GHz. All modes have been tested and normal link mode is worst.

Test Data and Plots

30 MHz to 1 GHz, ANT H


RE Test case_FCC Part 15C_FCC Part 15C-30MHz-1GHz



No.	Frequency (MHz)	Results (dBUV/m)	Factor (dB)	Limit (dBUV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	161.969	22.88	-25.32	43.5	20.62	Peak	115.00	200	Horizontal	Pass
2	199.314	30.16	-28.70	43.5	13.34	Peak	84.00	100	Horizontal	Pass
3	211.827	30.84	-28.89	43.5	12.66	Peak	96.00	100	Horizontal	Pass
4	335.938	29.57	-24.05	46.0	16.43	Peak	268.00	100	Horizontal	Pass
5	362.419	29.67	-23.10	46.0	16.33	Peak	96.00	100	Horizontal	Pass
6	890.972	32.42	-10.56	46.0	13.58	Peak	183.00	100	Horizontal	Pass

30 MHz to 1 GHz, ANT V

RE Test case_FCC Part 15C_FCC Part 15C-30MHz-1GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	58.955	21.44	-27.10	40.0	18.56	Peak	305.00	100	Vertical	Pass
2	74.038	22.95	-29.18	40.0	17.05	Peak	353.00	100	Vertical	Pass
3	130.298	26.04	-27.41	43.5	17.46	Peak	101.00	100	Vertical	Pass
4	194.852	27.62	-28.53	43.5	15.88	Peak	156.00	100	Vertical	Pass
5	329.682	26.51	-23.32	46.0	19.49	Peak	122.00	200	Vertical	Pass
6	891.020	30.59	-10.55	46.0	15.41	Peak	233.00	100	Vertical	Pass

Note ¹: The marked spikes near 2400 MHz with circle should be ignored because they are Fundamental signal.

Note ²: The spurious above 18G is noise only, do not show on the report.

Note ³: All antenna were pre tested, but only the worst case has been reported in this report.

SISO-Antenna 1

1 GHz to 18 GHz, ANT H 802.11b Low Channel

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1437.600	45.60	74.0	28.40	Peak	151.00	200	Horizontal	Pass
1**	1437.600	37.34	54.0	16.66	AV	151.00	200	Horizontal	Pass
2	2413.400	97.36	74.0	-23.36	Peak	205.00	200	Horizontal	N/A
2**	2413.400	94.50	54.0	-40.50	AV	205.00	200	Horizontal	N/A
3	4824.200	53.17	74.0	20.83	Peak	68.00	150	Horizontal	Pass
3**	4824.200	50.40	54.0	3.60	AV	68.00	150	Horizontal	Pass
4	6996.600	54.95	74.0	19.05	Peak	55.00	300	Horizontal	Pass
4**	6996.600	46.03	54.0	7.97	AV	55.00	300	Horizontal	Pass
5	11922.862	52.46	74.0	21.54	Peak	0.00	400	Horizontal	Pass
5**	11922.862	42.79	54.0	11.21	AV	0.00	400	Horizontal	Pass
6	16112.625	54.77	74.0	19.23	Peak	343.00	300	Horizontal	Pass
6**	16112.625	45.27	54.0	8.73	AV	343.00	300	Horizontal	Pass

1 GHz to 18 GHz, ANT V 802.11b Low Channel

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1329.800	44.71	74.0	29.29	Peak	144.00	200	Vertical	Pass
1**	1329.800	33.29	54.0	20.71	AV	144.00	200	Vertical	Pass
2	2413.500	101.67	74.0	-27.67	Peak	349.00	100	Vertical	N/A
2**	2413.500	98.70	54.0	-44.70	AV	349.00	100	Vertical	N/A
3	4824.200	54.52	74.0	19.48	Peak	350.00	150	Vertical	Pass
3**	4824.200	50.81	54.0	3.19	AV	350.00	150	Vertical	Pass
4	6976.800	55.40	74.0	18.60	Peak	299.00	300	Vertical	Pass
4**	6976.800	46.28	54.0	7.72	AV	299.00	300	Vertical	Pass
5	12394.937	51.99	74.0	22.01	Peak	118.00	300	Vertical	Pass
5**	12394.937	43.30	54.0	10.70	AV	118.00	300	Vertical	Pass
6	16135.200	55.10	74.0	18.90	Peak	68.00	300	Vertical	Pass
6**	16135.200	45.77	54.0	8.23	AV	68.00	300	Vertical	Pass

1 GHz to 18 GHz, ANT H 802.11b Middle Channel

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1437.000	45.49	74.0	28.51	Peak	183.00	100	Horizontal	Pass
1**	1437.000	36.92	54.0	17.08	AV	183.00	100	Horizontal	Pass
2	2435.600	95.18	74.0	-21.18	Peak	196.00	150	Horizontal	N/A
2**	2435.600	92.27	54.0	-38.27	AV	196.00	150	Horizontal	N/A
3	4873.600	52.54	74.0	21.46	Peak	121.00	200	Horizontal	Pass
3**	4873.600	45.83	54.0	8.17	AV	121.00	200	Horizontal	Pass
4	4874.400	51.76	74.0	22.24	Peak	76.00	150	Horizontal	Pass
4**	4874.400	48.76	54.0	5.24	AV	76.00	150	Horizontal	Pass
5	12831.112	51.81	74.0	22.19	Peak	10.00	400	Horizontal	Pass
5**	12831.112	44.07	54.0	9.93	AV	10.00	400	Horizontal	Pass
6	16069.576	54.79	74.0	19.21	Peak	206.00	200	Horizontal	Pass
6**	16069.576	44.81	54.0	9.19	AV	206.00	200	Horizontal	Pass

1 GHz to 18 GHz, ANT V 802.11b Middle Channel

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1328.600	46.16	74.0	27.84	Peak	82.00	300	Vertical	Pass
1**	1328.600	34.09	54.0	19.91	AV	82.00	300	Vertical	Pass
2	2435.500	101.04	74.0	-27.04	Peak	349.00	100	Vertical	N/A
2**	2435.500	98.05	54.0	-44.05	AV	349.00	100	Vertical	N/A
3	4873.800	54.37	74.0	19.63	Peak	0.00	100	Vertical	Pass
3**	4873.800	49.20	54.0	4.80	AV	0.00	100	Vertical	Pass
4	4874.000	53.71	74.0	20.29	Peak	328.00	150	Vertical	Pass
4**	4874.000	50.33	54.0	3.67	AV	328.00	150	Vertical	Pass
5	11330.326	52.66	74.0	21.34	Peak	51.00	100	Vertical	Pass
5**	11330.326	43.38	54.0	10.62	AV	51.00	100	Vertical	Pass
6	17443.762	55.01	74.0	18.99	Peak	52.00	400	Vertical	Pass
6**	17443.762	46.31	54.0	7.69	AV	52.00	400	Vertical	Pass

1 GHz to 18 GHz, ANT H 802.11b High Channel

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1437.400	44.63	74.0	29.37	Peak	182.00	100	Horizontal	Pass
1**	1437.400	37.25	54.0	16.75	AV	182.00	100	Horizontal	Pass
2	2463.400	94.52	74.0	-20.52	Peak	196.00	200	Horizontal	N/A
2**	2463.400	91.61	54.0	-37.61	AV	196.00	200	Horizontal	N/A
3	4924.200	51.66	74.0	22.34	Peak	89.00	150	Horizontal	Pass
3**	4924.200	49.02	54.0	4.98	AV	89.00	150	Horizontal	Pass
4	6996.800	54.62	74.0	19.38	Peak	89.00	400	Horizontal	Pass
4**	6996.800	45.79	54.0	8.21	AV	89.00	400	Horizontal	Pass
5	10926.387	52.36	74.0	21.64	Peak	360.00	300	Horizontal	Pass
5**	10926.387	43.01	54.0	10.99	AV	360.00	300	Horizontal	Pass
6	17317.239	55.14	74.0	18.86	Peak	30.00	100	Horizontal	Pass
6**	17317.239	45.41	54.0	8.59	AV	30.00	100	Horizontal	Pass

1 GHz to 18 GHz, ANT V 802.11b High Channel

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1166.000	46.45	74.0	27.55	Peak	93.00	200	Vertical	Pass
1**	1166.000	32.19	54.0	21.81	AV	93.00	200	Vertical	Pass
2	2463.500	99.88	74.0	-25.88	Peak	347.00	100	Vertical	N/A
2**	2463.500	96.95	54.0	-42.95	AV	347.00	100	Vertical	N/A
3	4924.000	53.92	74.0	20.08	Peak	360.00	200	Vertical	Pass
3**	4924.000	49.34	54.0	4.66	AV	360.00	200	Vertical	Pass
4	4924.200	53.47	74.0	20.53	Peak	351.00	150	Vertical	Pass
4**	4924.200	50.16	54.0	3.84	AV	351.00	150	Vertical	Pass
5	11497.650	51.63	74.0	22.37	Peak	106.00	100	Vertical	Pass
5**	11497.650	42.38	54.0	11.62	AV	106.00	100	Vertical	Pass
6	17466.337	55.69	74.0	18.31	Peak	29.00	300	Vertical	Pass
6**	17466.337	44.99	54.0	9.01	AV	29.00	300	Vertical	Pass

1 GHz to 18 GHz, ANT H 802.11g Low Channel

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1440.700	45.53	74.0	28.47	Peak	134.00	200	Horizontal	Pass
1**	1440.700	38.36	54.0	15.64	AV	134.00	200	Horizontal	Pass
2	2413.900	102.39	74.0	-28.39	Peak	89.00	150	Horizontal	N/A
2**	2413.900	95.08	54.0	-41.08	AV	89.00	150	Horizontal	N/A
3	4823.200	51.30	74.0	22.70	Peak	23.00	150	Horizontal	Pass
3**	4823.200	47.40	54.0	6.60	AV	23.00	150	Horizontal	Pass
4	4830.600	54.66	74.0	19.34	Peak	189.00	200	Horizontal	Pass
4**	4830.600	43.86	54.0	10.14	AV	189.00	200	Horizontal	Pass
5	12723.550	51.89	74.0	22.11	Peak	4.00	200	Horizontal	Pass
5**	12723.550	41.99	54.0	12.01	AV	4.00	200	Horizontal	Pass
6	17423.813	55.62	74.0	18.38	Peak	294.00	150	Horizontal	Pass
6**	17423.813	46.87	54.0	7.13	AV	294.00	150	Horizontal	Pass

1 GHz to 18 GHz, ANT V 802.11g Low Channel

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1440.400	44.83	74.0	29.17	Peak	181.00	100	Vertical	Pass
1**	1440.400	35.37	54.0	18.63	AV	181.00	100	Vertical	Pass
2	2413.500	107.56	74.0	-33.56	Peak	347.00	100	Vertical	N/A
2**	2413.500	99.92	54.0	-45.92	AV	347.00	100	Vertical	N/A
3	4820.600	56.77	74.0	17.23	Peak	297.00	150	Vertical	Pass
3**	4820.600	44.95	54.0	9.05	AV	297.00	150	Vertical	Pass
4	4820.800	53.01	74.0	20.99	Peak	297.00	150	Vertical	Pass
4**	4820.800	47.84	54.0	6.16	AV	297.00	150	Vertical	Pass
5	12820.612	51.90	74.0	22.10	Peak	174.00	100	Vertical	Pass
5**	12820.612	42.14	54.0	11.86	AV	174.00	100	Vertical	Pass
6	15517.013	54.90	74.0	19.10	Peak	149.00	100	Vertical	Pass
6**	15517.013	44.62	54.0	9.38	AV	149.00	100	Vertical	Pass

1 GHz to 18 GHz, ANT H 802.11g Middle Channel

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1441.800	45.98	74.0	28.02	Peak	125.00	100	Horizontal	Pass
1**	1441.800	37.82	54.0	16.18	AV	125.00	100	Horizontal	Pass
2	2434.800	102.98	74.0	-28.98	Peak	86.00	150	Horizontal	N/A
2**	2434.800	95.56	54.0	-41.56	AV	86.00	150	Horizontal	N/A
3	4871.000	53.52	74.0	20.48	Peak	214.00	200	Horizontal	Pass
3**	4871.000	44.68	54.0	9.32	AV	214.00	200	Horizontal	Pass
4	6808.200	54.95	74.0	19.05	Peak	11.00	100	Horizontal	Pass
4**	6808.200	45.38	54.0	8.62	AV	11.00	100	Horizontal	Pass
5	11769.625	52.03	74.0	21.97	Peak	259.00	400	Horizontal	Pass
5**	11769.625	42.20	54.0	11.80	AV	259.00	400	Horizontal	Pass
6	17450.588	54.73	74.0	19.27	Peak	97.00	100	Horizontal	Pass
6**	17450.588	45.48	54.0	8.52	AV	97.00	100	Horizontal	Pass

1 GHz to 18 GHz, ANT V 802.11g Middle Channel

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2435.500	106.78	74.0	-32.78	Peak	334.00	200	Vertical	N/A
1**	2435.500	99.43	54.0	-45.43	AV	334.00	200	Vertical	N/A
2	4875.400	52.48	74.0	21.52	Peak	11.00	150	Vertical	Pass
2**	4875.400	46.35	54.0	7.65	AV	11.00	150	Vertical	Pass
3	4882.200	54.19	74.0	19.81	Peak	346.00	200	Vertical	Pass
3**	4882.200	44.19	54.0	9.81	AV	346.00	200	Vertical	Pass
4	5325.400	56.42	74.0	17.58	Peak	89.00	200	Vertical	Pass
4**	5325.400	45.91	54.0	8.09	AV	89.00	200	Vertical	Pass
5	10923.800	51.86	74.0	22.14	Peak	62.00	100	Vertical	Pass
5**	10923.800	43.54	54.0	10.46	AV	62.00	100	Vertical	Pass
6	17457.938	55.17	74.0	18.83	Peak	0.00	200	Vertical	Pass
6**	17457.938	46.05	54.0	7.95	AV	0.00	200	Vertical	Pass

1 GHz to 18 GHz, ANT H 802.11g High Channel

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1442.400	45.51	74.0	28.49	Peak	139.00	300	Horizontal	Pass
1**	1442.400	39.01	54.0	14.99	AV	139.00	300	Horizontal	Pass
2	2467.200	101.40	74.0	-27.40	Peak	349.00	150	Horizontal	N/A
2**	2467.200	93.60	54.0	-39.60	AV	349.00	150	Horizontal	N/A
3	4922.800	51.66	74.0	22.34	Peak	186.00	100	Horizontal	Pass
3**	4922.800	42.49	54.0	11.51	AV	186.00	100	Horizontal	Pass
4	6999.600	54.40	74.0	19.60	Peak	353.00	400	Horizontal	Pass
4**	6999.600	45.95	54.0	8.05	AV	353.00	400	Horizontal	Pass
5	11769.625	52.20	74.0	21.80	Peak	111.00	300	Horizontal	Pass
5**	11769.625	42.97	54.0	11.03	AV	111.00	300	Horizontal	Pass
6	17431.425	55.50	74.0	18.50	Peak	46.00	300	Horizontal	Pass
6**	17431.425	45.99	54.0	8.01	AV	46.00	300	Horizontal	Pass

1 GHz to 18 GHz, ANT V 802.11g High Channel

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1439.200	44.82	74.0	29.18	Peak	198.00	200	Vertical	Pass
1**	1439.200	35.42	54.0	18.58	AV	198.00	200	Vertical	Pass
2	2459.900	107.42	74.0	-33.42	Peak	355.00	200	Vertical	N/A
2**	2459.900	99.75	54.0	-45.75	AV	355.00	200	Vertical	N/A
3	4919.200	51.96	74.0	22.04	Peak	322.00	150	Vertical	Pass
3**	4919.200	45.53	54.0	8.47	AV	322.00	150	Vertical	Pass
4	4923.800	52.75	74.0	21.25	Peak	360.00	200	Vertical	Pass
4**	4923.800	44.94	54.0	9.06	AV	360.00	200	Vertical	Pass
5	12703.425	51.99	74.0	22.01	Peak	215.00	100	Vertical	Pass
5**	12703.425	42.09	54.0	11.91	AV	215.00	100	Vertical	Pass
6	17472.375	54.76	74.0	19.24	Peak	172.00	300	Vertical	Pass
6**	17472.375	45.92	54.0	8.08	AV	172.00	300	Vertical	Pass

1 GHz to 18 GHz, ANT H 802.11n20 Low Channel

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1442.900	45.38	74.0	28.62	Peak	155.00	100	Horizontal	Pass
1**	1442.900	37.68	54.0	16.32	AV	155.00	100	Horizontal	Pass
2	2415.100	102.06	74.0	-28.06	Peak	93.00	150	Horizontal	N/A
2**	2415.100	94.84	54.0	-40.84	AV	93.00	150	Horizontal	N/A
3	4823.000	50.89	74.0	23.11	Peak	360.00	150	Horizontal	Pass
3**	4823.000	46.54	54.0	7.46	AV	360.00	150	Horizontal	Pass
4	4823.200	53.48	74.0	20.52	Peak	63.00	200	Horizontal	Pass
4**	4823.200	44.40	54.0	9.60	AV	63.00	200	Horizontal	Pass
5	11761.287	51.98	74.0	22.02	Peak	148.00	100	Horizontal	Pass
5**	11761.287	42.45	54.0	11.55	AV	148.00	100	Horizontal	Pass
6	17428.537	56.12	74.0	17.88	Peak	338.00	400	Horizontal	Pass
6**	17428.537	46.37	54.0	7.63	AV	338.00	400	Horizontal	Pass

1 GHz to 18 GHz, ANT V 802.11n20 Low Channel

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1441.600	45.33	74.0	28.67	Peak	182.00	400	Vertical	Pass
1**	1441.600	37.87	54.0	16.13	AV	182.00	400	Vertical	Pass
2	2413.400	108.06	74.0	-34.06	Peak	360.00	100	Vertical	N/A
2**	2413.400	100.97	54.0	-46.97	AV	360.00	100	Vertical	N/A
3	4823.000	54.72	74.0	19.28	Peak	322.00	150	Vertical	Pass
3**	4823.000	47.14	54.0	6.86	AV	322.00	150	Vertical	Pass
4	6976.200	54.84	74.0	19.16	Peak	55.00	200	Vertical	Pass
4**	6976.200	46.45	54.0	7.55	AV	55.00	200	Vertical	Pass
5	11815.338	51.80	74.0	22.20	Peak	0.00	400	Vertical	Pass
5**	11815.338	43.60	54.0	10.40	AV	0.00	400	Vertical	Pass
6	17470.276	54.97	74.0	19.03	Peak	262.00	100	Vertical	Pass
6**	17470.276	45.65	54.0	8.35	AV	262.00	100	Vertical	Pass

1 GHz to 18 GHz, ANT H 802.11n20 Middle Channel

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1436.600	45.58	74.0	28.42	Peak	182.00	400	Horizontal	Pass
1**	1436.600	36.87	54.0	17.13	AV	182.00	400	Horizontal	Pass
2	2434.700	102.62	74.0	-28.62	Peak	98.00	100	Horizontal	N/A
2**	2434.700	94.94	54.0	-40.94	AV	98.00	100	Horizontal	N/A
3	4877.400	52.70	74.0	21.30	Peak	185.00	100	Horizontal	Pass
3**	4877.400	43.71	54.0	10.29	AV	185.00	100	Horizontal	Pass
4	6807.600	55.33	74.0	18.67	Peak	282.00	200	Horizontal	Pass
4**	6807.600	45.69	54.0	8.31	AV	282.00	200	Horizontal	Pass
5	11815.338	52.14	74.0	21.86	Peak	215.00	400	Horizontal	Pass
5**	11815.338	42.44	54.0	11.56	AV	215.00	400	Horizontal	Pass
6	17432.214	55.20	74.0	18.80	Peak	0.00	200	Horizontal	Pass
6**	17432.214	46.29	54.0	7.71	AV	0.00	200	Horizontal	Pass

1 GHz to 18 GHz, ANT V 802.11n20 Middle Channel

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1329.500	44.62	74.0	29.38	Peak	84.00	400	Vertical	Pass
1**	1329.500	32.21	54.0	21.79	AV	84.00	400	Vertical	Pass
2	2434.700	106.56	74.0	-32.56	Peak	338.00	200	Vertical	N/A
2**	2434.700	99.33	54.0	-45.33	AV	338.00	200	Vertical	N/A
3	4873.200	53.22	74.0	20.78	Peak	323.00	150	Vertical	Pass
3**	4873.200	45.84	54.0	8.16	AV	323.00	150	Vertical	Pass
4	6807.000	55.63	74.0	18.37	Peak	109.00	300	Vertical	Pass
4**	6807.000	47.32	54.0	6.68	AV	109.00	300	Vertical	Pass
5	11932.349	51.89	74.0	22.11	Peak	163.00	400	Vertical	Pass
5**	11932.349	42.80	54.0	11.20	AV	163.00	400	Vertical	Pass
6	17414.625	55.21	74.0	18.79	Peak	0.00	400	Vertical	Pass
6**	17414.625	45.91	54.0	8.09	AV	0.00	400	Vertical	Pass

1 GHz to 18 GHz, ANT H 802.11n20 High Channel

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1442.400	45.51	74.0	28.49	Peak	139.00	100	Horizontal	Pass
1**	1442.400	39.01	54.0	14.99	AV	139.00	100	Horizontal	Pass
2	2467.200	101.40	74.0	-27.40	Peak	349.00	100	Horizontal	N/A
2**	2467.200	93.60	54.0	-39.60	AV	349.00	100	Horizontal	N/A
3	4922.800	51.66	74.0	22.34	Peak	186.00	200	Horizontal	Pass
3**	4922.800	42.49	54.0	11.51	AV	186.00	200	Horizontal	Pass
4	6999.600	54.40	74.0	19.60	Peak	353.00	200	Horizontal	Pass
4**	6999.600	45.95	54.0	8.05	AV	353.00	200	Horizontal	Pass
5	11769.625	52.20	74.0	21.80	Peak	111.00	100	Horizontal	Pass
5**	11769.625	42.97	54.0	11.03	AV	111.00	100	Horizontal	Pass
6	17431.425	55.50	74.0	18.50	Peak	46.00	400	Horizontal	Pass
6**	17431.425	45.99	54.0	8.01	AV	46.00	400	Horizontal	Pass

1 GHz to 18 GHz, ANT V 802.11n20 High Channel

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1439.200	44.82	74.0	29.18	Peak	198.00	400	Vertical	Pass
1**	1439.200	35.42	54.0	18.58	AV	198.00	400	Vertical	Pass
2	2459.900	107.42	74.0	-33.42	Peak	355.00	100	Vertical	N/A
2**	2459.900	99.75	54.0	-45.75	AV	355.00	100	Vertical	N/A
3	4919.200	51.96	74.0	22.04	Peak	322.00	150	Vertical	Pass
3**	4919.200	45.53	54.0	8.47	AV	322.00	150	Vertical	Pass
4	6818.000	54.71	74.0	19.29	Peak	201.00	200	Vertical	Pass
4**	6818.000	44.98	54.0	9.02	AV	201.00	200	Vertical	Pass
5	12703.425	51.99	74.0	22.01	Peak	215.00	400	Vertical	Pass
5**	12703.425	42.09	54.0	11.91	AV	215.00	400	Vertical	Pass
6	17472.375	54.76	74.0	19.24	Peak	172.00	400	Vertical	Pass
6**	17472.375	45.92	54.0	8.08	AV	172.00	400	Vertical	Pass

1 GHz to 18 GHz, ANT H 802.11n40 Low Channel

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1439.400	45.54	74.0	28.46	Peak	329.00	300	Horizontal	Pass
1**	1439.400	36.91	54.0	17.09	AV	329.00	300	Horizontal	Pass
2	2433.100	99.41	74.0	-25.41	Peak	106.00	200	Horizontal	N/A
2**	2433.100	91.92	54.0	-37.92	AV	106.00	200	Horizontal	N/A
3	4843.000	48.60	74.0	25.40	Peak	82.00	150	Horizontal	Pass
3**	4843.000	45.41	54.0	8.59	AV	82.00	150	Horizontal	Pass
4	6803.400	54.97	74.0	19.03	Peak	265.00	300	Horizontal	Pass
4**	6803.400	45.46	54.0	8.54	AV	265.00	300	Horizontal	Pass
5	11319.975	52.23	74.0	21.77	Peak	321.00	400	Horizontal	Pass
5**	11319.975	41.83	54.0	12.17	AV	321.00	400	Horizontal	Pass
6	15335.363	55.08	74.0	18.92	Peak	160.00	100	Horizontal	Pass
6**	15335.363	44.72	54.0	9.28	AV	160.00	100	Horizontal	Pass

1 GHz to 18 GHz, ANT V 802.11n40 Low Channel

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1441.900	43.84	74.0	30.16	Peak	310.00	200	Vertical	Pass
1**	1441.900	34.77	54.0	19.23	AV	310.00	200	Vertical	Pass
2	2412.800	104.71	74.0	-30.71	Peak	349.00	200	Vertical	N/A
2**	2412.800	96.33	54.0	-42.33	AV	349.00	200	Vertical	N/A
3	4826.800	52.83	74.0	21.17	Peak	291.00	150	Vertical	Pass
3**	4826.800	41.99	54.0	12.01	AV	291.00	150	Vertical	Pass
4	6792.800	54.80	74.0	19.20	Peak	333.00	200	Vertical	Pass
4**	6792.800	45.52	54.0	8.48	AV	333.00	200	Vertical	Pass
5	12417.651	51.79	74.0	22.21	Peak	107.00	400	Vertical	Pass
5**	12417.651	41.88	54.0	12.12	AV	107.00	400	Vertical	Pass
6	17467.650	54.99	74.0	19.01	Peak	163.00	400	Vertical	Pass
6**	17467.650	45.67	54.0	8.33	AV	163.00	400	Vertical	Pass

1 GHz to 18 GHz, ANT H 802.11n40 Middle Channel

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1443.800	45.92	74.0	28.08	Peak	162.00	100	Horizontal	Pass
1**	1443.800	37.73	54.0	16.27	AV	162.00	100	Horizontal	Pass
2	2434.900	100.51	74.0	-26.51	Peak	102.00	200	Horizontal	N/A
2**	2434.900	92.45	54.0	-38.45	AV	102.00	200	Horizontal	N/A
3	4791.600	51.60	74.0	22.40	Peak	4.00	100	Horizontal	Pass
3**	4791.600	41.80	54.0	12.20	AV	4.00	100	Horizontal	Pass
4	6978.600	54.99	74.0	19.01	Peak	360.00	100	Horizontal	Pass
4**	6978.600	46.93	54.0	7.07	AV	360.00	100	Horizontal	Pass
5	11801.250	51.96	74.0	22.04	Peak	325.00	200	Horizontal	Pass
5**	11801.250	44.02	54.0	9.98	AV	325.00	200	Horizontal	Pass
6	17404.387	55.02	74.0	18.98	Peak	20.00	400	Horizontal	Pass
6**	17404.387	45.91	54.0	8.09	AV	20.00	400	Horizontal	Pass

1 GHz to 18 GHz, ANT V 802.11n40 Middle Channel

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1442.600	43.64	74.0	30.36	Peak	166.00	300	Vertical	Pass
1**	1442.600	35.30	54.0	18.70	AV	166.00	300	Vertical	Pass
2	2429.100	104.37	74.0	-30.37	Peak	360.00	100	Vertical	N/A
2**	2429.100	96.99	54.0	-42.99	AV	360.00	100	Vertical	N/A
3	4871.000	52.59	74.0	21.41	Peak	321.00	100	Vertical	Pass
3**	4871.000	44.25	54.0	9.75	AV	321.00	100	Vertical	Pass
4	4876.000	50.13	74.0	23.87	Peak	292.00	150	Vertical	Pass
4**	4876.000	45.53	54.0	8.47	AV	292.00	150	Vertical	Pass
5	11939.537	51.99	74.0	22.01	Peak	19.00	300	Vertical	Pass
5**	11939.537	42.99	54.0	11.01	AV	19.00	300	Vertical	Pass
6	17435.099	55.41	74.0	18.59	Peak	88.00	200	Vertical	Pass
6**	17435.099	46.29	54.0	7.71	AV	88.00	200	Vertical	Pass

1 GHz to 18 GHz, ANT H 802.11n40 High Channel

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1440.900	46.10	74.0	27.90	Peak	157.00	200	Horizontal	Pass
1**	1440.900	38.71	54.0	15.29	AV	157.00	200	Horizontal	Pass
2	2447.200	99.48	74.0	-25.48	Peak	149.00	150	Horizontal	N/A
2**	2447.200	92.75	54.0	-38.75	AV	149.00	150	Horizontal	N/A
3	4799.400	51.21	74.0	22.79	Peak	335.00	200	Horizontal	Pass
3**	4799.400	41.67	54.0	12.33	AV	335.00	200	Horizontal	Pass
4	6804.600	54.68	74.0	19.32	Peak	294.00	300	Horizontal	Pass
4**	6804.600	45.71	54.0	8.29	AV	294.00	300	Horizontal	Pass
5	12395.513	51.80	74.0	22.20	Peak	125.00	300	Horizontal	Pass
5**	12395.513	42.36	54.0	11.64	AV	125.00	300	Horizontal	Pass
6	17444.286	55.62	74.0	18.38	Peak	137.00	300	Horizontal	Pass
6**	17444.286	45.92	54.0	8.08	AV	137.00	300	Horizontal	Pass

1 GHz to 18 GHz, ANT V 802.11n40 High Channel

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1444.200	44.12	74.0	29.88	Peak	157.00	200	Vertical	Pass
1**	1444.200	36.48	54.0	17.52	AV	157.00	200	Vertical	Pass
2	2448.000	104.00	74.0	-30.00	Peak	341.00	150	Vertical	N/A
2**	2448.000	96.42	54.0	-42.42	AV	341.00	150	Vertical	N/A
3	4901.400	51.63	74.0	22.37	Peak	360.00	150	Vertical	Pass
3**	4901.400	43.29	54.0	10.71	AV	360.00	150	Vertical	Pass
4	6994.800	55.26	74.0	18.74	Peak	239.00	100	Vertical	Pass
4**	6994.800	45.42	54.0	8.58	AV	239.00	100	Vertical	Pass
5	11777.100	52.13	74.0	21.87	Peak	134.00	400	Vertical	Pass
5**	11777.100	42.89	54.0	11.11	AV	134.00	400	Vertical	Pass
6	17389.687	55.13	74.0	18.87	Peak	210.00	300	Vertical	Pass
6**	17389.687	46.75	54.0	7.25	AV	210.00	300	Vertical	Pass

A.7 Band Edge (Restricted-band band-edge)

Note ¹: The lowest and highest channels are tested to verify the band edge emissions. Please refer to the following the plots for emissions values.

Note ²: The test data all are tested in the vertical and horizontal antenna which the trace is max hold. So these plots have shown the worst case.

Note ³: According the ANSI C63.10-2013, where limits are specified for both average and peak (or quasi-peak) detector functions, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement.

Note ⁴: All antenna were pre tested, but only the worst case has been reported in this report.

Test Data

SISO-Antenna 1

802.11b LOW CHANNEL

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2386.500	57.99	74.0	16.01	Peak	9.00	200	Vertical	Pass
1**	2386.500	46.95	54.0	7.05	AV	9.00	200	Vertical	Pass
2	2389.950	55.49	74.0	18.51	Peak	107.00	150	Vertical	Pass
2**	2389.950	46.49	54.0	7.51	AV	107.00	150	Vertical	Pass

802.11b HIGH CHANNEL

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2483.575	56.55	74.0	17.45	Peak	47.00	100	Vertical	Pass
1**	2483.575	46.82	54.0	7.18	AV	47.00	100	Vertical	Pass
2	2488.915	57.78	74.0	16.22	Peak	62.00	150	Vertical	Pass
2**	2488.915	46.22	54.0	7.78	AV	62.00	150	Vertical	Pass

802.11g LOW CHANNEL

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2389.650	65.89	74.0	8.11	Peak	81.00	100	Vertical	Pass
1**	2389.650	50.40	54.0	3.60	AV	81.00	100	Vertical	Pass
2	2389.950	63.90	74.0	10.10	Peak	56.00	150	Vertical	Pass
2**	2389.950	50.85	54.0	3.15	AV	56.00	150	Vertical	Pass

802.11g HIGH CHANNEL

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2483.515	62.60	74.0	11.40	Peak	360.00	150	Vertical	Pass
1**	2483.515	50.80	54.0	3.20	AV	360.00	150	Vertical	Pass
2	2483.770	63.23	74.0	10.77	Peak	237.00	200	Vertical	Pass
2**	2483.770	50.42	54.0	3.58	AV	237.00	200	Vertical	Pass

802.11n20 LOW CHANNEL

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2389.500	66.12	74.0	7.88	Peak	74.00	200	Vertical	Pass
1**	2389.500	49.49	54.0	4.51	AV	74.00	200	Vertical	Pass
2	2389.950	63.97	74.0	10.03	Peak	77.00	100	Vertical	Pass
2**	2389.950	49.64	54.0	4.36	AV	77.00	100	Vertical	Pass

802.11n20 HIGH CHANNEL

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2483.515	65.13	74.0	8.87	Peak	244.00	150	Vertical	Pass
1**	2483.515	50.83	54.0	3.17	AV	244.00	150	Vertical	Pass
2	2483.740	63.80	74.0	10.20	Peak	258.00	150	Vertical	Pass
2**	2483.740	50.19	54.0	3.81	AV	258.00	150	Vertical	Pass

802.11n40 LOW CHANNEL

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2387.800	64.63	74.0	9.37	Peak	326.00	150	Vertical	Pass
1**	2387.800	50.93	54.0	3.07	AV	326.00	150	Vertical	Pass
2	2389.950	61.79	74.0	12.21	Peak	329.00	150	Vertical	Pass
2**	2389.950	50.38	54.0	3.62	AV	329.00	150	Vertical	Pass

802.11n40 HIGH CHANNEL

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2483.575	62.64	74.0	11.36	Peak	354.00	200	Vertical	Pass
1**	2483.575	49.50	54.0	4.50	AV	354.00	200	Vertical	Pass
2	2483.815	63.24	74.0	10.76	Peak	347.00	150	Vertical	Pass
2**	2483.815	49.78	54.0	4.22	AV	347.00	150	Vertical	Pass
3	2484.745	60.27	74.0	13.73	Peak	360.00	150	Vertical	Pass
3**	2484.745	50.35	54.0	3.65	AV	360.00	150	Vertical	Pass

A.8 Power Spectral Density (PSD)

Note: All antenna were pre tested, but only the worst case has been reported in this report.

SISO-Antenna 1

Test Data

802.11b Mode:

Channel	Spectral power density (dBm/3kHz)	Limit (dBm/3kHz)
Low	-8.83	6.25
Middle	-10.37	6.25
High	-9.56	6.25

802.11g Mode:

Channel	Spectral power density (dBm/3kHz)	Limit (dBm/3kHz)
Low	-11.62	6.25
Middle	-11.57	6.25
High	-11.56	6.25

802.11n-20 MHz Mode:

Channel	Spectral power density (dBm/3kHz)	Limit (dBm/3kHz)
Low	-12.81	8
Middle	-11.47	8
High	-14.31	8

802.11n-40 MHz Mode:

Channel	Spectral power density (dBm/3kHz)	Limit (dBm/3kHz)
Low	-18.51	8
Middle	-13.66	8
High	-19.55	8

Test Plots

802.11b LOW CHANNEL




802.11b MIDDLE CHANNEL




802.11b HIGH CHANNEL




802.11g LOW CHANNEL



802.11g MIDDLE CHANNEL




802.11g HIGH CHANNEL



802.11n-20 MHz LOW CHANNEL




802.11n-20 MHz MIDDLE CHANNEL




802.11n-20 MHz HIGH CHANNEL




802.11n-40 MHz LOW CHANNEL



802.11n-40 MHz MIDDLE CHANNEL



802.11n-40 MHz HIGH CHANNEL



ANNEX B TEST SETUP PHOTOS

Please refer the document “BL-SZ2530227-AR.PDF”.

ANNEX C EUT EXTERNAL PHOTOS

Please refer the document “BL-SZ2530227-AW.PDF”.

ANNEX D EUT INTERNAL PHOTOS

Please refer the document “BL-SZ2530227-AI.PDF”.

Statement

1. The laboratory guarantees the scientificity, accuracy and impartiality of the test, and is responsible for all the information in the report, except the information provided by the customer. The customer is responsible for the impact of the information provided on the validity of the results.
2. The report without China inspection body and laboratory Mandatory Approval (CMA) mark has no effect of proving to the society.
3. For the report with CNAS mark or A2LA mark, the items marked with "☆" are not within the accredited scope.
4. This report is invalid if it is altered, without the signature of the testing and approval personnel, or without the "inspection and testing dedicated stamp" or test report stamp.
5. The test data and results are only valid for the tested samples provided by the customer.
6. This report shall not be partially reproduced without the written permission of the laboratory.
7. Any objection shall be raised to the laboratory within 30 days after receiving the report.

--END OF REPORT--