

RF EXPOSURE REPORT  
for  
**Hunan Keyshare Information Technology Co., Ltd**  
**Remote control**  
Model Number: **GLINT 2.0**

FCC ID: **2AE40GLINT2**

Prepared for : **Hunan Keyshare Information Technology Co., Ltd**  
Room 707-712,7/F,Headquarters,Changsha CEC Software Park,No.39  
Jianshan Road,High-Tech Industrial Eataste,Yuelu District, Changsha,  
Address : Hunan, P.R.China

Prepared by : Shenzhen BCTC Technology Co., Ltd.  
Address : No.101,Yousong Road, Longhua New District,  
Shenzhen,China

# 1. RF EXPOSURE EVALUATION

Frequency	Maximum Conducted Output Power(AV)		Maximum Conducted Output Power	
	ANT1	ANT2	ANT1	ANT2
(MHz)	(dBm)		(mW)	
2404	8.50	7.89	7.08	6.15
2440	8.38	7.78	6.89	6.00
2480	8.45	7.65	7.00	5.82

## Test Result of RF Exposure Evaluation

According to the KDB-447498 D01 V05, FCC 47CFR § 2.1093 the following RF exposure evaluation shall to demonstrate RF exposure compliance.

[(max. power of channel, including tune-up tolerance, mW) / (min. test separation distance,mm)]

\* [  $\sqrt{f(\text{GHz})}$  ]

	Target power W/ tolerance (dBm)	Max tune up power tolerance (dBm)	Maximum Output Power: mW	Separation distance mm	RF exposure
2404	8.0 ±1.0	9.0	7.94	5	2.46

The Max RF exposure is 2.47.

Threshold at which no SAR required is  $\leq 3.0$  for 1-g SAR, Separation distance is 5mm.

### Conclusion:

So no SAR is required.