SAR Test Report

Report No.: AGC00069150808FH01

FCC ID : 2AE56A6

APPLICATION PURPOSE: Original Equipment

PRODUCT DESIGNATION: Smart Phone

BRAND NAME : KENXINDA

MODEL NAME : A6

CLIENT: KENXINDA TECHNOLOGY CO., LIMITED

DATE OF ISSUE : Sep. 7,2015

IEEE Std. 1528:2003

STANDARD(S): IEEE Std. 1528a:2005 FCC 47CFR § 2.1093

IEEE/ANSI C95.1:1992

REPORT VERSION: V1.0

Attestation of Global Compliance (Shenzhen) Co., Ltd.

CAUTION:

This report shall not be reproduced except in full without the written permission of the test laboratory and shall not be quoted out of context.



Page 2 of 85

Report Revise Record

Report Version	Revise Time	Issued Date	Valid Version	Notes
V1.0	/	Sep. 7,2015	Valid	Original Report

Page 3 of 85

	٦	Test Report Certification
Applicant Name	:	KENXINDA TECHNOLOGY CO., LIMITED
Applicant Address	:	UNIT B 13/F PRAT COMMERCIAL BUILDING 17-19 PRAT AVENUE TSIMSHATSUI KL HONGKONG
Manufacturer Name	:	SHENZHEN KENXINDA TECHNOLOGY CO., LTD. (BAO'AN BRANCH)
Manufacturer Address	:	1-6 Floor, No.105 Work Shop & 1-5 Floor, No.104 Work Shop, Xinweihuaning Road, Dalang Community, Dalang Street, Baoán District, Shenzhen, P.R.C
Product Designation	:	Smart Phone
Brand Name	:	KENXINDA
Model Name	:	A6
Different Description		N/A
EUT Voltage	:	DC3.7V by battery
Applicable Standard	:	IEEE Std. 1528:2003 IEEE Std. 1528a:2005 FCC 47CFR § 2.1093 IEEE/ANSI C95.1:1992
Test Date	:	Aug. 26,2015 to Aug. 29,2015
Performed Location		Attestation of Global Compliance(Shenzhen) Co., Ltd.
		2 F, Building 2, No.1-No.4, Chaxi Sanwei Technical Industrial Park, Gushu, Xixiang Street, Bao'an District, Shenzhen, China
Report Template		AGCRT-US-3G3/SAR (2015-05-01)

	Bobby Wang	
Tested By	Bobby wang(Wang Zhicheng)	Sep. 7,2015
Checked By	Angola li	
	Angela Li(Li Jiao)	Sep. 7,2015
Authorized By	solga slong	
	Solger Zhang(Zhang Hongyi) Authorized Officer	Sep. 7,2015

Page 4 of 85

TABLE OF CONTENTS

1. SUMMARY OF MAXIMUM SAR VALUE	5
2. GENERAL INFORMATION	6
2.1. EUT DESCRIPTION	6
3. SAR MEASUREMENT SYSTEM	8
3.1. THE DASY5 SYSTEM USED FOR PERFORMING COMPLIANCE TESTS CONSISTS OF FOLLOWING ITEMS	9 9 10
3.5. LIGHT BEAM UNIT	11 11
4. SAR MEASUREMENT PROCEDURE	13
4.1. SPECIFIC ABSORPTION RATE (SAR) 4.2. SAR MEASUREMENT PROCEDURE 4.3. RF EXPOSURE CONDITIONS	14
5. TISSUE SIMULATING LIQUID	18
5.1. THE COMPOSITION OF THE TISSUE SIMULATING LIQUID	18
6. SAR SYSTEM CHECK PROCEDURE	21
6.1. SAR SYSTEM CHECK PROCEDURES	
7. EUT TEST POSITION	24
7.1. DEFINE TWO IMAGINARY LINES ON THE HANDSET	25 25
8. SAR EXPOSURE LIMITS	27
9. TEST EQUIPMENT LIST	28
10. MEASUREMENT UNCERTAINTY	29
11. CONDUCTED POWER MEASUREMENT	32
12. TEST RESULTS	40
12.1. SAR TEST RESULTS SUMMARY	40
APPENDIX A. SAR SYSTEM CHECK DATA	52
APPENDIX B. SAR MEASUREMENT DATA	58
APPENDIX C. TEST SETUP PHOTOGRAPHS & EUT PHOTOGRAPHS	85
APPENDIX D. CALIBRATION DATA	85

Page 5 of 85

1. SUMMARY OF MAXIMUM SAR VALUE

The maximum results of Specific Absorption Rate (SAR) found during testing for EUT are as follows:

Francisco Pond	Highest Reported 1g-SAR(W/Kg)			
Frequency Band	Head	Body-worn(with 10mm separation)		
GSM 850	0.057	0.233		
PCS 1900	0.452	0.695		
UMTS Band II	0.253	0.940		
UMTS Band V	0.026	0.125		
WIFI 2.4G	0.160	0.183		
Simultaneous Reported SAR	1.123			

This device is compliance with Specific Absorption Rate (SAR) for general population/uncontrolled exposure limits (1.6W/Kg) specified in IEEE Std. 1528:2003; IEEE1528a-2005;FCC 47CFR § 2.1093; IEEE/ANSI C95.1:1992 and the following specific FCC Test Procedures:

- KDB 447498 D01 General RF Exposure Guidance v05r02
- KDB 648474 D04 Handset SAR v01r02
- KDB 865664 D01 SAR measurement 100 MHz to 6 GHz v01r04
- KDB 941225 D01 3G SAR Procedures v03
- KDB 941225 D06 Hot Spot SAR v02
- KDB 248227 D01 802.11 Wi-Fi SAR v02r01

Page 6 of 85

2. GENERAL INFORMATION

2.1. EUT Description

General Information			
Product Designation	Smart Phone		
Test Model	A6		
Hardware Version	M820_V7.1SX		
Software Version	ALPS.KK1.MP1.V2.22		
IMEI 1	864120021083705		
IMEI 2	864120021114005		
Device Category	Portable		
RF Exposure Environment	Uncontrolled		
Antenna Type	Internal		
GSM and GPRS			
Support Band	☑GSM 850 ☑PCS 1900 ☑GSM 900 ☑DCS 1800		
GPRS Type	Class B		
GPRS Class	Class 12(1Tx+4Rx, 2Tx+3Rx, 3Tx+2Rx, 4Tx+1Rx)		
TX Frequency Range	GSM 850 : 820-850MHz;; PCS 1900: 1850-1910MHz;		
RX Frequency Range	GSM 850 : 869~894MHz; PCS 1900: 1930~1990MHz		
Release Version	R99		
Type of modulation	GMSK for GSM/GPRS;		
Antenna Gain	-1.0dBi		
Max. Average Power (Max. Peak Power)	GSM850: 31.21dBm(32.53dBm) ;PCS1900: 28.22dBm(29.56dBm)		
WCDMA			
Support Band	☑UMTS FDD Band II ☑UMTS FDD Band V ☐UMTS FDD Band I ☐UMTS FDD Band VIII		
HS Type	HSPA(HSUPA/HSDPA)		
TX Frequency Range	WCDMA FDD Band II: 1850-1910MHz WCDMA FDD Band V: 820-850MHz		
RX Frequency Range	WCDMA FDD Band II: 1930-1990MHz WCDMA FDD Band V: 869-894MHz		
Release Version	Rel-6		
Type of modulation	HSDPA:QPSK/16QAM; HSUPA:BPSK; WCDMA:QPSK		
Antenna Gain	-1.0dBi		
Max. Average Power (Max. Peak Power)	Band II: 21.35dBm (23.59dBm); Band V: 21.28dBm (23.42dBm)		

Page 7 of 85


EUT Description(Continue)

	<u> </u>		
Bluetooth			
Bluetooth Version	□V2.0 □V2.1 □V2.1+EDR □V3.0 □V3.0+HS □V4.0		
Operation Frequency	2402~2480MHz		
Type of modulation	⊠GFSK ⊠∏/4-DQPSK ⊠8-DPSK		
Avg. Burst Power	-0.24dBm		
Antenna Gain	0.8dBi		
WIFI			
WIFI Specification	□802.11a ⊠802.11b ⊠802.11g ⊠802.11n(20) ⊠802.11n(40)		
Operation Frequency	2412~2462MHz		
Avg. Burst Power	11b: 11.51Bm,11g:9.26dBm,11n(20): 9.08dBm,11n(40): 7.86dBm		
Antenna Gain	0.8dBi		
Accessories			
Battery	Brand name: KENXINDA Model No. : A6 Voltage and Capacitance: 3.8 V & 2000mAh		
Adapter	Brand name: KENXINDA Model No. : A6 Input: AC 100-240V, 50/60Hz, 100mA Output: DC 5V, 1000mA		
Earphone	Brand name: N/A Model No. : N/A		
Note:CMU200 can measur	e the average power and Peak power at the same time		
Product	Type Display Display		

Page 8 of 85

3. SAR MEASUREMENT SYSTEM

3.1. The DASY5 system used for performing compliance tests consists of following items



- A standard high precision 6-axis robot with controller, teach pendant and software.
- Data acquisition electronics (DAE) which attached to the robot arm extension. The DAE consist of a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD-converter and a command decoder with a control logic unit. Transmission to the measurement server is accomplished through an optical downlink for data and status information, as well as an optical uplink for commands and the clock
- A dosimetric probe equipped with an optical surface detector system.
- The Electro-optical converter (EOC) performs the conversion from optical to electrical signals for the digital Communication to the DAE. To use optical surface detection, a special version of the EOC is required. The EOC signal is transmitted to the measurement server.
- A Light Beam used is for probe alignment. This improves the (absolute) accuracy of the probe positioning.
- A computer running WinXP and the DASY5 software.
- Remote control and teach pendant as well as additional circuitry for robot safety such as warning lamps, etc.
- Phantoms, device holders and other accessories according to the targeted measurement.

Page 9 of 85

3.2. DASY5 E-Field Probe

The SAR measurement is conducted with the dosimetric probe manufactured by SPEAG. The probe is specially designed and calibrated for use in liquid with high permittivity. The dosimetric probe has special calibration in liquid at different frequency. SPEAG conducts the probe calibration in compliance with international and national standards (e.g. IEEE 1528 and relevant KDB files.) The calibration data are in Appendix D.

Isotropic E-Field Probe Specification

Model	EX3DV4		
Manufacture	SPEAG		
frequency	0.3GHz-6 GHz Linearity:±0.2dB(300 MHz-6 GHz)		
Dynamic Range	0.01W/Kg-100W/Kg Linearity:±0.2dB		
Dimensions	Overall length:337mm Tip diameter:2.5mm Typical distance from probe tip to dipole centers:1mm		
Application	High precision dosimetric measurements in any exposure scenario (e.g., very strong gradient fields). Only probe which enables compliance testing for frequencies up to 6 GHz with precision of better 30%.		

3.3. Data Acquisition Electronics description

The data acquisition electronics (DAE) consist if a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD-converte and a command decoder with a control logic unit. Transmission to the measurement sever is accomplished through an optical downlink fir data and status information, as well as an optical uplink for commands and the clock.

The mechanical probe mounting device includes two different sensor systems for frontal and sideways probe contacts. They are used for mechanical surface detection and probe collision detection.

DAE4

Input Impedance	200MOhm	ENGS.
The Inputs	Symmetrical and floating	A TOTAL MARKET TO THE PARTY OF
Common mode rejection	above 80 dB	DAKE TO STATE OF THE PARTY OF T

Page 10 of 85

3.4. Robot

The DASY system uses the high precision robots (DASY5:TX60) type from Stäubli SA (France). For the 6-axis controller system, the robot controller version from is used.

The XL robot series have many features that are important for our application:

- ☐ High precision (repeatability 0.02 mm)
- ☐ High reliability (industrial design)
- ☐ Jerk-free straight movements
- □ Low ELF interference (the closed metallic construction shields against motor control fields)
- □ 6-axis controller



3.5. Light Beam Unit

The light beam switch allows automatic "tooling" of the probe. During the process, the actual position of the probe tip with respect to the robot arm is measured, as well as the probe length and the horizontal probe offset. The software then corrects all movements, such that the robot coordinates are valid for the probe tip.

The repeatability of this process is better than 0.1 mm. If a position has been taught with an aligned prob.1 mm, even if the other probe has different dimensions. During probe rotations, the probe tip will keep its actual position. e, the same position will be reached with another aligned probe within 0



Page 11 of 85

3.6. Device Holder

The DASY device holder is designed to cope with different positions given in the standard. It has two scales for the device rotation (with respect to the body axis) and the device inclination (with respect to the line between the ear reference points). The rotation center for both scales is the ear reference point (EPR).

Thus the device needs no repositioning when changing the angles.

The DASY device holder has been made out of low-loss POM material having the following dielectric parameters: relative permittivity $\epsilon{=}3$ and loss tangent $\delta=0.02.$ The amount of dielectric material has been reduced in the closest vicinity of the device, since measurements have suggested that the influence of the clamp on the test results could thus be lowered.



3.7. Measurement Server

The measurement server is based on a PC/104 CPU board with CPU (DASY5: 400 MHz, Intel Celeron), chip-disk (DASY5: 128MB), RAM (DASY5: 128MB). The necessary circuits for communication with the DAE electronic box, as well as the 16 bit AD converter system for optical detection and digital I/O interface are contained on the DAYS I/O board, which is directly connected to the PC/104 bus of the CPU board.

The measurement server performs all the real-time data evaluation for field measurements and surface detection, controls robot movements and handles safety operations.



Page 12 of 85

3.8. PHANTOM SAM Twin Phantom

The SAM twin phantom is a fiberglass shell phantom with 2mm shell thickness (except the ear region where shell thickness increases to 6mm). It has three measurement areas:

□ Left head

□ Right head

☐ Flat phantom



The bottom plate contains three pair of bolts for locking the device holder. The device holder positions are adjusted to the standard measurement positions in the three sections. A white cover is provided to tap the phantom during off-periods to prevent water evaporation and changes in the liquid parameters. On the phantom top, three reference markers are provided to identify the phantom position with respect to the robot.

ELI4 Phantom

☐ Flat phantom a fiberglass shell flat phantom with 2mm+/- 0.2 mm shell thickness. It has only one measurement area for Flat phantom



Page 13 of 85

4. SAR MEASUREMENT PROCEDURE

4.1. Specific Absorption Rate (SAR)

SAR is related to the rate at which energy is absorbed per unit mass in object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and occupational/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of given mass density (ρ). The equation description is as below:

$$SAR = \frac{d}{dt} \left(\frac{dW}{dm} \right) = \frac{d}{dt} \left(\frac{dW}{\rho dV} \right)$$

SAR is expressed in units of Watts per kilogram (W/Kg) SAR can be obtained using either of the following equations:

$$SAR = \frac{\sigma E^2}{\rho}$$

$$SAR = c_h \frac{dT}{dt}\Big|_{t=0}$$

Where

 $\begin{array}{lll} \text{SAR} & \text{is the specific absorption rate in watts per kilogram;} \\ \text{E} & \text{is the r.m.s. value of the electric field strength in the tissue in volts per meter;} \\ \sigma & \text{is the conductivity of the tissue in siemens per metre;} \\ \rho & \text{is the density of the tissue in kilograms per cubic metre;} \\ c_h & \text{is the heat capacity of the tissue in joules per kilogram and Kelvin;} \\ \end{array}$

 $\frac{dT}{dt}$ | t=0 is the initial time derivative of temperature in the tissue in kelvins per second

Page 14 of 85

4.2. SAR Measurement Procedure

Step 1: Power Reference Measurement

The Power Reference Measurement and Power Drift Measurement are for monitoring the power drift of the device under test in the batch process. The minimum distance of probe sensors to surface is 2.7mm This distance cannot be smaller than the distance os sensor calibration points to probe tip as `defined in the probe properties,

Step 2: Area Scan

The Area Scan is used as a fast scan in two dimensions to find the area of high field values, before doing a fine measurement around the hot spot. The sophisticated interpolation routines implemented in DASY software can find the maximum locations even in relatively coarse grids. When an Area Scan has measured all reachable points, it computes the field maximal found in the scanned area, within a range of the global maximum. The range (in db) is specified in the standards for compliance testing. For example, a 2db range is required in IEEE Standard 1528 and IEC62209 standards, whereby 3db is a requirement when compliance is assessed in accordance with the ARIB standard (Japan) If one Zoom Scan follows the Area Scan, then only the absolute maximum will be taken as reference. For cases where multiple maximum are detected, the number of Zoom Scan has to be increased accordingly.

Area Scan Parameters extracted from KDB 865664 D01 SAR Measurement 100MHz to 6GHz

	≤ 3 GHz	> 3 GHz
Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface	5 ± 1 mm	½·δ·ln(2) ± 0.5 mm
Maximum probe angle from probe axis to phantom surface normal at the measurement location	30° ± 1°	20° ± 1°
	≤2 GHz: ≤15 mm 2 – 3 GHz: ≤12 mm	3 – 4 GHz: ≤ 12 mm 4 – 6 GHz: ≤ 10 mm
Maximum area scan spatial resolution: Δx _{Area} , Δy _{Area}	When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be \leq the corresponding x or y dimension of the test device with at least one measurement point on the test device.	

Step 3: Zoom Scan

Zoom Scan are used to assess the peak spatial SAR value within a cubic average volume containing 1g abd 10g of simulated tissue. The Zoom Scan measures points(refer to table below) within a cube whose base faces are centered on the maxima found in a preceding area scan job within the same procedure. When the measurement is done, the Zoom Scan evaluates the averaged SAR for 1g and 10g and displays these values next to the job's label.

Page 15 of 85

Zoom Scan Parameters extracted from KDB865664 d01 SAR Measurement 100MHz to 6GHz

Maximum zoom scan spatial resolution: Δx_{Zoom} , Δy_{Zoom}			≤ 2 GHz: ≤ 8 mm 2 - 3 GHz: ≤ 5 mm*	3 – 4 GHz: ≤ 5 mm* 4 – 6 GHz: ≤ 4 mm*
	uniform grid: $\Delta z_{Zoom}(n)$		≤ 5 mm	3 – 4 GHz: ≤ 4 mm 4 – 5 GHz: ≤ 3 mm 5 – 6 GHz: ≤ 2 mm
Maximum zoom scan spatial resolution, normal to phantom surface	$\begin{array}{c} \Delta z_{Zoom}(1)\text{: between} \\ 1^{\text{st}} \text{ two points closest} \\ \text{to phantom surface} \\ \\ \Delta z_{Zoom}(n \ge 1)\text{:} \\ \text{between subsequent} \\ \text{points} \end{array}$	1 st two points closest	≤ 4 mm	3 – 4 GHz: ≤ 3 mm 4 – 5 GHz: ≤ 2.5 mm 5 – 6 GHz: ≤ 2 mm
		$\leq 1.5 \cdot \Delta z_{Zoom}(n-1)$		
Minimum zoom scan volume	x, y, z		≥ 30 mm	3 – 4 GHz: ≥ 28 mm 4 – 5 GHz: ≥ 25 mm 5 – 6 GHz: ≥ 22 mm

Note: δ is the penetration depth of a plane-wave at normal incidence to the tissue medium; see draft standard IEEE P1528-2011 for details.

Step 4: Power Drift Measurement

The Power Drift Measurement measures the field at the same location as the most recent power reference measurement within the same procedure, and with the same settings. The Power Drift Measurement gives the field difference in dB from the reading conducted within the same settings. This allows a user to monitor the power drift of the device under test within a batch process. The measurement procedure is the same as Step 1.

^{*} When zoom scan is required and the <u>reported</u> SAR from the area scan based 1-g SAR estimation procedures of KDB 447498 is ≤ 1.4 W/kg, ≤ 8 mm, ≤ 7 mm and ≤ 5 mm zoom scan resolution may be applied, respectively, for 2 GHz to 3 GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz.

Report No.: AGC00069150808FH01 Page 16 of 85

4.3. RF Exposure Conditions


Test Configuration and setting:

The EUT is a model of GSM Portable Mobile Station (MS). It supports GSM/GPRS, WCDMA/HSPA, BT, WIFI, and support hotspot mode.

For WWAN SAR testing, the device was controlled by using a base station emulator. Communication between the device and the emulator were established by air link. The distance between the EUT and the antenna is larger than 50cm, and the output power radiated from the emulator antenna is at least 30db smaller than the output power of EUT.

For WLAN testing, the EUT is configured with the WLAN continuous TX tool through engineering command.

Antenna Location: (the front view)



Page 17 of 85

For WWAN mode:

Test Configurations	Antenna to edges/surface	SAR required	Note
Head			
Left Touch		Yes	
Left Tilt		Yes	
Right Touch		Yes	
Right Tilt		Yes	
Body			
Back	<25mm	Yes	
Front	<25mm	Yes	
Hotspot			
Back	<25mm	Yes	
Front	<25mm	Yes	
Edge 1 (Top)	110	No	SAR is not required for the distance between the antenna and the edge is >25mm as per KDB 941225D06 Hotspot SAR
Edge 2 (Right)	10	Yes	
Edge 3 (Bottom)	2	Yes	
Edge 4 (Left)	2	Yes	

For WLAN mode:

Test Configurations	Antenna to edges/surface	SAR required	Note
Head			
Left Touch		Yes	
Left Tilt		Yes	
Right Touch		Yes	
Right Tilt		Yes	
Body			
Back	<25mm	Yes	
Front	<25mm	Yes	
Hotspot			
Back	<25mm	Yes	
Front	<25mm	Yes	
Edge 1 (Top)	2	Yes	
Edge 2 (Right)	53	No	SAR is not required for the distance between the antenna and the edge is >25mm as per KDB 941225D06 Hotspot SAR
Edge 3 (Bottom)	113	No	SAR is not required for the distance between the antenna and the edge is >25mm as per KDB 941225D06 Hotspot SAR
Edge 4 (Left)	2	Yes	

Page 18 of 85

5. TISSUE SIMULATING LIQUID

For SAR measurement of the field distribution inside the phantom, the phantom must be filled with homogeneous tissue simulating liquid to a depth of at least 15cm. For head SAR testing the liquid height from the ear reference point (ERP) of the phantom to the liquid top surface is larger than 15cm For body SAR testing, the liquid height from the center of the flat phantom to the liquid top surface is larger than 15cm. The nominal dielectric values of the tissue simulating liquids in the phantom and the tolerance of 5% are listed in 4.2

5.1. The composition of the tissue simulating liquid

					0 1			
Ingredient	Water	Salt	Sugar	HEC	Preventol	DGBE	TWEEN	Triton X-100
835MHz Head	√	√	√	√	√			
835MHz Body	√	√	√	√	√			
1900MHz Head	√	√		-		√		
1900MHz Body	√	√	√	√	√			
2450MHz Head	√	√		-				√
2450MHz Body	√	√				√		

5.2. Tissue Dielectric Parameters for Head and Body Phantoms

The head tissue dielectric parameters recommended by the IEEE 1528 have been incorporated in the following table. These head parameters are derived from planar layer models simulating the highest expected SAR for the dielectric properties and tissue thickness variations in a human head. Other head and body tissue parameters that have not been specified in IEEE 1528 are derived from the tissue dielectric parameters computed from the 4-Cole-Cole equations described in Reference [12] and extrapolated according to the head parameters specified in IEEE 1528.

Target Frequency	he	ad	body		
(MHz)	εr	σ (S/m)	εr	σ (S/m)	
300	45.3	0.87	58.2	0.92	
450	43.5	0.87	56.7	0.94	
835	41.5	0.90	55.2	0.97	
900	41.5	0.97	55.0	1.05	
915	41.5	1.01	55.0	1.06	
1450	40.5	1.20	54.0	1.30	
1610	40.3	1.29	53.8	1.40	
1800 – 2000	40.0	1.40	53.3	1.52	
2450	39.2	1.80	52.7	1.95	
3000	38.5	2.40	52.0	2.73	
5800	35.3	5.27	48.2	6.00	

($\varepsilon r = relative permittivity$, $\sigma = conductivity and <math>\rho = 1000 \text{ kg/m3}$)

Page 19 of 85

5.3. Tissue Calibration Result

The dielectric parameters of the liquids were verified prior to the SAR evaluation using DASY5

Dielectric Probe	Kit and	R&S	Network	<u>Anal</u>	yzer	ZVL	.6.
				_		_	

	Tissue Stimulant Measurement for 835MHz									
	Fr.	Dielectric Parameters (±5%)		Tissue	To at time a					
	(MHz)	εr 41.5 (39.425-43.575)	δ[s/m] 0.90(0.855-0.945)	Temp [°C]	Test time					
	824.2	41.82	0.87							
Head	826.4	41.61	0.88							
	835	41.03	0.89	21.5	Aug. 26,2015					
	836.6	40.58	0.90	21.5	Aug. 26,2015					
	846.6	40.23	0.91							
	848.8	40.00	0.92							
	Fr.	Dielectric Par	Tissue	Test time						
	(MHz)	εr 55.20(52.44-57-96)	δ[s/m]0.97(0.9215-1.0185)	Temp [°C]	rest time					
	824.2	55.87	0.94							
Pody	826.4	55.68	0.95							
Body	835	55.18	0.97	21.6	Aug. 26,2015					
	836.6	54.93	0.98	21.0	Aug. 26,2015					
	846.6	54.20	0.98							
	848.8	54.03	0.99							

	Tissue Stimulant Measurement for 1900MHz								
	Fr.	Dielectric Parameters (±5%)			T4 4i				
	(MHz)	εr40.00(38.00-42.00)	δ[s/m]1.40(1.33-1.47)	Temp [°C]	Test time				
	1850.2	41.25	1.36						
Head	1852.4	41.03	1.39						
	1880	40.73	1.40	21.6	Aug. 28,2015				
	1900	40.24	1.43	21.0	Aug. 26,2015				
	1907.6	40.01	1.45						
	1909.8	39.42 1.45							
	Fr.	Dielectric Par	Tissue						
	(MHz)	εr53.30(50.635-55.965)	δ[s/m]1.52(1.444-1.596)	Temp [°C]	Test time				
	1850.2	54.75	1.48						
Pody.	1852.4	53.19	1.50						
Body	1880	53.13	1.50	21.6	Aug. 28,2015				
	1900	52.88	1.52	21.0	Aug. 20,2015				
	1907.6	52.01	1.54						
	1909.8	51.76	1.57						

Page 20 of 85

	Tissue Stimulant Measurement for 2450MHz									
	Fr.	Fr. Dielectric Parameters (±5%)			-					
	(MHz)	εr39.2(37.24-41.16) δ[s/m]1.80(1.71-1.89)		Temp [°C]	Test time					
Head	2412	40.83	1.75							
	2437	40.56	1.78	21.2	Aug. 29,2015					
	2450	40.27	1.80	21.2	Aug. 29,2015					
	2462	39.66	1.85							
	Fr.	Dielectric Parameters (±5%)		Tissue	Test time					
	(MHz)	er52.7(50.065-55.335)	δ[s/m]1.95(1.8525-2.0475)	Temp [°C]	rest time					
Dody	2412	53.24	1.89							
Body	2437	52.75	1.92	21.4	Aug 20 2015					
	2450	52.64	1.92	21.4	Aug. 29,2015					
	2462	51.45	1.95							

Page 21 of 85


6. SAR SYSTEM CHECK PROCEDURE

6.1. SAR System Check Procedures

SAR system check is required to confirm measurement accuracy, according to the tissue dielectric media, probe calibration points and other system operating parameters required for measuring the SAR of a test device. The system verification must be performed for each frequency band and within the valid range of each probe calibration point required for testing the device. The same SAR probe(s) and tissue-equivalent media combinations used with each specific SAR system for system verification must be used for device testing. When multiple probe calibration points are required to cover substantially large transmission bands, independent system verifications are required for each probe calibration point. A system verification must be performed before each series of SAR measurements using the same probe calibration point and tissue-equivalent medium. Additional system verification should be considered according to the conditions of the tissue-equivalent medium and measured tissue dielectric parameters, typically every three to four days when the liquid parameters are remeasured or sooner when marginal liquid parameters are used at the beginning of a series of measurements.


Each DASY system is equipped with one or more system check kits. These units, together with the predefined measurement procedures within the DASY software, enable the user to conduct the system check and system validation. System kit includes a dipole, and dipole device holder.

The system check verifies that the system operates within its specifications. It's performed daily or before every SAR measurement. The system check uses normal SAR measurement in the flat section of the phantom with a matched dipole at a specified distance. The system check setup is shown as below.



Page 22 of 85

6.2. SAR System Check 6.2.1. Dipoles



The dipoles used is based on the IEEE-1528 standard, and is complied with mechanical and electrical specifications in line with the requirements of both IEEE and FCC Supplement C. the table below provides details for the mechanical and electrical Specifications for the dipoles.



The dipoles used is based on the IEEE-1528 standard, and is complied with mechanical and electrical specifications in line with the requirements of both IEEE and FCC Supplement C. the table below provides details for the mechanical and electrical Specifications for the dipoles.

Frequency	L (mm)	h (mm)	d (mm)
835MHz	161.0	89.8	3.6
1900MHz	68	39.5	3.6
2450MHz	51.5	30.4	3.6

Page 23 of 85

6.2.2. System Check Result

System Perf	System Performance Check at 835MHz&1900MHz &2450MHz for Head									
Validation K	Validation Kit: SN 46/11DIP 0G835-190 & SN 46/11DIP 1G900-187& D2450V2-SN:968									
Frequency	Target Value(W/Kg)		Reference Result (± 10%)		Tested Value(W/Kg)		Tissue Temp.	Test time		
[MHz]	1g	10g	1g	10g	1g	10g	[°C]			
835	9.60	6.20	8.64-10.56	5.58-6.82	10.256	6.448	21.5	Aug. 26,2015		
1900	39.65	20.24	35.685-43.615	18.216-22.264	39.200	19.680	21.6	Aug. 28,2015		
2450	53.8	25.4	48.42-59.18	22.86-27.94	53.760	24.640	21.2	Aug. 29,2015		
System Perf	ormance	Check at 8	335 MHz &1900N	/IHz & 2450MHz	for Body					
Frequency		get W/Kg)		ce Result 0%)		sted (W/Kg)	Tissue Temp.	Test time		
[MHz]	1g	10g	1g	10g	1g	10g	[°C]			
835	9.90	6.39	8.91-10.89	5.75-7.03	10.496	6.800	21.6	Aug. 26,2015		
1900	40.74	21.43	36.666-44.814	19.287-23.573	43.520	21.120	21.6	Aug. 28,2015		
2450	51.7	24.3	46.53-56.87	21.87-26.73	55.360	25.440	21.4	Aug. 29,2015		


Page 24 of 85

7. EUT TEST POSITION

This EUT was tested in Right Cheek, Right Titled, Left Cheek, Left Titled, Body back and Body front and 4 edges.

7.1. Define Two Imaginary Lines on the Handset

- (1)The vertical centerline passes through two points on the front side of the handset the midpoint of the width wt of the handset at the level of the acoustic output, and the midpoint of the width wb of the handset.
- (2) The horizontal line is perpendicular to the vertical centerline and passes through the center of the acoustic output. The horizontal line is also tangential to the face of the handset at point A.
- (3)The two lines intersect at point A. Note that for many handsets, point A coincides with the center of the acoustic output; however, the acoustic output may be located elsewhere on the horizontal line. Also note that the vertical centerline is not necessarily to the front face of the handset, especially for clamshell handsets, handsets with flip covers, and other irregularly shaped handsets.



Page 25 of 85

7.2. Cheek Position

(1) To position the device with the vertical center line of the body of the device and the horizontal line crossing the center picec in a plane parallel to the sagittal plane of the phantom. While maintaining the device in this plane, align the vertical center line with the reference plane containing the ear and mouth reference point (M: Mouth, RE: Right Ear, and LE: Left Ear) and align the center of the ear piece with the line RE-LE.

(2) To move the device towards the phantom with the ear piece aligned with the the line LE-RE until the phone touched the ear. While maintaining the device in the reference plane and maintaining the phone contact with ear, move the bottom of the phone until any point on the front side is in contact with the cheek of the phantom or until contact with the ear is lost









7.3. Title Position

- (1) To position the device in the "cheek" position described above.
- (2) While maintaining the device in the reference plane described above and pivoting against the ear, moves it outward away from the mouth by an angle of 15 degrees or until with the ear is lost.









Page 26 of 85

7.4. Body Worn Position

- (1) To position the EUT parallel to the phantom surface.
- (2) To adjust the EUT parallel to the flat phantom.
- (3) To adjust the distance between the EUT surface and the flat phantom to 10mm.

General Note: Referring KDB941225 D06 v02, when the overall device length and width are \geq 9cm *5cm, the test distance is 10mm. SAR must be measured for all sides and surfaces with a transmitting antenna within 25mm from that surface or edge.





Page 27 of 85

8. SAR EXPOSURE LIMITS

SAR assessments have been made in line with the requirements of IEEE-1528, FCC Supplement C, and comply with ANSI/IEEE C95.1-1992 "Uncontrolled Environments" limits. These limits apply to a location which is deemed as "Uncontrolled Environment" which can be described as a situation where the general public may be exposed to an RF source with no prior knowledge or control over their exposure.

Limits for General Population/Uncontrolled Exposure (W/kg)

Type Exposure	Uncontrolled Environment Limit (W/kg)
Spatial Peak SAR (1g cube tissue for brain or body)	1.60
Spatial Average SAR (Whole body)	0.08
Spatial Peak SAR (Limbs)	4.0

Page 28 of 85

9. TEST EQUIPMENT LIST

Equipment description	Manufacturer/ Model	Identification No.	Current calibration date	Next calibration date
Stäubli Robot	Stäubli-TX60	F13/5Q2UD1/A/01	N/A	N/A
Robot Controller	Stäubli-CS8	139522	N/A	N/A
TISSUE Probe	SATIMO	SN 45/11 OCPG45	12/03/2014	12/02/2015
E-Field Probe	Speag-EX3DV4	3953	11/06/2014	11/05/2015
SAM Twin Phantom	Speag-SAM	1790	N/A	N/A
Device Holder	Speag-SD 000 H01 KA	SD 000 H01 KA	N/A	N/A
DAE4	Speag-SD 000 D04 BM	1398	03/11/2015	03/10/2016
SAR Software	Speag-DASY5	DASY52.8	N/A	N/A
Liquid	SATIMO	-	N/A	N/A
Radio Communication Tester	R&S-CMU200	069Y7-158-13-712	03/06/2015	03/05/2016
Dipole	SATIMO SID835	SN46/11 DIP 0G835-190		10/01/2017
Dipole	SATIMO SID1900	SN46/11 DIP 1G900-187	11/14/2013	11/13/2016
Dipole	D2450V2	SN968	06/12/2015	06/11/2018
Signal Generator	Agilent-E4438C	MY44260051	03/06/2015	03/05/2016
Power Sensor	NRP-Z23	US38261498	03/06/2015	03/05/2016
Spectrum Analyzer E4440	Agilent	US41421290	07/23/2015	07/22/2016
Network Analyzer	Rhode & Schwarz ZVL6	SN100132	03/06/2015	03/05/2016
Attenuator	Warison /WATT-6SR1211	N/A	N/A	N/A
Attenuator	Mini-circuits / VAT-10+	N/A	N/A	N/A
Amplifier	EM30180	SN060552	03/06/2015	03/05/2016
Directional Couple	Werlatone/ C5571-10	SN99463	07/29/2015	07/28/2016
Directional Couple	Werlatone/ C6026-10	SN99482	07/29/2015	07/28/2016
Power Sensor	NRP-Z21	1137.6000.02	10/22/2014	10/21/2015
Power Viewer	R&S	V2.3.1.0	N/A	N/A

Note: Per KDB 865664Dipole SAR Validation, AGC Lab has adopted 3 years calibration intervals. On annual basis, every measurement dipole has been evaluated and is in compliance with the following criteria:

- 1. There is no physical damage on the dipole;
- 2. System validation with specific dipole is within 10% of calibrated value;
- 3. Return-loss is within 20% of calibrated measurement;
- 4. Impedance is within 5Ω of calibrated measurement.

Page 29 of 85

10. MEASUREMENT UNCERTAINTY

The component of uncertainly may generally be categorized according to the methods used to evaluate them. The evaluation of uncertainly by the statistical analysis of a series of observations is termed a Type An evaluation of uncertainty. The evaluation of uncertainty by means other than the statistical analysis of a series of observation is termed a Type B evaluation of uncertainty. Each component of uncertainty, however evaluated, is represented by an estimated standard deviation, termed standard uncertainty, which is determined by the positive square root of the estimated variance.

A Type A evaluation of standard uncertainty may be based on any valid statistical method for treating data. This includes calculating the standard deviation of the mean of a series of independent observations; using the method of least squares to fit a curve to the data in order to estimate the parameter of the curve and their standard deviations; or carrying out an analysis of variance in order to identify and quantify random effects in certain kinds of measurement.

A type B evaluation of standard uncertainty is typically based on scientific judgment using all of the relevant information available. These may include previous measurement data, experience, and knowledge of the behavior and properties of relevant materials and instruments, manufacture's specification, data provided in calibration reports and uncertainties assigned to reference data taken from handbooks. Broadly speaking, the uncertainty is either obtained from an outdoor source or obtained from an assumed distribution, such as the normal distribution, rectangular or triangular distributions indicated in Table as follow.

Uncertainty Distributions	Normal		Triangular	U-Shape
Multi-plying Factor(a)	1/k(b)	1/√3	1/√6	1/√2

- (a) Standard uncertainty is determined as the product of the multiplying factor and the estimated range of variations in the measured quantity
- (b) κ is the coverage factor

Table 13.1 Standard Uncertainty for Assumed Distribution (above table)

The combined standard uncertainty of the measurement result represents the estimated standard deviation of the result. It is obtained by combining the individual standard uncertainties of both Type A and Type B evaluation using the usual "root-sum-squares" (RSS) methods of combining standard deviations by taking the positive square root of the estimated variances.

Expanded uncertainty is a measure of uncertainty that defines an interval about the measurement result within which the measured value is confidently believed to lie. It is obtained by multiplying the combined standard uncertainty by a coverage factor. Typically, the coverage factor ranges from 2 to 3. Using a coverage factor allows the true value of a measured quantity to be specified with a defined probability within the specified uncertainty range. For purpose of this document, a coverage factor two is used, which corresponds to confidence interval of about 95 %. The DASY uncertainty Budget is shown in the following tables.

Page 30 of 85

DAYS5 Measurement Uncertainty											
Measurement uncertainty for 30 MHz to 3GHz averaged over 1 gram / 10 gram.											
Error Description	Uncertainty value(±10%)	Probability Distribution	Divisor	(Ci) 1g	(Ci) 10g	Standard Uncertainty (1g)	Standard Uncertainty (10g)				
Measurement System											
Probe Calibration	6.53	Normal	1	1	1	6.53	6.53				
Axial Isotropy	4.6	Rectangular	$\sqrt{3}$	1	1	2.66	2.66				
Hemispherical Isotropy	9.3	Rectangular	$\sqrt{3}$	1	1	5.37	5.37				
Linearity	4.5	Rectangular	$\sqrt{3}$	1	1	2.60	2.60				
Probe Modulation Response	0.2	Rectangular	$\sqrt{3}$	1	1	0.12	0.12				
System Detection Limits	0.9	Rectangular	$\sqrt{3}$	1	1	0.52	0.52				
Boundary Effects	0.9	Rectangular	$\sqrt{3}$	0	0	0	0				
Readout Electronics	0.2	Normal	$\sqrt{3}$	1	1	0.12	0.12				
Response Time	0	Rectangular	$\sqrt{3}$	1	1	0	0				
Integration Time	0	Rectangular	$\sqrt{3}$	1	1	0	0				
RF Ambient Noise	0.9	Rectangular	$\sqrt{3}$	1	1	0.52	0.52				
RF Ambient Reflection	0.9	Rectangular	$\sqrt{3}$	1	1	0.52	0.52				
Probe Positioner	0.7	Rectangular	$\sqrt{3}$	1	1	0.40	0.40				
Probe Positioning	6.5	Rectangular	$\sqrt{3}$	1	1	3.75	3.75				
Post-processing	3.8	Rectangular	$\sqrt{3}$	1	1	2.19	2.19				
Test Sample Related											
Device Positioning	3.6	Normal	1	1	1	3.6	3.6				
Device Holder	2.9	Normal	1	1	1	2.9	2.9				
Measurement SAR Drift	5.0	Rectangular	$\sqrt{3}$	1	1	2.89	2.89				
Power Scaling	0.0	Rectangular	$\sqrt{3}$	1	1	0	0				
Phantom and Setup				•							
Phantom Uncertainty	3.9	Rectangular	$\sqrt{3}$	1	1	2.25	2.25				
Liquid Conductivity(Meas.)	2.4	Normal	1	0.78	0.71	1.87	1.70				
Liquid Conductivity(Target)	4.9	Rectangular	$\sqrt{3}$	0.64	0.43	1.81	1.22				
Liquid Permittivity(Meas.)	2.4	Normal	1	0.26	0.26	0.62	0.62				
Liquid Permittivity((Target)	4.9	Rectangular	$\sqrt{3}$	0.6	0.49	1.70	1.39				
Liquid Conductivity-temperature uncertainty	1.6	Rectangular	$\sqrt{3}$	0.78	0.71	0.72	0.66				
Liquid Permittivity-temperature uncertainty	0.2	Rectangular	$\sqrt{3}$	0.23	0.26	0.026	0.03				
Combined Standard Uncertainty 12.03 12.00											
Coverage Factor for 95%	K=	=2									
Expanded Uncertainty						±24.06%	±24.00%				

Page 31 of 85

DAYS5 System Check Uncertainty for 30 MHz to 6GHz averaged range										
Error Description	Uncer. value (±10%)	Prob. Dist.	Div.	(Ci) 1g	(Ci) 10g	Std. Unc. (1g)	Std. Unc. (10g)	(v _i) V _{eff}		
Measurement System										
Probe Calibration	6.53	Normal	1	1	1	6.53	6.53	8		
Axial Isotropy	4.6	Rectangular	$\sqrt{3}$	1	1	2.66	2.66	8		
Hemispherical Isotropy	9.3	Rectangular	$\sqrt{3}$	1	1	5.37	5.37	8		
Boundary Effects	0.9	Rectangular	$\sqrt{3}$	0	0	0	0	∞		
Linearity	4.5	Rectangular	$\sqrt{3}$	1	1	2.60	2.60	∞		
System Detection Limits	0.9	Rectangular	$\sqrt{3}$	1	1	0.52	0.52	∞		
Modulation Response	0	Rectangular	$\sqrt{3}$	1	1	0	0	8		
Readout Electronics	0.2	Normal	1	1	1	0.2	0.2	∞		
Response Time	0	Rectangular	$\sqrt{3}$	1	1	0	0	8		
Integration Time	0	Rectangular	$\sqrt{3}$	1	1	0	0	∞		
RF Ambient Noise	0.9	Rectangular	$\sqrt{3}$	1	1	0.52	0.52	∞		
RF Ambient Reflection	0.9	Rectangular	$\sqrt{3}$	1	1	0.52	0.52	8		
Probe Positioner	0.7	Rectangular	$\sqrt{3}$	1	1	0.402	0.402	8		
Probe Positioning	6.5	Rectangular	$\sqrt{3}$	1	1	3.752	3.752	∞		
Max. SAR Eval.	1.9	Rectangular	$\sqrt{3}$	1	1	1.10	1.10	∞		
Dipole Related										
Deviation of exp. dipole	5.3	Rectangular	$\sqrt{3}$	1	1	3.06	3.06	∞		
Dipole Axis to Liquid Dist.	2.0	Rectangular	$\sqrt{3}$	1	1	1.15	1.15	∞		
Input power & SAR drift	3.3	Rectangular	$\sqrt{3}$	1	1	1.91	1.91	∞		
Phantom and Setup										
Phantom Uncertainty	3.9	Rectangular	$\sqrt{3}$	1	1	2.25	2.25	8		
SAR correction	1.8	Rectangular	$\sqrt{3}$	1	0.84	1.04	0.87	∞		
Liquid Conductivity(Meas.)	2.4	Normal	1	0.78	0.71	1.87	1.70	8		
Liquid Permittivity(Meas.)	2.4	Normal	1	0.26	0.26	0.62	0.62	8		
Temp. unc Conductivity	1.6	Rectangular	$\sqrt{3}$	0.78	0.71	0.72	0.66	8		
Temp. unc Permittivity	0.2	Rectangular	$\sqrt{3}$	0.23	0.26	0.02	0.03	∞		
Combined Std. Uncertainty						11.16	11.10			
Expanded STD Uncertainty						±22.32%	±22.20%			

Page 32 of 85

11. CONDUCTED POWER MEASUREMENT GSM BAND

GSW BAND											
Mode	Frequency(MHz)	Avg. Burst Power(dBm)	Duty cycle Factor(dBm)	Frame Power(dBm)							
Maximum Power <1>	Maximum Power <1>										
	824.2	31.21	-9	22.21							
GSM 850	836.6	31.19	-9	22.19							
	848.8	31.15	-9	22.15							
CDDC 050	824.2	30.68	-9	21.68							
GPRS 850 (1 Slot)	836.6	30.64	-9	21.64							
(1 3101)	848.8	30.62	-9	21.62							
000000	824.2	28.39	-6	22.39							
GPRS 850 (2 Slot)	836.6	28.34	-6	22.34							
(2 0101)	848.8	28.37	-6	22.37							
0000000	824.2	26.34	-4.26	22.08							
GPRS 850 (3 Slot)	836.6	26.29	-4.26	22.03							
(3 3101)	848.8	26.26	-4.26	22.00							
0000 050	824.2	25.32	-3	22.32							
GPRS 850 (4 Slot)	836.6	25.38	-3	22.38							
(4 5101)	848.8	25.26	-3	22.26							

Page 33 of 85

GSM BAND CONTINUE

Mode	Frequency(MHz)	Avg. Burst Power(dBm)	Duty cycle Factor(dBm)	Frame Power(dBm)
	1850.2	28.22	-9	19.22
PCS1900	1880	28.18	-9	19.18
	1909.8	28.15	-9	19.15
00004000	1850.2	27.65	-9	18.65
GPRS1900 (1 Slot)	1880	27.61	-9	18.61
(1 3101)	1909.8	27.57	-9	18.57
00004000	1850.2	25.37	-6	19.37
GPRS1900 (2 Slot)	1880	25.34	-6	19.34
(2 0101)	1909.8	25.32	-6	19.32
00004000	1850.2	23.45	-4.26	19.19
GPRS1900 (3 Slot)	1880	23.44	-4.26	19.18
(3 3101)	1909.8	23.42	-4.26	19.16
00004000	1850.2	22.34	-3	19.34
GPRS1900 (4 Slot)	1880	22.31	-3	19.31
(4 3101)	1909.8	22.28	-3	19.28
Maximum Power <2>				
GSM850	824.2	31.12	-9	22.12
PCS1900	1850.2	28.05	-9	19.05

Note 1:

The Frame Power (Source-based time-averaged Power) is scaled the maximum burst average power based on time slots. The calculated methods are show as following:

Frame Power = Max burst power (1 Up Slot) - 9 dB

Frame Power = Max burst power (2 Up Slot) - 6 dB

Frame Power = Max burst power (3 Up Slot) – 4.26 dB

Frame Power = Max burst power (4 Up Slot) - 3 dB

Page 34 of 85

UMTS BAND HSDPA Setup Configuration:

- •The EUT was connected to Base Station Agilent E5515C referred to the Setup Configuration.
- •The RF path losses were compensated into the measurements.
- ·A call was established between EUT and Based Station with following setting:
- (1) Set Gain Factors(βc and βd) parameters set according to each
- (2) Set RMC 12.2Kbps+HSDPA mode.
- (3) Set Cell Power=-86dBm
- (4) Set HS-DSCH Configuration Type to FRC (H-set 1, QPSK)
- (5) Select HSDPA Uplink Parameters
- (6) Set Delta ACK, Delta NACK and Delta CQI=8
- (7) Set Ack Nack Repetition Factor to 3
- (8) Set CQI Feedback Cycle (k) to 4ms
- (9) Set CQI Repetition Factor to 2
- (10) Power Ctrl Mode=All Up bits
- •The transmitted maximum output power was recorded.

Table C.10.2.4: β values for transmitter characteristics tests with HS-DPCCH

Sub-test	βс	64	βd βc/βd βHS		βHS	CM (dB)	MPR (dB)
Sub-lest	(Note5)	β d	(SF)	-	(Note1, Note 2)	(Note 3)	(Note 3)
1	2/15	15/15	64	2/15	4/15	0.0	0.0
2	12/15(Note 4)	15/15(Note 4)	64	12/15(Note 4)	24/15	1.0	0.0
3	15/15	8/15	64	15/8	30/15	1.5	0.5
4	15/15	4/15	64	15/4	30/15	1.5	0.5

Note 1: \triangle ACK, \triangle NACK and \triangle CQI = 30/15 with $\beta_{hs} = 30/15 * \beta_c$.

Note 2: For the HS-DPCCH power mask requirement test in clause 5.2C, 5.7A, and the Error Vector Magnitude (EVM) with HS-DPCCH test in clause 5.13.1A, and HSDPA EVM with phase discontinuity in clause 5.13.1AA, \triangle ACK

and Δ NACK = 30/15 with β_{hs} = 30/15 * β_c , and Δ CQI = 24/15 with β_{hs} = 24/15 * β_c .

Note 3: CM = 1 for $\beta c/\beta d$ =12/15, hs/ c=24/15. For all other combinations of DPDCH, DPCCH and HS-DPCCH the MPR is based on the relative CM difference. This is applicable for only UEs that support HSDPA in release 6 and later releases.

Note 4: For subtest 2 the c/d ratio of 12/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signalled gain factors for the reference TFC (TF1, TF1) to c = 11/15 and d = 15/15.

Page 35 of 85

HSUPA Setup Configuration:

- · The EUT was connected to Base Station Agilent E5515C referred to the Setup Configuration.
- · The RF path losses were compensated into the measurements.
- · A call was established between EUT and Base Station with following setting *:
- (1) Call Configs = 5.2B, 5.9B, 5.10B, and 5.13.2B with QPSK
- (2) Set the Gain Factors (βc and βd) and parameters (AG Index) were set according to each specific sub-test in the following table, C11.1.3, quoted from the TS 34.121
- (3) Set Cell Power = -86 dBm
- (4) Set Channel Type = 12.2k + HSPA
- (5) Set UE Target Power
- (6) Power Ctrl Mode= Alternating bits
- (7) Set and observe the E-TFCI
- (8) Confirm that E-TFCI is equal to the target E-TFCI of 75 for sub-test 1, and other subtest's E-TFCI
- The transmitted maximum output power was recorded.

Table C.11.1.3: β values for transmitter characteristics tests with HS-DPCCH and E-DCH

Sub-t est	βс	βd	βd (SF)	βc/βd	βHS (Note1)	βес	βed (Note 4) (Note 5)	βed (SF)	βed (Codes)	CM (dB) (Note 2)	MPR (dB) (Note 2) (Note 6)	AG Index (Note 5)	E-TFCI
1	11/15 (Note 3)	15/15 (Note 3)	64	11/15 (Note 3)	22/15	209/225	1309/225	4	1	1.0	0.0	20	75
2	6/15	15/15	64	6/15	12/15	12/15	94/75	4	1	3.0	2.0	12	67
3	15/15	9/15	64	15/9	30/15	30/15	βed1: 47/15 βed2: 47/15	4 4	2	2.0	1.0	15	92
4	2/15	15/15	64	2/15	4/15	2/15	56/75	4	1	3.0	2.0	17	71
5	15/15	0	-	-	5/15	5/15	47/15	4	1	1.0	0.0	12	67

Note 1: For sub-test 1 to 4, \triangle ACK, \triangle NACK and \triangle CQI = 30/15 with β_{hs} = 30/15 * β_c . For sub-test 5, \triangle ACK, \triangle NACK and \triangle CQI = 5/15 with β_{hs} = 5/15 * β_c .

Note 2: CM = 1 for $\beta c/\beta d$ =12/15, hs/ c=24/15. For all other combinations of DPDCH, DPCCH, HS- DPCCH, E-DPDCH and E-DPCCH the MPR is based on the relative CM difference.

Note 3: For subtest 1 the c/d ratio of 11/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signalled gain factors for the reference TFC (TF1, TF1) to c = 10/15 and d = 15/15.

Note 4: In case of testing by UE using E-DPDCH Physical Layer category 1, Sub-test 3 is omitted according to TS25.306 Table 5.1g.

Note 5: βed cannot be set directly; it is set by Absolute Grant Value.

Note 6: For subtests 2, 3 and 4, UE may perform E-DPDCH power scaling at max power which could results in slightly smaller MPR values.

Report No.: AGC00069150808FH01 Page 36 of 85

UMTS BAND II

MHz (MHz) (dBm)	Mode	Frequency	Avg. Burst Power
WCDMA 1900 1880 21.32 RMC 1907.6 21.28 WCDMA 1900 1852.4 21.17 AMR 1907.6 21.12 HSDPA 1852.4 20.26 HSDPA 1880 20.23 Subtest 1 1907.6 20.21 HSDPA 1880 20.29 Subtest 2 1907.6 20.26 HSDPA 1852.4 20.34 HSDPA 1852.4 20.34 HSDPA 1852.4 20.34 HSDPA 1852.4 20.31 HSDPA 1850 20.27 HSUPA 1850 20.28 Subtest 4 1907.6 20.24 HSUPA 1880 20.16 Subtest 1 1907.6 20.18 HSUPA 1852.4 20.24 HSUPA 1850 20.26 1907.6 20.22 20.34 1880 20.26 20.22 1852.4 20.34 20.34		(MHz)	(dBm)
RMC 1880 21.32 1907.6 21.28 WCDMA 1900 1880 21.17 AMR 1907.6 21.12 HSDPA 1880 20.23 Subtest 1 1907.6 20.21 HSDPA 1880 20.23 Subtest 2 1907.6 20.26 HSDPA 1880 20.29 Subtest 3 1907.6 20.27 HSDPA 1880 20.29 IBSDA 1880 20.29 Subtest 3 1907.6 20.27 HSDPA 1852.4 20.31 HSDPA 1852.4 20.31 HSUPA 1880 20.28 Subtest 4 1907.6 20.24 HSUPA 1880 20.16 Subtest 1 1907.6 20.18 HSUPA 1880 20.16 Subtest 2 1907.6 20.18 HSUPA 1880 20.26 HSUPA 1880 20.26 HSUPA 1880 20.26 HSUPA 1880 20.26 HSUPA 1880 20.29 HSUPA 1880 20.36 HSUPA 1880 20.38 HSUPA 1880 20.38 HSUPA 1880 20.38 HSUPA 1880 20.39 HSUPA 1852.4 20.34	WCDMA 1900		
1907.6 21.28			
MCDMA 1900 AMR 1907.6 1880 21.14 HSDPA Subtest 1 1880 20.23 Subtest 1 1907.6 20.21 HSDPA Subtest 2 1882.4 1880 20.29 1885.4 1880 20.29 Subtest 3 1907.6 20.26 HSDPA Subtest 3 1907.6 20.27 HSDPA Subtest 4 1880 20.29 Subtest 4 1880 20.29 Subtest 5 1852.4 1880 20.29 Subtest 3 1907.6 20.27 HSDPA Subtest 4 1880 20.28 Subtest 4 1907.6 20.24 HSUPA Subtest 1 1907.6 20.24 HSUPA Subtest 2 1880 20.26 HSUPA Subtest 3 1880 20.26 HSUPA Subtest 4 1880 20.29 HSUPA Subtest 4 1880 20.36 HSUPA Subtest 4 1907.6 20.28 HSUPA Subtest 5			
AMR 1880 21.14 HSDPA 1852.4 20.26 Subtest 1 1880 20.23 HSDPA 1852.4 20.37 Subtest 2 1907.6 20.29 HSDPA 1852.4 20.34 Subtest 3 1907.6 20.29 HSDPA 1852.4 20.31 Subtest 4 1907.6 20.27 HSUPA 1852.4 20.21 HSUPA 1852.4 20.24 HSUPA 1852.4 20.22 HSUPA 1852.4 20.24 HSUPA 1852.4 20.24 HSUPA 1852.4 20.24 HSUPA 1852.4 20.24 HSUPA 1852.4 20.34 Subtest 3 1907.6 20.22 HSUPA 1852.4 20.34 HSUPA 1852.4 20.32 HSUPA 1850 20.36 HSUPA 1850 20.36 HSUPA 1850 20.34 HSUPA 1850 20.34 HSUPA 1850 20.34 HSUPA 1850 20.34 Subtest 5 1850 20.34 HSUPA <td< td=""><td>WCDMA 1900</td><td></td><td></td></td<>	WCDMA 1900		
HSDPA			
HSDPA	7.1011.	1907.6	
Subtest 1 1907.6 20.21 HSDPA 1880 20.29 Subtest 2 1907.6 20.26 HSDPA 1880 20.29 HSDPA 1852.4 20.34 HSDPA 1880 20.29 Subtest 3 1907.6 20.27 HSDPA 1880 20.29 HSDPA 1880 20.29 HSDPA 1852.4 20.31 HSDPA 1880 20.28 Subtest 4 1907.6 20.24 HSUPA 1880 20.16 Subtest 1 1907.6 20.18 HSUPA 1880 20.16 Subtest 2 1907.6 20.18 HSUPA 1880 20.26 HSUPA 1880 20.29 HSUPA 1880 20.29 HSUPA 1880 20.29 HSUPA 1880 20.29 HSUPA 1852.4 20.34 HSUPA 1880 20.36 HSUPA 20.34	HSDDA	1852.4	20.26
HSDPA 1852.4 20.37 HSDPA 20.29 HSDPA 1880 20.29 HSDPA 1880 20.26 HSDPA 1880 20.29 HSDPA 1880 20.29 HSDPA 1880 20.29 HSDPA 1880 20.27 HSDPA 1852.4 20.31 HSDPA 1880 20.28 Subtest 4 1907.6 20.24 HSUPA 1852.4 20.22 HSUPA 1880 20.16 Subtest 1 1907.6 20.18 HSUPA 1852.4 20.24 HSUPA 1852.4 20.24 HSUPA 1852.4 20.22 HSUPA 1880 20.26 HSUPA 1852.4 20.22 HSUPA 1880 20.26 HSUPA 1880 20.26 HSUPA 1880 20.26 HSUPA 1880 20.29 HSUPA 1880 20.36 HSUPA 1852.4 20.34 HSUPA 1852.4 20.34 HSUPA 1852.4 20.34		1880	20.23
HSDPA Subtest 2 1907.6 20.26	Subtest	1907.6	20.21
Subtest 2 1880 20.29 1897.6 20.26 HSDPA 1852.4 20.31 HSDPA 1852.4 20.21 1852.4 20.28 1852.4 20.24 HSUPA 1852.4 20.24 1852.4 20.24 1852.4 20.24 1852.4 20.24 1852.4 20.24 1852.4 20.24 1852.4 20.24 1850.4 20.26 1850.4 20.34 1850.4 20.33 1850.4 20.32 1850.4 20.36 1850.4 20.36 1850.4 20.34 1850.4 20.34 1850.4 20.34 1850.4 20.34 1850.4 20.34 1850.4 20.34 1850.4 20.34 1850.4 20.34 1850.4 20.34 1850.4 20.34 <td>LICDDA</td> <td>1852.4</td> <td>20.37</td>	LICDDA	1852.4	20.37
1907.6 20.26 HSDPA 1852.4 20.34 Subtest 3 1907.6 20.27 HSDPA 1852.4 20.31 HSDPA 1880 20.28 Subtest 4 1907.6 20.24 HSUPA 1852.4 20.16 Subtest 2 1907.6 20.24 HSUPA 1852.4 20.22 HSUPA 1880 20.16 Subtest 2 1907.6 20.24 HSUPA 1880 20.26 HSUPA 1852.4 20.32 HSUPA 1852.4 20.34 Subtest 3 1907.6 20.33 HSUPA 1852.4 20.32 HSUPA 1852.4 20.32 HSUPA 1880 20.36 Subtest 4 1907.6 20.28 HSUPA 1852.4 20.34 HSUPA 1852.4 20.32 HSUPA 1852.4 20.36 HSUPA 1852.4 20.34 HSUPA 20.37 HS		1880	20.29
HSDPA Subtest 3 1880 20.29	Sublest 2	1907.6	20.26
Subtest 3 1880 20.29 HSDPA Subtest 4 1852.4 20.31 HSUPA 1880 20.28 Subtest 1 1852.4 20.22 HSUPA 1852.4 20.16 Subtest 2 1852.4 20.24 HSUPA 1852.4 20.24 Subtest 3 1852.4 20.34 HSUPA 1880 20.29 Subtest 3 1907.6 20.33 HSUPA 1852.4 20.32 Subtest 4 1907.6 20.28 HSUPA 1852.4 20.36 Subtest 5 1852.4 20.34 HSUPA 1852.4 20.34 Subtest 5 1852.4 20.34	HODDA	1852.4	20.34
1907.6 20.27 HSDPA 1852.4 20.31 HSUPA 1852.4 20.22 HSUPA 1880 20.16 Subtest 1 1907.6 20.18 HSUPA 1852.4 20.24 HSUPA 1880 20.16 Subtest 2 1907.6 20.28 HSUPA 1880 20.26 Subtest 3 1880 20.29 HSUPA 1852.4 20.34 HSUPA 1852.4 20.33 HSUPA 1852.4 20.32 HSUPA 1880 20.36 Subtest 4 1907.6 20.28 HSUPA 1852.4 20.34 HSUPA 1852.4 20.34 HSUPA 1852.4 20.35 HSUPA 1852.4 20.36 HSUPA 1852.4 20.34 HSUPA 1852.4 20.34 HSUPA 1852.4 20.34 HSUPA 1850 20.37 Subtest 5		1880	20.29
Subtest 4 1880 20.28 Subtest 4 1907.6 20.24 HSUPA 1852.4 20.22 HSUPA 1852.4 20.24 HSUPA 1852.4 20.24 HSUPA 1880 20.26 Subtest 2 1907.6 20.22 HSUPA 1880 20.26 Subtest 3 1907.6 20.33 HSUPA 1880 20.29 Subtest 4 1880 20.32 HSUPA 1852.4 20.32 HSUPA 1880 20.36 HSUPA 1880 20.36 HSUPA 1852.4 20.34 HSUPA 1850 20.37 HSUPA 1880 20.37 HSUPA 1880 20.37	Subtest 3	1907.6	20.27
Subtest 4 1880 20.28 1907.6 20.24 HSUPA Subtest 1 1880 20.22 1852.4 20.22 1880 20.16 Subtest 1 1907.6 20.18 1852.4 20.24 1880 20.26 Subtest 2 1880 20.16 20.18 1852.4 20.24 1880 20.26 1907.6 20.22 1852.4 20.34 1880 20.29 Subtest 3 1907.6 20.33 1852.4 20.32 HSUPA Subtest 4 1880 20.36 1850 20.28 HSUPA Subtest 5	HODDA	1852.4	20.31
HSUPA Subtest 3 1907.6 20.24 HSUPA Subtest 4 20.22 HSUPA 1880 20.16 1907.6 20.18 1852.4 20.24 1880 20.26 1880 20.26 1880 20.26 1907.6 20.22 1852.4 20.34 HSUPA 1880 20.29 Subtest 3 1907.6 20.33 HSUPA 1880 20.32 HSUPA 1880 20.36 HSUPA 1852.4 20.34 HSUPA 1852.4 20.34 HSUPA 1852.4 20.34 HSUPA 1852.4 20.34 HSUPA 1880 20.37		1880	20.28
HSUPA Subtest 1 1880 20.16 1907.6 20.18 HSUPA Subtest 2 1880 20.24 1880 20.26 Subtest 2 1907.6 20.22 HSUPA Subtest 3 1880 20.29 1852.4 20.34 1880 20.29 Subtest 3 1907.6 20.33 HSUPA Subtest 4 1880 20.36 1852.4 20.36 1880 20.36 HSUPA Subtest 5	Subtest 4	1907.6	20.24
Subtest 1 1880 20.16 HSUPA 1852.4 20.24 Subtest 2 1880 20.26 HSUPA 1852.4 20.34 Subtest 3 1907.6 20.33 HSUPA 1852.4 20.32 HSUPA 1880 20.32 HSUPA 1880 20.36 HSUPA 1852.4 20.34 HSUPA 1852.4 20.34 Subtest 5 1880 20.37		1852.4	20.22
HSUPA Subtest 4 1907.6 20.18 HSUPA 1880 20.26 1907.6 20.22 1907.6 20.22 1852.4 20.34 1880 20.29 1852.4 20.34 1880 20.29 1852.4 20.33 1907.6 20.33 1907.6 20.32 HSUPA 1880 20.36 1880 20.36 HSUPA 1880 20.36 1852.4 20.32 HSUPA 1880 20.36 Subtest 4 1907.6 20.28 HSUPA 1880 20.37		1880	20.16
HSUPA 1880 20.26 Subtest 2 1907.6 20.22 HSUPA 1852.4 20.34 Subtest 3 1907.6 20.33 HSUPA 1852.4 20.32 HSUPA 1880 20.36 Subtest 4 1907.6 20.28 HSUPA 1852.4 20.34 HSUPA 1852.4 20.34 Subtest 5 1880 20.37 Subtest 6 1880 20.37 Subtest 7 1880 20.37 Subtest 8 1880 20.37 Subtest 9 1880 20.37	Subtest 1	1907.6	20.18
HSUPA Subtest 2 1880 20.26		1852.4	20.24
1907.6 20.22			20.26
HSUPA Subtest 3 HSUPA Subtest 4 1852.4 1880 20.29 1907.6 20.33 1852.4 20.32 1880 20.36 1890.6 1890.6 1852.4 1800 20.28 1852.4 1852.4 1852.4 1852.4 1852.4 1852.4 1852.4 1852.4 1852.4 1852.4 1852.4 1852.4 1852.4 1852.4 1852.4 1852.4 1852.4	Subtest 2		20.22
HSUPA Subtest 3 1880 20.29 1907.6 20.33 HSUPA Subtest 4 1880 20.32 1880 20.36 1880 20.36 1890.6 20.38 1890.6 20.28 1852.4 20.34 20.34 20.37			20.34
Subtest 3 1907.6 20.33 HSUPA Subtest 4 1852.4 20.32 1880 20.36 1907.6 20.38 1890 1852.4 20.34 1852.4 20.34 1880 20.37			20.29
HSUPA Subtest 5 1852.4 20.32 20.36 20.36 20.36 20.28 20.28 20.34 20.34 20.37	Subtest 3		
HSUPA Subtest 4 1880 20.36 1907.6 20.28 HSUPA Subtest 5 1880 20.37			
Subtest 4 1907.6 20.28 HSUPA 1852.4 20.34 Subtest 5 1880 20.37			
HSUPA 1852.4 20.34 1880 20.37	Subtest 4		
HSUPA 1880 20.37			
Subtest 5			
	Subtest 5		

Page 37 of 85

UMTS BAND V

Mode	Frequency	Avg. Burst Power
Wode	(MHz)	(dBm)
MODMA 050	826.4	21.28
WCDMA 850	836.6	21.26
RMC	846.6	21.23
14/ODMA 050	826.4	21.17
WCDMA 850	836.6	21.16
AMR	846.6	21.13
110004	826.4	20.31
HSDPA	836.6	20.26
Subtest 1	846.6	20.24
110004	826.4	20.25
HSDPA	836.6	20.22
Subtest 2	846.6	20.19
110004	826.4	20.34
HSDPA	836.6	20.29
Subtest 3	846.6	20.27
110004	826.4	20.34
HSDPA	836.6	20.29
Subtest 4	846.6	20.26
1101104	826.4	20.24
HSUPA	836.6	20.22
Subtest 1	846.6	20.16
1101104	826.4	20.23
HSUPA	836.6	20.21
Subtest 2	846.6	20.17
1101104	826.4	20.33
HSUPA	836.6	20.26
Subtest 3	846.6	20.23
1101104	826.4	20.35
HSUPA	836.6	20.31
Subtest 4	846.6	20.28
	826.4	20.34
HSUPA	836.6	20.26
Subtest 5	846.6	20.29

Page 38 of 85

According to 3GPP 25.101 sub-clause 6.2.2, the maximum output power is allowed to be reduced by following the table.

Table 6.1aA: UE maximum output power with HS-DPCCH and E-DCH

1 000 0 1 100 0 0 1 100 0 1 1 1 1 1 1 1									
UE Transmit Channel Configuration	CM(db)	MPR(db)							
For all combinations of ,DPDCH,DPCCH HS-DPDCH,E-DPDCH and E-DPCCH	0≤ CM≤3.5	MAX(CM-1,0)							
Note: CM=1 for β_c/β_d =12/15, β_{hs}/β_c =24/15.For all other combinations of DPDCH, DPCCH, HS-DPCCH,									
E-DPDCH and E-DPCCH the MPR is based on the relative CM difference.									

The device supports MPR to solve linearity issues (ACLR or SEM) due to the higher peak-to average ratios (PAR) of the HSUPA signal. This prevents saturating the full range of the TX DAC inside of device and provides a reduced power output to the RF transceiver chip according to the Cubic Metric (a function of the combinations of DPDCH, DPCCH, HS-DPCCH, E-DPDCH and E-DPCCH).

When E-DPDCH channels are present the beta gains on those channels are reduced firsts to try to get the power under the allowed limit. If the beta gains are lowered as far as possible, then a hard limiting is applied at the maximum allowed level.

The SW currently recalculates the cubic metric every time the beta gains on the E-DPDCH are reduced. The cubic metric will likely get lower each time this is done .However, there is no reported reduction of maximum output power in the HSUPA mode since the device also provides a compensation for the power back-off by increasing the gain of TX_AGC in the transceiver (PA) device.

The end effect is that the DUT output power is identical to the case where there is no MPR in the device.

Page 39 of 85

WIFI

Mode	Data Rate (Mbps)	Channel	Frequency(MHz)	Avg. Burst Power(dBm)
		01	2412	11.51
802.11b	1	06	2437	11.27
		11	2462	11.22
		01	2412	9.26
802.11g	6	06	2437	9.12
		11	2462	9.08
		01	2412	9.08
802.11n(20)	6.5	06	2437	9.05
		11	2462	9.02
		03	2422	7.86
802.11n(40)	13.5	06	2437	7.51
		09	2452	7.42

Bluetooth_V3.0

Modulation	Channel	Frequency(MHz)	Average Power (dBm)
	0	2402	-1.43
GFSK	39	2441	-1.19
	78	2480	-0.24
	0	2402	-2.25
π /4-DQPSK	39	2441	-2.05
	78	2480	-1.26
	0	2402	-2.39
8-DPSK	39	2441	-2.19
	78	2480	-1.36

Bluetooth_V4.0

Modulation	Channel	Frequency(MHz)	Peak Burst Power (dBm)
	0	2402	-7.58
GFSK	19	2440	-7.74
	39	2480	-6.99

Page 40 of 85

12. TEST RESULTS

12.1. SAR Test Results Summary

12.1.1. Test position and configuration

Head SAR was performed with the device configured in the positions according to IEEE 1528-2003, and Body SAR was performed with the device 10mm from the phantom.

12.1.2. Operation Mode

- 1. Per KDB 447498 D01 v05r02 ,for each exposure position, if the highest 1-g SAR is ≤ 0.8 W/kg, testing for low and high channel is optional.
- 2. Per KDB 865664 D01 v01r04,for each frequency band, if the measured SAR is ≥0.8W/Kg, testing for repeated SAR measurement is required, that the highest measured SAR is only to be tested. When the SAR results are near the limit, the following procedures are required for each device to verify these types of SAR measurement related variation concerns by repeating the highest measured SAR configuration in each frequency band.
 - (1) When the original highest measured SAR is \geq 0.8W/Kg, repeat that measurement once.
 - (2) Perform a second repeated measurement only if the ratio of largest to smallest SAR for the original and first repeated measurements is >1.20 or when the original or repeated measurement is >1.45 W/Kg.
 - (3) Perform a third repeated measurement only if the original, first and second repeated measurement is ≥1.5 W/Kg and ratio of largest to smallest SAR for the original, first and second measurement is ≥ 1.20.
- 3. Body-worn exposure conditions are intended to voice call operations, therefore GSM voice call mode is selected to be test.
- 4. Per KDB 648474 D04 v01r02,when the reported SAR for a body-worn accessory measured without a headset connected to the handset is ≤1.2W/Kg, SAR testing with a headset connected is not required.
- 5. Per 941225 D06 v02, when the overall device length and width are > 9cm×5cm, Hotspot mode with a test separation distance of 10mm. For device with form factors smaller than 9cm×5cm, Hotspot mode with a test separation distance of 5mm. Body SAR was also performed with the headset attached and without.
- 6. Per 248227 D01 v02r01, SAR is not required for 802.11g channels when the maximum average output power is less than 1/4dB higher than measured on the corresponding 802.11b channels.
- 7. Maximum Scaling SAR in order to calculate the Maximum SAR values to test under the standard Peak Power, Calculation method is as follows:

 Maximum Scaling SAR =tested SAR (Max.) ×[maximum turn-up power (mw)/ maximum measurement output power(mw)]

Page 41 of 85

12.1.3. Test Result

SAR MEASURE	MENT								
Depth of Liquid	(cm):>15			Relative Humidity (%): 49.2					
Product: Smart	Phone								
Test Mode: GSN	M850 with GMS	K modulati	on						
Position	Mode	Ch.	Fr. (MHz)	Power Drift (<±0.2)	SAR (1g) (W/kg)	Max. Turn-up Power (dBm)	Meas. output Power (dBm)	Scaled SAR (W/Kg)	Limit W/kg
SIM 1 Card									
Left Cheek	voice	190	836.6	0.18	0.034	31.50	31.19	0.037	1.6
Left Tilt	voice	190	836.6	0.13	0.012	31.50	31.19	0.013	1.6
Right Cheek	voice	190	836.6	-0.02	0.024	31.50	31.19	0.026	1.6
Right Tilt	voice	190	836.6	0.07	0.016	31.50	31.19	0.017	1.6
Body back	voice	190	836.6	0.11	0.100	31.50	31.19	0.107	1.6
Body front	voice	190	836.6	0.02	0.035	31.50	31.19	0.038	1.6
Left Cheek	GPRS-2 slot	190	836.6	0.17	0.049	29	28.34	0.057	1.6
Left Tilt	GPRS-2 slot	190	836.6	-0.14	0.020	29	28.34	0.023	1.6
Right Cheek	GPRS-2 slot	190	836.6	0.10	0.038	29	28.34	0.044	1.6
Right Tilt	GPRS-2 slot	190	836.6	0.20	0.026	29	28.34	0.030	1.6
Body back	GPRS-2 slot	190	836.6	0.04	0.200	29	28.34	0.233	1.6
Body front	GPRS-2 slot	190	836.6	-0.19	0.059	29	28.34	0.069	1.6
Edge 1 (Top)	GPRS-2 slot	190	836.6	0.11	0.013	29	28.34	0.015	1.6
Edge 2(Right)	GPRS-2 slot	190	836.6	-0.05	0.094	29	28.34	0.109	1.6
Edge 3(Bottom)	GPRS-2 slot	190	836.6	-0.13	0.025	29	28.34	0.029	1.6
Edge 4(Left)	GPRS-2 slot	190	836.6	-0.10	0.120	29	28.34	0.140	1.6
SIM 2 Card									
Left Cheek	GPRS-2 slot	190	836.6	-0.12	0.045	29	28.34	0.052	1.6
Body back	GPRS-2 slot	190	836.6	0.04	0.151	29	28.34	0.176	1.6

[•] When the 1-g Reported SAR is \leq 0.8 W/kg, testing for low and high channel is optional. Refer to KDB 447498. • The test separation for body is 10mm of all above table.

Page 42 of 85

SAR MEASURE											
Depth of Liquid	(cm):>15			Relative Humidity (%): 50.9							
Product: Smart	Phone										
Test Mode: PCS	S1900 with GMS	SK modula	ation								
Position	Mode	Ch.	Fr. (MHz)	Power Drift (<±0.2)	SAR (1g) (W/kg)	Max. Turn-up Power (dBm)	Meas. output Power (dBm)	Scaled SAR (W/Kg)	Limit W/kg		
SIM 1 Card											
Left Cheek	voice	661	1880.0	0.18	0.256	29.50	28.18	0.347	1.6		
Left Tilt	voice	661	1880.0	0.10	0.050	29.50	28.18	0.068	1.6		
Right Cheek	voice	661	1880.0	0.13	0.126	29.50	28.18	0.171	1.6		
Right Tilt	voice	661	1880.0	0.06	0.055	29.50	28.18	0.075	1.6		
Body back	voice	661	1880.0	0.05	0.390	29.50	28.18	0.529	1.6		
Body front	voice	661	1880.0	0.03	0.237	29.50	28.18	0.321	1.6		
Left Cheek	GPRS-2 slot	661	1880.0	-0.03	0.282	26	25.34	0.328	1.6		
Left Tilt	GPRS-2 slot	661	1880.0	0.01	0.063	26	25.34	0.073	1.6		
Right Cheek	GPRS-2 slot	661	1880.0	0.03	0.388	26	25.34	0.452	1.6		
Right Tilt	GPRS-2 slot	661	1880.0	0.10	0.097	26	25.34	0.113	1.6		
Body back	GPRS-2 slot	661	1880.0	0.02	0.597	26	25.34	0.695	1.6		
Body front	GPRS-2 slot	661	1880.0	-0.08	0.380	26	25.34	0.442	1.6		
Edge 1 (Top)	GPRS-2 slot	661	1880.0	-0.04	0.059	26	25.34	0.069	1.6		
Edge 2(Right)	GPRS-2 slot	661	1880.0	0.11	0.267	26	25.34	0.311	1.6		
Edge 3(Bottom)	GPRS-2 slot	661	1880.0	-0.10	0.582	26	25.34	0.678	1.6		
Edge 4(Left)	GPRS-2 slot	661	1880.0	0.17	0.298	26	25.34	0.347	1.6		
SIM 2 Card											
Right Cheek	GPRS-2 slot	661	1880.0	-0.20	0.347	26	25.34	0.404	1.6		
Body back	GPRS-2 slot	661	1880.0	0.06	0.509	26	25.34	0.593	1.6		

[•] When the 1-g Reported SAR is \leq 0.8 W/kg, testing for low and high channel is optional. Refer to KDB 447498. • The test separation for body is 10mm of all above table.

Page 43 of 85

SAR MEASURI	SAR MEASUREMENT											
Depth of Liquid	(cm):>15			Relative Humidity (%): 50.9								
Product: Smart	Product: Smart Phone											
Test Mode: WCDMA Band II with QPSK modulation												
Position	Mode	Ch.	Fr. (MHz)	Power Drift (<±0.2)	SAR (1g) (W/kg)	Max. Turn-up Power (dBm)	Meas. output Power (dBm)	Scaled SAR (W/Kg)	Limit W/kg			
SIM 1 Card												
Left Cheek	RMC 12.2kbps	9400	1880	0	0.209	22	21.32	0.244	1.6			
Left Tilt	RMC 12.2kbps	9400	1880	-0.06	0.062	22	21.32	0.073	1.6			
Right Cheek	RMC 12.2kbps	9400	1880	0.06	0.216	22	21.32	0.253	1.6			
Right Tilt	RMC 12.2kbps	9400	1880	0.12	0.071	22	21.32	0.083	1.6			
Body back	RMC 12.2kbps	9262	1852.4	0.01	0.809	22	21.35	0.940	1.6			
Body back	RMC 12.2kbps	9400	1880	-0.15	0.797	22	21.32	0.932	1.6			
Body back	RMC 12.2kbps	9538	1907.6	0.16	0.644	22	21.28	0.760	1.6			
Body front	RMC 12.2kbps	9400	1880	-0.10	0.418	22	21.32	0.489	1.6			
Edge 1 (Top)	RMC 12.2kbps	9400	1880	-0.16	0.043	22	21.32	0.050	1.6			
Edge 2(Right)	RMC 12.2kbps	9400	1880	0.04	0.113	22	21.32	0.132	1.6			

Edge 4(Left) Note:

Edge 3(Bottom)

0.04

-0.16

0.522

0.374

1880

1880

22

22

21.32

21.32

0.610

0.437

1.6

1.6

9400

9400

RMC 12.2kbps

RMC 12.2kbps

[•] When the 1-g Reported SAR is ≤ 0.8 W/kg, testing for low and high channel is optional. Refer to KDB 447498.

[•]The test separation for body is 10mm of all above table.

Page 44 of 85

SAR MEASURE	EMENT											
Depth of Liquid		Relative Humidity (%): 49.2										
Product: Smart	Phone											
Test Mode: WCDMA Band V with QPSK modulation												
Position	Mode	Ch.	Fr. (MHz)	Power Drift (<±0.2)	SAR (1g) (W/kg)	Max. Turn-up Power (dBm)	Meas. output Power (dBm)	Scaled SAR (W/Kg)	Limit W/kg			
SIM 1 Card												
Left Cheek	RMC 12.2kbps	4183	836.6	0.05	0.015	22	21.26	0.018	1.6			
Left Tilt	RMC 12.2kbps	4183	836.6	-0.12	0.010	22	21.26	0.012	1.6			
Right Cheek	RMC 12.2kbps	4183	836.6	- 0.12	0.022	22	21.26	0.026	1.6			
Right Tilt	RMC 12.2kbps	4183	836.6	0.11	0.012	22	21.26	0.014	1.6			
Body back	RMC 12.2kbps	4183	836.6	0.13	0.105	22	21.26	0.125	1.6			
Body front	RMC 12.2kbps	4183	836.6	0.17	0.030	22	21.26	0.036	1.6			
Edge 1 (Top)	RMC 12.2kbps	4183	836.6	0.20	0.004	22	21.26	0.005	1.6			
Edge 2(Right)	RMC 12.2kbps	4183	836.6	-0.09	0.055	22	21.26	0.065	1.6			
Edge 3(Bottom)	RMC 12.2kbps	4183	836.6	0.12	0.011	22	21.26	0.013	1.6			
Edge 4(Left)	RMC 12.2kbps	4183	836.6	0.01	0.044	22	21.26	0.052	1.6			

[•] When the 1-g Reported SAR is ≤ 0.8 W/kg, testing for low and high channel is optional. Refer to KDB 447498.

[•]The test separation for body is 10mm of all above table.

Page 45 of 85

SAR MEASURE	SAR MEASUREMENT											
Depth of Liquid	(cm):>15			Relative Humidity (%): 53.2								
Product: Smart	Phone											
Test Mode:802.11b												
Position	Mode	Ch.	Fr. (MHz)	Power Drift (<±0.2)	SAR (1g) (W/kg)	Max. Turn-up Power (dBm)	Meas. output Power (dBm)	Scaled SAR (W/Kg)	Limit W/kg			
Left Cheek	DTS	6	2437	-0.02	0.086	12	11.27	0.102	1.6			
Left Tilt	DTS	6	2437	0.01	0.120	12	11.27	0.142	1.6			
Right Cheek	DTS	6	2437	-0.20	0.108	12	11.27	0.128	1.6			
Right Tilt	DTS	6	2437	-0.13	0.135	12	11.27	0.160	1.6			
Body back	DTS	6	2437	0.02	0.155	12	11.27	0.183	1.6			
Body front	DTS	6	2437	0.06	0.123	12	11.27	0.146	1.6			
Edge 1 (Top)	DTS	6	2437	-0.11	0.137	12	11.27	0.162	1.6			
Edge 2(Right)	DTS	6	2437	0.09	0.067	12	11.27	0.079	1.6			
Edge 3(Bottom)	DTS	6	2437	0.03	0.028	12	11.27	0.033	1.6			
Edge 4(Left)	DTS	6	2437	0.12	0.116	12	11.27	0.137	1.6			

- According to KDB248227, SAR is not required for 802.11n HT20/HT40 channels when the maximum average output power is less than 1/4 dB higher than that measured on the corresponding 802.11a/b channels.

 All of above "DTS" means data transmitters.
- The test separation of all above table for body part is 10mm.

Repeated SAR										
Product: Smart Phone										
Test Mode: WCDMA Band II with QPSK modulation										
Position	Mode	Ch.	Fr. (MHz)	Power Drift (<±0.2)	Once SAR (1g) (W/kg)	Power Drift (<±0.2)	Twice SAR (1g) (W/kg)	Power Drift (<±0.2)	Third SAR (1g) (W/kg)	Limit W/kg
Body back	RMC 12.2kbps	9262	1852.4	0.11	0.537					1.6

Page 46 of 85

Simultaneous Multi-band Transmission Evaluation:

Application Simultaneous Transmission information:

NO	Simultaneous state		Portable Handset	
NO	Simultaneous State	Head	Body-worn	Hotspot
1	GSM(voice)+WLAN 2.4GHz (data)	Yes	Yes	-
2	WCDMA(voice)+WLAN 2.4GHz (data)	Yes	Yes	-
3	GSM(voice)+Bluetooth(data)	-	Yes	-
4	WCDMA(voice)+Bluetooth(data)	-	Yes	-
5	GSM (Data) + Bluetooth(data)	-	Yes	
6	GSM (Data) + WLAN 2.4GHz (data)	Yes	Yes	Yes
7	WCDMA (Data) + Bluetooth(data)		Yes	
8	WCDMA (Data) + WLAN 2.4GHz (data)	Yes	Yes	Yes

NOTE:

- 1. WLAN and BT share the same antenna, and cannot transmit simultaneously.
- 2. Simultaneous with every transmitter must be the same test position.
- 3. KDB 447498 D01, BT SAR is excluded as below table.
- 4. KDB 447498 D01, for handsets the test separation distance is determined by the smallest distance between the outer surface of the device and the user; which is 0mm for head SAR and 10mm for body-worn SAR.
- 5. If the test separation distance is <5mm, 5mm is used for excluded SAR calculation.
- 6. According to KDB447497 D01 4.3.2, simultaneous transmission SAR test exclusion is as follow:
 - (1) Simultaneous transmission SAR test exclusion is determined for each operating configuration and exposure condition according to the reported standalone SAR of each applicable simultaneous transmitting antenna.
 - (2) Any transmitters and antennas should be considered when calculating simultaneous mode.
 - (3) For mobile phone and PC, it's the sum of all transmitters and antennas at the same mode with same position in each applicable exposure condition
 - (4) When the standalone SAR test exclusion of section 4.3.1 is applied to an antenna that transmits simultaneously with other antennas, the standalone SAR must be estimated according to the following to determine simultaneous transmission SAR test exclusion:

(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)]·[$\sqrt{f(GHz)/x}$] W/kg for test separation distances ≤ 50 mm;

where x = 7.5 for 1-g SAR, and x = 18.75 for 10-g SAR.

7. When the sum of SAR is larger than the limit, SAR test exclusion is determined by the SAR to peak location separation ratio. The simultaneous transmitting antennas in each operating mode and exposure condition combination must be considered one pair at a time to determine the SAR to peak location separation ratio to qualify for test exclusion. The ratio is determined by (SAR1 + SAR2)1.5/Ri, rounded to two decimal digits, and must be ≤ 0.04 for all antenna pairs in the configuration to qualify for 1-g SAR test exclusion.

Page 47 of 85

Estimated SAR			luding Tune-up ance	Separation Distance (mm)	Estimated SAR (W/kg)	
		dBm	mW	Distance (IIIII)	(vv/kg)	
ВТ	Head	0	1	0	0.042	
ы	Body	0	1	10	0.021	

Maximum test results (WWAN) with BT SAR: BT: Head (0 cm gap): 0.042 W/kg and Body (1.0cm gap): 0.021W/kg

Page 48 of 85

Sum of the SAR for GSM 850 &Wi-Fi & BT:

RF Exposure Conditions	Test Position	Simultaneous Transmission Scenario			Σ1-g SAR	SPLSR
		GSM 850 Band	WI-Fi DTS Band	Bluetooth	(W/Kg)	(Yes/No)
	Left Touch	0.037	0.102		0.139	No
Head	Left Tilt	0.013	0.142		0.155	No
(voice)	Right Touch	0.026	0.128		0.154	No
	Right Tilt	0.017	0.160		0.177	No
	Door.	0.107	0.183		0.290	No
Dadeam	Rear	0.107		0.021	0.128	No
Body-worn	Frant	0.038	0.146		0.184	No
	Front	0.038		0.021	0.059	No
	Left Touch	0.057	0.102		0.159	No
Head (VoIP)	Left Tilt	0.023	0.142		0.165	No
	Right Touch	0.044	0.128		0.172	No
	Right Tilt	0.030	0.160		0.190	No
	Rear	0.233	0.183		0.416	No
	Front	0.069	0.146		0.215	No
	Edge 1	0.015	0.162		0.177	No
	Edge 2	0.109	0.079		0.188	No
	Edge 3	0.029	0.033		0.062	No
Uetonet	Edge 4	0.140	0.137		0.277	No
Hotspot	Rear	0.233		0.021	0.254	No
	Front	0.069		0.021	0.090	No
	Edge 1	0.015		0.021	0.036	No
	Edge 2	0.109		0.021	0.130	No
	Edge 3	0.029		0.021	0.050	No
	Edge 4	0.140		0.021	0.161	No

- According to KDB 447498 D01 General RF Exposure Guidance, when the simultaneous transmission SAR is less than 1.6 W/Kg, SPLSR assessment is not required.
- SPLSR mean is "The SAR to Peak Location Separation Ratio "

Page 49 of 85

Sum of the SAR for GSM 1900 &Wi-Fi & BT:

RF Exposure Conditions	Test Position	Simultane	eous Transmissior	Σ1-g SAR	SPLSR	
		GSM 1900 Band	WI-Fi DTS Band	Bluetooth	(W/Kg)	(Yes/No)
	Left Touch	0.347	0.102		0.449	No
Head	Left Tilt	0.068	0.142		0.210	No
(voice)	Right Touch	0.171	0.128		0.299	No
	Right Tilt	0.075	0.160		0.235	No
	Rear	0.529	0.183		0.712	No
Bady warn	Real	0.529		0.021	0.550	No
Body-worn	Front	0.321	0.146		0.467	No
		0.321		0.021	0.342	No
	Left Touch	0.328	0.102		0.430	No
Head (VoIP)	Left Tilt	0.073	0.142		0.215	No
	Right Touch	0.452	0.128		0.580	No
	Right Tilt	0.113	0.160		0.273	No
	Rear	0.695	0.183		0.878	No
	Front	0.442	0.146		0.588	No
	Edge 1	0.069	0.162		0.231	No
	Edge 2	0.311	0.079		0.390	No
	Edge 3	0.678	0.033		0.711	No
Hetomot	Edge 4	0.347	0.137		0.484	No
Hotspot	Rear	0.695		0.021	0.716	No
	Front	0.442		0.021	0.463	No
	Edge 1	0.069		0.021	0.090	No
	Edge 2	0.311		0.021	0.332	No
	Edge 3	0.678		0.021	0.699	No
	Edge 4	0.347		0.021	0.368	No

- According to KDB 447498 D01 General RF Exposure Guidance, when the simultaneous transmission SAR is less than 1.6 W/Kg, SPLSR assessment is not required.
- SPLSR mean is "The SAR to Peak Location Separation Ratio "

Page 50 of 85

Sum of the SAR for WCDMA Band II &Wi-Fi & BT:

RF Exposure Conditions	Test Position	Simultaneous Transmission Scenario			Σ1-g SAR	SPLSR
		WCDMA Band II	Wi-Fi DTS Band	Bluetooth	(W/Kg)	(Yes/No)
	Left Touch	0.244	0.102		0.346	No
Head	Left Tilt	0.073	0.142		0.215	No
пеац	Right Touch	0.253	0.128		0.381	No
	Right Tilt	0.083	0.160		0.243	No
	Rear	0.940	0.183		1.123	No
	Front	0.489	0.146		0.635	No
	Edge 1	0.050	0.162		0.212	No
	Edge 2	0.132	0.079		0.211	No
	Edge 3	0.610	0.033		0.643	No
Hotopot	Edge 4	0.437	0.137		0.574	No
Hotspot	Rear	0.940		0.021	0.961	No
	Front	0.489		0.021	0.510	No
	Edge 1	0.050		0.021	0.071	No
	Edge 2	0.132		0.021	0.153	No
	Edge 3	0.610		0.021	0.631	No
	Edge 4	0.437		0.021	0.458	No

- According to KDB 447498 D01 General RF Exposure Guidance, when the simultaneous transmission SAR is less than 1.6 W/Kg, SPLSR assessment is not required.
- SPLSR mean is "The SAR to Peak Location Separation Ratio "

Page 51 of 85

Sum of the SAR for WCDMA Band V &Wi-Fi & BT:

RF Exposure Conditions	Test Position	Simultaneous Transmission Scenario			Σ1-g SAR	SPLSR
		WCDMA Band V	Wi-Fi DTS Band	Bluetooth	(W/Kg)	(Yes/No)
	Left Touch	0.018	0.102		0.120	No
Head	Left Tilt	0.012	0.142		0.154	No
пеац	Right Touch	0.026	0.128		0.154	No
	Right Tilt	0.014	0.160		0.174	No
	Rear	0.125	0.183		0.308	No
	Front	0.036	0.146		0.182	No
	Edge 1	0.005	0.162		0.167	No
	Edge 2	0.065	0.079		0.144	No
	Edge 3	0.013	0.033		0.046	No
Hotonot	Edge 4	0.052	0.137		0.189	No
Hotspot	Rear	0.125		0.021	0.146	No
	Front	0.036		0.021	0.057	No
	Edge 1	0.005		0.021	0.026	No
	Edge 2	0.065		0.021	0.086	No
	Edge 3	0.013		0.021	0.034	No
	Edge 4	0.052		0.021	0.073	No

- According to KDB 447498 D01 General RF Exposure Guidance, when the simultaneous transmission SAR is less than 1.6 W/Kg, SPLSR assessment is not required.
- SPLSR mean is "The SAR to Peak Location Separation Ratio "

Page 52 of 85

APPENDIX A. SAR SYSTEM CHECK DATA

Test Laboratory: AGC Lab Date: Aug. 26,2015

System Check Head 835 MHz

DUT: Dipole 835MHz Type: SID 835

Communication System CW; Communication System Band: D835 (835.0 MHz); Duty Cycle: 1:1;

Frequency: 835 MHz; Medium parameters used: f = 835 MHz; $\sigma = 0.89$ mho/m; $\epsilon r = 41.03$; $\rho = 1000$ kg/m³;

Phantom section: Flat Section; Input Power=18dBm

Ambient temperature (°C): 21.6, Liquid temperature (°C): 21.5

DASY Configuration:

• Probe: EX3DV4 - SN3953; ConvF(10.12, 10.12, 10.12); Calibrated:11/06/2014;

- Sensor-Surface: 2mm (Mechanical Surface Detection), z = 1.0, 31.0
- Electronics: DAE4 Sn1398; Calibrated: 03/11/2015
- Phantom: SAM (20deg probe tilt) with CRP v5.0; Type: QD000P40CD;
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)

Configuration/System Check 835MHz Head/Area Scan (7x12x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (measured) = 0.810 W/kg


Configuration/System Check 835MHz Head/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm,

dy=8mm, dz=5mm

Reference Value = 27.562 V/m; Power Drift =0.12 dB

Peak SAR (extrapolated) = 0.964 W/kg

SAR(1 g) = 0.641 W/kg; SAR(10 g) = 0.403 W/kg Maximum value of SAR (measured) = 0.822 W/kg



Date: Aug. 26,2015

Page 53 of 85

Test Laboratory: AGC Lab System Check Body 835 MHz

DUT: Dipole 835 MHz Type: SID 835

Communication System CW; Communication System Band: D835 (835.0 MHz); Duty Cycle: 1:1;

Frequency: 835 MHz; Medium parameters used: f = 835 MHz; $\sigma = 0.97$ mho/m; $\epsilon r = 55.18$; $\rho = 1000$ kg/m³;

Phantom section: Flat Section; Input Power=18dBm

Ambient temperature (°C): 21.6, Liquid temperature (°C): 21.6

DASY Configuration:

- Probe: EX3DV4 SN3953; ConvF(10.08,10.08, 10.08); Calibrated: 11/06/2014;
- Sensor-Surface: 2mm (Mechanical Surface Detection), z = 1.0, 31.0
- · Electronics: DAE4 Sn1398; Calibrated: 03/11/2015
- Phantom: SAM (20deg probe tilt) with CRP v5.0; Type: QD000P40CD;
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)


Configuration/System Check 835MHz Body/Area Scan (7x12x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (measured) = 0.831 W/kg

Configuration/System Check 835MHz Body/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dv=8mm, dz=5mm

Reference Value = 27.869 V/m; Power Drift = -0.05 dB

Peak SAR (extrapolated) = 1.00 W/kg

SAR(1 g) = 0.656 W/kg; SAR(10 g) = 0.425 W/kg Maximum value of SAR (measured) = 0.837 W/kg



Date: Aug. 28,2015

Page 54 of 85

Test Laboratory: AGC Lab System Check Head 1900MHz

DUT: Dipole 1900 MHz; Type: SID 1900

Communication System: CW; Communication System Band: D1900 (1900.0 MHz); Duty Cycle:1:1;

Frequency: 1900 MHz; Medium parameters used: f = 1900 MHz; $\sigma = 1.43 \text{ mho/m}$; $\epsilon r = 40.24$; $\rho = 1000 \text{ kg/m}^3$;

Phantom section: Flat Section; Input Power=18dBm

Ambient temperature ($^{\circ}$):21.8, Liquid temperature ($^{\circ}$): 21.6

DASY Configuration:

- Probe: EX3DV4 SN3953; ConvF(7.89, 7.89, 7.89); Calibrated: 11/06/2014;
- Sensor-Surface: 2mm (Mechanical Surface Detection), z = 1.0, 31.0
- Electronics: DAE4 Sn1398; Calibrated: 03/11/2015
- Phantom: SAM (20deg probe tilt) with CRP v5.0; Type: QD000P40CD;
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)

Configuration/System Check 1900MHz Head/ Area Scan (7x9x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (measured) = 3.42 W/k


Configuration/System Check 1900MHz Head/ Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 49.766 V/m; Power Drift = -0.08 dB

Peak SAR (extrapolated) = 4.69 W/kg

SAR(1 g) = 2.45 W/kg; SAR(10 g) = 1.23 W/kg

Maximum value of SAR (measured) = 3.51 W/kg



Date: Aug. 28,2015

Page 55 of 85

Test Laboratory: AGC Lab System Check Body 1900MHz

DUT: Dipole 1900 MHz; Type: SID 1900

Communication System: CW; Communication System Band: D1900 (1900.0 MHz); Duty Cycle:1:1;

Frequency: 1900 MHz; Medium parameters used: f = 1900 MHz; $\sigma = 1.52$ mho/m; $\epsilon r = 52.88$; $\rho = 1000$ kg/m³;

Phantom section: Flat Section; Input Power=18dBm

Ambient temperature (°C):21.8, Liquid temperature (°C): 21.6

DASY Configuration:

- Probe: EX3DV4 SN3953; ConvF(7.79,7.79,7.79); Calibrated: 11/06/2014;
- Sensor-Surface: 2mm (Mechanical Surface Detection), z = 1.0, 31.0
- Electronics: DAE4 Sn1398; Calibrated: 03/11/2015
- Phantom: SAM (20deg probe tilt) with CRP v5.0; Type: QD000P40CD;
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)


Configuration/System Check 1900MHz Body/ Area Scan (7x9x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (measured) = 3.89 W/kg

Configuration/System Check 1900MHz Body/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 53.210 V/m; Power Drift = -0.00 dB

Peak SAR (extrapolated) = 5.43 W/kg

SAR(1 g) = 2.72 W/kg; SAR(10 g) = 1.32 W/kg Maximum value of SAR (measured) = 4.06 W/kg



Page 56 of 85

Test Laboratory: AGC Lab

System Check Head 2450 MHz

Date: Aug. 29,2015

DUT: Dipole 2450 MHz Type: SID 2450

Communication System: CW; Communication System Band: D2450 (2450.0 MHz); Duty Cycle: 1:1;

Frequency: 2450 MHz; Medium parameters used: f = 2450 MHz; $\sigma = 1.80$ mho/m; $\epsilon r = 40.27$; $\rho = 1000$ kg/m³;

Phantom section: Flat Section; Input Power=18dBm

Ambient temperature (°C): 21.4, Liquid temperature (°C): 21.2

DASY Configuration:

Probe: EX3DV4 - SN3953; ConvF(7.32, 7.32, 7.32); Calibrated: 11/06/2014
 Sensor-Surface: 2mm (Mechanical Surface Detection), z = 1.0, 31.0

- · Electronics: DAE4 Sn1398; Calibrated: 03/11/2015
- Phantom: SAM (20deg probe tilt) with CRP v5.0; Type: QD000P40CD;
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)

Configuration/System Check 2450MHz Head/ Area Scan (9x12x1): Measurement grid: dx=10mm, dy=10mm


Maximum value of SAR (measured) = 4.78 W/kg

Configuration/System Check 2450MHz Head/ Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 53.460 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 6.94 W/kg

SAR(1 g) = 3.36 W/kg; SAR(10 g) = 1.54 W/kg Maximum value of SAR (measured) = 5.15 W/kg



Date: Aug. 29,2015

Page 57 of 85

Test Laboratory: AGC Lab System Check Body 2450 MHz

DUT: Dipole 2450 MHz Type: SID 2450

Communication System: CW; Communication System Band: D2450 (2450.0 MHz); Duty Cycle: 1:1;

Frequency: 2450 MHz; Medium parameters used: f = 2450 MHz; $\sigma = 1.92$ mho/m; $\epsilon r = 52.64$; $\rho = 1000$ kg/m³;

Phantom section: Flat Section; Input Power=18dBm

Ambient temperature ($^{\circ}$ C): 21.4, Liquid temperature ($^{\circ}$ C): 21.4

DASY Configuration:

•Probe: EX3DV4 - SN3953; ConvF(7.48, 7.48, 7.48); Calibrated: 11/06/2014

- Sensor-Surface: 2mm (Mechanical Surface Detection), z = 1.0, 31.0
- Electronics: DAE4 Sn1398; Calibrated: 03/11/2015
- Phantom: SAM (20deg probe tilt) with CRP v5.0; Type: QD000P40CD;
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)

Configuration/System Check 2450MHz Body/ Area Scan (9x12x1): Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (measured) = 4.92 W/kg


Configuration/System Check 2450MHz Body/ Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 54.275 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 7.16 W/kg

SAR(1 g) = 3.46 W/kg; SAR(10 g) = 1.59 W/kg

Maximum value of SAR (measured) = 5.31 W/kg



Page 58 of 85

APPENDIX B. SAR MEASUREMENT DATA

Test Laboratory: AGC Lab Date: Aug. 26,2015

GSM 850 Mid-Touch-Left <SIM 1> DUT: Smart Phone; Type: A6

Communication System: UID 0, Generic GSM (0); Communication System Band: GSM 850 (824.2 – 848.8 MHz); Duty Cycle: 1:8.3; Frequency: 836.6 MHz; Medium parameters used: f = 835 MHz; $\sigma = 0.90$ mho/m; $\epsilon r = 40.58$; $\rho = 1000$ kg/m³;

Phantom section: Left Section

Ambient temperature (°C):21.6, Liquid temperature (°C): 21.5

DASY Configuration:

- Probe: EX3DV4 SN3953; ConvF(10.12, 10.12, 10.12); Calibrated:11/06/2014;
- Sensor-Surface: 2mm (Mechanical Surface Detection), z = 1.0, 31.0
- Electronics: DAE4 Sn1398; Calibrated: 03/11/2015
- Phantom: SAM (20deg probe tilt) with CRP v5.0; Type: QD000P40CD;
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)


LEFT/L-C/Area Scan (8x12x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (measured) = 0.0458 W/kg

LEFT/L-C/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 2.330 V/m; Power Drift = 0.18 dB

Peak SAR (extrapolated) = 0.0540 W/kg

SAR(1 g) = 0.034 W/kg; SAR(10 g) = 0.022 W/kg Maximum value of SAR (measured) = 0.0436 W/kg



Page 59 of 85

Test Laboratory: AGC Lab Date: Aug. 26,2015

GSM 850 Mid- Body- Back(MS)<SIM 1> DUT: Smart Phone; Type: A6

Communication System: UID 0, Generic GSM (0); Communication System Band: GSM 850 (824.2 – 848.8 MHz); Duty Cycle: 1:8.3; Frequency: 836.6 MHz; Medium parameters used: f = 835 MHz; $\sigma = 0.98$ mho/m; $\epsilon r = 54.93$ $\rho = 1000$ kg/m³;

Phantom section: Flat Section

Ambient temperature (°C):21.6, Liquid temperature (°C): 21.6

DASY Configuration:

- Probe: EX3DV4 SN3953; ConvF(10.08,10.08, 10.08); Calibrated: 11/06/2014;
- Sensor-Surface: 2mm (Mechanical Surface Detection), z = 1.0, 31.0
- · Electronics: DAE4 Sn1398; Calibrated: 03/11/2015
- Phantom: SAM (20deg probe tilt) with CRP v5.0; Type: QDOVA002AA;
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)


BODY/BACK/Area Scan (8x11x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (measured) = 0.114 W/kg

BODY/BACK/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 6.992 V/m; Power Drift = 0.11 dB

Peak SAR (extrapolated) = 0.126 W/kg

SAR(1 g) = 0.100 W/kg; SAR(10 g) = 0.076 W/kg



Date: Aug. 26,2015

Page 60 of 85

Test Laboratory: AGC Lab

GPRS 850 Mid-Touch-Left (2up) <SIM 1>

DUT: Smart Phone; Type: A6

Communication System: : GPRS-2 Slot; Communication System Band: GSM 850 (824.2 – 848.8 MHz); Duty Cycle:

1:4.2; Frequency: 836.6 MHz; Medium parameters used: f = 836.6 MHz; $\sigma = 0.90$ mho/m; $\epsilon r = 40.58$;

 $\rho = 1000 \text{ kg/m}^3$;

Phantom section: Left Section

Ambient temperature (°C):21.6, Liquid temperature (°C): 21.5

DASY Configuration:

- Probe: EX3DV4 SN3953; ConvF(10.12, 10.12, 10.12); Calibrated:11/06/2014;
- Sensor-Surface: 2mm (Mechanical Surface Detection), z = 1.0, 31.0
- Electronics: DAE4 Sn1398; Calibrated: 03/11/2015
- Phantom: SAM (20deg probe tilt) with CRP v5.0; Type: QD000P40CD;
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)

LEFT/2ST-L-C/Area Scan (8x12x1): Measurement grid: dx=15mm, dy=15mm


Maximum value of SAR (measured) = 0.0665 W/kg

LEFT/2ST-L-C/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm


Reference Value = 3.492 V/m; Power Drift = 0.17 dB

Peak SAR (extrapolated) = 0.0780 W/kg

SAR(1 g) = 0.049 W/kg; SAR(10 g) = 0.033 W/kg Maximum value of SAR (measured) = 0.0625 W/kg



Page 61 of 85



Date: Aug. 26,2015

Page 62 of 85

Test Laboratory: AGC Lab

GPRS 850 Mid-Touch-Left (2up) <SIM 2>

DUT: Smart Phone; Type: A6

Communication System: : GPRS-2 Slot; Communication System Band: GSM 850 (824.2 – 848.8 MHz); Duty Cycle:

1:4.2; Frequency: 836.6 MHz; Medium parameters used: f = 836.6 MHz; $\sigma = 0.90$ mho/m; $\epsilon r = 40.58$;

 $\rho = 1000 \text{ kg/m}^3$;

Phantom section: Left Section

Ambient temperature (°C):21.6, Liquid temperature (°C): 21.5

DASY Configuration:

- Probe: EX3DV4 SN3953; ConvF(10.12, 10.12, 10.12); Calibrated:11/06/2014;
- Sensor-Surface: 2mm (Mechanical Surface Detection), z = 1.0, 31.0
- Electronics: DAE4 Sn1398; Calibrated: 03/11/2015
- Phantom: SAM (20deg probe tilt) with CRP v5.0; Type: QD000P40CD;
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)

LEFT/2ST-L-C 2/Area Scan (8x12x1): Measurement grid: dx=15mm, dy=15mm


Maximum value of SAR (measured) = 0.0583 W/kg

LEFT/2ST-L-C 2/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 2.920 V/m; Power Drift = -0.12 dB

Peak SAR (extrapolated) = 0.0670 W/kg

SAR(1 g) = 0.045 W/kg; SAR(10 g) = 0.031 W/kg Maximum value of SAR (measured) = 0.0560 W/kg



Page 63 of 85

Test Laboratory: AGC Lab Date: Aug. 26,2015

GPRS 850 Mid- Body- Back (2up) < SIM 1>

DUT: Smart Phone; Type: A6

Communication System: GPRS-2 Slot; Communication System Band: GSM 850 (824.2 – 848.8 MHz); Duty Cycle: 1:4.2; Frequency: 836.6 MHz; Medium parameters used: f = 835 MHz; $\sigma = 0.98$ mho/m; $\epsilon r = 54.93$; $\rho = 1000$ kg/m³; Phantom section: Flat Section

Ambient temperature (°C):21.6, Liquid temperature (°C): 21.6

DASY Configuration:

- Probe: EX3DV4 SN3953; ConvF(10.08,10.08, 10.08); Calibrated: 11/06/2014;
- Sensor-Surface: 2mm (Mechanical Surface Detection), z = 1.0, 31.0
- · Electronics: DAE4 Sn1398; Calibrated: 03/11/2015
- Phantom: SAM (20deg probe tilt) with CRP v5.0; Type: QDOVA002AA;
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)

BODY/2ST-BACK/Area Scan (8x11x1): Measurement grid: dx=15mm, dy=15mm


Maximum value of SAR (measured) = 0.207 W/kg

BODY/2ST-BACK/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm


Reference Value = 11.567 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 0.266 W/kg

SAR(1 g) = 0.200 W/kg; SAR(10 g) = 0.146 W/kg Maximum value of SAR (measured) = 0.237 W/kg



Page 64 of 85



Page 65 of 85

Test Laboratory: AGC Lab Date: Aug. 26,2015

GPRS 850 Mid- Body- Back (2up) < SIM 2>

DUT: Smart Phone; Type: A6

Communication System: GPRS-2 Slot; Communication System Band: GSM 850 (824.2 – 848.8 MHz); Duty Cycle: 1:4.2; Frequency: 836.6 MHz; Medium parameters used: f = 835 MHz; $\sigma = 0.98$ mho/m; $\epsilon r = 54.93$; $\rho = 1000$ kg/m³; Phantom section: Flat Section

Ambient temperature (°C):21.6, Liquid temperature (°C): 21.6

DASY Configuration:

- Probe: EX3DV4 SN3953; ConvF(10.08,10.08, 10.08); Calibrated: 11/06/2014;
- Sensor-Surface: 2mm (Mechanical Surface Detection), z = 1.0, 31.0
- · Electronics: DAE4 Sn1398; Calibrated: 03/11/2015
- Phantom: SAM (20deg probe tilt) with CRP v5.0; Type: QDOVA002AA;
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)

BODY/2ST-BACK 2/Area Scan (8x11x1): Measurement grid: dx=15mm, dy=15mm


Maximum value of SAR (measured) = 0.170 W/kg

BODY/2ST-BACK 2/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 8.469 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 0.191 W/kg

SAR(1 g) = 0.151 W/kg; SAR(10 g) = 0.115 W/kg Maximum value of SAR (measured) = 0.173 W/kg



Page 66 of 85

Test Laboratory: AGC Lab

Date: Aug. 28,2015

PCS 1900 Mid-Touch-Left <SIM 1> DUT: Smart Phone; Type: A6

Communication System: UID 0, Generic GSM (0); Communication System Band: PCS 1900 (1850.2 – 1909.8 MHz); Duty Cycle: 1:8.3; Frequency: 1880 MHz; Medium parameters used: f = 1900 MHz; $\sigma = 1.40$ mho/m; $\epsilon r = 40.73$;

 $\rho = 1000 \text{ kg/m}^3$;

Phantom section: Left Section

Ambient temperature (°C):21.8, Liquid temperature (°C): 21.6

DASY Configuration:

- Probe: EX3DV4 SN3953; ConvF(7.89, 7.89, 7.89); Calibrated: 11/06/2014;
- Sensor-Surface: 2mm (Mechanical Surface Detection), z = 1.0, 31.0
- Electronics: DAE4 Sn1398; Calibrated: 03/11/2015
- Phantom: SAM (20deg probe tilt) with CRP v5.0; Type: QD000P40CD;
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)

LEFT/L-C/Area Scan (8x12x1): Measurement grid: dx=15mm, dy=15mm


Maximum value of SAR (measured) = 0.348 W/kg

LEFT/L-C/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 4.517 V/m; Power Drift = 0.18 dB

Peak SAR (extrapolated) = 0.419 W/kg

SAR(1 g) = 0.256 W/kg; SAR(10 g) = 0.150 W/kg Maximum value of SAR (measured) = 0.334 W/kg



Page 67 of 85

Test Laboratory: AGC Lab Date: Aug. 28,2015

PCS 1900 Mid-Body- Back(MS)<SIM 1> DUT: Smart Phone; Type: A6

Communication System: UID 0, Generic GSM (0); Communication System Band: PCS 1900 (1850.2 – 1909.8 MHz); Duty Cycle: 1:8.3; Frequency: 1880 MHz; Medium parameters used: f = 1900 MHz; $\sigma = 1.50$ mho/m; $\epsilon r = 53.13$;

ρ= 1000 kg/m³; Phantom section: Flat Section

Ambient temperature ($^{\circ}$ C):21.8, Liquid temperature ($^{\circ}$ C): 21.6

DASY Configuration:

- Probe: EX3DV4 SN3953; ConvF(7.79,7.79,7.79); Calibrated: 11/06/2014;
- Sensor-Surface: 2mm (Mechanical Surface Detection), z = 1.0, 31.0
- Electronics: DAE4 Sn1398; Calibrated: 03/11/2015
- Phantom: SAM (20deg probe tilt) with CRP v5.0; Type: QD000P40CD;
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)

BODY/BACK/Area Scan (8x11x1): Measurement grid: dx=15mm, dy=15mm


Maximum value of SAR (measured) = 0.499 W/kg

BODY/BACK/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 18.196 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 0.631 W/kg

SAR(1 g) = 0.390 W/kg; SAR(10 g) = 0.231 W/kg Maximum value of SAR (measured) = 0.505 W/kg



Page 68 of 85

Test Laboratory: AGC Lab Date: Aug. 28,2015

GPRS 1900 Mid-Touch-Right (2up) < SIM 1>

DUT: Smart Phone; Type: A6

Communication System: GPRS-2 Slot; Communication System Band: PCS 1900 (1850.2 – 1909.8 MHz); Duty Cycle:

1:4.2; Frequency: 1880 MHz; Medium parameters used: f = 1900 MHz; $\sigma = 1.40$ mho/m; $\epsilon r = 40.73$;

 $\rho = 1000 \text{ kg/m}^3$;

Phantom section: Right Section

Ambient temperature ($^{\circ}$ C):21.8, Liquid temperature ($^{\circ}$ C): 21.6

DASY Configuration:

- Probe: EX3DV4 SN3953; ConvF(7.89, 7.89, 7.89); Calibrated: 11/06/2014;
- Sensor-Surface: 2mm (Mechanical Surface Detection), z = 1.0, 31.0
- Electronics: DAE4 Sn1398; Calibrated: 03/11/2015
- Phantom: SAM (20deg probe tilt) with CRP v5.0; Type: QD000P40CD;
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)

RIGHT/2ST R-C/Area Scan (8x12x1): Measurement grid: dx=15mm, dy=15mm


Maximum value of SAR (measured) = 0.435 W/kg

RIGHT/2ST R-C/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm


Reference Value = 4.756 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 0.564 W/kg

SAR(1 g) = 0.388 W/kg; SAR(10 g) = 0.239 W/kg Maximum value of SAR (measured) = 0.479 W/kg



Page 69 of 85



Page 70 of 85

Test Laboratory: AGC Lab Date: Aug. 28,2015

GPRS 1900 Mid-Touch-Right (2up) < SIM 2>

DUT: Smart Phone; Type: A6

Communication System: GPRS-2 Slot; Communication System Band: PCS 1900 (1850.2 – 1909.8 MHz); Duty Cycle:

1:4.2; Frequency: 1880 MHz; Medium parameters used: f = 1900 MHz; $\sigma = 1.40$ mho/m; $\epsilon r = 40.73$;

 $\rho = 1000 \text{ kg/m}^3$;

Phantom section: Right Section

Ambient temperature (°C):21.8, Liquid temperature (°C): 21.6

DASY Configuration:

- Probe: EX3DV4 SN3953; ConvF(7.89, 7.89, 7.89); Calibrated: 11/06/2014;
- Sensor-Surface: 2mm (Mechanical Surface Detection), z = 1.0, 31.0
- Electronics: DAE4 Sn1398; Calibrated: 03/11/2015
- Phantom: SAM (20deg probe tilt) with CRP v5.0; Type: QD000P40CD;
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)

RIGHT/2ST R-C 2/Area Scan (8x12x1): Measurement grid: dx=15mm, dy=15mm


Maximum value of SAR (measured) = 0.368 W/kg

RIGHT/2ST R-C 2/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 5.122 V/m; Power Drift = -0.20 dB

Peak SAR (extrapolated) = 0.502 W/kg

SAR(1 g) = 0.347 W/kg; SAR(10 g) = 0.216 W/kg Maximum value of SAR (measured) = 0.424 W/kg



Page 71 of 85

Test Laboratory: AGC Lab

Date: Aug. 28,2015

GPRS 1900 Mid-Body- Back (2up) < SIM 1>

DUT: Smart Phone; Type: A6

Communication System: GPRS-2 Slot; Communication System Band: PCS 1900 (1850.2 – 1909.8 MHz); Duty Cycle:

1:4.2; Frequency: 1880 MHz; Medium parameters used: f = 1900 MHz; σ = 1.50 mho/m; ϵ r =53.13;

 $\rho = 1000 \text{ kg/m}^3$;

Phantom section: Flat Section

Ambient temperature (°C):21.8, Liquid temperature (°C): 21.6

DASY Configuration:

- Probe: EX3DV4 SN3953; ConvF(7.79,7.79,7.79); Calibrated: 11/06/2014;
- Sensor-Surface: 2mm (Mechanical Surface Detection), z = 1.0, 31.0
- · Electronics: DAE4 Sn1398; Calibrated: 03/11/2015
- Phantom: SAM (20deg probe tilt) with CRP v5.0; Type: QD000P40CD;
- · DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)

BODY/2ST-BACK/Area Scan (8x11x1): Measurement grid: dx=15mm, dy=15mm


Maximum value of SAR (measured) = 0.760 W/kg

BODY/2ST-BACK/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm


Reference Value = 23.786 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 0.997 W/kg

SAR(1 g) = 0.597 W/kg; SAR(10 g) = 0.340 W/kg Maximum value of SAR (measured) = 0.787 W/kg



Page 72 of 85



Page 73 of 85

Test Laboratory: AGC Lab Date: Aug. 28,2015

GPRS 1900 Mid-Body- Back (2up) < SIM 2>

DUT: Smart Phone; Type: A6

Communication System: GPRS-2 Slot; Communication System Band: PCS 1900 (1850.2 – 1909.8 MHz); Duty Cycle:

1:4.2; Frequency: 1880 MHz; Medium parameters used: f = 1900 MHz; $\sigma = 1.50$ mho/m; $\epsilon r = 53.13$;

 $\rho = 1000 \text{ kg/m}^3$;

Phantom section: Flat Section

Ambient temperature (°C):21.8, Liquid temperature (°C): 21.6

DASY Configuration:

- Probe: EX3DV4 SN3953; ConvF(7.79,7.79,7.79); Calibrated: 11/06/2014;
- Sensor-Surface: 2mm (Mechanical Surface Detection), z = 1.0, 31.0
- Electronics: DAE4 Sn1398; Calibrated: 03/11/2015
- Phantom: SAM (20deg probe tilt) with CRP v5.0; Type: QD000P40CD;
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)

BODY/2ST-BACK 2/Area Scan (8x11x1): Measurement grid: dx=15mm, dy=15mm


Maximum value of SAR (measured) = 0.613 W/kg

BODY/2ST-BACK 2/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 19.710 V/m; Power Drift = 0.06 dB

Peak SAR (extrapolated) = 0.813 W/kg

SAR(1 g) = 0.509 W/kg; SAR(10 g) = 0.311 W/kg Maximum value of SAR (measured) = 0.666 W/kg



Page 74 of 85

Test Laboratory: AGC Lab Date: Aug. 28,2015

WCDMA Band II Mid-Touch-Right DUT: Smart Phone; Type: A6

Communication System: UID 0, WCDMA 1900 (0); Communication System Band: Band $\,$ II UTRA/FDD; Duty Cycle:1:1; Frequency: 1880MHz; Medium parameters used: f = 1900 MHz; σ = 1.40 mho/m; ϵ r =40.73; ρ = 1000 kg/m³;

Phantom section: Right Section

Ambient temperature ($^{\circ}$ C):21.8, Liquid temperature ($^{\circ}$ C): 21.6

DASY Configuration:

- Probe: EX3DV4 SN3953; ConvF(7.89, 7.89, 7.89); Calibrated: 11/06/2014;
- Sensor-Surface: 2mm (Mechanical Surface Detection), z = 1.0, 31.0
- Electronics: DAE4 Sn1398; Calibrated: 03/11/2015
- Phantom: SAM (20deg probe tilt) with CRP v5.0; Type: QD000P40CD;
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)


RIGHT/R-C/Area Scan (8x12x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (measured) = 0.262 W/kg

RIGHT/R-C/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm


Reference Value = 5.242 V/m; Power Drift = 0.06 dB

Peak SAR (extrapolated) = 0.349 W/kg

SAR(1 g) = 0.216 W/kg; SAR(10 g) = 0.131 W/kg Maximum value of SAR (measured) = 0.279 W/kg



Page 75 of 85



Page 76 of 85

Test Laboratory: AGC Lab Date: Aug. 28,2015

WCDMA Band $\ \ \, \mathbb{II} \ \mbox{Low -Body-Towards Grounds}$

DUT: Smart Phone; Type: A6

Communication System: UID 0, WCDMA 1900 (0); Communication System Band: Band: II UTRA/FDD; Duty Cycle:1:1; Frequency: 1852.4 MHz; Medium parameters used: f = 1900 MHz; $\sigma = 1.50$ mho/m; $\epsilon r = 53.19$;

 ρ = 1000 kg/m³;

Phantom section: Flat Section

Ambient temperature (°C):21.8, Liquid temperature (°C): 21.6

DASY Configuration:

- Probe: EX3DV4 SN3953; ConvF(7.79,7.79,7.79); Calibrated: 11/06/2014;
- Sensor-Surface: 2mm (Mechanical Surface Detection), z = 1.0, 31.0
- · Electronics: DAE4 Sn1398; Calibrated: 03/11/2015
- Phantom: SAM (20deg probe tilt) with CRP v5.0; Type: QD000P40CD;
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)


BODY/BACK-L/Area Scan (8x11x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (measured) = 1.05 W/kg

BODY/BACK-L/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm


Reference Value = 23.395 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 1.29 W/kg

SAR(1 g) = 0.809 W/kg; SAR(10 g) = 0.483 W/kg Maximum value of SAR (measured) = 1.07 W/kg



Page 77 of 85



Page 78 of 85

Test Laboratory: AGC Lab Date: Aug. 26,2015

WCDMA Band V Mid-Touch-Right DUT: Smart Phone; Type: A6

Communication System: UID 0, WCDMA 850 (0); Communication System Band: BAND V UTRA/FDD; Duty Cycle:1:1; Frequency: 836.6 MHz; Medium parameters used: f = 835 MHz; σ =0.90 mho/m; ε r =40.58

 $\rho = 1000 \text{ kg/m}^3$;

Phantom section: Right Section

Ambient temperature ($^{\circ}$ C):21.6, Liquid temperature ($^{\circ}$ C): 21.5

DASY Configuration:

- Probe: EX3DV4 SN3953; ConvF(10.12, 10.12, 10.12); Calibrated:11/06/2014;
- Sensor-Surface: 2mm (Mechanical Surface Detection), z = 1.0, 31.0
- Electronics: DAE4 Sn1398; Calibrated: 03/11/2015
- Phantom: SAM (20deg probe tilt) with CRP v5.0; Type: QD000P40CD;
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)


RIGHT HEAD/R-C/Area Scan (8x12x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (measured) = 0.0237 W/kg

RIGHT HEAD/R-C/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm


Reference Value = 0.965 V/m; Power Drift =- 0.12 dB

Peak SAR (extrapolated) = 0.0270 W/kg

SAR(1 g) = 0.022 W/kg; SAR(10 g) = 0.017 W/kg Maximum value of SAR (measured) = 0.0242 W/kg



Page 79 of 85



Page 80 of 85

Test Laboratory: AGC Lab Date: Aug. 26,2015

WCDMA Band V Mid-Body-Towards Grounds

DUT: Smart Phone; Type: A6

Communication System: UID 0, WCDMA 850 (0); Communication System Band: BAND V UTRA/FDD; Duty Cycle:1:1; Frequency: 836.6 MHz; Medium parameters used: f = 835 MHz; σ =0.98 mho/m; ϵ r =54.93;

 $\rho = 1000 \text{ kg/m}^3$;

Phantom section: Flat Section

Ambient temperature ($^{\circ}$ C):21.6, Liquid temperature ($^{\circ}$ C): 21.6

DASY Configuration:

- Probe: EX3DV4 SN3953; ConvF(10.08,10.08, 10.08); Calibrated: 11/06/2014;
- Sensor-Surface: 2mm (Mechanical Surface Detection), z = 1.0, 31.0
- Electronics: DAE4 Sn1398; Calibrated: 03/11/2015
- Phantom: SAM (20deg probe tilt) with CRP v5.0; Type: QD000P40CD;
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)


BODY/BACK/Area Scan (8x11x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (measured) = 0.151 W/kg

BODY/BACK/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm


Reference Value = 11.225 V/m; Power Drift = 0.13 dB

Peak SAR (extrapolated) = 0.193 W/kg

SAR(1 g) = 0.105 W/kg; SAR(10 g) = 0.065 W/kg Maximum value of SAR (measured) = 0.150 W/kg



Page 81 of 85



Date: Aug. 29,2015

Page 82 of 85

Test Laboratory: AGC Lab 802.11b Mid-Tilt-Right

DUT: Smart Phone; Type: A6

Communication System: UID 0, WiFi 802.11b (0); Communication System Band: 802.11b; Duty Cycle: 1:1; Frequency: 2437 MHz; Medium parameters used: f = 2450 MHz; $\sigma = 1.78$ mho/m; $\epsilon r = 40.56; \rho = 1000$ kg/m³;

Phantom section: Right Section

Ambient temperature (°C): 21.4, Liquid temperature (°C): 21.2

DASY Configuration:

Probe: EX3DV4 - SN3953; ConvF(7.32, 7.32, 7.32); Calibrated: 11/06/2014

- Sensor-Surface: 2mm (Mechanical Surface Detection), z = 1.0, 31.0
- · Electronics: DAE4 Sn1398; Calibrated: 03/11/2015
- Phantom: SAM (20deg probe tilt) with CRP v5.0; Type: QD000P40CD;
- · DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)

RIGHT HEAD/R-T/Area Scan (12x17x1): Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (measured) = 0.226 W/kg


RIGHT HEAD/R-T/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 2.031 V/m; Power Drift = -0.13 dB

Peak SAR (extrapolated) = 0.572 W/kg

SAR(1 g) = 0.135 W/kg; SAR(10 g) = 0.050 W/kg

Maximum value of SAR (measured) = 0.255 W/kg



Page 83 of 85

Test Laboratory: AGC Lab Date: Aug. 29,2015

802.11b Mid- Body- Back (DTS) DUT: Smart Phone; Type: A6

Communication System: UID 0, WiFi 802.11b (0); Communication System Band: 802.11b; Duty Cycle: 1:1; Frequency: 2437 MHz; Medium parameters used: f = 2450 MHz; $\sigma = 1.92$ mho/m; $\epsilon r = 52.75$;; $\rho = 1000$ kg/m³;

Phantom section: Flat Section

Ambient temperature (°C): 21.4, Liquid temperature (°C): 21.4

DASY Configuration:

Probe: EX3DV4 - SN3953; ConvF(7.48, 7.48, 7.48); Calibrated: 11/06/2014

- Sensor-Surface: 2mm (Mechanical Surface Detection), z = 1.0, 31.0
- · Electronics: DAE4 Sn1398; Calibrated: 03/11/2015
- Phantom: SAM (20deg probe tilt) with CRP v5.0; Type: QD000P40CD;
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)

BODY/BACK/Area Scan (12x16x1): Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (measured) = 0.218 W/kg


BODY/BACK/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 2.627 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 0.485 W/kg

SAR(1 g) = 0.155 W/kg; SAR(10 g) = 0.057 W/kg

Maximum value of SAR (measured) = 0.272 W/kg



Page 84 of 85

Repeated SAR

Test Laboratory: AGC Lab Date: Aug. 28,2015

WCDMA Band II Low -Body-Towards Grounds

DUT: Smart Phone; Type: A6

Communication System: UID 0, WCDMA 1900 (0); Communication System Band: Band: II UTRA/FDD; Duty Cycle:1:1; Frequency: 1852.4 MHz; Medium parameters used: f = 1900 MHz; $\sigma = 1.50$ mho/m; $\epsilon r = 53.19$;

 $\rho = 1000 \text{ kg/m}^3$;

Phantom section: Flat Section

Ambient temperature (°C):21.8, Liquid temperature (°C): 21.6

DASY Configuration:

• Probe: EX3DV4 - SN3953; ConvF(7.79,7.79,7.79); Calibrated: 11/06/2014;

- Sensor-Surface: 2mm (Mechanical Surface Detection), z = 1.0, 31.0
- Electronics: DAE4 Sn1398; Calibrated: 03/11/2015
- Phantom: SAM (20deg probe tilt) with CRP v5.0; Type: QD000P40CD;
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)


BODY/REPEATED-BACK 2/Area Scan (8x11x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (measured) = 0.717 W/kg

BODY/REPEATED-BACK 2/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm Reference Value = 19.776 V/m; Power Drift = 0.11 dB

Peak SAR (extrapolated) = 0.997 W/kg

SAR(1 g) = 0.537 W/kg; SAR(10 g) = 0.303 W/kg

Maximum value of SAR (measured) = 0.772 W/kg



Page 85 of 85

APPENDIX C. TEST SETUP PHOTOGRAPHS & EUT PHOTOGRAPHS

Refer to Attached files.

APPENDIX D. CALIBRATION DATA

Refer to Attached files.