

FCC PART 90

TEST REPORT

For

Shenzhen Excera Technology Co., Ltd.

3rd Floor, Jiada R&D Building, No.5 Songpingshan Road, Hi-Tech Park North, Nanshan District, Shenzhen

FCC ID: 2AE6CEP8100VHF

Report Type: Product Type: Original Report Digital Portable Radio **Test Engineer:** Sonia Zhou Report Number: RSZ160201012-00D **Report Date:** 2016-02-24 Rocky Kang Rocky Kang Reviewed By: RF Engineer **Prepared By:** Bay Area Compliance Laboratories Corp. (Shenzhen) 6/F, the 3rd Phase of WanLi Industrial Building, ShiHua Road, FuTian Free Trade Zone Shenzhen, Guangdong, China Tel: +86-755-33320018 Fax: +86-755-33320008 www.baclcorp.com.cn

Note: This test report is prepared for the customer shown above and for the equipment described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp.

TABLE OF CONTENTS

TEST REPORT	1
GENERAL INFORMATION	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	
Objective	4
RELATED SUBMITTAL(S)/GRANT(S)	
TEST METHODOLOGY TEST FACILITY	
SYSTEM TEST CONFIGURATION	
DESCRIPTION OF TEST CONFIGURATION	
EQUIPMENT MODIFICATIONS	5
EXTERNAL I/O CABLE	5
BLOCK DIAGRAM OF TEST SETUP	5
SUMMARY OF TEST RESULTS	
FCC §1.1307(b) & §2.1093 - RF EXPOSURE	7
APPLICABLE STANDARD	
FCC §2.1046 & §90.205 - RF OUTPUT POWER	
APPLICABLE STANDARD	
TEST PROCEDURE	
TEST FROCEBORE TEST EQUIPMENT LIST AND DETAILS.	
Test Data	
FCC §2.1047 & §90.207 - MODULATION CHARACTERISTIC	10
APPLICABLE STANDARD	
TEST EQUIPMENT LIST AND DETAILS.	
Test Procedure	
TEST DATA	10
FCC §2.1049 & §90.209 & §90.210 – OCCUPIED BANDWIDTH & EMISSION MASK	16
Applicable Standard	
TEST EQUIPMENT LIST AND DETAILS.	
TEST PROCEDURE	
FCC §2.1051 & §90.210 - SPURIOUS EMISSIONS AT ANTENNA TERMINALS	
APPLICABLE STANDARD	
TEST EQUIPMENT LIST AND DETAILS TEST PROCEDURE	
TEST PROCEDURE TEST DATA	
FCC §2.1053 & §90.210 - RADIATED SPURIOUS EMISSIONS	
APPLICABLE STANDARD	
TEST EQUIPMENT LIST AND DETAILS.	
TEST PROCEDURE	26
Test Data	27
FCC §2.1055 & §90.213- FREQUENCY STABILITY	28
APPLICABLE STANDARD	28

TEST EQUIPMENT LIST AND DETAILS	28
TEST PROCEDURE	
TEST DATA	28
FCC §90.214 - TRANSIENT FREQUENCY BEHAVIOR	30
APPLICABLE STANDARD	30
TEST EQUIPMENT LIST AND DETAILS.	30
TEST PROCEDURE	
Test Data	31

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

The Shenzhen Excera Technology Co., Ltd.'s product, model number: EP8100 VHF (FCC ID: 2AE6CEP8100VHF) or the "EUT" in this report was a Digital Portable Radio, which was measured approximately: 125 mm (L) x 54 mm (W) x 35 mm (H), rated with input voltage: DC 7.4 V rechargeable battery.

Report No.: RSZ160201012-00D

* All measurement and test data in this report was gathered from production sample serial number: 1601347 (Assigned by BACL, Shenzhen). The EUT supplied by the applicant was received on 2016-02-01

Objective

This test report is prepared on behalf of *Shenzhen Excera Technology Co., Ltd.* in accordance with Part 2 and Part 90 of the Federal Communication Commissions rules.

Related Submittal(s)/Grant(s)

No related submittal(s)

Test Methodology

All tests and measurements indicated in this document were performed in accordance with the Code of federal Regulations Title 47 Part 2, Sub-part J as well as the following individual parts:

Part 90 - Private Land Mobile Radio Service

Applicable Standards: TIA-603-D and ANSI 63.4-2014.

All emissions measurement was performed and Bay Area Compliance Laboratories Corp. (Shenzhen). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Measurement uncertainty with radiated emission is 5.81 dB for 30MHz-1GHz.and 4.88 dB for above 1GHz, 1.95dB for conducted measurement.

Test Facility

The test site used by Bay Area Compliance Laboratories Corp. (Shenzhen) to collect test data is located on the 6/F, the 3rd Phase of WanLi Industrial Building, ShiHua Road, FuTian Free Trade Zone Shenzhen, Guangdong, China.

Test site at Bay Area Compliance Laboratories Corp. (Shenzhen) has been fully described in reports submitted to the Federal Communication Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on October 31, 2013. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2014.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 382179. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

FCC PART 90 Page 4 of 32

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in a test mode which has been done in the factory.

Equipment Modifications

No modification was made to the EUT tested.

Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
/	/	/	/

Report No.: RSZ160201012-00D

External I/O Cable

Cable Description	Length (m)	From Port	То
/	/	/	/

Block Diagram of Test Setup



FCC PART 90 Page 5 of 32

SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Results
§1.1307(b);§2.1093	RF Exposure	Compliance
§2.1046;§90.205	RF Output Power	Compliance
§2.1047;§90.207	Modulation Characteristic	Compliance
§2.1049;§90.209; §90.210	Occupied Bandwidth & Emission Mask	Compliance
§2.1051;§90.210	Spurious Emission at Antenna Terminal	Compliance
§2.1053;§90.210	Spurious Radiated Emissions	Compliance
§2.1055;§90.213	Frequency Stability	Compliance
§90.214	Transient Frequency Behavior	Compliance

Report No.: RSZ160201012-00D

FCC PART 90 Page 6 of 32

FCC §1.1307(b) & §2.1093 - RF EXPOSURE

Applicable Standard

According to FCC §1.1307(b) and §2.1093, protable device operates Part 90 should be subjected to rountine environmental evaluation for RF exposure prior or equipment authorization or use.

Report No.: RSZ160201012-00D

Result: Compliance.

Please refer to SAR Report Number: RSZ160201012-20B.

FCC PART 90 Page 7 of 32

FCC §2.1046 & §90.205 - RF OUTPUT POWER

Applicable Standard

FCC §2.1046 and §90.205

Test Procedure

Conducted RF Output Power:

The RF output of the transmitter was connected to the input of the spectrum analyzer through sufficient attenuation.

Report No.: RSZ160201012-00D

Spectrum Analyzer Setting:

R B/W Video B/W 100 kHz 300 kHz

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	Signal Analyzer	FSIQ26	8386001028	2015-12-11	2016-12-11
HP Agilent	RF Communication test set	8920A	3325U00859	2015-06-03	2016-06-02
Ducommun technologies	RF Cable	RG-214	3	2015-06-15	2016-06-15
JFW	30dB Attenuator	50FH-030-100 RF	170006716507	2015-06-12	2016-06-12

^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	23 ℃
Relative Humidity:	52 %
ATM Pressure:	101.0 kPa

The testing was performed by Sonia Zhou on 2016-02-17.

Test Mode: Transmitting

Test Result: Compliance. Please refer to following table.

FCC PART 90 Page 8 of 32

Modulation	Channel Separation (kHz)	Frequency (MHz)	Power Level	Output Power (dBm)	Output Power (W)	Result
	10.5	126.025	High	36.81	4.80	Pass
	12.5	136.025	Low	30.26	1.06	Pass
	10.5	155.005	High	37.11	5.14	Pass
Analog	12.5	155.025	Low	30.57	1.14	Pass
	12.5 173	172.07	High	37.07	5.09	Pass
		1/3.97	Low	30.64	1.16	Pass
	12.5	126 025	High	36.78	4.76	Pass
	12.3	136.025	Low	30.19	1.04	Pass
Digital	Digital 12.5 155.025	High	37.10	5.13	Pass	
Digital		155.025	Low	30.56	1.14	Pass
12.5	172 07	High	37.07	5.09	Pass	
	12.5 173.97	1/3.9/	Low	30.71	1.18	Pass

Note: The rated high power is 5W. The limit of the high output power is 4W-6W. The rated low power is 1W. The limit of the low output power is 0.8W-1.2W.

FCC PART 90 Page 9 of 32

FCC §2.1047 & §90.207 - MODULATION CHARACTERISTIC

Applicable Standard

FCC§2.1047and §90.207:

(a) Equipment which utilizes voice modulated communication shall show the frequency response of the audio modulating circuit over a range of 100 to 5000 Hz. for equipment which is required to have a low pass filter, the frequency response of the filter, or all of the circuitry installed between the modulation limited and the modulated stage shall be supplied.

Report No.: RSZ160201012-00D

(b) Equipment which employs modulation limiting, a curve showing the percentage of modulation versus the modulation input voltage shall be supplied.

Test Equipment List and Details

Manufacturer	Description	Model No.	Serial No.	Calibration Date	Calibration Due Date
HP	RF Communication Test Set	8920A	3438A05201	2015-06-14	2016-06-13
LEADER	MILLIVOLTMETER	LMV-181A	6041126	2015-06-09	2016-06-09
Ducommun technologies	RF Cable	RG-214	3	2015-06-15	2016-06-15
JFW	30dB Attenuator	50FH-030-100 RF	170006716507	2015-06-12	2016-06-12

^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements, traceable to National Primary Standards and International System of Units (SI).

Test Procedure

Test Method: TIA -603-D 2.2.3

Test Data

Environmental Conditions

Temperature:	23 ℃
Relative Humidity:	52 %
ATM Pressure:	101.0 kPa

The testing was performed by Sonia Zhou on 2016-02-17.

Test Mode: Transmitting

Result: Compliance.

FCC PART 90 Page 10 of 32

Analog Modulation:


MODULATION LIMITING

Report No.: RSZ160201012-00D

Carrier Frequency: 155.025 MHz, Channel Separation=12.5 kHz

	Instant	aneous	Steady	y-state	
Audio Frequency (Hz)	DEVIATION (@+20dB) [kHz]	DEVIATION (@-20dB) [kHz]	DEVIATION (@+20dB) [kHz]	DEVIATION (@-20dB) [kHz]	FCC Limit [kHz]
300	2.254	0.122	2.251	0.094	2.500
400	2.267	0.131	2.263	0.106	2.500
500	2.269	0.143	2.257	0.117	2.500
600	2.279	0.152	2.265	0.133	2.500
700	2.250	0.162	2.240	0.149	2.500
800	2.263	0.174	2.266	0.158	2.500
900	2.291	0.195	2.275	0.172	2.500
1000	2.296	0.209	2.288	0.192	2.500
1200	2.301	0.232	2.283	0.217	2.500
1400	2.317	0.261	2.301	0.240	2.500
1600	2.302	0.287	2.288	0.268	2.500
1800	2.316	0.304	2.305	0.286	2.500
2000	2.311	0.333	2.306	0.314	2.500
2100	2.305	0.347	2.293	0.326	2.500
2200	2.324	0.358	2.313	0.338	2.500
2300	2.334	0.366	2.327	0.351	2.500
2400	2.341	0.377	2.343	0.360	2.500
2500	2.285	0.394	2.269	0.376	2.500
2600	2.236	0.403	2.218	0.387	2.500
2700	2.100	0.414	2.087	0.398	2.500
2800	2.088	0.422	1.891	0.409	2.500
2900	1.623	0.431	1.615	0.422	2.500
3000	1.370	0.442	1.367	0.431	2.500

FCC PART 90 Page 11 of 32



FCC PART 90 Page 12 of 32


Audio Frequency Response

Report No.: RSZ160201012-00D

Carrier Frequency: 155.025 MHz, Channel Separation=12.5 kHz

Audio Frequency (Hz)	Response Attenuation (dB)
300	-10.75
400	-8.59
500	-6.13
600	-3.99
700	-2.85
800	-1.77
900	-0.67
1000	0.00
1200	1.51
1400	2.72
1600	3.92
1800	4.82
2000	5.66
2100	6.10
2200	6.47
2300	6.83
2400	7.04
2500	7.26
2600	7.62
2700	7.98
2800	8.25
2900	8.34
3000	8.57

FCC PART 90 Page 13 of 32




Report No.: RSZ160201012-00D

FCC PART 90 Page 14 of 32

Carrier Frequency: 155.025 MHz, Channel Separation=12.5 kHz

Audio Frequency (kHz)	Response Attenuation (dB)	Limit (dB)
1.0	0.0	/
3.0	-35.3	0.0
4.0	-46.3	-12.5
5.0	-61.5	-22.2
6.0	-65.6	-30.1
7.0	-76.0	-36.8
8.0	-75.3	-42.6
9.0	-78.1	-47.7
10.0	-79.0	-52.3
12.0	-76.3	-60.2
14.0	-82.8	-66.9
16.0	-86.0	-72.7
18.0	-88.6	-77.8
20.0	-91.6	-82.5



FCC PART 90 Page 15 of 32

FCC §2.1049 & §90.209 & §90.210 – OCCUPIED BANDWIDTH & EMISSION MASK

Applicable Standard

FCC §2.1049, §90.209 and §90.210

Emission Mask D—12.5 kHz channel bandwidth equipment. For transmitters designed to operate with a 12.5 kHz channel bandwidth, any emission must be attenuated below the power (P) of the highest emission contained within the authorized bandwidth as follows:

Report No.: RSZ160201012-00D

- 1) For any frequency removed from the center of the authorized bandwidth f_0 to 5.625 kHz removed from f_0 , 0dB.
- 2) On any frequency removed from the center of the authorized bandwidth by a displacement frequency (f_d in kHz) of more than 5.626 kHz but no more than 12.5 kHz, at least 7.27 (f_d –2.88 kHz) dB.
- 3) On any frequency removed from the center of the authorized bandwidth by a displacement frequency (f_d in kHz) of more than 12.5 kHz: At least 50 + 10 log (P) dB or 70 dB, whichever is the lesser attenuation.

Emission Mask E—6.25 kHz or less channel bandwidth equipment. For transmitters designed to operate with a 6.25 kHz or less bandwidth, any emission must be attenuated below the power (P) of the highest emission contained within the authorized bandwidth as follows:

- 1) On any frequency from the center of the authorized bandwidth f0 to 3.0 kHz removed from f0: Zero dB.
- 2) On any frequency removed from the center of the authorized bandwidth by a displacement frequency (fd in kHz) of more than 3.0 kHz but no more than 4.6 kHz: At least 30 + 16.67(fd-3 kHz) or 55 + 10 log (P) or 65 dB, whichever is the lesser attenuation.
- 3) On any frequency removed from the center of the authorized bandwidth by more than 4.6 kHz: At least 55 + 10 log (P) or 65 dB, whichever is the lesser attenuation.
- (4) The reference level for showing compliance with the emission mask shall be established using a resolution bandwidth sufficiently wide (usually two or three times the channel bandwidth) to capture the true peak emission of the equipment under test. In order to show compliance with the emission mask up to and including 50 kHz removed from the edge of the authorized bandwidth, adjust the resolution bandwidth to 100 Hz with the measuring instrument in a peak hold mode. A sufficient number of sweeps must be measured to insure that the emission profile is developed. If video filtering is used, its bandwidth must not be less than the instrument resolution bandwidth. For emissions beyond 50 kHz from the edge of the authorized bandwidth, see paragraph (o) of this section. If it can be shown that use of the above instrumentation settings do not accurately represent the true interference potential of the equipment under test, an alternate procedure may be used provided prior Commission approval is obtained.

FCC PART 90 Page 16 of 32

Test Equipment List and Details

Manufacturer	Description	Model No.	Serial No.	Calibration Date	Calibration Due Date
Rohde & Schwarz	Signal Analyzer	FSIQ26	8386001028	2015-12-11	2016-12-11
НР	RF Communication Test Set	8920A	3325U00859	2015-06-03	2016-06-03
Ducommun technologies	RF Cable	RG-214	3	2015-06-15	2016-06-15
JFW	30dB Attenuator	50FH-030- 100 RF	170006716507	2015-06-12	2016-06-12

Report No.: RSZ160201012-00D

Test Procedure

The RF output of the transmitter was connected to the input of the spectrum analyzer through sufficient attenuation.

The resolution bandwidth of the spectrum analyzer was set at 100 Hz and the spectrum was recorded in the frequency band ± 50 kHz from the carrier frequency.

Test Data

Environmental Conditions

Temperature:	20~23 ℃		
Relative Humidity:	48~52 %		
ATM Pressure:	100.0~101.0 kPa		

The testing was performed by Sonia Zhou from 2016-02-17 to 2016-03-02.

Test Mode: Transmitting


Modulation	Frequency (MHz)	Channel space (kHz)	Power Level	99% Occupied Bandwidth (kHz)	26 dB Emissions Bandwidth (kHz)
Anglog	155 025	12.5	High	9.92	10.32
Analog 155.025	133.023		Low	9.92	10.32
Dinital	155.025	12.5	High	7.62	10.12
Digital	155.025	12.5	Low	7.41	9.52

FCC PART 90 Page 17 of 32


^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements, traceable to National Primary Standards and International System of Units (SI).

Analog Modulation:

99% Occupied Bandwidth & 26 dB Emissions Bandwidth 12.5 kHz, 155.025 MHz (High Power)




99% Occupied Bandwidth & 26 dB Emissions Bandwidth 12.5 kHz, 155.025 MHz (Low Power)




FCC PART 90 Page 18 of 32

Emission Mask D with High Power 12.5 kHz, 155.025 MHz




Emission Mask D with Low Power 12.5 kHz, 155.025 MHz




FCC PART 90 Page 19 of 32

Digital Modulation:

99% Occupied Bandwidth & 26 dB Emissions Bandwidth 12.5 kHz, 155.025 MHz (High Power)




99% Occupied Bandwidth & 26 dB Emissions Bandwidth 12.5 kHz, 155.025 MHz (Low Power)




FCC PART 90 Page 20 of 32

Emission Mask D with High Power 12.5 kHz, 155.025 MHz



Emission Mask D with Low Power 12.5 kHz, 155.025 MHz



FCC PART 90 Page 21 of 32

FCC §2.1051 & §90.210 - SPURIOUS EMISSIONS AT ANTENNA TERMINALS

Applicable Standard

Emission Mask D—12.5 kHz channel bandwidth equipment. For transmitters designed to operate with a 12.5 kHz channel bandwidth, any emission must be attenuated below the power (P) of the highest emission contained within the authorized bandwidth as follows:

Report No.: RSZ160201012-00D

- 1) For any frequency removed from the center of the authorized bandwidth f_0 to 5.625 kHz removed from f_0 , 0 dB.
- 2) On any frequency removed from the center of the authorized bandwidth by a displacement frequency (f_d in kHz) of more than 5.626 kHz but no more than 12.5 kHz, at least 7.27 (f_d –2.88 kHz) dB.
- 3) On any frequency removed from the center of the authorized bandwidth by a displacement frequency (f_d in kHz) of more than 12.5 kHz: At least $50 + 10 \log (P) dB$ or 70 dB, whichever is the lesser attenuation.

Emission Mask E—6.25 kHz or less channel bandwidth equipment. For transmitters designed to operate with a 6.25 kHz or less bandwidth, any emission must be attenuated below the power (P) of the highest emission contained within the authorized bandwidth as follows:

- 1) On any frequency from the center of the authorized bandwidth f0 to 3.0 kHz removed from f0: Zero dB.
- 2)On any frequency removed from the center of the authorized bandwidth by a displacement frequency (fd in kHz) of more than 3.0 kHz but no more than 4.6 kHz: At least 30 + 16.67(fd-3 kHz) or $55 + 10 \log (P)$ or 65 dB, whichever is the lesser attenuation.
- 3) On any frequency removed from the center of the authorized bandwidth by more than 4.6 kHz: At least 55 + 10 log (P) or 65 dB, whichever is the lesser attenuation.
- 4) The reference level for showing compliance with the emission mask shall be established using a resolution bandwidth sufficiently wide (usually two or three times the channel bandwidth) to capture the true peak emission of the equipment under test. In order to show compliance with the emission mask up to and including 50 kHz removed from the edge of the authorized bandwidth, adjust the resolution bandwidth to 100 Hz with the measuring instrument in a peak hold mode. A sufficient number of sweeps must be measured to insure that the emission profile is developed. If video filtering is used, its bandwidth must not be less than the instrument resolution bandwidth. For emissions beyond 50 kHz from the edge of the authorized bandwidth, see paragraph (o) of this section. If it can be shown that use of the above instrumentation settings do not accurately represent the true interference potential of the equipment under test, an alternate procedure may be used provided prior Commission approval is obtained.

FCC PART 90 Page 22 of 32

Test Equipment List and Details

Manufacturer	Description	Model No.	Serial No.	Calibration Date	Calibration Due Date
Rohde & Schwarz	Signal Analyzer	FSIQ26	8386001028	2015-12-11	2016-12-11
Ducommun technologies	RF Cable	RG-214	3	2015-06-15	2016-06-15
JFW	30dB Attenuator	50FH-030- 100 RF	1700067165 07	2015-06-12	2016-06-12

Report No.: RSZ160201012-00D

Test Procedure

The RF output of the EUT was connected to a spectrum analyzer through appropriate attenuation. The resolution bandwidth of the spectrum analyzer was set at 100 kHz for below 1GHz, and 1MHz for above 1GHz. sufficient scans were taken to show any out of band emissions up to 10th harmonic.

Test Data

Environmental Conditions

Temperature:	23 ℃	
Relative Humidity:	52 %	
ATM Pressure:	101.0 kPa	

The testing was performed by Sonia Zhou from 2016-02-19 to 2016-03-01.

Test Mode: Transmitting


Please refer to the following plots.

FCC PART 90 Page 23 of 32


^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements, traceable to National Primary Standards and International System of Units (SI).

Analog Modulation:

30 MHz – 1 GHz, Spacing Channel 12.5 kHz, 155.025 MHz




1 GHz – 2GHz, Spacing Channel 12.5 kHz, 155.025 MHz




FCC PART 90 Page 24 of 32

Digital Modulation:

30 MHz – 1 GHz, Spacing Channel 12.5 kHz, 155.025 MHz



1 GHz – 2GHz, Spacing Channel 12.5 kHz, 155.025 MHz



FCC PART 90 Page 25 of 32

FCC §2.1053 & §90.210 - RADIATED SPURIOUS EMISSIONS

Applicable Standard

FCC §2.1053 and §90.210

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCI	101120	2015-11-03	2016-11-03
HP	Amplifier	HP8447E	1937A01046	2015-05-06	2016-05-05
Sunol Sciences	Bi-log Antenna	JB1	A040904-2	2014-12-07	2017-12-06
Rohde & Schwarz	Signal Analyzer	FSIQ26	8386001028	2015-12-11	2016-12-11
Sunol Sciences	Horn Antenna	DRH-118	A052304	2015-12-01	2018-11-30
HP	Synthesized Sweeper	HP 8341B	2624A00116	2015-07-02	2016-07-01
Mini	Amplifier	ZVA-183-S+	5969001149	2015-04-23	2016-04-22
A.H. System	tem Horn Antenna SAS-200/57		135	2015-08-18	2018-08-17
Ducommun technologies	RF Cable	UFA210A-1- 4724-30050U	MFR64369 223410-001	2015-06-15	2016-06-15
Ducommun technologies	RF Cable	104PEA	218124002	2015-06-15	2016-06-15
Ducommun technologies	RF Cable	RG-214	1	2015-06-15	2016-06-15
Ducommun technologies	RF Cable	RG-214	2	2015-06-15	2016-06-15
COM POWER	Dipole Antenna	AD-100	041000	NCR	NCR

Report No.: RSZ160201012-00D

Test Procedure

The transmitter was placed on a wooden turntable, and it was transmitting into a non-radiating load, which was also placed on the turntable.

The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis.

The frequency range up to teeth harmonic of the fundamental frequency was investigated.

Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the spurious emissions were measured by the substitution.

Spurious emissions in dB = 10 1g (TXpwr in Watts/0.001)-the absolute level

Spurious attenuation limit in dB = $50+10 \text{ Log}_{10}$ (power out in Watts) for EUT with a 12.5 kHz channel bandwidth.

Spurious attenuation limit in dB = $55+10 \text{ Log}_{10}$ (power out in Watts) for EUT with a 6.25 kHz channel bandwidth.

FCC PART 90 Page 26 of 32

^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	23 ℃	
Relative Humidity:	52 %	
ATM Pressure:	101.0 kPa	

The testing was performed by Sonia Zhou on 2016-02-19.

Test Mode: Transmitting

30 MHz – 2 GHz:

	Receiver	Turn	Rx An	tenna		Substitut	ed	Absolute	FCC I	Part 90
Frequency (MHz)	Reading (dBµV)	Table Angle Degree	Height (m)	Polar (H/V)	SG Level (dBm)	Cable Loss (dB)	Antenna Gain (dB)	Level (dBm)	Limit (dBm)	Margin (dB)
		Analo	g Modulat	tion 155.0	25MHz, 0	Channel Sp	pacing 12.5	K		
620.10	34.21	80	2.2	Н	-62.8	0.57	0	-63.37	-20	43.37
620.10	35.81	209	1.1	V	-61.2	0.57	0	-61.77	-20	41.77
1240.20	44.23	89	1.2	Н	-62.9	1.50	6.20	-58.20	-20	38.20
1240.20	45.38	294	2.4	V	-63.0	1.50	6.20	-58.30	-20	38.30
		Digita	al Modula	tion 155.0)25MHz, (Channel Sp	pacing 12.5I	ζ		
620.10	35.23	278	1.1	Н	-61.8	0.57	0	-62.37	-20	42.37
620.10	37.12	197	2.3	V	-59.9	0.57	0	-60.47	-20	40.47
1240.20	44.75	134	1.3	Н	-62.4	1.50	6.20	-57.70	-20	37.70
1240.20	45.59	260	1.9	V	-62.8	1.50	6.20	-58.10	-20	38.10

Report No.: RSZ160201012-00D

Note:

Absolute Level = SG Level - Cable loss + Antenna Gain Margin = Limit- Absolute Level

FCC PART 90 Page 27 of 32

FCC §2.1055 & §90.213- FREQUENCY STABILITY

Applicable Standard

FCC §2.1055 and §90.213

Test Equipment List and Details

Manufacturer	Description	Model No.	Serial No.	Calibration Date	Calibration Due Date
Hewlett-Packard	Frequency Counter	5343A	2232A00827	2013-05-09	2016-05-08
ESPEC	Temperature & Humidity Chamber	EL-10KA	09107726	2015-11-01	2016-10-31
Ducommun technologies	RF Cable	RG-214	3	2015-06-15	2016-06-15
JFW	30dB Attenuator	50FH-030-100 RF	170006716507	2015-06-12	2016-06-12
Long Wei	DC Power Supply	TPR-6420D	398363	NCR	NCR

Report No.: RSZ160201012-00D

Test Procedure

Frequency Stability vs. Temperature: The equipment under test was connected to an external DC power supply and the RF output was connected to a frequency counter via feed-through attenuators. The EUT was placed inside the temperature chamber. The DC leads and RF output cable exited the chamber through an opening made for the purpose.

After the temperature stabilized for approximately 20 minutes, the frequency output was recorded from the counter.

Test Data

Environmental Conditions

Temperature:	23 ℃		
Relative Humidity:	52 %		
ATM Pressure:	101.0 kPa		

The testing was performed by Sonia Zhouon 2016-02-19.

Test Mode: Transmitting

FCC PART 90 Page 28 of 32

^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements, traceable to National Primary Standards and International System of Units (SI).

Reference Frequency: 155.025 MHz, Limit: ±5.0 ppm, 12.5 kHz						
Test Envi	ronment	Frequency Meas	ure with Time Elapsed			
Temperature (°C)	Power Supplied (V _{DC})	Measured Frequency (MHz)	Frequency Error (ppm)			
	Frequency Stability versus Input Temperature					
50	7.40	155.024977	-0.135			
40	7.40	155.024975	-0.150			
30	7.40	155.024977	-0.173			
20	7.40	155.024972	-0.175			
10	7.40	155.024975	-0.132			
0	7.40	155.024978	-0.129			
-10	7.40	155.024973	-0.179			
-20	7.40	155.024976	-0.173			
-30	7.40	155.024977	-0.179			
	Frequency Stabi	lity versus Input Volta	ige			
20	6.30	155.024975	-0.163			

Report No.: RSZ160201012-00D

For Digital Modulation

Reference Frequency: 155.025 MHz, Limit: ±5.0 ppm, 12.5 kHz						
Test Environment		Frequency Measure with Time Elapsed				
Temperature (°C)	Power Supplied (V _{DC})	Measured Frequency (MHz)	Frequency Error (ppm)			
	Frequency Stability versus Input Temperature					
50	7.40	155.024978	-0.143			
40	7.40	155.024972	-0.181			
30	7.40	155.024976	-0.155			
20	7.40	155.024975	-0.163			
10	7.40	155.024977	-0.148			
0	7.40	155.024977	-0.149			
-10	7.40	155.024976	-0.153			
-20	7.40	155.024975	-0.160			
-30	7.40	155.024979	-0.134			
Frequency Stability versus Input Voltage						
20	6.30	155.024977	-0.149			

FCC PART 90 Page 29 of 32

FCC §90.214 - TRANSIENT FREQUENCY BEHAVIOR

Applicable Standard

Regulations: FCC §90.214

Test method: ANSI/TIA-603-D 2010, section 2.2.19.3

Test Equipment List and Details

Manufacturer	Description	Model No.	Serial No.	Calibration Date	Calibration Due Date
Rohde & Schwarz	Signal Analyzer	FSIQ26	8386001028	2015-12-11	2016-12-11
НР	RF Communication Test Set	8920A	3325U00859	2015-06-03	2016-06-02
Ducommun technologies	RF Cable	RG-214	3	2015-06-15	2016-06-15
JFW	30dB Attenuator	50FH-030-100 RF	170006716507	2015-06-12	2016-06-12

Report No.: RSZ160201012-00D


Test Procedure

- a) Connect the EUT and test equipment as shown on the following block diagram.
- b) Set the Spectrum Analyzer to measure FM deviation, and tune the RF frequency to the transmitter assigned frequency.
- c) Set the signal generator to the assigned transmitter frequency and modulate it with a 1 kHz tone at ± 12.5 kHz deviation and set its output level to -100dBm.
- d) Turn on the transmitter.
- e) Supply sufficient attenuation via the RF attenuator to provide an input level to the Spectrum Analyzer that is 40 dB below the maximum allowed input power when the transmitter is operating at its rated power level. Note this power level on the Spectrum Analyzer as P₀.
- f) Turn off the transmitter.
- g) Adjust the RF level of the signal generator to provide RF power equal to P₀. This signal generator RF level shall be maintained throughout the rest of the measurement.
- h) Remove the attenuation 1, so the input power to the Spectrum Analyzer is increased by 30 dB when the transmitter is turned on.
- i) Adjust the vertical amplitude control of the spectrum analyzer to display the 1000 Hz at ± 4 divisions vertically centered on the display. Set trigger mode of the Spectrum Analyzer to "Video", and tune the "trigger level" on suitable level. Then set the "tiger offset" to -10ms for turn on and -15ms for turn off.
- j) Turn on the transmitter and the transient wave will be captured on the screen of Spectrum Analyzer. Observe the stored display. The instant when the 1 kHz test signal is completely suppressed is considered to be t_{on}. The trace should be maintained within the allowed divisions during the period t₁ and t₂.

FCC PART 90 Page 30 of 32

^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements, traceable to National Primary Standards and International System of Units (SI).

k) Then turn off the transmitter, and another transient wave will be captured on the screen of Spectrum Analyzer. The trace should be maintained within the allowed divisions during the period t₃.



Test Data

Environmental Conditions

Temperature:	23 ℃	
Relative Humidity:	52 %	
ATM Pressure:	101.0 kPa	

The testing was performed by Sonia Zhouon 2016-02-19.

Test Mode: Transmitting

Channel Separation (kHz)	Transient Period (ms)	Transient Frequency	Result
	5 (t1)	<+/-12.5 kHz	
12.5	20(t2)	<+/-6.25 kHz	Pass
	5 (t3)	<+/-12.5 kHz	


Please refer to the following plots.

FCC PART 90 Page 31 of 32


Channel Spacing 12.5 kHz

Turn on

Report No.: RSZ160201012-00D



Turn off



***** END OF REPORT *****

FCC PART 90 Page 32 of 32