

Choose certainty.
Add value.

Report On

FCC Testing of the Vertex Telecom, Inc. DW33D Damai WiFi AC1750M Dual Band Gigabit Router in accordance with FCC CFR 47 Part 15, Subpart E

COMMERCIAL-IN-CONFIDENCE

FCC ID: 2AE7MRDW33D-E2

Document 57015092 Report 03 Issue 1

September 2015

COMMERCIAL-IN-CONFIDENCE



REPORT ON FCC Testing of the

Vertex Telecom, Inc.

DW33D Damai WiFi AC1750M Dual Band Gigabit Router

Document 57015092 Report 03 Issue 1

September 2015

PREPARED FOR Vertex Telecom, Inc.

980 Corporate Center Dr, Pomona, CA 91768, USA

PREPARED BY

G Zhao

Engineer

Zhao Guigin

APPROVED BY

C Zhang

Manager

DATED 07 September 2015

ENGINEERING STATEMENT

The measurements shown in this report were made in accordance with the procedures described on test pages. All reported testing was carried out on one sample equipment to demonstrate limited compliance with FCC CFR 47 Part 15, Subpart E. The sample tested was found to comply with the requirements defined in the applied rules.

Test Engineer(s);

G Zhao

COMMERCIAL-IN-CONFIDENCE



CONTENTS

| Section | | Page No |
|---|---|---------|
| 1 | REPORT SUMMARY | 3 |
| 1.1 1.2 1.3 1.4 1.5 1.6 1.7 | Introduction Brief Summary of Results Declaration of Build Status Product Information Test Conditions Deviations From the Standard Modification Record | |
| 1.8 2 | Alternative Test Site TEST DETAILS | |
| 2.1 2.2 2.3 2.4 2.5 2.6 2.7 | Conducted Emissions Duty Cycle 99% Occupied Bandwidth, 6dB and 26dB Emission Bandwidth Maximum Conducted Output Power - Average Power Spectral Density - Average Frequency Stability Measurement Radiated Emissions and Band Edge | |
| 3 | TEST EQUIPMENT USED | 58 |
| 3.1 3.2 | Test Equipment Used Measurement Uncertainty | |
| 4 | DISCLAIMERS AND COPYRIGHT | 61 |
| 4.1 | Disclaimers and Copyright | 62 |



SECTION 1

REPORT SUMMARY

FCC Testing of the Vertex Telecom, Inc. DW33D Damai WiFi AC1750M Dual Band Gigabit Router in accordance with FCC CFR 47 Part 15, Subpart E

COMMERCIAL-IN-CONFIDENCE



1.1 INTRODUCTION

The information contained in this report is intended to show verification of the Vertex Telecom, Inc. DW33D Damai WiFi AC1750M Dual Band Gigabit Router to the requirements of FCC CFR 47 Part 15 Subpart E.

Objective To perform FCC Testing to determine the Equipment Under

Test's (EUT's) compliance with the Test Specification, for

the series of tests carried out.

Manufacturer Vertex Telecom, Inc.

Product Name Damai WiFi AC1750M Dual Band Gigabit Router

Product Type DW33D

Serial Number(s) RDW33DI0121150400025

Software Version 00.00.00.01

Hardware Version DW33D V1.0

Number of Samples Tested 1

Test Specification/Issue/Date FCC CFR 47 Part 15, Subpart E: 2014

Start of Test 15 July 2015

Finish of Test 28 August 2015

Name of Engineer(s) G Zhao

COMMERCIAL-IN-CONFIDENCE



1.2 BRIEF SUMMARY OF RESULTS

A brief summary of results in accordance with FCC CFR 47 Part 15, Subpart E.

| Test | Spec Clause | Test Description | Result |
|------|---------------------------|---|--------|
| 2.1 | 15.207, 15.407(b)(6) | Conducted Emission AC Power Port | Pass |
| 2.2 | KDB 789033 D02 II.B | Duty Cycle | - |
| 2.3 | 15.407(a), 15.407(e) | 99% Occupied Bandwidth 6dB and 26dB Emission Bandwidth | Pass |
| 2.4 | 15.407(a)(3) | Maximum Conducted Output Power - Average | Pass |
| 2.5 | 15.407(a)(3) | Power Spectral Density | Pass |
| 2.6 | 15.407(g) | Frequency Stability | Pass |
| 2.7 | 15.205, 15.209, 15.407(b) | Radiated Emissions and Band Edge | Pass |



1.3 DECLARATION OF BUILD STATUS

| MAIN EUT | | | |
|---|--|------------------|--|
| Manufacture | Vertex Telecom, Inc. | | |
| Product Name | Damai WiFi AC1750M Dual Band Gigabit Router | | |
| Product Type | DW33D | | |
| Serial Number | RDW33DI0121150400025 | | |
| Radio Access Technology | WLAN | | |
| Hardware Version | DW33D V1.0 | | |
| Software Version | 00.00.00.01 | | |
| Operating Frequency | 2400MHz to 2483.5MHz, 57 | 25MHz to 5850MHz | |
| Transfer Rate | 802.11b: 1Mbps, 2Mbps, 5.5Mbps, 11Mbps 802.11a/g: 6Mbps, 9Mbps, 12Mbps, 18Mbps, 24Mbps, 36Mbps, 48Mbps, 54Mbps 802.11n: up to 450Mbps 802.11ac: up to 1299.9Mbps | | |
| Number of channel | For 2400MHz to 2483.5MHz 802.11b/g/n(20MHz): 11 802.11n(40MHz): 7 For 5725MHz to 5850MHz: 802.11a/11n(20MHz)/11ac(20MHz): 5 802.11n(40MHz)/11ac(40MHz): 2 802.11ac(80MHz): 1 | | |
| Modulation Type | 802.11ac(60MHz). 1 802.11b: DSSS (CCK, DQPSK, DBPSK) 802.11a/g: OFDM (64QAM, 16QAM, QPSK, BPSK) 802.11n: OFDM (64QAM, 16QAM, QPSK, BPSK) 802.11ac: OFDM (256QAM, 64QAM, 16QAM, QPSK, BPSK) | | |
| Maximum Output Power (dBm) | Band 2400MHz to 2483.5M Band 5725MHz to 5850MHz | | |
| Antenna Gain (dBi) | Band 2400MHz to 2483.5M Band 5725MHz to 5850MH: | | |
| Antenna Number | 3 | | |
| FCC ID | 2AE7MRDW33D-E2 | | |
| Environment temperature range(s) | Minimum | Maximum | |
| | 0 °C +40 °C | | |
| DC Power source | 12.0V | | |
| TECHNICAL DESCRIPTION (a brief description of the intended use and operation) | This Damai WiFi AC1750M Dual Band Gigabit Router is an indoor access, which operates on the frequency band 2400MHz to 2483.5MHz and band 5725MHz to 5850MHz. | | |

No responsibility will be accepted by TÜV SÜD Certification and Testing (China) Co., Ltd. Beijing Branch as to the accuracy of the information declared in this document by the manufacturer.



1.4 PRODUCT INFORMATION

1.4.1 Technical Description

The Equipment Under Test (EUT) DW33D is Damai WiFi AC1750M Dual Band Gigabit Router from Vertex Telecom, Inc.

There is only one model with Damai WiFi AC1750M Dual Band Gigabit Router for approval, which is DW33D. This Damai WiFi AC1750M Dual Band Gigabit Router is an indoor access, which operates on the frequency band 2400MHz to 2483.5MHz and band 5725MHz to 5825MHz. Only the test results of frequency band 5725MHz to 5825MHz were shown in this report. A full technical description is held by Vertex Telecom, Inc.

The Equipment Under Test (EUT) is shown in the photograph below. A full technical description can be found in the Manufacturers documentation.



Equipment Under Test



1.4.2 Test Configuration

Configuration 1: 5GHz WLAN

The worst configurations were representative for all traffic scenarios after different data rates for each operating mode were measured. The settings of MIMO mode below were used for all measurements if not otherwise noted.

| Frequency band IV: 5725MHz to 5850MHz | | | |
|---------------------------------------|-----------------|--|--|
| Operating Mode | Data Rate / MCS | | |
| 802.11a | 54Mbps | | |
| 802.11n(20) | MCS6 | | |
| 802.11n(40) | MCS6 | | |
| 802.11ac(20) | MCS8 | | |
| 802.11ac(40) | MCS9 | | |
| 802.11ac(80) | MCS5 | | |

Note: All the information below was used in this report.

802.11n(20) denotes 802.11n with 20MHz nominal channel bandwidth

802.11n(40) denotes 802.11n with 40MHz nominal channel bandwidth

802.11ac(20) denotes 802.11ac with 20MHz nominal channel bandwidth

802.11ac(40) denotes 802.11ac with 40MHz nominal channel bandwidth

802.11ac(80) denotes 802.11ac with 80MHz nominal channel bandwidth

The EUT was powered by a 12.0VDC power supply.

1.4.3 Test Frequencies

The frequencies for measurement are shown in the table below.

| Francisco Dand | Onersting Made | Frequencies (MHz) and Channel Number | | | |
|--------------------|----------------|--------------------------------------|------------|------------|--|
| Frequency Band | Operating Mode | Bottom(B) | Middle(M) | Top(T) | |
| | 802.11a | 5745 (149) | 5785 (157) | 5825 (165) | |
| | 802.11n(20) | 5745 (149) | 5785 (157) | 5825 (165) | |
| Band IV | 802.11n(40) | 5755 (151) | - | 5795(159) | |
| 5725MHz to 5850MHz | 802.11ac(20) | 5745 (149) | 5785 (157) | 5825 (165) | |
| | 802.11ac(40) | 5755 (151) | - | 5795(159) | |
| | 802.11ac(80) | | 5775 (155) | | |

1.5 TEST CONDITIONS

For all tests the EUT was set up in accordance with the relevant test standard and to represent typical operating conditions. Tests were applied with the EUT situated in a shielded enclosure, test laboratories or an open test area as appropriate.

1.6 DEVIATIONS FROM THE STANDARD

No deviations from the applicable test standards or test plan were made during testing.

COMMERCIAL-IN-CONFIDENCE



1.7 MODIFICATION RECORD

No modifications were made to the EUT during testing.

1.8 ALTERNATIVE TEST SITE

The testing was conducted at following site registrations:

FCC Accreditation 910917:

The State Radio Monitoring Center, No.80 Beilishi Road Xicheng District Beijing, China.



SECTION 2

TEST DETAILS

FCC Testing of the Vertex Telecom, Inc.
DW33D Damai WiFi AC1750M Dual Band Gigabit Router in accordance with FCC CFR 47 Part 15 Subpart E



2.1 CONDUCTED EMISSIONS

2.1.1 Specification Reference

FCC CFR 47 Part 15, Clause 15.207, 15.407(b)(6)

2.1.2 Equipment Under Test

DW33D, S/N: RDW33DI0121150400025

2.1.3 Date of Test and Modification State

17 July 2015 – Modification State 0

2.1.4 Test Equipment Used

The major items of test equipment used for the above tests are identified in Section 3.1.

2.1.5 Test Method

The test was applied in accordance with the test method requirements in clause 15.207 and 15.407 of FCC CFR 47 Part 15, Subpart E.

The test was performed in a shield room, and EUT was placed on a table, which was 0.8m above ground plane. The power line of the EUT was connected to the AC mains through a line Impedance Stabilization Network (LISN). The EUT was control to operate at traffic mode with maximum output power on MIMO mode.

A EMI test receiver was used to test the emissions from both sides of AC line. The conducted emission is scanned over the frequency from 150kHz to 30MHz with peak detector. A final measurement is performed with quasi-peak detector and average detector.

2.1.6 Environmental Conditions


Ambient Temperature 25.5°C Relative Humidity 50.5%



2.1.7 Test Results

The test results are shown below.

L Line:



MEASUREMENT RESULT: "07-17_fin QP"


| Frequency MHz | Level dBµV | Transd dB | Limit dBµV | Margin dB |
|------------------|---------------|--------------|---------------|--------------|
| 0.155000 | 45.70 | 20.1 | 66 | 20.0 |
| 0.445000 | 36.40 | 20.1 | 57 | 20.6 |
| 2.045000 | 29.70 | 20.3 | 56 | 26.3 |
| 3.110000 | 30.30 | 20.3 | 56 | 25.7 |
| 6.005000 | 26.20 | 20.4 | 60 | 33.8 |
| 14.115000 | 25.50 | 20.7 | 60 | 34.5 |

MEASUREMENT RESULT: "07-17_fin AV"

| Frequency MHz | Level dBuV | Transd dB | Limit dBµV | Margin dB |
|----------------------|----------------|--------------|---------------|--------------|
| | | 20.2 | • | |
| 0.300000 0.425000 | 23.90 25.80 | 20.2 | 50 47 | 26.4 21.5 |
| 2.040000 | 23.50 | 20.3 | 46 | 22.5 |
| 3.085000 | 25.70 | 20.3 | 46 | 20.3 |
| 7.755000 | 21.10 | 20.5 | 50 | 28.9 |
| 14.025000 | 20.10 | 20.7 | 50 | 29.9 |



N Line:



MEASUREMENT RESULT: "07-17_fin QP"

| Frequency MHz | Level dBµV | Transd dB | Limit dBµV | _ |
|------------------|---------------|--------------|---------------|------|
| 0.155000 | 43.60 | 20.1 | 66 | 22.2 |
| 0.440000 | 36.00 | 20.1 | 57 | 21.1 |
| 2.120000 | 32.20 | 20.3 | 56 | 23.8 |
| 3.540000 | 29.70 | 20.3 | 56 | 26.3 |
| 5.790000 | 28.70 | 20.4 | 60 | 31.3 |
| 14.355000 | 28.40 | 20.7 | 60 | 31.6 |

MEASUREMENT RESULT: "07-17_fin AV"

| Frequency MHz | Level dBµV | Transd dB | Limit dBµV | |
|------------------|---------------|--------------|---------------|------|
| 0.305000 | 26.70 | 20.2 | 50 | 23.4 |
| 0.420000 | 27.00 | 20.1 | 47 | 20.4 |
| 2.120000 | 24.30 | 20.3 | 46 | 21.7 |
| 3.125000 | 25.60 | 20.3 | 46 | 20.4 |
| 5.825000 | 23.00 | 20.4 | 50 | 27.0 |
| 15 405000 | 21 40 | 20.7 | 50 | 28.6 |

COMMERCIAL-IN-CONFIDENCE



| Frequency (MHz) | QP Limit (dBµV) | AV Limit (dBμV) | |
|-----------------|-----------------|-----------------|--|
| 0.150-0.500 | 66-56* | 56-46* | |
| 0.500-5 | 56 | 46 | |
| 5-30 | 60 | 50 | |

^{*}Decreasing linearly with logarithm of the frequency

Remarks

The result of test did not exceed the limits at the measured frequencies.



2.2 DUTY CYCLE

2.2.1 Specification Reference

FCC KDB 789033 D02 II.B

2.2.2 Equipment Under Test

DW33D, S/N: RDW33DI0121150400025

2.2.3 Date of Test and Modification State

03 and 04 August 2015 - Modification State 0

2.2.4 Test Equipment Used

The major items of test equipment used for the above tests are identified in Section 3.1.

2.2.5 Test Method

The test was applied in accordance with the requirements in FCC KDB 789033 D02 Chapter II.B.

The EUT was connected to the spectrum analyzer via an RF cable, and was controlled to transmitting at its maximum output power. Test procedures refer to II.B of KDB 789033 D02. The analyzer was set to zero-span mode, and RBW and VBW were set to 10MHz. Only the duty cycle of ANT3 was measured and recorded.

The path loss was measured and entered as a reference level offset.

2.2.6 Environmental Conditions

Ambient Temperature 22.8 - 24.5°C Relative Humidity 51.5 - 53.0%



2.2.7 Test Results

For the period of test the EUT met the requirements of FCC KDB 789033 D02 Chapter II.B for Duty Cycle.

The test results are shown below.

Band IV


| Operating Mode | Data Rate | Frequency (MHz) | Duty Cycle (%) |
|----------------|-----------|-----------------|----------------|
| 11a | 54Mbps | 5745 | 79.08 |
| 11a | 54Mbps | 5785 | 79.90 |
| 11a | 54Mbps | 5825 | 79.90 |
| 11n(20) | MCS6 | 5745 | 77.11 |
| 11n(20) | MCS6 | 5785 | 79.90 |
| 11n(20) | MCS6 | 5825 | 80.00 |
| 11n(40) | MCS6 | 5755 | 67.97 |
| 11n(40) | MCS6 | 5795 | 67.97 |
| 11ac(20) | MCS8 | 5745 | 75.30 |
| 11ac(20) | MCS8 | 5785 | 75.76 |
| 11ac(20) | MCS8 | 5825 | 74.85 |
| 11ac(40) | MCS9 | 5755 | 63.06 |
| 11ac(40) | MCS9 | 5795 | 63.06 |
| 11ac(80) | MCS5 | 5775 | 53.41 |




The test plots are shown below

802.11a

Configuration 1 - 5745MHz, 5785MHz and 5825MHz



Duty Cycle - 5825MHz




Date: 3.AUG.2015 15:20:55




802.11n(20)

Configuration 1 - 5745MHz, 5785MHz and 5825MHz



Duty Cycle - 5825MHz




Date: 3.AUG.2015 17:19:16




802.11n(40)

Configuration 1 - 5755MHz and 5795MHz





802.11ac(20)

Configuration 1 - 5745MHz, 5785MHz and 5825MHz










Date: 3.AUG.2015 18:35:2


802.11ac(40)

Configuration 1 - 5755MHz and 5795MHz

Duty Cycle - 5755MHz



Duty Cycle - 5795MHz




Date: 4.AUG.2015 14:37:05


Date: 4.AUG.2015 14:13:51



802.11ac(80)

Configuration 1 - 5775MHz





Date: 4.AUG.2015 16:09:09

Remarks

The duty cycles of EUT for each mode are lower than 98%.



2.3 99% OCCUPIED BANDWIDTH, 6DB AND 26DB EMISSION BANDWIDTH

2.3.1 Specification Reference

FCC CFR 47 Part 15, Clause 15.407(a), 15.407(e)

2.3.2 Equipment Under Test

DW33D, S/N: RDW33DI0121150400025

2.3.3 Date of Test and Modification State

03 and 04 August 2015 - Modification State 0

2.3.4 Test Equipment Used

The major items of test equipment used for the above tests are identified in Section 3.1.

2.3.5 Test Method

The test was applied in accordance with the test method requirements in clause 15.407 of FCC CFR 47 Part 15 Subpart E.

The EUT was connected to the spectrum analyzer, and tranmitting on its maximum output power.

For FCC requirement, outside of which all emissions are attenuated by at least X dB below the transmitter power, where the value of X is typically specified as 6 and 26. In addition, the 99% Occupied Bandwidth was measured. The limit for 6dBc bandwidth should be ≥500kHz. Test procedures refer to Bandwidth Measurement in KDB 789033 D02. The peak detector was used for measurement.

The test was performed with the EUT in the following configurations and modes of operation:

2.3.6 Environmental Conditions

Ambient Temperature 22.8 - 24.5°C Relative Humidity 51.5 - 53.0%



2.3.7 Test Results

For the period of test the EUT met the requirements of FCC CFR 47 Part 15 for Occupied Band width and Emission Bandwidth.

The test results are shown below.

99% Occupied Bandwidth

Band IV

| Operating | Data Rate | Frequency | Tes | st Result (M | Hz) |
|-----------|-----------|-----------|-------|--------------|-------|
| Mode | Dala Nale | (MHz) | ANT1 | ANT2 | ANT3 |
| 11a | 54Mbps | 5745 | 16.83 | 16.73 | 16.73 |
| 11a | 54Mbps | 5785 | 16.78 | 16.78 | 16.78 |
| 11a | 54Mbps | 5825 | 16.78 | 16.73 | 16.83 |
| 11n(20) | MCS6 | 5745 | 17.88 | 17.88 | 17.88 |
| 11n(20) | MCS6 | 5785 | 17.88 | 17.88 | 17.88 |
| 11n(20) | MCS6 | 5825 | 17.88 | 17.93 | 17.88 |
| 11n(40) | MCS6 | 5755 | 36.73 | 36.73 | 36.73 |
| 11n(40) | MCS6 | 5795 | 36.73 | 36.83 | 36.83 |
| 11ac(20) | MCS8 | 5745 | 17.88 | 17.88 | 17.88 |
| 11ac(20) | MCS8 | 5785 | 17.88 | 17.93 | 17.88 |
| 11ac(20) | MCS8 | 5825 | 17.84 | 17.88 | 17.98 |
| 11ac(40) | MCS9 | 5755 | 36.73 | 36.73 | 36.73 |
| 11ac(40) | MCS9 | 5795 | 36.73 | 36.73 | 36.83 |
| 11ac(80) | MCS5 | 5775 | 76.73 | 76.73 | 76.73 |

26dB Emission Bandwidth

Band IV

| Operating Mode | Data Rate | Frequency | Test Result (MHz) | | | |
|-------------------|-----------|-----------|-------------------|-------|-------|--|
| | | (MHz) | ANT1 | ANT2 | ANT3 | |
| 11a | 54Mbps | 5745 | 22.84 | 22.79 | 23.51 | |
| 11a | 54Mbps | 5785 | 23.17 | 23.89 | 24.23 | |
| 11a | 54Mbps | 5825 | 23.89 | 23.85 | 25.48 | |
| 11n(20) | MCS6 | 5745 | 23.32 | 23.37 | 23.56 | |
| 11n(20) | MCS6 | 5785 | 23.80 | 24.18 | 23.56 | |
| 11n(20) | MCS6 | 5825 | 23.94 | 23.99 | 24.28 | |
| 11n(40) | MCS6 | 5755 | 45.29 | 46.06 | 45.96 | |
| 11n(40) | MCS6 | 5795 | 45.77 | 46.15 | 46.25 | |
| 11ac(20) | MCS8 | 5745 | 23.37 | 23.46 | 23.65 | |
| 11ac(20) | MCS8 | 5785 | 23.61 | 24.04 | 24.28 | |
| 11ac(20) | MCS8 | 5825 | 23.27 | 23.80 | 24.86 | |
| 11ac(40) | MCS9 | 5755 | 45.58 | 45.10 | 45.29 | |
| 11ac(40) | MCS9 | 5795 | 45.96 | 46.06 | 45.48 | |
| 11ac(80) | MCS5 | 5775 | 95.00 | 94.62 | 93.85 | |



6dB Emission Bandwidth


Band IV


| Operating Mode | Data Rate | Frequency (MHz) | Test Result (MHz) | | | |
|-------------------|-----------|--------------------|-------------------|-------|-------|--|
| | | | ANT1 | ANT2 | ANT3 | |
| 11a | 54Mbps | 5745 | 16.59 | 16.59 | 16.59 | |
| 11a | 54Mbps | 5785 | 16.59 | 16.59 | 16.57 | |
| 11a | 54Mbps | 5825 | 16.59 | 16.59 | 16.59 | |
| 11n(20) | MCS6 | 5745 | 17.84 | 17.84 | 17.84 | |
| 11n(20) | MCS6 | 5785 | 17.84 | 17.84 | 17.84 | |
| 11n(20) | MCS6 | 5825 | 17.84 | 17.84 | 17.84 | |
| 11n(40) | MCS6 | 5755 | 36.73 | 36.73 | 36.63 | |
| 11n(40) | MCS6 | 5795 | 36.73 | 36.63 | 36.63 | |
| 11ac(20) | MCS8 | 5745 | 17.84 | 17.84 | 17.84 | |
| 11ac(20) | MCS8 | 5785 | 17.84 | 17.84 | 17.84 | |
| 11ac(20) | MCS8 | 5825 | 17.84 | 17.84 | 17.84 | |
| 11ac(40) | MCS9 | 5755 | 36.63 | 36.63 | 36.63 | |
| 11ac(40) | MCS9 | 5795 | 36.73 | 36.63 | 36.63 | |
| 11ac(80) | MCS5 | 5775 | 76.73 | 76.92 | 76.92 | |

Only the test plots of ANT3 are shown below

802.11a

Configuration 1 - 5745MHz, 5785MHz and 5825MHz






Date: 3.AUG.2015 16:07:35

Document 57015092 Report 03 Issue 1




Product Service






26dB Emission Bandwidth - 5745MHz




Date: 3.AUG.2015 15:09:4

Date: 3.AUG.2015 14:43:27

26dB Emission Bandwidth - 5785MHz




26dB Emission Bandwidth - 5825MHz




Date: 3.AUG.2015 16:09:02

Date: 3.AUG.2015 15:05:24

6dB Emission Bandwidth - 5745MHz



6dB Emission Bandwidth - 5785MHz




Date: 3.AUG.2015 16:10:47

Date: 3.AUG.2015 14:45:35









Date: 3.AUG.2015 15:11:13

802.11n(20)

Configuration 1 - 5745MHz, 5785MHz and 5825MHz




99% Occupied Bandwidth - 5785MHz




Date: 3.AUG.2015 17:05:13

Date: 3.AUG.2015 16:18:12

99% Occupied Bandwidth - 5825MHz



26dB Emission Bandwidth - 5745MHz




Date: 3.AUG.2015 17:03:40

Date: 3.AUG.2015 17:21:53




Product Service

26dB Emission Bandwidth - 5785MHz




26dB Emission Bandwidth - 5825MHz




Date: 3.AUG.2015 16:20:15

Date: 3.AUG.2015 17:21:21

6dB Emission Bandwidth - 5745MHz




6dB Emission Bandwidth - 5785MHz



Date: 3.AUG.2015 17:06:25

Date: 3.AUG.2015 16:22:50

6dB Emission Bandwidth - 5825MHz



Date: 3.AUG.2015 17:23:42



802.11n(40)


Configuration 1 - 5755MHz and 5795MHz

99% Occupied Bandwidth - 5795MHz




Date: 4.AUG.2015 10:21:58

26dB Emission Bandwidth - 5755MHz



26dB Emission Bandwidth - 5795MHz


Date: 4.AUG.2015 10:50:44




Date: 4.AUG.2015 10:19:48

Date: 4.AUG.2015 10:51:48

6dB Emission Bandwidth - 5755MHz



6dB Emission Bandwidth - 5795MHz




Date: 4.AUG.2015 10:54:39

Date: 4.AUG.2015 10:24:17



802.11ac(20)

Configuration 1 - 5745MHz, 5785MHz and 5825MHz




Date: 3.AUG.2015 18:52:10

Date: 3.AUG.2015 18:25:57




Product Service






6dB Emission Bandwidth - 5785MHz



: 3.AUG.2015 19:34:08

Date: 3.AUG.2015 18:54:18

6dB Emission Bandwidth - 5825MHz




Date: 3.AUG.2015 18:28:57


802.11ac(40)

Configuration 1 - 5755MHz and 5795MHz

99% Occupied Bandwidth - 5755MHz




99% Occupied Bandwidth - 5795MHz




Date: 4.AUG.2015 14:19:27



Product Service




26dB Emission Bandwidth - 5795MHz




Date: 4.AUG.2015 14:25:56

Date: 4.AUG.2015 14:17:35

6dB Emission Bandwidth - 5755MHz



6dB Emission Bandwidth - 5795MHz




Date: 4.AUG.2015 14:21:02

802.11ac(80)


Date: 4.AUG.2015 14:27:37

Configuration 1 - 5775MHz

99%Occupied Bandwidth - 5775MHz




26dB Emission Bandwidth - 5775MHz




Date: 4.AUG.2015 16:15:39

Date: 4.AUG.2015 16:16:51







Date: 4.AUG.2015 16:19:00

| 6 dB Bandwidth Limit | ≥ 500kHz |
|----------------------|----------|
| 0 db bandwidth Linnt | E 300KHZ |

Remarks

The results of test did not exceed the limits at the measured frequencies.



2.4 MAXIMUM CONDUCTED OUTPUT POWER - AVERAGE

2.4.1 Specification Reference

FCC CFR 47 Part 15, Clause 15.407(a)(3)

2.4.2 Equipment Under Test

DW33D, S/N: RDW33DI0121150400025

2.4.3 Date of Test and Modification State

26 August 2015 - Modification State 0

2.4.4 Test Equipment Used

The major items of test equipment used for the above tests are identified in Section 3.1.

2.4.5 Test Method

The test was applied in accordance with the requirements in clause 15.407 of FCC CFR 47 Part 15 Subpart E.

The EUT was connected to the spectrum analyzer via an RF cable. The path loss of the cable was measured and entered as an offset. The peak level was recorded and compared with the test limits. According to the duty cycle measurement, the test procedures refer to Method SA-3 of Maximum Conducted Output Power in KDB 789033 D02. The channel bandwidth was sent as the 99% occupied bandwidth measured. The RMS detector was used for measurement.

The path loss was measured and entered as a reference level offset.

2.4.6 Environmental Conditions

Ambient Temperature 22.8°C Relative Humidity 48.5%



2.4.7 Test Results

For the period of test the EUT met the requirements of FCC CFR 47 Part 15 for Maximum Conducted Output Power.

The test results are shown below.


Band IV


| Operating | Data | Frequency (MHz) | Conducted Output Power | | | | |
|-----------|--------------|--------------------|------------------------|-------|-------|-------|-------|
| Mode | Data Rate | | dBm | | | mW | |
| wode | | | ANT1 | ANT2 | ANT3 | Total | Total |
| 11a | 54Mbps | 5745 | 12.01 | 12.43 | 12.90 | 17.23 | 52.88 |
| 11a | 54Mbps | 5785 | 13.90 | 13.38 | 14.16 | 18.60 | 72.39 |
| 11a | 54Mbps | 5825 | 13.75 | 13.28 | 13.74 | 18.37 | 68.65 |
| 11n(20) | MCS6 | 5745 | 12.07 | 12.36 | 12.86 | 17.21 | 52.64 |
| 11n(20) | MCS6 | 5785 | 13.82 | 13.35 | 14.03 | 18.51 | 71.02 |
| 11n(20) | MCS6 | 5825 | 13.66 | 13.16 | 13.71 | 18.29 | 67.43 |
| 11n(40) | MCS6 | 5755 | 11.50 | 11.42 | 11.81 | 16.35 | 43.16 |
| 11n(40) | MCS6 | 5795 | 12.78 | 11.91 | 12.64 | 17.23 | 52.86 |
| 11ac(20) | MCS8 | 5745 | 12.11 | 12.25 | 12.87 | 17.19 | 52.41 |
| 11ac(20) | MCS8 | 5785 | 14.02 | 13.18 | 14.03 | 18.53 | 71.32 |
| 11ac(20) | MCS8 | 5825 | 13.86 | 13.24 | 13.73 | 18.39 | 69.01 |
| 11ac(40) | MCS9 | 5755 | 11.52 | 11.36 | 11.80 | 16.34 | 43.00 |
| 11ac(40) | MCS9 | 5795 | 12.80 | 11.92 | 12.74 | 17.28 | 53.41 |
| 11ac(80) | MCS5 | 5775 | 8.50 | 7.92 | 8.40 | 13.05 | 20.19 |

Only the test plots of ANT3 are shown below

802.11a

Configuration 1 - 5745MHz, 5785MHz and 5825MHz






Date: 26.AUG.2015 13:38:31 Date: 26.AUG.2015 13:36:53



Conducted Output Power - 5825MHz




Date: 26.AUG.2015 13:34:24

802.11n(20)

Configuration 1 - 5745MHz, 5785MHz and 5825MHz

Conducted Output Power - 5745MHz




Conducted Output Power - 5785MHz



Date: 26.AUG.2015 13:40:16

Date: 26.AUG.2015 13:43:18

Conducted Output Power - 5825MHz



Date: 26.AUG.2015 13:49:20



802.11n(40)

Configuration 1 - 5755MHz and 5795MHz

Conducted Output Power - 5795MHz




Date: 26.AUG.2015 14:05:31


Date: 26.AUG.2015 14:07:44

802.11ac(20)

Configuration 1 - 5745MHz, 5785MHz and 5825MHz



Conducted Output Power - 5785MHz




Date: 26.AUG.2015 13:59:12

Date: 26.AUG.2015 13:56:52



Conducted Output Power - 5825MHz




Date: 26.AUG.2015 13:53:37


802.11ac(40)

Configuration 1 - 5755MHz and 5795MHz

Conducted Output Power - 5755MHz



Conducted Output Power - 5795MHz



Date: 26.AUG.2015 14:13:40

Date: 26.AUG.2015 14:11:31



802.11ac(80)

Configuration 1 - 5775MHz

Conducted Output Power - 5775MHz



Date: 26.AUG.2015 14:19:16

| Limit | ≤30dBm or ≤1000mW (Directional Antenna Gain ≤ 6dBi) |
|-------|---|
| | ≤26.2dBm* (Directional Antenna Gain> 6dBi) |

*Note: The directional antenna gain = 5dBi+10log (3) =9.8dBi, so the limit = 30dBm-(9.8dBi-6dBi) = 26.2dBm.

Remarks

The maximum output power of EUT did not exceed the limit at the measured frequencies.



2.5 POWER SPECTRAL DENSITY - AVERAGE

2.5.1 Specification Reference

FCC CFR 47 Part 15, Clause 15.407(a)(3)

2.5.2 Equipment Under Test

DW33D, S/N: RDW33DI0121150400025

2.5.3 Date of Test and Modification State

26 August 2015 – Modification State 0

2.5.4 Test Equipment Used

The major items of test equipment used for the above tests are identified in Section 3.1.

2.5.5 Test Method

The test was applied in accordance with the requirements in clause 15.407 of FCC CFR 47 Part 15, Subpart E.

The EUT was connected to the spectrum analyzer via an RF cable, and controlled to transmit on its maximum output power. The peak level was recorded and compared with the test limits.

Test procedures refer to Method SA-3 of KDB 789033 D02, and the test span was set to 1.5*nominal bandwidth of each mode. The RMS detector was used for measurement.

The path loss was measured and entered as a reference level offset.

The test was performed with the EUT in the following configurations and modes of operation:

2.5.6 Environmental Conditions

Ambient Temperature 22.8°C Relative Humidity 48.5%



2.5.7 Test Results

For the period of test the EUT met the requirements of FCC CFR 47 Part 15 for Power Spectral Density.

The test results are shown below.

Band IV

| | | | Average Power Spectral Density | | | | |
|-------------------|--------------|--------------------|--------------------------------|------------|--------|-------|---------------|
| Operating Mode | Data Rate | Frequency (MHz) | | dBm/500kHz | | | mW/500k Hz |
| | | | ANT1 | ANT2 | ANT3 | Total | Total |
| 11a | 54Mbps | 5745 | -0.58 | -1.02 | -0.39 | 4.12 | 2.58 |
| 11a | 54Mbps | 5785 | 0.81 | 0.21 | 0.96 | 5.44 | 3.50 |
| 11a | 54Mbps | 5825 | 0.70 | 0.05 | 0.35 | 5.15 | 3.27 |
| 11n(20) | MCS6 | 5745 | -1.38 | -1.17 | -0.65 | 3.72 | 2.35 |
| 11n(20) | MCS6 | 5785 | 0.42 | -0.07 | 0.42 | 5.03 | 3.19 |
| 11n(20) | MCS6 | 5825 | 0.22 | -0.22 | 0.33 | 4.89 | 3.08 |
| 11n(40) | MCS6 | 5755 | -4.85 | -5.10 | -4.55 | -0.06 | 0.99 |
| 11n(40) | MCS6 | 5795 | -3.58 | -4.53 | -3.75 | 0.84 | 1.21 |
| 11ac(20) | MCS8 | 5745 | -1.18 | -1.20 | -0.62 | 3.78 | 2.39 |
| 11ac(20) | MCS8 | 5785 | 0.36 | -0.48 | 0.70 | 4.99 | 3.16 |
| 11ac(20) | MCS8 | 5825 | 0.46 | -0.12 | 0.07 | 4.91 | 3.10 |
| 11ac(40) | MCS9 | 5755 | -4.71 | -5.08 | -4.59 | -0.02 | 1.00 |
| 11ac(40) | MCS9 | 5795 | -3.13 | -4.39 | -3.64 | 1.08 | 1.28 |
| 11ac(80) | MCS5 | 5775 | -11.00 | -11.62 | -10.97 | -6.42 | 0.23 |

Only the test plots of ANT3 are shown below


802.11a

Configuration 1 - 5745MHz, 5785MHz and 5825MHz





Power Spectral Density - 5825MHz




Date: 26.AUG.2015 13:34:59


802.11n(20)

Configuration 1 - 5745MHz, 5785MHz and 5825MHz

Power Spectral Density - 5745MHz




Power Spectral Density - 5785MHz



Date: 26.AUG.2015 13:40:51

Date: 26.AUG.2015 13:44:41

Power Spectral Density - 5825MHz



Date: 26.AUG.2015 13:46:15



802.11n(40)

Configuration 1 - 5755MHz and 5795MHz




802.11ac(20)

Configuration 1 - 5745MHz, 5785MHz and 5825MHz





Power Spectral Density - 5825MHz




Date: 26.AUG.2015 13:54:15


802.11ac(40)

Configuration 1 - 5755MHz and 5795MHz

Power Spectral Density - 5755MHz



Power Spectral Density - 5795MHz



Date: 26.AUG.2015 14:14:33


Date: 26.AUG.2015 14:09:50



802.11ac(80)

Configuration 1 - 5775MHz

Power Spectral Density - 5775MHz



Date: 26.AUG.2015 14:16:23

| Limit | ≤30dBm/500kHz |
|-------|---------------|
|-------|---------------|

Remarks

The test results of EUT did not exceed the limit at all measured frequencies.



2.6 FREQUENCY STABILITY MEASUREMENT

2.6.1 Specification Reference

FCC CFR 47 Part 15, Clause 15.407(g)

2.6.2 Equipment Under Test

DW33D, S/N: RDW33DI0121150400025

2.6.3 Date of Test and Modification State

15 July 2015 – Modification State 0

2.6.4 Test Equipment Used

The major items of test equipment used for the above tests are identified in Section 3.1.

2.6.5 Test Method

The test was applied in accordance with the test requirements in clause 15.407 of FCC CFR 47 Part 15, Subpart E.

Frequency Stability - Temperature Variation

The EUT was tested over the temperature range -30°C to +50°C in 10°C steps with 120VAC Power Supply. At each temperature step, the EUT was configured to transmit at its maximum power on the lowest and highest channels of the operating band. After achieving thermal balance, the averages of 200 transmission bursts were measured and the result recorded.

Frequency Stability - Voltage Variation

The EUT was tested at the supplied voltages varied from 85 to 115 percent of the nominal values of 120VAC. At +20°C, the EUT was configured to transmit at its maximum power on the lowest and highest channels of the operating band. The average of 200 transmission bursts was measured and the result recorded.

The ANT3 of EUT was measured and recorded, whilst others were terminated.

2.6.6 Environmental Conditions

Ambient Temperature 24.5°C Relative Humidity 57.0%



2.6.7 Test Results

For the period of test the EUT met the requirements of FCC CFR 47 Part 15 for Frequency Stability.

The test results are shown below.

Band IV

Frequency Stability - Temperature Variation

| Supply | | Frequency Stability | | | | |
|-------------------|-------------|---------------------|-----------------|----------------------|-----------------|--|
| Voltage AC (V) | Temperature | Lowest Frequency | Result (MHz) | Highest Frequency | Result (MHz) | |
| | -30°C | | 5745.03285 | | 5825.03271 | |
| | -20°C | 5745MHz | 5745.06078 | 5825MHz | 5825.06165 | |
| | -10°C | | 5745.07236 | | 5825.07323 | |
| | 0°C | | 5745.07467 | | 5825.07583 | |
| 120.0 | +10°C | | 5745.07033 | | 5825.07091 | |
| | +20°C | | 5745.05962 | | 5825.06078 | |
| | +30°C | | 5745.04573 | | 5825.04689 | |
| | +40°C | | 5745.03415 | | 5825.03473 | |
| | +50°C | | 5745.02894 | | 5825.02923 | |

Frequency Stability - Voltage Variation

| Supply | | Frequency Stability | | | | |
|-------------------|-------------|---------------------|-----------------|----------------------|-----------------|--|
| Voltage AC (V) | Temperature | Lowest Frequency | Result (MHz) | Highest Frequency | Result (MHz) | |
| 102.0 | +20°C | 5745MHz | 5745.05991 | 5825MHz | 5825 06049 | |
| 120.0 | | | 5745.05962 | | 5825.06078 | |
| 138.0 | | | 5745.05962 | | 5825 06049 | |

| | Limit | Manufacturers of U-NII devices are responsible for ensuring frequency stability such that an emission is maintained within the band of operation under all conditions of normal operation |
|---|-------|---|
| ١ | | as specified in the user manual. |

Remarks

The test results of EUT did not exceed the limit at all measured frequencies.



2.7 RADIATED EMISSIONS AND BAND EDGE

2.7.1 Specification Reference

FCC CFR 47 Part 15, Clause 15.205, 15.209, 15.407(b)

2.7.2 Equipment Under Test

DW33D, S/N: RDW33DI0121150400025

2.7.3 Date of Test and Modification State

17 July, 26 and 28 August 2015 – Modification State 0

2.7.4 Test Equipment Used

The major items of test equipment used for the above tests are identified in Section 3.1.

2.7.5 Test Method

The test was applied in accordance with the requirements in clause 15.407 of FCC CFR 47 Part 15 Subpart E.

A preliminary profile of the Spurious Radiated Emissions was obtained by operating the EUT on a remotely controlled turntable within the chamber. Measurements of emissions from the EUT were obtained with the Measurement Antenna in both Horizontal and Vertical Polarisations.

Emissions identified within the range 30MHz – 40GHz were then formally measured using a Peak detector as the worst case.

In the frequency Range 30MHz – 40GHz, the measurement was performed with a resolution bandwidth of 1MHz.

The measurements were performed at a 3m distance unless otherwise stated.

The test was performed with the EUT in the following configurations and modes of operation:

2.7.6 Environmental Conditions

Ambient Temperature 22.8 - 25.5°C Relative Humidity 48.5 - 53.0%



2.7.7 Test Results

For the period of test the EUT met the requirements of FCC CFR 47 Part 15 Radiated Emissions and Band Edge.

Radiated Emissions

Note: Only the worst test results plots have been included as all of the unwanted emissions are below the limit. A set of plots have been included to show the measurement system noise floor.

The test results are shown below.

802.11a

Configuration 1 - 5785MHz

No unwanted emissions were dectected beyond the limit.

802.11n(20)

Configuration 1 - 5785MHz

No unwanted emissions were dectected beyond the limit.

802.11ac(20)

Configuration 1 - 5745MHz

No unwanted emissions were dectected beyond the limit.


Configuration 1 - 5785MHz

No unwanted emissions were dectected beyond the limit.




Configuration 1 - 5825MHz

30MHz - 1GHz




1GHz - 3GHz






3GHz - 4GHz




<u>4GHz – 6GHz</u>




Note: The emission beyond the limit is the operating frequency.



<u>6GHz – 8GHz</u>




8GHz - 18GHz






18GHz - 26.5GHz



26.5GHz - 40GHz



COMMERCIAL-IN-CONFIDENCE



802.11n(40)

Configuration 1 - 5795MHz

No unwanted emissions were dectected beyond the limit.

802.11ac(40)

Configuration 1 - 5755MHz

No unwanted emissions were dectected beyond the limit.

Configuration 1 - 5795MHz

No unwanted emissions were dectected beyond the limit.

802.11ac(80)

Configuration 1 - 5775MHz

No unwanted emissions were dectected beyond the limit.



Band Edge


Note: Only the worst test results plots have been included as all of the unwanted emissions are below the limit.

The test results are shown below.

802.11ac(20)

Configuration 1 - 5745MHz


RE-Power_5.685G-5.765GHz





Configuration 1 - 5825MHz


RE-Power_5.810G-5.890GHz



802.11ac(40)

Configuration 1 - 5755MHz


RE-Power_5.685G-5.765GHz





Configuration 1 - 5795MHz


RE-Power_5.810G-5.890GHz



802.11ac(80)

Configuration 1 - 5775MHz

 $RE\text{-}Power_5.685G\text{-}5.765GHz$



COMMERCIAL-IN-CONFIDENCE



| Requirement of Clause 15.209 | | |
|---|---------------------------------|--|
| Frequency range | Limit | |
| 30 MHz to 88 MHz | 40dBμV/m | |
| 88 MHz to 216 MHz | 43.5dBμV/m | |
| 216 MHz to 960 MHz | 46dBμV/m | |
| >960MHz | Average:54dBμV/m, Peak:74dBμV/m | |
| Requirement of Clause 15.407 (b)(4) | | |
| Frequency range | Limit | |
| Frequencies 10 MHz or greater above or below the band edge | Peak: 68.2dBµV/m | |
| Frequency range from the band edge to 10 MHz above or below the band edge | Peak: 78.2dBμV/m | |

Remarks

The test results of EUT did not exceed the limit during the test.



SECTION 3

TEST EQUIPMENT USED



3.1 TEST EQUIPMENT USED

List of absolute measuring and other principal items of test equipment.

| Instrument | Manufacturer | Туре No. | Serial No. | Calibration Period (months) | Calibration Due | |
|---|--|--------------------------|-------------|-----------------------------------|--------------------|--|
| Section 2.1 Conducted Emission | | | | | | |
| EMI Receiver | Rohde & Schwarz | ESIB7 | 100280 | 12 | 15-Aug-2016 | |
| LISN | AFJ | LS16C | 16011306281 | 12 | 01-Apr-2016 | |
| Digital Multimeter | FLUKE | 179 | 91820401 | 12 | 14-Dec-2015 | |
| Thermo- hygrometer | AZ Instruments | 8705 | 9151665 | 12 | 10-Dec-2015 | |
| | l and 2.5 – 6dB and 26 Emissions and Conduc | | | n Conducted O | utput Power- | |
| Spectrum Analyzer | Rohde & Schwarz | FSV40 | 101065 | 12 | 19-Aug-2016 | |
| Power Meter | Agilent | E9327A | MY52420006 | 12 | 29-Feb-2016 | |
| Power Sensor | Agilent | E4416A | MY52370013 | 12 | 29-Feb-2016 | |
| Digital Multimeter | FLUKE | 179 | 91820401 | 12 | 14-Dec-2015 | |
| Thermo- hygrometer | AZ Instruments | 8705 | 9151665 | 12 | 10-Dec-2015 | |
| Section 2.5 – Radi | ated Spurious Emissio | ns | | | | |
| EMI Receiver | Rohde & Schwarz | ESI 40 | 100015 | 12 | 19-Aug-2016 | |
| Ultra log test antenna | Rohde & Schwarz | HL562 | 100167 | 12 | 19-Aug-2016 | |
| Double-Ridged Wave-guide Horn Antenna | Rohde & Schwarz | HF 906 | 100029 | 12 | 19-Aug-2016 | |
| Pyramidal Horn Antenna | EMCO | 3160-09 | - | - | - | |
| Antenna master | Frankonia | MA 260 | - | 12 | 19-Aug-2016 | |
| Relay Switch Unit | Rohde & Schwarz | 331.1601.31 | 338965002 | - | TU | |
| Semi Anechoic Chamber | Frankonia | 23.18m×16.88 m× 9.60m | - | 12 | 19-Aug-2016 | |
| Digital Multimeter | FLUKE | 179 | 91820401 | 12 | 14-Dec-2015 | |
| Thermo- hygrometer | AZ Instruments | 8705 | 9151665 | 12 | 10-Dec-2015 | |

TU - Traceability Unscheduled.



3.2 MEASUREMENT UNCERTAINTY

For a 95% confidence level, the measurement uncertainties for defined systems are:

| Test Discipline | Frequency / Parameter | MU | | |
|--|----------------------------|----------------------|--|--|
| Conducted RF Output Power | 30MHz to 10GHz Amplitude | 0.5dB* | | |
| Conducted Emissions | QP detector AV detector | 3.34 dB 3.39 dB | | |
| Frequency Stability | 30MHz to 6GHz | <±1x10 ⁻⁷ | | |
| Radiated Emissions, Bilog Antenna, AOATS | 30MHz to 1GHz Amplitude | 5.1dB* | | |
| Radiated Emissions, Horn Antenna, AOATS | 1GHz to 40GHz Amplitude | 6.3dB* | | |
| Worst case error for both Time and Frequency measurement 12 parts in 10 ⁶ | | | | |

^{*} In accordance with CISPR 16-4



SECTION 4

DISCLAIMERS AND COPYRIGHT



4.1 DISCLAIMERS AND COPYRIGHT

This report relates only to the actual item/items tested.

This report must not be reproduced without the written permission of TÜV SÜD Certification and Testing (China) Co., Ltd. Beijing Branch

M Building, No. 7 Wangjing Zhonghuan Nanlu, Chaoyang District Beijing 100102 P.R. China

© 2015 TÜV SÜD Certification and Testing (China) Co., Ltd. Beijing Branch