

Project no.: 278347 FCC ID: 2AEAN391002

Page 1 (2)

Nemko Canada, Inc. 303 River Road, Ottawa Ontario K1V1H2 Canada

Letter of Explanation for RØDELink RX-CAM SAR Exemption

FCC ID: 2AEAN391002

Product Type: 2.4 GHz Wireless Microphone

To Whom It May Concern

2.4GHz Wireless Microphone RX SAR Exemption for TCB Certification under Part 15.247

This Wireless Microphone Receiver uses TDMA technology and frequency hopping and operates in the 2.4GHz frequency band.

Operational Description

The equipment is a Wireless Microphone Receiver that operates in the frequency range of 2403 to 2481 MHz with 40 RF channels and channel separation of 2 MHz.

RF Exposure Conditions

The Wireless Microphone Receiver is intended for use in the portable exposure condition and General Population / Uncontrolled exposure environment.

Transmission Mode

Each RF frame is 7.5ms and the frame is divided into 15 transmit slots. The Receiver transmits one packet of 168 bits each 10000 bit frame, alternating every frame between the two active frequencies.

The duty cycle is 168/10000 = 1.7 %



Project no.: 278347 FCC ID: 2AEAN391002

Page 2 (2)

RF Output Power

TX Frequency Range: 2403 – 2481 MHz

Pmax (incl. Tune-Up tolerance): 8.5 + 2.0 + 0.5 = 11 dBm = 12.6 mW

Maximum Duty Factor: 1.7 %

Maximum Tune-Up Tolerance: 0.5 dB

Maximum source-based time-averaged output power, including Tune-Up Tolerance: 0.214 mW

Max. power of channel: 0.214 mW
Min. separation distance: 5 mm
Max. frequency: 2.481 GHz

[(Pwr/Dist)*VFreq.] = 0.1

The result of the above SAR threshold calculation demonstrates that the result is less than the 1-g numeric threshold of 3 and the 10-g numeric threshold of 7.5.

Conclusion: The above analysis shows that the evaluated device qualifies for exemption from SAR testing.

Frode Sveinsen Chief Engineer

Nemko AS

Kjeller, 29-May-2015