RF EXPOSURE REPORT



Report No.: 16070822-FCC-H2
Supersede Report No.: N/A

Applicant	AOC				
Product Name	Tablet PC	Tablet PC			
Model No.	A725				
Serial No.	A721,A722	,A723,A724,A	726,A727,A728	,A729	
Test Standard	FCC 2.1093	3:2015			
Test Date	July 22 to August 05, 2016				
Issue Date	August 06, 2016				
Test Result	Pass	☐ Fail			
Equipment complied with the specification					
Equipment did not comply with the specification					
Loven	Luo	Dewiol	Huang		
Loren Luo Test Engineer			Huang ked By		

This test report may be reproduced in full only

Test result presented in this test report is applicable to the tested sample only

Issued by:

SIEMIC (SHENZHEN-CHINA) LABORATORIES

Zone A, Floor 1, Building 2 Wan Ye Long Technology Park
South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong China 518108
Phone: +86 0755 2601 4629801 Email: China@siemic.com.cn



Test Report	16070822-FCC-H2
Page	2 of 9

Laboratories Introduction

SIEMIC, headquartered in the heart of Silicon Valley, with superior facilities in US and Asia, is one of the leading independent testing and certification facilities providing customers with one-stop shop services for Compliance Testing and Global Certifications.



In addition to testing and certification, SIEMIC provides initial design reviews and compliance management throughout a project. Our extensive experience with China, Asia Pacific, North America, European, and International compliance requirements, assures the fastest, most cost effective way to attain regulatory compliance for the global markets.

Accreditations for Conformity Assessment

Country/Region	Scope
USA	EMC, RF/Wireless, SAR, Telecom
Canada	EMC, RF/Wireless, SAR, Telecom
Taiwan	EMC, RF, Telecom, SAR, Safety
Hong Kong	RF/Wireless, SAR, Telecom
Australia	EMC, RF, Telecom, SAR, Safety
Korea	EMI, EMS, RF, SAR, Telecom, Safety
Japan	EMI, RF/Wireless, SAR, Telecom
Singapore	EMC, RF, SAR, Telecom
Europe	EMC, RF, SAR, Telecom, Safety



Test Report	16070822-FCC-H2
Page	3 of 9

This page has been left blank intentionally.



Test Report	16070822-FCC-H2
Page	4 of 9

CONTENTS

1.	REPORT REVISION HISTORY	5
	CUSTOMER INFORMATION	
۷.	CUSTOMER INFORMATION	2
3.	TEST SITE INFORMATION	5
4.	EQUIPMENT UNDER TEST (EUT) INFORMATION	6
5.	FCC §2.1093 - RADIOFREQUENCY RADIATION EXPOSURE EVALUATION: PORTABLE DEVICES	. 8
5.1	RF EXPOSURE	8
52	TEST RESULT	C



Test Report	16070822-FCC-H2
Page	5 of 9

1. Report Revision History

Report No.	Report Version	Description	Issue Date
16070822-FCC-H2	NONE	Original	August 06, 2016

2. Customer information

Applicant Name	AOC	
Applicant Add	14F-5, NO.258, Liancheng Rd., Zhonghe Dist., New Taipei	
	City, Taiwan	
Manufacturer	China Great Wall Computer Shenzhen Co., Ltd.	
Manufacturer Add	No.Great Wall Computer Industrial Park,Bao Shi East Road,Bao' an	
	Bistrict,Shenzhen,P.R.China	

3. Test site information

Lab performing tests	SIEMIC (Shenzhen-China) LABORATORIES	
	Zone A, Floor 1, Building 2 Wan Ye Long Technology Park	
Lab Address	South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong China	
	518108	
FCC Test Site No.	718246	
IC Test Site No.	4842E-1	
Test Software	Radiated Emission Program-To Shenzhen v2.0	



Description of EUT:

Main Model:

Trade Name:

Test Report	16070822-FCC-H2
Page	6 of 9

4. Equipment under Test (EUT) Information

Tablet PC

A725

Serial Model:	A721,A722,A723,A724,A726,A727,A728,A729
Date EUT received:	July 21, 2016
Test Date(s):	July 22 to August 05, 2016
Antenna Gain:	Bluetooth/BLE/WIFI: 0dBi
Antenna Type:	PIFA antenna
Type of Modulation:	802.11b/g/n: DSSS, OFDM Bluetooth: GFSK, π /4DQPSK, 8DPSK BLE: GFSK
RF Operating Frequency (ies):	WIFI: 802.11b/g/n(20M): 2412-2472 MHz Bluetooth& BLE: 2402-2480 MHz
Number of Channels:	WIFI:802.11b/g/n(20M): 13CH Bluetooth: 79CH BLE: 40CH
Port:	Earphone Port, USB Port , SD Card Port
Input Power:	Adapter: Model:LFS0501500D-A8S Input: AC 100-240V~50/60Hz;0.5A Output: DC 5.0V,1500mA Battery: Spec: 3.7V,2500mAh(9.25Wh)

AOC



Test Report	16070822-FCC-H2
Page	7 of 9

FCC ID: 2AEB5-A725



Test Report	16070822-FCC-H2
Page	8 of 9

5. FCC §2.1093 - Radiofrequency radiation exposure evaluation: portable devices.

5.1 RF Exposure

Standard Requirement:

According to §15.247 (i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] $\cdot \sqrt{f_{(GHz)}} \le 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, 16 where

- f_(GHz) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation¹⁷
- The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is ≤ 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

Routine SAR evaluation refers to that specifically required by § 2.1093, using measurements or computer simulation. When routine SAR evaluation is not required, portable transmitters with output power greater than the applicable low threshold require SAR evaluation to qualify for TCB approval.

result = $P\sqrt{F}/D$

P= Maximum turn-up power in mW

F= Channel frequency in GHz

D= Minimum test separation distance in mm



Test Report	16070822-FCC-H2
Page	9 of 9

5.2 Test Result

Bluetooth Mode:

Modulation	СН	Freque ncy	Conducted Power	Tune Up Power	Max Tune Up Power	Max Tune Up Power	Result	Limit
		(MHz)	(dBm)	(dBm)	(dBm)	(mW)		
GFSK	Low	2402	2.741	3±1	4	2.512	0.78	3
	Mid	2441	2.453	3±1	4	2.512	0.78	3
	High	2480	3.407	3±1	4	2.512	0.79	3
π /4 DQPSK	Low	2402	3.348	3.5±1	4.5	2.818	0.87	3
	Mid	2441	3.119	3.5±1	4.5	2.818	0.88	3
	High	2480	4.068	3.5±1	4.5	2.818	0.89	3
8-DPSK	Low	2402	3.235	3.5±1	4.5	2.818	0.87	3
	Mid	2441	3.009	3.5±1	4.5	2.818	0.88	3
	High	2480	4.051	3.5±1	4.5	2.818	0.89	3

BLE Mode:

Modulation	СН	Freq (MHz)	Conducted Power (dBm)	Tune Up Power (dBm)	Max Tune Up Power (dBm)	Max Tune Up Power (mW)	Result	Limit
GFSK	Low	2402	-4.200	-3.5±1	-2.5	0.562	0.17	3
	Mid	2440	-3.766	-3.5±1	-2.5	0.562	0.18	3
	High	2480	-3.336	-3.5±1	-2.5	0.562	0.18	3

Result: Compliance

No SAR measurement is required.