

FCC PART 15 TEST REPORT

The device described below is tested by Dongguan Nore Testing Center Co., Ltd. to determine the maximum emission levels emanating from the device, the severe levels which the device can endure and E.U.T.'s performance criterion. The test results, data evaluation, test procedures, and equipment of configurations shown in this report were made in accordance with the procedures in ANSI C63.10(2013).

Applicant : Guangde Ledup Enterprise Inc.
Address : Jingtang Road, Economic Development Zone, Xuanchang City, China
Manufacturer & Factory : Guangde Ledup Enterprise Inc
Address : Jingtang Road, Economic Development Zone, Xuanchang City, China
E.U.T. : Remote Control
Brand Name : N/A
Model No. : 102R5-1701B1W, 132STR5-1801B1W, 226R5-1801B1W
(For model difference refer to section 1)
FCC ID : 2AEBHT2R51801B1
Measurement Standard : FCC PART 15.231
Date of Receiver : April 03, 2018
Date of Test : April 03, 2018 to April 25, 2018
Date of Report : April 25, 2018

This Test Report is Issued Under the Authority of :

Prepared by



Rose Hu / Engineer

Approved & Authorized Signer



Lori Fan / Authorized Signatory

This test report is for the customer shown above and their specific product only. This report applies to above tested sample only and shall not be reproduced in part without written approval of Dongguan Nore Testing Center Co., Ltd.

Table of Contents

1. GENERAL INFORMATION	4
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST.....	4
1.2 RELATED SUBMITTAL(S) / GRANT (S)	6
1.3 TEST METHODOLOGY	6
1.4 EQUIPMENT MODIFICATIONS.....	6
1.5 SUPPORT DEVICE.....	6
1.6 TEST FACILITY AND LOCATION.....	7
1.7 SUMMARY OF TEST RESULTS.....	8
2. RADIATED EMISSION TEST.....	9
2.1 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION).....	9
2.2 MEASUREMENT PROCEDURE.....	10
2.3 LIMIT.....	11
2.4 MEASUREMENT RESULTS	12
3. OCCUPIED BANDWIDTH.....	17
3.1 MEASUREMENT PROCEDURE	17
3.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	17
3.3 LIMIT	17
3.4 MEASUREMENT RESULTS	17
4. TRANSMISSION TIME.....	19
4.1 MEASUREMENT PROCEDURE	19
4.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	19
4.3 LIMIT.....	19
4.4 MEASUREMENT RESULTS	19
5. ANTENNA APPLICATION	21
5.1 ANTENNA REQUIREMENT	21
5.2 MEASUREMENT RESULTS.....	21
6. TEST EQUIPMENT LIST.....	22

Revision History of This Test Report

1. GENERAL INFORMATION

1.1 Product Description for Equipment under Test

E.U.T. : Remote Control

Main Model Name : 102R5-1701B1W

Additional Model name : 132STR5-1801B1W, 226R5-1801B1W

Rating : 3* DC 1.5V AAA Battery

Adapter : N/A

Test Voltage : DC 4.5V Battery

Cable : N/A

I/O Port : N/A

Hardware version : V1.0

Software version : V1.0

Description of model difference : These models have the same circuitry, electrical mechanical, PCB layout and physical construction. The differences in model number due to trading purpose.

Note : N/A

Remark : According these model difference, all tests were carried on model 102R5-1701B1W.

Technical parameters

Frequency: : 433.92MHz

Modulation : FSK

Antenna Type : PCB

Antenna Gain : 3dBi

Number of Channels : 1

1.2 Related Submittal(s) / Grant (s)

This submittal(s) (test report) is intended for FCC ID: **2AEBHT2R51801B1** filing to comply with Section 15.231 of the FCC Part 15 (2016), Subpart C Rule.

1.3 Test Methodology

The radiated emission measurement was performed according to the procedures in ANSI C63.10 (2013). Radiated emission measurement was performed in semi-anechoic chamber. For radiated emission measurement, preliminary scans were performed in the semi-anechoic chamber only to determine the worst case modes. All radiated tests were performed at an antenna to EUT distance of 3 meters.

1.4 Equipment Modifications

Not available for this EUT intended for grant.

1.5 Support Device

None

1.6 Test Facility and Location

Site Description

EMC Lab : Listed by CNAS, August 14, 2015
The certificate is valid until August 13, 2018
The Laboratory has been assessed and proved to
be in compliance with CNAS/CL01
The Certificate Registration Number is L5795.

Listed by A2LA, November 01, 2017
The certificate is valid until December 31, 2019
The Laboratory has been assessed and proved to
be in compliance with ISO17025
The Certificate Registration Number is 4429.01

Listed by FCC, November 06, 2017
The Designation Number is CN1214
Test Firm Registration Number: 907417

Listed by Industry Canada, June 08, 2017
The Certificate Registration Number. Is 46405-9743

Name of Firm : Dongguan Nore Testing Center Co., Ltd.
(Dongguan NTC Co., Ltd.)


Site Location : Building D, Gaosheng Science & Technology Park,
Zhouxi Longxi Road, Nancheng District, Dongguan
City, Guangdong Province, China

1.7 Summary of Test Results

FCC Rules	Description Of Test	Result
§15.207	AC Power Conducted Emission	N/A <small>see note 2</small>
§15.231&15.209	Radiated Emission	Compliant
§15.231(c)	Occupied bandwidth	Compliant
§15.231(a)	Transmission time	Compliant
§15.203	Antenna Requirement	Compliant

Note: 1. The EUT has been tested as an independent unit. And Continual transmitting in maximum power (The new battery be used during test)
2. Due to this EUT is powered by battery only, the AC Power Conducted Emission is not applicable.
3. The EUT powered by battery and operating multiple positions, so the EUT shall be performed three orthogonal planes. The worst plane is X.


Example:




2. Radiated Emission Test

2.1 Test SET-UP (Block Diagram of Configuration)

(1) Radiated Emission Test Set-Up, Frequency Below 30MHz



(2) Radiated Emission Test Set-Up, Frequency above 1GHz



2.2 Measurement Procedure

- a. Blow 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi- anechoic chamber room.
- b. For the radiated emission test above 1GHz:
The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter full anechoic chamber room. The table was rotated 360 degrees to determine the position of the highest radiation. Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
- c. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- d. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. The test-receiver system was set to peak detect function and specified bandwidth with maximum hold mode.
- f. A Quasi-peak measurement was then made for that frequency point for below 1GHz test. PK and AV for above 1GHz emission test.

During the radiated emission test, the spectrum analyzer was set with the following configurations:

Frequency Band (MHz)	Level	Resolution Bandwidth	Video Bandwidth
30 to 1000	QP	120 kHz	300 kHz
Above 1000	Peak	1 MHz	3 MHz
	Average	Peak+ AV Factor	

2.3 Limit

Table A [0.009MHz~1GHz]

Frequency range MHz	Distance Meters	Field Strengths Limit (15.209)
		μV/m
0.009 ~ 0.490	300	2400/F(kHz)
0.490 ~ 1.705	30	24000/F(kHz)
1.705 ~ 30	30	30
30 ~ 88	3	100
88 ~ 216	3	150
216 ~ 960	3	200
Above 960	3	500

Remark: (1) Emission level (dB) μ V = 20 log Emission level μ V/m
(2) The smaller limit shall apply at the cross point between two frequency bands.
(3) As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.
(4) The frequency range scanned is from the lowest radio frequency signal generated in the device which is greater than 9 kHz to the tenth harmonic of the highest fundamental frequency or 40 GHz, whichever is lower.

Table B

Fundamental Frequency (MHz)	Field Strength of Fundamental		Field Strength of Spurious Emissions	
	µV/m	dBµV/m	µV/m	dBµV/m
40.66-40.70	2250	67.04	225	47.04
70-130	1250	61.94	125	41.94
130-174	1250-3370**	61.9-70.55	125-375**	41.94-51.48
174-260	3750	71.48	375	51.48
260-470	3750-12500**	71.48-81.94	375-1250**	51.48-61.94
Above 470	12500	81.94	1250	61.94

**) Linear interpolations

2.4 Measurement Results

Note: (1) Emission Level= Reading Level+Probe Factor +Cable Loss
(2) Factor= Antenna Gain + Cable Loss – Amplifier Gain
(3) Measurement uncertainty: $\pm 3.7\text{dB}$
(4) Emission (the row indicated by bold) within the restricted band meets the requirement of FCC part 15 Section 15.205.
(5) Horn antenna used for the emission over 1000MHz.



Dongguan NTC Co., Ltd.
 Tel:+86-769-22022444 Fax:+86-769-22022799
 Web: [Http://www.ntc-c.com](http://www.ntc-c.com)

Radiated Emission Measurement


File :102R5-1701B1W

Data :#22

Date: 2018-4-8

Time: 17:49:28

100.0 dBuV/m



Site

Limit: FCC_part 15C_433M_3M

EUT: Remote Control

M/N: 102R5-1701B1W

Mode: TX

Note:

Polarization: **Horizontal**

Temperature: 26

Power: DC4.5V

Humidity: 47 %

Distance: 3m

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree
1		64.9200	36.93	-15.53	21.40	80.80	-59.40	QP		
2		433.9200	67.75	-11.35	56.40	100.80	-44.40	peak		
3		433.9200	51.35	-11.35	40.00	80.80	-40.80	AVG		
4		502.3900	36.35	-8.75	27.60	80.80	-53.20	QP		
5		621.3211	25.20	-7.00	18.20	80.80	-62.60	QP		
6		677.6376	23.91	-4.41	19.50	80.80	-61.30	QP		
7		737.8378	22.68	-2.88	19.80	80.80	-61.00	QP		
8		867.8400	32.02	-1.12	30.90	80.80	-49.90	peak		
9	*	867.8400	21.22	-1.12	20.10	60.80	-40.70	AVG		

Note: Below 30MHz, the emissions are lower than 20dB below the allowable limit.
 Other emissions are lower than 20dB below the allowable limit. And according to FCC rule, they had not recorded in the report.



Dongguan NTC Co., Ltd.
 Tel:+86-769-22022444 Fax:+86-769-22022799
 Web: [Http://www.ntc-c.com](http://www.ntc-c.com)


Radiated Emission Measurement

File :102R5-1701B1W

Data :#23

Date: 2018-4-8

Time: 17:56:50



Site
 Limit: FCC_part 15C_433M_3M
 EUT: Remote Control
 M/N: 102R5-1701B1W
 Mode: TX
 Note: Remote Control

Polarization: **Vertical**

Temperature: 26

Power: DC4.5V

Humidity: 47 %

Distance: 3m

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Antenna	Table		
			Level	Factor	ment					Degree	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	
1		47.4774	31.10	-13.50	17.60	80.80	-63.20	QP			
2		433.9200	76.85	-11.35	65.50	100.80	-35.30	peak			
3	*	433.9200	64.52	-11.35	53.17	80.80	-27.63	AVG			
4		502.3900	38.65	-8.75	29.90	80.80	-50.90	QP			
5		599.9600	22.89	-6.99	15.90	80.80	-64.90	QP			
6		662.1019	24.64	-4.84	19.80	80.80	-61.00	QP			
7		762.1121	23.73	-2.43	21.30	80.80	-59.50	QP			
8		867.8400	41.68	-1.12	40.56	80.80	-40.24	peak			
9		867.8400	31.36	-1.12	30.24	60.80	-30.56	AVG			

Note: Below 30MHz, the emissions are lower than 20dB below the allowable limit. Other emissions are lower than 20dB below the allowable limit. And according to FCC rule, they had not recorded in the report.



Dongguan NTC Co., Ltd.
 Tel:+86-769-22022444 Fax:+86-769-22022799
 Web: [Http://www.ntc-c.com](http://www.ntc-c.com)


Radiated Emission Measurement

File :102R5-1701B1W

Data :#20

Date: 2018-4-16

Time: 9:01:25



Site Polarization: **Horizontal** Temperature: 26

Limit: FCC_part 15C_433M_3M Power: DC4.5V Humidity: 47 %

EUT: Remote Control Distance: 3m

M/N: 102R5-1701B1W

Mode: TX

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over	Antenna Height	Table Degree		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1		1301.760	64.47	-7.09	57.38	74.00	-16.62	peak			
2		1301.760	54.87	-7.09	47.78	54.00	-6.22	AVG			
3		1735.680	69.39	-4.33	65.06	80.80	-15.74	peak			
4		1735.680	59.79	-4.33	55.46	60.80	-5.34	AVG			
5		2169.600	70.19	-0.47	69.72	80.80	-11.08	peak			
6	*	2169.600	60.59	-0.47	60.12	60.80	-0.68	AVG			
7		2603.520	63.17	0.77	63.94	80.80	-16.86	peak			
8		2603.520	53.57	0.77	54.34	60.80	-6.46	AVG			
9		3038.461	60.87	1.86	62.73	80.80	-18.07	peak			
10		3038.461	51.27	1.86	53.13	60.80	-7.67	AVG			

Other emissions are lower than 20dB below the allowable limit. And according to FCC rule, they had not recorded in the report.



Dongguan NTC Co., Ltd.
 Tel:+86-769-22022444 Fax:+86-769-22022799
 Web: [Http://www.ntc-c.com](http://www.ntc-c.com)

Radiated Emission Measurement


File :102R5-1701B1W

Data :#21

Date: 2018-4-16

Time: 9:10:25

100.0 dBuV/m



Site Polarization: **Vertical** Temperature: 26

Limit: FCC_part 15C_433M_3M Power: DC4.5V Humidity: 47 %

EUT: Remote Control Distance: 3m

M/N: 102R5-1701B1W

Mode: TX

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree
1		1301.760	57.18	-7.09	50.09	74.00	-23.91	peak		
2		1301.760	47.58	-7.09	40.49	54.00	-13.51	AVG		
3		1735.680	60.76	-4.33	56.43	80.80	-24.37	peak		
4		1735.680	51.16	-4.33	46.83	60.80	-13.97	AVG		
5		2169.600	63.37	-0.47	62.90	80.80	-17.90	peak		
6	*	2169.600	53.77	-0.47	53.30	60.80	-7.50	AVG		
7		2603.520	52.41	0.77	53.18	80.80	-27.62	peak		
8		2603.520	42.81	0.77	43.58	60.80	-17.22	AVG		
9		3038.461	55.60	1.86	57.46	80.80	-23.34	peak		
10		3038.461	46.00	1.86	47.86	60.80	-12.94	AVG		

Other emissions are lower than 20dB below the allowable limit. And according to FCC rule, they had not recorded in the report.

3. Occupied Bandwidth

3.1 Measurement Procedure

Same as section 2.2.

3.2 Test SET-UP (Block Diagram of Configuration)

Same as section 2.1.

3.3 Limit

Please refer section 15.231

According to 15.231(C), the bandwidth of the emission shall be no wider than 0.25% of the center frequency for devices operating above 70MHz and below 900MHz.


Limit = $433.92 \times 0.25\% = 1.08 \text{ MHz}$

3.4 Measurement Results

20dB Bandwidth	Limit
128KHz	1.08MHz

Please refer to the following plot.

20dB Bandwidth



Date: 16.APR.2018 13:45:59

4 Transmission Time

4.1 Measurement Procedure

Same as section 2.2.

4.2 Test SET-UP (Block Diagram of Configuration)

Same as section 2.1.

4.3 Limit


According to 15.231(a)(2), A transmitter activated automatically shall cease transmission within 5 seconds after activation.

4.4 Measurement Results

Transmission Time	Limit
0.817s	5s

Please refer to the following plot.

Transmission Time



Date: 16.APR.2018 14:00:50

5. Antenna Application

5.1 Antenna requirement

According to of FCC part 15C section 15.203 and 15.240:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

5.2 Measurement Results

The antenna is integrated on the main PCB and no consideration of replacement, and the best case gain of the antenna is 3dBi. So, the antenna is consider meet the requirement.

6. Test Equipment List

Description	Manufacturer	Model Number	Serial Number	Characteristics	Calibration Date	Calibration Due Date
Test Receiver	Rohde & Schwarz	ESCI7	100837	9KHz~7GHz	Mar. 13, 2018	Mar. 12, 2019
Antenna	Schwarzbeck	VULB9162	9162-010	30MHz~7GHz	Mar. 14, 2018	Mar. 13, 2019
Cable	Huber+Suhner	CBL2-NN-1M	22390001	9KHz~7GHz	Mar. 13, 2018	Mar. 12, 2019
Cable	Huber+Suhner	CIL02	N/A	9KHz~7GHz	Mar. 13, 2018	Mar. 12, 2019
RF Cable	Huber+Suhner	SF-104	MY16559/4	9KHz~25GHz	Apr. 25, 2017	Apr. 25, 2018
Power Amplifier	HP	HP 8447D	1145A00203	100KHz~1.3GHz	Mar. 13, 2018	Mar. 12, 2019
Horn Antenna	Schwarzbeck	BBHA9170	9170-242	15GHz~40GHz	Mar. 13, 2018	Mar. 12, 2019
Horn Antenna	Com-Power	AH-118	071078	1GHz~18GHz	Mar. 14, 2018	Mar. 13, 2019
RF Cable	Huber+Suhner	SF-104	N/A	9KHz~40GHz	Apr. 25, 2017	Apr. 24, 2018
Loop antenna	Daze	ZA30900A	0708	9KHz~30MHz	Apr. 25, 2017	Apr. 24, 2018
Spectrum Analyzer	Rohde & Schwarz	FSU26	200409/026	20Hz~26.5GHz	Apr. 25, 2017	Apr. 24, 2018
Spectrum Analyzer	Rohde & Schwarz	FSV40	101003	10Hz~40GHz	Apr. 06, 2017	Apr. 05, 2018
Pre-Amplifier	EMCI	EMC 184045	980102	18GHz~40GHz	Nov. 03, 2017	Nov. 02, 2018
Pre-Amplifier	Agilent	8449B	3008A02964	1GHz~26.5GHz	Apr. 25, 2017	Apr. 24, 2018
L.I.S.N.	Rohde & Schwarz	ENV 216	101317	9KHz~30MHz	Mar. 13, 2018	Mar. 12, 2019
Temporary antenna connector	TESCOM	SS402	N/A	9KHz-25GHz	N/A	N/A
Power Meter	Anritsu	ML2495A	1139001	100k-65GHz	Nov. 03, 2017	Nov. 02, 2018
Power Sensor	Anritsu	MA2411B	100345	300M-40GHz	Nov. 03, 2017	Nov. 02, 2018

Note: The temporary antenna connector is soldered on the PCB board in order to perform conducted tests and this temporary antenna connector is listed in the equipment list.

---End---