## **FCC 47 CFR MPE REPORT**

#### **BONFIRE ACOUSTIC**

Multi media Bluetooth Speaker system

Model Number: MM2B

FCC ID: 2AECWMM2B

Prepared for : BONFIRE ACOUSTIC

302 222 Maeyeong-ro, Yeongtong-gu, Suwon-si,

Gyeonggi-do, Korea

Prepared By: EST Technology Co., Ltd.

Santun(guantai Road), Houjie Town, DongGuan City,

GuangDong, China.

Tel: 86-769-83081888-808

Report Number: ESTE-R1504022

Date of Test : February 12,2015~ April 22, 2015

Date of Report: April 27, 2015

# **Maximum Permissible Exposure**

#### 1. Applicable Standard

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2m normally can be maintained between the user and the device.

### (a) Limits for Occupational / Controlled Exposure

Frequency	Electric Field	Magnetic	Power	Averaging	
Range (MHz)	Strength E)	Field Strength	Density (S)	Times   E	
	(V/m)	(H) (A/m)	(mW/cm2)	2 ,   H   2 or	
				S (minutes)	
0.3-3.0	614	1.63	(100)*	6	
3.0-30	1842/f	4.89/f	(900/f)*	6	
30-300	61.4	0.163	1.0	6	
300-1500			F/300	6	
1500-10000			5	6	

## (b), Limits for General Population / Uncontrolled Exposure

` '	•				
Frequency	Electric Field	Magnetic	Power	Averaging	
Range (MHz)	Strength E)	Field Strength	Density (S)	Times   E	
	(V/m)	(H) (A/m)	(mW/cm2)	2 ,   H   2 or	
				S (minutes)	
0.3-1.34	614	1.63	(100)*	30	
1.34-30	824/f	2.19/f	(180/f)*	30	
30-300	27.5	0.073	0.2	30	
300-1500			F/1500	30	
1500-10000			1.0	30	

Note: f=frequency in MHz; \*Plane-wave equivalent power density

#### 2. MPE Calculation Method

E (V/m) = (30\*P\*G) 0.5/d Power Density: Pd (W/m2) = E2/377

E = Electric Field (V/m)

P = Peak RF output Power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

Pd = (30\*P\*G) / (377\*d2)

From the peak EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained



# 3. Calculated Result and Limit

Model		Peak	Peak	Ante	enna gain	Target power (dBm)	Power Density (S) (mW/cm2)	Limited of	
		output	output	•	(Linear)			Power	Test
		power	power					Density (S)	Result
		(dBm)	(mW)					(mW/cm2)	
BT	2402	0.12	1.028	-0.61	0.87	0±1	0.00022	1	Compiles
4.0-BLE	2440	2.34	1.714	-0.61	0.87	2±1	0.00035	1	Compiles
GFSK	2480	2.95	1.972	-0.61	0.87	2±1	0.00035	1	Compiles