

RF EXPOSURE EVALUATION METHOD

FCC ID: 2AECY-S-52

SAR Test Exclusion Thresholds for 100 MHz - 6 GHz and \leq 50 mm

Approximate SAR Test Exclusion Power Thresholds at Selected Frequencies and Test Separation Distances are illustrated in the following Table.

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances \leq 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] • [$\sqrt{f(GHz)}$] \leq 3.0 for 1-g SAR and \leq 7.5 for 10-g extremity SAR,where f(GHz) is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation. The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

Maximum measured transmitter power.

BT 3.0

1Mbps								
Test Channel	Frequency	Peak Output Power	Peak Output Power					
	(MHz)	(dBm)	(mW)					
CH00	CH00 2402 -7.85		0.164					
CH39 2441		-7.88	0.163					
CH78	2480	-7.07	0.196					
2Mbps								
CH00	2402	-7.24	0.189					
CH39	2441	-6.35	0.232					
CH78	2480	-5.65	0.272					
3Mbps								
CH00	2402	-6.97	0.201					
CH39	2441	-6.04	0.249					
CH78	2480	-5.37	0.290					

BLE

Test Channe	Frequency	Maximum Conducted Output Power(PK)	Maximum Conducted Output Power(mW)	
	(MHz)	(dBm)	dBm	
CH00	2402	-8.02	0.158	
CH19	2440	-8.09	0.155	
CH39	2480	-7.26	0.188	



Remark: The best case gain of the antenna is 0.5dBi.

0. 5 dBi logarithmic terms convert to numeric result is nearly 1.12

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances \leq 50 mm are determined by: [(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance,mm)] • [$\sqrt{f(GHz)}$]

BT 3.0

	7.0									
Test Channel	Range	tune up max power (dBm)	[(max. power of channel, including tune-up tolerance, mW)	(min. test separation distance,mm)]	[f(GHz)]	Result	Limit			
1Mbps										
CH00	-8~-6	-6	0.251	5	2.402	0.078	3			
CH39	-8~-6	-6	0.251	5	2.441	0.078	3			
CH78	-8~-6	-6	0.251	5	2.480	0.079	3			
			2	Mbps						
CH00	-7.5~-5.5	-5.5	0.282	5	2.402	0.087	3			
CH39	-7.5~-5.5	-5.5	0.282	5	2.441	0.088	3			
CH78	-7.5~-5.5	-5.5	0.282	5	2.480	0.089	3			
	3Mbps									
CH00	-7~-5	-5	0.316	5	2.402	0.098	3			
CH39	-7~-5	-5	0.316	5	2.441	0.099	3			
CH78	-7~-5	-5	0.316	5	2.480	0.100	3			
BLE										
CH00	-9~-7	-7	0.200	5	2.402	0.062	3			
CH19	-9~-7	-7	0.200	5	2.441	0.062	3			
CH39	-9~-7	-7	0.200	5	2.480	0.063	3			

The test Result is less than 3.0 for 1-g SAR and \leq 7.5 for 10-g extremity SAR.

Conclusion: No SAR is required.