

RF Exposure Report

Report No.: SA191211C28 R1

FCC ID: 2AEDS110LTEWIFI

Test Model: SD-WAN 110-LTE-WiFi

Received Date: Dec. 11, 2019

Date of Evaluation: Feb. 27, 2020

Issued Date: Mar. 02, 2020

Applicant: CITRIX SYSTEMS,INC

Address: 4988 Great America Parkway Santa Clara,CA 95054 USA

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
Lin Kou Laboratories

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan

Test Location: No. 19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City
33383, TAIWAN

**FCC Registration /
Designation Number:** 788550 / TW0003



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.

Table of Contents

Release Control Record	3
1 Certificate of Conformity	4
2 RF Exposure	5
2.1 Limits for Maximum Permissible Exposure (MPE)	5
2.2 MPE Calculation Formula	5
2.3 Classification	5
2.4 Calculation Result of Maximum Conducted Power	6

Release Control Record

Issue No.	Description	Date Issued
SA191211C28	Original Release	Feb. 03, 2020
SA191211C28 R1	1. Add FCC ID of WLAN module 2. Remove WLAN 5GHz Band 2 & 3 3. Update WWAN antenna gain 4. Update WLAN power & recalculate MPE	Mar. 02, 2020

1 Certificate of Conformity

Product: Networking device

Brand: **CITRIX®**

Test Model: SD-WAN 110-LTE-WiFi

Sample Status: Engineering Sample

Applicant: CITRIX SYSTEMS, INC


Date of Evaluation: Feb. 27, 2020

Standards: FCC Part 2 (Section 2.1091)

References Test Guidance : KDB 447498 D01 General RF Exposure Guidance v06
IEEE C95.3 -2002

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.


Prepared by :



Date: Mar. 02, 2020

Rona Chen / Specialist

Approved by :



Date: Mar. 02, 2020

Dylan Chiou / Senior Project Engineer

2 RF Exposure

2.1 Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)
Limits For General Population / Uncontrolled Exposure				
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f ²)*	30
30-300	27.5	0.073	0.2	30
300-1500	...	...	f/1500	30
1500-100,000	...	...	1.0	30

f = Frequency in MHz ; *Plane-wave equivalent power density

2.2 MPE Calculation Formula

$$Pd = (P_{out} * G) / (4 * \pi * r^2)$$

where

Pd = power density in mW/cm²

Pout = output power to antenna in mW

G = gain of antenna in linear scale

pi = 3.1416

r = distance between observation point and center of the radiator in cm

2.3 Classification

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as **Mobile Device**.

The WWAN module (Brand: Quectel, Model: EG25-G, EG25-G MINIPCIE) was installed in EUT.

2.4 Calculation Result of Maximum Conducted Power

Band	Frequency Band (MHz)	Max Average Power (dBm)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
WCDMA II	1850-1910	25.00	4.5	20	0.177	1.00
WCDMA IV	1710-1755	25.00	4.5	20	0.177	1.00
WCDMA V	824-849	25.00	1.5	20	0.089	0.55
LTE 2	1850-1910	25.00	4.5	20	0.177	1.00
LTE 4	1710-1755	25.00	4.5	20	0.177	1.00
LTE 5	824-849	25.00	1.5	20	0.089	0.55
LTE 7	2500-2570	25.00	4	20	0.158	1.00
LTE 12	699-716	25.00	2.6	20	0.114	0.47
LTE 13	777-787	25.00	2.6	20	0.114	0.52
LTE 25	1850-1915	25.00	4.5	20	0.177	1.00
LTE 26	814-849	25.00	1.5	20	0.089	0.54
LTE 38	2570-2620	25.00	4	20	0.158	1.00
LTE 41	2496-2690	25.00	4	20	0.158	1.00
The End-product has a WLAN module						
WLAN	2412-2462	21.99	5.61	20	0.114	1.00
	5180-5240	21.71	8.01	20	0.187	1.00
	5745-5825	24.33	8.01	20	0.341	1.00

Note:

1. WLAN 2.4GHz and WLAN 5GHz Band cannot transmit simultaneously.
2. Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.
3. 2.4GHz: Directional gain = 2.6 dBi + 10log(2) = 5.61 dBi
5.0GHz: Directional gain = 5.0 dBi + 10log(2) = 8.01 dBi

Conclusion:

The formula of calculated the MPE is:

$CPD1 / LPD1 + CPD2 / LPD2 + \dots \text{etc.} < 1$

CPD = Calculation power density

LPD = Limit of power density

$WWAN + WLAN\ 2.4G = 0.114 / 0.47 + 0.114 / 1.00 = 0.358$

$WWAN + WLAN\ 5G = 0.114 / 0.47 + 0.341 / 1.00 = 0.585$

Therefore the maximum calculations of above situations are less than the “1” limit.

--- END ---