7560 Lindbergh Drive Gaithersburg, MD 20879 301.216.1500 . info@wll.com

FCC Certification Test Report For the

MARINE INSTRUMENTS, S.A.
M3P BUOY HEAD

FCC ID: 2AEES-MPTR

WLL REPORT# 14489-01 Rev 0 December 13, 2016

Prepared for:

Marine Instruments, S.A. Rúa dos Padróns No 4 (Vial 3) Parque Empresarial Porto do Molle Nigrán, Pontevedra 36350 Spain

> Prepared By: Washington Laboratories, Ltd. 7560 Lindbergh Drive Gaithersburg, Maryland 20879



Testing Certificate AT-1448

FCC Certification Test Report For the

MARINE INSTRUMENTS, S.A.
M3P BUOY HEAD

WLL REPORT# 14489-01 Rev 1 December 13, 2016

Prepared by:

James Ritter EMC Compliance Engineer

Reviewed by:

Steven D. Koster President

Abstract

This report has been prepared on behalf of Marine Instruments, S.A. to support the attached Application for Equipment Authorization. The test report and application are submitted for a Licensed Transmitter under Part 80. This was authorized by the FCC by waiver DA 16-219 granting a waiver of section 80.373(c) to permit use of frequencies 26.145, 26.150, 26.155, 26.160, 26.165, 26.170, and 26.175 MHz to transmit position and related information pertaining to equipment used in fishing operations

Testing was performed at Washington Laboratories, Ltd, 7560 Lindbergh Drive, Gaithersburg, MD 20879.

Washington Laboratories, Ltd. has been accepted by the FCC and approved by ANAB under Certificate AT-1448 as an independent FCC test laboratory.

These tests are accredited and meet the requirements of ISO/IEC 17025 as verified by the ANSI-ASQ National Accreditation Board/ANAB. Refer to certificate and scope of accreditation AT-1448.

The Marine Instruments M3P Buoy Head complies with the limits for a Licensed Transmitter device under FCC Part 80.

| Revision History | Reason | Date |
|------------------|-----------------|-------------------|
| Rev 0 | Initial Release | December 13, 2016 |
| | | |

Table of Contents

| ADSU | ract | |
|-------|--|----|
| 1 | Introduction | |
| 1.1 | 1 | |
| 1.2 | | |
| 1.3 | 3 Contract Information | |
| 1.4 | 4 Test Dates | |
| 1.5 | 5 Test and Support Personnel | |
| 1.6 | | |
| 2 | Equipment Under Test | 3 |
| 2.1 | | |
| 2.2 | 1 | |
| 2.3 | 3 Test Configuration | 3 |
| 2.4 | | |
| 2.5 | | |
| 2.6 | 5 Interface Cables | |
| 2.7 | | |
| 2.8 | | |
| 2.9 | • | |
| 4 | Test Equipment | |
| 5 | FCC Additional Requirements | |
| 5.1 | FCC Waiver DA 16-219 | 9 |
| 6 | Test Results | |
| 6.1 | \ '\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ | |
| 6.2 | , , , | |
| 6.3 | , , | |
| 6.4 | Emissions Limitations (spurious emissions) [FCC Part 80.211 (f), 2.1051, 2.1053] | 18 |
| 6.5 | Frequency Tolerance [FCC Part 80.205,2 1055] | 29 |
| 6.6 | Modulation Characteristics [FCC 2.1047] | 31 |
| | List of Tables | |
| | | |
| | e 1: Overview of M3P Buoy Head, Equipment Under Test | |
| | e 2: Equipment Configuration | |
| | e 3: Support Equipment | |
| | e 4: Interface Cables | |
| | e 5: Expanded Uncertainty List | |
| | e 6: Test Summary Table | |
| | e 7: Occupied Bandwidth results | |
| | e 8: RF Power Results | |
| | e 9: Unwanted Emissions, Radiated emissions, Unit Upright | |
| | e 10: Unwanted Emissions, Radiated emissions, Unit on side 1 | |
| | e 11: Unwanted Emissions, Radiated emissions, Unit Side 2 | |
| | e 12: Frequency Tolerance vs. Temperature | |
| Table | e 13: Frequency Tolerance vs. Battery Voltage | 30 |

List of Figures

| Figure 1: Low Channel Occupied Bandwidth | 11 |
|--|----|
| Figure 2: Center Channel Occupied Bandwidth | 12 |
| Figure 3: High Channel Occupied Bandwidth | 13 |
| Figure 4: RF Power, Low Channel | 15 |
| Figure 5: RF Power, Center Channel | |
| Figure 6: RF Power, High Channel | |
| Figure 7: Spurious Emissions, 9kHz -1MHz | |
| Figure 8: Spurious Emissions, 1-25MHz | 21 |
| Figure 9: Spurious Emissions, 25 – 26.15MHz | 22 |
| Figure 10: Spurious Emissions, 26.06 – 26.26MHz. | |
| Figure 11: Spurious Emissions, 26.17 - 28MHz | |
| Figure 12: Spurious Emissions, 28 – 1000MHz. | |

1 Introduction

1.1 Compliance Statement

The Marine Instruments, S.A. M3P Buoy Head complied with the requirements of Part 80 as modified by waiver DA 16-219 granting a waiver of section 80.373(c) to permit use of frequencies 26.145, 26.150, 26.155, 26.160, 26.165, 26.170, and 26.175 MHz to transmit position and related information pertaining to equipment used in fishing operations and FCC inquiry Tracking Number 847377

1.2 Test Scope Summary

The following tests were performed to show compliance with Part 80E of the FCC rules:

Total Power limited to 6W Per FCC waiver DA 16-219

Emission Bandwidth 80.205 (F1D, authorized Bandwidth 20kHz per FCC Inquiry

Tracking Number 847377)

Emission Limitations FCC Part 80.211 (f) Frequency Tolerance FCC Part 80.209

Modulation Characteristics FCC Part 80.213 (Duty cycle Limitations)

1.3 Contract Information

Customer: Marine Instruments, S.A.

Rúa dos Padróns No 4 (Vial 3); Parque Empresarial Porto do Molle Nigrán, Pontevedra 36350 Spain

Quotation Number: 68638B

1.4 Test Dates

Testing was performed on the following date(s): 8/29/2016 to 12/9/2016

1.5 Test and Support Personnel

Washington Laboratories, Ltd.

James Ritter

Client Representative Gregory Hammann

1.6 Abbreviations

| A | Ampere |
|---------------|--|
| ac | alternating current |
| AM | Amplitude Modulation |
| Amps | Amperes |
| b/s | bits per second |
| \mathbf{BW} | BandWidth |
| CE | Conducted Emission |
| cm | c enti m eter |
| CW | Continuous Wave |
| dB | d eci B el |
| dc | direct current |
| EMI | Electromagnetic Interference |
| EUT | Equipment Under Test |
| FM | Frequency Modulation |
| G | giga - prefix for 10 ⁹ multiplier |
| Hz | Hertz |
| IF | Intermediate Frequency |
| k | k ilo - prefix for 10 ³ multiplier |
| LISN | Line Impedance Stabilization Network |
| M | \mathbf{M} ega - prefix for 10^6 multiplier |
| m | m eter |
| μ | m icro - prefix for 10 ⁻⁶ multiplier |
| NB | N arrow b and |
| QP | Quasi-Peak |
| RE | Radiated Emissions |
| RF | Radio Frequency |
| rms | root-mean-square |
| SN | Serial Number |
| S/A | Spectrum Analyzer |
| V | Volt |

2 Equipment Under Test

2.1 EUT Identification

The results obtained relate only to the item(s) tested.

Table 1: Overview of M3P Buoy Head, Equipment Under Test

| ITEM | DESCRIPTION |
|-------------------------|---|
| Manufacturer: | Marine Instruments, S.A. |
| EUT Name | Recon Scout Operator Control Unit |
| FCC ID: | 2AEES-MPTR |
| Model: | M3P Buoy Head |
| Model covered: | M3P, M3P-T, M3P-R |
| FCC Rule Parts: | Part 80 |
| Frequency Range: | 26.145 - 26.175 MHz |
| Measured Output Power: | 28.5dBm (0.7W) conducted total power |
| Modulation: | FSK |
| Emission Bandwidth: | 526Hz |
| Keying: | Automatic |
| Type of Information: | Data |
| Number of Channels: | 7 channels available- units fixed at factory for single channel |
| Antenna Connector | N Type |
| Antenna Type | Omni Whip |
| Antenna Gain | 2dBi |
| Frequency Tolerance: | <10Hz |
| Emission Designator: | 526HF1D |
| Interface Cables: | None |
| Power Source & Voltage: | Rechargeable Battery, Ni-MH Batteries / 12 V |

2.2 EUT Description

HF Radio buoy for monitoring longline fishing gear or any other fishing gear or drifting assets. The buoy provides GPS position, battery level and optionally sea surface temperature. These buoys permit the vessel captain to monitor the gear's drift and current location using proprietary software specially designed for that purpose. The devices are pre-configured with the transmit frequency (not user changeable)

2.3 Test Configuration

The Marine Instruments, S.A. M3P Buoy Head, Equipment Under Test (EUT), was operated from a Lab power supply. The channels were preprogrammed and switchable via an external switch for lab testing. As the frequency range of programmable channels is less than 1 MHz only the center channel at 26.16MHz was tested. The unit was a stand-alone device.

2.4 Equipment Configuration

The EUT was comprised of the following equipment. (All Modules, PCBs, etc. listed were considered as part of the EUT, as tested.)

Table 2: Equipment Configuration

| Name / Description | Model Number | Part Number | Serial Number | Revision |
|--------------------|--------------|-------------|---------------|----------|
| РСВ МЗР | P-1912 | | | 03 |

2.5 Support Equipment

The following support equipment was used during testing:

Table 3: Support Equipment

| Item Model/Part Number | | Serial Number |
|------------------------|---|---------------|
| AC/DC Transformer | CPE45-120800/9 (with female DC jack adapter and VHR-2N) | |

2.6 Interface Cables

Table 4: Interface Cables

| Ref. ID | Port name on EUT | Cable Description or reason for no cable | Qty. | Length (m) | Shielded? | Termination Box ID & Port ID |
|------------|--|---|------|---------------|-----------|---------------------------------|
| 1 | DC IN (from Power Supply) Only for charging battery | Red/black cable with banana jacks on one end, various DC jacks on other | 1 | 1 | No | Port 1 |

2.7 EUT Modifications

None.

2.8 Test Location

All measurements herein were performed at Washington Laboratories, Ltd. test center in Gaithersburg, MD. Washington Laboratories, Ltd. has been accepted by the FCC and approved by ANAB under Certificate AT-1448 as an independent FCC test laboratory.

2.9 Measurement Uncertainty

All results reported herein relate only to the equipment tested. The basis for uncertainty calculation uses ANSI/NCSL Z540-2-1997 with a type B evaluation of the standard uncertainty. Elements contributing to the standard uncertainty are combined using the method described in Equation 1 to arrive at the total standard uncertainty. The standard uncertainty is multiplied by the coverage factor to determine the expanded uncertainty which is generally accepted for use in commercial, industrial, and regulatory applications and when health and safety are concerned (see Equation 2). A coverage factor was selected to yield a 95% confidence in the uncertainty estimation.

Equation 1: Standard Uncertainty

$$u_{c} = \pm \sqrt{\frac{a^{2}}{div_{a}^{2}} + \frac{b^{2}}{div_{b}^{2}} + \frac{c^{2}}{div_{c}^{2}} + \dots}$$

where u_c = standard uncertainty

a, b, $c_{,..}$ = individual uncertainty elements

div_a, _b, _c = the individual uncertainty element divisor based on the probability distribution

on the probability distribution

divisor = 1.732 for rectangular distribution

divisor = 2 for normal distribution

divisor = 1.414 for trapezoid distribution

Equation 2: Expanded Uncertainty

$$U = ku_c$$

where U = expanded uncertainty

k = coverage factor

 $k \le 2$ for 95% coverage (ANSI/NCSL Z540-2 Annex G)

u_c = standard uncertainty

The measurement uncertainty complies with the maximum allowed uncertainty from CISPR 16-4-2. Measurement uncertainty is <u>not</u> used to adjust the measurements to determine compliance.

The expanded uncertainty values for the various scopes in the WLL accreditation are provided in Table 5 below.

Table 5: Expanded Uncertainty List

| Scope | Standard(s) | Expanded Uncertainty |
|---------------------|-------------|-------------------------|
| Conducted Emissions | FCC Part 15 | 2.63 dB |
| Radiated Emissions | FCC Part 15 | 4.55 dB |

3 Test Summary

The Table Below shows the results of testing for compliance with a M3P Buoy transmitter.

Table 6: Test Summary Table

| FCC Rule Part | Description | Result |
|---------------------|--|----------------|
| 80.207, FCC Inquiry | Classes of Emission | Pass |
| 80.205, 2.1049 | Emission Bandwidth (Occupied Bandwidth) | Pass |
| 80.215, 2.1046 | Maximum Transmitter Power (RF Power) | Pass |
| 80.211(f), 2.1051 | Unwanted Radiation (at antenna terminal) | Pass |
| 80.211(f), 2.1053 | Unwanted Radiation (Radiated Emissions) | Pass |
| 95.637, 2.1047 | Modulation Standards (Duty Cycle) | Attested to by |
| | | Manufacturer |
| 80.205 2.1055 | Frequency Stability | Pass |

4 Test Equipment

| Test Name: | Temperature Stability | Test Date: | 12/9/2016 |
|------------|-----------------------|-------------------------------------|------------|
| Asset # | Manufacturer/Model | Description | Cal. Due |
| Rental | AGILENT -EXA N9010B | ANALYZER SPECTRUM Ser#MY55460673 | 10/17/2017 |
| 00776 | TENNY - TJR-A-WS4 | 1.22 CUFT | 05/22/2017 |
| 00641 | HQ power PS5005U | DC Power Supply | CNR |
| 685 | Fluke 115 | True RMS Voltmeter | 12/30/2016 |

| Test Name: | Radiated Emissions | Test Date: | 9/1/2016 |
|------------|--|--|------------|
| Asset # | Manufacturer/Model | Description | Cal. Due |
| 856 | EMCO - 6507 | ACTIVE LOOP 1KHZ - 30MHZ | 11/12/2017 |
| 644 | SUNOL SCIENCES CORPORATION - JB1 925-833-9936 | BICONALOG ANTENNA | 8/14/2017 |
| 559 | HP - 8447D | AMPLIFIER | 9/30/2016 |
| 823 | AGILENT - N9010A | EXA SPECTRUM ANALYZER | 9/30/2016 |
| 734 | HEWLET PACKARD - 8647A | SIGNAL GENERATOR - 250KHZ - 1GHZ OPT 1E5 -HIGH STABILITY TIMEBASE | 9/9/2016 |
| 428 | EMCO - 3109 | ANTENNA BICONICAL | 9/30/2016 |

| Test Name: Conducted Antenna PortEmissions | | Test Date: | 9/1/2016 | |
|--|--------------------|-----------------------|-----------|--|
| Asset # | Manufacturer/Model | Description | Cal. Due | |
| 823 | AGILENT - N9010A | EXA SPECTRUM ANALYZER | 9/30/2016 | |

5 FCC Additional Requirements

5.1 FCC Waiver DA 16-219

5.1.1 Waiver Specifications

- 1. Grant a waiver of section 80.373(c) to permit use of frequencies 26.145, 26.150, 26.155, 26.160, 26.165, 26.170, and 26.175 MHz to transmit position and related information pertaining to equipment used in fishing operations.
- 2. Output power is limited to 6 watts.
- 3. Duty cycle is limited to a 3.9-second transmission every 5 to 15 minutes.
- 4. The technical requirements in part 80 Subpart E General Technical Standards of the rules must be met.
- 5. Use is permitted only by fishing vessels with a ship station license issued under section 80.13(b) or 80.55 of the Commission's rules

5.1.2 FCC Inquiry Response

The FCC approved the following test methods per FCC inquiry Tracking Number 847377:

- 1. Authorized bandwidth (80.205) for the F1D transmission is authorized a 20kHz BW.
- 2. Then power is limited to 6 Watts peak conducted power.
- 3. The emission limit to be used is mask under section 802.11 (f).
- 4. The class of emission is radio determination.

6 Test Results

6.1 Classes of Emission (80.207, FCC Inquiry)

Pursuant to FCC waiver DA-16-219 and FCC inquiry Tracking Number 847377 the Class of emission shall be Radio Determination with a F1D designator and 20kHz authorized bandwidth. The frequency is waived. As the unit uses a FSK modulation with an occupied bandwidth of 526.1Hz these conditions are met.

Emission Bandwidth [FCC Part 80.205, 2.1049]

1.1.1 Test Method

The emission bandwidth test was performed as an occupied bandwidth measurement. The EUT antenna was disconnected from its antenna port and replaced with a calibrated cable connected to a spectrum analyzer through appropriate attenuators. A spectrum analyzer was tuned to the transmit frequency. The span of the analyzer was the reduced to approximately 2 to 3 times the span of the Tx signal. The resolution bandwidth of the device was lowered to approximately 1-5% of the estimated occupied bandwidth.. The span between points on each side of the Tx signal corresponding to 26dB below the peak were then recorded as the emission bandwidth.

1.1.2 Test Limit

FCC inquiry Tracking Number 847377 states that the authorized bandwidth is 20kHz.

1.1.3 Test Results

Figure 1 shows the plot of the occupied bandwidth. The recorded level is 526.1 Hz

1.1.4 Test Summary

The EUT complied with the requirements. Figure 1 through Figure 3 show the Occupied bandwidth Plots.

Table 7 provides a summary of the Occupied Bandwidth Results.

Table 7: Occupied Bandwidth results

| Frequency | Bandwidth | Limit | Pass/Fail |
|-----------|-----------|-------|-----------|
| 26.145MHz | 525Hz | 20kHz | Pass |
| 26.160MHz | 525Hz | 20kHz | Pass |
| 26.175MHz | 526Hz | 20kHz | Pass |




Figure 1: Low Channel Occupied Bandwidth




Figure 2: Center Channel Occupied Bandwidth



Figure 3: High Channel Occupied Bandwidth

6.3 RF Power [FCC Part 80.215, 2.1046]

6.3.1 Test Method

To measure the total power the EUT antenna was disconnected from its antenna port and replaced with a calibrated cable connected to a spectrum analyzer through appropriate attenuators. The EUT was the set to transmit with its modulation enabled. The resolution bandwidth was set larger than the occupied bandwidth with the video bandwidth set to greater than 3 times the RBW. A peak hold captured the highest peak power. This level was recorded for the conducted power.

6.3.2 Test Limit

Per FCC Waiver DA-16-219 the conducted power is limited to 6 Watts.

6.3.3 Test Results

Table 8 provides a summary of the RF Power Results.

Frequency Power Limit Pass/Fail 26.145MHz 28.0dBm 37.8dBm (6W) Pass 26.160MHz 27.9dBm 37.8dBm (6W) Pass 26.175MHz 28.5dBm 37.8dBm (6W) Pass

Table 8: RF Power Results

6.3.4 Test Summary

The RF Conducted power complies with the 6W limit.




Figure 4: RF Power, Low Channel




Figure 5: RF Power, Center Channel




Figure 6: RF Power, High Channel

6.4 Emissions Limitations (spurious emissions) [FCC Part 80.211 (f), 2.1051, 2.1053]

6.4.1 Test Method

The unwanted radiation tests were tested via 2 methods using the limits set for in FCC Part 80.211(f). The first method was a conducted method connecting the internal antenna connector to a spectrum analyzer. A resolution bandwidth of 30Hz was used inband. Larger resolution bandwidths were used out of band where possible to reduce the plots required to test the EUT (larger RBW's provide a worst case reading).

In addition the EUT was tested out of band (>250 % of authorized bandwidth) for radiated emissions on an open air test site (OATS) using the substitution method specified in TIA-603-D

A sample from the substitution tables is provided below to clarify them.

| Frequency (MHz) | Polarity | Azimuth | Ant. Height (m) | Spurious Level (dBuV) | Sub. Sig. Gen. Level (dBm) | Sub. Power Level (dBm) | Sub. Ant. Factor (dB) | Sub. Ant. Gain (dB) | EIRP Level (dBm) | Limit (dBm) | Margin (dB) |
|--------------------|----------|---------|-----------------------|-----------------------------|--|---------------------------------|--------------------------------|------------------------------|------------------------|----------------|----------------|
| 151.42(a) | V(b) | 0.0(b) | 1.5(b) | 25.69(c) | -54.2(d) | -58.0(e) | 8.8(f) | 5.0(g) | -52.9(h) | -26(j) | -27.1(k) |

Columns:

- a= Frequency of detected emission
- b=Position of EUT and height/polarization of receive antenna at maximum emission level
- c= maximum field strength level of EUT emission on receiver without any corrections
- d=Level of Signal Generator attached to a substitution antenna (replacing EUT) that produced a field strength identical to the EUT emission.
- e=Signal Generator level at Substitution antenna (d minus any cable/connector losses)
- f=Antenna Factor of substitution antenna used to get Antenna Gain
- g=Substitution Antenna Gain
- h=EIRP level of emission per TIA-603-D (column e plus column g) Note: numbers may have fractional differences j= EIRP limit as specified in FCC part 80
- k=Level of EUT EIRP (column i) compared to EIRP limit (Column j). Minus numbers indicate level below limit.

The EUT was placed on motorized turntable for radiated testing on a 3-meter open field test site. The emissions from the EUT were measured continuously at every azimuth by rotating the turntable. Receiving antennas were mounted on an antenna mast to determine the height of maximum emissions. The EUT was tested in 3 orthogonal positions for compliance. The EUT was then replaced with a substitution antenna of known gain and the levels of the initial emissions re-created with a signal generator feeding the substitution antenna. The signal generator reading was then converted to EIRP as shown in the above table explanation. A resolution bandwidth of 100kHz was used for radiated measurements. The EUT antenna was replaced by a dummy load for these readings.

Both tests were performed from 30MHz to the tenth harmonic of the fundamental frequency.

6.4.2 Test Limit

Per FCC Part 80.2119(f):

The attenuation from the mean peak power is as follows:

On any frequency removed from the assigned frequency by more than 50 percent up to and including 100 percent of the authorized bandwidth: At least 25 dB;

On any frequency removed from the assigned frequency by more than 100 percent up to and including 250 percent of the authorized bandwidth: At least 35 dB; and

On any frequency removed from the assigned frequency by more than 250 percent of the authorized bandwidth: At least 43 plus $10\log^{10}$ (mean power in watts) dB.

6.4.3 Test Results

The conducted tests are shown in Figure 7 to Figure 12. Radiated results are shown in Table 9 to Table 11.

6.4.4 Test Summary

The EUT complied with the requirements of FCC Part 80.211 mask f.




Figure 7: Spurious Emissions, 9kHz -1MHz




Figure 8: Spurious Emissions, 1-25MHz




Figure 9: Spurious Emissions, 25 – 26.15MHz




Figure 10: Spurious Emissions, 26.06 – 26.26MHz




Figure 11: Spurious Emissions, 26.17 - 28MHz




Figure 12: Spurious Emissions, 28 – 1000MHz

Table 9: Unwanted Emissions, Radiated emissions, Unit Upright

| Frequency (MHz) | Polarity | Azimuth | Ant. Height (m) | Spurious Level (dBuV) | Sub. Sig. Gen. Level (dBm) | Sub. Power Level (dBm) | Sub. Ant. Factor (dB) | Sub. Ant. Gain (dB) | EIRP Level (dBm) | Limit (dBm) | Margin (dB) |
|--------------------|----------|---------|-----------------------|-----------------------------|----------------------------|---------------------------------|--------------------------------|------------------------------|------------------------|----------------|----------------|
| 52.32 | V | 180.0 | 1.0 | 39.1 | -72.3 | -74.7 | 12.4 | -7.8 | -82.5 | -13 | -69.5 |
| 78.49 | V | 90.0 | 1.0 | 44.1 | -72.3 -56.9 | -59.7 | 8.6 | -0.4 | -60.2 | -13 | -09.3 -47.2 |
| 130.80 | V | 190.0 | 1.0 | 36.1 | -50.9 -67.4 | -71.1 | 12.8 | -0.4 | -71.3 | -13 | -47.2 -58.3 |
| 156.96 | v | 10.0 | 1.0 | 31.6 | -73.7 | -77.6 | 13.0 | 1.1 | -76.5 | -13 | -63.5 |
| 183.12 | v | 0.0 | 1.4 | 39.3 | -66.6 | -70.9 | 13.6 | 1.9 | -69.0 | -13 | -56.0 |
| 209.28 | v | 180.0 | 1.3 | 41.7 | -63.3 | -67.9 | 15.3 | 1.3 | -66.6 | -13 | -53.6 |
| 235.44 | v | 10.0 | 1.6 | 40.2 | -64.7 | -69.5 | 15.9 | 1.7 | -67.8 | -13 | -54.8 |
| 261.61 | v | 180.0 | 2.0 | 39.9 | -61.5 | -66.5 | 18.7 | -0.1 | -66.6 | -13 | -53.6 |
| 287.76 | V | 90.0 | 2.0 | 39.0 | -55.7 | -60.9 | 23.4 | -4.0 | -65.0 | -13 | -52.0 |
| | | | | | | | | | | | |
| 52.32 | Н | 180.0 | 3.4 | 33.4 | -69.3 | -71.7 | 12.4 | -7.8 | -79.5 | -13 | -66.5 |
| 78.48 | Н | 180.0 | 2.5 | 33.9 | -75.5 | -78.3 | 8.6 | -0.4 | -78.8 | -13 | -65.8 |
| 130.80 | Н | 180.0 | 2.5 | 30.3 | -75.1 | -78.8 | 12.8 | -0.2 | -79.0 | -13 | -66.0 |
| 156.96 | Н | 270.0 | 2.5 | 29.5 | -79.0 | -82.9 | 13.0 | 1.1 | -81.8 | -13 | -68.8 |
| 183.12 | Н | 90.0 | 3.0 | 40.4 | -71.1 | -75.4 | 13.6 | 1.9 | -73.5 | -13 | -60.5 |
| 209.28 | Н | 270.0 | 2.4 | 31.4 | -79.3 | -83.9 | 15.3 | 1.3 | -82.6 | -13 | -69.6 |
| 235.44 | Н | 0.0 | 1.7 | 44.3 | -64.1 | -68.9 | 15.9 | 1.7 | -67.2 | -13 | -54.2 |
| 261.60 | Н | 270.0 | 1.4 | 38.8 | -68.1 | -73.1 | 18.7 | -0.1 | -73.2 | -13 | -60.2 |
| 287.75 | Н | 10.0 | 1.0 | 41.0 | -63.4 | -68.6 | 23.4 | -4.0 | -72.7 | -13 | -59.7 |

Table 10: Unwanted Emissions, Radiated emissions, Unit on side 1

| Frequency (MHz) | Polarity | Azimuth | Ant. Height (m) | Spurious Level (dBuV) | Sub. Sig. Gen. Level (dBm) | Sub. Power Level (dBm) | Sub. Ant. Factor (dB) | Sub. Ant. Gain (dB) | EIRP Level (dBm) | Limit (dBm) | Margin (dB) |
|--------------------|----------|---------|-----------------------|-----------------------------|--|---------------------------------|--------------------------------|------------------------------|------------------------|----------------|----------------|
| 52.32 | V | 0.0 | 1.0 | 36.8 | -75.0 | -77.4 | 12.4 | -7.8 | -85.2 | -13 | -72.2 |
| 78.49 | V | 0.0 | 1.0 | 38.5 | -62.2 | -65.0 | 8.6 | -0.4 | -65.5 | -13 | -52.5 |
| 130.80 | V | 180.0 | 1.2 | 33.1 | -70.0 | -73.7 | 12.8 | -0.2 | -73.9 | -13 | -60.9 |
| 156.96 | V | 270.0 | 1.4 | 28.4 | -76.9 | -80.8 | 13.0 | 1.1 | -79.7 | -13 | -66.7 |
| 183.12 | V | 270.0 | 1.3 | 38.6 | -67.4 | -71.7 | 13.6 | 1.9 | -69.8 | -13 | -56.8 |
| 209.28 | V | 0.0 | 1.4 | 33.9 | -71.5 | -76.1 | 15.3 | 1.3 | -74.8 | -13 | -61.8 |
| 235.44 | V | 90.0 | 1.5 | 37.5 | -67.4 | -72.2 | 15.9 | 1.7 | -70.5 | -13 | -57.5 |
| 261.61 | V | 90.0 | 2.0 | 39.1 | -62.3 | -67.3 | 18.7 | -0.1 | -67.4 | -13 | -54.4 |
| 287.76 | V | 0.0 | 2.2 | 37.2 | -57.7 | -62.9 | 23.4 | -4.0 | -67.0 | -13 | -54.0 |
| 52.32 | Н | 10.0 | 3.2 | 33.8 | -68.9 | -71.3 | 12.4 | -7.8 | -79.1 | -13 | -66.1 |
| 78.48 | Н | 180.0 | 2.6 | 38.2 | -71.1 | -73.9 | 8.6 | -0.4 | -74.4 | -13 | -61.4 |
| 130.80 | Н | 10.0 | 2.5 | 30.1 | -75.3 | -79.0 | 12.8 | -0.2 | -79.2 | -13 | -66.2 |
| 156.96 | Н | 180.0 | 2.5 | 30.8 | -77.8 | -81.7 | 13.0 | 1.1 | -80.6 | -13 | -67.6 |
| 183.12 | Н | 270.0 | 2.5 | 39.2 | -72.3 | -76.6 | 13.6 | 1.9 | -74.7 | -13 | -61.7 |
| 209.28 | Н | 180.0 | 2.5 | 37.1 | -73.7 | -78.3 | 15.3 | 1.3 | -77.0 | -13 | -64.0 |
| 235.44 | Н | 180.0 | 1.5 | 41.1 | -67.2 | -72.0 | 15.9 | 1.7 | -70.3 | -13 | -57.3 |
| 261.60 | Н | 180.0 | 1.2 | 41.2 | -65.6 | -70.6 | 18.7 | -0.1 | -70.7 | -13 | -57.7 |
| 287.75 | Н | 190.0 | 1.2 | 41.6 | -62.8 | -68.0 | 23.4 | -4.0 | -72.1 | -13 | -59.1 |

Table 11: Unwanted Emissions, Radiated emissions, Unit Side 2

| Frequency (MHz) | Polarity | Azimuth | Ant. Height (m) | Spurious Level (dBuV) | Sub. Sig. Gen. Level (dBm) | Sub. Power Level (dBm) | Sub. Ant. Factor (dB) | Sub. Ant. Gain (dB) | EIRP Level (dBm) | Limit (dBm) | Margin (dB) |
|--------------------|----------|--------------|-----------------------|-----------------------------|--|---------------------------------|--------------------------------|------------------------------|------------------------|----------------|----------------|
| 52.32 | V | 180.0 | 1.0 | 37.7 | -74.4 | -76.8 | 12.4 | -7.8 | -84.6 | -13 | -71.6 |
| 78.49 | V | 10.0 | 1.0 | 37.8 | -63.2 | -66.0 | 8.6 | -0.4 | -66.5 | -13 | -53.5 |
| 130.80 | V | 10.0 | 1.0 | 32.2 | -71.4 | -75.1 | 12.8 | -0.2 | -75.3 | -13 | -62.3 |
| 156.96 | V | 90.0 | 1.3 | 29.7 | -75.4 | -79.3 | 13.0 | 1.1 | -78.2 | -13 | -65.2 |
| 183.12 | V | 90.0 | 1.3 | 39.5 | -66.7 | -71.0 | 13.6 | 1.9 | -69.1 | -13 | -56.1 |
| 209.28 | V | 45.0 | 1.5 | 35.6 | -69.3 | -73.9 | 15.3 | 1.3 | -72.6 | -13 | -59.6 |
| 235.44 | V | 90.0 | 1.6 | 37.5 | -67.3 | -72.1 | 15.9 | 1.7 | -70.4 | -13 | -57.4 |
| 261.61 | V | 90.0 | 2.5 | 38.6 | -62.8 | -67.8 | 18.7 | -0.1 | -67.9 | -13 | -54.9 |
| 287.76 | V | 10.0 | 2.5 | 36.3 | -58.5 | -63.7 | 23.4 | -4.0 | -67.8 | -13 | -54.8 |
| 52.32 78.48 | H H | 0.0 180.0 | 3.0 2.8 | 34.0 39.8 | -68.5 -69.5 | -70.9 -72.3 | 12.4 8.6 | -7.8 -0.4 | -78.7 -72.8 | -13 -13 | -65.7 -59.8 |
| 130.80 | Н | 0.0 | 2.5 | 29.4 | -76.2 | -79.9 | 12.8 | -0.2 | -80.1 | -13 | -67.1 |
| 156.96 | Н | 90.0 | 2.4 | 31.2 | -77.4 | -81.3 | 13.0 | 1.1 | -80.2 | -13 | -67.2 |
| 183.12 | Н | 90.0 | 2.5 | 42.0 | -69.5 | -73.8 | 13.6 | 1.9 | -71.9 | -13 | -58.9 |
| 209.28 | Н | 180.0 | 2.4 | 39.4 | -71.4 | -76.0 | 15.3 | 1.3 | -74.7 | -13 | -61.7 |
| 235.44 | Н | 180.0 | 1.6 | 45.0 | -63.8 | -68.6 | 15.9 | 1.7 | -66.9 | -13 | -53.9 |
| 261.60 | Н | 0.0 | 1.3 | 47.7 | -59.3 | -64.3 | 18.7 | -0.1 | -64.4 | -13 | -51.4 |
| 287.75 | Н | 190.0 | 1.3 | 40.1 | -64.2 | -69.4 | 23.4 | -4.0 | -73.5 | -13 | -60.5 |

6.5 Frequency Tolerance [FCC Part 80.209,2 1055]

6.5.1 Test Method

The EUT was placed in a calibrated temperature chamber. A receive antenna was placed in the temperature chamber with the device connected to a frequency counter outside the chamber. The EUT was set to transmit at 26.160MHz with an unmodulated carrier. A frequency reading was taken with the temperature at ambient (26C). The EUT was turned off and the temperature chamber set to -30 Celsius after 1 hour at this temperature the unit was turned on and a frequency reading was taken. The unit was turned back off and the temperature changed to -20 C. This process was repeated in 10 degree increments up to 50 Degrees Celsius allowing the unit to stabilize for 1 hour at each level before turning on the unit and recording the frequency. At each level the frequency recorded was compared to the ambient reading with the amount of deviation in Hz compared to the part 80 limit.

6.5.2 Test Limit

As the is no direct equivalent in the table in section 80.209 for Buoy devices the level of 10Hz maximum deviation from the table in FCC 80.209 used in the range of 4000-27500 kHz.

6.5.3 Test Results

The test results are show in Table 12 and Table 13.

6.5.4 Test Summary

The EUT complied with the requirements of Part 80 per the FCC.

Table 12: Frequency Tolerance vs. Temperature

Limit: 10Hz% Most stringent level for frequency range in FCC

80.209

Freq=26.160MHz **Temperature Variations**

| Temperature (Centigrade) | Frequency (MHz) | Deviation (Hz) | Limit (Hz) | Pass/Fail |
|-----------------------------|--------------------|-------------------|---------------|-----------|
| 23 (ambient) | 26.159990 | 0 | NA | NA |
| -30 | 26.159993 | 3 | 10 | Pass |
| -20 | 26.159995 | 5 | 10 | Pass |
| -10 | 26.159995 | 5 | 10 | Pass |
| 0 | 26.159995 | 5 | 10 | Pass |
| 10 | 26.159991 | 1 | 10 | Pass |
| 20 | 26.159990 | 0 | 10 | Pass |
| 30 | 26.159990 | 0 | 10 | Pass |
| 40 | 26.159991 | 1 | 10 | Pass |
| 50 | 26.159990 | 0 | 10 | Pass |

Table 13: Frequency Tolerance vs. Battery Voltage

Nominal voltage Level = 12VDC

Voltage Variations

| Voltage (Volts) | Frequency (MHz) | Deviation (Hz) | Limit (Hz) | Pass/Fail |
|---------------------------|--------------------|-------------------|---------------|-----------|
| Nominal Voltage 12VDC | 26.159990 | 0 | NA | Pass |
| Battery ENDPOINT (7.5vdc) | 26.159990 | 0 | 10 | Pass |

6.6 Modulation Characteristics [FCC 2.1047]

6.6.1 Test Method

Per waiver DA-16-219 the duty cycle requirements for a digital signal are modified as follows: 'Duty cycle is limited to a 3.9-second transmission every 5 to 15 minutes'

6.6.2 Transmission Attestation

Marine Instruments states that transmissions are 3.9 seconds in duration and occur every five, ten, or fifteen minutes, depending on how it is configured by the user.

WLL Report #14489-01 Rev 0