

FCC Radio Test Report

FCC ID: 2AEEX-GEMINI

This report concerns (check one): ⊠Original Grant □Class II Change

Project No. : 1504C059 Equipment : Smart Phone Model Name : Gemini Applicant : SACO LLC

Address : 2170 NW 87th Ave, Doral Florida, 33172, Doral,

Florida, United States 33172

Date of Receipt : Apr. 07, 2015

Date of Test : Apr. 07, 2015~ May 25, 2015
Issued Date : May 26, 2015
Tested by : BTL Inc.

Testing Engineer

Technical Manager

(Leo Hung)

Authorized Signatory

(Steven Lu)

BTL INC

No.3, Jinshagang 1st Road, Shixia, Dalang Town, Dongguan, Guangdong, China.

TEL: +86-769-8318-3000 FAX: +86-769-8319-6000

Report No.: BTL-FCCP-2-1504C059 Page 1 of 104



Declaration

BTL represents to the client that testing is done in accordance with standard procedures as applicable and that test instruments used has been calibrated with the standards traceable to National Measurement Laboratory (**NML**) of **R.O.C**, or National Institute of Standards and Technology (**NIST**) of **U.S.A.**

BTL's reports apply only to the specific samples tested under conditions. It is manufacture's responsibility to ensure that additional production units of this model are manufactured with the identical electrical and mechanical components. **BTL** shall have no liability for any declarations, inferences or generalizations drawn by the client or others from **BTL** issued reports.

BTL's report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.

This report is the confidential property of the client. As a mutual protection to the clients, the public and **BTL-self**, extracts from the test report shall not be reproduced except in full with **BTL**'s authorized written approval.

BTL's laboratory quality assurance procedures are in compliance with the **ISO Guide 17025** requirements, and accredited by the conformity assessment authorities listed in this test report.

Limitation

For the use of the authority's logo is limited unless the Test Standard(s)/Scope(s)/Item(s) mentioned in this test report is (are) included in the conformity assessment authorities acceptance respective.

Report No.: BTL-FCCP-2-1504C059 Page 2 of 104



Page 3 of 104

Table of Contents	Page
1. CERTIFICATION	6
2 . SUMMARY OF TEST RESULTS	7
2.1 TEST FACILITY	8
2.2 MEASUREMENT UNCERTAINTY	8
3 . GENERAL INFORMATION	9
3.1 GENERAL DESCRIPTION OF EUT	9
3.2 DESCRIPTION OF TEST MODES	11
3.3 TABLE OF PARAMETERS OF TEXT SOFTWARE SETTING	12
3.4 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TI	ESTED 13
3.5 DESCRIPTION OF SUPPORT UNITS	13
4 . EMC EMISSION TEST	14
4.1 CONDUCTED EMISSION MEASUREMENT	14
4.1.1 POWER LINE CONDUCTED EMISSION LIMITS	14
4.1.2 TEST PROCEDURE 4.1.3 DEVIATION FROM TEST STANDARD	14 14
4.1.4 TEST SETUP	15
4.1.5 EUT OPERATING CONDITIONS	15
4.1.6 EUT TEST CONDITIONS	15
4.1.7 TEST RESULTS	15
4.2 RADIATED EMISSION MEASUREMENT 4.2.1 RADIATED EMISSION LIMITS	16 16
4.2.1 RADIATED EMISSION LIMITS 4.2.2 TEST PROCEDURE	17
4.2.3 DEVIATION FROM TEST STANDARD	17
4.2.4 TEST SETUP	17
4.2.5 EUT OPERATING CONDITIONS 4.2.6 EUT TEST CONDITIONS	18
4.2.7 TEST RESULTS (9KHZ TO 30MHZ)	18 19
4.2.8 TEST RESULTS (30MHZ TO 1000 MHZ)	19
4.2.9 TEST RESULTS (ABOVE 1000 MHZ)	19
5 . BANDWIDTH TEST	20
5.1 APPLIED PROCEDURES	20
5.1.1 TEST PROCEDURE 5.1.2 DEVIATION FROM STANDARD	20 20
5.1.3 TEST SETUP	20 20
5.1.4 EUT OPERATION CONDITIONS	20
5.1.5 EUT TEST CONDITIONS	20
5.1.6 TEST RESULTS	20

Report No.: BTL-FCCP-2-1504C059



Table of Contents	Page
6 . MAXIMUM PEAK CONDUCTED OUTPUT POWER TEST	21
6.1 APPLIED PROCEDURES / LIMIT	21
6.1.1 TEST PROCEDURE	21
6.1.2 DEVIATION FROM STANDARD 6.1.3 TEST SETUP	21 21
6.1.4 EUT OPERATION CONDITIONS	21
6.1.5 EUT TEST CONDITIONS	21
6.1.6 TEST RESULTS	21
7 . ANTENNA CONDUCTED SPURIOUS EMISSION	22
7.1 APPLIED PROCEDURES / LIMIT	22
7.1.1 TEST PROCEDURE	22
7.1.2 DEVIATION FROM STANDARD 7.1.3 TEST SETUP	22 22
7.1.4 EUT OPERATION CONDITIONS	22
7.1.5 EUT TEST CONDITIONS	22
7.1.6 TEST RESULTS	22
8 . POWER SPECTRAL DENSITY TEST	23
8.1 APPLIED PROCEDURES / LIMIT	23
8.1.1 TEST PROCEDURE 8.1.2 DEVIATION FROM STANDARD	23
8.1.2 DEVIATION FROM STANDARD 8.1.3 TEST SETUP	23 23
8.1.4 EUT OPERATION CONDITIONS	23
8.1.5 EUT TEST CONDITIONS	23
8.1.6 TEST RESULTS	23
9 . MEASUREMENT INSTRUMENTS LIST	24
10 . EUT TEST PHOTO	26
ATTACHMENT A - CONDUCTED EMISSION	30
ATTACHMENT B - RADIATED EMISSION (9KHZ TO 30MHZ)	33
ATTACHMENT C - RADIATED EMISSION (30MHZ TO 1000MHZ)	35
ATTACHMENT D - RADIATED EMISSION (ABOVE 1000MHZ)	42
ATTACHMENT E - BANDWIDTH	79
ATTACHMENT F – MAXIMUM PEAK CONDUCTED OUTPUT POWER	86
ATTACHMENT G - ANTENNA CONDUCTED SPURIOUS EMISSION	88
ATTACHMENT H - POWER SPECTRAL DENSITY	98

Report No.: BTL-FCCP-2-1504C059 Page 4 of 104



REPORT ISSUED HISTORY

Issued No.	Description	Issued Date
BTL-FCCP-2-1504C059	Original Issue.	May 26, 2015

Report No.: BTL-FCCP-2-1504C059 Page 5 of 104



1. CERTIFICATION

Equipment : Smart Phone

Brand Name: AFFIX
Model Name: Gemini
Applicant: SACO LLC

Manufacturer: shanghai YIXI technology co., LTD

Address : 8F modernmodern logistics plaza 102 rd ginjiang,caohejing,hi-tech park shang

city 200233pr china

Factory : Skycom Telecommunications Co., Limited

Address : 4 Floor, Building A, Zhi Yang Technology Park. No. 014 Tang Qian Zhang Qi

Road, Zhang Ge Community, Guan Lan Street, Long Hua New Dictrict, Shen

Zhen.

Date of Test : Apr. 07, 2015~ May 25, 2015 Test Sample : ENGINEERING SAMPLE

Standard(s) : FCC Part15, Subpart C: 2014 (15.247) / ANSI C63.4-2009

The above equipment has been tested and found compliance with the requirement of the relative standards by BTL Inc.

The test data, data evaluation, and equipment configuration contained in our test report (Ref No. BTL-FCCP-2-1504C059) were obtained utilizing the test procedures, test instruments, test sites that has been accredited by the Authority of TAF according to the ISO-17025 quality assessment standard and technical standard(s).

Report No.: BTL-FCCP-2-1504C059 Page 6 of 104



2. SUMMARY OF TEST RESULTS

Test procedures according to the technical standard(s):

Applied Standard(s): FCC Part15 (15.247), Subpart C: 2014					
Standard(s) Section FCC	Test Item	Judgment	Remark		
15.207	Conducted Emission	PASS			
15.247(d)	Antenna conducted Spurious Emission	PASS			
15.247(a)(2)	6dB Bandwidth	PASS			
15.247(b)(3)	Peak Output Power	PASS			
15.247(e)	Power Spectral Density	PASS			
15.203	Antenna Requirement	PASS			
15.209/15.205	Transmitter Radiated Emissions	PASS			

NOTE:

- (1)" N/A" denotes test is not applicable in this test report.
- (2) The test follows FCC KDB Publication No. 558074 D01 DTS Meas Guidance v03r02 (Measurement Guidelines of DTS)

Report No.: BTL-FCCP-2-1504C059 Page 7 of 104



2.1 TEST FACILITY

The test facilities used to collect the test data in this report is at the location of No.3, Jinshagang 1st Road, Shixia, Dalang Town, Dongguan, Guangdong, China.

BTL's test firm number for FCC: 319330

2.2 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2. The BTL measurement uncertainty is less than the CISPR 16-4-2 U_{cispr} requirement.

The reported uncertainty of measurement y \pm U, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of k=2, providing a level of confidence of approximately 95 % $^{\circ}$

A. Conducted Measurement:

Test Site	Method	Measurement Frequency Range	U, (dB)	Note
DG-C02	CISPR	150 KHz ~ 30MHz	1.94	

B. Radiated Measurement:

Test Site	Method	Measurement Frequency Range	Ant. H / V	U, (dB)	Note
		9KHz~30MHz	V	3.79	
		9KHz~30MHz	Н	3.57	
		30MHz ~ 200MHz	V	3.82	
	CISPR	30MHz ~ 200MHz	Η	3.60	
DG-CB 3		200MHz ~ 1,000MHz	V	3.86	
DG-CB 3	CISER	200MHz ~ 1,000MHz	Η	3.94	
		1GHz~18GHz	V	3.12	
	1GHz~18GHz	Η	3.68		
		18GHz~40GHz	V	4.15	
		18GHz~40GHz	Н	4.14	

Note: Unless specifically mentioned, the uncertainty of measurement has not been taken into account to declare the compliance or non-compliance to the specification.

Report No.: BTL-FCCP-2-1504C059 Page 8 of 104



3. GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

Equipment	Smart Phone		
Brand Name	AFFIX		
Model Name	Gemini		
Model Difference	N/A		
	Operation Frequency	2412~2462 MHz	
	Modulation Technology	802.11b:DSSS 802.11g:OFDM 802.11n:OFDM	
Product Description	Bit Rate of Transmitter	802.11b: 11/5.5/2/1 Mbps 802.11g: 54/48/36/24/18/12/9/6 Mbps 802.11n up to150 Mbps	
	Output Power (Max.)	802.11b: 14.89dBm 802.11g: 11.56dBm 802.11n(20MHz):8.72dBm	
Power Source	#1 DC voltage supplied from AC/DC adapter. Brand/Model: Avvio/A31-501000 #2 Battery supplied. Brand/Model: AFFIX/ROCKET #3 Supplied from USB port.		
Power Rating	#1 I/P:100-240V~50/60Hz 0.5A MAX O/P: DC 5V/2A #2 DC 3.8V 3000mAh #3 DC 5V		

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.

Report No.: BTL-FCCP-2-1504C059 Page 9 of 104



2. Channel List:

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
01	2412	04	2427	07	2442	10	2457
02	2417	05	2432	08	2447	11	2462
03	2422	06	2437	09	2452		

3. Table for Filed Antenna:

Ant.	Brand	Model Name	Antenna Type	Connector	(dDi)	Note
1	N/A	N/A	Internal	N/A	-3.00	TX/RX

Report No.: BTL-FCCP-2-1504C059 Page 10 of 104



3.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Mode	Description
Mode 1	TX B MODE CHANNEL 01/06/11
Mode 2	TX G MODE CHANNEL 01/06/11
Mode 3	TX N-20MHZ MODE CHANNEL 01/06/11
Mode 4	TX MODE

The EUT system operated these modes were found to be the worst case during the pre-scanning test as following:

<u> </u>	For Conducted Test
Final Test Mode	Description
Mode 4	TX MODE

For Radiated Test				
Final Test Mode	Description			
Mode 1	TX B MODE CHANNEL 01/06/11			
Mode 2	TX G MODE CHANNEL 01/06/11			
Mode 3	TX N-20MHZ MODE CHANNEL 01/06/11			

Note:

- (1) The measurements are performed at the high, middle, low available channels.
- (2) 802.11b mode: DBPSK (1Mbps)

802.11g mode: OFDM (6Mbps)

802.11n HT20 mode: BPSK (6.5Mbps)

For radiated emission tests, the highest output powers were set for final test.

- (3) For radiated below 1G test, the 802.11b is found to be the worst case and recorded.
- (4) The EUT was programmed to be in continuously transmitting mode and the transmit duty cycle is not less than 98%.
- (5) Both adapter and battery are evaluated, operated the battery is the worst and recorded as below test data
- (6) The EUT is considered a portable unit, it was pre-tested on the positioned of each 3 axis. The worst case was found positioned on X-plane. Therefore only the test data of this X-plane was used for radiated emission measurement test

Report No.: BTL-FCCP-2-1504C059 Page 11 of 104



3.3 TABLE OF PARAMETERS OF TEXT SOFTWARE SETTING

During testing, channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product power parameters of WLAN

Test software version	QRCT		
Frequency (MHz)	2412	2437	2462
802.11b	16	15	14
802.11g	14	14	13
802.11n (20MHz)	11	11	10

Report No.: BTL-FCCP-2-1504C059 Page 12 of 104



3.4 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED EUT Control Room

3.5 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	FCC ID	Series No.	Note
-	-	-	1	1	1	

Iter	Shielded Type	Ferrite Core	Length	Note
-	-	-	-	

Report No.: BTL-FCCP-2-1504C059 Page 13 of 104



4. EMC EMISSION TEST

4.1 CONDUCTED EMISSION MEASUREMENT

4.1.1 POWER LINE CONDUCTED EMISSION Limits (Frequency Range 150KHz-30MHz)

Fraguency of Emission (MHz)	Conducted Limit (dBμV)		
Frequency of Emission (MHz)	Quasi-peak	Average	
0.15 -0.	66 to 56*	56 to 46*	
0.50 -5.0	56	46	
5.0 -30.0	60	50	

Note

- (1) The limit of " * " decreases with the logarithm of the frequency
- (2) The test result calculated as following: Measurement Value = Reading Level + Correct Factor Correct Factor = Insertion Loss + Cable Loss + Attenuator Factor(if use) Margin Level = Measurement Value - Limit Value

The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 KHz

4.1.2 TEST PROCEDURE

- a. The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- d. LISN at least 80 cm from nearest part of EUT chassis.
- e For the actual test configuration, please refer to the related Item –EUT Test Photos.


4.1.3 DEVIATION FROM TEST STANDARD

No deviation

Report No.: BTL-FCCP-2-1504C059 Page 14 of 104



4.1.4 TEST SETUP



Note: 1.Support units were connected to second LISN.

2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

4.1.5 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

4.1.6 EUT TEST CONDITIONS

Temperature: 25°C Relative Humidity: 55% Test Voltage: AC 120V/60Hz

4.1.7 TEST RESULTS

Please refer to the Attachment A.

Report No.: BTL-FCCP-2-1504C059 Page 15 of 104



4.2 RADIATED EMISSION MEASUREMENT

4.2.1 RADIATED EMISSION LIMITS

20dB in any 100 KHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

LIMITS OF RADIATED EMISSION MEASUREMENT (9KHz-1000MHz)

Frequency	Field Strength	Measurement Distance
(MHz)	(microvolts/meter)	(meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
960~1000	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

Frequency (MHz)	(dBuV/m) (at 3 meters)		
	PEAK	AVERAGE	
Above 1000	74	54	

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).
- (4) The test result calculated as following: Measurement Value = Reading Level + Correct Factor Correct Factor = Antenna Factor + Cable Loss - Amplifier Gain(if use) Margin Level = Measurement Value - Limit Value

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RBW / VBW	RBW 1MHz VBW 3MHz peak detector for Pk value
(Emission in restricted band)	RMS detector for AV value

Report No.: BTL-FCCP-2-1504C059 Page 16 of 104



Receiver Parameter Setting	
Attenuation	Auto
Start ~ Stop Frequency	9KHz~90KHz for PK/AVG detector
Start ~ Stop Frequency	90KHz~110KHz for QP detector
Start ~ Stop Frequency	110KHz~490KHz for PK/AVG detector
Start ~ Stop Frequency	490KHz~30MHz for QP detector
Start ~ Stop Frequency	30MHz~1000MHz for QP detector

4.2.2 TEST PROCEDURE


- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.(below 1GHz)
- b. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.(above 1GHz)
- c. The height of the equipment or of the substitution antenna shall be 0.8 m; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- e. If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- f. For the actual test configuration, please refer to the related Item –EUT Test Photos.

4.2.3 DEVIATION FROM TEST STANDARD

No deviation

4.2.4 TEST SETUP


(A) Radiated Emission Test Set-Up Frequency Below 1 GHz




Report No.: BTL-FCCP-2-1504C059 Page 17 of 104



(B) Radiated Emission Test Set-Up Frequency Above 1 GHz



(C) For radiated emissions below 30MHz



4.2.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of **4.1.5** Unless otherwise a special operating condition is specified in the follows during the testing.

4.2.6 EUT TEST CONDITIONS

Temperature: 25°C Relative Humidity: 55% Test Voltage: DC 3.8V

Report No.: BTL-FCCP-2-1504C059 Page 18 of 104



4.2.7 TEST RESULTS (9KHZ TO 30MHZ)

Please refer to the Attachment B

Remark:

- (1) The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.
- (2) Distance extrapolation factor = 40 log (specific distance / test distance) (dB).
- (3) Limit line = specific limits (dBuV) + distance extrapolation factor.

4.2.8 TEST RESULTS (30MHZ TO 1000 MHZ)

Please refer to the Attachment C.

4.2.9 TEST RESULTS (ABOVE 1000 MHZ)

Please refer to the Attachment D.

Remark:

(1) No limit: This is fundamental signal, the judgment is not applicable. For fundamental signal judgment was referred to Peak output test.

Report No.: BTL-FCCP-2-1504C059 Page 19 of 104



5. BANDWIDTH TEST

5.1 APPLIED PROCEDURES

FCC Part15 (15.247) , Subpart C				
Section Test Item Frequency Range (MHz) Res				
15.247(a)(2) Bandwidth 2400-2483.5 F				

5.1.1 TEST PROCEDURE

- a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- b Spectrum Setting: RBW= 100KHz, VBW=300KHz, Sweep time = 2.5 ms.

5.1.2 DEVIATION FROM STANDARD

No deviation.

5.1.3 TEST SETUP

EUT	SPECTRUM
	ANALYZER

5.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 4.1.5 Unless otherwise a special operating condition is specified in the follows during the testing.

5.1.5 EUT TEST CONDITIONS

Temperature: 25°C Relative Humidity: 55% Test Voltage: DC 3.8V

5.1.6 TEST RESULTS

Please refer to the Attachment E.

Report No.: BTL-FCCP-2-1504C059 Page 20 of 104



6. MAXIMUM PEAK CONDUCTED OUTPUT POWER TEST

6.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C					
Section	Test Item	Limit	Frequency Range (MHz)	Result	
15.247(b)(3)	Maximum Output Power	1 Watt or 30dBm	2400-2483.5	PASS	

6.1.1 TEST PROCEDURE

- a. The EUT was directly connected to the power meter and antenna output port as show in the block diagram below,
- b. The maximum peak conducted output power was performed in accordance with method 9.1.2 of FCC KDB 558074 D01 DTS Meas Guidance v03r02.

6.1.2 DEVIATION FROM STANDARD

No deviation.

6.1.3 TEST SETUP

EUT	Power Meter
	1 Circi meter

6.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 4.1.5 Unless otherwise a special operating condition is specified in the follows during the testing.

Transmit output power was measured while the host equipment supply voltage was varied from 85 % to 115 % of the nominal rated supply voltage. No change in transmit output power was observed.

6.1.5 EUT TEST CONDITIONS

Temperature: 25°C Relative Humidity: 55% Test Voltage: DC 3.8V

6.1.6 TEST RESULTS

Please refer to the Attachment F.

Report No.: BTL-FCCP-2-1504C059 Page 21 of 104



7. ANTENNA CONDUCTED SPURIOUS EMISSION

7.1 APPLIED PROCEDURES / LIMIT

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.

7.1.1 TEST PROCEDURE

- a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- b Spectrum Setting: RBW= 100KHz, VBW=300KHz, Sweep time = Auto.

7.1.2 DEVIATION FROM STANDARD

No deviation.

7.1.3 TEST SETUP



7.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 4.1.5 Unless otherwise a special operating condition is specified in the follows during the testing.

7.1.5 EUT TEST CONDITIONS

Temperature: 25°C Relative Humidity: 55% Test Voltage: DC 3.8V

7.1.6 TEST RESULTS

Please refer to the Attachment G.

Report No.: BTL-FCCP-2-1504C059 Page 22 of 104



8. POWER SPECTRAL DENSITY TEST

8.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C								
Section	Test Item	Limit	Frequency Range (MHz)	Result				
15.247(e)	Power Spectral Density	8 dBm (in any 3KHz)	2400-2483.5	PASS				

8.1.1 TEST PROCEDURE

- a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- b. Spectrum Setting: RBW=3KHz, VBW=10KHz, Sweep time = Auto.

8.1.2 DEVIATION FROM STANDARD

No deviation.

8.1.3 TEST SETUP

EUT	SPECTRUM
	ANALYZER

8.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 4.1.5 Unless otherwise a special operating condition is specified in the follows during the testing.

8.1.5 EUT TEST CONDITIONS

Temperature: 25°C Relative Humidity: 55% Test Voltage: DC 3.8V

8.1.6 TEST RESULTS

Please refer to the Attachment H.

Report No.: BTL-FCCP-2-1504C059 Page 23 of 104



9. MEASUREMENT INSTRUMENTS LIST

	Conducted Emission Measurement									
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until					
1	LISN	EMCO	3816/2	00052765	Mar. 28, 2016					
2	LISN	R&S	ENV216	101447	Mar. 28, 2016					
3	Test Cable	N/A	C_17	N/A	Mar.13, 2016					
4	EMI TEST RECEIVER	R&S	ESCS30	833364/017	Mar. 28, 2016					
5	50Ω Terminator	SHX	TF2-3G-A	08122902	Mar. 28, 2016					
6	Measurement Software	Farad	EZ-EMC Ver.NB-03A1-0 1	N/A	N/A					

	Radiated Emission Measurement									
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until					
1	Antenna	Schwarbeck	VULB9160	9160-3232	Mar. 28, 2016					
2	Amplifier	HP	8447D	2944A09673	Nov. 17, 2015					
3	Receiver	AGILENT	N9038A	MY52130039	Sep. 30, 2015					
4	Test Cable	N/A	C-01_CB03	N/A	Jul. 01, 2015					
5	Controller	СТ	SC100	N/A	N/A					
6	Measurement Software	Farad	EZ-EMC Ver.NB-03A1-0 N/A 1		N/A					
7	Antenna	ETS	3115	00075789	Mar. 28, 2016					
8	Amplifier	Agilent	8449B	3008A02274	Nov. 02, 2015					
9	Broad-Band Horn Antenna	Schwarzbeck	BBHA 9170	9170319	Mar. 28, 2016					
10	Microwave Preamplifier With Adaptor	EMC INSTRUMENT	EMC2654045	980039 & HA01	Mar. 28, 2016					
11	Active Loop Antenna	R&S	HFH2-Z2	830749/020	Aug. 16, 2015					

Report No.: BTL-FCCP-2-1504C059 Page 24 of 104



	6dB Bandwidth Measurement							
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until			
1	Spectrum Analyzer	R&S	FSP 40	100185	Nov. 02, 2015			

	Peak Output Power Measurement								
Item	m Kind of Equipment Manufacturer Type No. Serial No. Calibrated								
1	P-series Power meter	Agilent	N1911A	MY45100473	Mar. 28, 2016				
2	Wireband Power sensor	Agilent	N1921A	MY51100041	Mar. 28, 2016				

	Antenna Conducted Spurious Emission Measurement								
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until				
1	Spectrum Analyzer R&S		FSP 40	100185	Nov. 02, 2015				

	Power Spectral Density Measurement							
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until			
1	Spectrum Analyzer	R&S	FSP 40	100185	Nov. 02, 2015			


Remark: "N/A" denotes no model name, serial no. or calibration specified.

All calibration period of equipment list is one year.

Report No.: BTL-FCCP-2-1504C059 Page 25 of 104



10. EUT TEST PHOTO







Report No.: BTL-FCCP-2-1504C059 Page 26 of 104



Radiated Measurement Photos

9KHz to 30MHz





Report No.: BTL-FCCP-2-1504C059 Page 27 of 104



Radiated Measurement Photos

30MHz to 1000MHz





Report No.: BTL-FCCP-2-1504C059 Page 28 of 104



Radiated Measurement Photos

Above 1000MHz





Report No.: BTL-FCCP-2-1504C059 Page 29 of 104




ATTACHMENT A - CONDUCTED EMISSION

Report No.: BTL-FCCP-2-1504C059 Page 30 of 104








No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Margin		
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector	Comment
1		0.1578	38.68	9.55	48.23	65.58	-17.35	peak	
2		0.1930	36.25	9.57	45.82	63.91	-18.09	peak	
3	*	0.5172	38.42	9.69	48.11	56.00	-7.89	peak	
4		0.5172	18.70	9.69	28.39	46.00	-17.61	AVG	
5		0.8492	36.31	9.76	46.07	56.00	-9.93	peak	
6		0.8492	17.30	9.76	27.06	46.00	-18.94	AVG	
7		1.6852	34.50	9.87	44.37	56.00	-11.63	peak	
8		1.6852	13.10	9.87	22.97	46.00	-23.03	AVG	
9		2.3413	31.98	9.97	41.95	56.00	-14.05	peak	

Report No.: BTL-FCCP-2-1504C059 Page 31 of 104








No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Margin		
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector	Comment
1		0.4313	33.30	9.54	42.84	57.23	-14.39	peak	
2	*	0.5054	37.26	9.56	46.82	56.00	-9.18	peak	
3		0.5054	19.80	9.56	29.36	46.00	-16.64	AVG	
4		0.6110	36.31	9.56	45.87	56.00	-10.13	peak	
5		0.6110	18.80	9.56	28.36	46.00	-17.64	AVG	
6		0.7360	36.77	9.54	46.31	56.00	-9.69	peak	
7		0.7360	20.10	9.54	29.64	46.00	-16.36	AVG	
8		0.8062	35.47	9.56	45.03	56.00	-10.97	peak	
9		0.8062	18.80	9.56	28.36	46.00	-17.64	AVG	
10		1.4977	34.08	9.66	43.74	56.00	-12.26	peak	

Report No.: BTL-FCCP-2-1504C059 Page 32 of 104





Report No.: BTL-FCCP-2-1504C059 Page 33 of 104



Test Mode: TX Mode

Frequency (MHz)	Ant 0°/90°	Read level dBuV/m	Factor (dB)	Measured(FS) (dBuV/m)	Limit(QP) (dBuV/m)	Margin (dB)	Note
0.0168	0°	13.64	24.50	38.14	123.10	-84.96	AVG
0.0168	0°	14.53	24.50	39.03	143.10	-104.07	PEAK
0.0359	0°	6.91	23.29	30.20	116.50	-86.30	AVG
0.0359	0°	7.54	23.29	30.83	136.50	-105.67	PEAK
0.0386	0°	3.77	23.12	26.89	115.87	-88.98	AVG
0.0386	0°	5.46	23.12	28.58	135.87	-107.29	PEAK
0.0467	0°	0.92	22.61	23.53	114.22	-90.69	AVG
0.0467	0°	3.05	22.61	25.66	134.22	-108.56	PEAK
2.0652	0°	30.54	19.46	50.00	69.54	-19.54	QP
3.3676	0°	21.69	18.94	40.63	69.54	-28.91	QP

Frequency (MHz)	Ant 0°/90°	Read level dBuV/m	Factor (dB)	Measured(FS) (dBuV/m)	Limit(QP) (dBuV/m)	Margin (dB)	Note
0.0154	90°	13.58	24.30	37.88	123.85	-85.97	AVG
0.0154	90°	14.51	24.30	38.81	143.85	-105.04	PEAK
0.0355	90°	6.36	23.32	29.68	116.60	-86.92	AVG
0.0355	90°	8.75	23.32	32.07	136.60	-104.53	PEAK
0.0374	90°	3.63	23.20	26.83	116.15	-89.32	AVG
0.0374	90°	5.42	23.20	28.62	136.15	-107.53	PEAK
0.0692	90°	0.63	22.02	22.65	110.80	-88.16	AVG
0.0692	90°	2.95	22.02	24.97	130.80	-105.84	PEAK
2.0563	90°	30.66	19.47	50.13	69.54	-19.41	QP
3.2476	90°	21.47	18.92	40.39	69.54	-29.15	QP


Report No.: BTL-FCCP-2-1504C059 Page 34 of 104



ATTACHMENT C - RADIATED EMISSION (30MHZ TO 1000MHZ

Report No.: BTL-FCCP-2-1504C059 Page 35 of 104





Report No.: BTL-FCCP-2-1504C059 Page 36 of 104





Horizontal



No.	Mk.	. Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Margin		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		69.7700	36.12	-16.22	19.90	40.00	-20.10	peak	
2		173.5600	30.81	-12.84	17.97	43.50	-25.53	peak	
3		469.4100	29.85	-9.36	20.49	46.00	-25.51	peak	
4		678.9300	30.32	-5.02	25.30	46.00	-20.70	peak	
5		769.1400	34.50	-3.96	30.54	46.00	-15.46	peak	
6	*	831.2200	36.76	-3.05	33.71	46.00	-12.29	peak	


Report No.: BTL-FCCP-2-1504C059 Page 37 of 104





Report No.: BTL-FCCP-2-1504C059 Page 38 of 104






	No.	Mk	. Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Margin		
-			MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
	1		69.7700	36.51	-16.22	20.29	40.00	-19.71	peak	
	2	*	220.1200	43.33	-14.87	28.46	46.00	-17.54	peak	
	3		448.0700	29.38	-8.66	20.72	46.00	-25.28	peak	
	4		656.6200	30.80	-5.12	25.68	46.00	-20.32	peak	
	5		787.5700	31.09	-3.32	27.77	46.00	-18.23	peak	
	6		831.2200	31.36	-3.05	28.31	46.00	-17.69	peak	


Report No.: BTL-FCCP-2-1504C059 Page 39 of 104





Report No.: BTL-FCCP-2-1504C059 Page 40 of 104






	No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Margin		
			MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
	1		69.7700	36.19	-16.22	19.97	40.00	-20.03	peak	
	2	;	391.8100	29.74	-9.89	19.85	46.00	-26.15	peak	
Ī	3	4	153.8900	28.93	-8.76	20.17	46.00	-25.83	peak	
Ī	4	(556.6200	30.14	-5.12	25.02	46.00	-20.98	peak	
Ī	5		787.5700	32.46	-3.32	29.14	46.00	-16.86	peak	
_	6	* (331.2200	36.32	-3.05	33.27	46.00	-12.73	peak	

Report No.: BTL-FCCP-2-1504C059 Page 41 of 104






Report No.: BTL-FCCP-2-1504C059 Page 42 of 104



Orthogonal Axis: X
Test Mode: TX B MODE 2412MHz

Vertical




No.	Mk	. Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Margin		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		2390.000	23.41	34.17	57.58	74.00	-16.42	peak	
2		2390.000	13.95	34.17	48.12	54.00	-5.88	AVG	
3	Х	2411.100	58.76	34.23	92.99	74.00	18.99	peak	No Limit
4	*	2411.200	56.59	34.23	90.82	54.00	36.82	AVG	No Limit

Report No.: BTL-FCCP-2-1504C059 Page 43 of 104



Orthogonal Axis: X
Test Mode: TX B MODE 2412MHz

Vertical




No.	Mk	. F	req.		Correct Factor	Measure- ment	Limit	Margin		
		ı	MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		4823	.960	41.55	6.81	48.36	74.00	-25.64	peak	
2	*	4824	.010	39.27	6.81	46.08	54.00	-7.92	AVG	

Report No.: BTL-FCCP-2-1504C059 Page 44 of 104



Test Mode: TX B MODE 2412MHz

Horizontal




	No.	M	c. Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Margin			
			MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment	
	1		2390.000	23.60	34.17	57.77	74.00	-16.23	peak		
-	2		2390.000	13.99	34.17	48.16	54.00	-5.84	AVG		
	3	*	2412.800	67.18	34.23	101.41	54.00	47.41	AVG	No Limit	
	4	Х	2412.900	69.32	34.23	103.55	74.00	29.55	peak	No Limit	

Report No.: BTL-FCCP-2-1504C059 Page 45 of 104



Test Mode: TX B MODE 2412MHz

Horizontal




No.	M	. Freq.		Correct Factor	Measure- ment		Margin		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		4823.830	40.37	6.81	47.18	74.00	-26.82	peak	
2	*	4824.000	36.50	6.81	43.31	54.00	-10.69	AVG	

Report No.: BTL-FCCP-2-1504C059 Page 46 of 104



Orthogonal Axis: X
Test Mode: TX B MODE 2437MHz

Vertical



_	No.	Mk	. Freq.		Correct Factor	Measure- ment		Margin		
			MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
	1	X	2436.200	59.59	34.30	93.89	74.00	19.89	peak	No Limit
	2	*	2436.200	57.44	34.30	91.74	54.00	37.74	AVG	No Limit

Report No.: BTL-FCCP-2-1504C059 Page 47 of 104



Orthogonal Axis: X
Test Mode: TX B MODE 2437MHz

Vertical




No.	Mk	c. Freq.		Correct Factor	Measure- ment	Limit	Margin		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		4873.920	42.07	6.96	49.03	74.00	-24.97	peak	
2	*	4873.960	38.88	6.96	45.84	54.00	-8.16	AVG	

Report No.: BTL-FCCP-2-1504C059 Page 48 of 104



Test Mode: TX B MODE 2437MHz

Horizontal



No.	Mk	ζ.	Freq.		Correct Factor	Measure- ment		Margin		
			MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	X	243	6.200	68.37	34.30	102.67	74.00	28.67	peak	No Limit
2	*	243	6.200	66.29	34.30	100.59	54.00	46.59	AVG	No Limit

Report No.: BTL-FCCP-2-1504C059 Page 49 of 104



Orthogonal Axis: X
Test Mode: TX B MODE 2437MHz

Horizontal




No.	М	k.	Freq.		Correct Factor	Measure- ment	Limit	Margin		
			MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	*	48	73.980	36.29	6.96	43.25	54.00	-10.75	AVG	
2		48	74.040	40.30	6.96	47.26	74.00	-26.74	peak	

Report No.: BTL-FCCP-2-1504C059 Page 50 of 104



Orthogonal Axis: X
Test Mode: TX B MODE 2462MHz

Vertical




	No.	Mk	. Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Margin			
			MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment	
	1	*	2460.200	58.60	34.36	92.96	54.00	38.96	AVG	No Limit	
	2	X	2461.200	60.72	34.37	95.09	74.00	21.09	peak	No Limit	
	3		2483.500	23.70	34.43	58.13	74.00	-15.87	peak		
	4		2483.500	13.78	34.43	48.21	54.00	-5.79	AVG		
_											

Report No.: BTL-FCCP-2-1504C059 Page 51 of 104



Orthogonal Axis: X
Test Mode: TX B MODE 2462MHz

Vertical




No.	Mk	. Freq.		Correct Factor	Measure- ment		Margin		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	*	4923.990	37.11	7.12	44.23	54.00	-9.77	AVG	
2		4924.030	41.11	7.12	48.23	74.00	-25.77	peak	

Report No.: BTL-FCCP-2-1504C059 Page 52 of 104



Test Mode: TX B MODE 2462MHz

Horizontal



	No.	MI	k. F	req.	Reading Level	Correct Factor	Measure- ment	Limit	Margin		
			N	1Hz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
	1	*	2460.	200	67.64	34.36	102.00	54.00	48.00	AVG	No Limit
	2	X	2461.	200	69.72	34.37	104.09	74.00	30.09	peak	No Limit
Ī	3		2483.	500	25.03	34.43	59.46	74.00	-14.54	peak	
	4		2483.	500	14.07	34.43	48.50	54.00	-5.50	AVG	

Report No.: BTL-FCCP-2-1504C059 Page 53 of 104



Orthogonal Axis: X
Test Mode: TX B MODE 2462MHz

Horizontal




No.	. N	Λk.	Freq.		Correct Factor	Measure- ment		Margin		
			MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		49	923.920	40.10	7.12	47.22	74.00	-26.78	peak	
2	*	49	923.970	34.80	7.12	41.92	54.00	-12.08	AVG	

Report No.: BTL-FCCP-2-1504C059 Page 54 of 104



Orthogonal Axis: X
Test Mode: TX G MODE 2412MHz

Vertical




	No.	Mk.	. Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Margin		
			MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
	1		2390.000	24.33	34.17	58.50	74.00	-15.50	peak	
	2		2390.000	14.00	34.17	48.17	54.00	-5.83	AVG	
	3	X	2418.800	59.29	34.25	93.54	74.00	19.54	peak	No Limit
	4	*	2419.600	50.23	34.25	84.48	54.00	30.48	AVG	No Limit
_										

Report No.: BTL-FCCP-2-1504C059 Page 55 of 104



Orthogonal Axis: X
Test Mode: TX G MODE 2412MHz

Vertical




No.	М	k.	Freq.		Correct Factor	Measure- ment	Limit	Margin		
			MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	*	482	23.580	31.46	3.62	35.08	54.00	-18.92	AVG	
2		482	24.020	42.46	3.62	46.08	74.00	-27.92	peak	

Report No.: BTL-FCCP-2-1504C059 Page 56 of 104



Test Mode: TX G MODE 2412MHz

Horizontal



	No.	Mk	. Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Margin		
			MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
	1		2390.000	24.97	34.17	59.14	74.00	-14.86	peak	
Ī	2		2390.000	15.10	34.17	49.27	54.00	-4.73	AVG	
Ī	3	Х	2419.100	69.47	34.25	103.72	74.00	29.72	peak	No Limit
	4	*	2419.400	60.39	34.25	94.64	54.00	40.64	AVG	No Limit

Report No.: BTL-FCCP-2-1504C059 Page 57 of 104



Test Mode: TX G MODE 2412MHz

Horizontal




No.	М	k.	Freq.		Correct Factor	Measure- ment		Margin		
			MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		48	23.180	42.35	3.62	45.97	74.00	-28.03	peak	
2	*	48	23.420	30.63	3.62	34.25	54.00	-19.75	AVG	

Report No.: BTL-FCCP-2-1504C059 Page 58 of 104



Orthogonal Axis: X Test Mode: TX G MODE 2437MHz

Vertical



No.	Mk	. Freq.		Correct Factor	Measure- ment		Margin			
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment	
1	*	2429.700	50.29	34.28	84.57	54.00	30.57	AVG	No Limit	
2	Х	2429.900	59.61	34.28	93.89	74.00	19.89	peak	No Limit	

Report No.: BTL-FCCP-2-1504C059 Page 59 of 104



Orthogonal Axis: X
Test Mode: TX G MODE 2437MHz

Vertical




No.	M	K .	Freq.		Correct Factor	Measure- ment	Limit	Margin		
			MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	*	487	3.980	30.22	3.72	33.94	54.00	-20.06	AVG	
2		487	4.440	40.68	3.72	44.40	74.00	-29.60	peak	

Report No.: BTL-FCCP-2-1504C059 Page 60 of 104



Test Mode: TX G MODE 2437MHz

Horizontal




No.	М	k.	Freq.			Measure- ment		Margin		
			MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	*	24	29.500	59.24	34.28	93.52	54.00	39.52	AVG	No Limit
2	Х	24	30.000	67.97	34.28	102.25	74.00	28.25	peak	No Limit

Report No.: BTL-FCCP-2-1504C059 Page 61 of 104



Test Mode: TX G MODE 2437MHz

Horizontal



No.	N	Иk.	Freq.		Correct Factor	Measure- ment		Margin		
			MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		4	872.940	41.55	3.72	45.27	74.00	-28.73	peak	
2	*	* 4	873.920	29.66	3.72	33.38	54.00	-20.62	AVG	

Report No.: BTL-FCCP-2-1504C059 Page 62 of 104



Orthogonal Axis: X
Test Mode: TX G MODE 2462MHz

No.	М	k.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Margin		
			MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	*	24	56.700	52.00	34.36	86.36	54.00	32.36	AVG	No Limit
2	Х	24	57.100	61.58	34.36	95.94	74.00	21.94	peak	No Limit
3		24	83.500	23.62	34.43	58.05	74.00	-15.95	peak	
4		24	83.500	14.11	34.43	48.54	54.00	-5.46	AVG	

2462.00

2472.00

2482.00

2492.00

2512.00 MHz

30.0

2412.000 2422.00

2432.00

2442.00

2452.00

Report No.: BTL-FCCP-2-1504C059 Page 63 of 104



Orthogonal Axis: X
Test Mode: TX G MODE 2462MHz

Vertical




No.	М	k. Freq.		Correct Factor	Measure- ment		Margin		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		4923.300	43.03	3.80	46.83	74.00	-27.17	peak	
2	*	4923.960	31.76	3.80	35.56	54.00	-18.44	AVG	

Report No.: BTL-FCCP-2-1504C059 Page 64 of 104



Test Mode: TX G MODE 2462MHz

Horizontal




		Margin	Limit	Measure- ment	Factor	Reading Level	Freq.	Mk.	No.
Comment	Detector	dB	dBuV/m	dBuV/m	dB	dBuV	MHz		
No Limit	AVG	41.46	54.00	95.46	34.36	61.10	456.800	* 2	1
No Limit	peak	30.76	74.00	104.76	34.36	70.40	456.900	X 2	2
	peak	-11.27	74.00	62.73	34.43	28.30	483.500	2	3
	AVG	-3.95	54.00	50.05	34.43	15.62	483.500	2	4
 No Limit	AVG peak peak	41.46 30.76 -11.27	54.00 74.00 74.00	95.46 104.76 62.73	34.36 34.36 34.43	61.10 70.40 28.30	456.800 456.900 483.500	X 2	3

Report No.: BTL-FCCP-2-1504C059 Page 65 of 104



Orthogonal Axis: X
Test Mode: TX G MODE 2462MHz

Horizontal




No.	M	lk.	Freq.		Correct Factor	Measure- ment		Margin		
			MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	*	49	24.200	29.78	3.80	33.58	54.00	-20.42	AVG	
2		49	25.300	40.94	3.80	44.74	74.00	-29.26	peak	

Report No.: BTL-FCCP-2-1504C059 Page 66 of 104



Orthogonal Axis: X
Test Mode: TX N-20M MODE 2412MHz

Vertical




	No.	Mk	. Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Margin		
Ī			MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
Ī	1		2390.000	24.61	31.88	56.49	74.00	-17.51	peak	
	2		2390.000	14.30	31.88	46.18	54.00	-7.82	AVG	
Ī	3	X	2419.400	66.48	31.92	98.40	74.00	24.40	peak	No Limit
Ī	4	*	2419.800	56.74	31.92	88.66	54.00	34.66	AVG	No Limit
-										

Report No.: BTL-FCCP-2-1504C059 Page 67 of 104



Orthogonal Axis: X
Test Mode: TX N-20M MODE 2412MHz

Vertical




No.	M	c. Freq.		Correct Factor	Measure- ment		Margin		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		4823.960	40.15	3.62	43.77	74.00	-30.23	peak	
2	*	4824.060	29.76	3.62	33.38	54.00	-20.62	AVG	

Report No.: BTL-FCCP-2-1504C059 Page 68 of 104



Test Mode: TX N-20M MODE 2412MHz

Horizontal



No.	М	c. Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Margin			
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment	
1		2390.000	23.86	31.88	55.74	74.00	-18.26	peak		
2		2390.000	14.51	31.88	46.39	54.00	-7.61	AVG		
3	X	2417.800	69.50	31.91	101.41	74.00	27.41	peak	No Limit	
4	*	2419.500	60.22	31.92	92.14	54.00	38.14	AVG	No Limit	

Report No.: BTL-FCCP-2-1504C059 Page 69 of 104



Test Mode: TX N-20M MODE 2412MHz

Horizontal




No.	М	k.	Freq.		Correct Factor	Measure- ment	Limit	Margin		
			MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	*	482	3.640	29.89	3.62	33.51	54.00	-20.49	AVG	
2		482	3.760	40.73	3.62	44.35	74.00	-29.65	peak	

Report No.: BTL-FCCP-2-1504C059 Page 70 of 104



Orthogonal Axis: X
Test Mode: TX N-20M MODE 2437MHz

Vertical



No.	М	۲.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Margin		
			MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	Х	243	31.600	66.50	31.94	98.44	74.00	24.44	peak	No Limit
2	*	244	44.400	56.38	31.96	88.34	54.00	34.34	AVG	No Limit

Report No.: BTL-FCCP-2-1504C059 Page 71 of 104



Orthogonal Axis: X
Test Mode: TX N-20M MODE 2437MHz

Vertical



No.	М	c. Free	Reading Level		Measure- ment		Margin		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		4873.68	0 39.65	3.72	43.37	74.00	-30.63	peak	
2	*	4874.96	0 29.17	3.72	32.89	54.00	-21.11	AVG	


Report No.: BTL-FCCP-2-1504C059 Page 72 of 104



Orthogonal Axis: X

Test Mode: TX N-20M MODE 2437MHz

Horizontal



No.	Mk	. Freq.		Correct Factor	Measure- ment	Limit	Margin			
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment	
1	*	2429.600	59.46	31.93	91.39	54.00	37.39	AVG	No Limit	
2	Х	2431.900	69.51	31.94	101.45	74.00	27.45	peak	No Limit	

Report No.: BTL-FCCP-2-1504C059 Page 73 of 104



Orthogonal Axis: X

Test Mode: TX N-20M MODE 2437MHz

Horizontal



No.	М	k.	Freq.		Correct Factor	Measure- ment		Margin		
			MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	*	487	74.120	29.25	3.72	32.97	54.00	-21.03	AVG	
2		487	75.420	40.07	3.72	43.79	74.00	-30.21	peak	

Report No.: BTL-FCCP-2-1504C059 Page 74 of 104



Orthogonal Axis: X
Test Mode: TX N-20M MODE 2462MHz

	No.	M	c. Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Margin			
Ī			MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment	
	1	*	2454.800	58.53	31.96	90.49	54.00	36.49	AVG	No Limit	
Ī	2	Х	2456.100	67.86	31.96	99.82	74.00	25.82	peak	No Limit	
	3		2483.500	24.80	32.01	56.81	74.00	-17.19	peak		
Ī	4		2483.500	14.94	32.01	46.95	54.00	-7.05	AVG		
_											_

2462.00

2472.00

2492.00

2482.00

2512.00 MHz

30.0

2412.000 2422.00

2432.00

2442.00


2452.00

Report No.: BTL-FCCP-2-1504C059 Page 75 of 104



Orthogonal Axis: X
Test Mode: TX N-20M MODE 2462MHz

Vertical




No.	M	. Freq.		Correct Factor	Measure- ment		Margin		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	*	4924.040	28.97	3.80	32.77	54.00	-21.23	AVG	
2		4925.220	39.70	3.80	43.50	74.00	-30.50	peak	

Report No.: BTL-FCCP-2-1504C059 Page 76 of 104



Orthogonal Axis: X
Test Mode: TX N-20M MODE 2462MHz

Horizontal



No. Mk. Freq. Level Factor ment Limit Margin			Margin		Measure- ment		Reading Level	Freq.	Mk.	No.
MHz dBuV dB dBuV/m dBuV/m dB Detector Commen	Comme	Detector	dB	dBuV/m	dBuV/m	dB	dBuV	MHz		
1 * 2454.700 61.35 31.96 93.31 54.00 39.31 AVG No Limit	No Limit	AVG	39.31	54.00	93.31	31.96	61.35	454.700	* 2	1
2 X 2456.700 70.89 31.97 102.86 74.00 28.86 peak No Limit	No Limit	peak	28.86	74.00	102.86	31.97	70.89	456.700	X 2	2
3 2483.500 26.60 32.01 58.61 74.00 -15.39 peak		peak	-15.39	74.00	58.61	32.01	26.60	483.500	2	3
4 2483.500 15.54 32.01 47.55 54.00 -6.45 AVG		AVG	-6.45	54.00	47.55	32.01	15.54	483.500	2	4


Report No.: BTL-FCCP-2-1504C059 Page 77 of 104



Orthogonal Axis: X

Test Mode: TX N-20M MODE 2462MHz

Horizontal



No.	М	k.	Freq.		Correct Factor	Measure- ment	Limit	Margin		
			MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	*	492	23.840	28.91	3.80	32.71	54.00	-21.29	AVG	
2		492	24.540	39.91	3.80	43.71	74.00	-30.29	peak	

Report No.: BTL-FCCP-2-1504C059 Page 78 of 104



ATTACHMENT E - BANDWIDTH	


Report No.: BTL-FCCP-2-1504C059 Page 79 of 104



Test Mode: TX B Mode_CH01/06/11

Frequency (MHz)	6dB Bandwidth (MHz)	99% Occupied BW (MHz)	Min. Limit (kHz)	Test Result
2412	7.50	12.60	500	Complies
2437	8.00	12.20	500	Complies
2462	7.61	11.76	500	Complies


TX CH01




Date: 21.APR.2015 10:31:34

Report No.: BTL-FCCP-2-1504C059 Page 80 of 104





Date: 21.APR.2015 10:33:08




Date: 21.APR.2015 10:34:35



Test Mode: TX G Mode_CH01/06/11

Frequency (MHz)	6dB Bandwidth (MHz)	99% Occupied BW (MHz)	Min. Limit (kHz)	Test Result
2412	15.76	16.56	500	Complies
2437	16.55	16.64	500	Complies
2462	14.57	16.52	500	Complies


TX CH01




Date: 21.APR.2015 10:36:04

Report No.: BTL-FCCP-2-1504C059 Page 82 of 104





Date: 21.APR.2015 10:37:20




Date: 21.APR.2015 10:38:43



Test Mode: TX N-20MHz Mode_CH01/06/11

Frequency (MHz)	6dB Bandwidth (MHz)	99% Occupied BW (MHz)	Min. Limit (kHz)	Test Result
2412	17.44	17.72	500	Complies
2437	17.68	17.76	500	Complies
2462	16.40	17.72	500	Complies


TX CH01




Date: 21.APR.2015 10:40:07

Report No.: BTL-FCCP-2-1504C059 Page 84 of 104





Date: 21.APR.2015 10:41:27



Date: 21.APR.2015 10:42:42



ATTACHMENT F – MAXIMUM PEAK CONDUCTED OUTPUT POWER

Report No.: BTL-FCCP-2-1504C059 Page 86 of 104



Test Mode :TX B Mode_CH01/06/11

Frequency (MHz)	Conducted Power (dBm)	Conducted Power (W)	Max. Limit (dBm)	Max. Limit (W)	Result
2412	14.89	0.03	30.00	1.00	Complies
2437	14.42	0.03	30.00	1.00	Complies
2462	14.31	0.03	30.00	1.00	Complies

Test Mode :TX G Mode_CH01/06/11

Frequency (MHz)	Conducted Power (dBm)	Conducted Power (W)	Max. Limit (dBm)	Max. Limit (W)	Result
2412	11.34	0.01	30.00	1.00	Complies
2437	11.56	0.01	30.00	1.00	Complies
2462	11.23	0.01	30.00	1.00	Complies

Test Mode :TX N20 Mode_CH01/06/11

Frequency (MHz)	Conducted Power (dBm)	Conducted Power (W)	Max. Limit (dBm)	Max. Limit (W)	Result
2412	8.65	0.01	30.00	1.00	Complies
2437	8.72	0.01	30.00	1.00	Complies
2462	8.48	0.01	30.00	1.00	Complies


Report No.: BTL-FCCP-2-1504C059 Page 87 of 104




ATTACHMENT G - ANTENNA CONDUCTED SPURIOUS **EMISSION**


Report No.: BTL-FCCP-2-1504C059 Page 88 of 104












Date: 20.MAY.2015 04:49:48


TX B mode CH06 (10 Harmonic of the frequency)



Date: 20.MAY.2015 04:59:25




TX B mode CH11 (10 Harmonic of the frequency)



Date: 20.MAY.2015 05:01:06


Report No.: BTL-FCCP-2-1504C059 Page 91 of 104













Date: 20.MAY.2015 05:05:43


TX G mode CH06 (10 Harmonic of the frequency)



Date: 20.MAY.2015 05:03:48








Date: 20.MAY.2015 05:08:06


Report No.: BTL-FCCP-2-1504C059 Page 94 of 104












Date: 20.MAY.2015 05:09:37


TX HT20 mode CH06 (10 Harmonic of the frequency)



Date: 20.MAY.2015 05:11:42







Date: 20.MAY.2015 05:13:21

Report No.: BTL-FCCP-2-1504C059 Page 97 of 104



ATTACHMENT H - POWER SPECTRAL DENSITY					


Report No.: BTL-FCCP-2-1504C059 Page 98 of 104



Test Mode :TX B Mode_CH01/06/11

Frequency (MHz)	Power Density (dBm/3kHz)	Power Density (mW/3kHz)	Max. Limit (dBm/3kHz)	Result
2412	-9.49	0.11	8.00	Complies
2437	-9.47	0.11	8.00	Complies
2462	-10.16	0.10	8.00	Complies


TX CH01



Date: 21.APR.2015 10:32:05

Report No.: BTL-FCCP-2-1504C059 Page 99 of 104





Date: 21.APR.2015 10:33:31

TX CH11 *RBW 3 kHz Marker 1 [T1] *VBW 10 kHz -10.16 dBm Ref 20 dBm *Att 30 dB SWT 2.8 s 2.461500000 GHz 20 Offset 1 dB -10 -20 -20 -30 -40 -50 -60 Center 2.462 GHz 2.5 MHz/ Span 25 MHz


Date: 21.APR.2015 10:35:05



Test Mode :TX G Mode_CH01/06/11

Frequency (MHz)	Power Density (dBm/3kHz)	Power Density (mW/3kHz)	Max. Limit (dBm/3kHz)	Result
2412	-14.68	0.03	8.00	Complies
2437	-15.96	0.03	8.00	Complies
2462	-15.27	0.03	8.00	Complies


TX CH01



Date: 21.APR.2015 10:36:35

Report No.: BTL-FCCP-2-1504C059 Page 101 of 104





Date: 21.APR.2015 10:37:44


Date: 21.APR.2015 10:39:13



Test Mode: TX N-20M Mode_CH01/06/11

Frequency (MHz)	Power Density (dBm/3kHz)	Power Density (mW/3kHz)	Max. Limit (dBm/3kHz)	Result
2412	-12.26	0.06	8.00	Complies
2437	-20.06	0.01	8.00	Complies
2462	-17.83	0.02	8.00	Complies


TX CH01




Date: 21.APR.2015 10:40:38

Report No.: BTL-FCCP-2-1504C059 Page 103 of 104





Date: 21.APR.2015 10:41:50



Date: 21.APR.2015 10:43:13