

RF Exposure Report

Report No.: SA160217D08

FCC ID: 2AEFTAW330S

Model No.: AW330S

Received Date: Feb. 17, 2016

Test Date: Feb. 17 ~ 24, 2016

Issued Date: Feb. 26, 2016

Applicant: AVerMedia Technologies Inc.

Address: NO.135, Jian 1st Rd., Zhonghe Dist, New Taipei City, Taiwan (R.O.C.)

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan

(R.O.C.)





This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.

Report No.: SA160217D08 Page No. 1 / 5 Report Format Version: 6.1.1



Table of Contents

Relea	se Control Record	3
1	Certificate of Conformity	4
	RF Exposure	
2.1 2.2	Limits For Maximum Permissible Exposure (MPE)	5 5
2.3	Classification	5
3	Calculation Result Of Maximum Conducted Power	5



Release Control Record

Issue No.	Description	Date Issued
SA160217D08	Original release.	Feb. 26, 2016



1 Certificate of Conformity

Product: Wireless Speaker

Brand: AVerMedia

Model No.: AW330S

Sample Status: Engineering sample

Applicant: AVerMedia Technologies Inc.

Test Date: Feb. 17 ~ 24, 2016

Standards: FCC Part 2 (Section 2.1091)

KDB 447498 D01 General RF Exposure Guidance v06

IEEE C95.1-2005

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

Prepared by:

Date: Feb. 26, 2016

Approved by 3

(Rex Lai / Assistant Manager)

(Celia Chen / Supervisor)

Date: Feb. 26, 2016



2 RF Exposure

2.1 Limits For Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)				
Limits For General Population / Uncontrolled Exposure								
300-1500			F/1500	30				
1500-100,000	•••		1.0	30				

F = Frequency in MHz

2.2 MPE Calculation Formula

 $Pd = (Pout*G) / (4*pi*r^2)$

where

Pd = power density in mW/cm²

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

2.3 Classification

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as **Mobile Device**.

3 Calculation Result Of Maximum Conducted Power

Frequency	Max Power	Antenna Gain	Distance	Power Density (mW/cm ²)	Limit
(MHz)	(dBm)	(dBi)	(cm)		(mW/cm ²)
2406 ~ 2474	8.96	0.46	20	0.0017	1

--- END ---