

FCC Test Report

Report No.: RF160217D08

FCC ID: 2AEFTAW330S

Test Model: AW330S

Received Date: Feb. 17, 2016

Test Date: Feb. 17 ~ 24, 2016

Issued Date: Feb. 26, 2016

Applicant: AVerMedia Technologies Inc.

Address: NO.135, Jian 1st Rd., Zhonghe Dist, New Taipei City, Taiwan (R.O.C.)

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan

(R.O.C.)





This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.

Report No.: RF160217D08 Page No. 1 / 38 Report Format Version: 6.1.1



Table of Contents

R	Release Control Record4					
1	1 Certificate of Conformity5					
2	S	ummary of Test Results	6			
	2.1 2.2	Measurement Uncertainty				
3	G	eneral Information	7			
	3.1 3.2 3.2.1 3.3 3.3.1 3.4	General Description of EUT Description of Test Modes Test Mode Applicability and Tested Channel Detail Description of Support Units Configuration of System under Test General Description of Applied Standards	8 9 .11 .11			
4	I	est Types and Results				
	4.1.2 4.1.3 4.1.4 4.1.5	Radiated Emission and Bandedge Measurement. Limits of Radiated Emission and Bandedge Measurement Test Instruments Test Procedures Deviation from Test Standard Test Set Up	13 14 15 15 16			
		EUT Operating Conditions				
	4.2	Conducted Emission Measurement				
		Limits of Conducted Emission Measurement	21			
		Test Instruments				
		Test Procedures Deviation From Test Standard				
		Test Setup				
		EUT Operating Condition				
	4.2.7	Test Results				
	4.3	Number of Hopping Frequency Used				
	4.3.1	Limits of Hopping Frequency Used Measurement				
		Test Setup Test Instruments				
		Test Procedure				
		Deviation fromTest Standard				
		Test Results				
	4.4	Dwell Time on Each Channel				
		Limits of Dwell Time on Each Channel Measurement				
		Test Setup				
		Test Instruments				
		Deviation from Test Standard				
		Test Results				
	4.5	Channel Bandwidth	_			
	4.5.1	Limits of Channel Bandwidth Measurement				
		Test Setup				
		Test Instruments				
		Test Procedure				
		Deviation from Test Standard				
		EUT Operating Condition Test Results				
	4.5.7	Hopping Channel Separation				
		-11 0 - · · · · · · · · · F - · · · · · ·				



4.6.1	Limits of Hopping Channel Separation Measurement	31				
	Test Setup					
	Test Instruments					
	Test Procedure					
	Deviation From Test Standard					
	Test Results					
4.7	Maximum Output Power	33				
4.7.1	Limits of Maximum Output Power Measurement	33				
4.7.2	Test Setup	33				
4.7.3	Test Instruments	33				
4.7.4	Test Procedure	33				
4.7.5	Deviation fromTest Standard	33				
	EUT Operating Condition					
4.7.7	Test Results					
4.8	Conducted Out of Band Emission Measurement					
4.8.1	Elimic Of Conductor Cat Of Band Elimonor Moderation					
	Test Instruments					
	Test Procedure					
	Deviation From Test Standard					
	Eut Operating Condition					
4.8.6	Test Results	35				
5 F	Pictures of Test Arrangements	37				
	_					
Append	Appendix – Information on the Testing Laboratories					



Release Control Record

Issue No.	Description	Date Issued
RF160217D08	Original release.	Feb. 26, 2016



1 Certificate of Conformity

Product: Wireless Speaker

Brand: AVerMedia

Test Model: AW330S

Sample Status: Engineering sample

Applicant: AVerMedia Technologies Inc.

Test Date: Feb. 17 ~ 24, 2016

Standards: 47 CFR FCC Part 15, Subpart C (Section 15.247)

ANSI C63.10:2013

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

Prepared by: , Date: Feb. 26, 2016

(Celia Chen / Supervisor)

(Rex Lai / Assistant Manager)

Approved by: , Date: Feb. 26, 2016

Report No.: RF160217D08 Page No. 5 / 38 Report Format Version: 6.1.1



2 Summary of Test Results

47 CFR FCC Part 15, Subpart C (SECTION 15.247)							
FCC Test Item		Result	Remarks				
15.207	AC Power Conducted Emission	PASS	Meet the requirement of limit. Minimum passing margin is -7.08dB at 0.19687MHz.				
15.247(a)(1) (iii)	Number of Hopping Frequency Used	PASS	Meet the requirement of limit.				
15.247(a)(1) (iii)			Meet the requirement of limit.				
15.247(a)(1)	Hopping Channel Separation Spectrum Bandwidth of a Frequency Hopping Sequence Spread Spectrum System	PASS	Meet the requirement of limit.				
15.247(b)	Maximum Peak Output Power	PASS	Meet the requirement of limit.				
15.205 & 209	Radiated Emissions	PASS	Meet the requirement of limit. Minimum passing margin is -8.9dB at 32.76MHz.				
15.247(d)	Band Edge Measurement	PASS	Meet the requirement of limit. Minimum passing margin is -10.4dB at 2483.50MHz.				
15.247(d)	Antenna Port Emission	PASS	Meet the requirement of limit.				
15.203	Antenna Requirement	PASS	No antenna connector is used.				

NOTE: If The Frequency Hopping System operating in 2400-2483.5MHz band and the output power less than 125mW. The hopping channel carrier frequencies separated by a minimum of 25kHz or two-thirds of the 20dB bandwidth of hopping channel whichever is greater.

2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Measurement	Frequency	Expended Uncertainty (k=2) (±)
Conducted Emissions at mains ports	150kHz ~ 30MHz	2.78 dB
Radiated Emissions up to 1 GHz	30MHz ~ 1000MHz	4.00 dB
Radiated Emissions above 1 GHz	1GHz ~ 40GHz	3.36 dB

2.2 Modification Record

There were no modifications required for compliance.



3 General Information

3.1 General Description of EUT

Product	Wireless Speaker
Brand	AVerMedia
Test Model	AW330S
Status of EUT	Engineering sample
Dawer Cumby Dating	9Vdc from adapter
Power Supply Rating	7.4Vdc from battery
Modulation Type	GFSK
Modulation Technology	FHSS
Transfer Rate	4Mbps
Operating Frequency	2406 ~ 2474MHz
Number of Channel	18
Output Power	7.870mW
Antenna Type	PCB antenna with 0.46dBi gain
Antenna Connector	N/A
Accessory Device	Adapter
Data Cable Supplied	Non-shielded audio cable (0.6m) with two ferrite cores

Note:

- 1. The EUT is a Wireless Speaker.
- 2. The EUT uses following adapter and battery.

Adapter	Adapter			
Brand	Sunny			
Model	SYS1541-1809			
Input Power	100-240Vac, 1.0A, 50-60Hz			
Output Power	9Vdc, 2A			
Power Line	Non-shielded DC cable (1.5m) with one ferrite core			
Battery	Battery			
Brand	SHENZHEN POW-TECH NEW POWER CO.,LTD			
Model	ICR18650-2S-PCM2600			
Rating	7.4Vdc, 2600mAh			

- 3. The EUT was pre-tested with the following modes:
 - Operating Mode (EUT stand-alone)
 - Operating Mode (EUT with adapter)

The worst emission level was found when the EUT tested under **Operating Mode (EUT with adapter)**.

4. The above EUT information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or User's Manual.



3.2 Description of Test Modes

18 channels are provided for EUT:

Channel	Channel Freq. (MHz)		Freq. (MHz)
4	2406	40	2442
8	2410	44	2446
12	2414	48	2450
16	2418	52	2454
20	2422	56	2458
24	2426	60	2462
28	2430	64	2466
32	2434	68	2470
36	2438	72	2474



3.2.1 Test Mode Applicability and Tested Channel Detail

EUT CONFIGURE	APPLICABLE TO				DESCRIPTION
MODE	RE ³ 1G	RE<1G	PLC	APCM	DESCRIPTION
-	V	V	V	√	Operating Mode (EUT with adapter)

Where **RE**³**1G**: Radiated Emission above 1GHz

RE<1G: Radiated Emission below 1GHz

PLC: Power Line Conducted Emission APCM: Antenna Port Conducted Measurement

NOTE: The EUT had been pre-tested on the positioned of each 3 axis. The worst case was found when positioned on X-plane.

Radiated Emission Test (Above 1GHz):

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE		AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE
	=	4 to 72	4, 36, 72	FHSS	GFSK

Radiated Emission Test (Below 1GHz):

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE
-	4 to 72	72	FHSS	GFSK

Power Line Conducted Emission Test:

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE		AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE
	-	4 to 72	72	FHSS	GFSK

Report No.: RF160217D08 Page No. 9 / 38 Report Format Version: 6.1.1



Antenna Port Conducted Measurement:

- This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE
-	4 to 72	4, 36, 72	FHSS	GFSK

Test Condition:

APPLICABLE TO	ENVIRONMENTAL CONDITIONS	INPUT POWER	TESTED BY
RE ³ 1G	17deg. C, 73%RH	120Vac, 60Hz	Aaron You
RE<1G	17deg. C, 73%RH	120Vac, 60Hz	Aaron You
PLC	20deg. C, 73%RH	120Vac, 60Hz	Aaron You
APCM	25deg. C, 60%RH	120Vac, 60Hz	Saxon Lee

Report No.: RF160217D08 Page No. 10 / 38 Report Format Version: 6.1.1



3.3 Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

ID	Product	Brand	Model No.	Serial No.	FCC ID	Remarks
A.	iPhone 6 Plus	Apple	A1524	NA	NA	Supplied by client
B.	Smart Microphone	AVerMedia	AW313T	NA	NA	Supplied by client


Note: All power cords of the above support units are non-shielded (1.8m).

ID	Descriptions	Qty.	Length (m)	Shielding (Yes/No)	Cores (Qty.)	Remarks
1.	Audio cable	1	0.6	N	2	Supplied by client
2.	DC cable	1	1.5	N	1	Supplied by client


Note: The core(s) is(are) originally attached to the cable(s).

3.3.1 Configuration of System under Test

TEST CONFIGURATION <For PLC & RE<1G Tests>



TEST CONFIGURATION <For RE31G Test>



Report No.: RF160217D08 Page No. 11 / 38 Report Format Version: 6.1.1



3.4 **General Description of Applied Standards** The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards: FCC Part 15, Subpart C (15.247) ANSI C63.10-2013 All test items have been performed and recorded as per the above standards.

Report No.: RF160217D08 Page No. 12 / 38 Report Format Version: 6.1.1



4 Test Types and Results

4.1 Radiated Emission and Bandedge Measurement

4.1.1 Limits of Radiated Emission and Bandedge Measurement

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 20dB below the highest level of the desired power:

_ I		
Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

NOTE:

- 1. The lower limit shall apply at the transition frequencies.
- 2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
- 3. For frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

Report No.: RF160217D08 Page No. 13 / 38 Report Format Version: 6.1.1



4.1.2 Test Instruments

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
HP Preamplifier	8447D	2432A03504	Feb. 26, 2015	Feb. 25, 2016
HP Preamplifier	8449B	3008A01201	Feb. 26, 2015	Feb. 25, 2016
MITEQ Preamplifier	AMF-6F-260400-33-8P	892164	Mar. 01, 2015	Feb. 28, 2016
Agilent TEST RECEIVER	N9038A	MY51210129	Feb. 02, 2016	Feb. 01, 2017
Schwarzbeck Antenna	VULB 9168	139	Jan. 04, 2016	Jan. 03, 2017
Schwarzbeck Antenna	VHBA 9123	480	May 29, 2015	May 28, 2017
Schwarzbeck Horn Antenna	BBHA-9170	212	Jan. 08, 2016	Jan. 07, 2017
Schwarzbeck Horn Antenna	BBHA 9120-D1	D130	Jan. 21, 2016	Jan. 20, 2017
ADT. Turn Table	TT100	0306	NA	NA
ADT. Tower	AT100	0306	NA	NA
Software	Radiated_V7.6.15.9.4	NA	NA	NA
SUHNER RF cable With 4dB PAD	SF104	CABLE-CH6	Aug. 15, 2015	Aug. 14, 2016
SUHNER RF cable With 3dB PAD	SF102	Cable-CH8-3.6m	Aug. 15, 2015	Aug. 14, 2016
KEYSIGHT MIMO Powermeasurement Test set	U2021XA	U2021XA-001	May 04, 2015	May 03, 2016
KEYSIGHT Spectrum Analyzer	N9030A	MY54490260	Jul. 14, 2015	Jul. 13, 2016
EMCO Horn Antenna	3115	00028257	Jan. 19, 2016	Jan. 18, 2017
Highpass filter Wainwright Instruments	WHK 3.1/18G-10SS	SN 8	NA	NA
ROHDE & SCHWARZ Spectrum Analyzer	FSV40	101042	Sep. 23, 2015	Sep. 22, 2016
Anritsu Power Sensor	MA2411B	0738404	Apr. 21, 2015	Apr. 20, 2016
Anritsu Power Meter	ML2495A	0842014	Apr. 21, 2015	Apr. 20, 2016

NOTE: 1. The calibration interval of the above test instruments is 12/24 months. And the calibrations are traceable to NML/ROC and NIST/USA.

- 2. The horn antenna and HP preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
- 3. The test was performed in Chamber No. 6.
- 4. The Industry Canada Reference No. IC 7450E-6.
- 5. The FCC Site Registration No. is 447212.



4.1.3 Test Procedures

- a. The EUT was placed on the top of a rotating table 0.8 meters (for below 1GHz) / 1.5 meters (for above 1GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f. The test-receiver system was set to peak detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz.

Note:

- 1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
- 2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1GHz.
- 3. All modes of operation were investigated and the worst-case emissions are reported.


4.1.4	Deviation	from Te	est Stanc	lard
T. I.T	Deviation	110111 10	JOL OLAITO	auru

No deviation.




4.1.5 Test Set Up

<Frequency Range below 1GHz>



<Frequency Range above 1GHz>



For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.1.6 EUT Operating Conditions

Set the EUT under transmission condition continuously at specific channel frequency.



4.1.7 Test Results

ABOVE 1GHz DATA

CHANNEL	TX Channel 4	DETECTOR	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz	FUNCTION	Average (AV)

	ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M							
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	58.0 PK	74.0	-16.0	3.04 H	322	56.68	1.35
2	2390.00	44.5 AV	54.0	-9.5	3.04 H	322	43.19	1.35
3	*2406.00	94.2 PK			3.04 H	322	92.76	1.45
4	*2406.00	45.2 AV			3.04 H	322	43.72	1.45
5	4812.00	56.9 PK	74.0	-17.1	1.06 H	336	48.88	8.04
6	4812.00	35.4 AV	54.0	-18.6	1.06 H	336	27.36	8.04
7	7218.00	59.5 PK	74.0	-14.5	2.04 H	276	43.88	15.62
8	7218.00	41.7 AV	54.0	-12.3	2.04 H	276	26.05	15.62
		ANTENNA	A POLARITY	/ & TEST DI	STANCE: V	ERTICAL A	T 3 M	
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	57.2 PK	74.0	-16.8	1.31 V	243	55.82	1.35
2	2390.00	43.7 AV	54.0	-10.3	1.31 V	243	42.39	1.35
3	*2406.00	93.4 PK			1.31 V	243	91.98	1.45
4	*2406.00	45.0 AV			1.31 V	243	43.53	1.45
5	4812.00	56.0 PK	74.0	-18.0	3.94 V	252	47.99	8.04
6	4812.00	34.4 AV	54.0	-19.6	3.94 V	252	26.38	8.04
7	7218.00	58.5 PK	74.0	-15.5	3.09 V	324	42.89	15.62
8	7218.00	40.8 AV	54.0	-13.2	3.09 V	324	25.17	15.62

- 1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
- 2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) Pre-Amplifier Factor(dB)
- 3. The other emission levels were very low against the limit.
- 4. Margin value = Emission Level Limit value
- 5. " * ": Fundamental frequency.



CHANNEL	TX Channel 36	DETECTOR	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz	FUNCTION	Average (AV)

	ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M							
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2438.00	101.4 PK			2.04 H	338	99.81	1.59
2	*2438.00	45.0 AV			2.04 H	338	43.44	1.59
3	4876.00	53.1 PK	74.0	-20.9	3.61 H	337	44.98	8.12
4	4876.00	33.9 AV	54.0	-20.2	3.61 H	337	25.73	8.12
5	7314.00	58.7 PK	74.0	-15.3	1.99 H	279	42.75	15.96
6	7314.00	41.8 AV	54.0	-12.2	1.99 H	279	25.81	15.96
		ANTENNA	A POLARITY	/ & TEST DI	STANCE: V	ERTICAL A	T 3 M	
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2438.00	92.2 PK			2.59 V	327	90.60	1.59
2	*2438.00	44.6 AV			2.59 V	327	42.96	1.59
3	4876.00	52.8 PK	74.0	-21.2	1.94 V	210	44.69	8.12
4	4876.00	33.8 AV	54.0	-20.2	1.94 V	210	25.66	8.12
5	7314.00	57.9 PK	74.0	-16.1	2.78 V	273	41.91	15.96
6	7314.00	41.6 AV	54.0	-12.4	2.78 V	273	25.60	15.96

- 1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
- 2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) Pre-Amplifier Factor(dB)
- 3. The other emission levels were very low against the limit.
- 4. Margin value = Emission Level Limit value
- 5. " * ": Fundamental frequency.



CHANNEL	TX Channel 72	DETECTOR	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz	FUNCTION	Average (AV)

	ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)			
1	*2474.00	93.1 PK			2.19 H	336	91.37	1.76			
2	*2474.00	44.8 AV			2.19 H	336	43.04	1.76			
3	2483.50	57.3 PK	74.0	-16.7	2.19 H	336	55.46	1.80			
4	2483.50	43.6 AV	54.0	-10.4	2.19 H	336	41.77	1.80			
5	4948.00	55.6 PK	74.0	-18.4	2.37 H	332	47.29	8.30			
6	4948.00	34.4 AV	54.0	-19.6	2.37 H	332	26.11	8.30			
7	7422.00	58.7 PK	74.0	-15.3	2.53 H	271	42.75	15.98			
8	7422.00	42.0 AV	54.0	-12.0	2.53 H	271	25.98	15.98			
		ANTENNA	A POLARITY	/ & TEST DI	STANCE: V	ERTICAL A	T 3 M				
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)			
1	*2474.00	92.9 PK			2.20 V	0	91.14	1.76			
2	*2474.00	44.2 AV			2.20 V	0	42.45	1.76			
3	2483.50	55.5 PK	74.0	-18.5	2.20 V	0	53.72	1.80			
4	2483.50	42.0 AV	54.0	-12.0	2.20 V	0	40.16	1.80			
5	4948.00	55.2 PK	74.0	-18.8	2.00 V	208	46.93	8.30			
6	4948.00	34.3 AV	54.0	-19.7	2.00 V	208	26.02	8.30			
7	7422.00	58.6 PK	74.0	-15.4	2.60 V	279	42.63	15.98			
8	7422.00	41.8 AV	54.0	-12.2	2.60 V	279	25.81	15.98			

- 1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
- 2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) Pre-Amplifier Factor(dB)
- 3. The other emission levels were very low against the limit.
- 4. Margin value = Emission Level Limit value
- 5. " * ": Fundamental frequency.



BELOW 1GHz WORST-CASE DATA

CHANNEL	TX Channel 72	DETECTOR	Ougai Book (OD)
FREQUENCY RANGE	30MHz ~ 1GHz	FUNCTION	Quasi-Peak (QP)

	ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)	
1	33.49	29.8 QP	40.0	-10.3	4.00 H	90	39.90	-10.15	
2	216.43	28.6 QP	46.0	-17.4	4.00 H	360	39.46	-10.86	
3	512.24	32.2 QP	46.0	-13.8	2.08 H	150	34.71	-2.54	
4	588.04	35.5 QP	46.0	-10.5	1.82 H	122	36.35	-0.84	
5	643.04	34.9 QP	46.0	-11.1	1.44 H	353	34.86	0.01	
6	951.11	34.4 QP	46.0	-11.6	1.00 H	160	28.89	5.50	
		ANTENNA	A POLARITY	/ & TEST DI	STANCE: V	ERTICAL A	T 3 M		
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)	
1	32.76	31.1 QP	40.0	-8.9	1.12 V	335	41.48	-10.34	
2	85.78	25.5 QP	40.0	-14.5	1.53 V	243	39.54	-14.08	
3	583.92	32.3 QP	46.0	-13.7	2.20 V	118	33.39	-1.06	
4	639.40	36.5 QP	46.0	-9.5	2.37 V	121	36.46	0.03	
5	913.43	34.7 QP	46.0	-11.4	2.18 V	264	30.06	4.59	
6	985.64	34.5 QP	54.0	-19.5	2.04 V	82	28.78	5.74	

- 1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
- 2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) Pre-Amplifier Factor(dB)
- 3. The other emission levels were very low against the limit.
- 4. Margin value = Emission Level Limit value



4.2 Conducted Emission Measurement

4.2.1 Limits of Conducted Emission Measurement

Fraguenov (MHz)	Conducted Limit (dBuV)				
Frequency (MHz)	Quasi-peak	Average			
0.15 - 0.5	66 - 56	56 - 46			
0.50 - 5.0	56	46			
5.0 - 30.0	60	50			

Note: 1. The lower limit shall apply at the transition frequencies.

2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

4.2.2 Test Instruments

Description & Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Due
ROHDE & SCHWARZ TEST RECEIVER	ESCS 30	100276	Apr. 01, 2015	Mar. 31, 2016
ROHDE & SCHWARZ				
Artificial Mains Network	ENV216	101197	Apr. 27, 2015	Apr. 26, 2016
(for EUT)				
LISN With Adapter	AD10	C10Ada-002	Apr. 27, 2015	Apr. 26, 2016
(for EUT)	7,010	010/1dd 002	7101. 27, 2010	7101: 20, 2010
ROHDE & SCHWARZ				
Artificial Mains Network	ESH3-Z5	100218	Nov. 25, 2015	Nov. 24, 2016
(for peripherals)				
SCHWARZBECK				
Artificial Mains Network (For	NNLK8129	8129229	May 06, 2015	May 05, 2016
EUT)				
Software	Cond_V7.3.7	NA	NA	NA
RF cable (JYEBAO) With 10dB PAD	5D-FB	Cable-C10.01	Feb. 15, 2016	Feb. 14, 2017
SUHNER Terminator				
(For ROHDE & SCHWARZ	65BNC-5001	E1-011484	May 19, 2015	May 18, 2016
LISN)				
ROHDE & SCHWARZ				
Artificial Mains Network (For	ESH3-Z5	100220	Nov. 13, 2015	Nov. 12, 2016
TV EUT)				
LISN With Adapter	100220	N/A	Nov. 13, 2015	Nov. 12, 2016
(for TV EUT)	100220	IN/A	1407. 13, 2013	1407. 12, 2016

Notes: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

- 2. The test was performed in Shielded Room No. 10.
- 3. The VCCI Site Registration No. C-1852.



4.2.3 Test Procedures


- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit 20dB) was not recorded.

NOTE: The resolution bandwidth and video bandwidth of test receiver is 9kHz for quasi-peak detection (QP) and average detection (AV) at frequency 0.15MHz-30MHz.

4.2.4 Deviation From Test Standard

No deviation.

4.2.5 Test Setup



Note: 1.Support units were connected to second LISN.

2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.2.6 EUT Operating Condition

Same as item 4.1.6.




4.2.7 Test Results

Fraguency Banga	150kHz ~ 30MHz	Detector Function &	Quasi-Peak (QP) /
Frequency Range	150KHZ ~ SUMHZ	Resolution Bandwidth	Average (AV), 9kHz

	Phase Of Power : Line (L)											
	Frequency	Correction		Reading Value		n Level			Margin			
No		Factor		uV)	•	uV)		uV)		B)		
	(MHz)	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.		
1	0.15002	9.66	41.02	17.69	50.68	27.35	66.00	56.00	-15.32	-28.65		
2	0.19687	9.65	47.01	34.34	56.66	43.99	63.74	53.74	-7.08	-9.75		
3	0.20859	9.65	43.06	25.01	52.71	34.66	63.26	53.26	-10.55	-18.60		
4	0.25938	9.66	40.20	25.76	49.86	35.42	61.45	51.45	-11.59	-16.03		
5	0.27500	9.66	38.28	21.19	47.94	30.85	60.97	50.97	-13.02	-20.11		
6	0.31016	9.67	33.03	13.31	42.70	22.98	59.97	49.97	-17.27	-26.99		
7	0.32969	9.67	34.82	20.13	44.49	29.80	59.46	49.46	-14.97	-19.66		
8	0.38438	9.68	31.25	25.87	40.93	35.55	58.18	48.18	-17.26	-12.64		
9	6.58984	10.05	29.32	18.11	39.37	28.16	60.00	50.00	-20.63	-21.84		

Remarks:

- 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
- 2. The emission levels of other frequencies were very low against the limit.
- 3. Margin value = Emission level Limit value
- 4. Correction factor = Insertion loss + Cable loss
- 5. Emission Level = Correction Factor + Reading Value






Eroguanov Banga	150kHz ~ 30MHz	Detector Function &	Quasi-Peak (QP) /
Frequency Range	150KH2 ~ 50WH2	Resolution Bandwidth	Average (AV), 9kHz

	Phase Of Power : Neutral (N)											
No	Frequency	Correction Factor		g Value uV)		on Level suV)		nit uV)		gin B)		
	(MHz)	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.		
1	0.15391	9.69	38.55	14.26	48.24	23.95	65.79	55.79	-17.55	-31.84		
2	0.18516	9.69	45.20	25.86	54.89	35.55	64.25	54.25	-9.36	-18.70		
3	0.19297	9.69	46.21	33.37	55.90	43.06	63.91	53.91	-8.01	-10.85		
4	0.25156	9.70	40.00	23.91	49.70	33.61	61.71	51.71	-12.01	-18.10		
5	0.31406	9.71	36.10	19.36	45.81	29.07	59.86	49.86	-14.06	-20.80		
6	0.34531	9.71	31.69	15.40	41.40	25.11	59.07	49.07	-17.67	-23.96		
7	6.41016	10.15	26.86	15.78	37.01	25.93	60.00	50.00	-22.99	-24.07		

Remarks:

- 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
- 2. The emission levels of other frequencies were very low against the limit.
- 3. Margin value = Emission level Limit value
- 4. Correction factor = Insertion loss + Cable loss
- 5. Emission Level = Correction Factor + Reading Value






4.3 Number of Hopping Frequency Used

4.3.1 Limits of Hopping Frequency Used Measurement

At least 15 channels frequencies, and should be equally spaced.

4.3.2 Test Setup



4.3.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.3.4 Test Procedure

- a. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
- b. Turn on the EUT and connect its antenna terminal to measurement via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.
- c. Set the SA on MaxHold Mode, and then keep the EUT in hopping mode. Record all the signals from each channel until each one has been recorded.
- d. Set the SA on View mode and then plot the result on SA screen.
- e. Repeat above procedures until all frequencies measured were complete.


4.3.5 Deviation from Test Standard


No deviation.



4.3.6 Test Results

There are 18 hopping frequencies in the hopping mode. Please refer to next page for the test result. On








4.4 Dwell Time on Each Channel

4.4.1 Limits of Dwell Time on Each Channel Measurement

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

4.4.2 Test Setup



4.4.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.4.4 Test Procedures

- a. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
- b. Turn on the EUT and connect its antenna terminal to measurement via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.
- c. Adjust the center frequency of SA on any frequency be measured and set SA to zero span mode. And then, set RBW and VBW of spectrum analyzer to proper value.
- d. Measure the time duration of one transmission on the measured frequency. And then plot the result with time difference of this time duration.
- e. Repeat above procedures until all different time-slot modes have been completed.

4.4.5 Deviation from Test Standard


No deviation.



4.4.6 Test Results

Number of transmission in a 7.2 (18Hopping*0.4)	Length of transmission time (msec)	Result (msec)	Limit (msec)	
36 (times / 5 sec) * 1.44 = 51.84 times	0.662	34.318	400	

NOTE: Test plots of the transmitting time slot are shown on as below.






4.5 Channel Bandwidth

4.5.1 Limits of Channel Bandwidth Measurement

For frequency hopping system operating in the 2400-2483.5MHz, If the 20dB bandwidth of hopping channel is greater than 25kHz, two-thirds 20dBbandwidth of hopping channel shell be a minimum limit for the hopping channel separation.

4.5.2 Test Setup



4.5.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.5.4 Test Procedure

- a. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- b. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
- c. Measure the frequency difference of two frequencies that were attenuated 20dB from the reference level. Record the frequency difference as the emission bandwidth.
- d. Repeat above procedures until all frequencies measured were complete.

4.5.5 Deviation from Test Standard

No deviation.


4.5.6 EUT Operating Condition

The software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel frequencies individually.



4.5.7 Test Results

Channel	Frequency (MHz)	20dB Bandwidth (MHz)
4	2406	4.35
36	2438	4.34
72	2474	4.26





4.6 Hopping Channel Separation

4.6.1 Limits of Hopping Channel Separation Measurement

At least 25kHz or two-third of 20dB hopping channel bandwidth (whichever is greater).

4.6.2 Test Setup



4.6.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.6.4 Test Procedure

Measurement Procedure REF


- a. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- b. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range.
- c. By using the MaxHold function record the separation of two adjacent channels.
- d. Measure the frequency difference of these two adjacent channels by SA MARK function. And then plot the result on SA screen.
- e. Repeat above procedures until all frequencies measured were complete.
- 4.6.5 Deviation From Test Standard No deviation.



4.6.6 Test Results

Channel	Frequency (MHz)	Adjacent Channel Separation (MHz)	20dB Bandwidth (MHz)	Minimum Limit (MHz)	Pass / Fail
4	2406	4.05	4.35	2.90	Pass
36	2438	4.05	4.34	2.89	Pass
72	2474	4.02	4.26	2.84	Pass

NOTE: The minimum limit is two-third 20dB bandwidth.






4.7 Maximum Output Power

4.7.1 Limits of Maximum Output Power Measurement

The Maximum Output Power Measurement is 125mW.

4.7.2 Test Setup



4.7.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.7.4 Test Procedure

A peak / average power sensor was used on the output port of the EUT. A power meter was used to read the response of the peak / average power sensor. Record the peak power level.

4.7.5 Deviation from Test Standard

No deviation.

4.7.6 EUT Operating Condition

The software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel frequencies individually.



4.7.7 Test Results

Channel	Frequency (MHZ)	Output Power (mW)	Output Power (dBm)	Power Limit (mW)	Pass / Fail
4	2406	6.067	7.83	125	Pass
36	2438	6.934	8.41	125	Pass
72	2474	7.870	8.96	125	Pass



4.8 Conducted Out of Band Emission Measurement

4.8.1 Limits Of Conducted Out Of Band Emission Measurement

Below –20dB of the highest emission level of operating band (in 100kHz RBW).

4.8.2 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.8.3 Test Procedure

The transmitter output was connected to the spectrum analyzer via a low lose cable. Set both RBW and VBW of spectrum analyzer to 100 kHz and 300 kHz with suitable frequency span including 100 MHz bandwidth from band edge. The band edges was measured and recorded.

4.8.4 Deviation From Test Standard

No deviation.


4.8.5 Eut Operating Condition

The software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel frequencies individually.

4.8.6 Test Results

The spectrum plots are attached on the following images. D1 line indicates the highest level, D2 line indicates the 20dB offset below D1. It shows compliance with the requirement.







5 Pictures of Test Arrangements					
Please refer to the attached file (Test Setup Photo).					



Appendix – Information on the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Linko EMC/RF Lab

Hsin Chu EMC/RF/Telecom Lab

Tel: 886-2-26052180 Fax: 886-2-26051924 Tel: 886-3-6668565 Fax: 886-3-6668323

Hwa Ya EMC/RF/Safety

Tel: 886-3-3183232 Fax: 886-3-3270892

Email: service.adt@tw.bureauveritas.com
Web Site: www.bureauveritas-adt.com

The address and road map of all our labs can be found in our web site also.

--- END ---