RF Exposure Evaluation for FCC ID: 2AEGJBTE01

Refer user manual this device is a Boothearphone and this device was designed used in portable

devices the minimum distance between human's body is 5mm. Based on the 47CFR 2.1093, this

device belongs to portable device. The definition of the category as following:

Portable Derives:

CFR Title 47 § 2.1093(b)

(b) For purposes of this section, a portable device is defined as a transmitting device designed

to be used so that the radiating structure(s) of the device is/are within 20 centimeters of the

body of the user.

FCC KDB 447498 D01 General RF Exposure Guidance v05r02 Limit

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by

measurement or numerical simulation, is not required when the corresponding SAR Test

Exclusion Threshold condition, listed below, is satisfied. These test exclusion conditions are

based on source-based time-averaged maximum conducted output power of the RF channel

requiring evaluation, adjusted for tune-up tolerance, and the minimum test separation distance

required for the exposure conditions. The minimum test separation distance is determined by the

smallest distance from the antenna and radiating structures or outer surface of the device,

according to the host form factor, exposure conditions and platform requirements, to any part of

the body or extremity of a user or bystander.

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances

≤ 50 mm are determined by:

[] \cdot [] \leq 3.0 for 1-g SAR and \leq 7.5 for 10-g extremity SAR

• f (GHz) is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation.

• The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is \leq 50 mm

and

for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation

distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

FCC exclusion condition= $[] \cdot [] = 0.178 < 3.0$

RF Exposure Evaluation Result: Pass

Note: More power data, Please refer to the RF report.