

# Zhuhai Pantum Electronics Co., Ltd.

# TEST REPORT

## SCOPE OF WORK

FCC Testing – M6550NW Plus, M6551NW Plus, M6552NW Plus, M6553NW Plus,  
M6554NW Plus, M6555NW Plus, M6556NW Plus, M6557NW Plus,  
M6558NW Plus, M6559NW Plus, M6500NW Plus, M6501NW Plus,  
M6502NW Plus, M6503NW Plus, M6504NW Plus, M6505NW Plus,  
M6506NW Plus, M6507NW Plus, M6508NW Plus, M6509NW Plus,  
M6510NW Plus

## REPORT NUMBER

221009018SZN-001

## ISSUE DATE

07 March 2023

## [REVISED DATE]

[-----]

## PAGES

26

## DOCUMENT CONTROL NUMBER

FCC ID 247\_b

© 2017 INTERTEK





Total Quality. Assured.

TEST REPORT

101, 201, Building B, No. 308 Wuhe Avenue, Zhangkengjing Community, GuanHu Subdistrict, LongHua District, Shenzhen, P.R. China.

Tel: (86 755) 8601 6288

Fax: (86 755) 8601 6751

[www.intertek.com](http://www.intertek.com)

Intertek Report No.: 221009018SZN-001

**Zhuhai Pantum Electronics Co., Ltd.**

Application  
For  
Certification

**FCC ID: 2AEGO2013MB15**

**Monochrome Laser Multifunction Printer**

**Model: M6550NW Plus, M6551NW Plus, M6552NW Plus, M6553NW Plus, M6554NW Plus,  
M6555NW Plus, M6556NW Plus, M6557NW Plus, M6558NW Plus, M6559NW Plus, M6500NW  
Plus, M6501NW Plus, M6502NW Plus, M6503NW Plus, M6504NW Plus, M6505NW Plus,  
M6506NW Plus, M6507NW Plus, M6508NW Plus, M6509NW Plus, M6510NW Plus**

**2.4GHz Wi-Fi Transceiver**

Report No.: 221009018SZN-001

We hereby certify that the sample of the above item is considered to comply with the requirements  
of FCC Part 15, Subpart C for Intentional Radiator,  
mention 47 CFR [10-1-21]

**Prepared and Checked by:**

---

**Jeff Liang**  
**Project Engineer**

**Approved by:**

---

**Peter Kang**  
**Senior Technical Supervisor**  
**Date: 07 March 2023**

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

**Intertek Testing Services Shenzhen Ltd. Longhua Branch**

101, 201, Building B, No. 308 Wuhe Avenue, Zhangkengjing Community, GuanHu Subdistrict, LongHua District, Shenzhen, P.R. China.  
Tel: (86 755) 8601 6288 Fax: (86 755) 8601 6751

**MEASUREMENT/TECHNICAL REPORT**

This report concerns (check one) Original Grant  X Class II Change \_\_\_\_\_

Equipment Type: DTS - Part 15 Digital Transmission Systems (Wi-Fi transmitter portion)

Deferred grant requested per 47 CFR 0.457(d)(1)(ii)? Yes \_\_\_\_\_ No  X \_\_\_\_\_

If yes, defer until: \_\_\_\_\_  
date

Company Name agrees to notify the Commission by: \_\_\_\_\_  
date

of the intended date of announcement of the product so that the grant can be issued on that date.

Transition Rules Request per 15.37? Yes \_\_\_\_\_ No  X \_\_\_\_\_

If no, assumed Part 15, Subpart C for intentional radiator - the new 47 CFR [10-01-21] Edition] provision.

Report prepared by:

**Jeff Liang**

**Intertek Testing Services Shenzhen Ltd. Longhua Branch**

101, 201, Building B, No. 308 Wuhe Avenue, Zhangkengjing Community,  
GuanHu Subdistrict, LongHua District, Shenzhen, P.R. China.

Tel: (86 755) 8601 6288 Fax: (86 755) 8601 6661

## Table of Contents

<b>1.0</b>	<b>Summary of Test results</b>	<b>4</b>
<b>2.0</b>	<b><u>General Description</u></b>	<b>5</b>
2.1	Product Description .....	5
2.2	Related Submittal(s) Grants .....	5
2.3	Test Methodology.....	5
2.4	Test Facility .....	5
<b>3.0</b>	<b><u>System Test Configuration</u></b>	<b>6</b>
3.1	Justification.....	6
3.2	EUT Exercising Software.....	6
3.3	Special Accessories .....	6
3.4	Measurement Uncertainty.....	7
3.5	Equipment Modification .....	7
3.6	Support Equipment List and Description.....	7
<b>4.0</b>	<b><u>Measurement Results</u></b>	<b>8</b>
4.1	Maximum Conducted Output Power at Antenna Terminals .....	8
4.2	Minimum 6 dB RF Bandwidth.....	10
4.3	Maximum Power Density Reading.....	10
4.4	Out of Band Conducted Emissions.....	10
4.5	Out of Band Radiated Emissions.....	11
4.6	Transmitter Radiated Emissions in Restricted Bands.....	11
4.7	Field Strength Calculation .....	12
4.8	Radiated Spurious Emission .....	13
4.9	Conducted Emission.....	21
4.10	Radiated Emissions from Digital Section of Transceiver.....	24
4.11	Transmitter Duty Cycle Calculation and Measurements .....	24
<b>5.0</b>	<b><u>Equipment Photographs</u></b>	<b>25</b>
<b>6.0</b>	<b><u>Product Labelling</u></b>	<b>25</b>
<b>7.0</b>	<b><u>Technical Specifications</u></b>	<b>25</b>
<b>8.0</b>	<b><u>Instruction Manual</u></b>	<b>25</b>
<b>9.0</b>	<b><u>Confidentiality Request</u></b>	<b>25</b>
<b>10.0</b>	<b><u>Discussion of Pulse Desensitization</u></b>	<b>25</b>
<b>11.0</b>	<b><u>Test Equipment List</u></b>	<b>26</b>

**1.0 Summary of Test results**

Applicant: Zhuhai Pantum Electronics Co., Ltd.

Applicant Address: Building 02, 06 and 08, No. 888 Shengping Avenue, Pingsha Town, Zhuhai City, Guangdong, China

Manufacturer: Zhuhai Pantum Electronics Co., Ltd.

Manufacturer Address: Building 02, 06 and 08, No. 888 Shengping Avenue, Pingsha Town, Zhuhai City, Guangdong, China

Model: M6550NW Plus, M6551NW Plus, M6552NW Plus, M6553NW Plus, M6554NW Plus, M6555NW Plus, M6556NW Plus, M6557NW Plus, M6558NW Plus, M6559NW Plus, M6500NW Plus, M6501NW Plus, M6502NW Plus, M6503NW Plus, M6504NW Plus, M6505NW Plus, M6506NW Plus, M6507NW Plus, M6508NW Plus, M6509NW Plus, M6510NW Plus

FCC ID: 2AEGO2013MB15

TEST ITEM	REFERENCE	RESULTS
Max. Output power	15.247(b)(3)	Pass
6 dB Bandwidth	15.247(a)(2)	Pass
Max. Power Density	15.247(e)	Pass
Out of Band Antenna Conducted Emission	15.247(d)	Pass
Radiated Emission in Restricted Bands	15.247(d), 15.209, 15.205	Pass
AC Conducted Emission	15.207	Pass
Antenna Requirement	15.203	Pass (See Notes)

Notes: The EUT uses an Integral Antenna which in accordance to Section 15.203 is considered sufficient to comply with the provisions of this section.

## 2.0 General Description

### 2.1 Product Description

The Equipment Under Test (EUT) is a Monochrome Laser Printer with 2.4G Wi-Fi function operating at 2412-2462MHz for 802.11b/g/n HT20 and 2422-2452MHz for 802.11n HT40, Bluetooth function operating at 2402-2480MHz. The EUT is powered by AC120V/60Hz. For more detailed features description, please refer to the user's manual.

Type of Modulation: BPSK, QPSK, 16QAM, 64QAM for OFDM; CCK, DQPSK, DBPSK for DSSS.

Antenna Type: Integral Antenna

Antenna Gain: 3.55dBi

Their electrical circuit design, layout, components used and internal wiring are identical. Only the below are different. Test with the M6550NW Plus model which has all the functions.

Model	Communication ports	Color
M6500NW Plus, M6501NW Plus, M6502NW Plus, M6503NW Plus, M6504NW Plus, M6505NW Plus, M6506NW Plus, M6507NW Plus, M6508NW Plus, M6509NW Plus, M6510NW Plus	USB, NET, Wi-Fi, Bluetooth	various
M6550NW Plus, M6551NW Plus, M6552NW Plus, M6553NW Plus, M6554NW Plus, M6555NW Plus, M6556NW Plus, M6557NW Plus, M6558NW Plus, M6559NW Plus	USB, NET, ADF, Wi-Fi, Bluetooth	

For electronic filing, the brief circuit description is saved with filename: descri.pdf.

### 2.2 Related Submittal(s) Grants

This is an application for certification of:

This is an application for certification of a transceiver for the Monochrome Laser Multifunction Printer which has 2.4GHz Wi-Fi function.

For the Bluetooth function was tested and demonstrated in report 221009018SZN-002.

For the other function was tested and demonstrated in FCC SDoC report 221009017SZN-001.

### 2.3 Test Methodology

Both AC mains line-conducted and radiated emission measurements were performed according to the procedures in ANSI C63.10 (2013) and KDB 558074 D01 v05r02. Radiated emission measurement was performed in semi-anechoic chamber and conducted emission measurement was performed in shield room. For radiated emission measurement, preliminary scans were performed in the semi-anechoic chamber only to determine the worst case modes. All radiated tests were performed at an antenna to EUT distance of 3 meters, unless stated otherwise in the "**Justification Section**" of this Application.

### 2.4 Test Facility

The Semi-anechoic chamber and shielded room used to collect the radiated data and conducted data are **Intertek Testing Services Shenzhen Ltd. Longhua Branch** and located at 101, 201, Building B, No. 308 Wuhe Avenue, Zhangkengjing Community, GuanHu Subdistrict, LongHua District, Shenzhen, P.R. China. This test facility and site measurement data have been fully placed on file with File Number: CN1188.

### **3.0 System Test Configuration**

#### **3.1 Justification**

For emissions testing, the equipment under test (EUT) setup to transmit continuously to simplify the measurement methodology. Care was taken to ensure proper power supply voltages during testing. During testing, all cables were manipulated to produce worst case emissions. The EUT was powered by AC120V/60Hz during the test.

On 802.11b/g/n-HT20/n-HT40 mode, one antenna are used, and all data rate were tested and only the worst case data is shown in the report.

For maximizing emissions, the EUT was rotated through 360°, the EUT was placed on the styrene turntable with 0.8m. The antenna height and polarization are varied during the search for maximum signal level. The antenna height is varied from 1 to 4 meters. Radiated emissions are taken at three meters unless the signal level is too low for measurement at that distance. If necessary, a pre-amplifier is used and/or the test is conducted at a closer distance.

All readings are extrapolated back to the equivalent three meter reading using inverse scaling with distance. Analyzer resolution is 100 kHz or greater for frequencies below 1000 MHz. The resolution is 1 MHz or greater for frequencies above 1000 MHz. The spurious emissions more than 20 dB below the permissible value are not reported.

The EUT and transmitting antenna was centered on the turntable.

Radiated emission measurement were performed the lowest radio frequency signal generated in the device which is greater than 9 kHz to the tenth harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower.

#### **3.2 EUT Exercising Software**

The EUT exercise program (provided by client) used during radiated and conducted testing was designed to exercise the various system components in a manner similar to a typical use. The worst case configuration is used in all specified testing.

The parameters of test software setting:

During the test, Channel and power controlling software provided by the applicant was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the application and is going to be fixed on the firmware of the end product.

Test software: Tera Term, Version: 4.73

#### **3.3 Special Accessories**

N/A.

### 3.4 Measurement Uncertainty

When determining of the test conclusion, the Measurement Uncertainty of test has been considered.

### 3.5 Equipment Modification

Any modifications installed previous to testing by Zhuhai Pantum Electronics Co., Ltd. will be incorporated in each production model sold / leased in the United States.

No modifications were installed by Intertek Testing Services Shenzhen Ltd. Longhua Branch.

### 3.6 Support Equipment List and Description

Description	Manufacturer	Model No.
Portable computer (Provided by Intertek)	DELL	Latitude 3480
RJ45 Cable (Provided by Intertek)	/	Unshielded, 200cm
AC Cable	Zhuhai Pantum Electronics Co., Ltd.	Unshielded, 150cm
USB Cable	Zhuhai Pantum Electronics Co., Ltd.	Shielded, 150cm

Applicant: Zhuhai Pantum Electronics Co., Ltd.

Date of Test: 22 February 2023

Model: M6550NW Plus

**4.0 Measurement Results****4.1 Maximum Conducted Output Power at Antenna Terminals, FCC Rules 15.247(b)(3):**

The antenna power of the EUT was connected to the input of a broadband peak RF power meter. The power meter has a video bandwidth that is greater than DTS bandwidth and utilize a fast-responding diode detector. Power was read directly at the EUT antenna terminals with cable loss added.

For antennas with gains of 6 dBi or less, maximum allowed Transmitter output is 1 watt (+30 dBm).

IEEE 802.11b (CCK, 1Mbps)		
Frequency (MHz)	Output in dBm (Peak Reading)	Output (mWatt)
Low Channel: 2412	16.05	40.27
Middle Channel: 2437	15.53	35.73
High Channel: 2462	15.87	38.64

IEEE 802.11g (16QAM, 6Mbps)		
Frequency (MHz)	Output in dBm (Peak Reading)	Output (mWatt)
Low Channel: 2412	18.83	76.38
Middle Channel: 2437	18.19	65.92
High Channel: 2462	19.08	80.91

IEEE 802.11n-HT20 (64QAM, 6.5Mbps)		
Frequency (MHz)	Output in dBm (Peak Reading)	Output (mWatt)
Low Channel: 2412	17.69	58.75
Middle Channel: 2437	18.37	68.71
High Channel: 2462	18.58	72.11

IEEE 802.11n-HT40 (64QAM, 13.5Mbps)		
Frequency (MHz)	Output in dBm (Peak Reading)	Output (mWatt)
Low Channel: 2422	16.46	44.26
Middle Channel: 2437	16.82	48.08
High Channel: 2452	17.11	51.40



Total Quality. Assured.

TEST REPORT

Intertek Report No.: 221009018SZN-001

Cable loss: 1.0 dB    External Attenuation: 0 dB

Cable loss, external attenuation has been included in OFFSET function

EUT max. output level = 19.08dBm

EUT max. E.I.R.P = 19.08dBm + 3.55dBi = 22.63dBm = 183.23mW

For RF Exposure, the information is saved with filename: RF exposure.pdf.

Applicant: Zhuhai Pantum Electronics Co., Ltd.

Date of Test: 22 February 2023

Model: M6550NW Plus

#### 4.2 Minimum 6 dB RF Bandwidth, FCC Rule 15.247(a) (2):

The antenna port of the EUT was connected to the input of a spectrum analyzer. Analyzer RES BW was set to 100 KHz according to FCC KDB 558074 D01 v05r02. For each RF output channel investigated, the spectrum analyzer center frequency was set to the channel carrier. A PEAK output reading was taken, a DISPLAY line was drawn 6 dB lower than PEAK level. The 6dB bandwidth was determined from where the channel output spectrum intersected the display line.

Limit: The 6 dB Bandwidth is at least 500 kHz.

Test Result: Please refer to Appendix A of “221009018SZN-001\_Appendix”

#### 4.3 Maximum Power Density Reading, FCC Rule 15.247(e):

The Measurement Procedure PKPSD was set according to the FCC KDB 558074 D01 v05r02.

Antenna output of the EUT was coupled directly to spectrum analyzer; if an external attenuator and/or cable was used, these losses are compensated for with the analyzer OFFSET function.

Limit: The Power Density does not exceed 8dBm/3 kHz.

Test Result: Please refer to Appendix B of “221009018SZN-001\_Appendix”

#### 4.4 Out of Band Conducted Emissions, FCC Rule 15.247(d)

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. The Measurement Procedure was set according to the FCC KDB 558074 D01 v05r02.

All other types of emissions from the EUT shall meet the general limits for radiated frequencies outside the passband.

Refer to the attached test plots for out of band conducted emissions data with rate of 1Mbps for 802.11b and 6Mbps for 802.11g and 6.5Mbps for 802.11n-HT20 and 13.5Mbps for 802.11n-HT40.

The test plots showed all spurious emission up to the tenth harmonic were measured and they were found to be at least 20 dB below the highest level of the desired power in the passband.

Test Result: Please refer to Appendix C of “221009018SZN-001\_Appendix”

4.5 Out of Band Radiated Emissions (for emissions in 4.4 above that are less than 20dB below carrier), FCC Rule 15.247(d):

For out of band emissions that are close to or that exceed the 20dB attenuation requirement described in the specification, radiated measurements were performed at a 3m separation distance to determine whether these emissions complied with the general radiated emission requirement.

- Not required, since all emissions are more than 20dB below fundamental
- See attached data sheet

4.6 Transmitter Radiated Emissions in Restricted Bands, FCC Rule 15.35(b) (c):

Data is included of the worst case configuration (the configuration which resulted in the highest emission levels). A sample calculation, configuration photographs and data tables of the emissions are included. All measurements were performed with peak detection unless otherwise specified.

The data on the following pages list the significant emission frequencies, the limit and the margin of compliance.

Test Result: Please refer to Appendix D of “221009018SZN-001\_Appendix”

Applicant: Zhuhai Pantum Electronics Co., Ltd.

Date of Test: 22 February 2023

Model: M6550NW Plus

## 4.7 Field Strength Calculation

The field strength is calculated by adding the reading on the Spectrum Analyzer to the factors associated with preamplifiers (if any), antennas, cables, pulse desensitization and average factors (when specified limit is in average and measurements are made with peak detectors). A sample calculation is included below.

$$FS = RA + AF + CF - AG + PD$$

Where  $FS$  = Field Strength in  $\text{dB}\mu\text{V}/\text{m}$

$RA$  = Receiver Amplitude (including preamplifier) in  $\text{dB}\mu\text{V}$

$CF$  = Cable Attenuation Factor in dB

$AF$  = Antenna Factor in dB

$AG$  = Amplifier Gain in dB

$PD$  = Pulse Desensitization in dB

In the radiated emission table which follows, the reading shown on the data table may reflect the preamplifier gain. An example of the calculations, where the reading does not reflect the preamplifier gain, follows:

$$FS = RA + AF + CF - AG + PD$$

### Example

Assume a receiver reading of 62.0  $\text{dB}\mu\text{V}$  is obtained. The antenna factor of 7.4 dB and cable factor of 1.6 dB is added. The amplifier gain of 29 dB is subtracted. The pulse desensitization factor of the spectrum analyzer was 0 dB. The net field strength for comparison to the appropriate emission limit is 42  $\text{dB}\mu\text{V}/\text{m}$ . This value in  $\text{dB}\mu\text{V}/\text{m}$  was converted to its corresponding level in  $\mu\text{V}/\text{m}$ .

$$RA = 62.0 \text{ dB}\mu\text{V}$$

$$AF = 7.4 \text{ dB}$$

$$CF = 1.6 \text{ dB}$$

$$AG = 29.0 \text{ dB}$$

$$PD = 0 \text{ dB}$$

$$FS = 62 + 7.4 + 1.6 - 29 + 0 = 42 \text{ dB}\mu\text{V}/\text{m}$$

$$\text{Level in mV/m} = \text{Common Antilogarithm} [(42 \text{ dB}\mu\text{V}/\text{m})/20] = 125.9 \mu\text{V}/\text{m}$$

Applicant: Zhuhai Pantum Electronics Co., Ltd.

Date of Test: 22 February 2023

Model: M6550NW Plus

## 4.8 Radiated Spurious Emission

Worst Case Radiated Spurious Emission  
at 2390.000MHz  
is passed by 1.1dB margin.

For the electronic filing, the worst case radiated emission configuration photographs are saved with filename: radiated photos.pdf.

Applicant: Zhuhai Pantum Electronics Co., Ltd.


Date of Test: 22 February 2023

Worst Case Operating Mode:

Model: M6550NW Plus

Simultaneous transmission (Wi-Fi+Bluetooth)

ANT Polarity: Horizontal



Frequency (MHz)	Quasi Peak (dBµV/m)	Meas. Time (ms)	Bandwidth (kHz)	Polarization	Corr. (dB/m)	Margin - QPK (dB)	Limit - QPK (dBµV/m)
224.160000	41.4	1000.0	120.000	H	19.7	4.6	46.0
239.099667	37.5	1000.0	120.000	H	19.9	8.5	46.0
373.412333	41.6	1000.0	120.000	H	23.8	4.4	46.0

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Quasi Peak (dBµV/m) = Corr. (dB/m) + Read Level (dBµV)
3. Margin (dB) = Limit Line (dBµV/m) – Level (dBµV/m)

Applicant: Zhuhai Pantum Electronics Co., Ltd.


Date of Test: 22 February 2023

Worst Case Operating Mode:

Model: M6550NW Plus

Simultaneous transmission (Wi-Fi+Bluetooth)

ANT Polarity: Vertical



Frequency (MHz)	Quasi Peak (dB $\mu$ V/m)	Meas. Time (ms)	Bandwidth (kHz)	Polarization	Corr. (dB/m)	Margin - QPK (dB)	Limit - QPK (dB $\mu$ V/m)
48.120000	31.8	1000.0	120.000	V	13.8	8.2	40.0
376.581000	36.1	1000.0	120.000	V	24.0	9.9	46.0
921.042000	39.8	1000.0	120.000	V	32.0	6.2	46.0

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Quasi Peak (dB $\mu$ V/m) = Corr. (dB/m) + Read Level (dB $\mu$ V)
3. Margin (dB) = Limit Line (dB $\mu$ V/m) – Level (dB $\mu$ V/m)

Applicant: Zhuhai Pantum Electronics Co., Ltd.

Date of Test: 22 February 2023

Model: M6550NW Plus

### Radiated Emissions (above 1GHz)

Worst Case Operating Mode: Transmitting (802.11b-Channel 01)

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-Amp Gain (dB)	Antenna Factor (dB/m)	Net at 3m (dB $\mu$ V/m)	Peak Limit at 3m (dB $\mu$ V/m)	Margin (dB)
Vertical	*4824.000	44.0	30.6	32.7	46.1	74.0	-27.9
Vertical	*7236.000	46.4	31.0	37.2	52.6	74.0	-21.4
Vertical	*2390.000	67.5	31.9	27.4	63.0	74.0	-11.0

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-Amp Gain (dB)	Antenna Factor (dB/m)	Net at 3m (dB $\mu$ V/m)	Average Limit at 3m (dB $\mu$ V/m)	Margin (dB)
Vertical	*4824.000	33.7	30.6	32.7	35.8	54.0	-18.2
Vertical	*7236.000	39.8	31.0	37.2	46.0	54.0	-8.0
Vertical	*2390.000	39.8	31.9	27.4	51.0	54.0	-3.0

Worst Case Operating Mode: Transmitting (802.11b-Channel 06)

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-Amp Gain (dB)	Antenna Factor (dB/m)	Net at 3m (dB $\mu$ V/m)	Peak Limit at 3m (dB $\mu$ V/m)	Margin (dB)
Vertical	*4874.000	43.7	30.6	32.7	45.8	74.0	-28.2
Vertical	*7311.000	50.5	31.0	37.2	56.7	74.0	-17.3

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-Amp Gain (dB)	Antenna Factor (dB/m)	Net at 3m (dB $\mu$ V/m)	Average Limit at 3m (dB $\mu$ V/m)	Margin (dB)
Vertical	*4874.000	33.5	30.6	32.7	35.6	54.0	-18.4
Vertical	*7311.000	40.6	31.0	37.2	46.8	54.0	-7.2

Worst Case Operating Mode: Transmitting (802.11b-Channel 11)

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-Amp Gain (dB)	Antenna Factor (dB/m)	Net at 3m (dB $\mu$ V/m)	Peak Limit at 3m (dB $\mu$ V/m)	Margin (dB)
Vertical	*4924.000	43.8	30.6	32.7	45.9	74.0	-28.1
Vertical	*7386.000	46.3	31.0	37.2	52.5	74.0	-21.5
Vertical	*2483.500	66.2	31.9	27.4	61.7	74.0	-12.3

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-Amp Gain (dB)	Antenna Factor (dB/m)	Net at 3m (dB $\mu$ V/m)	Average Limit at 3m (dB $\mu$ V/m)	Margin (dB)
Vertical	*4924.000	33.6	30.6	32.7	35.7	54.0	-18.3
Vertical	*7386.000	41.7	31.0	37.2	47.9	54.0	-6.1
Vertical	*2483.500	53.8	31.9	27.4	49.3	54.0	-4.7

## Worst Case Operating Mode: Transmitting (802.11g-Channel 01)

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-Amp Gain (dB)	Antenna Factor (dB/m)	Net at 3m (dB $\mu$ V/m)	Peak Limit at 3m (dB $\mu$ V/m)	Margin (dB)
Vertical	*4824.000	43.5	30.4	32.7	45.8	74.0	-28.2
Vertical	*7236.000	44.6	31.0	37.2	50.8	74.0	-23.2
Vertical	*2390.000	71.5	31.9	27.4	67.0	74.0	-7.0

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-Amp Gain (dB)	Antenna Factor (dB/m)	Net at 3m (dB $\mu$ V/m)	Average Limit at 3m (dB $\mu$ V/m)	Margin (dB)
Vertical	*4824.000	33.3	30.4	32.7	35.6	54.0	-18.4
Vertical	*7236.000	35.1	31.0	37.2	41.3	54.0	-12.7
Vertical	*2390.000	55.9	31.9	27.4	51.4	54.0	-2.6

## Worst Case Operating Mode: Transmitting (802.11g-Channel 06)

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-Amp Gain (dB)	Antenna Factor (dB/m)	Net at 3m (dB $\mu$ V/m)	Peak Limit at 3m (dB $\mu$ V/m)	Margin (dB)
Vertical	*4874.000	43.6	30.4	32.7	45.9	74.0	-28.1
Vertical	*7311.000	44.3	31.0	37.2	50.5	74.0	-23.5

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-Amp Gain (dB)	Antenna Factor (dB/m)	Net at 3m (dB $\mu$ V/m)	Average Limit at 3m (dB $\mu$ V/m)	Margin (dB)
Vertical	*4874.000	33.2	30.4	32.7	35.5	54.0	-18.5
Vertical	*7311.000	35.3	31.0	37.2	41.5	54.0	-12.5

## Worst Case Operating Mode: Transmitting (802.11g-Channel 11)

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-Amp Gain (dB)	Antenna Factor (dB/m)	Net at 3m (dB $\mu$ V/m)	Peak Limit at 3m (dB $\mu$ V/m)	Margin (dB)
Vertical	*4924.000	43.3	30.4	32.7	45.6	74.0	-28.4
Vertical	*7386.000	44.5	31.0	37.2	50.7	74.0	-23.3
Vertical	*2483.500	66.3	31.9	27.4	61.8	74.0	-12.2

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-Amp Gain (dB)	Antenna Factor (dB/m)	Net at 3m (dB $\mu$ V/m)	Average Limit at 3m (dB $\mu$ V/m)	Margin (dB)
Vertical	*4924.000	47.7	30.4	32.7	50.0	54.0	-4.0
Vertical	*7386.000	29.5	31.0	37.2	35.7	54.0	-18.3
Vertical	*2483.500	45.9	31.9	27.4	41.4	54.0	-12.6

## Worst Case Operating Mode: Transmitting (802.11n20-Channel 01)

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-Amp Gain (dB)	Antenna Factor (dB/m)	Net at 3m (dB $\mu$ V/m)	Peak Limit at 3m (dB $\mu$ V/m)	Margin (dB)
Vertical	*4824.000	43.2	30.4	32.7	45.5	74.0	-28.5
Vertical	*7236.000	44.1	31.0	37.2	50.3	74.0	-23.7
Vertical	*2390.000	71.8	31.9	27.4	67.3	74.0	-6.7

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-Amp Gain (dB)	Antenna Factor (dB/m)	Net at 3m (dB $\mu$ V/m)	Average Limit at 3m (dB $\mu$ V/m)	Margin (dB)
Vertical	*4824.000	33.5	30.4	32.7	35.8	54.0	-18.2
Vertical	*7236.000	35.3	31.0	37.2	41.5	54.0	-12.5
Vertical	*2390.000	55.8	31.9	27.4	51.3	54.0	-2.7

## Worst Case Operating Mode: Transmitting (802.11n20-Channel 06)

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-Amp Gain (dB)	Antenna Factor (dB/m)	Net at 3m (dB $\mu$ V/m)	Peak Limit at 3m (dB $\mu$ V/m)	Margin (dB)
Vertical	*4874.000	43.0	30.4	32.7	45.3	74.0	-28.7
Vertical	*7311.000	44.2	31.0	37.2	50.4	74.0	-23.6

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-Amp Gain (dB)	Antenna Factor (dB/m)	Net at 3m (dB $\mu$ V/m)	Average Limit at 3m (dB $\mu$ V/m)	Margin (dB)
Vertical	*4874.000	32.9	30.4	32.7	35.2	54.0	-18.8
Vertical	*7311.000	35.1	31.0	37.2	41.3	54.0	-12.7

## Worst Case Operating Mode: Transmitting (802.11n20-Channel 11)

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-Amp Gain (dB)	Antenna Factor (dB/m)	Net at 3m (dB $\mu$ V/m)	Peak Limit at 3m (dB $\mu$ V/m)	Margin (dB)
Vertical	*4924.000	43.4	30.4	32.7	45.7	74.0	-28.3
Vertical	*7386.000	44.2	31.0	37.2	50.4	74.0	-23.6
Vertical	*2483.500	68.2	31.9	27.4	63.7	74.0	-10.3

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-Amp Gain (dB)	Antenna Factor (dB/m)	Net at 3m (dB $\mu$ V/m)	Average Limit at 3m (dB $\mu$ V/m)	Margin (dB)
Vertical	*4924.000	33.2	30.4	32.7	35.5	54.0	-18.5
Vertical	*7386.000	35.2	31.0	37.2	41.4	54.0	-12.6
Vertical	*2483.500	54.6	31.9	27.4	50.1	54.0	-3.9

## Worst Case Operating Mode: Transmitting (802.11n40-Channel 03)

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-Amp Gain (dB)	Antenna Factor (dB/m)	Net at 3m (dB $\mu$ V/m)	Peak Limit at 3m (dB $\mu$ V/m)	Margin (dB)
Vertical	*4844.000	43.6	30.4	32.7	45.9	74.0	-28.1
Vertical	*7266.000	44.5	31.0	37.2	50.7	74.0	-23.3
Vertical	*2390.000	71.7	31.9	27.4	67.2	74.0	-6.8

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-Amp Gain (dB)	Antenna Factor (dB/m)	Net at 3m (dB $\mu$ V/m)	Average Limit at 3m (dB $\mu$ V/m)	Margin (dB)
Vertical	*4844.000	33.5	30.4	32.7	35.8	54.0	-18.2
Vertical	*7266.000	35.4	31.0	37.2	41.6	54.0	-12.4
Vertical	*2390.000	57.4	31.9	27.4	52.9	54.0	-1.1

## Worst Case Operating Mode: Transmitting (802.11n40-Channel 06)

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-Amp Gain (dB)	Antenna Factor (dB/m)	Net at 3m (dB $\mu$ V/m)	Peak Limit at 3m (dB $\mu$ V/m)	Margin (dB)
Vertical	*4874.000	43.5	30.4	32.7	45.8	74.0	-28.2
Vertical	*7311.000	44.5	31.0	37.2	50.7	74.0	-23.3

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-Amp Gain (dB)	Antenna Factor (dB/m)	Net at 3m (dB $\mu$ V/m)	Average Limit at 3m (dB $\mu$ V/m)	Margin (dB)
Vertical	*4874.000	33.6	30.4	32.7	35.9	54.0	-18.1
Vertical	*7311.000	35.3	31.0	37.2	41.5	54.0	-12.5

## Worst Case Operating Mode: Transmitting (802.11n40-Channel 09)

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-Amp Gain (dB)	Antenna Factor (dB/m)	Net at 3m (dB $\mu$ V/m)	Peak Limit at 3m (dB $\mu$ V/m)	Margin (dB)
Vertical	*4904.000	43.3	30.4	32.7	45.6	74.0	-28.4
Vertical	*7356.000	44.6	31.0	37.2	50.8	74.0	-23.2
Vertical	*2483.500	67.4	31.9	27.4	62.9	74.0	-11.1

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-Amp Gain (dB)	Antenna Factor (dB/m)	Net at 3m (dB $\mu$ V/m)	Average Limit at 3m (dB $\mu$ V/m)	Margin (dB)
Vertical	*4904.000	33.5	30.4	32.7	35.8	54.0	-18.2
Vertical	*7356.000	35.5	31.0	37.2	41.7	54.0	-12.3
Vertical	*2483.500	54.6	31.9	27.4	50.1	54.0	-3.9

NOTES:

1. Peak detector is used, RBW=1MHz/VBW=3MHz for peak value and RBW=1MHz / VBW=10Hz for average value.
2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative value in the margin column shows emission below limit.
4. Horn antenna used for the emission over 1000MHz.

\* Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

Applicant: Zhuhai Pantum Electronics Co., Ltd.

Date of Test: 03 November 2022

Model: M6550NW Plus

#### 4.9 Conducted Emission

Worst Case Conducted Emission  
at 0.534000MHz  
is passed by 8.2dB margin.

For the electronic filing, the worst case radiated emission configuration photographs are saved with filename: conducted photos.pdf.


Applicant: Zhuhai Pantum Electronics Co., Ltd.

Date of Test: 03 November 2022

Model: M6550NW Plus

Worst Case Operating Mode: Simultaneous transmission

Phase: Live

**Graphic / Data Table****Conducted Emissions****Pursuant to FCC 15.207: Emissions Requirement****Limit and Margin QP**

Frequency (MHz)	Quasi Peak (dB $\mu$ V)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dB $\mu$ V)
0.266000	42.5	9.000	L1	9.6	18.7	61.2
0.538000	46.6	9.000	L1	9.6	9.4	56.0
0.670000	44.2	9.000	L1	9.6	11.8	56.0
0.938000	41.8	9.000	L1	9.7	14.2	56.0
2.274000	40.2	9.000	L1	9.7	15.8	56.0
9.238000	38.6	9.000	L1	9.9	21.4	60.0

**Limit and Margin AV**

Frequency (MHz)	Average (dB $\mu$ V)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dB $\mu$ V)
0.266000	33.7	9.000	L1	9.6	17.5	51.2
0.538000	35.7	9.000	L1	9.6	10.3	46.0
0.670000	33.2	9.000	L1	9.6	12.8	46.0
0.938000	31.1	9.000	L1	9.7	14.9	46.0
2.274000	28.3	9.000	L1	9.7	17.7	46.0
9.238000	26.2	9.000	L1	9.9	23.8	50.0


Applicant: Zhuhai Pantum Electronics Co., Ltd.

Date of Test: 03 November 2022

Model: M6550NW Plus

Worst Case Operating Mode: Simultaneous transmission

Phase: Neutral

**Graphic / Data Table****Conducted Emissions  
Pursuant to FCC 15.207: Emissions Requirement****Limit and Margin QP**

Frequency (MHz)	Quasi Peak (dB $\mu$ V)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dB $\mu$ V)
0.534000	47.8	9.000	N	9.6	8.2	56.0
0.670000	44.2	9.000	N	9.6	11.8	56.0
0.938000	42.2	9.000	N	9.6	13.8	56.0
1.606000	40.1	9.000	N	9.6	15.9	56.0
2.274000	40.4	9.000	N	9.7	15.6	56.0
9.106000	36.9	9.000	N	9.9	23.1	60.0

**Limit and Margin AV**

Frequency (MHz)	Average (dB $\mu$ V)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dB $\mu$ V)
0.534000	36.8	9.000	N	9.6	9.2	46.0
0.670000	33.2	9.000	N	9.6	12.8	46.0
0.938000	31.4	9.000	N	9.6	14.6	46.0
1.606000	28.3	9.000	N	9.6	17.7	46.0
2.274000	28.5	9.000	N	9.7	17.5	46.0
9.106000	24.7	9.000	N	9.9	25.3	50.0

## 4.10 Radiated Emissions from Digital Section of Transceiver, FCC Ref: 15.109

- Not required - No digital part
- Test results are attached
- Included in the separated report.

## 4.11 Transmitter Duty Cycle Calculation and Measurements, FCC Rule 15.35(b), (c)

The EUT antenna output port was connected to the input of the spectrum analyzer. The analyzer center frequency was set to EUT RF channel carrier. The SWEP function on the analyzer was set to ZERO SPAN. The Transmitter ON time was determined from the resultant time-amplitude display:

	See attached spectrum analyzer chart (s) for Transmitter timing
	See Transmitter timing diagram provided by manufacturer
x	Not applicable, duty cycle was not used.

## 5.0 Equipment Photographs

For electronic filing, the photographs are saved with filename: external photos.pdf & internal photos.pdf.

## 6.0 Product Labeling

For electronic filing, the FCC ID label artwork and location is saved with filename: label.pdf.

## 7.0 Technical Specifications

For electronic filing, the block diagram and circuit diagram are saved with filename: block.pdf and circuit.pdf respectively.

## 8.0 Instruction Manual

For electronic filing, a preliminary copy of the Instruction Manual is saved with filename: manual.pdf.

This manual will be provided to the end-user with each unit sold/leased in the United States.

## 9.0 Confidentiality Request

For electronic filing, the confidentiality request of the tested EUT is saved with filename: request.pdf.

## 10.0 Discussion of Pulse Desensitization

The determination of pulse desensitivity was made in accordance with Hewlett Packard Application Note 150-2, *Spectrum Analysis ... Pulsed RF*.

Pulse desensitivity is not applicable for this device since the transmitter transmits the RF signal continuously.

**11.0 Test Equipment List**

Equipment No.	Equipment	Manufacturer	Model No.	Serial No.	Cal. Date	Due Date
SZ182-02	RF Power Meter	Anritsu	ML2496A	1302005	2022-05-16	2023-05-16
SZ182-02-01	Power Sensor	Anritsu	MA2411B	1207429	2022-05-16	2023-05-16
SZ056-06	Signal Analyzer	R&S	FSV 40	101101	2022-10-19	2023-10-19
SZ062-10	RF Cable	Beda	RG 58	--	2022-10-01	2023-04-01
SZ056-08	Signal Analyzer	R&S	FSV 40	101430	2022-10-19	2023-10-19
SZ185-03	EMI Receiver	R&S	ESR7	101975	2022-10-26	2023-10-26
SZ061-06	Active Loop Antenna	Electro-Metrics	EM-6876	217	2021-05-18	2023-05-18
SZ061-12	BiConiLog Antenna	ETS	3142E	00166158	2021-08-04	2024-08-04
SZ061-09	Double-Ridged Waveguide Horn Antenna	ETS	3115	00092347	2022-10-14	2025-10-14
SZ061-15	Double-Ridged Waveguide Horn Antenna	ETS	3116C-PA	00224718	2021-07-06	2024-07-06
SZ181-08	Microwave System Amplifier	Agilent	83017A	MY57280108	2022-08-05	2023-08-05
SZ188-05	Anechoic Chamber	ETS	FACT 3-2.0	CT001880-Q1391	2021-05-25	2024-05-25
SZ062-23	RF Cable	RADIALL	SF104PE	MY4262/4PE	2022-10-17	2023-10-17
SZ062-35	RF Cable	Rebes	A50-3.5M3.5M-8M	19100879	2022-10-17	2023-10-17
SZ067-04	Notch Filter	Micro-Tronics	BRM50702-02	015	2022-05-17	2023-05-17
SZ185-02	EMI Test Receiver	R&S	ESCI	100692	2022-07-08	2023-07-08
SZ187-01	Two-Line V-Network	R&S	ENV216	100072	2022-10-24	2023-10-24
SZ187-02	Two-Line V-Network	R&S	ENV216	100073	2022-05-09	2023-05-09
SZ188-03	Shielding Room	ETS	RFD-100	4100	2020-01-07	2023-01-07

\*\*\*\*\* End of Report\*\*\*\*\*