

RF Exposure evaluation

Product Description: Smart band

Model Number: IW-20X

FCC ID: 2AEISIW-20X

According to 447498 D01 General RF Exposure Guidance v05 The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances \leq 50 mm are determined by: $[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

$f(\text{GHz})$ is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

According to the follow transmitter output power (P_t) formula :

$$P_t = (E \times d)^2 / (30 \times g_t)$$

P_t =transmitter output power in watts

g_t =numeric gain of the transmitting antenna (unitless)

E =electric field strength in V/m

d =measurement distance in meters (m)

According to the above test data,

$$E_{\text{max}} = 90.55 \text{ dBuV/m} = 0.034 \text{ V/m}$$

$$d = 3 \text{ m}$$

$$g_t = 0.3$$

$$P_t = (E \times d)^2 / (30 \times g_t) = (0.034 \times 3)^2 / (30 \times 0.3) = 0.0012 \text{ W} = 1.2 \text{ mW}$$

The result is rounded to one decimal place for comparison

Worse case is as below: [2402MHz -1.2mW output power]

$$(1.2 \text{ mW} / 5 \text{ mm}) \cdot [\sqrt{2.402(\text{GHz})}] = 0.37 < 3.0 \text{ for 1-g SAR}$$

Then SAR evaluation is not required

NOTE: The transmitter output power formula you can refer to Part15F (K).

For the maximum power, you can refer FCC test report.