

---

# FCC Test Report

---

Report No.: AGC01835160401FE03

**FCC ID** : 2AEISMB10  
**APPLICATION PURPOSE** : Original Equipment  
**PRODUCT DESIGNATION** : MOVEBAND  
**BRAND NAME** : alcatel  
**MODEL NAME** : MB10  
**CLIENT** : Guangdong Spark Technology Co., Ltd.  
**DATE OF ISSUE** : May 06,2016  
**STANDARD(S)** : FCC Part 15 Rules  
**TEST PROCEDURE(S)** :  
**REPORT VERSION** : V1.0

Attestation of Global Compliance (Shenzhen) Co., Ltd



**CAUTION:**

This report shall not be reproduced except in full without the written permission of the test laboratory and shall not be quoted out of context.



### Report Revise Record

Report Version	Revise Time	Issued Date	Valid Version	Notes
V1.0	/	May 06,2016	Valid	Original Report

## TABLE OF CONTENTS

<b>1. VERIFICATION OF CONFORMITY .....</b>	<b>4</b>
<b>2. GENERAL INFORMATION .....</b>	<b>5</b>
2.1. PRODUCT DESCRIPTION.....	5
2.2. TABLE OF CARRIER FREQUENCYS.....	5
<b>3. MEASUREMENT UNCERTAINTY.....</b>	<b>6</b>
<b>4. DESCRIPTION OF TEST MODES.....</b>	<b>6</b>
<b>5. SYSTEM TEST CONFIGURATION .....</b>	<b>8</b>
5.1. CONFIGURATION OF EUT SYSTEM .....	8
5.2. EQUIPMENT USED IN EUT SYSTEM .....	8
5.3. SUMMARY OF TEST RESULTS .....	8
<b>6. TEST FACILITY .....</b>	<b>9</b>
<b>7 TEST METHODOLOGY.....</b>	<b>9</b>
<b>8. ALL TEST EQUIPMENT LIST .....</b>	<b>9</b>
<b>9. RADIATED EMISSION .....</b>	<b>11</b>
9.1 TEST LIMIT.....	11
9.2. MEASUREMENT PROCEDURE .....	12
9.3. TEST SETUP .....	14
9.4. TEST RESULT .....	16
<b>10. BAND EDGE EMISSION .....</b>	<b>30</b>
10.1. MEASUREMENT PROCEDURE .....	30
10.2 TEST SETUP .....	30
10.3 RADIATED TEST RESULT .....	31
<b>11. 20DB BANDWIDTH .....</b>	<b>35</b>
11.1. MEASUREMENT PROCEDURE .....	35
11.2. TEST SET-UP .....	35
11.3. LIMITS AND MEASUREMENT RESULTS .....	35
<b>12. FCC LINE CONDUCTED EMISSION TEST .....</b>	<b>38</b>
12.1. LIMITS OF LINE CONDUCTED EMISSION TEST .....	38
12.2. BLOCK DIAGRAM OF LINE CONDUCTED EMISSION TEST .....	38
12.3. PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST .....	39
12.4. FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST .....	39
12.5. TEST RESULT OF LINE CONDUCTED EMISSION TEST .....	39
<b>APPENDIX A: PHOTOGRAPHS OF TEST SETUP .....</b>	<b>42</b>
<b>APPENDIX B: PHOTOGRAPHS OF EUT .....</b>	<b>45</b>

## 1. VERIFICATION OF CONFORMITY

<b>Applicant</b>	Guangdong Spark Technology Co., Ltd.
<b>Address</b>	Room 306,308,310,NO.6, South Industrial Road, Songshan Lake National Hitech Industrial Development Zone, Dongguan, Guangdong, China 523808
<b>Manufacturer</b>	Guangdong Spark Technology Co., Ltd.
<b>Address</b>	Room 306,308,310,NO.6, South Industrial Road, Songshan Lake National Hitech Industrial Development Zone, Dongguan, Guangdong, China 523808
<b>Product Designation</b>	MOVEBAND
<b>Brand Name</b>	alcatel
<b>Test Model</b>	MB10
<b>Date of test</b>	Apr.23,2016 to Apr.25,2016
<b>Deviation</b>	None
<b>Condition of Test Sample</b>	Normal
<b>Report Template</b>	AGCRT-US-BR/RF

We hereby certify that:

The above equipment was tested by Dongguan Precise Testing Service Co., Ltd. The test data, the energy emitted by the sample tested as described in this report is in compliance with the requirements of FCC Rules Part 15.249.

Tested By



Time Huang(Huang Nanhui) May 06,2016

Reviewed By



Forrest Lei(Lei Yonggang) May 06,2016

Approved By



Solger Zhang(Zhang Hongyi)  
Authorized Officer May 06,2016

## 2. GENERAL INFORMATION

### 2.1. PRODUCT DESCRIPTION

A major technical description of EUT is described as following

<b>Operation Frequency</b>	2.402 GHz to 2.480GHz
<b>RF Output Power</b>	3.49dBm(Max)
<b>Bluetooth Version</b>	V 4.0
<b>Modulation</b>	GFSK
<b>Number of channels</b>	40 for BLE
<b>Hardware Version</b>	V0.7
<b>Software Version</b>	V1.0
<b>Antenna Designation</b>	PCB Antenna
<b>Antenna Gain</b>	0dBi
<b>Power Supply</b>	Normal Voltage: DC 3.7V

Note: 1.The USB port only used for charging and can't be used to transfer data with PC.  
2.The test model has many kind of color, including pink, blue and black.

### 2.2. TABLE OF CARRIER FREQUENCYS

BLE Channel List

<b>Frequency Band</b>	<b>Channel Number</b>	<b>Frequency</b>
2400~2483.5MHZ	0	2402MHZ
	1	2404MHZ
	:	:
	38	2478 MHZ
	39	2480 MHZ

### 3. MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement  $y \pm U$  , where expended uncertainty  $U$  is based on a standard uncertainty multiplied by a coverage factor of  $k=2$  , providing a level of confidence of approximately 95 % .


No.	Item	Uncertainty
1	Conducted Emission Test	$\pm 3.18\text{dB}$
2	All emissions, radiated	$\pm 3.91\text{dB}$
3	Temperature	$\pm 0.5^\circ\text{C}$
4	Humidity	$\pm 2\%$

### 4. DESCRIPTION OF TEST MODES

NO.	TEST MODE DESCRIPTION
1	Low channel TX
2	Middle channel TX
3	High channel TX
4	BT Link with charging
5	BT Link

Note:


1. All the test modes can be supply by battery, only the result of the worst case was recorded in the report, if no other cases.
2. For Radiated Emission, 3axis were chosen for testing for each applicable mode.
3. The EUT used fully-charged battery when tested.



## 5. SYSTEM TEST CONFIGURATION


### 5.1. CONFIGURATION OF EUT SYSTEM

Configure 1: (Normal hopping)



**Note:** Owing to the EUT has own battery, Testing will be performed while PC or Adapter remove.

Configure 2: (Control continuous TX)



### 5.2. EQUIPMENT USED IN EUT SYSTEM

Item	Equipment	Model No.	ID or Specification	Remark
1	MOVEBAND	alcatel	MB10	EUT
2	PC	SONY	E1412AYCW	A.E
3	Control box	N/A	N/A	A.E
4	Battery	NV 602060	DC3.7V/ 700mAh	Accessory
5	Adapter	ETPCA-050100U3W	N/A	A.E

### 5.3. SUMMARY OF TEST RESULTS

FCC RULES	DESCRIPTION OF TEST	RESULT
§15.249	Radiated Emission	Compliant
§15.249	Band Edges	Compliant
§15.207	Conduction Emission	Compliant
§15.215	BANDWIDTH	Compliant

## 6. TEST FACILITY

<b>Site</b>	Dongguan Precise Testing Service Co., Ltd.
<b>Location</b>	Building D, Baoding Technology Park, Guangming Road 2, Dongcheng District, Dongguan, Guangdong, China,
<b>FCC Registration No.</b>	371540
<b>Description</b>	The test site is constructed and calibrated to meet the FCC requirements in documents ANSI C63.4:2014.

## 7 TEST METHODOLOGY

All measurements contained in this report were conducted with ANSI C63.10-2013.

## 8. ALL TEST EQUIPMENT LIST

FOR RADIATED EMISSION TEST (BELOW 1GHZ)

Radiated Emission Test Site					
<b>Name of Equipment</b>	<b>Manufacturer</b>	<b>Model Number</b>	<b>Serial Number</b>	<b>Last Calibration</b>	<b>Due Calibration</b>
EMI Test Receiver	Rohde & Schwarz	ESCI	101417	July 4, 2015	July 3, 2016
Trilog Broadband Antenna (25M-1GHz)	SCHWARZBECK	VULB9160	9160-3355	July 4, 2015	July 3, 2016
Signal Amplifier	SCHWARZBECK	BBV 9475	9745-0013	July 4, 2015	July 3, 2016
RF Cable	SCHWARZBECK	AK9515E	96221	July 4, 2015	July 3, 2016
3m Anechoic Chamber	CHENGYU	966	PTS-001	June 6, 2015	June 5, 2016
MULTI-DEVICE Positioning Controller	Max-Full	MF-7802	MF780208339	N/A	N/A
Active loop antenna (9K-30MHz)	Schwarzbeck	FMZB1519	1519-038	June 6, 2015	June 5, 2016
Spectrum analyzer	Agilent	E4407B	MY46185649	June 6, 2015	June 5, 2016
Radiation Cable 1	MXT	RS1	R005	June 6, 2015	June 5, 2016
Radiation Cable 2	MXT	RS1	R006	June 6, 2015	June 5, 2016

FOR RADIATED EMISSION TEST (1GHZ ABOVE)

Radiated Emission Test Site					
Name of Equipment	Manufacturer	Model Number	Serial Number	Last Calibration	Due Calibration
EMI Test Receiver	Rohde & Schwarz	ESCI	101417	July 4, 2015	July 3, 2016
Horn Antenna (1G-18GHz)	SCHWARZBECK	BBHA9120D	9120D-1246	July 11, 2015	July 10, 2016
Spectrum Analyzer	Agilent	E4411B	MY4511453	July 4, 2015	July 3, 2016
Signal Amplifier	SCHWARZBECK	BBV 9718	9718-269	July 7, 2015	July 6, 2016
RF Cable	SCHWARZBECK	AK9515H	96220	July 8, 2015	July 7, 2016
3m Anechoic Chamber	CHENGYU	966	PTS-001	June 6, 2015	June 5, 2016
MULTI-DEVICE Positioning Controller	Max-Full	MF-7802	MF780208339	N/A	N/A
Horn Ant (18G-40GHz)	Schwarzbeck	BBHA 9170	9170-181	June 6, 2015	June 5, 2016
Radiation Cable 1	MXT	RS1	R005	June 6, 2015	June 5, 2016
Radiation Cable 2	MXT	RS1	R006	June 6, 2015	June 5, 2016

Conducted Emission Test Site

Name of Equipment	Manufacturer	Model Number	Serial Number	Last Calibration	Due Calibration
EMI Test Receiver	- Rohde & Schwarz	ESCI	101417	July 4, 2015	July 3, 2016
Artificial Mains Network	Narda	L2-16B	000WX31025	July 8, 2015	July 7, 2016
Artificial Mains Network (AUX)	Narda	L2-16B	000WX31026	July 8, 2015	July 7, 2016
RF Cable	SCHWARZBECK	AK9515E	96222	July 4, 2015	July 3, 2016
Shielded Room	CHENGYU	843	PTS-002	June 6, 2015	June 5, 2016
Conduction Cable	MXT	SE1	S003	June 6, 2015	June 5, 2016

## 9. RADIATED EMISSION

### 9.1 TEST LIMIT

#### Standard FCC15.249

Fundamental Frequency	Field Strength of Fundamental (millivolts/meter)	Field Strength of Harmonics (microvolts/meter)
900-928MHz	50	500
2400-2483.5MHz	50	500
5725-5875MHz	50	500
24.0-24.25GHz	250	2500

#### Standard FCC 15.209

Frequency (MHz)	Distance Meters	Field Strengths Limit	
		$\mu$ V/m	dB( $\mu$ V)/m
0.009 ~ 0.490	300	2400/F(kHz)	---
0.490 ~ 1.705	30	24000/F(kHz)	---
1.705 ~ 30	30	30	---
30 ~ 88	3	100	40.0
88 ~ 216	3	150	43.5
216 ~ 960	3	200	46.0
960 ~ 1000	3	500	54.0
Above 1000	3	Other: 74.0 dB( $\mu$ V)/m (Peak) 54.0 dB( $\mu$ V)/m (Average)	
Remark: (1) Emission level dB $\mu$ V = 20 log Emission level $\mu$ V/m (2) The smaller limit shall apply at the cross point between two frequency bands. (3) Distance is the distance in meters between the measuring instrument, antenna and the closest point of any part of the device or system.			

## 9.2. MEASUREMENT PROCEDURE

1. The measuring distance of 3m shall be used for measurements. The EUT was placed on the top of a rotating table 0.8 meter above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation(below 1GHz)
2. The measuring distance of 3m shall used for measurements. The EUT was placed on the top of a rotating table 1.5 meter above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation(above 1GHz)
3. The height of the test antenna shall vary between 1m to 4m. Both horizontal and vertical polarization Of the antenna are set to make the measurement.
4. The initial step in collecting radiated emission data is a receive peak detector mode. Pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
5. All readings are peak unless otherwise stated QP in column of Note. Peak denoted that the Peak reading compliance with the QP limits and then QP Mode measurement didn't perform(Below 1GHz)
6. All readings are Peak mode value unless otherwise stated AVG in column of Note. If the Peak mode measured value compliance with the Peak limits and lower than AVG Limits, the EUT shall be deemed to meet Peak&AVG limits and then only Peak mode was measured, but AVG mode didn't perform.(above 1GHz)


The following table is the setting of spectrum analyzer and receiver.

<b>Spectrum Parameter</b>	<b>Setting</b>
Start ~Stop Frequency	9KHz~150KHz/RB 200Hz for QP
Start ~Stop Frequency	150KHz~30MHz/RB 9KHz for QP
Start ~Stop Frequency	30MHz~1000MHz/RB 120KHz for QP
Start ~Stop Frequency	1GHz~26.5GHz 1MHz/3MHz for Peak, 1MHz/10Hz for Average


<b>Receiver Parameter</b>	<b>Setting</b>
Start ~Stop Frequency	9KHz~150KHz/RB 200Hz for QP
Start ~Stop Frequency	150KHz~30MHz/RB 9KHz for QP
Start ~Stop Frequency	30MHz~1000MHz/RB 120KHz for QP

### 9.3. TEST SETUP


Radiated Emission Test-Setup Frequency Below 30MHz



RADIATED EMISSION TEST SETUP 30MHz-1000MHz



RADIATED EMISSION TEST SETUP ABOVE 1000MHz



**9.4. TEST RESULT**

**(Worst modulation: GFSK)**


**FOR BLE**

**RADIATED EMISSION BELOW 30MHZ**

No emission found between lowest internal used/generated frequencies to 30MHz.

## RADIATED EMISSION BELOW 1GHZ

### RADIATED EMISSION TEST- (30MHZ-1GHZ)-LOW CHANNEL-HORIZONTAL



Site: site #1  
 Limit: FCC Class B 3M Radiation  
 EUT: MOVEBAND  
 M/N: MB10  
 Mode: Low Channel TX  
 Note:

Polarization: *Horizontal*

Temperature: 23.1

Power:


Humidity: 52.4 %

Distance:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		199.7500	14.09	11.99	26.08	43.50	-17.42	peak			
2		230.4667	19.15	8.89	28.04	46.00	-17.96	peak			
3		490.7500	8.80	21.03	29.83	46.00	-16.17	peak			
4		521.4667	11.17	21.71	32.88	46.00	-13.12	peak			
5		599.0667	8.74	23.71	32.45	46.00	-13.55	peak			
6	*	734.8667	7.08	26.19	33.27	46.00	-12.73	peak			

**RESULT: PASS**

RADIATED EMISSION TEST- (30MHZ-1GHZ)-LOW CHANNEL -VERTICAL



Site: site #1 Polarization: **Vertical** Temperature: 23.1  
 Limit: FCC Class B 3M Radiation Power: Humidity: 52.4 %  
 EUT: MOVEBAND Distance:  
 M/N: MB10  
 Mode: Low Channel TX  
 Note:


No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna	Table	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		Height	Degree	
1		152.8667	10.43	15.28	25.71	43.50	-17.79	peak			
2		230.4667	18.55	11.99	30.54	46.00	-15.46	peak			
3		445.4833	4.14	20.45	24.59	46.00	-21.41	peak			
4		536.0167	5.27	22.10	27.37	46.00	-18.63	peak			
5	*	599.0667	13.44	22.73	36.17	46.00	-9.83	peak			
6		723.5500	8.19	25.87	34.06	46.00	-11.94	peak			

**RESULT: PASS**

**Note:** 1. Factor=Antenna Factor + Cable loss, Margin=Measurement-Limit.

2. The "Factor" value can be calculated automatically by software of measurement system.

## RADIATED EMISSION TEST- (30MHZ-1GHZ)-MIDDLE CHANNEL-HORIZONTAL




Site: site #1 Polarization: **Horizontal** Temperature: 23.1  
Limit: FCC Class B 3M Radiation Power: Humidity: 52.4 %  
EUT: MOVEBAND Distance:  
M/N: MB10  
Mode: Middle Channel TX  
Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		201.3667	13.71	11.86	25.57	43.50	-17.93	peak			
2		230.4667	17.70	8.89	26.59	46.00	-19.41	peak			
3		400.2167	10.69	19.08	29.77	46.00	-16.23	peak			
4		498.8333	9.82	21.12	30.94	46.00	-15.06	peak			
5	*	599.0667	11.61	23.71	35.32	46.00	-10.68	peak			
6		736.4833	6.73	26.24	32.97	46.00	-13.03	peak			

## RESULT: PASS

RADIATED EMISSION TEST- (30MHZ-1GHZ)- MIDDLE CHANNEL -VERTICAL



Site: site #1  
 Limit: FCC Class B 3M Radiation  
 EUT: MOVEBAND  
 M/N: MB10  
 Mode: Middle Channel TX  
 Note:

Polarization: *Vertical*

Temperature: 23.1

Power:

Humidity: 52.4 %

Distance:


No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		152.8667	9.03	15.28	24.31	43.50	-19.19	peak			
2		230.4667	19.58	11.99	31.57	46.00	-14.43	peak			
3		536.0167	4.49	22.10	26.59	46.00	-19.41	peak			
4	*	597.4500	15.15	22.72	37.87	46.00	-8.13	peak			
5		723.5500	8.19	25.87	34.06	46.00	-11.94	peak			
6		784.9833	7.39	27.11	34.50	46.00	-11.50	peak			

**RESULT: PASS**

**Note:** 1. Factor=Antenna Factor + Cable loss, Margin=Measurement-Limit.

2. The "Factor" value can be calculated automatically by software of measurement system.

RADIATED EMISSION TEST- (30MHZ-1GHZ)-HIGH CHANNEL-HORIZONTAL




Site: site #1 Polarization: *Horizontal* Temperature: 23.1  
 Limit: FCC Class B 3M Radiation Power: Humidity: 52.4 %  
 EUT: MOVEBAND Distance:  
 M/N: MB10  
 Mode: High Channel TX  
 Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna	Table	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		Height	Degree	
1		230.4667	19.92	8.89	28.81	46.00	-17.19	peak			
2		400.2167	9.04	19.08	28.12	46.00	-17.88	peak			
3		463.2667	8.92	20.73	29.65	46.00	-16.35	peak			
4	*	526.3167	12.49	21.84	34.33	46.00	-11.67	peak			
5		600.6833	8.84	23.73	32.57	46.00	-13.43	peak			
6		689.6000	7.19	24.91	32.10	46.00	-13.90	peak			

**RESULT: PASS**

RADIATED EMISSION TEST- (30MHZ-1GHZ)-HIGH CHANNEL -VERTICAL



Site: site #1  
Polarization: *Vertical*  
Temperature: 23.1  
Limit: FCC Class B 3M Radiation  
Power:  
Humidity: 52.4 %  
EUT: MOVEBAND  
Distance:  
M/N: MB10  
Mode: High Channel TX  
Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		152.8667	9.92	15.28	25.20	43.50	-18.30	peak			
2		230.4667	13.46	11.99	25.45	46.00	-20.55	peak			
3		450.3333	4.57	20.59	25.16	46.00	-20.84	peak			
4		536.0167	4.68	22.10	26.78	46.00	-19.22	peak			
5	*	597.4500	12.02	22.72	34.74	46.00	-11.26	peak			
6		749.4167	7.66	26.61	34.27	46.00	-11.73	peak			

**RESULT: PASS**

**Note:** 1. Factor=Antenna Factor + Cable loss, Margin=Measurement-Limit.


2. The "Factor" value can be calculated automatically by software of measurement system.

## RADIATED EMISSION ABOVE 1GHZ

## (Worst modulation: GFSK)

## FOR BLE

## RADIATED EMISSION TEST- (ABOVE 1GHZ)-LOW CHANNEL-HORIZONTAL




Site: site #1 Polarization: *Horizontal* Temperature: 26  
Limit: FCC Class B 3M Radiation above 1GHZ(PK)- Power: Humidity: 60 %  
EUT: MOVEBAND Distance: 3m  
M/N: MB10  
Mode: Low Channel TX  
Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		2402.000	108.20	-9.68	98.52	114.00	-15.48	peak			
2		3866.667	50.43	-5.63	44.80	74.00	-29.20	peak			
3		4400.000	48.47	-3.45	45.02	74.00	-28.98	peak			
4	*	2402.000	93.09	-9.68	83.41	94.00	-10.59	AVG	100	103	

## RESULT: PASS

RADIATED EMISSION TEST- (ABOVE 1GHZ)-LOW CHANNEL- VERTICAL




Site: site #1 Polarization: *Vertical* Temperature: 26  
 Limit: FCC Class B 3M Radiation above 1GHZ(PK)- Power: Humidity: 60 %  
 EUT: MOVEBAND Distance: 3m  
 M/N: MB10  
 Mode: Low Channel TX  
 Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna	Table	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		Height	Degree	
1		2402.000	108.25	-9.68	98.57	114.00	-15.43	peak			
2		3158.333	54.09	-8.21	45.88	74.00	-28.12	peak			
3		4441.667	49.09	-3.31	45.78	74.00	-28.22	peak			
4	*	2402.000	93.37	-9.68	83.69	94.00	-10.31	AVG	100	319	

**RESULT: PASS**

## RADIATED EMISSION TEST- (ABOVE 1GHZ)-MIDDLE CHANNEL-HORIZONTAL




Site: site #1 Polarization: *Horizontal* Temperature: 26  
Limit: FCC Class B 3M Radiation above 1GHZ(PK)- Power: Humidity: 60 %  
EUT: MOVEBAND Distance: 3m  
M/N: MB10  
Mode: Middle Channel TX  
Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		2440.000	108.33	-9.64	98.69	114.00	-15.31	peak			
2		3125.000	53.51	-8.24	45.27	74.00	-28.73	peak			
3		3850.000	50.98	-5.73	45.25	74.00	-28.75	peak			
4	*	2440.000	93.02	-9.64	83.38	94.00	-10.62	AVG	100	99	

## RESULT: PASS

## RADIATED EMISSION TEST- (ABOVE 1GHZ)-MIDDLE CHANNEL- VERTICAL




Site: site #1 Polarization: *Vertical* Temperature: 26  
Limit: FCC Class B 3M Radiation above 1GHZ(PK)- Power: Humidity: 60 %  
EUT: MOVEBAND Distance: 3m  
M/N: MB10  
Mode: Middle Channel TX  
Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		2440.000	108.28	-9.64	98.64	114.00	-15.36	peak			
2		4058.333	49.64	-4.61	45.03	74.00	-28.97	peak			
3		5125.000	46.64	-1.80	44.84	74.00	-29.16	peak			
4	*	2440.000	92.78	-9.64	83.14	94.00	-10.86	AVG	100	315	

## RESULT: PASS

## RADIATED EMISSION TEST- (ABOVE 1GHZ)-HIGH CHANNEL-HORIZONTAL




Site: site #1 Polarization: **Horizontal** Temperature: 26  
Limit: FCC Class B 3M Radiation above 1GHZ(PK)- Power: Humidity: 60 %  
EUT: MOVEBAND Distance: 3m  
M/N: MB10  
Mode: High Channel TX  
Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		2480.000	107.90	-9.59	98.31	114.00	-15.69	peak			
2		3833.333	51.90	-5.84	46.06	74.00	-27.94	peak			
3		4533.333	49.17	-3.02	46.15	74.00	-27.85	peak			
4	*	2480.000	92.72	-9.59	83.13	94.00	-10.87	AVG	100	95	

## RESULT: PASS

## RADIATED EMISSION TEST- (ABOVE 1GHZ)-HIGH CHANNEL- VERTICAL



Site: site #1 Polarization: **Vertical** Temperature: 26  
Limit: FCC Class B 3M Radiation above 1GHZ(PK)- Power: Humidity: 60 %  
EUT: MOVEBAND Distance: 3m  
M/N: MB10  
Mode: High Channel TX  
Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		2480.000	107.84	-9.59	98.25	114.00	-15.75	peak			
2		3133.333	52.39	-8.23	44.16	74.00	-29.84	peak			
3		4425.000	48.26	-3.36	44.90	74.00	-29.10	peak			
4	*	2480.000	92.64	-9.59	83.05	94.00	-10.95	AVG	100	311	

## RESULT: PASS

**Note:** 6~25GHz at least have 20dB margin. No recording in the test report.

Factor=Antenna Factor + Cable loss - Amplifier gain, Margin=Measurement-Limit.

The “Factor” value can be calculated automatically by software of measurement system.

**Field strength of the fundamental signal(GFSK):**

**Peak value**

Frequency (MHz)	Reading Level (dBuv)	Factor (dB/m)	Measurement (dBuv/m)	Limit (dBuv/m)	Over (dB)	Antenna Polarization
2402	108.20	-9.68	98.52	114.00	-15.48	Horizontal
2402	108.25	-9.68	98.57	114.00	-15.43	Vertical
2440	108.33	-9.64	98.69	114.00	-15.31	Horizontal
2440	108.28	-9.64	98.64	114.00	-15.36	Vertical
2480	107.90	-9.59	98.31	114.00	-15.69	Horizontal
2480	107.84	-9.59	98.25	114.00	-15.75	Vertical

**Average value**

Frequency (MHz)	Reading Level (dBuv)	Factor (dB/m)	Measurement (dBuv/m)	Limit (dBuv/m)	Over (dB)	Antenna Polarization
2402	93.09	-9.68	83.41	94.00	-10.59	Horizontal
2402	93.37	-9.68	83.69	94.00	-10.31	Vertical
2440	93.02	-9.64	83.38	94.00	-10.62	Horizontal
2440	92.78	-9.64	83.14	94.00	-10.86	Vertical
2480	92.72	-9.59	83.13	94.00	-10.87	Horizontal
2480	92.64	-9.59	83.05	94.00	-10.95	Vertical

## 10. BAND EDGE EMISSION

### 10.1. MEASUREMENT PROCEDURE


1The EUT operates at hopping-off test mode. The lowest or highest channels are tested to verify the largest transmission and spurious emissions power at the continuous transmission mode.

2Max hold the trace of the step 1, and the EUT operates at hopping-on test mode to verify the largest spurious emissions power.

3Set the spectrum analyzer in the following setting in order to capture the lower and upper band-edges of the emission

### 10.2 TEST SETUP

RADIATED EMISSION TEST SETUP




### 10.3 RADIATED TEST RESULT

(Worst modulation: GFSK)

FOR BLE

TEST PLOT OF BAND EDGE FOR LOW CHANNEL-Horizontal





---

Site: site #1      Polarization: *Horizontal*      Temperature: 26  
 Limit: FCC Class B 3M Radiation above 1GHZ(PK)      Power:      Humidity: 60 %  
 EUT: MOVEBAND      Distance:  
 M/N: MB10  
 Mode: Low Channel TX  
 Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		2272.775	31.53	10.18	41.71	74.00	-32.29	peak			
2		2390.000	30.62	10.31	40.93	74.00	-33.07	peak			
3	*	2402.000	88.41	10.32	98.73	74.00	24.73	peak			

TEST PLOT OF BAND EDGE FOR LOW CHANNEL –Vertical




---

Site: site #1 Polarization: **Vertical** Temperature: 26  
Limit: FCC Class B 3M Radiation above 1GHZ(PK) Power: Humidity: 60 %  
EUT: MOVEBAND Distance:  
M/N: MB10  
Mode: Low Channel TX  
Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dB	cm		degree		
1		2287.467	31.88	10.20	42.08	74.00	-31.92	peak			
2		2390.000	30.35	10.31	40.66	74.00	-33.34	peak			
3	*	2402.000	88.30	10.32	98.62	74.00	24.62	peak			


## TEST PLOT OF BAND EDGE FOR HIGH CHANNEL -Horizontal



Site: site #1 Polarization: *Horizontal* Temperature: 26  
Limit: FCC Class B 3M Radiation above 1GHZ(PK) Power: Humidity: 60 %  
EUT: MOVEBAND Distance:  
M/N: MB10  
Mode: High Channel TX  
Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1	*	2480.000	87.96	10.41	98.37	74.00	24.37	peak			
2		2483.500	29.25	10.41	39.66	74.00	-34.34	peak			
3		2490.943	30.95	10.42	41.37	74.00	-32.63	peak			

## TEST PLOT OF BAND EDGE FOR HIGH CHANNEL-Vertical



Site: site #1 Polarization: **Vertical** Temperature: 26  
Limit: FCC Class B 3M Radiation above 1GHZ(PK) Power: Humidity: 60 %  
EUT: MOVEBAND Distance:  
M/N: MB10  
Mode: High Channel TX  
Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1	*	2480.000	87.85	10.41	98.26	74.00	24.26	peak			
2		2483.500	30.37	10.41	40.78	74.00	-33.22	peak			
3		2491.237	31.07	10.42	41.49	74.00	-32.51	peak			

## RESULT: PASS

**Note:** The other modes radiation emission have enough 20dB margin.

Factor=Antenna Factor + Cable loss - Amplifier gain, Over=Measure-Limit.

The “Factor” value can be calculated automatically by software of measurement system.

Hopping on mode and Hopping off mode have been tested, but only worst case reported.


## 11. 20DB BANDWIDTH

### 11.1. MEASUREMENT PROCEDURE

1. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
2. Set the EUT Work on the top, the middle and the bottom operation frequency individually.
3. Set Span = approximately 2 to 3 times the 20 dB bandwidth, centered on a hopping channel  
 $RBW \geq 1\% \text{ of the } 20 \text{ dB bandwidth}$ ,  $VBW \geq RBW$ ; Sweep = auto; Detector function = peak
4. Set SPA Trace 1 Max hold, then View.

### 11.2. TEST SET-UP

#### (BLOCK DIAGRAM OF CONFIGURATION)




Note: The EUT has been used temporary antenna connector for testing.

### 11.3. LIMITS AND MEASUREMENT RESULTS


#### FOR BLE

BLUETOOTH 1MBPS LIMITS AND MEASUREMENT RESULT			
Applicable Limits	Measurement Result		
	Test Data (MHz)	Criteria	
N/A	Low Channel	1.629	PASS
	Middle Channel	1.676	PASS
	High Channel	1.430	PASS

TEST PLOT OF BANDWIDTH FOR LOW CHANNEL



TEST PLOT OF BANDWIDTH FOR MIDDLE CHANNEL



TEST PLOT OF BANDWIDTH FOR HIGH CHANNEL



## 12. FCC LINE CONDUCTED EMISSION TEST


### 12.1. LIMITS OF LINE CONDUCTED EMISSION TEST

Frequency	Maximum RF Line Voltage	
	Q.P. ( dBuV)	Average( dBuV)
150kHz~500kHz	66-56	56-46
500kHz~5MHz	56	46
5MHz~30MHz	60	50

Note:

1. The lower limit shall apply at the transition frequency.
2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz.

### 12.2. BLOCK DIAGRAM OF LINE CONDUCTED EMISSION TEST



### **12.3. PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST**

1. The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10 (see Test Facility for the dimensions of the ground plane used). When the EUT is a floor-standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.
2. Support equipment, if needed, was placed as per ANSI C63.10.
3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10.
4. All support equipments received AC120V/60Hz power from a LISN, if any.
5. The EUT received DC charging voltage by PC or Adapter
6. The test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
7. Analyzer / Receiver scanned from 150 kHz to 30MHz for emissions in each of the test modes.
8. During the above scans, the emissions were maximized by cable manipulation.
9. The test mode(s) were scanned during the preliminary test.

Then, the EUT configuration and cable configuration of the above highest emission level were recorded for reference of final testing.


### **12.4. FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST**

- EUT and support equipment was set up on the test bench as per step 2 of the preliminary test.
- 2. A scan was taken on both power lines, Line 1 and Line 2, recording at least the six highest emissions. Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit. If EUT emission level was less -2dB to the A.V. limit in Peak mode, then the emission signal was re-checked using Q.P and Average detector.
- 3. The test data of the worst case condition(s) was reported on the Summary Data page.

### **12.5. TEST RESULT OF LINE CONDUCTED EMISSION TEST**


**Note:** The below data was tested by adapter (worst case)

FOR BLE RESULT



Site: Conduction Phase: L1 Temperature: 22.9  
 Limit: FCC Class B Conduction(QP) Power: Humidity: 53.2 %  
 EUT: MOVEBAND  
 M/N: MB10  
 Mode: BT Link with charging  
 Note:

No.	Freq. (MHz)	Reading_Level (dBuV)			Correct Factor	Measurement (dBuV)			Limit (dBuV)		Margin (dB)		P/F	Comment
		Peak	QP	AVG		Peak	QP	AVG	QP	AVG	QP	AVG		
1	0.2860	18.43		5.45	10.28	28.71		15.73	60.64	50.64	-31.93	-34.91	P	
2	0.6740	20.48		8.62	10.34	30.82		18.96	56.00	46.00	-25.18	-27.04	P	
3	1.8220	20.64		11.68	10.28	30.92		21.96	56.00	46.00	-25.08	-24.04	P	
4	3.6420	23.22		11.49	10.49	33.71		21.98	56.00	46.00	-22.29	-24.02	P	
5	9.5338	26.14		10.44	10.36	36.50		20.80	60.00	50.00	-23.50	-29.20	P	
6	17.6899	27.39		12.51	10.12	37.51		22.63	60.00	50.00	-22.49	-27.37	P	



Site: Conduction  
Limit: FCC Class B Conduction(QP)

Phase: **N**

Temperature: 22.9

EUT: MOVEBAND

## Power:

Humidity: 53.2 %

M/N: MB10

Mode: BT I

Mode: BT Link with charging  
Notes:


### Note.



No.	Freq. (MHz)	Reading_Level (dBuV)			Correct Factor	Measurement (dBuV)			Limit (dBuV)		Margin (dB)		P/F	Comment
		Peak	QP	AVG		Peak	QP	AVG	QP	AVG	QP	AVG		
1	0.4500	21.70		9.79	10.37	32.07		20.16	56.87	46.87	-24.80	-26.71	P	
2	0.6700	23.43		10.08	10.34	33.77		20.42	56.00	46.00	-22.23	-25.58	P	
3	1.8220	22.61		12.14	10.28	32.89		22.42	56.00	46.00	-23.11	-23.58	P	
4	2.7300	22.74		11.48	10.49	33.23		21.97	56.00	46.00	-22.77	-24.03	P	
5	6.7699	27.30		11.89	10.33	37.63		22.22	60.00	50.00	-22.37	-27.78	P	
6	16.8259	32.02		13.26	10.13	42.15		23.39	60.00	50.00	-17.85	-26.61	P	


**APPENDIX A: PHOTOGRAPHS OF TEST SETUP**  
**CONDUCTED EMISSION TEST SETUP**




**FCC RADIATED EMISSION TEST SETUP**







**APPENDIX B: PHOTOGRAPHS OF EUT**  
**WHOLE VIEW OF EUT--RED**



TOP VIEW OF EUT-RED



BOTTOM VIEW OF EUT-RED



FRONT VIEW OF EUT-RED



BACK VIEW OF EUT-RED



LEFT VIEW OF EUT-RED




RIGHT VIEW OF EUT-RED




OPEN VIEW OF EUT-1




OPEN VIEW OF EUT-2




INTERNAL VIEW OF EUT-1




INTERNAL VIEW OF EUT-2




INTERNAL VIEW OF EUT-3




WHOLE VIEW OF EUT--BLUE



TOP VIEW OF EUT-BLUE



BOTTOM VIEW OF EUT-BLUE



FRONT VIEW OF EUT-BLUE



BACK VIEW OF EUT-BLUE



LEFT VIEW OF EUT-BLUE



RIGHT VIEW OF EUT-BLUE



VIEW OF EUT-RED



VIEW OF EUT-BLUE



VIEW OF EUT-BLACK



VIEW OF ADAPTER(AE)



THE ADAPTER WAS SUPPLIED BY AGC

**----END OF REPORT----**