FCC Test Report

Report No.: AGC02866150301FE02

FCC ID : 2AEJ9FREEDOM

APPLICATION PURPOSE : Original Equipment

PRODUCT DESIGNATION: GSM/WCDMA Mobile Phone

BRAND NAME : N/A

MODEL NAME : Freedom

CLIENT : Digit Secure India Private Limited

DATE OF ISSUE : Apr.24, 2015

STANDARD(S) : FCC Part 22H & 24E Rules

REPORT VERSION: V1.0

Attestation of Global Compliance (Shenzhen) Co., Ltd.

CAUTION:

This report shall not be reproduced except in full without the written permission of the test laboratory and shall not be quoted out of context.



Page 2 of 142

REPORT REVISE RECORD

Report Version	Revise Time	Issued Date	Valid Version	Notes
V1.0	/	Apr.24, 2015	Valid	Original Report

TABLE OF CONTENTS

TABLE OF CONTENTS	3
1. VERIFICATION OF COMPLIANCE	5
2. GENERAL INFORMATION	6
2.1 PRODUCT DESCRIPTION	6
2.2 RELATED SUBMITTAL(S) / GRANT (S)	
2.3 TEST METHODOLOGY	
2.4 TEST FACILITY	3
2.5 MEASUREMENT INSTRUMENTS	9
2.6 SPECIAL ACCESSORIES	11
2.7 EQUIPMENT MODIFICATIONS	11
3. SYSTEM TEST CONFIGURATION	12
3.1 EUT CONFIGURATION	12
3.2 EUT EXERCISE	12
3.3 GENERAL TECHNICAL REQUIREMENTS	
3.4 CONFIGURATION OF EUT SYSTEM	13
4. SUMMARY OF TEST RESULTS	14
5. DESCRIPTION OF TEST MODES	14
6. OUTPUT POWER	15
6.1 CONDUCTED OUTPUT POWER	15
6.2 RADIATED OUTPUT POWER	22
6.3. PEAK-TO-AVERAGE RATIO	25
7. OCCUPIED BANDWIDTH	27
7.1 MEASUREMENT METHOD	27
7.2 PROVISIONS APPLICABLE	27
7.3 MEASUREMENT RESULT	28
APPENDIX A:BANDWIDTH	28
8. BAND EDGE	48
8.1 MEASUREMENT METHOD	48

8.2 PROVISIONS APPLICABLE	48
8.3 MEASUREMENT RESULT	49
APPENDIX B: BAND EDGES COMPLIANCE	49
9. SPURIOUS EMISSION	61
9.1 CONDUCTED SPURIOUS EMISSION	61
APPENDIX C: SPURIOUS EMISSION AT ANTENNA TERMINAL	62
9.2 RADIATED SPURIOUS EMISSION	116
10. MAINS CONDUCTED EMISSION	120
10.1 MEASUREMENT METHOD	120
10.2 PROVISIONS APPLICABLE	120
10.3 MEASUREMENT RESULT	121
11. FREQUENCY STABILITY	123
11.1 MEASUREMENT METHOD	123
11.2 PROVISIONS APPLICABLE	
11.3 MEASUREMENT RESULT	
Appendix D:Frequency Stability	125
PHOTOGRAPHS OF TEST SETUP	134
PHOTOGRAPHS OF EUT	136

Page 5 of 142

1. VERIFICATION OF COMPLIANCE

Applicant	Digit Secure India Private Limited
Address	Plot No-1303&1304, 4th Floor, Khanamet, HiTech City, Ayappa Society, Madhapur, Hyderabad, Telangana, India
Manufacturer	SHENZHEN HSEM TECHNOLOGY CO., LTD.
Address	4TH FLOOR, 5 PLANTS, TONGFUYU INDUSTRIAL, TAOYUAN STREET, NANSHAN DISTRICT, SHENZHEN P.R. CHINA
Product Designation	GSM/WCDMA Mobile Phone
Brand Name	N/A
Test Model	Freedom
Date of test	Apr.17, 2015 to Apr.23, 2015
Deviation None	
Condition of Test Sample	Normal

We hereby certify that:

The above equipment was tested by Attestation of Global Compliance (Shenzhen) Co., Ltd. The data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C 63.4:2003 and TIA/EIA 603. The sample tested as described in this report is in compliance with the FCC Rules Part 22H and 24E.

The test results of this report relate only to the tested sample identified in this report.

Reviewed By:

Bart Xie Apr.24, 2015

Kidd Yang Apr.24, 2015

Approved By:

Solger Zhang Apr.24, 2015

Report No.: AGC02866150301FE02 Page 6 of 142

2. GENERAL INFORMATION

2.1 PRODUCT DESCRIPTION

A major technical description of EUT is described as following:

<u> </u>	<u> </u>		
Product Designation:	GSM/WCDMA Mobile Phone		
Hardware version:	DX01_MB_P2_V01		
Software version:	ALPS.KK1.MP1.V2.11		
Frequency Bands:	☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐		
Antenna:	PIFA Antenna		
Type of Modulation	GSM / GPRS : GMSK EDGE : GMSK/8PSK WCDMA : QPSK		
Antenna gain(GSM):	-1.0dBi(GSM/WCDMA 850), -0.8dBi (GSM/WCDMA 1900)		
Power Supply:	DC 3.7V by Battery		
Battery parameter:	DC3.7V/4000 mAh		
Adapter Input:	AC100-240V, 50-60Hz, 350mA		
Adapter Output:	DC5V, 2000mA		
Dual Card:	WCDMA / GSM Card Slot GSM Card Slot		
GPRS Class	12		
Extreme Vol. Limits:	DC3.4 V to 4.2 V (Normal: DC3.7 V)		
Extreme Temp. Tolerance	-10℃ to +50℃		
*** NI=4= . Th=	OCA 2V and Law Valtage DC2 4V were declared by many facturer. The		

^{***} Note: The High Voltage DC4.2V and Low Voltage DC3.4V were declared by manufacturer, The EUT couldn't be operating normally with higher or lower voltage.

Other functions have been performed according to verification procedure except for Bluetooth and MS function. Card 1 can't transmit with Card 2 simultaneously.

We found out the test mode with the highest power level after we analyze all the data rates. So we chose worst case as a representative.

^{***} **Note:** The maximum power levels are GSM for MCS-4: GMSK link, EDGE for MCS-9:8PSK link, and RMC 12.2kbps mode for WCDMA band II, WCDMA band V, only these modes were used for all tests.

Report No.: AGC02866150301FE02 Page 7 of 142

WCDMA Card Slot:

	Maximum ERP/EIRP	Max. Conducted Power	Max. Average	
	(dBm)	(dBm)	Burst Power (dBm)	
GSM 850	30.82	32.62	31.29	
PCS 1900	27.62	29.72	28.23	
UMTS BAND II	21.59	23.58	21.42	
UMTS BAND V	21.58	23.69	21.38	

GSM Card Slot:

	Maximum ERP/EIRP	Max. Conducted Power	Max. Average	
	(dBm)	(dBm)	Burst Power (dBm)	
GSM 850	30.49	32.36	30.75	
PCS 1900	27.23	29.45	27.71	

Page 8 of 142

2.2 RELATED SUBMITTAL(S) / GRANT (S)

This submittal(s) (test report) is intended for **FCC ID: 2AEJ9FREEDOM**, filing to comply with the FCC Part 22H&24E requirements.

2.3 TEST METHODOLOGY

The radiated emission testing was performed according to the procedures of ANSI C 63.4: 2003; TIA/EIA 603 and FCC CFR 47 Rules of 2.1046, 2.1047, 2.1049, 2.1051, 2.1053, 2.1055, 2.1057.

KDB 971168 D01 Power Meas License Digital Systems v02r01

2.4 TEST FACILITY

Site	Compliance Certification Services (Shenzhen) Inc.	
Location No.10-1 Mingkeda Logistics park, No.18, Huanguan South Rd.,Guan Lan T Baoan District, Shenzhen, China		
Description	Test Firm Registration Number: 441872	

Report No.: AGC02866150301FE02 Page 9 of 142

2.5 MEASUREMENT INSTRUMENTS

Name of Equipment	Manufacturer	Model	S/N	Calibration Date	Calibration Due.
SPECTRUM ANALYZER	AGILENT	E4440A	US41421290	Feb.17,2015	Feb.16,2016
TEST RECEIVER	R&S	ESCI	100694	July 25, 2014	July 24, 2015
COMMUNICATION TESTER	AGILENT	8960	122500087	July 25, 2014	July 24, 2015
COMMUNICATION TESTER	R&S	CMU200	122500166	July 25, 2014	July 24, 2015
SIGNAL GENERATOR	AGILENT	E4438C	MY44260051	Feb.23,2015	Feb. 22,2016
LISN	R&S	ESH3-Z5	838979/009	July 25, 2014	July 24, 2015
CLIMATE CHAMBER	ALBATROSS			July 25, 2014	July 24, 2015
Loop Antenna	A.H.	SAS-562B	SEL0097	May 10, 2014	May 09, 2015
WIDEBAND REQUENCY ANTENNA	SCHWARZBECK	VULB9168	VULB9168-494	Aug.16, 2014	Aug.15, 2015
Substitution Antenna	EMCO	3142C		Aug.16, 2014	Aug.15, 2015
Substitution Antenna	EM	EM-AH-10180	69	Apr.19, 2015	Apr.18, 2016
Horn Antenna	EM	EM-AH-10180	67	Feb.17,2015	Feb.16,2016
Horn Antenna	A.H. Systems Inc.	SAS-574		June 6, 2014	June 5, 2015
Radiation Cable 1	Sat	RE1	R003	June 4, 2014	June 3, 2015
Radiation Cable 2	Sat	RE2	R002	June 4, 2014	June 3, 2015
Conduction Cable	Sat	CE1	C001	June 4, 2014	June 3, 2015

Radiated Emission Test Site 966(2)					
Name of Equipment	Manufacturer	Model Number	Serial Number	Last Calibration	Due Calibration
PSA Series Spectrum Analyzer	Agilent	E4446A	US44300399	03/01/2015	03/01/2016
EMI TEST RECEIVER	ROHDE&SCHWAR Z	ESCI	100783	03/09/2015	03/08/2016
Amplifier	MITEQ	AM-1604-3000	1123808	03/18/2015	03/17/2016
High Noise Amplifier	Agilent	8449B	3008A01838	03/18/2015	03/17/2016
Board-Band Horn Antenna	Schwarzbeck	BBHA 9170	9170-497	07/10/2014	07/09/2015
Bilog Antenna	SCHAFFNER	CBL6143	5082	03/01/2015	03/01/2016
Horn Antenna	SCHWARZBECK	BBHA9120	D286	03/01/2015	03/01/2016
Loop Antenna	COM-POWER	AL-130	121044	09/27/2014	09/26/2015
Turn Table	N/A	N/A	N/A	N.C.R	N.C.R
Controller	Sunol Sciences	SC104V	022310-1	N.C.R	N.C.R
Controller	СТ	N/A	N/A	N.C.R	N.C.R
Temp. / Humidity Meter	Anymetre	JR913	N/A	02/28/2015	02/27/2016
Antenna Tower	SUNOL	TLT2	N/A	N.C.R	N.C.R
Test S/W FARAD		LZ-RF / CCS-SZ-3A2			

Conducted Emission Test Site					
Name of Equipment	Manufacturer	Model Number	Serial Number	Last Calibration	Due Calibration
EMI TEST RECEIVER	ROHDE&SCHWAR Z	ESCI	100783	03/09/2015	03/08/2016
LISN(EUT)	ROHDE&SCHWAR Z	ENV216	101543-WX	03/09/2015	03/08/2016
LISN	EMCO	3825/2	8901-1459	03/09/2015	03/08/2016
Temp. / Humidity Meter	VICTOR	HTC-1	N/A	03/04/2015	03/03/2016
Test S/W	FARAD	EZ-EMC/ CCS-3A1-CE			

Page 11 of 142

2.6 SPECIAL ACCESSORIES

The battery and the charger, earphone supplied by the applicant were used as accessories and being tested with EUT intended for FCC grant together.

2.7 EQUIPMENT MODIFICATIONS

Not available for this EUT intended for grant.

Page 12 of 142

3. SYSTEM TEST CONFIGURATION

3.1 EUT CONFIGURATION

The EUT configuration for testing is installed on RF field strength measurement to meet the Commission's requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

3.2 EUT EXERCISE

The Transmitter was operated in the maximum output power mode through Communication Tester. The TX frequency was fixed which was for the purpose of the measurements.

3.3 GENERAL TECHNICAL REQUIREMENTS

Item Number	Item Description		FCC Rules
4	Output Davier	Conducted output power	2.1046/22.913(a) (2) / 24.232
1	Output Power	Radiated output power	(c)
2	Peak-to-Average Ratio	Peak-to-Average Ratio	24.232(d)
3	Spurious Emission	Conducted spurious emission	2.1051 / 22.917 / 24.238
		Radiated spurious emission	
4	Mains Conducted Emi	ssion	15.107 / 15.207
5	Frequency Stability		2.1055/22.355 /24.235
6	Occupied Bandwidth		2.1049 (h)(i)
7	Emission Bandwidth		22.917(a)/24.238(a)
8	Band Edge		22.917(a)/24.238(a)

Page 13 of 142

3.4 CONFIGURATION OF EUT SYSTEM

Fig. 2-1 Configuration of EUT System




Table 2-1 Equipment Used in EUT System

Item	Equipment	Model No.	ID or Specification	Note
1	GSM/WCDMA Mobile Phone	Freedom	FCC ID:2AEJ9FREEDOM	EUT
2	Adapter	Freedom	5V 2000mA	Accessory
3	Battery	Freedom	DC3.7V / 4000 mAh	Accessory
4	Earphone	Freedom	N/A	Accessory
5	USB Cable	Freedom	N/A	Accessory

^{***}Note: All the accessories have been used during the test. The following "EUT" in setup diagram means EUT system.

Report No.: AGC02866150301FE02 Page 14 of 142

4. SUMMARY OF TEST RESULTS

Item Number	Item Description		FCC Rules	Result	
		Conducted			
1	Output Dower	Output Power	2.1046/22.913(a) (2) /	Pass	
'	Output Power	Radiated	24.232 (c)	Pass	
		Output Power			
2	Peak-to-Average	Peak-to-Average	24.222(4)	Door	
2	Ratio	Ratio	24.232(d)	Pass	
	Spurious Emission	Conducted			
3		Spurious Emission	2.1051 / 22.917 / 24.238	Door	
3		Radiated	2.1051/22.91//24.230	Pass	
		Spurious Emission			
4	Mains Conducted Em	ission	15.107 / 15.207	Pass	
5	Fraguency Stability		2.1055/22.355	Pass	
5	Frequency Stability		/24.235	Fass	
6	Occupied Bandwidth		2.1049 (h)(i)	Pass	
7	Emission Bandwidth		22.917(a)/24.238(a)	Pass	
8	Band Edge		22.917(a)/24.238(a)	Pass	

5. DESCRIPTION OF TEST MODES

During the testing, the EUT was controlled via Rhode & Schwarz Digital Radio Communication Tester (CMU 200) to ensure max power transmission and proper modulation. Three channels (The top channel, the middle channel and the bottom channel) were chosen for testing on both GSM and PCS frequency band.

***Note: GSM/GPRS/EGPRS 850, GSM/GPRS/EGPRS 1900, WCDMA/HSPA band II, WCDMA/HSPA band V, mode have been tested during the test.

The worst condition was recorded in the test report if no other modes test data.

Report No.: AGC02866150301FE02 Page 15 of 142

6. OUTPUT POWER

6.1 CONDUCTED OUTPUT POWER

6.1.1 MEASUREMENT METHOD

The transmitter output port was connected to base station.

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.

The path loss was compensated to the results for each measurement.

Measure the maximum burst average power and average power for other modulation signal.

The EUT was setup for the max output power with pseudo random data modulation. Power was measured with Spectrum Analyzer. The measurements were performed on all modes (GSM/GPRS/EGPRS 850, GSM/GPRS/EGPRS1900, WCDMA/HSPA band II, WCDMA/HSPA band V) at 3 typical channels (the Top Channel, the Middle Channel and the Bottom Channel) for each band.

6.1.2 MEASUREMENT RESULT

U. I.Z WILAGUINLINI							
	Conducted Output Power Limits for GSM850/EDGE band						
Mode	Nominal Peak Power	Tolerance(dB)					
GSM	33 dBm (2W)	- 2					
EDGE	27 dBm(0.5W)	±2					
	Conducted Output Power Limits for PCS1900/	EDGE band					
Mode	Nominal Peak Power	Tolerance(dB)					
GSM	30 dBm (1W)	- 2					
EDGE	26 dBm (0.4W)	±2					
	Conducted Output Power Limits for UMTS	band II					
Mode	Nominal Peak Power	Tolerance(dB)					
WCDMA	24 dBm (0.25W)	- 2					
Conducted Output Power Limits for UMTS band V							
Mode	Nominal Peak Power	Tolerance(dB)					
WCDMA	24 dBm (0.25W)	- 2					

Report No.: AGC02866150301FE02 Page 16 of 142

GSM 850:

Mode	Frequency	Reference	Peak	Tolerance	Avg.Burst	Duty cycle	Frame
Mode	(MHz)	Power	Power		Power	Factor(dB)	Power(dBm)
	824.2	33	32.62	-0.38	31.29	-9	22.29
GSM850	836.6	33	32.58	-0.42	31.27	-9	22.27
	848.8	33	32.56	-0.44	31.22	-9	22.22
CDDC050	824.2	33	32.34	-0.66	30.86	-9	21.86
GPRS850	836.6	33	32.31	-0.69	30.82	-9	21.82
(1 Slot)	848.8	33	32.26	-0.74	30.78	-9	21.78
CDDC050	824.2	30	29.68	-0.32	28.37	-6	22.37
GPRS850	836.6	30	29.64	-0.36	28.32	-6	22.32
(2 Slot)	848.8	30	29.61	-0.39	28.31	-6	22.31
CDDC050	824.2	28.23	27.66	-0.57	26.28	-4.26	22.02
GPRS850	836.6	28.23	27.63	-0.6	26.26	-4.26	22
(3 Slot)	848.8	28.23	27.61	-0.62	26.21	-4.26	21.95
GPRS850	824.2	27	26.78	-0.22	25.35	-3	22.35
	836.6	27	26.75	-0.25	25.32	-3	22.32
(4 Slot)	848.8	27	26.74	-0.26	25.29	-3	22.29

Mode	Channel	Frequency	Peak Power	Avg.Burst Power
Mode		(MHz)	(dBm)	(dBm)
FDCF	128	824.2	26.46	25.19
EDGE	189	836.6	26.42	25.16
(1 Slot)	251	848.8	26.37	25.13
FDCF	128	824.2	25.36	24.11
EDGE	189	836.6	25.32	24.08
(2 Slot)	251	848.8	25.29	24.06
EDGE	128	824.2	23.64	22.41
	189	836.6	23.61	22.36
(3 Slot)	251	848.8	23.56	22.32
EDGE	128	824.2	22.76	21.47
	189	836.6	22.74	21.42
(4 Slot)	251	848.8	22.68	21.38

Report No.: AGC02866150301FE02 Page 17 of 142

PCS 1900:

Mode	Frequency (MHz)	Reference Power	Peak Power	Tolerance	Avg.Burst Power	Duty cycle Factor(dB)	Frame Power(dBm)
	1850.2	30	29.72	-0.28	28.23	-9	19.23
GSM1900	1880	30	29.68	-0.32	28.18	-9	19.18
	1909.8	30	29.65	-0.35	28.13	-9	19.13
CDDC1000	1850.2	30	29.41	-0.59	27.83	-9	18.83
GPRS1900 (1 Slot)	1880	30	29.38	-0.62	27.77	-9	18.77
(1 3101)	1909.8	30	29.36	-0.64	27.72	-9	18.72
GPRS1900	1850.2	27	26.74	-0.26	25.32	-6	19.32
	1880	27	26.71	-0.29	25.29	-6	19.29
(2 Slot)	1909.8	27	26.67	-0.33	25.25	-6	19.25
GPRS1900	1850.2	25.23	24.72	-0.51	23.23	-4.26	18.97
	1880	25.23	24.69	-0.54	23.21	-4.26	18.95
(3 Slot)	1909.8	25.23	24.66	-0.57	23.18	-4.26	18.92
00004000	1850.2	24	23.75	-0.25	22.34	-3	19.34
GPRS1900	1880	24	23.72	-0.28	22.29	-3	19.29
(4 Slot)	1909.8	24	23.68	-0.32	22.23	-3	19.23

Mode	Channel	Frequency	Peak Power	Avg.Burst Power
Wode		(MHz)	(dBm)	(dBm)
EDGE	512	1850.2	25.68	24.34
(1 Slot)	661	1880	25.61	24.31
(1 3101)	810	1909.8	25.57	24.22
EDGE	512	1850.2	24.72	23.31
(2 Slot)	661	1880	24.69	23.26
(2 3101)	810	1909.8	24.63	23.22
EDGE	512	1850.2	22.71	21.42
(3 Slot)	661	1880	22.68	21.37
(3 3101)	810	1909.8	22.62	21.34
EDGE	512	1850.2	21.74	20.41
	661	1880	21.71	20.35
(4 Slot)	810	1909.8	21.65	20.32

Report No.: AGC02866150301FE02 Page 18 of 142

UMTS BAND II

Mode	Frequency (MHz)	Reference power	Peak Power	Tolerance	Avg.Burst Power
	1852.6	24	23.58	-0.42	21.42
WCDMA 1900 F	1880	24	23.55	-0.45	21.38
	1907.4	24	23.51	-0.49	21.32
	1852.6	24	23.31	-0.69	21.14
WCDMA 1900 AMR	1880	24	23.26	-0.74	21.12
AWIIX	1907.4	24	23.21	-0.79	21.09
	1852.6	24	22.84	-1.16	20.37
HSDPA Subtest 1	1880	24	22.82	-1.18	20.34
Oublest 1	1907.4	24	22.78	-1.22	20.31
	1852.6	24	22.71	-1.29	20.43
HSDPA Subtest 2	1880	24	22.67	-1.33	20.38
Cubicot 2	1907.4	24	22.64	-1.36	20.32
	1852.6	24	22.67	-1.33	20.38
HSDPA Subtest 3	1880	24	22.63	-1.37	20.34
Cubicst 5	1907.4	24	22.61	-1.39	20.31
	1852.6	24	22.75	-1.25	20.44
HSDPA Subtest 4	1880	24	22.68	-1.32	20.41
Cubicot 4	1907.4	24	22.64	-1.36	20.36
	1852.6	24	22.66	-1.34	20.37
HSUPA Subtest 1	1880	24	22.63	-1.37	20.35
Cubicot 1	1907.4	24	22.61	-1.39	20.34
	1852.6	24	22.69	-1.31	20.32
HSUPA Subtest 2	1880	24	22.65	-1.35	20.31
Cubicot 2	1907.4	24	22.62	-1.38	20.26
	1852.6	24	22.64	-1.36	20.28
HSUPA Subtest 3	1880	24	22.61	-1.39	20.23
	1907.4	24	22.56	-1.44	20.18
	1852.6	24	22.78	-1.22	20.34
HSUPA Subtest 4	1880	24	22.74	-1.26	20.36
Cubicot 4	1907.4	24	22.71	-1.29	20.33
	1852.6	24	22.68	-1.32	20.35
HSUPA Subtest 5	1880	24	22.66	-1.34	20.29
	1907.4	24	22.58	-1.42	20.25

Report No.: AGC02866150301FE02 Page 19 of 142

UMTS BAND V

Mode	Frequency (MHz)	Reference power	Peak Power	Tolerance	Avg.Burst Power
	826.6	24	23.69	-0.31	21.38
WCDMA 850 RMC	836.4	24	23.63	-0.37	21.35
TAMO	846.4	24	23.61	-0.39	21.27
	826.6	24	23.38	-0.62	21.14
WCDMA 850 AMR	836.4	24	23.36	-0.64	21.11
7 UVII C	846.4	24	23.31	-0.69	21.09
	826.6	24	22.64	-1.36	20.32
HSDPA Subtest 1	836.4	24	22.61	-1.39	20.29
Subtest 1	846.4	24	22.58	-1.42	20.24
	826.6	24	22.66	-1.34	20.33
HSDPA Subtest 2	836.4	24	22.61	-1.39	20.31
Subtest 2	846.4	24	22.58	-1.42	20.28
	826.6	24	22.74	-1.26	20.41
HSDPA Subtest 3	836.4	24	22.71	-1.29	20.36
Subtest 5	846.4	24	22.68	-1.32	20.34
	826.6	24	22.65	-1.35	20.36
HSDPA Subtest 4	836.4	24	22.61	-1.39	20.33
Oublest 4	846.4	24	22.54	-1.46	20.31
	826.6	24	22.66	-1.34	20.28
HSUPA Subtest 1	836.4	24	22.61	-1.39	20.24
Cablest 1	846.4	24	22.57	-1.43	20.23
	826.6	24	22.65	-1.35	20.36
HSUPA Subtest 2	836.4	24	22.62	-1.38	20.31
Gastoot 2	846.4	24	22.58	-1.42	20.27
	826.6	24	22.74	-1.26	20.38
HSUPA Subtest 3	836.4	24	22.68	-1.32	20.36
	846.4	24	22.67	-1.33	20.31
	826.6	24	22.73	-1.27	20.38
HSUPA Subtest 4	836.4	24	22.71	-1.29	20.39
C C C C C C C C C C	846.4	24	22.67	-1.33	20.36
1101:54	826.6	24	22.66	-1.34	20.32
HSUPA Subtest 5	836.4	24	22.64	-1.36	20.27
	846.4	24	22.62	-1.38	20.24

Report No.: AGC02866150301FE02 Page 20 of 142

According to 3GPP 25.101 sub-clause 6.2.2 , the maximum output power is allowed to be reduced by following the table.

Table 6.1aA: UE maximum output power with HS-DPCCH and E-DCH

UE Transmit Channel Configuration	CM(db)	MPR(db)		
For all combinations of ,DPDCH,DPCCH	0≤ CM≤3.5	MAY(CM 1 O)		
HS-DPDCH,E-DPDCH and E-DPCCH	0≤ CIVI≤3.5	MAX(CM-1,0)		
Note: CM=1 for $\beta_c/\beta_d=12/15$. $\beta_{bs}/\beta_c=24/15$. For all other combinations of DPDCH, DPCCH.				

Note: CM=1 for β_c/β_d =12/15, β_{hs}/β_c =24/15.For all other combinations of DPDCH, DPCCH, HS-DPCCH, E-DPDCH and E-DPCCH the MPR is based on the relative CM difference.

Report No.: AGC02866150301FE02 Page 21 of 142

The device supports MPR to solve linearity issues (ACLR or SEM) due to the higher peak-to average ratios (PAR) of the HSUPA signal. This prevents saturating the full range of the TX DAC inside of device and provides a reduced power output to the RF transceiver chip according to the Cubic Metric (a function of the combinations of DPDCH, DPCCH, HS-DPCCH, E-DPDCH and E-DPCCH).

When E-DPDCH channels are present the beta gains on those channels are reduced firsts to try to get the power under the allowed limit. If the beta gains are lowered as far as possible, then a hard limiting is applied at the maximum allowed level.

The SW currently recalculates the cubic metric every time the beta gains on the E-DPDCH are reduced. The cubic metric will likely get lower each time this is done. However, there is no reported reduction of maximum output power in the HSUPA mode since the device also provides a compensate for the power back-off by increasing the gain of TX_AGC in the transceiver (PA) device.

The end effect is that the DUT output power is identical to the case where there is no MPR in the device.

Page 22 of 142

6.2 RADIATED OUTPUT POWER

6.2.1 MEASUREMENT METHOD

The measurements procedures specified in TIA-603C-2004 were applied.

- In an anechoic antenna test chamber, a half-wave dipole antenna for the frequency band of interest is placed at the reference centre of the chamber. An RF Signal source for the frequency band of interest is connected to the dipole with a cable that has been constructed to not interfere with the radiation pattern of the antenna. A known (measured) power (Pin) is applied to the input of the dipole, and the power received (Pr) at the chamber's probe antenna is recorded.
- 2 The substitution method is used. Substitution values at each frequency are measured before and saved to the test software. A "reference path loss" is established as ARpl=Pin + 2.15 Pr. The ARpl is the attenuation of "reference path loss", and including the gain of receive antenna, the cable loss and the air loss. The measurement results are obtained as described below: Power=PMea+ARpl
- 3 The EUT is substituted for the dipole at the reference centre of the chamber and a scan is performed to obtain the radiation pattern.
- 4 From the radiation pattern, the co-ordinates where the maximum antenna gain occurs are identified.
- 5 The EUT is then put into continuously transmitting mode at its maximum power level.
- Power mode measurements are performed with the receiving antenna placed at the coordinates determined in Step 3 to determine the output power as defined in Rule 24.232 (b) and (c). The "reference path loss" from Step1 is added to this result.
- 7 This value is EIRP since the measurement is calibrated using a half-wave dipole antenna of known gain (2.15 dBi) and known input power (Pin).
- 8 ERP can be calculated from EIRP by subtracting the gain of the dipole, ERP = EIRP -2.15dBi..

6.2.2 PROVISIONS APPLICABLE

This is the test for the maximum radiated power from the EUT. Rule Part 24.232(b) specifies, "Mobile/portable stations are limited to 2 watts e.i.r.p. Peak power" and 24.232(c) specifies that "Peak transmit power must be measured over any interval of continuous transmission using instrumentation calibrated in terms of an rms-equivalent voltage." Rule Part 22.913(a) specifies "Maximum ERP. The effective radiated power (ERP) of base transmitters and cellular repeaters must not exceed 500 Watts. The ERP of mobile transmitters and auxiliary test transmitters must not exceed 7 Watts."

Mode	Nominal Peak Power
GSM 850/EDGE	<=38.45 dBm (7W)
PCS 1900/EDGE	<=33 dBm (2W)
UMTS BAND II	<=33 dBm (2W)
UMTS BANDV	<=38.45 dBm (7W)

Report No.: AGC02866150301FE02 Page 23 of 142

6.2.3 MEASUREMENT RESULT

Radiated Power (ERP) for GSM 850/EDGE 8						
		Res	Result			
Mode	Frequency	Max. Peak ERP	Polarization	Conclusion		
		(dBm)	Of Max. ERP			
	824.2	30.82	Horizontal	Pass		
	836.6	30.77	Horizontal	Pass		
GSM850	848.8	30.73	Horizontal	Pass		
GSIVIOSU	824.2	28.65	Vertical	Pass		
	836.6	28.62	Vertical	Pass		
	848.8	28.57	Vertical	Pass		
	824.2	25.66	Horizontal	Pass		
	836.6	25.61	Horizontal	Pass		
EDCE	848.8	25.55	Horizontal	Pass		
EDGE	824.2	25.59	Vertical	Pass		
	836.6	25.45	Vertical	Pass		
	848.8	25.36	Vertical	Pass		

Radiated Power (E.I.R.P) for PCS 1900/EDGE 8						
		Res				
Mode	Frequency	Max. Peak	Polarization	Conclusion		
		E.I.R.P.(dBm)	Of Max. E.I.R.P.			
	1850.2	27.62	Horizontal	Pass		
	1880.0	27.57	Horizontal	Pass		
GSM 1900 -	1909.8	27.45	Horizontal	Pass		
G3W 1900 -	1850.2	26.66	Vertical	Pass		
	1880.0	26.61	Vertical	Pass		
	1909.8	26.55	Vertical	Pass		
	1850.2	24.56	Horizontal	Pass		
	1880.0	24.51	Horizontal	Pass		
EDGE -	1909.8	24.42	Horizontal	Pass		
EDGE	1850.2	23.78	Vertical	Pass		
	1880.0	23.67	Vertical	Pass		
Ī	1909.8	23.66	Vertical	Pass		

		Result		
Mode	Frequency	Max. Peak E.I.R.P	Polarization	
		(dBm)	Of Max. E.I.R.P	
	1852.6	21.59	Horizontal	Pass
	1880	21.47	Horizontal	Pass
RMC	1907.4	21.42	Horizontal	Pass
12.2kbps	1852.6	21.41	Vertical	Pass
	1880	21.36	Vertical	Pass
	1907.4	21.32	Vertical	Pass

Radiated Power (ERP) for UMTS band V						
		Re				
Mode	Frequency	Max. Peak ERP	Polarization	Conclusion		
		(dBm)	Of Max. E.I.R.P.			
	826.6	21.58	Horizontal	Pass		
	836.4	21.54	Horizontal	Pass		
RMC	846.4	21.51	Horizontal	Pass		
12.2kbps	826.6	21.39	Vertical	Pass		
	836.4	21.35	Vertical	Pass		
	846.4	21.32	Vertical	Pass		

Note: Above is worst mode data.

Page 25 of 142

6.3. PEAK-TO-AVERAGE RATIO

6.3.1 MEASUREMENT METHOD

Use one of the procedures presented in 4.1 to measure the total peak power and record as PPk. Use one of the applicable procedures presented 4.2 to measure the total average power and record as PAvg. Both the peak and average power levels must be expressed in the same logarithmic units (e.g., dBm). Determine the PAPR from:

PAPR (dB) = PPk (dBm) - PAvg (dBm).

6.3.2 PROVISIONS APPLICABLE

This is the test for the Peak-to-Average Ratio from the EUT.

Power Complementary Cumulative Distribution Function (CCDF) curves provide a means for characterizing the power peaks of a digitally modulated signal on a statistical basis. A CCDF curve depicts the probability of the peak signal amplitude exceeding the average power level. Most contemporary measurement instrumentation include the capability to produce CCDF curves for an input signal provided that the instrument's resolution bandwidth can be set wide enough to accommodate the entire input signal bandwidth. In measuring transmissions in this band using an average power technique, the peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

6.3.3 MEASUREMENT RESULT

Modes	GSM850(GSM)		
Channel	128	190	251
oname	(Low)	(Mid)	(High)
Frequency	824.2	836.6	848.8
(MHz)	024.2		
Peak-To-Average Ratio (dB)/GSM	1.33	1.31	1.34
Peak-To-Average Ratio (dB)/EDGE	1.27	1.26	1.24

Modes	PCS 1900 (GSM)			
Channel	512	661	810	
Gilainici	(Low)	(Mid)	(High)	
Frequency	1850.2	1880	1909.8	
(MHz)	1030.2	1000	1303.0	
Peak-To-Average Ratio (dB)/GSM	1.49	1.5	1.52	
Peak-To-Average Ratio (dB)/EDGE	1.34	1.3	1.35	

Report No.: AGC02866150301FE02 Page 26 of 142

Modes	UMTS BAND II			
Channel	9663	9800	9937	
- Chambo	(Low)	(Mid)	(High)	
Frequency	1852.6	1880	1907.4	
(MHz)	1032.0	1000	1007.4	
Peak-To-Average Ratio (dB)	2.16	2.17	2.19	

Modes	UMTS BAND V			
Channel	4358	4407	4457	
Shame	(Low)	(Mid)	(High)	
Frequency (MHz)	826.6	836.6	846.4	
Peak-To-Average Ratio (dB)	2.31	2.28	2.34	

Page 27 of 142

7. OCCUPIED BANDWIDTH

7.1 MEASUREMENT METHOD

The test set up and general procedure is similar to conducted peak output power test. Only different for setting the measurement configuration of the measuring instrument of Spectrum Analyzer.

7.2 PROVISIONS APPLICABLE

The emission bandwidth is defined as two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26dB below the transmitter power

Report No.: AGC02866150301FE02 Page 28 of 142

7.3 MEASUREMENT RESULT

APPENDIX A:BANDWIDTH

Test Results

Test	Test	Test	Occupied Bandwidth	Emission Bandwidth	Verdict	
Band	Mode	Channel	(KHZ)	(KHZ)	verdict	
		LCH	242.99	314.03	PASS	
	GSM	MCH	244.72	313.43	PASS	
GSM850		HCH	247.02	314.79	PASS	
		LCH	257.17	331.94	PASS	
	EDGE	MCH	258.31	324.78	PASS	
		HCH	254.95	325.75	PASS	

Test Band	Test	Test	Occupied Bandwidth	Emission Bandwidth	Verdict	
	Mode	Channel	(KHZ)	(KHZ)	verdict	
	GSM EDGE	LCH	245.58	317.50	PASS	
		MCH	242.84	313.17	PASS	
00144000		HCH	247.43	311.69	PASS	
GSM1900		LCH	249.88	317.62	PASS	
		MCH	248.69	306.41	PASS	
		HCH	248.12	303.27	PASS	

Report No.: AGC02866150301FE02 Page 29 of 142

For GSM

Test Band=GSM850


Test Mode=GSM

Test Channel=LCH




Report No.: AGC02866150301FE02 Page 30 of 142

Test Channel=MCH



Report No.: AGC02866150301FE02 Page 31 of 142

Test Channel=HCH



Report No.: AGC02866150301FE02 Page 32 of 142


Test Band=GSM850

Test Mode=EDGE Test Channel=LCH




Report No.: AGC02866150301FE02 Page 33 of 142

Test Channel=MCH



Report No.: AGC02866150301FE02 Page 34 of 142


Test Channel=HCH



Report No.: AGC02866150301FE02 Page 35 of 142


Test Band=GSM1900

Test Mode=GSM




Report No.: AGC02866150301FE02 Page 36 of 142

Test Channel=MCH




Report No.: AGC02866150301FE02 Page 37 of 142




Report No.: AGC02866150301FE02 Page 38 of 142


Test Mode=EDGE Test Channel=LCH



Report No.: AGC02866150301FE02 Page 39 of 142



Report No.: AGC02866150301FE02 Page 40 of 142



Report No.: AGC02866150301FE02 Page 41 of 142

Test Band	Test	Test	Occupied Bandwidth	Emission Bandwidth	Verdi
	Mode	Channel	(KHZ)	(KHZ)	ct
WCDMA8 50	UMTS	LCH	4151.8	4659	PASS
		MCH	4151.9	4669	PASS
		HCH	4137.7	4677	PASS


Test Band	Test	Test	Occupied Bandwidth	Emission Bandwidth	Verdi
	Mode	Channel	(KHZ)	(KHZ)	ct
WCDMA1 900	UMTS	LCH	4145.6	4676	PASS
		MCH	4143.6	4678	PASS
		HCH	4145.1	4697	PASS

Report No.: AGC02866150301FE02 Page 42 of 142


For WCDMA

Test Band=WCDMA850


Test Mode=UMTS



Report No.: AGC02866150301FE02 Page 43 of 142




Report No.: AGC02866150301FE02 Page 44 of 142




Report No.: AGC02866150301FE02 Page 45 of 142

Test Band=WCDMA1900


Test Mode=UMTS



Report No.: AGC02866150301FE02 Page 46 of 142



Report No.: AGC02866150301FE02 Page 47 of 142



Report No.: AGC02866150301FE02

Page 48 of 142

8. BAND EDGE

8.1 MEASUREMENT METHOD

The test set up and general procedure is similar to conducted peak output power test. Only different for setting the measurement configuration of the measuring instrument of Spectrum Analyzer.

8.2 PROVISIONS APPLICABLE

As Specified in FCC rules of 22.917(a) and 24.238(a)

Report No.: AGC02866150301FE02 Page 49 of 142

8.3 MEASUREMENT RESULT


APPENDIX B: BAND EDGES COMPLIANCE

Test Results


For GSM

Test Band=GSM850

Test Mode=GSM




Report No.: AGC02866150301FE02 Page 50 of 142




Report No.: AGC02866150301FE02 Page 51 of 142

Test Mode=EDGE Test Channel=LCH




Report No.: AGC02866150301FE02 Page 52 of 142




Report No.: AGC02866150301FE02 Page 53 of 142

Test Band=GSM1900

Test Mode=GSM
Test Channel=LCH




Report No.: AGC02866150301FE02 Page 54 of 142




Report No.: AGC02866150301FE02 Page 55 of 142

Test Mode=EDGE Test Channel=LCH



Report No.: AGC02866150301FE02 Page 56 of 142




Report No.: AGC02866150301FE02 Page 57 of 142

For WCDMA

Test Band=WCDMA850

Test Mode=UMTS




Report No.: AGC02866150301FE02 Page 58 of 142



Report No.: AGC02866150301FE02 Page 59 of 142

Test Band=WCDMA1900

Test Mode=UMTS Test Channel=LCH



Report No.: AGC02866150301FE02 Page 60 of 142



Report No.: AGC02866150301FE02 Page 61 of 142

9. SPURIOUS EMISSION

9.1 CONDUCTED SPURIOUS EMISSION

9.1.1 MEASUREMENT METHOD

The following steps outline the procedure used to measure the conducted emissions from the EUT.

- 1, Determine frequency range for measurements: From CFR 2.1057 the spectrum should be investigated from the lowest radio frequency generated in the equipment up to at least the 10th harmonic of the carrier frequency. For the equipment of PCS1900 band, this equates to a frequency range of 30 MHz to 19.1 GHz, data taken from 30 MHz to 20 GHz. For GSM 850, data taken from 30 MHz to 9 GHz.
- 2, Determine EUT transmit frequencies: the following typical channels were chosen to conducted emissions testing.

Typical Channels for testing of GSM 850/EDGE 8		
Channel	Frequency (MHz)	
128	824.2	
190	836.6	
251	848.8	

Typical Channels for testing of PCS 1900/EDGE 8		
Channel	Frequency (MHz)	
512	1850.2	
661	1880.0	
810	1909.8	

Typical Channels for testing of UMTS band II		
Channel	Frequency (MHz)	
9663	1852.6	
9800	1880	
9937	1907.4	

Typical Channels for testing of UMTS band V		
Channel	Frequency (MHz)	
4358	826.6	
4407	836.4	
4457	846.4	

Report No.: AGC02866150301FE02 Page 62 of 142

9.1.2 PROVISIONS APPLICABLE

On any frequency outside frequency band of the USPCS spectrum, the power of any emission shall be attenuated below the transmitter power (P, in Watts) by at least 43+10Log(P) dB. For all power levels +30 dBm to 0 dBm, this becomes a constant specification limit of -13 dBm.


9.1.3 MEASUREMENT RESULT

APPENDIX C: SPURIOUS EMISSION AT ANTENNA TERMINAL


Test Results

Test Band=GSM850


Test Mode=GSM




Report No.: AGC02866150301FE02




Report No.: AGC02866150301FE02 Page 64 of 142




Report No.: AGC02866150301FE02 Page 65 of 142



Report No.: AGC02866150301FE02 Page 66 of 142




Report No.: AGC02866150301FE02




Report No.: AGC02866150301FE02 Page 68 of 142


Test Mode=EDGE Test Channel=LCH




Report No.: AGC02866150301FE02




Report No.: AGC02866150301FE02 Page 70 of 142




Report No.: AGC02866150301FE02



Report No.: AGC02866150301FE02 Page 72 of 142








Report No.: AGC02866150301FE02 Page 74 of 142


Test Band=GSM1900

Test Mode=GSM
Test Channel=LCH













Report No.: AGC02866150301FE02 Page 78 of 142

Test Channel=MCH













Report No.: AGC02866150301FE02 Page 82 of 142

Test Channel=HCH













Report No.: AGC02866150301FE02 Page 86 of 142

Test Mode=EDGE













Report No.: AGC02866150301FE02 Page 90 of 142

Test Channel=MCH












Page 94 of 142


Test Channel=HCH



Report No.: AGC02866150301FE02 Page 95 of 142









Report No.: AGC02866150301FE02 Page 98 of 142

Test Band=WCDMA850


Test Mode=UMTS Test Channel=LCH






Report No.: AGC02866150301FE02 Page 100 of 142


Test Channel=MCH






Report No.: AGC02866150301FE02 Page 102 of 142

Test Channel=HCH








Report No.: AGC02866150301FE02 Page 104 of 142


Test Band=WCDMA1900

Test Mode=UMTS Test Channel=LCH













Report No.: AGC02866150301FE02 Page 108 of 142

Test Channel=MCH













Report No.: AGC02866150301FE02 Page 112 of 142

Test Channel=HCH









Note: 1. Below 30MHZ no Spurious found and The GSM modes is the worst condition.

2. As no emission found in standby or receive mode, no recording in this report.

Report No.: AGC02866150301FE02 Page 116 of 142


9.2 RADIATED SPURIOUS EMISSION

9.2.1 MEASUREMENT METHOD

The measurements procedures specified in TIA-603C-2004 were used for testing. The spectrum was scanned from 30 MHz to the 10th harmonic of the highest frequency generated within the equipment. The resolution bandwidth is set 1MHz as outlined in Part 24.238. The measurements were performed on all modes(GPRS/EGPRS 850, GPRS/EGPRS 1900, HSPA band II, HSPA band V) at 3 typical channels(the Top Channel, the Middle Channel and the Bottom Channel) for each band.


The procedure of radiated spurious emissions is as follows:

a) Pre-calibration With pre-calibration method, the Radiated Spurious Emissions(RSE) is calculated as, RSE=Rx(dBuV)+CL(dB)+SA(dB)+Gain(dBi)-107(dBuV to dBm) The SA is calibrated using following setup.



b) EUT was placed on a 0.8 meter high non-conductive stand at a 3 meter test distance from the receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the test item for emission measurements. The height of receiving antenna is 0.8m. The test setup refers to figure below. Detected emissions were maximized at each frequency by rotating the test item and adjusting the receiving antenna polarization. The radiated emission measurements of all non-harmonic and harmonics of the transmit frequency through the 10th harmonic were measured with peak detector and 1MHz bandwidth.

Report No.: AGC02866150301FE02 Page 117 of 142



Radiated emissions measurements were made only at the upper, middle, and lower carrier frequencies of the PCS 1900 band (1850.2 MHz, 1880 MHz and 1909.8 MHz), GSM850 band (824.2MHz, 836.6MHz, 848.8MHz), UMTS band II(1852.6MHz, 1880MHz, 1907.4MHz), UMTS band V(826.6MHz, 836.4MHz, 846.4MHz). It was decided that measurements at these three carrier frequencies would be sufficient to demonstrate compliance with emissions limits because it was seen that all the significant spurs occur well outside the band and no radiation was seen from a carrier in one block of any band into any of the other blocks.

The substitution method is used. Substitution values at each frequency are measured before and saved to the test software. A "reference path loss" is established and the A_{Rpl} is the attenuation of "reference path loss", and including the gain of receive antenna, the gain of the preamplifier, the cable loss and the air loss. The measurement results are obtained as described below: Power=P_{Mea}+A_{Rpl}

9.2.2 PROVISIONS APPLICABLE

(a) On any frequency outside a licensee's frequency block (e.g. A, D, B, etc.) within the USPCS spectrum, the power of any emission shall be attenuated below the transmitter power (P, in Watts) by at least 43+10Log(P) dB. The specification that emissions shall be attenuated below the transmitter power (P) by at least 43 + 10 log (P) dB, translates in the relevant power range (1 to 0.001 W) to -13 dBm. At 1 W the specified minimum attenuation becomes 43 dB and relative to a 30 dBm (1 W) carrier becomes a limit of -13 dBm. At 0.001 W (0 dBm) the minimum attenuation is 13 dB, which again yields a limit of -13 dBm. In this way a translation of the specification from relative to absolute terms is carried out.

Note: only result the worst condition of each test mode:

Report No.: AGC02866150301FE02 Page 118 of 142

9.2.3 MEASUREMENT RESULT

GSM 850:

The Worst Test Results for Channel 251/848.8 MHz												
Frequency(MHz)	Power(dBm)	ARpl (dBm)	PMea(dBm)	Limit (dBm)	Polarity							
1685.23	-41.62	-5.01	-46.63	-13.00	Horizontal							
2456.12	-42.48	-2.18	-44.66	-13.00	Vertical							
3645.78	-42.39	3.46	-38.93	-13.00	Vertical							
4536.58	-42.72	2.79	-39.93	-13.00	Horizontal							

GSM 850(EDGE 8):

The Worst Test Results for Channel 251/848.8 MHz													
Frequency(MHz)	Power(dBm)	ARpl (dBm)	PMea(dBm)	Limit(dBm)	Polarity								
1696.28	-46.61	-2.26	-48.87	-13.00	Horizontal								
2162.19	-46.37	-3.12	-49.49	-13.00	Vertical								
3645.78	-47.29	-1.74	-49.03	-13.00	Vertical								
9257.65	-45.32	8.46	-36.86	-13.00	Horizontal								

PCS 1900:

	The Worst Test Results for Channel 810/1909.8MHz												
Frequency(MHz)	Power(dBm)	ARpl (dBm)	PMea(dBm)	Limit (dBm)	Polarity								
1429.36	-43.19	-3.22	-46.41	-13.00	Vertical								
2563.47	-42.63	-0.24	-42.87	-13.00	Vertical								
3645.26	-44.48	3.98	-40.50	-13.00	Horizontal								
4563.56	-44.69	11.56	-33.13	-13.00	Vertical								
5689.25	-44.41	17.89	-26.52	-13.00	Horizontal								

Report No.: AGC02866150301FE02 Page 119 of 142

PCS 1900(EDGE 8):

	The Worst Test Results for Channel 810/1909.8MHz												
Frequency(MHz)	Power(dBm)	ARpl (dBm)	PMea(dBm)	Limit (dBm)	Polarity								
1430.15	-45.82	9.7	-36.12	-13.00	Vertical								
9367.91	-44.29	11.6	-32.69	-13.00	Vertical								
13356.68	-45.61	14.89	-30.72	-13.00	Horizontal								
15249.71	-44.48	13.87	-30.61	-13.00	Vertical								
17913.63	-47.61	19.76	-27.85	-13.00	Horizontal								

UMTS band II:

	The Worst Test Results for Channel 9938/1907.4MHz												
Frequency(MHz)	Power(dBm)	ARpl (dBm)	PMea(dBm)	Limit (dBm)	Polarity								
2000.00	-39.88	-2.25	-42.13	-13.00	Vertical								
9548.50	-40.42	-3.03	-43.45	-13.00	Horizontal								
13367.40	-41.76	-1.87	-43.63	-13.00	Horizontal								
15277.80	-41.39	8.52	-32.87	-13.00	Vertical								
17931.60	-41.44	18.7	-22.74	-13.00	Horizontal								

UMTS band V:

	The Worst Test Results for Channel 4458/846.4MHz												
Frequency(MHz)	Power(dBm)	ARpl (dBm) PMea(dBm)		Limit (dBm)	Polarity								
1598.26	-41.64	-2.26	-43.9	-13.00	Vertical								
2365.78	-41.38	-3.12	-44.5	-13.00	Horizontal								
4967.65	-42.32	-1.74	-44.06	-13.00	Horizontal								
6457.86	-42.49	8.74	-33.75	-13.00	Vertical								
7896.56	-43.73	17.89	-25.84	-13.00	Horizontal								

Note: ARpl= Factor=Antenna Factor+ Cable loss-Amplifier gain.

The "Factor" value can be calculated automatically by software of measurement system.

Below 30MHZ no Spurious found and The GSM modes is the worst condition.

Page 120 of 142

10. MAINS CONDUCTED EMISSION

10.1 MEASUREMENT METHOD

The measurement procedure specified in ANSI C63.4-2003 was used for testing. Conducted Emission was measured with travel charger.

10.2 PROVISIONS APPLICABLE

Frequency of Emission (MHz)	Conducted Limit(dBuV)					
	Quasi-Peak	Average				
0.15 – 0.5	66 to 56 *	56 to 46 *				
0.5 – 5	56	46				
5 – 30	60	50				
*Decreases with the logarithm of the frequency.						

^{*}The lower limit shall apply at the transition frequency.

Note: The GSM850 mode is the worst condition and the test result as following:

Page 121 of 142

10.3 MEASUREMENT RESULT

LINE CONDUCTED EMISSION - L

Job No.: 20150422 Date: 2015-4-22 Company: Time: 18:26:50


Standard: FCC Class B Conduction(QP) Temp.(C)/Hum.(%): 26(C) / 60 %

Test item: Conduction Test EUT:

Line: L1 Test Voltage AC 120V/60Hz

Model: Freedom Test By :

Description: Call



No.	No. Freq.		Reading_Level (dBuV)		Correct Factor	Measurement (dBuV)		Limit (dBuV)			Margin (dB)		Comment	
	(MHz)	Peak	QP	AVG	dB	Peak	QP	AVG	QP	AVG	QP	AVG		
1	0.1780	30.18		18.34	10.19	40.37		28.53	64.57	54.57	-24.20	-26.04	Р	
2	0.4940	29.31		14.29	10.40	39.71		24.69	56.10	46.10	-16.39	-21.41	Р	
3	1.3340	29.01		16.30	10.38	39.39		26.68	56.00	46.00	-16.61	-19.32	Р	
4	3.1420	37.65		22.44	10.54	48.19		32.98	56.00	46.00	-7.81	-13.02	Р	
5	8.0180	23.03		7.45	10.35	33.38		17.80	60.00	50.00	-26.62	-32.20	Р	
6	29.1140	26.78		15.26	10.12	36.90		25.38	60.00	50.00	-23.10	-24.62	Р	

LINE CONDUCTED EMISSION - N

Job No.: 20150422 Date: 2015-4-22

Company: Time: 18:29:38


Standard: FCC Class B Conduction(QP) Temp.(C)/Hum.(%): 26(C) / 60 %

Test item: Conduction Test EUT:

Line: N Test Voltage AC 120V/60Hz

Model: Freedom ... Test By :

Description: Call



No.	No. Freq.		Reading_Level (dBuV)		Correct Factor	Measurement (dBuV)		Limit (dBuV)		Margin (dB)		P/F	Comment	
	(MHz)	Peak	QP	AVG	dB	Peak	QP	AVG	QP	AVG	QP	AVG		
1	0.1580	35.82		11.13	10.17	45.99		21.30	65.56	55.56	-19.57	-34.26	Р	
2	0.3260	29.44		11.77	10.30	39.74		22.07	59.55	49.55	-19.81	-27.48	Р	
3	0.8420	29.12		12.47	10.33	39.45		22.80	56.00	46.00	-16.55	-23.20	Р	
4	1.9180	29.31		15.26	10.25	39.56		25.51	56.00	46.00	-16.44	-20.49	Р	
5	3.1780	37.53		20.29	10.54	48.07		30.83	56.00	46.00	-7.93	-15.17	Р	
6	29.1140	20.73		9.47	10.12	30.85		19.59	60.00	50.00	-29.15	-30.41	Р	

Note: The GSM850 mode is the worst condition.

Page 123 of 142

11. FREQUENCY STABILITY

11.1 MEASUREMENT METHOD

In order to measure the carrier frequency under the condition of AFC lock, it is necessary to make measurements with the EUT in a "call mode". This is accomplished with the use of R&S CMU200 DIGITAL RADIO COMMUNICATION TESTER.

- 1 , Measure the carrier frequency at room temperature.
- 2 , Subject the EUT to overnight soak at -10℃.
- 3 , With the EUT, powered via nominal voltage, connected to the CMU200 and in a simulated call on channel 661 for PCS 1900 band , channel 190 for GSM 850 band, channel 9400 for UMTS band II and channel 4175 for UMTS band V measure the carrier frequency. These measurements should be made within 2 minutes of Powering up the EUT, to prevent significant self-warming.
- 4 , Repeat the above measurements at 10° C increments from -10°C to +55°C. Allow at least 1 1/2 hours at each temperature, unpowered, before making measurements.
- 5 , Re-measure carrier frequency at room temperature with nominal voltage. Vary supply voltage from minimum voltage to maximum voltage, in 0.1Volt increments re-measuring carrier frequency at each voltage. Pause at nominal voltage for 1 1/2 hours unpowered, to allow any self-heating to stabilize, before continuing.
- 6 , Subject the EUT to overnight soak at +55°C.
- 7 , With the EUT, powered via nominal voltage, connected to the CMU200 and in a simulated call on the centre channel, measure the carrier frequency. These measurements should be made within 2 minutes of Powering up the EUT, to prevent significant self-warming.
- 8 , Repeat the above measurements at 10° C increments from +55 $^{\circ}$ C to -10 $^{\circ}$ C. Allow at least 1 1/2 hours at each temperature, unpowered, before making measurements.
- 9 , At all temperature levels hold the temperature to +/- 0.5℃ during the measurement procedure.

11.2 PROVISIONS APPLICABLE

11.2.1 For Hand carried battery powered equipment

According to the JTC standard the frequency stability of the carrier shall be accurate to within 0.1 ppm of the received frequency from the base station. This accuracy is sufficient to meet Sec. 24.235, Frequency Stability. The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. As this transceiver is considered "Hand carried, battery powered equipment" Section 2.1055(d)(2) applies. This requires that the lower voltage for frequency stability testing be specified by the manufacturer. This transceiver is specified to operate with an input voltage of between 6.3VDC and 8.5VDC, with a nominal voltage of 7.4VDC. Operation above or below these voltage limits is prohibited by transceiver software in order to prevent improper operation as well as to protect components from overstress. These voltages represent a tolerance of -10 % and +12.5 %. For the purposes of measuring frequency stability these voltage limits are to be used.

Page 124 of 142

11.2.2 For equipment powered by primary supply voltage

According to the JTC standard the frequency stability of the carrier shall be accurate to within 0.1 ppm of the received frequency from the base station. This accuracy is sufficient to meet Sec. 24.235, Frequency Stability. The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. For this EUT section 2.1055(d)(1) applies. This requires varying primary supply voltage from 85 to 115 percent of the nominal value for other than hand carried battery equipment, the normal environment temperature is 20°C.

Report No.: AGC02866150301FE02 Page 125 of 142

11.3 MEASUREMENT RESULT

Appendix D:Frequency Stability

Test Results

Frequency Error vs. Voltage:

Test	Test	Test	Test	Test	Freq.Error	Freq.vs.rated	Limit	\/a ==!: a4
Band	Mode	Channel	Temp.	Volt.(V)	(Hz)	(ppm)	(ppm)	Verdict
			TN	3.4	-16.34	-0.02	±2.5	PASS
		LCH M MCH	TN	3.7	-17.05	-0.02	±2.5	PASS
			TN	4.2	-13.24	-0.02	±2.5	PASS
			TN	3.4	-18.08	-0.02	±2.5	PASS
GSM850	GSM		TN	3.7	-13.30	-0.02	±2.5	PASS
			TN	4.2	-17.95	-0.02	±2.5	PASS
			TN	3.4	-11.04	-0.01	±2.5	PASS
		HCH	TN	3.7	-12.85	-0.02	±2.5	PASS
			TN	4.2	-14.98	-0.02	±2.5	PASS

Test	Test	Test	Test	Test	Freq.Error	Freq.vs.rated	Limit	Verdict
Band	Mode	Channel	Temp.	Volt.	(Hz)	(ppm)	(ppm)	
				(V)				
			TN	3.4	-15.95	-0.02	±2.5	PASS
		LCH	TN	3.7	-15.46	-0.02	±2.5	PASS
			TN	4.2	-18.73	-0.02	±2.5	PASS
			TN	3.4	-13.59	-0.02	±2.5	PASS
GSM850	EDGE	MCH	TN	3.7	-15.79	-0.02	±2.5	PASS
			TN	4.2	-12.95	-0.02	±2.5	PASS
			TN	3.4	-10.59	-0.01	±2.5	PASS
		HCH	TN	3.7	-13.08	-0.02	±2.5	PASS
			TN	4.2	-15.01	-0.02	±2.5	PASS

Test	Test	Test	Test	Test	Freq.Error	Freq.vs.rated	Limit	Verdict
Band	Mode	Channel	Temp.	Volt.	(Hz)	(ppm)	(ppm)	
				(V)				
			TN	3.4	15.95	0.01	±2.5	PASS
		LCH	TN	3.7	11.82	0.01	±2.5	PASS
			TN	4.2	22.54	0.01	±2.5	PASS
		SM MCH	TN	3.4	14.98	0.01	±2.5	PASS
GSM1900	GSM		TN	3.7	26.15	0.01	±2.5	PASS
			TN	4.2	8.46	0.00	±2.5	PASS
			TN	3.4	22.34	0.01	±2.5	PASS
		нсн	TN	3.7	-14.46	-0.01	±2.5	PASS
			TN	4.2	18.98	0.01	±2.5	PASS

Test	Test	Test	Test	Test	Freq.Error	Freq.vs.rated	Limit	Verdict
Band	Mode	Channel	Temp.	Volt.	(Hz)	(ppm)	(ppm)	
				(V)				
			TN	3.4	-12.91	-0.01	±2.5	PASS
		LCH	TN	3.7	-20.05	-0.01	±2.5	PASS
	EDGE		TN	4.2	19.57	0.01	±2.5	PASS
			TN	3.4	-17.34	-0.01	±2.5	PASS
GSM1900		MCH	TN	3.7	-16.30	-0.01	±2.5	PASS
			TN	4.2	16.24	0.01	±2.5	PASS
			TN	3.4	-14.17	-0.01	±2.5	PASS
		HCH	TN	3.7	-17.11	-0.01	±2.5	PASS
			TN	4.2	17.43	0.01	±2.5	PASS

Report No.: AGC02866150301FE02 Page 127 of 142

Frequency Error vs. Temperature:

Test	Test	Test	Test	Test	Freq.Error	Freq.vs.rated	Limit	Verdict
Band	Mode	Channe	Volt.	Temp	(Hz)	(ppm)	(ppm	
		1)	
			VN	-10	-13.62	-0.02	±2.5	PASS
			VN	0	-13.50	-0.02	±2.5	PASS
			VN	10	-16.72	-0.02	±2.5	PASS
GSM850	GSM	LCH	VN	20	-12.20	-0.01	±2.5	PASS
			VN	30	-10.01	-0.01	±2.5	PASS
			VN	40	-12.40	-0.02	±2.5	PASS
			VN	50	-15.11	-0.02	±2.5	PASS
			VN	-10	-14.66	-0.02	±2.5	PASS
			VN	0	-15.76	-0.02	±2.5	PASS
			VN	10	-10.46	-0.01	±2.5	PASS
GSM850	GSM	MCH	VN	20	-17.89	-0.02	±2.5	PASS
			VN	30	-11.95	-0.01	±2.5	PASS
			VN	40	-11.36	-0.01	±2.5	PASS
			VN	50	-11.95	-0.01	±2.5	PASS
			VN	-10	-15.05	-0.02	±2.5	PASS
			VN	0	-10.53	-0.01	±2.5	PASS
			VN	10	-10.53	-0.01	±2.5	PASS
GSM850	GSM	HCH	VN	20	-10.07	-0.01	±2.5	PASS
			VN	30	-14.53	-0.02	±2.5	PASS
			VN	40	-13.69	-0.02	±2.5	PASS
			VN	50	-17.43	-0.02	±2.5	PASS

Test	Test	Test	Test	Test	Freq.Error	Freq.vs.rated	Limit	Verdict
Band	Mode	Channe	Volt.	Temp	(Hz)	(ppm)	(ppm	
		1)	
			VN	-10	-17.76	-0.02	±2.5	PASS
			VN	0	-17.60	-0.02	±2.5	PASS
			VN	10	-11.01	-0.01	±2.5	PASS
GSM850	EDGE	LCH	VN	20	-18.31	-0.02	±2.5	PASS
			VN	30	-14.88	-0.02	±2.5	PASS
			VN	40	-15.92	-0.02	±2.5	PASS
			VN	50	-10.62	-0.01	±2.5	PASS
			VN	-10	-7.46	-0.01	±2.5	PASS
			VN	0	-9.33	-0.01	±2.5	PASS
			VN	10	-17.18	-0.02	±2.5	PASS
GSM850	EDGE	MCH	VN	20	-10.69	-0.01	±2.5	PASS
			VN	30	-8.20	-0.01	±2.5	PASS
			VN	40	-7.75	-0.01	±2.5	PASS
			VN	50	-13.75	-0.02	±2.5	PASS
			VN	-10	-11.78	-0.01	±2.5	PASS
			VN	0	-15.43	-0.02	±2.5	PASS
			VN	10	-15.69	-0.02	±2.5	PASS
GSM850	EDGE	HCH	VN	20	-7.23	-0.01	±2.5	PASS
			VN	30	-9.98	-0.01	±2.5	PASS
			VN	40	-9.49	-0.01	±2.5	PASS
			VN	50	-11.33	-0.01	±2.5	PASS

Test	Test	Test	Test	Test	Freq.Error	Freq.vs.rated	Limit	Verdict
Band	Mode	Channel	Volt.	Temp.	(Hz)	(ppm)	(ppm)	
			VN	-10	21.50	0.01	±2.5	PASS
			VN	0	22.28	0.01	±2.5	PASS
			VN	10	23.76	0.01	±2.5	PASS
GSM1900	GSM	LCH	VN	20	23.76	0.01	±2.5	PASS
			VN	30	26.80	0.01	±2.5	PASS
			VN	40	11.30	0.01	±2.5	PASS
			VN	50	25.05	0.01	±2.5	PASS
			VN	-10	18.34	0.01	±2.5	PASS
			VN	0	23.37	0.01	±2.5	PASS
			VN	10	12.72	0.01	±2.5	PASS
GSM1900	GSM	MCH	VN	20	9.49	0.01	±2.5	PASS
			VN	30	14.66	0.01	±2.5	PASS
			VN	40	22.79	0.01	±2.5	PASS
			VN	50	22.02	0.01	±2.5	PASS
			VN	-10	22.28	0.01	±2.5	PASS
			VN	0	22.21	0.01	±2.5	PASS
			VN	10	24.86	0.01	±2.5	PASS
GSM1900	GSM	HCH	VN	20	23.83	0.01	±2.5	PASS
			VN	30	28.09	0.01	±2.5	PASS
			VN	40	28.22	0.01	±2.5	PASS
			VN	50	15.30	0.01	±2.5	PASS

Test	Test	Test	Test	Test	Freq.Error	Freq.vs.rated	Limit	Verdict
Band	Mode	Channel	Volt.	Temp.	(Hz)	(ppm)	(ppm)	
			VN	-10	-16.30	-0.01	±2.5	PASS
			VN	0	-9.20	0.00	±2.5	PASS
			VN	10	-17.14	-0.01	±2.5	PASS
GSM1900	EDGE	LCH	VN	20	11.27	0.01	±2.5	PASS
			VN	30	-10.43	-0.01	±2.5	PASS
			VN	40	10.17	0.01	±2.5	PASS
			VN	50	-12.85	-0.01	±2.5	PASS
			VN	-10	-8.94	0.00	±2.5	PASS
			VN	0	-14.75	-0.01	±2.5	PASS
			VN	10	-16.34	-0.01	±2.5	PASS
GSM1900	EDGE	MCH	VN	20	13.40	0.01	±2.5	PASS
			VN	30	16.01	0.01	±2.5	PASS
			VN	40	-13.40	-0.01	±2.5	PASS
			VN	50	-13.79	-0.01	±2.5	PASS
			VN	-10	6.07	0.00	±2.5	PASS
			VN	0	15.50	0.01	±2.5	PASS
			VN	10	-12.62	-0.01	±2.5	PASS
GSM1900	EDGE	HCH	VN	20	6.78	0.00	±2.5	PASS
			VN	30	11.40	0.01	±2.5	PASS
			VN	40	16.56	0.01	±2.5	PASS
			VN	50	21.11	0.01	±2.5	PASS

Report No.: AGC02866150301FE02 Page 131 of 142

Frequency Error vs. Voltage:

Test	Test	Test	Test	Test	Freq.Error	Freq.vs.rated	Limit	Verdict
Band	Mode	Channe	Temp.	Volt.	(Hz)	(ppm)	(ppm	
		I		(V))	
			TN	3.4	14.42	0.02	±2.5	PASS
	UMTS	LCH	TN	3.7	14.88	0.02	±2.5	PASS
			TN	4.2	11.90	0.01	±2.5	PASS
WCDMA			TN	3.4	12.13	0.01	±2.5	PASS
850		MCH	TN	3.7	14.88	-0.01	±2.5	PASS
830			TN	4.2	13.73	0.02	±2.5	PASS
			TN	3.4	13.28	0.02	±2.5	PASS
		HCH	TN	3.7	14.88	0.02	±2.5	PASS
			TN	4.2	9.16	0.01	±2.5	PASS

Test	Test	Test	Test	Test	Freq.Error	Freq.vs.rated	Limit	Verdict
Band	Mode	Channe	Temp.	Volt.	(Hz)	(ppm)	(ppm	
		1		(V))	
			TN	3.4	40.28	0.02	±2.5	PASS
	UMTS	LCH	TN	3.7	29.53	0.02	±2.5	PASS
			TN	4.2	32.50	0.02	±2.5	PASS
WCDMA			TN	3.4	28.84	0.02	±2.5	PASS
1900		MCH	TN	3.7	29.53	0.02	±2.5	PASS
1900			TN	4.2	42.57	0.02	±2.5	PASS
			TN	3.4	3419.04	1.79	±2.5	PASS
		HCH	TN	3.7	29.53	2.17	±2.5	PASS
			TN	4.2	3412.63	1.79	±2.5	PASS

Report No.: AGC02866150301FE02 Page 132 of 142

Frequency Error vs. Temperature:

Test	Test	Test	Test	Test	Freq.Error	Freq.vs.rated	Limit	Verdict
Band	Mode	Channe	Volt.	Temp	(Hz)	(ppm)	(ppm	
		1)	
			VN	-10	10.76	0.01	±2.5	PASS
			VN	0	7.32	0.01	±2.5	PASS
WCDMA			VN	10	16.02	0.02	±2.5	PASS
850	UMTS	LCH	VN	20	8.70	0.01	±2.5	PASS
650			VN	30	10.53	0.01	±2.5	PASS
			VN	40	9.61	0.01	±2.5	PASS
			VN	50	15.56	0.02	±2.5	PASS
			VN	-10	7.78	0.01	±2.5	PASS
			VN	0	14.19	0.02	±2.5	PASS
WCDMA			VN	10	13.05	0.02	±2.5	PASS
850	UMTS	MCH	VN	20	20.83	0.02	±2.5	PASS
650			VN	30	13.50	0.02	±2.5	PASS
			VN	40	16.94	0.02	±2.5	PASS
			VN	50	17.17	0.02	±2.5	PASS
			VN	-10	15.11	0.02	±2.5	PASS
			VN	0	13.28	0.02	±2.5	PASS
MCDMA			VN	10	16.94	0.02	±2.5	PASS
WCDMA 850	UMTS	HCH	VN	20	9.61	0.01	±2.5	PASS
050			VN	30	8.01	0.01	±2.5	PASS
			VN	40	13.73	0.02	±2.5	PASS
			VN	50	13.50	0.02	±2.5	PASS

Test	Test	Test	Test	Test	Freq.Error	Freq.vs.rated	Limit	Verdict
Band	Mode	Channe	Volt.	Temp	(Hz)	(ppm)	(ppm	
		1)	
			VN	-10	23.80	0.01	±2.5	PASS
			VN	0	31.13	0.02	±2.5	PASS
WCDMA			VN	10	35.02	0.02	±2.5	PASS
1900	UMTS	LCH	VN	20	36.85	0.02	±2.5	PASS
1900			VN	30	26.09	0.01	±2.5	PASS
			VN	40	40.51	0.02	±2.5	PASS
			VN	50	39.37	0.02	±2.5	PASS
	UMTS		VN	-10	40.28	0.02	±2.5	PASS
			VN	0	45.78	0.02	±2.5	PASS
WCDMA			VN	10	41.89	0.02	±2.5	PASS
1900		MCH	VN	20	41.20	0.02	±2.5	PASS
1900			VN	30	41.43	0.02	±2.5	PASS
			VN	40	38.45	0.02	±2.5	PASS
			VN	50	53.79	0.03	±2.5	PASS
			VN	-10	41.72	0.02	±2.5	PASS
			VN	0	34.34	0.02	±2.5	PASS
MCDMA			VN	10	34.62	0.02	±2.5	PASS
WCDMA 1900	UMTS	HCH	VN	20	34.75	0.02	±2.5	PASS
1900			VN	30	34.53	0.02	±2.5	PASS
			VN	40	41.70	0.02	±2.5	PASS
			VN	50	34.82	0.02	±2.5	PASS


Report No.: AGC02866150301FE02 Page 134 of 142

PHOTOGRAPHS OF TEST SETUP

CONDUCTED EMISSION



RADIATED SPURIOUS EMISSION



CONDUCTED MEASUREMENTS



Report No.: AGC02866150301FE02 Page 136 of 142

PHOTOGRAPHS OF EUT

TOTAL VIEW OF EUT



TOP VIEW OF EUT



Report No.: AGC02866150301FE02 Page 137 of 142

BOTTOM VIEW OF EUT



FRONT VIEW OF EUT



Report No.: AGC02866150301FE02 Page 138 of 142

BACK VIEW OF EUT



LEFT VIEW OF EUT



Report No.: AGC02866150301FE02 Page 139 of 142

RIGHT VIEW OF EUT




OPEN VIEW OF EUT-1




Report No.: AGC02866150301FE02 Page 140 of 142

OPEN VIEW OF EUT-2



OPEN VIEW OF EUT-3




Report No.: AGC02866150301FE02 Page 141 of 142

OPEN VIEW OF EUT-4




INTERNAL VIEW OF EUT-1



Report No.: AGC02866150301FE02 Page 142 of 142

INTERNAL VIEW OF EUT-2



----END OF REPORT----