



RF Exposure Evaluation Report

APPLICANT : Octonion SA
EQUIPMENT : Piq Sensor Device
BRAND NAME : Piq
MODEL NAME : Piq Sensor Device v1
MARKETING NAME : Piq
FCC ID : 2AEJC-PIQ1
STANDARD : 47 CFR Part 2.1093
FCC KDB 447498 D01 v05r02

We, SPORTON INTERNATIONAL INC., would like to declare that the device has been evaluated in accordance with 47 CFR Part 2.1093 and pass the limit. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.

Reviewed by: Eric Huang / Deputy Manager



Approved by: Jones Tsai / Manager

SPORTON INTERNATIONAL INC.
No.52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan District, Taoyuan City, Taiwan (R.O.C.)



Table of Contents

1.	Administration Data	3
2.	General Information	3
2.1	Description of Device Under Test (DUT)	3
3.	Maximum RF output power among production units.....	3
4.	RF Exposure Evaluation.....	4

Revision History

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FA541402	Rev. 01	Initial issue of report	Sep. 08, 2015



1. Administration Data

Testing Laboratory	
Test Site	SPORTON INTERNATIONAL INC.
Test Site Location	No.52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan District, Taoyuan City, Taiwan (R.O.C.) TEL: +886-3-327-3456 FAX: +886-3-328-4978

Applicant	
Company Name	Octonion SA
Address	EPFL Innovation Park Batiment C, 1015 Lausanne Switzerland

Manufacturer	
Company Name	FIH Mobile Limited
Address	No.4, Minsheng St., Tucheng Dist., New Taipei City 23679, Taiwan (R.O.C.)/ 23679

2. General Information

2.1 Description of Device Under Test (DUT)

Product Feature & Specification	
DUT Type	Piq Sensor Device
Brand Name	Piq
Model Name	Piq Sensor Device v1
Marketing Name	Piq
FCC ID	2AEJC-PIQ1
Wireless Technology and Frequency Range	Bluetooth: 2402 MHz ~ 2480 MHz
Mode	• Bluetooth v4.0-LE
Antenna Type	Chip Antenna
HW Version	SU2
DUT Stage	Identical Prototype

Remark: The above DUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

3. Maximum RF output power among production units

Mode / Band	Average Power (dBm)
	Bluetooth v4.0 with LE
2.4 GHz Band	3



4. RF Exposure Evaluation

Bluetooth Max Power (dBm)	mW	Separation Distance (mm)	Frequency (GHz)	Exclusion Thresholds
3	2.00	5	2.48	0.63

Note:

1. Per KDB 447498 D01v05r02, the 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at *test separation distances* \leq 50 mm are determined by:

$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for}$$

1-g SAR and \leq 7.5 for 10-g extremity SAR

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

Conclusion: Per KDB 447498 D01v05r02, when the minimum test separation distance is $<$ 5 mm, a distance of 5 mm is applied to determine SAR test exclusion. The test exclusion threshold is 0.63 which is \leq 3, SAR testing is not required.