

# RADIO TEST REPORT FCC ID: 2AEJL-ATLANTIS

**Product:** Atlantis

Trade Mark: N/A

Model No.: 201702hxatwg

Serial Model: N/A

**Report No.:** NTEK-2017NT03061803F2

**Issue Date:** 24 Mar. 2017

# **Prepared for**

Hallmark Global LTD. dba HEXA.
Suite 1801 1 Yonge Street, Toronto Ontario, Canada, M5E1W7

# Prepared by

NTEK TESTING TECHNOLOGY CO., LTD.

1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street Bao'an District, Shenzhen P.R. China

Tel.: +86-755-6115 6588 Fax.: +86-755-6115 6599 Website:http://www.ntek.org.cn



# **TABLE OF CONTENTS**

1	TEST RESULT CERTIFICATION	3
2	SUMMARY OF TEST RESULTS	4
3	FACILITIES AND ACCREDITATIONS	5
_	3.1 FACILITIES	5
_	3.2 LABORATORY ACCREDITATIONS AND LISTINGS	
4	GENERAL DESCRIPTION OF EUT	
5	DESCRIPTION OF TEST MODES	8
6	SETUP OF EQUIPMENT UNDER TEST	9
6	6.1 BLOCK DIAGRAM CONFIGURATION OF TEST SYSTEM	
-	6.2 SUPPORT EQUIPMENT	10
6		
7	TEST REQUIREMENTS	13
7	7.1 CONDUCTED EMISSIONS TEST	13
7	7.2 RADIATED SPURIOUS EMISSION	
7	7.3 6DB BANDWIDTH	
•	7.4 PEAK OUTPUT POWER	
	7.5 POWER SPECTRAL DENSITY	
	7.6 CONDUCTED BAND EDGE MEASUREMENT	
	7.7 SPURIOUS RF CONDUCTED EMISSIONS	
7	7.8 ANTENNA APPLICATION	43



# 1 TEST RESULT CERTIFICATION

Applicant's name:	Hallmark Global LTD. dba HEXA.		
Address:	Suite 1801 1 Yonge Street, Toronto Ontario, Canada, M5E1W7		
Manufacturer's Name:	Hallmark Global LTD. dba HEXA.		
Address	Suite 1801 1 Yonge Street, Toronto Ontario, Canada, M5E1W7		
Product description			
Product name:	Atlantis		
Model and/or type reference:	201702hxatwg		
Serial Model:	N/A		

#### Measurement Procedure Used:

APPLICABLE STANDARDS				
APPLICABLE STANDARD/ TEST PROCEDURE	TEST RESULT			
FCC 47 CFR Part 2, Subpart J:2016				
FCC 47 CFR Part 15, Subpart C:2016				
KDB 174176 D01 Line Conducted FAQ v01r01	Complied			
ANSI C63.10-2013				
FCC KDB 558074 D01 DTS Meas Guidance v03r05				

This device described above has been tested by NTEK Testing Technology Co., Ltd., and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of NTEK Testing Technology Co., Ltd., this document may be altered or revised by NTEK Testing Technology Co., Ltd., personnel only, and shall be noted in the revision of the document.

The test results of this report relate only to the tested sample identified in this report.

Date of Test	:	06 Mar. 2017 ~ 24 Mar. 2017	
Testing Engineer	:	Eileen Wu.	
		(Eileen Liu)	
Technical Manager	į	Jason chen	
ŭ	_	(Jason Chen)	
		Sam. Chen	
Authorized Signatory	:	ATACINET WAS INDEED	
		(Sam Chen)	



# 2 SUMMARY OF TEST RESULTS

FCC Part15 (15.247), Subpart C					
Standard Section	Verdict	Remark			
15.207	Conducted Emission	PASS			
15.247 (a)(2)	6dB Bandwidth	PASS			
15.247 (b)	Peak Output Power	PASS			
15.247 (c)	Radiated Spurious Emission	PASS			
15.247 (d)	Power Spectral Density	PASS			
15.205	Band Edge Emission	PASS			
15.203	Antenna Requirement	PASS			

#### Remark:

- 1. "N/A" denotes test is not applicable in this Test Report.
- 2. All test items were verified and recorded according to the standards and without any deviation during the test.
- This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.



# 3 FACILITIES AND ACCREDITATIONS

#### 3.1 FACILITIES

All measurement facilities used to collect the measurement data are located at 1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street Bao'an District, Shenzhen 518126 P.R. China

The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.10 and CISPR Publication 22.

#### 3.2 LABORATORY ACCREDITATIONS AND LISTINGS

Site Description

EMC Lab. : Accredited by CNAS, 2014.09.04

The certificate is valid until 2017.09.03

The Laboratory has been assessed and proved to be in compliance with

CNAS-CL01:2006 (identical to ISO/IEC 17025:2005) The Certificate Registration Number is L5516.

Accredited by Industry Canada, August 29, 2012

The Certificate Registration Number is 9270A-1.

Accredited by FCC, September 6, 2013

The Certificate Registration Number is 238937.

Name of Firm : NTEK Testing Technology Co., Ltd

Site Location : 1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang

Street, Bao'an District, Shenzhen P.R. China.

#### 3.3 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement y±U, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of k=2, providing a level of confidence of approximately 95 %.

No.	Item	Uncertainty
1	Conducted Emission Test	±1.38dB
2	RF power, conducted	±0.16dB
3	Spurious emissions, conducted	±0.21dB
4	All emissions, radiated(<1G)	±4.68dB
5	All emissions, radiated(>1G)	±4.89dB
6	Temperature	±0.5°C
7	Humidity	±2%



# 4 GENERAL DESCRIPTION OF EUT

Product Feature and Specification				
Equipment Atlantis				
Trade Mark N/A				
FCC ID 2AEJL-ATLANTIS				
Model No.	201702hxatwg			
Serial Model	N/A			
Model Difference	N/A			
Operating Frequency	2402MHz~2480MHz			
Modulation GFSK				
Number of Channels 40 Channels				
Bluetooth Version BT V4.0(EDR+BLE)				
Antenna Type FPCB Antenna				
Antenna Gain	1 dBi			
Rating(s)	DC 3.7V from battery or DC 5V from adapter			
	☑DC supply: DC 3.7V, 3900mAh			
Power supply	☐Adapter supply:  Model:PS10J050K2000UU  Input:100-240V 50/60Hz 0.35A  Output:DC 5V, 2000mA			
HW Version M80HR110				
SW Version MRA58K dev-keys				

Note: Based on the application, features, or specification exhibited in User's Manual, the EUT is considered as an ITE/Computing Device. More details of EUT technical specification, please refer to the User's Manual.



# **Revision History**

Report No.	Version	Description	Issued Date
NTEK-2017NT03061803F2	Rev.01	Initial issue of report	Mar 24, 2017



#### 5 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

The Transmitter was operated in the normal operating mode. The TX frequency was fixed which was for the purpose of the measurements.

Test of channel included the lowest and middle and highest frequency to perform the test, then record on this report.

Those data rates (1Mbps for GFSK modulation) were used for all test.

The EUT was pretested with 3 orientations placed on the table for the radiated emission measurement –X, Y, and Z-plane. The X-plane results were found as the worst case and were shown in this report.

Carrier Frequency and Channel list:

Channel	Frequency(MHz)
0	2402
1	2404
19	2440
20	2442
	•••
38	2478
39	2480

Note: fc=2402MHz+k×2MHz k=0 to 39

The following summary table is showing all test modes to demonstrate in compliance with the standard.

Test Cases				
Toot Itom	Data Rate/ Modulation			
Test Item Bluetooth 4.0_LE / GFSK	Bluetooth 4.0_LE / GFSK			
AC Conducted Emission	Mode 1: normal link mode			
	Mode 1: normal link mode			
Radiated Test	Mode 2: Bluetooth Tx Ch00_2402MHz_1Mbps			
Cases	Mode 3: Bluetooth Tx Ch19_2440MHz_1Mbps			
	Mode 4: Bluetooth Tx Ch39_2480MHz_1Mbps			
Conducted Test	Mode 2: Bluetooth Tx Ch00_2402MHz_1Mbps			
Conducted Test - Cases -	Mode 3: Bluetooth Tx Ch19_2440MHz_1Mbps			
Cases	Mode 4: Bluetooth Tx Ch39_2480MHz_1Mbps			

#### Note:


- 1. The engineering test program was provided and the EUT was programmed to be in continuously transmitting mode.
- 2. AC power line Conducted Emission was tested under maximum output power.
- 3. For radiated test cases, the worst mode was only reported for data rate 1Mbps, because this data rate has the highest RF output power at preliminary tests, and it doesn't found other significantly frequencies in conducted spurious emission.
- 4. EUT is set to continuous transmission mode. duty cycle greater than 98%.



# **6 SETUP OF EQUIPMENT UNDER TEST**

#### 6.1 BLOCK DIAGRAM CONFIGURATION OF TEST SYSTEM


For AC Conducted Emission Mode



For Radiated Test Cases

E-1 EUT

# For Conducted Test Cases



Note:The temporary antenna connector is soldered on the PCB board in order to perform conducted tests and this temporary antenna connector is listed in the equipment list.



# **6.2 SUPPORT EQUIPMENT**

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

		_			
Item	Equipment	Mfr/Brand	Model/Type No.	FCC ID	Note
E-1	Atlantis	N/A	201702hxatwg	2AEJL-ATLANTIS	EUT
E-2	Adapter	N/A	PS10J050K2000UU	N/A	Peripherals
E-3	Earphone	N/A	2688	N/A	

Item	Cable Type	Shielded Type	Ferrite Core	Length
C-1	USB Cable	NO	NO	1.2m
C-2	Earphone Cable	NO	NO	0.8m
C-3	RF Cable	NO	NO	0.5m

#### Notes:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in <code>[Length]</code> column.
- (3) "YES" is means "shielded" "with core"; "NO" is means "unshielded" "without core".



# 6.3 EQUIPMENTS LIST FOR ALL TEST ITEMS

Radiation Test equipment

kadiatio	on Test equipmer	nt					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibrati on period
1	Spectrum Analyzer	Agilent	E4407B	MY45108040	2016.07.06	2017.07.05	1 year
2	Spectrum Analyzer	Agilent	N9020A	MY49100060	2016.07.06	2017.07.05	1 year
3	EMI Test Receiver	Agilent	N9038A	MY53227146	2016.06.06	2017.06.05	1 year
4	Test Receiver	R&S	ESPI	101318	2016.06.06	2017.06.05	1 year
5	Bilog Antenna	TESEQ	CBL6111D	31216	2016.07.06	2017.07.05	1 year
6	50Ω Coaxial Switch	Anritsu	MP59B	6200264416	2016.06.06	2017.06.05	1 year
7	Horn Antenna	EM	EM-AH-1018 0	2011071402	2016.07.06	2017.07.05	1 year
8	Horn Ant	Schwarzbeck	BBHA 9170	9170-181	2016.07.06	2017.07.05	1 year
9	Amplifier	EM	EM-30180	060538	2016.12.22	2017.12.21	1 year
10	Amplifier	MITEQ	TTA1840-35- HG	177156	2016.06.06	2017.06.05	1 year
11	Loop Antenna	ARA	PLA-1030/B	1029	2016.06.06	2017.06.05	1 year
12	Power Meter	DARE	RPR3006W	100696	2016.07.06	2017.07.05	1 year
13	Test Cable (9KHz-30MHz)	N/A	R-01	N/A	2016.07.06	2017.07.05	1 year
14	Test Cable (30MHz-1GHz)	N/A	R-02	N/A	2016.07.06	2017.07.05	1 year
15	High Test Cable(1G-40G Hz)	N/A	R-03	N/A	2016.06.06	2017.06.05	1 year
16	High Test Cable(1G-40G Hz)	N/A	R-04	N/A	2016.06.06	2017.06.05	1 year
17	temporary antenna connector (Note)	NTS	R001	N/A	N/A	N/A	N/A

# Note:

We will use the temporary antenna connector (soldered on the PCB board) When conducted test And this temporary antenna connector is listed within the instrument list



Condu	Conduction Test equipment						
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
1	Test Receiver	R&S	ESCI	101160	2016.06.06	2017.06.05	1 year
2	LISN	R&S	ENV216	101313	2016.08.24	2017.08.23	1 year
3	LISN	EMCO	3816/2	00042990	2016.08.24	2017.08.23	1 year
4	50Ω Coaxial Switch	Anritsu	MP59B	6200264417	2016.06.07	2017.06.06	1 year
5	Passive Voltage Probe	R&S	ESH2-Z3	100196	2016.06.07	2017.06.06	1 year
6	Absorbing clamp	R&S	MOS-21	100423	2016.06.08	2017.06.07	1 year
7	Test Cable (9KHz-30MH z)	N/A	C01	N/A	2016.06.08	2017.06.07	1 year
8	Test Cable (9KHz-30MH z)	N/A	C02	N/A	2016.06.08	2017.06.07	1 year
9	Test Cable (9KHz-30MH z)	N/A	C03	N/A	2016.06.08	2017.06.07	1 year

Note: Each piece of equipment is scheduled for calibration once a year.



#### 7 TEST REQUIREMENTS

#### 7.1 CONDUCTED EMISSIONS TEST

#### 7.1.1 Applicable Standard

According to FCC Part 15.207(a) and KDB 174176 D01 Line Conducted FAQ v01r01

#### 7.1.2 Conformance Limit

Fraguanov(MHz)	Conducted Emission Limit			
Frequency(MHz)	Quasi-peak	Average		
0.15-0.5	66-56*	56-46*		
0.5-5.0	56	46		
5.0-30.0	60	50		


Note: 1. \*Decreases with the logarithm of the frequency

- 2. The lower limit shall apply at the transition frequencies
- 3. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

#### 7.1.3 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

#### 7.1.4 Test Configuration



#### 7.1.5 Test Procedure

According to the requirements in Section 13.1.4.1 of ANSI C63.10-2013 Conducted emissions the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-Peak and average detector mode.

- 1. The EUT was placed 0.4 meter from the conducting wall of the shielding room.
- 2. The EUT was placed on a table which is 0.8m above ground plane.
- Connect EUT to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- 4. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40cm long.
- 5. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- 6. LISN at least 80 cm from nearest part of EUT chassis.
- 7. The frequency range from 150KHz to 30MHz was searched.
- Set the test-receiver system to Peak Detect Function and specified bandwidth(IF bandwidth=9KHz) with Maximum Hold Mode
- 9. For the actual test configuration, please refer to the related Item –EUT Test Photos.




# 7.1.6 Test Results

EUT:	Atlantis	Model Name:	201702hxatwg
Temperature:	26 ℃	Relative Humidity:	54%
Pressure:	1010hPa	Phase :	L
Test Voltage:	DC 5V from Adapter AC 120V/60Hz	Test Mode:	Mode 1

Frequency	Reading Level	Correct Factor	Measure-ment	Limits	Margin	Remark
(MHz)	(dBµV)	(dB)	(dBµV)	(dBµV)	(dB)	Remark
0.1980	43.80	9.68	53.48	63.69	-10.21	QP
0.1980	27.13	9.68	36.81	53.69	-16.88	AVG
0.2620	42.19	9.67	51.86	61.36	-9.50	QP
0.2620	21.05	9.67	30.72	51.36	-20.64	AVG
0.6300	30.90	9.68	40.58	56.00	-15.42	QP
0.6300	23.73	9.68	33.41	46.00	-12.59	AVG
24.0019	25.48	10.02	35.50	60.00	-24.50	QP
24.0019	17.17	10.02	27.19	50.00	-22.81	AVG

#### Remark:

- All readings are Quasi-Peak and Average values.
   Factor = Insertion Loss + Cable Loss.






EUT:	Atlantis	Model Name:	201702hxatwg
Temperature:	26 ℃	Relative Humidity:	54%
Pressure:	1010hPa	Phase :	N
Test Voltage:	DC 5V from Adapter AC 120V/60Hz	Test Mode:	Mode 1

Frequency	Reading Level	Correct Factor	Measure-ment	Limits	Margin	Remark
(MHz)	(dBµV)	(dB)	(dBµV)	(dBµV)	(dB)	Remark
0.1660	45.06	9.68	54.74	65.15	-10.41	QP
0.1660	24.09	9.68	33.77	55.15	-21.38	AVG
0.2700	38.18	9.67	47.85	61.12	-13.27	QP
0.2700	20.03	9.67	29.70	51.12	-21.42	AVG
0.6180	33.93	9.68	43.61	56.00	-12.39	QP
0.6180	22.36	9.68	32.04	46.00	-13.96	AVG
24.0020	28.87	10.02	38.89	60.00	-21.11	QP
24.0020	15.87	10.02	25.89	50.00	-24.11	AVG

# Remark:

All readings are Quasi-Peak and Average values.
 Factor = Insertion Loss + Cable Loss.








EUT:	Atlantis	Model Name:	201702hxatwg
Temperature:	26 ℃	Relative Humidity:	54%
Pressure:	1010hPa	Phase :	L
Test Voltage:	DC 5V from Adapter AC 240V/60Hz	Test Mode:	Mode 1

Frequency	Reading Level	Correct Factor	Measure-ment	Limits	Margin	Domostic
(MHz)	(dBµV)	(dB)	(dBµV)	(dBµV)	(dB)	Remark
0.2139	30.48	9.58	40.06	63.05	-22.99	QP
0.2139	14.99	9.58	24.57	53.05	-28.48	AVG
0.6059	29.48	9.58	39.06	56.00	-16.94	QP
0.6059	22.13	9.58	31.71	46.00	-14.29	AVG
0.9779	23.85	9.60	33.45	56.00	-22.55	QP
0.9779	15.32	9.60	24.92	46.00	-21.08	AVG
1.1100	23.89	9.60	33.49	56.00	-22.51	QP
1.1100	15.69	9.60	25.29	46.00	-20.71	AVG
24.0019	21.33	9.96	31.29	60.00	-28.71	QP
24.0019	14.97	9.96	24.93	50.00	-25.07	AVG

- All readings are Quasi-Peak and Average values.
   Factor = Insertion Loss + Cable Loss.






EUT:	Atlantis	Model Name:	201702hxatwg
Temperature:	26 ℃	Relative Humidity:	54%
Pressure:	1010hPa	Phase :	N
Test Voltage:	DC 5V from Adapter AC 240V/60Hz	Test Mode:	Mode 1

Frequency	Reading Level	Correct Factor	Measure-ment	Limits	Margin	Domostic
(MHz)	(dBµV)	(dB)	(dBµV)	(dBµV)	(dB)	Remark
0.1580	36.79	9.68	46.47	65.56	-19.09	QP
0.1580	16.93	9.68	26.61	55.56	-28.95	AVG
0.3140	30.20	9.67	39.87	59.86	-19.99	QP
0.3140	12.16	9.67	21.83	49.86	-28.03	AVG
0.5819	31.81	9.68	41.49	56.00	-14.51	QP
0.5819	17.53	9.68	27.21	46.00	-18.79	AVG
0.6139	31.23	9.68	40.91	56.00	-15.09	QP
0.6139	18.91	9.68	28.59	46.00	-17.41	AVG
24.0019	25.18	10.02	35.20	60.00	-24.80	QP
24.0019	12.63	10.02	22.65	50.00	-27.35	AVG

- All readings are Quasi-Peak and Average values.
   Factor = Insertion Loss + Cable Loss.





#### 7.2 RADIATED SPURIOUS EMISSION

## 7.2.1 Applicable Standard

According to FCC Part 15.247(d) and 15.209 and ANSI C63.10-2013

#### 7.2.2 Conformance Limit

According to FCC Part 15.247(d): radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

According to FCC Part15.205, Restricted bands

According to FCC Part 13.20	According to FCC Part 15.205, Restricted bands						
MHz	MHz	MHz	GHz				
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15				
10.495-0.505	16.69475-16.69525	608-614	5.35-5.46				
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75				
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5				
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2				
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5				
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7				
6.26775-6.26825	123-138	2200-2300	14.47-14.5				
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2				
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4				
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12				
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0				
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8				
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5				
12.57675-12.57725	322-335.4	3600-4400	(2)				
13.36-13.41							

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Restricted Frequency(MHz)	Field Strength (µV/m)	Field Strength (dBµV/m)	Measurement Distance
0.009~0.490	2400/F(KHz)	20 log (uV/m)	300
0.490~1.705	2400/F(KHz)	20 log (uV/m)	30
1.705~30.0	30	29.5	30
30-88	100	40	3
88-216	150	43.5	3
216-960	200	46	3
Above 960	500	54	3

Limits of Radiated Emission Measurement(Above 1000MHz)

Frequency(MHz)	Class B (dBuV/m) (at 3M)				
	PEAK	AVERAGE			
Above 1000	74	54			

Remark :1. Emission level in dBuV/m=20 log (uV/m)

- 2. Measurement was performed at an antenna to the closed point of EUT distance of meters.
- 3. Distance extrapolation factor =40log(Specific distance/ test distance)( dB); Limit line=Specific limits(dBuV) + distance extrapolation factor.




# 7.2.3 Measuring Instruments


The Measuring equipment is listed in the section 6.3 of this test report.

# 7.2.4 Test Configuration


(a) For radiated emissions below 30MHz



(b) For radiated emissions from 30MHz to 1000MHz



(c) For radiated emissions above 1000MHz





#### 7.2.5 Test Procedure

The test site semi-anechoic chamber has met the requirement of NSA tolerance 4 dB according to the standards: ANSI C63.10-2013. The test distance is 3m.The setup is according to the requirements in Section 13.1.4.1 of ANSI C63.10-2013 and CAN/CSA-CEI/IEC CISPR 22.

This test is required for any spurious emission that falls in a Restricted Band, as defined in Section 15.205. It must be performed with the highest gain of each type of antenna proposed for use with the EUT. Use the following spectrum analyzer settings:

3-1	
Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

- a. The measuring distance of at 3 m shall be used for measurements at frequency up to 1GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
- b. The EUT was placed on the top of a rotating table 0.8 m for below 1GHz and 1.5m for above 1GHz the ground at a 3 meter. The table was rotated 360 degrees to determine the position of the highest radiation
- c. The height of the equipment or of the substitution antenna shall be 0.8 m for below 1GHz and 1.5m for above 1GHz; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For the radiated emission test above 1GHz:
  - Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
- e. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- f. If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- g. For the actual test configuration, please refer to the related Item –EUT Test Photos.

#### Note:

Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported



During the radiated emission test, the Spectrum Analyzer was set with the following configurations:

Frequency Band (MHz)	Function	Resolution bandwidth	Video Bandwidth	
30 to 1000	QP	120 kHz	300 kHz	
Al 4000	Peak	1 MHz	1 MHz	
Above 1000	Average	1 MHz	10 Hz	

Note: for the frequency ranges below 30 MHz, a narrower RBW is used for these ranges but the measured value should add a RBW correction factor (RBWCF) where RBWCF [dB] =10\*lg(100 [kHz]/narrower RBW [kHz]). , the narrower RBW is 1 kHz and RBWCF is 20 dB for the frequency 9 kHz to 150 kHz, and the narrower RBW is 10 kHz and RBWCF is 10 dB for the frequency 150 kHz to 30 MHz.

#### 7.2.6 Test Results

■ Spurious Emission below 30MHz (9KHz to 30MHz)

EUT:	Atlantis	Model No.:	201702hxatwg
Temperature:	20 ℃	Relative Humidity:	48%
Test Mode:	Mode2/Mode3/Mode4	Test By:	Eileen Liu

Freq.	Ant.Pol.	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
(MHz)	H/V	PK	AV	PK	AV	PK	AV

Note: the amplitude of spurious emission that is attenuated by more than 20dB below the permissible limit has no need to be reported.

Distance extrapolation factor =20log(Specific distance/ test distance)( dB);

Limit line=Specific limits(dBuV) + distance extrapolation factor



■ Spurious Emission below 1GHz (30MHz to 1GHz)

All the modulation modes have been tested, and the worst result was report as below:

EUT:	Atlantis	Model Name:	201702hxatwg				
Temperature:	20 ℃	Relative Humidity:	48%				
Pressure:	1010hPa	Test Mode:	Mode 1				
Test Voltage:	DC 3.7V						

Polar	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark	
(H/V)	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)		
V	30.1054	13.30	19.82	33.12	40.00	-6.88	QP	
V	44.5868	13.59	11.46	25.05	40.00	-14.95	QP	
V	95.4270	14.18	11.50	25.68	43.50	-17.82	QP	
V	152.6641	21.23	12.83	34.06	43.50	-9.44	QP	
V	334.8589	11.58	17.35	28.93	46.00	-17.07	QP	
V	400.4319	12.21	20.23	32.44	46.00	-13.56	QP	

# Remark:


Absolute Level= ReadingLevel+ Factor, Margin= Absolute Level - Limit





Polar	Frequency	Meter Reading	Factor Emission Limits Margin		Margin	Remark		
(H/V)	(MHz)	(dBuV)	(dB)	(dBuV/m) (dBuV/m)		(dB)		
Н	90.8554	10.71	10.79	21.50	43.50	-22.00	QP	
Н	145.8611	14.89	13.00	27.89	43.50	-15.61	QP QP QP QP QP QP	
Н	199.9856	18.99	10.26	29.25	43.50	-14.25	QP	
Н	334.8589	11.58	17.35	28.93	46.00	-17.07	QP	
Н	744.8661	7.46	27.45	34.91	46.00	-11.09	QP	
Н	798.9796	11.29	28.03	39.32	46.00	-6.68	QP	

# Remark:





Spurious Emission Above 1GHz (1GHz to 25GHz)

EUT:	Atlantis	Model No.:	201702hxatwg						
Temperature:	20 ℃	Relative Humidity:	48%						
Test Mode:	Mode2/Mode3/Mode4	Test By:	Eileen Liu						

Frequenc y	Read Level	Cable loss	Antenna Factor	Preamp Factor	Emission Level	Limits	Margin	Remark	Comment
(MHz)	(dBµV)	(dB)	dB/m	(dB)	(dBµV/m)	(dBµV/m)	(dB)		
			Low	Channel (2	402 MHz)-	Above 1G			
4804.308	66.52	5.21	35.59	44.30	63.02	74.00	-10.98	Pk	Vertical
4804.308	42.12	5.21	35.59	44.30	38.62	54.00	-15.38	AV	Vertical
7206.162	61.67	6.48	36.27	44.60	59.82	74.00	-14.18	Pk	Vertical
7206.162	43.59	6.48	36.27	44.60	41.74	54.00	-12.26	AV	Vertical
4804.245	62.59	5.21	35.55	44.30	59.05	74.00	-14.95	Pk	Horizontal
4804.245	42.47	5.21	35.55	44.30	38.93	54.00	-15.07	AV	Horizontal
7206.131	63.36	6.48	36.27	44.52	61.59	74.00	-12.41	Pk	Horizontal
7206.131	41.14	6.48	36.27	44.52	39.37	54.00	-14.63	AV	Horizontal
			Mid	Channel (2	440 MHz)- <i>i</i>	Above 1G			
4882.273	68.98	5.21	35.66	44.20	65.65	74.00	-8.35	Pk	Vertical
4882.273	45.55	5.21	35.66	44.20	42.22	54.00	-11.78	AV	Vertical
7323.152	62.64	7.10	36.50	44.43	61.81	74.00	-12.19	Pk	Vertical
7323.152	41.14	7.10	36.50	44.43	40.31	54.00	-13.69	AV	Vertical
4882.168	69.97	5.21	35.66	44.20	66.64	74.00	-7.36	Pk	Horizontal
4882.168	47.84	5.21	35.66	44.20	44.51	54.00	-9.49	AV	Horizontal
7323.113	64.53	7.10	36.50	44.43	63.70	74.00	-10.30	Pk	Horizontal
7323.113	47.54	7.10	36.50	44.43	46.71	54.00	-7.29	AV	Horizontal
			High	Channel (2	480 MHz)-	Above 1G			
4960.241	65.25	5.21	35.52	44.21	61.77	74.00	-12.23	Pk	Vertical
4960.241	48.41	5.21	35.52	44.21	44.93	54.00	-9.07	AV	Vertical
7440.137	62.23	7.10	36.53	44.60	61.26	74.00	-12.74	Pk	Vertical
7440.137	45.12	7.10	36.53	44.60	44.15	54.00	-9.85	AV	Vertical
4960.256	69.89	5.21	35.52	44.21	66.41	74.00	-7.59	Pk	Horizontal
4960.256	48.74	5.21	35.52	44.21	45.26	54.00	-8.74	AV	Horizontal
7440.108	62.41	7.10	36.53	44.60	61.44	74.00	-12.56	Pk	Horizontal
7440.108	43.35	7.10	36.53	44.60	42.38	54.00	-11.62	AV	Horizontal

Note: (1) All Readings are Peak Value (VBW=3MHz) and AV Value (VBW=10Hz). (2) Emission Level= Antenna Factor + Cable Loss + Read Level - Preamp Factor

(3)All other emissions more than 20dB below the limit.



	■ Spurious Emission in Restricted Band 2310-2390MHz and 2483.5-2500MHz					
EUT: Atlantis Model No.: 201702hxatwg				201702hxatwg		
	Temperature:	20 ℃	Relative Humidity:	48%		
	Test Mode:	Mode2/ Mode4	Test By:	Eileen Liu		

Frequenc	Meter Reading	Cable Loss	Antenna Factor	Preamp Factor	Emission Level	Limits	Margin	Detector	Comment
(MHz)	(dBµV)	(dB)	dB/m	(dB)	(dBµV/m)	(dBµV/m)	(dB)	Туре	Comment
		. ,		. ,	SK	, , ,	,		
2310.00	62.24	2.97	27.80	43.80	49.21	74	-24.79	Pk	Horizontal
2310.00	41.19	2.97	27.80	43.80	28.16	54	-25.84	AV	Horizontal
2310.00	61.34	2.97	27.80	43.80	48.31	74	-25.69	Pk	Vertical
2310.00	47.48	2.97	27.80	43.80	34.45	54	-19.55	AV	Vertical
2390.00	62.54	3.14	27.21	43.80	49.09	74	-24.91	Pk	Vertical
2390.00	42.22	3.14	27.21	43.80	28.77	54	-25.23	AV	Vertical
2390.00	59.89	3.14	27.21	43.80	46.44	74	-27.56	Pk	Horizontal
2390.00	42.64	3.14	27.21	43.80	29.19	54	-24.81	AV	Horizontal
2483.50	61.47	3.58	27.70	44.00	48.75	74	-25.25	Pk	Vertical
2483.50	42.23	3.58	27.70	44.00	29.51	54	-24.49	AV	Vertical
2483.50	59.86	3.58	27.70	44.00	47.14	74	-26.86	Pk	Horizontal
2483.50	42.11	3.58	27.70	44.00	29.39	54	-24.61	AV	Horizontal

Note: (1) All other emissions more than 20dB below the limit.



■ Spurious Emission in Restricted Band 3260MMHz-18000MHz

EUT:	Atlantis	Model No.:	201702hxatwg
Temperature:	20 ℃	Relative Humidity:	48%
Test Mode:	Mode2/ Mode4	Test By:	Eileen Liu

Frequenc	Readin	Cable	Antenn	Preamp	Emission	Limits	Margin	Detect	
У	g Level	Loss	а	Factor	Level	LIIIIII	iviaigiii	or	Comment
(MHz)	(dBµV)	(dB)	dB/m	(dB)	(dBµ V/m)	(dBµ V/m)	(dB)	Type	Comment
3260	61.24	4.04	29.57	44.70	50.15	74	-23.85	Pk	Vertical
3260	55.59	4.04	29.57	44.70	44.50	54	-9.50	AV	Vertical
3260	61.34	4.04	29.57	44.70	50.25	74	-23.75	Pk	Horizontal
3260	54.47	4.04	29.57	44.70	43.38	54	-10.62	AV	Horizontal
3332	62.55	4.26	29.87	44.40	52.28	74	-21.72	Pk	Vertical
3332	52.42	4.26	29.87	44.40	42.15	54	-11.85	AV	Vertical
3332	61.23	4.26	29.87	44.40	50.96	74	-23.04	Pk	Horizontal
3332	54.47	4.26	29.87	44.40	44.20	54	-9.80	AV	Horizontal
17797	41.11	10.99	43.95	43.50	52.55	74	-21.45	Pk	Vertical
17797	62.34	10.99	43.95	43.50	73.78	54	19.78	AV	Vertical
17788	42.74	11.81	43.69	44.60	53.64	74	-20.36	Pk	Horizontal
17788	32.26	11.81	43.69	44.60	43.16	54	-10.84	AV	Horizontal

Note: (1) All other emissions more than 20dB below the limit.



#### 7.3 6DB BANDWIDTH

## 7.3.1 Applicable Standard

According to FCC Part 15.247(a)(2) and KDB 558074 DTS 01 Meas. Guidance v03r05

#### 7.3.2 Conformance Limit

The minimum permissible 6dB bandwidth is 500 kHz.

#### 7.3.3 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

#### 7.3.4 Test Setup

Please refer to Section 6.1 of this test report.

#### 7.3.5 Test Procedure

The testing follows KDB 558074 DTS 01 Meas. Guidance v03r05

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.

The path loss was compensated to the results for each measurement.

Set to the maximum power setting and enable the EUT transmit continuously.

The EUT was operating in controlled its channel.

Use the following spectrum analyzer settings:

Span = the frequency band of operation

RBW = 100KHz

 $VBW \geq 3^{*}RBW$ 

Sweep = auto

Detector function = peak


Trace = max hold

#### 7.3.6 Test Results


EUT:	Atlantis	Model No.:	201702hxatwg
Temperature:	20 ℃	Relative Humidity:	48%
Test Mode:	Mode2/Mode3/Mode4	Test By:	Eileen Liu

Channel	Frequency (MHz)	6dB bandwidth (kHz)	Limit (kHz)	Result
Low	2402	698.369	500	Pass
Middle	2440	694.789	500	Pass
High	2480	695.300	500	Pass











#### 7.4 PEAK OUTPUT POWER

# 7.4.1 Applicable Standard

According to FCC Part 15.247(b)(3) and KDB 558074 DTS 01 Meas. Guidance v03r05

#### 7.4.2 Conformance Limit

The maximum peak conducted output power of the intentional radiator for systems using digital modulation in the 2400 - 2483.5 MHz bands shall not exceed: 1 Watt (30dBm). If transmitting antenna of directional gain greater than 6dBi is used, the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.

#### 7.4.3 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

#### 7.4.4 Test Setup

Please refer to Section 6.1 of this test report.

# 7.4.5 Test Procedure

The testing follows KDB 558074 DTS 01 Meas. Guidance v03r05

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.

The path loss was compensated to the results for each measurement.

Set to the maximum power setting and enable the EUT transmit continuously.

The EUT was operating in controlled its channel.

Use the following spectrum analyzer settings:

Set the RBW ≧DTS bandwidth(about 1MHz).

Set VBW =3\*RBW(about 3MHz)

Set the span ≥3\*RBW

Set Sweep time = auto couple.

Set Detector = peak.

Set Trace mode = max hold.

Allow trace to fully stabilize.


Use peak marker function to determine the peak amplitude level.

#### 7.4.6 Test Results


EUT:	Atlantis	Model No.:	201702hxatwg
Temperature:	20 ℃	Relative Humidity:	48%
Test Mode:	Mode2/Mode3/Mode4	Test By:	Eileen Liu

Test Channel	Frequency (MHz)	Power Setting	Peak Output Power (dBm)	LIMIT (dBm)	Verdict		
1Mbps							
00	2402	Default	-7.71	30	PASS		
19	2440	Default	-5.78	30	PASS		
39	2480	Default	-5.93	30	PASS		











#### 7.5 POWER SPECTRAL DENSITY

#### 7.5.1 Applicable Standard

According to FCC Part 15.247(e) and KDB 558074 DTS 01 Meas. Guidance v03r05

#### 7.5.2 Conformance Limit

The transmitter power spectral density conducted from the transmitter to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

#### 7.5.3 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

#### 7.5.4 Test Setup

Please refer to Section 6.1 of this test report.

#### 7.5.5 Test Procedure

The testing follows Measurement Procedure 10.3 Method AVGPSD of FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r05

This procedure may be used when the maximum (average) conducted output power was used to demonstrate compliance to the output power limit. This is the baseline method for determining the maximum (average) conducted PSD level. If the instrument has an RMS power averaging detector, it must be used; otherwise, use the sample detector. The EUT must be configured to transmit continuously (duty cycle ≥ 98%); otherwise sweep triggering/signal gating must be implemented to ensure that measurements are made only when the EUT is transmitting at its maximum power control level (no transmitter off time is to be considered).

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.

The path loss was compensated to the results for each measurement.

Set to the maximum power setting and enable the EUT transmit continuously.

The EUT was operating in controlled its channel.

- a) Set instrument center frequency to DTS channel center frequency.
- b) Set span to at least 1.5 times the OBW.
- c) Set RBW to: 3 kHz ≤ RBW ≤ 100 kHz. .
- d) Set VBW ≥3 x RBW.
- e) Detector = power averaging (RMS) or sample detector (when RMS not available).
- f) Ensure that the number of measurement points in the sweep  $\geq 2 \times \text{span/RBW}$ .
- g) Sweep time = auto couple.
- h) Employ trace averaging (RMS) mode over a minimum of 100 traces.
- i) Use the peak marker function to determine the maximum amplitude level.
- j) If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat (note that this may require zooming in on the emission of interest and reducing




# 7.5.6 Test Results


EUT:	Atlantis	Model No.:	201702hxatwg
Temperature:	20 ℃	Relative Humidity:	48%
Test Mode:	Mode2/Mode3/Mode4	Test By:	Eileen Liu

Test Channel	Frequency (MHz)	Power Density (dBm/3KHz)	Limit (dBm/3KHz)	Verdict			
	1Mbps						
00	2402	-22.82	8	PASS			
19	2440	-20.98	8	PASS			
39	2480	-21.22	8	PASS			











#### 7.6 CONDUCTED BAND EDGE MEASUREMENT

#### 7.6.1 Applicable Standard

According to FCC Part 15.247(d) and KDB 558074 DTS 01 Meas. Guidance v03r05

#### 7.6.2 Conformance Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.

#### 7.6.3 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

#### 7.6.4 Test Setup

Please refer to Section 6.1 of this test report.

#### 7.6.5 Test Procedure

The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r05.

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.

The path loss was compensated to the results for each measurement.

Set to the maximum power setting and enable the EUT transmit continuously.

The EUT was operating in controlled its channel.

Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.


Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.

Repeat above procedures until all measured frequencies were complete.

#### 7.6.6 Test Results

EUT:	Atlantis	Model No.:	201702hxatwg
Temperature:	20 ℃	Relative Humidity:	48%
Test Mode:	Mode2/Mode4	Test By:	Eileen Liu







#### 7.7 SPURIOUS RF CONDUCTED EMISSIONS

#### 7.7.1 Conformance Limit

- 1. Below -20dB of the highest emission level in operating band.
- 2. Fall in the restricted bands listed in section 15.205. The maximum permitted average field strength is listed in section 15.209.

#### 7.7.2 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

#### 7.7.3 Test Setup

Please refer to Section 6.1 of this test report.

#### 7.7.4 Test Procedure

The Spurious RF conducted emissions compliance of RF radiated emission should be measured by following the guidance in ANSI C63.10-2013 with respect to maximizing the emission by rotating the EUT, measuring the emission while the EUT is situated in three orthogonal planes (if appropriate), adjusting the measurement antenna height and polarization etc. Set RBW=100kHz and VBW= 300KHz to measure the peak field strength, and mwasure frequeny range from 9KHz to 26.5GHz.


#### 7.7.5 Test Results

Remark: The measurement frequency range is from 9KHz to the 10th harmonic of the fundamental frequency. The lowest, middle and highest channels are tested to verify the spurious emissions and bandege measurement data.







#### GFSK on channel 00




#### GFSK on channel 00



#### GFSK on channel 00




#### GFSK on channel 00









#### GFSK on channel 19



#### GFSK on channel 19



#### GFSK on channel 19




#### GFSK on channel 19









#### GFSK on channel 39




#### GFSK on channel 39



#### GFSK on channel 39



#### GFSK on channel 39





# 7.8 ANTENNA APPLICATION

# 7.8.1 Antenna Requirement

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

#### 7.8.2 **Result**

The EUT antenna is permanent attached FPCB antenna(Gain:1dBi). It comply with the standard requirement.

END OF REPORT