

SAR EVALUATION REPORT

For

ZTE TRUNKING TECHNOLOGY CORPORATION

4/F, R&D Buliding 1, ZTE Industrial Park, LiuXian Road, Xili, Nanshan District, Shenzhen, P.R. China

FCC ID: 2AEKCPH7X0U1

Report Type:

Product Type:

Class II Permissive Change

DIGITAL PORTABLE RADIO

Jesse Huant

Report Number: RSZ161008001-20AA1

Report Date: 2016-12-26

Jesse Huang

Reviewed By: Manager

Bay Area Compliance Laboratories Corp. (Kunshan) Prepared By:

No.248 Chenghu Road, Kunshan, Jiangsu province, China

Tel: +86-0512-86175000 Fax: +86-0512-88934268 www.baclcorp.com.cn

Report No.: RSZ161008001-20AA1

Note: This wireless device has been shown to be capable of compliance for localized specific absorption rate SAR for Occupational /Controlled Exposure Environment limits specified in ANSI/IEEE Standards and has been tested in accordance with the measurement procedures specified in IEEE 1528-2013 and RF exposure KDB procedures.

KDB 643646D01 v01r03: SAR test Reduction Considerations for Occupational PTT Radios.

The results and statements contained in this report pertain only to the device(s) evaluated.

SAR Evaluation Report 2 of 33

TABLE OF CONTENTS

DOCUMENT REVISION HISTORY	4
EUT DESCRIPTION	5
TECHNICAL SPECIFICATION	5
REFERENCE, STANDARDS, AND GUILDELINES	6
SAR LIMITS	7
FACILITIES	8
POWER REFERENCE MEASUREMENT AREA SCAN ZOOM SCAN	9 10
POWER DRIFT MEASUREMENTZ-SCAN	
DESCRIPTION OF TEST SYSTEM	11
EQUIPMENT LIST AND CALIBRATION	16
EQUIPMENTS LIST & CALIBRATION INFORMATION	16
SAR MEASUREMENT SYSTEM VERIFICATION	17
LIQUID VERIFICATION	17
EUT TEST STRATEGY AND METHODOLOGY	22
CONDUCTED OUTPUT POWER MEASUREMENT	24
Provision Applicable	
SAR MEASUREMENT RESULTS	26
SAR SIMULTANEOUS TRANSMISSION DESCRIPTION	29
ADDENINIV A MEACHDEMENT INICEDTAINTY	21

DOCUMENT REVISION HISTORY

Revision Number	Report Number	Description of Revision	Date of Revision
0	RSZ160711004-20A	Original Report	2016-08-10
1	RSZ161008001-20AA1	CIIPC Report	2016-12-26

Note:

This is a CIIPC report application based on RSZ160711004-20A, the details as below

- 1) Changing the model name to "PH700 U(1)".
- 2) Changing the appearance of EUT, removing the screen from the EUT.
- 3) Changing the material and the Bluetooth antenna

Based on above differences, SAR needs to be retested.

SAR Evaluation Report 4 of 33

EUT DESCRIPTION

This report has been prepared on behalf of ZTE TRUNKING TECHNOLOGY CORPORATION and their product, FCC ID: 2AEKCPH7X0U1, Model: PH700 U(1) or the EUT (Equipment under Test) as referred to in the rest of this report.

Report No.: RSZ161008001-20AA1

Note:

1. All measurement and test data in this report was gathered from production sample serial number: 16100800112(Assigned by BACL, Kunshan). The EUT supplied by the applicant was received on 2016-10-18.

Technical Specification

Product Type	Portable		
Exposure Category:	Occupational/Controlled Exposure		
Antenna Type(s):	External Antenna		
Body-Worn Accessories:	Belt Clip		
Face-Head Accessories:	None		
Madulation Tomas	UHF: 4FSK&FM		
Modulation Type:	Bluetooth: GFSK, 4-DQPSK, 8DPSK		
Engagement Donds	UHF:400MHz-470MHz		
Frequency Band:	Bluetooth:2402-2480MHz		
Dimensions (L*W*H):	150 mm (L) × 60 mm (W) × 38 mm (H)		
Power Source:	7.4V Rechargeable Li-ION Battery		
Normal Operation:	Face Up and Body-worn		

SAR Evaluation Report 5 of 33

REFERENCE, STANDARDS, AND GUILDELINES

FCC:

The Report and Order requires routine SAR evaluation prior to equipment authorization of portable transmitter devices, including portable telephones. For portable devices, the RF radiation exposure evaluation requirement was provided in part 2.1093. According to KDB447498 D01 "General RF Exposure Guidance", the device should be evaluated at maximum output power (radiated from the antenna) under "worst-case" conditions for normal or intended use, incorporating normal antenna operating positions, device peak performance frequencies and positions for maximum RF energy coupling.

Report No.: RSZ161008001-20AA1

This report describes the methodology and results of experiments performed on wireless data terminal. The objective was to determine if there is RF radiation and if radiation is found, what is the extent of radiation with respect to safety limits. SAR (Specific Absorption Rate) is the measure of RF exposure determined by the amount of RF energy absorbed by human body (or its parts) – to determine how the RF energy couples to the body or head which is a primary health concern for body worn devices.

CE:

The order requires routine SAR evaluation prior to equipment authorization of portable transmitter devices, including portable telephones. For portable devices, the limitation of exposure of the general public to electromagnetic fields was recommended on Council Recommendation 1999/519/EC. According to the Standard IEC62209-1/2, the device should be evaluated at maximum output power (radiated from the antenna) under "worst-case" conditions for normal or intended use, incorporating normal antenna operating positions, device peak performance frequencies and positions for maximum RF energy coupling.

This report describes the methodology and results of experiments performed on wireless data terminal. The objective was to determine if there is RF radiation and if radiation is found, what is the extent of radiation with respect to safety limits. SAR (Specific Absorption Rate) is the measure of RF exposure determined by the amount of RF energy absorbed by human body (or its parts) – to determine how the RF energy couples to the body or head which is a primary health concern for body portable devices.

The test configurations were laid out on a specially designed test fixture to ensure the reproducibility of measurements. Each configuration was scanned for SAR. Analysis of each scan was carried out to characterize the above effects in the device.

SAR Evaluation Report 6 of 33

FCC Limit (1g Tissue)

Report No.: RSZ161008001-20AA1

	SAR (W/kg)					
EXPOSURE LIMITS	(General Population / Uncontrolled Exposure Environment)	(Occupational / Controlled Exposure Environment)				
Spatial Average (averaged over the whole body)	0.08	0.4				
Spatial Peak (averaged over any 1 g of tissue)	1.60	8.0				
Spatial Peak (hands/wrists/feet/ankles averaged over 10 g)	4.0	20.0				

CE Limit (10g Tissue)

	SAR (W/kg)					
EXPOSURE LIMITS	(General Population / Uncontrolled Exposure Environment)	(Occupational / Controlled Exposure Environment)				
Spatial Average (averaged over the whole body)	0.08	0.4				
Spatial Peak (averaged over any 10 g of tissue)	2.0	10				
Spatial Peak (hands/wrists/feet/ankles averaged over 10 g)	4.0	20.0				

Population/Uncontrolled Environments are defined as locations where there is the exposure of individual who have no knowledge or control of their exposure.

Occupational/Controlled Environments are defined as locations where there is exposure that may be incurred by people who are aware of the potential for exposure (i.e. as a result of employment or occupation).

SAR Evaluation Report 7 of 33

FACILITIES

The test site used by Bay Area Compliance Laboratories Corp. (Kunshan) to collect test data is located on No.248 Chenghu Road, Kunshan, Jiangsu province, China.

Report No.: RSZ161008001-20AA1

SAR Evaluation Report 8 of 33

DASY4 SAR Evaluation Procedure

Power Reference Measurement

The Power Reference Measurement and Power Drift Measurement jobs are useful jobs for monitoring the power drift of the device under test in the batch process. Both jobs measure the field at a specified reference position, at a selectable distance from the phantom surface. The reference position can be either the selected section's grid reference point or a user point in this section. The reference job projects the selected point onto the phantom surface, orients the probe perpendicularly to the surface, and approaches the surface using the selected detection method. The Minimum distance of probe sensors to surface determines the closest measurement point to phantom surface. By default, the Minimum distance of probe sensors to surface is 4mm. This distance can be modified by the user, but cannot be smaller than the Distance of sensor calibration points to probe tip as defined in the probe properties.


Area Scan


The Area Scan is used as a fast scan in two dimensions to find the area of high field values, before doing a finer measurement around the hot spot. The sophisticated interpolation routines implemented in DASY4 software can find the maximum locations even in relatively coarse grids.

The scanning area is defined by an editable grid. This grid is anchored at the grid reference point of the selected section in the phantom. When the Area Scan's property sheet is brought-up, grid settings can be edited by a user.

When an Area Scan has measured all reachable points, it computes the field maxima found in the scanned area, within a range of the global maximum. The range (in dB) is specified in the standards for compliance testing. For example, a 2 dB range is required in IEEE 1528-2013, IEC 62209-1:2006 and IEC 62209-2:2010 standards, whereby 3 dB is a requirement when compliance is assessed in accordance with the ARIB standard (Japan). If only one Zoom Scan follows the Area Scan, then only the absolute maximum will be taken as reference. For cases where multiple maximums are detected, the number of Zoom Scans has to be increased accordingly.

After measurement is completed, all maxima and their coordinates are listed in the Results property page. The maximum selected in the list is highlighted in the 3-D view. For the secondary maxima returned from an Area Scan, the user can specify a lower limit (peak SAR value), in addition to the Find secondary maxima within x dB condition. Only the primary maximum and any secondary maxima within x dB from the primary maximum and above this limit will be measured.





Report No.: RSZ161008001-20AA1

SAR Evaluation Report 9 of 33

Zoom Scan

Zoom Scans are used to assess the peak spatial SAR values within a cubic averaging volume containing 1 g and 10 g of simulated tissue. The default Zoom Scan measures 5 x 5 x 7 points within a cube whose base faces are centered around the maxima found in a preceding area scan job within the same procedure. When the measurement is done, the Zoom Scan evaluates the averaged SAR for 1 g and 10 g and displays these values next to the job's label.


Report No.: RSZ161008001-20AA1

Power drift measurement

The Power Drift Measurement job measures the field at the same location as the most recent power reference measurement job within the same procedure, and with the same settings. The Power Drift Measurement gives the field difference in dB from the reading conducted within the last Power Reference Measurement. Several drift measurements are possible for one reference measurement. This allows a user to monitor the power drift of the device under test within a batch process. The measurement procedure is the same as Step 1.

Z-Scan

The Z Scan job measures points along a vertical straight line. The line runs along the Z axis of a one-dimensional grid. A user can anchor the grid to the section reference point, to any defined user point or to the current probe location. As with any other grids, the local Z axis of the anchor location establishes the Z axis of the grid.



SAR Evaluation Report 10 of 33


DESCRIPTION OF TEST SYSTEM

These measurements were performed with the automated near-field scanning system DASY4 from Schmid & Partner Engineering AG (SPEAG) which is the Fifth generation of the system shown in the figure hereinafter:



DASY4 System Description

The DASY4 system for performing compliance tests consists of the following items:



SAR Evaluation Report 11 of 33

- A standard high precision 6-axis robot (Staubli TX=RX family) with controller, teach pendant and software. An arm extension for accommodating the data acquisition electronics (DAE).
- An isotropic field probe optimized and calibrated for the targeted measurement.
- A data acquisition electronics (DAE) which performs the signal amplication, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.
- The Electro-optical converter (EOC) performs the conversion from optical to electrical signals for the digital
 communication to the DAE. To use optical surface detection, a special version of the EOC is required. The EOC
 signal is transmitted to the measurement server.
- The function of the measurement server is to perform the time critical tasks such as signal filtering, control of the robot operation and fast movement interrupts.
- The Light Beam used is for probe alignment. This improves the (absolute) accuracy of the probe positioning.
- A computer running Win7 profesional operating system and the DASY42 software.
- Remote control and teach pendant as well as additional circuitry for robot safety such as warning lamps, etc.
- The phantom, the device holder and other accessories according to the targeted measurement.

DASY4 Measurement Server

The DASY4 measurement server is based on a PC/104 CPU board with a 400MHz intel ULV Celeron, 128MB chip-disk and 128MB RAM. The necessary circuits for communication with the DAE4 (or DAE3) electronics box, as well as the 16 bit AD converter system for optical detection and digital I/O interface are contained on the DASY4 I/O board, which is directly connected to the PC/104 bus of the CPU board.



The measurement server performs all real-time data evaluation of field measurements and surface detection, controls robot movements and handles safety operation. The PC operating system cannot interfere with these time critical processes. All connections are supervised by a watchdog, and disconnection of any of the cables to the measurement server will automatically disarm the robot and disable all program-controlled robot movements. Furthermore, the measurement server is equipped with an expansion port which is reserved for future applications. Please note that this expansion port does not have a standardized point out, and therefore only devices provided by SPEAG can be connected. Devices from any other supplier could seriously damage the measurement server.

Data Acquisition Electronics

The data acquisition electronics (DAE4) consist of a highly sensitive electrometer-grade preamplifer with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD-converter and a command decoder with a control logic unit. Transmission to the measurement server is accomplished through an optical downlink for data and status information, as well as an optical uplink for commands and the clock.

The mechanical probe mounting device includes two different sensor systems for frontal and sideways probe contacts. They are used for mechanical surface detection and probe collision detection.

The input impedance of both the DAE4 as well as of the DAE3 box is 200MOhm; the inputs are symmetrical and floating. Common mode rejection is above 80 dB.

SAR Evaluation Report 12 of 33

EX3DV4 E-Field Probes

Frequency	10 MHz to > 6 GHz Linearity: ± 0.2 dB (30 MHz to 6 GHz)
Directivity	\pm 0.3 dB in TSL (rotation around probe axis) \pm 0.5 dB in TSL (rotation normal to probe axis)
Dynamic Range	10 μW/g to > 100 mW/g Linearity: \pm 0.2 dB (noise: typically < 1 μW/g)
Dimensions	Overall length: 337 mm (Tip: 20 mm) Tip diameter: 2.5 mm (Body: 12 mm) Typical distance from probe tip to dipole centers: 1 mm
Application	High precision dosimetric measurements in any exposure scenario (e.g., very strong gradient fields); the only probe that enables compliance testing for frequencies up to 6 GHz with precision of better 30%.
Compatibility	DASY3, DASY4, DASY42 SAR and higher, EASY4/MRI

SAM Twin Phantom

The SAM twin phantom is a fiberglass shell phantom with 2mm shell thickness (except the ear region, where shell thickness increases to 6 mm). The phantom has three measurement areas:

- _ Left hand
- Right hand
- _ Flat phantom

The phantom table for the DASY systems based on the TX90XL and RX160L robots have the size of $100 \times 50 \times 85$ cm (L xWx H). The phantom table for the compact DASY systems based on the RX60L robot have the size of $100 \times 75 \times 91$ cm (L xWx H); these tables are reinforced for mounting of the robot onto the table.



For easy dislocation these tables have fork lift cut outs at the bottom.

The bottom plate contains three pairs of bolts for locking the device holder. The device holder positions are adjusted to the standard measurement positions in the three sections. Only one device holder is necessary if two phantoms are used (e.g., for different liquids)

A white cover is provided to cover the phantom during o_-periods to prevent water evaporation and changes in the liquid parameters. Free space scans of devices on top of this phantom cover are possible.

Three reference marks are provided on the phantom counter. These reference marks are used to teach the absolute phantom position relative to the robot.

SAR Evaluation Report 13 of 33

Robots

The DASY4 system uses the high precision industrial robots RX90XL from Staubli SA (France). The TX robot family is the successor of the well known RX robot family and offers the same features important for our application:

Report No.: RSZ161008001-20AA1

- High precision (repeatability 0.02mm)
- High reliability (industrial design)
- Low maintenance costs (virtually maintenance free due to direct drive gears; no belt drives)
- Jerk-free straight movements (brushless synchron motors; no stepper motors)
- Low ELF interference (motor control fields shielded via the closed metallic construction shields)

The above mentioned robots are controlled by the Staubli CS8c robot controllers. All information regarding the use and maintenance of the robot arm and the robot controller is contained on the CDs delivered along with the robot. Paper manuals are available upon request direct from Staubli.

Area Scans

Area scans are defined prior to the measurement process being executed with a user defined variable spacing between each measurement point (integral) allowing low uncertainty measurements to be conducted. Scans defined for FCC applications utilize a 10mm2 step integral, with 1mm interpolation used to locate the peak SAR area used for zoom scan assessments.

Where the system identifies multiple SAR peaks (which are within 25% of peak value) the system will provide the user with the option of assessing each peak location individually for zoom scan averaging.

Zoom Scan (Cube Scan Averaging)

The averaging zoom scan volume utilized in the DASY4 software is in the shape of a cube and the side dimension of a 1 g or 10 g mass is dependent on the density of the liquid representing the simulated tissue. A density of 1000 kg/m3 is used to represent the head and body tissue density and not the phantom liquid density, in order to be consistent with the definition of the liquid dielectric properties, i.e. the side length of the 1 g cube is 10mm, with the side length of the 10 g cube 21,5mm.

When the cube intersects with the surface of the phantom, it is oriented so that 3 vertices touch the surface of the shell or the center of a face is tangent to the surface. The face of the cube closest to the surface is modified in order to conform to the tangent surface.

The zoom scan integer steps can be user defined so as to reduce uncertainty, but normal practice for typical test applications (including FCC) utilize a physical step of 5x5x8 (8mmx8mmx5mm) providing a volume of 32mm in the X & Y axis, and 35mm in the Z axis.

SAR Evaluation Report 14 of 33

Tissue Dielectric Parameters for Head and Body Phantoms

The head tissue dielectric parameters recommended by the IEEE SCC-34/SC-2 in P1528 have been incorporated in the following table. These head parameters are derived from planar layer models simulating the highest expected SAR for the dielectric properties and tissue thickness variations in a human head. Other head and body tissue parameters that have not been specified in P1528 are derived from the tissue dielectric parameters computed from the 4-Cole-Cole equations described in Reference [12] and extrapolated according to the head parameters specified in P1528.

Report No.: RSZ161008001-20AA1

Recommended Tissue Dielectric Parameters for Head and Body

Frequency	Head	Tissue	Body	y Tissue
(MHz)	εr	O'(S/m)	εr	O (S/m)
150	52.3	0.76	61.9	0.80
300	45.3	0.87	58.2	0.92
450	43.5	0.87	56.7	0.94
835	41.5	0.90	55.2	0.97
900	41.5	0.97	55.0	1.05
915	41.5	0.98	55.0	1.06
1450	40.5	1.20	54.0	1.30
1610	40.3	1.29	53.8	1.40
1800-2000	40.0	1.40	53.3	1.52
2450	39.2	1.80	52.7	1.95
3000	38.5	2.40	52.0	2.73
5800	35.3	5.27	48.2	6.00

SAR Evaluation Report 15 of 33

EQUIPMENT LIST AND CALIBRATION

Equipments List & Calibration Information


Equipment	Model	S/N	Calibration Date	Calibration Due Date
Robot	RX90	5L79A1	N/A	N/A
DASY4 Test Software	DASY4.5	N/A	N/A	N/A
DASY4 Measurement Server	DASY 4.5.12	1180	N/A	N/A
Data Acquistion Electronics	DAE4	772	2016/10/25	2017/10/24
E-Field Probe	EX3DV4	7441	2016/11/15	2017/11/14
Dipole, 450 MHz	D450V3	1096	2016/11/07	2019/11/06
Mounting Device	SD 000 H01 KA	N/A	N/A	N/A
Oval Flat Phantom	ELI V8.0	2051	N/A	N/A
Simulated Tissue 450 MHz Head	TS-450-H	N/A	Each Time	/
Simulated Tissue 450 MHz Body	TS-450-B	N/A	Each Time	/
Network Analyzer	8753B	2625A00809	2016/10/06	2017/10/05
S-Parameter Test Set	85047A	3033A02428	2016/10/06	2017/10/05
Dielectric probe kit	85070B	US33020324	N/A	N/A
Signal Generator	SMBV100A	261558	2016-07-04	2017-07-04
Power Meter	E4419B	MY41291878	2016/01/08	2017/01/07
Power Meter Sensor	E9301A	US39210953	2016/05/30	2017/05/29
Power Amplifier	10S1G4M1	18060	N/A	N/A
Directional Coupler	488Z	N/A	N/A	N/A
Attenuator	20dB, 100W	N/A	N/A	N/A
Attenuator	3dB, 5W	N/A	N/A	N/A

Report No.: RSZ161008001-20AA1

SAR Evaluation Report 16 of 33

SAR MEASUREMENT SYSTEM VERIFICATION

Liquid Verification



Report No.: RSZ161008001-20AA1

Liquid Verification Setup Block Diagram

Liquid Verification Results

Frequency	Liquid		uid meter	Target Value		Target Value		_	lta ⁄6)	Tolerance
(MHz)	Туре	$\epsilon_{ m r}$	O' (S/m)	$\epsilon_{ m r}$	O' (S/m)	$\Delta \epsilon_{ m r}$	ΔΟ΄ (S/m)	(%)		
400.0125	Simulated Tissue 450MHz Head	43.57	0.88	43.50	0.87	0.161	1.149	±5		
418.0125	Simulated Tissue 450MHz Head	43.77	0.88	43.50	0.87	0.621	1.149	±5		
435.0125	Simulated Tissue 450MHz Head	43.78	0.88	43.50	0.87	0.644	1.149	±5		
450	Simulated Tissue 450MHz Head	43.82	0.88	43.50	0.87	0.736	1.149	±5		
452.0125	Simulated Tissue 450MHz Head	43.73	0.89	43.50	0.87	0.529	2.299	±5		
469.9875	Simulated Tissue 450MHz Head	43.92	0.90	43.50	0.87	0.966	3.448	±5		

^{*}Liquid Verification was performed on 2016-11-30.

SAR Evaluation Report 17 of 33

Frequency	Liquid	Liquid Parameter Target Value		t Value Delta (%)			Tolerance	
(MHz)	Туре	$\epsilon_{ m r}$	O' (S/m)	$\epsilon_{\rm r}$	O' (S/m)	$\Delta \epsilon_{ m r}$	ΔΟ΄ (S/m)	(%)
400.0125	Simulated Tissue 450MHz Body	56.81	0.95	56.70	0.94	0.194	1.064	±5
418.0125	Simulated Tissue 450MHz Body	56.84	0.96	56.70	0.94	0.247	2.128	±5
435.0125	Simulated Tissue 450MHz Body	56.87	0.97	56.70	0.94	0.300	3.191	±5
450	Simulated Tissue 450MHz Body	57.00	0.96	56.70	0.94	0.529	2.128	±5
452.0125	Simulated Tissue 450MHz Body	57.12	0.95	56.70	0.94	0.741	1.064	±5
469.9875	Simulated Tissue 450MHz Body	57.27	0.97	56.70	0.94	1.005	3.191	±5


^{*}Liquid Verification was performed on 2016-11-30.

SAR Evaluation Report 18 of 33

System Accuracy Verification

Prior to the assessment, the system validation kit was used to test whether the system was operating within its specifications of $\pm 10\%$. The validation results are tabulated below. And also the corresponding SAR plot is attached as well in the SAR plots files.

System Verification Setup Block Diagram



System Accuracy Check Results

Date	Frequency Band	Liquid Type		sured SAR W/Kg)	Target Value (W/Kg)	Delta (%)	Tolerance (%)
2016-11-30	450MHz	Head	1g	4.61	4.53	1.766	±10
2016-11-30	430MITZ	Body	1g	4.77	4.55	4.835	±10

Note:

The power inputted to dipole is 0.1Watt; the SAR values are normalized to 1 Watt forward power.

SAR Evaluation Report 19 of 33

SAR SYSTEM VALIDATION DATA

Test Laboratory: Bay Area Compliance Labs Corp.(Kunshan)

DUT: Dipole 450 MHz; Type: D450V3; S/N: 1096

Program Name: 450 MHz Head

Communication System: CW; Frequency: 450 MHz; Duty Cycle: 1:1

Medium parameters used: f = 450 MHz; $\sigma = 0.88 \text{ S/m}$; $\varepsilon_r = 43.82$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

DASY4 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(10.98, 10.98, 10.98); Calibrated: 15/11/2016

- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE SN772: Calibrated: 25/10/2016
- Phantom: ELI v8.0; Type: QDOVA004AA; Serial: TP-2051
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 145

450 Head system check /Area Scan (121x181x1): Measurement grid: dx=10mm, dy=10mm Maximum value of SAR (interpolated) = 0.463 mW/g

450 Head system check /Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm


Report No.: RSZ161008001-20AA1

Reference Value = 25.1 V/m; Power Drift = -0.121 dB

Peak SAR (extrapolated) = 0.494 W/kg

SAR(1 g) = 0.461 mW/g; SAR(10 g) = 0.307 mW/g

Maximum value of SAR (measured) = 0.476 mW/g



SAR Evaluation Report 20 of 33

Test Laboratory: Bay Area Compliance Labs Corp.(Kunshan)

DUT: Dipole 450 MHz; Type: D450V3; S/N: 1096

Program Name: 450 MHz Body

Communication System: CW; Frequency: 450 MHz; Duty Cycle: 1:1

Medium parameters used: f = 450 MHz; $\sigma = 0.96 \text{ S/m}$; $\varepsilon_r = 57.00$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

DASY4 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(12.08, 12.08, 12.08); Calibrated: 15/11/2016

- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE SN772; Calibrated: 25/10/2016
- Phantom: ELI v8.0; Type: QDOVA004AA; Serial: TP-2051
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 145

450 Body system check /Area Scan (121x181x1): Measurement grid: dx=10mm, dy=10mm Maximum value of SAR (interpolated) = 0.497 mW/g


450 Body system check /Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 21.6 V/m; Power Drift = -0.018 dB

Peak SAR (extrapolated) = 0.493 W/kg

SAR(1 g) = 0.477 mW/g; SAR(10 g) = 0.313 mW/g

Maximum value of SAR (measured) = 0.482 mW/g




SAR Evaluation Report 21 of 33

EUT TEST STRATEGY AND METHODOLOGY

Test Positions for front-of-face configurations

A typical example of a front-of-face device is a two-way radio that is held at a distance from the face of the user when transmitting. In these cases the device under test shall be positioned at the distance to the phantom surface that corresponds to the intended use as specified by the manufacturer in the user instructions. If the intended use is not specified, a separation distance of 25 mm5 between the phantom surface and the device shall be used.

Report No.: RSZ161008001-20AA1



Test positions for body-worn and other configurations

Body-worn operating configurations should be tested with the belt-clips and holsters attached to the device and positioned against a flat phantom in normal use configurations. Devices with a headset output should be tested with a headset connected to the device. When multiple accessories that do not contain metallic components are supplied with the device, the device may be tested with only the accessory that dictates the closest spacing to the body. When multiple accessories that contain metallic components are supplied with the device, the device must be tested with each accessory that contains a unique metallic component. If multiple accessories share an identical metallic component (e.g., the same metallic belt-clip used with different holsters with no other metallic components), only the accessory that dictates the closest spacing to the body must be tested.

Body-worn accessories may not always be supplied or available as options for some devices that are intended to be authorized for body-worn use. A separation distance of 1.5 cm between the back of the device and a flat phantom is recommended for testing body-worn SAR compliance under such circumstances. Other separation distances may be used, but they should not exceed 2.5 cm. In these cases, the device may use body-worn accessories that provide a separation distance greater than that tested for the device provided however that the accessory contains no metallic components.




Figure 5 - Test positions for body-worn devices

SAR Evaluation Report 22 of 33

For EUT Positioning Procedures

The EUT is a portable device operational at the body and face. The intended operating positions are "at the face" with the EUT at least 2.5cm from the mouth, and "at the body" by means of the offered body worn accessories. Body worn audio and PTT operation is accomplished by means of optional remote accessories that are connected to the radio.

Report No.: RSZ161008001-20AA1

Body

The EUT was positioned in normal use configuration against the phantom with the offered body worn accessory with the offered audio accessories as applicable

Head

Not applicable

Face

The EUT was positioned with its' front side separated 2.5cm from the phantom

SAR Evaluation Procedure

The evaluation was performed with the following procedure:

- Step 1: Measurement of the SAR value at a fixed location above the ear point or central position was used as a reference value for assessing the power drop. The SAR at this point is measured at the start of the test and then again at the end of the testing.
- Step 2: The SAR distribution at the exposed side of the head was measured at a distance of 4 mm from the inner surface of the shell. The area covered the entire dimension of the head or EUT and the horizontal grid spacing was 10 mm x 10 mm. Based on these data, the area of the maximum absorption was determined by spline interpolation. The first Area Scan covers the entire dimension of the EUT to ensure that the hotspot was correctly identified.
- Step 3: Around this point, a volume of 30 mm x 30 mm x 30 mm was assessed by measuring 7x 7 x 7 points. On the basis of this data set, the spatial peak SAR value was evaluated under the following procedure:
 - 1) The data at the surface were extrapolated, since the center of the dipoles is 1.2 mm away from the tip of the probe and the distance between the surface and the lowest measuring point is 1.3 mm. The extrapolation was based on a least square algorithm. A polynomial of the fourth order was calculated through the points in z-axes. This polynomial was then used to evaluate the points between the surface and the probe tip.
 - 2) The maximum interpolated value was searched with a straightforward algorithm. Around this maximum the SAR values averaged over the spatial volumes (1 g or 10 g) were computed by the 3D-Spline interpolation algorithm. The 3D-Spline is composed of three one dimensional splines with the "Not a knot"-condition (in x, y and z-directions). The volume was integrated with the trapezoidal-algorithm. One thousand points (10 x 10 x 10) were interpolated to calculate the averages.

All neighboring volumes were evaluated until no neighboring volume with a higher average value was found.

Step 4: Re-measurement of the SAR value at the same location as in Step 1. If the value changed by more than 5%, the evaluation was repeated.

SAR Evaluation Report 23 of 33


CONDUCTED OUTPUT POWER MEASUREMENT

Provision Applicable

The measured peak output power should be greater and within 5% than EMI measurement.

Test Procedure

The RF output of the transmitter was connected to the input of the Signal Analyzer through sufficient attenuation.



Report No.: RSZ161008001-20AA1

Maximum Output Power among production units

Max. tune-up tolerance power limit for Production Unit (dBm)						
Mo	ode/Band	Frequency(400-470MHz)				
UHF	Digital-12.5KHz	36.10				
UHF	Analog-12.5KHz					
Mode		Low channel	Low channel Middle channel			
	BDR(GFSK)	5.00	7.00	5.00		
Bluetooth	EDR(4-DQPSK)	2.50	5.00	5.50		
Diuetootii	EDR(8DPSK)	3.00	5.00	5.50		
	BLE(GFSK)	4.00	6.50	5.00		

SAR Evaluation Report 24 of 33

Test Results:

Mode	Frequency Spacing (kHz)	Frequency (MHz)	Output(dBm)	Output Power(W)	Power level
		400.0125	36.07	4.046	High
		418.0125	35.98	3.963	High
Digital	12.5	435.0125	36.06	4.036	High
		452.0125	35.92	3.908	High
		469.9875	36.04	4.018	High
		400.0125	36.05	4.027	High
		418.0125	35.97	3.954	High
Analog	12.5	435.0125	36.04	4.018	High
		452.0125	35.97	3.954	High
		469.9875	35.93	3.917	High

Note: The measurement was made in the room temperature.

Bluetooth:

Mode	Channel Frequency	Conducted O	utput Power	
Mode	(MHz)	dBm	mW	
	2402	4.57	2.864	
BDR(GFSK)	2441	6.99	5.000	
	2480	4.69	2.944	
	2402	2.17	1.648	
EDR(4-DQPSK)	2441	4.48	2.805	
	2480	5.10	3.236	
	2402	2.43	1.750	
EDR(8DPSK)	2441	4.72	2.965	
	2480	5.26	3.357	
	2402	3.57	2.275	
BLE(GFSK)	2440	6.06	4.036	
	2480	4.45	2.786	

SAR Evaluation Report 25 of 33

SAR MEASUREMENT RESULTS

This page summarizes the results of the performed dosimetric evaluation.

SAR Test Data

Environmental Conditions

Temperature:	21.8-22.4 °C
Relative Humidity:	57 %
ATM Pressure:	1013 mbar
Test Date:	2016-11-30

Testing was performed by Jack Xu, Apple Wu and Judy Huang.

Digital (Modulation 4FSK Channel Spacing 12.5 kHz):

Б	Max. Meas.	Max.		1 g SAR	Value (W/Kg)	
Frequency (MHz)	Power (dBm)	Rated Power (dBm)	Scaled Factor	Meas. SAR	Scaled SAR	50%	Plot
			Face up (2	.5cm)			
400.0125	36.07	36.10	1.007	2.48	2.50	1.25	1#
418.0125	35.98	36.10	1.028	/	/	/	/
435.0125	36.06	36.10	1.009	/	/	/	/
452.0125	35.92	36.10	1.042	/	/	/	/
469.9875	36.04	36.10	1.014	/	/	/	/
		Body-l	Back with Be	lt Clip (0.0cm)		
400.0125	36.07	36.10	1.007	4.06	4.09	2.05	2#
418.0125	35.98	36.10	1.028	/	/	/	/
435.0125	36.06	36.10	1.009	/	/	/	/
452.0125	35.92	36.10	1.042	/	/	/	/
469.9875	36.04	36.10	1.014	/	/	1	/

Report No.: RSZ161008001-20AA1

SAR Evaluation Report 26 of 33

Analog (Modulation FM; Channel Spacing 12.5 kHz):

E	Max. Meas.	Max.		1 g S.	AR Value (W/F	Kg)	
Frequency (MHz)	Power (dBm)	Rated Power (dBm)	Scaled Factor	Meas. SAR	Scaled SAR	50%	Plot
			Face up	(2.5cm)			
400.0125	36.05	36.10	1.012	5.09	5.15	2.58	3#
418.0125	35.97	36.10	1.030	/	/	/	/
435.0125	36.04	36.10	1.014	/	/	/	/
452.0125	35.97	36.10	1.030	/	/	/	/
469.9875	35.93	36.10	1.040	/	/	/	/
		Body-	Back with I	Belt Clip (0.0c	m)		
400.0125	36.05	36.10	1.012	9.08	9.189	4.594	4#
418.0125	35.97	36.10	1.030	7.18	7.395	3.698	5#
435.0125	36.04	36.10	1.014	5.59	5.668	2.834	6#
452.0125	35.97	36.10	1.030	5.04	5.191	2.596	7#
469.9875	35.93	36.10	1.040	5.17	5.377	2.688	8#

Note:

- 1. When the 1-g SAR tested using the default battery and default accessories under the highest power channel is \leq 3.5W/Kg (corrected by Multiplying 50%), testing for other channels are optional.
- 2. For PTT, only simplex communication technology was supported, so the SAR value needs to be corrected by Multiplying 50%.
- 3. Passive body-worn and audio accessories generally do not apply to the head SAR of PTT radios.
- 4. The whole antenna and radiating structures that may contribute to the measured SAR or influence the SAR distribution has been included in the area scan.

SAR Evaluation Report 27 of 33

SAR Measurement Variability

In accordance with published RF Exposure KDB procedure 865664 D01 SAR measurement 100 MHz to 6 GHz v01. These additional measurements are repeated after the completion of all measurements requiring the same head or body tissue-equivalent medium in a frequency band. The test device should be returned to ambient conditions (normal room temperature) with the battery fully charged before it is re-mounted on the device holder for the repeated measurement(s) to minimize any unexpected variations in the repeated results

Report No.: RSZ161008001-20AA1

- 1) Repeated measurement is not required when the original highest measured SAR is < 0.80 W/kg.
- When the original highest measured SAR is ≥ 0.80 W/kg, repeat that measurement once.
- Perform a second repeated measurement only if the ratio of largest to smallest SAR for the original and first repeated measurements is > 1.20 or when the original or repeated measurement is ≥ 1.45 W/kg ($\sim 10\%$ from the 1-g SAR limit).
- 4) Perform a third repeated measurement only if the original, first or second repeated measurement is ≥1.5 W/kg and the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20.
- 5) The same procedures should be adapted for measurements according to extremity and occupational exposure limits by applying a factor of 2.5 for extremity exposure and a factor of 5 for occupational exposure to the corresponding SAR thresholds.

The Highest Measured SAR Configuration in Each Frequency Band

Face up

			Meas. SA	Largest to		
Frequency Band	Freq.(MHz)	EUT Position	Original	Repeated	Smallest SAR Ratio	
/	/	/	/	/	/	

Body-Back with Belt Clip

			Meas. SA	Largest to	
Frequency Band	Freq.(MHz)	EUT Position	Original	Repeated	Smallest SAR Ratio
UHF	400.0125	Body-Back	9.08	8.97	1.012

Note:


Second Repeated Measurement is not required since the ratio of the largest to smallest SAR for the original and first repeated measurement is not > 1.20.

SAR Evaluation Report 28 of 33

KDB 447498D01 General RF Exposure Guidance v06

BT and UHF Antenna Location:

Report No.: RSZ161008001-20AA1



Antenna Information:

Description of Simultaneo	Antonnas Distanas (mm)		
Transmitter Combination	Simultaneous?	Antennas Distance (mm)	
UHF + Bluetooth	V	80	

Standalone SAR test exclusion considerations

Mode	Test Position	P _{avg} (dBm)	P _{avg} (mW)	Distance (mm)	Calculated value	SAR Test Exclusion
Bluetooth	Face up	7.00	5.01	25	0.3	Yes
	Body-Back	7.00	5.01	0	1.6	Yes

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at *test separation distances* \leq 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] $\cdot \sqrt{f(GHz)} \le 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

- 1. f(GHz) is the RF channel transmit frequency in GHz.
- 2. Power and distance are rounded to the nearest mW and mm before calculation.
- 3. The result is rounded to one decimal place for comparison.
- 4. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test Exclusion.
- 5. The device will be used under controlled environment; The exclusion limit shall be multiplied by a factor 5.0.

SAR Evaluation Report 29 of 33

Standalone SAR estimation:

Mode	Test Position	Distance (mm)	P _{avg} (dBm)	P _{avg} (mW)	Estimated 1-g (W/kg)
Bluetooth	Face up	25	7.00	5.01	0.042
	Body-Back	0	7.00	5.01	0.209

Report No.: RSZ161008001-20AA1

Note:

When standalone SAR test exclusion applies to an antenna that transmits simultaneously with other antennas, the standalone SAR must be estimated according to following to determine simultaneous transmission SAR test exclusion:

[(max. power of channel, including **tune-up tolerance**, mW)/(min. test separation distance,mm)]·[$\sqrt{f(GHz)/x}$] W/kg for test separation distances ≤ 50 mm; where x = 7.5 for 1-g SAR.

When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test Exclusion

Simultaneous SAR test exclusion considerations:

Position	Reported SA	AR (W/kg)	ΣSAR
rosition	UHF	ВТ	< 8.0 W/kg
Face up (25mm)	2.58	0.042	2.622
Body-Back (0mm)	4.594	0.209	4.803

Conclusion:

ΣSAR < 8.0 W/kg therefore simultaneous transmission SAR with Volume Scans is **not** required.

SAR Evaluation Report 30 of 33

APPENDIX A MEASUREMENT UNCERTAINTY

The uncertainty budget has been determined for the measurement system and is given in the following Table.

Measurement uncertainty evaluation for IEEE1528-2013 SAR test

Source of uncertainty	Tolerance/ uncertainty ± %	Probability distribution	Divisor	ci (1 g)	ci (10 g)	Standard uncertainty ± %, (1 g)	Standard uncertainty ± %, (10 g)			
Measurement system										
Probe calibration	6.55	N	1	1	1	6.6	6.6			
Axial Isotropy	4.7	R	√3	1	1	2.7	2.7			
Hemispherical Isotropy	9.6	R	√3	0	0	0.0	0.0			
Boundary effect	1.0	R	√3	1	1	0.6	0.6			
Linearity	4.7	R	√3	1	1	2.7	2.7			
Detection limits	1.0	R	√3	1	1	0.6	0.6			
Readout electronics	0.3	N	1	1	1	0.3	0.3			
Response time	0.0	R	√3	1	1	0.0	0.0			
Integration time	0.0	R	√3	1	1	0.0	0.0			
RF ambient conditions – noise	1.0	R	√3	1	1	0.6	0.6			
RF ambient conditions–reflections	1.0	R	√3	1	1	0.6	0.6			
Probe positioner mech. Restrictions	0.8	R	√3	1	1	0.5	0.5			
Probe positioning with respect to phantom shell	6.7	R	√3	1	1	3.9	3.9			
Post-processing	2.0	R	√3	1	1	1.2	1.2			
		Test sample	erelated							
Test sample positioning	2.8	N	1	1	1	2.8	2.8			
Device holder uncertainty	6.3	N	1	1	1	6.3	6.3			
Drift of output power	5.0	R	√3	1	1	2.9	2.9			
		Phantom an	d set-up							
Phantom uncertainty (shape and thickness tolerances)	4.0	R	√3	1	1	2.3	2.3			
Liquid conductivity target)	5.0	R	√3	0.64	0.43	1.8	1.2			
Liquid conductivity meas.)	2.5	N	1	0.64	0.43	1.6	1.1			
Liquid permittivity target)	5.0	R	√3	0.6	0.49	1.7	1.4			
Liquid permittivity meas.)	2.5	N	1	0.6	0.49	1.5	1.2			
Combined standard uncertainty		RSS				12.2	12.0			
Expanded uncertainty 95 % confidence interval)						24.3	23.9			

SAR Evaluation Report 31 of 33

Measurement uncertainty evaluation for IEC62209-2 SAR test

Source of uncertainty	Tolerance/ uncertainty ± %	Probability distribution	Divisor	ci (1 g)	ci (10 g)	Standard uncertainty ± %, (1 g)	Standard uncertainty ± %, (10 g)
Measurement system							
Probe calibration	6.55	N	1	1	1	6.6	6.6
Axial Isotropy	4.7	R	√3	1	1	2.7	2.7
Hemispherical Isotropy	9.6	R	√3	0	0	0.0	0.0
Linearity	4.7	R	√3	1	1	2.7	2.7
Modulation Response	0.0	R	√3	1	1	0.0	0.0
Detection limits	1.0	R	√3	1	1	0.6	0.6
Boundary effect	1.0	R	√3	1	1	0.6	0.6
Readout electronics	0.3	N	1	1	1	0.3	0.3
Response time	0.0	R	√3	1	1	0.0	0.0
Integration time	0.0	R	√3	1	1	0.0	0.0
RF ambient conditions – noise	1.0	R	√3	1	1	0.6	0.6
RF ambient conditions–reflections	1.0	R	√3	1	1	0.6	0.6
Probe positioner mech. Restrictions	0.8	R	√3	1	1	0.5	0.5
Probe positioning with respect to phantom shell	6.7	R	√3	1	1	3.9	3.9
Post-processing	2.0	R	√3	1	1	1.2	1.2
Test sample related							
Device holder Uncertainty	6.3	N	1	1	1	6.3	6.3
Test sample positioning	2.8	N	1	1	1	2.8	2.8
Power scaling	4.5	R	√3	1	1	2.6	2.6
Drift of output power	5.0	R	√3	1	1	2.9	2.9
Phantom and set-up							
Phantom uncertainty (shape and thickness tolerances)	4.0	R	√3	1	1	2.3	2.3
Algorithm for correcting SAR for deviations in permittivity and conductivity	1.9	N	1	1	0.84	1.1	0.9
Liquid conductivity (meas.)	2.5	N	1	0.64	0.43	1.6	1.1
Liquid permittivity (meas.)	2.5	N	1	0.6	0.49	1.5	1.2
Temp. unc Conductivity	1.7	R	√3	0.78	0.71	0.8	0.7
Temp. unc Permittivity	0.3	R	√3	0.23	0.26	0.0	0.0
Combined standard uncertainty		RSS				12.2	12.1
Expanded uncertainty 95 % confidence interval)						24.5	24.2

SAR Evaluation Report 32 of 33

Appendixes

Refer to separated files for the following appendixes.

APPENDIX B PROBE & DIPOLES CALIBRATION CERTIFICATES. APPENDIX C TEST POSITION PHOTOS. APPENDIX D SAR Plots.

***** END OF REPORT *****

Report No.: RSZ161008001-20AA1

SAR Evaluation Report 33 of 33